FCC §15.407(f) & §2.1091 - RF Exposure

Applicable Standard 4.1

According to FCC §15.407(f) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)	
Limits for General Population/Uncontrolled Exposure					
0.3-1.34	614	1.63	* (100)	30	
1.34-30	824/f	2.19/f	$*(180/f^2)$	30	
30-300	27.5	0.073	0.2	30	
300-1500	/	/	f/1500	30	
1500-100,000	/	/	1.0	30	

f = frequency in MHz

4.2 **MPE Prediction**

 $S = PG/4\pi R^2$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

4.3 **MPE Results**

25 dBi Antenna:

5.3 GHz Band

Maximum peak output power at antenna input terminal (dBm):		
Maximum peak output power at antenna input terminal (mW):	3.083	
Prediction distance (cm):	<u>20</u>	
<u>Prediction frequency (MHz):</u>	<u>5320</u>	
Maximum Antenna Gain, typical (dBi):	<u>25</u>	
Maximum Antenna Gain (numeric):	316.227	
Power density of prediction frequency at 20.0 cm (mW/cm ²):	0.1939	
Power density of prediction frequency at 20.0 cm (W/m ²):	1.9396	
MPE limit for uncontrolled exposure at prediction frequency (mW/cm ²):	<u>1.0</u>	
MPE limit for uncontrolled exposure at prediction frequency (W/m ²):	10	

^{* =} Plane-wave equivalent power density

Mimosa Networks FCC ID: 2ABZJ-100-00014

5.6 GHz Band

<u>Maximum peak output power at antenna input terminal (dBm):</u>	4.88
Maximum peak output power at antenna input terminal (mW):	3.076
Prediction distance (cm):	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>5500</u>
Maximum Antenna Gain, typical (dBi):	<u>25</u>
Maximum Antenna Gain (numeric):	316.227
Power density of prediction frequency at 20.0 cm (mW/cm ²):	0.1935
Power density of prediction frequency at 20.0 cm (W/m ²):	1.9352
MPE limit for uncontrolled exposure at prediction frequency (mW/cm ²):	1.0
MPE limit for uncontrolled exposure at prediction frequency (W/m ²):	<u>10</u>

0 dBi Antenna:

5.3 GHz Band

Maximum peak output power at antenna input terminal (dBm):	23.54
Maximum peak output power at antenna input terminal (mW):	225.94
Prediction distance (cm):	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>5260</u>
Maximum Antenna Gain, typical (dBi):	<u>0</u>
Maximum Antenna Gain (numeric):	<u>1</u>
Power density of prediction frequency at 20 cm (mW/cm ²):	0.045
MPE limit for uncontrolled exposure at prediction frequency (mW/cm ²):	<u>1</u>

5.6 GHz Band

Maximum peak output power at antenna input terminal (dBm):	<u>23.34</u>
Maximum peak output power at antenna input terminal (mW):	215.77
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>5700</u>
Maximum Antenna Gain, typical (dBi):	<u>0</u>
Maximum Antenna Gain (numeric):	<u>1</u>
Power density of prediction frequency at 20 cm (mW/cm ²):	0.043
MPE limit for uncontrolled exposure at prediction frequency (mW/cm ²):	<u>1</u>

The device meets FCC MPE requirement for uncontrolled exposure environment at 20 cm distance.