



Neutron Engineering Inc.

FCC RF EXPOSURE REPORT

FCC ID: 2ABZMW75AP

Project No. : 1405C054
Equipment : Wireless N900 High Power Dual Band Access Point
Model : W75AP
Applicant : SHENZHEN IP-COM NETWORKS CO.,LTD.
**Address : Unit A, First Floor, Tower E3, No. 1001,
Zhongshanyuan Road, Nanshan District,
Shenzhen,China. 518052**

According: : FCC Guidelines for Human Exposure IEEE C95.1

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL : (0769) 8318-3000 FAX : (0769) 8319-6000



Neutron Engineering Inc.

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)
0	Tenda	Q5078	Internal	N/A	5
1	Tenda	Q5078	Internal	N/A	5
2	Tenda	Q5078	Internal	N/A	5



Neutron Engineering Inc.

TEST RESULTS

EUT:	Wireless N900 High Power Dual Band Access Point	Model Name :	W75AP
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX B MODE /CH01, CH06, CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5	3.1623	23.96	248.8857	0.15665720	1	Complies
5	3.1623	24.02	252.3481	0.15883652	1	Complies
5	3.1623	24.05	254.0973	0.15993752	1	Complies

EUT:	Wireless N900 High Power Dual Band Access Point	Model Name :	W75AP
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX G MODE /CH01, CH06, CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5	3.1623	24.03	252.9298	0.15920268	1	Complies
5	3.1623	24.06	254.6830	0.16030622	1	Complies
5	3.1623	24.03	252.9298	0.15920268	1	Complies



Neutron Engineering Inc.

EUT:	Wireless N900 High Power Dual Band Access Point	Model Name :	W75AP
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX N-20M MODE_ Total /CH01, CH06, CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5	3.1623	27.01	502.3426	0.31619163	1	Complies
5	3.1623	27.02	503.5006	0.31692053	1	Complies
5	3.1623	26.98	498.8845	0.31401498	1	Complies

EUT:	Wireless N900 High Power Dual Band Access Point	Model Name :	W75AP
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX N-40M MODE_ Total /CH03, CH06, CH09		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5	3.1623	27.01	502.3426	0.31619163	1	Complies
5	3.1623	27.01	502.3426	0.31619163	1	Complies
5	3.1623	27.03	504.6613	0.31765110	1	Complies

The calculated distance is 20 cm