





# TEST REPORT

FCC ID..... :	2AC23-DCT2B	
Test Report No..... :	TCT220105E052	
Date of issue..... :	Feb. 15, 2022	
Testing laboratory .....	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an District Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	Hui Zhou Gaoshengda Technology Co., LTD	
Address..... :	NO.75 Zhongkai Development Area, Huizhou, Guangdong, China	
Manufacturer's name ... :	Hui Zhou Gaoshengda Technology Co., LTD	
Address..... :	NO.75 Zhongkai Development Area, Huizhou, Guangdong, China	
Standard(s) .....	FCC CFR Title 47 Part 1.1307	
Test item description .....	WIFI+BT Module	
Trade Mark .....	N/A	
Model/Type reference..... :	DCT2BM2501	
Rating(s) .....	DC 3.3V	
Date of receipt of test item .....	Jan. 05, 2022	
Date (s) of performance of test..... :	Jan. 05, 2022 ~ Feb. 15, 2022	
Tested by (+signature) ... :	Brews XU	
Check by (+signature).... :	Beryl ZHAO	
Approved by (+signature):	Tomsin	



**General disclaimer:**

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

## Table of Contents

<b>1. General Product Information .....</b>	<b>3</b>
1.1. EUT description .....	3
1.2. Model(s) list.....	3
<b>2. General Information.....</b>	<b>4</b>
2.1. Test environment and mode.....	4
2.2. Description of Support Units.....	4
<b>3. Facilities and Accreditations .....</b>	<b>5</b>
3.1. Facilities .....	5
3.2. Location .....	5
<b>4. Test Results and Measurement Data .....</b>	<b>6</b>

## 1. General Product Information

### 1.1. EUT description

<b>Test item description .....</b>	WIFI+BT Module
<b>Model/Type reference.....</b>	DCT2BM2501
<b>Sample Number.....</b>	TCT220105E022-0101
<b>Operation Frequency .....</b>	For BT/BLE: 2402MHz~2480MHz For 2.4GWIFI: 2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40)) For 5GWIFI: Band 1: 5180 MHz -5240 MHz Band 2A: 5260 MHz -5320 MHz Band 2C: 5500 MHz -5700 MHz Band 3: 5745 MHz -5825 MHz
<b>Modulation Type .....</b>	For BT: GFSK, $\pi/4$ -DQPSK, 8DPSK For BLE: GFSK For 2.4GWIFI: DSSS(802.11b), OFDM (802.11g/802.11n) For 5GWIFI: 256QAM, 64QAM, 16QAM, BPSK, QPSK
<b>Antenna Type.....</b>	PCB Antenna
<b>Antenna Gain.....</b>	For BT/BLE: 1.91dBi For 2.4GWIFI: Antenna 0: 3.01dBi Antenna 1: 2.79dBi For 5GWIFI: Band 1: Antenna 0: 3.51dBi, Antenna 1: 3.13dBi Band 2A: Antenna 0: 3.84dBi, Antenna 1: 3.40dBi Band 2C: Antenna 0: 3.83dBi, Antenna 1: 3.97dBi Band 3: Antenna 0: 3.97dBi, Antenna 1: 3.95dBi
<b>Rating(s) .....</b>	DC 3.3V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

### 1.2. Model(s) list

None.

## 2. General Information

### 2.1. Test environment and mode

Item	Normal condition
Temperature	+25°C
Voltage	DC 5 V(Notebook Computer Input AC 120 V/60 Hz)
Humidity	56%
Atmospheric Pressure:	1008 mbar
<b>Test Mode:</b>	
Engineering mode:	Keep the EUT in continuous transmitting by select channel

### 2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
Notebook Computer	G3 3500	00342-36088-998 32-AAOEM	/	DELL

**Note:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

### 3. Facilities and Accreditations

#### 3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098  
SHENZHEN TONGCE TESTING LAB  
Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1  
SHENZHEN TONGCE TESTING LAB  
CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

#### 3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an District Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

## 4. Test Results and Measurement Data

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1)

### SISO mode:

- For BT:** The maximum output power for antenna is 10.25dBm (10.59mW) at 2480MHz, 1.91dBi antenna gain(with 1.55 numeric antenna gain);
- For BLE(1M):** The maximum output power for antenna is 8.08dBm (6.43mW) at 2402MHz, 1.91dBi antenna gain(with 1.55 numeric antenna gain);
- For BLE(2M):** The maximum output power for antenna is 8.03dBm (6.35mW) at 2402MHz, 1.91dBi antenna gain(with 1.55 numeric antenna gain);
- For 2.4G WIFI:** The maximum output power is in 802.11g mode at 2462MHz, with antenna 1 is 15.97dBm (39.54mW), 2.79dBi antenna gain(1.90 numeric antenna gain);
- For Band 1:** The maximum output power is in 802.11a mode at 5180MHz, with antenna 1 is 14.63dBm (29.04mW), 3.13dBi antenna gain(2.06 numeric antenna gain)
- For Band 2A:** The maximum output power is in 802.11a mode at 5320M MHz, with antenna 1 is 14.57dBm (28.64mW) at 5260MHz, 3.40dBi antenna gain(2.19 numeric antenna gain)
- For Band 2C:** The maximum output power is in 802.11a mode at 5500MHz, with antenna 0 is 14.78dBm (30.06mW), 3.83dBi antenna gain(2.42 numeric antenna gain)
- For Band 3:** The maximum output power is in 802.11a mode at 5785MHz, with antenna 0 is 14.68dBm (29.38mW), 3.97dBi antenna gain(2.49 numeric antenna gain)

### MIMO mode:

- For 2.4G WIFI:** The maximum output power is in 802.11n(H40) mode at 2462MHz, for total power is 17.79dBm (60.12mW), 3.01dBi antenna gain(with 2.00 numeric antenna gain)
- For Band 1:** The maximum output power is in 802.11n(H40) mode at 5230MHz, for total power is 16.18dBm (41.50mW), 3.51dBi antenna gain(with 2.24 numeric antenna gain)
- For Band 2A:** The maximum output power is in 802.11n(H40) mode at 5310MHz, for total power is 16.47dBm(44.36mW), 3.84dBi antenna gain(with 2.42 numeric antenna gain)
- For Band 2C:** The maximum output power is in 802.11n(H40) mode at 5510MHz, for total power is 16.71dBm (46.88mW), 3.97dBi antenna gain(with 2.49 numeric antenna gain.)
- For Band 3:** The maximum output power is in 802.11n(H40) mode at 5795MHz, for total power is 16.79dBm (47.75mW), 3.97dBi antenna gain(with 2.49 numeric antenna gain.)

- 2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

### Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where  $E$  = Field Strength in Volts / meter

$P$  = Power in Watts

$G$  = Numeric antenna gain

$d$  = Distance in meters

$S$  = Power Density in milliwatts / square centimeter

Substituting the MPE safe distance using  $d=20\text{cm}$  into above equation.

Yields:  $S=0.000199 \times P \times G$

**SISO mode:**

Maximum Emissions Level					
Mode	Power(mW)	numeric antenna gain	Power density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
BT	10.59	1.55	0.003266	1.0	PASS
BLE(1M)	6.43	1.55	0.001983		
BLE(2M)	6.35	1.55	0.001959		
2.4G WIFI	39.54	1.9	0.014950		
Band 1	29.04	2.06	0.011905		
Band 2A	28.62	2.19	0.012473		
Band 2C	30.06	2.42	0.014476		
Band 3	29.38	2.49	0.014558		

**MIMO mode:**

Maximum Emissions Level					
Mode	Power(mW)	numeric antenna gain	Power density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
2.4G WIFI	60.12	2.0	0.023928	1.0	PASS
Band 1	41.50	2.24	0.018499		
Band 2A	44.36	2.42	0.021363		
Band 2C	46.88	2.49	0.023230		
Band 3	47.75	2.49	0.023661		

**Simultaneous transmitting:**

Maximum Emissions Level					
Mode	BT	WIFI	Total MPE	Limit	Result
BT + WIFI	0.003266	0.023928	0.027194	1.0	PASS
BT + U-NII	0.003266	0.023661	0.026927		
BLE + WIFI	0.001983	0.023928	0.025911		
BLE +U-NII	0.001983	0.023661	0.025644		

\*\*\*\*\*END OF REPORT\*\*\*\*\*