



FCC RF EXPOSURE REPORT

CERTIFICATION TEST REPORT

For

WIFI+BT Module

MODEL NUMBER: DCT2UM1111

FCC ID: 2AC23-DCT2U

REPORT NUMBER: 4790191813.2-6

ISSUE DATE: March 09, 2022

Prepared for

**Hui Zhou Gaoshengda Technology Co.,LTD
NO.75 Zhongkai Development Area ,Huizhou, Guangdong, China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	03/09/2022	Initial Issue	



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. REQUIREMENT	6



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD
 Address: NO.75 Zhongkai Development Area ,Huizhou, Guangdong, China

Manufacturer Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD
 Address: NO.75 Zhongkai Development Area ,Huizhou, Guangdong, China

EUT Information

EUT Name: WIFI+BT Module
 Model: DCT2UM1111
 Brand: GSD
 Sample Received Date: December 30, 2021
 Sample Status: Normal
 Sample ID: 4540907
 Date of Tested: December 30, 2021 ~ March 6, 2022

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47CFR§2.1091	PASS

Prepared By:

Kebo Zhang
Project Engineer

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	---

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.



4. REQUIREMENT

LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f ²)*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

CALCULATION METHOD

$$S = PG / 4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



CALCULATED RESULTS

Worst Case					
Mode	Output Power	Antenna Gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm ²	mW/cm ²	--
BLE	9	3	0.00315	1.0	Complies

Worst Case					
Mode	Output Power	Antenna Gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm ²	mW/cm ²	--
BT	12	3	0.00629	1.0	Complies

Worst Case					
Mode	Output Power	Directional Antenna Gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm ²	mW/cm ²	--
WIFI 2.4G	20	3	0.03969	1.0	Complies

Worst Case					
Mode	Output Power	Directional Antenna Gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm ²	mW/cm ²	--
WIFI 5G	21	4	0.06291	1.0	Complies

Note:

1. The Power comes from report operation description.
2. The EUT cannot support simultaneous emission.
3. The minimum separation distance of the device is greater than 20 cm.
3. Calculate by WORST-CASE mode.

END OF REPORT