

RF EXPOSURE REPORT

FCC ID: 2AC23-DT13
IC : 12290A-DT13

Applicant's name : Hui Zhou Gaoshengda Technology Co., LTD
Address : NO.75 Zhongkai Development Area, Huizhou,
Guangdong,China
Manufacturer : Hui Zhou Gaoshengda Technology Co., LTD

Equipment : WIFI+BT Module
Trade Mark : GSD
Model : DT13R2611
Ratings : DC 5V

Testing Laboratory : DongGuan ShuoXin Electronic Technology Co., Ltd.
Address : Zone A, 1F, No. 6, XinGang Road YuanGang Street,
XinAn District, ChangAn Town, DongGuan City,
GuangDong, China
According : FCC Guidelines for Human Exposure IEEE C95.1 &
FCC Part 2.1091

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)	Note
1	N/A	N/A	PCB	N/A	3.57	
2	N/A	N/A	PCB	N/A	3.57	

TEST RESULTS

EUT :	WIFI+BT Module	Model Name :	DT13R2611
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	DC 5V		

2.4G WIFI

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.68	1.8535	24.72	296.4831	0.10938	1	Complies

5G Band UNII-1

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.57	2.2751	16.39	43.5512	0.01972	1	Complies

5G Band UNII-2A

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.57	2.2751	16.68	46.5586	0.02108	1	Complies

5G Band UNII-2C

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.57	2.2751	16.88	48.7528	0.02208	1	Complies

5G Band UNII-3

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.57	2.2751	16.97	49.7737	0.02254	1	Complies

BT

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2	1.5849	8.919	7.7965	0.00246	1	Complies

LE

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2	1.5849	6.280	4.2462	0.00134	1	Complies

For 2.4G+5G simultaneous transmission MPE:

$$0.00246+0.00134+0.10938+0.02254=0.13572$$

Note: the calculated distance is 20 cm.