



FCC RF EXPOSURE REPORT

CERTIFICATION TEST REPORT

For

WIFI+BT Module

MODEL NUMBER: DT3AR1501

REPORT NUMBER: 4790836237-1-RF-5

ISSUE DATE: August 25, 2023

FCC ID: 2AC23-DT3A

Prepared for

Hui Zhou Gaoshengda Technology Co.,LTD No.2, Jin-da Road, Huinan High-tech Industrial Park, Huizhou, Guangdong, China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



REPORT NO.: 4790836237-1-RF-5 Page 2 of 8

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	August 25, 2023	Initial Issue	



TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	. 4
2.	TEST METHODOLOGY	. 5
3.	FACILITIES AND ACCREDITATION	. 5
4.	DESCRIPTION OF EUT	. 6
5	REQUIREMENT	7



REPORT NO.: 4790836237-1-RF-5

Page 4 of 8

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD

Address: No.2, Jin-da Road, Huinan High-tech Industrial Park, Huizhou,

Guangdong, China

Manufacturer Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD

Address: No.2, Jin-da Road, Huinan High-tech Industrial Park, Huizhou,

Guangdong, China

EUT Information

EUT Name: WIFI+BT Module Model: DT3AR1501

Brand: GSD

Sample Received Date: May 5, 2023
Sample Status: Normal
Sample ID: 6269427

Date of Tested: July 14, 2023 to August 25, 2023

APPLICABLE STANDARDS				
STANDARD	TEST RESULTS			
FCC 47CFR§2.1091	PASS			

		_
Prepared By:	Checked By:	
Tamry . Huang	Danny Harany	
Fanny Huang	Denny Huang	
Engineer Project Associate	Senior Project Engineer	
Approved By:		

Stephen Guo

Operations Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 and KDB447498D01v06.

3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with A2LA.
	FCC (FCC Designation No.: CN1187)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	Has been recognized to perform compliance testing on equipment subject
	to the Commission's Delcaration of Conformity (DoC) and Certification rules
	ISED (Company No.: 21320)
Aggraditation	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
Accreditation Certificate	has been registered and fully described in a report filed with ISED.
Certificate	The Company Number is 21320 and the test lab Conformity Assessment
	Body Identifier (CABID) is CN0046.
	VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with VCCI, the
	Membership No. is 3793.
	Facility Name:
	Chamber D, the VCCI registration No. is G-20019 and R-20004
	Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.



4. DESCRIPTION OF EUT

EUT Name:		WIFI+BT Module		
Model:		DT3AR1501		
Product	Frequency Range:	2402 MHz to 2480 MHz		
Description (BLE)	Type of Modulation:	GFSK		
	Data Rate:	1Mbps/2Mbps		
Product	Frequency Range:	2402 MHz to 2480 MHz		
Description (BT)	Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)		
(61)	Type of Modulation:	GFSK, ∏/4DQPSK, 8DPSK		
Product	Frequency Range:	2412 MHz to 2462 MHz		
Description (2.4G WLAN)	Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)		
(2.4G WLAIN)	Radio Technology:	IEEE 802.11b/g/n HT20/11n HT40		
Product	Frequency Range:	5180 MHz to 5240 MHz 5260 MHz to 5320 MHz 5500 MHz to 5720 MHz 5745 MHz to 5825 MHz		
Description (5G RLAN)	Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)		
	Radio Technology:	IEEE 802.11a/n HT20/11n HT40		
Normal Test Voltage:		DC 3.3 V		



5. REQUIREMENT

LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with. Limits for General Population/Uncontrolled Exposure

RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ², H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f ²)*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

CALCULATION METHOD

S=PG/4πR²

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



CALCULATED RESULTS

Worst Case						
Mode	Max Tune Up Power	Antenna Gain	Power Density	Power Density Limit	Test Result	
	dBm	dBi	mW/cm2	mW/cm2		
BLE	11	-4.01	0.00099	1.0	Complies	

Worst Case						
Mode	Max Tune Up Power	Antenna Gain	Power Density	Power Density Limit	Test Result	
	dBm	dBi	mW/cm2	mW/cm2		
ВТ	13.5	-4.01	0.00177	1.0	Complies	

Worst Case						
Mode	Max Tune Up Power	Antenna Gain	Power Density	Power Density Limit	Test Result	
	dBm	dBi	mW/cm2	mW/cm2		
WIFI 2.4G SISO	17	1.59	0.01438	1.0	Complies	

Worst Case							
Mode	Max Tune Up Power	Antenna Gain	Power Density	Power Density Limit	Test Result		
	dBm	dBi	mW/cm2	mW/cm2			
WIFI 5G SISO	16	3.29	0.01689	1.0	Complies		

Note:

- 1. The Power comes from report operation description.
- 2. BT and WIFI cannot support simultaneous emission.
- 3. The minimum separation distance of the device is greater than 20 cm, and 20cm separation distance was set for calculation.
 - 4. Calculate by WORST-CASE mode.

END OF REPORT