

FCC Radio Test Report

FCC ID: 2AC23-W79M1510S

FCC 47 CFR Part 15 Subpart C

Class II Change

Product : WIFI Module

Trade Name : GSD

Model Number : W79M1110, W79M1510S

Issued for

Hui Zhou Gaoshengda Technology Co.,LTD

NO.75 Zhongkai Development Area, Huizhou, Guangdong, China

Issued by

Shenzhen ATL Testing Technology Co., Ltd.

F/4, Building 10, Dayuan Industrial Zone, Xili Town, Nanshan District, Shenzhen,
China

Tel.: +86-0755-26909822 Fax.: +86-0755-61605504

Website: www.atllab.org

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen ATL Testing Technology Co., Ltd.. This document may be altered or revised by Shenzhen ATL Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample

TEST RESULT CERTIFICATION

Product : WIFI Module
Applicant..... : Hui Zhou Gaoshengda Technology Co.,LTD
Address : NO.75 Zhongkai Development Area, Huizhou, Guangdong,
China
Manufacturer..... : Hui Zhou Gaoshengda Technology Co.,LTD
Address : NO.75 Zhongkai Development Area, Huizhou, Guangdong,
China
Model No. : W79M1110, W79M1510S
Standards : FCC Part 15 Subpart C (15.247)
Test Method..... : ANSI C63.10: 2014
KDB 558074 D01 DTS Meas Guidance v03r02

The above equipment has been tested by Shenzhen ATL Testing Technology Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Test.....:

Date of receipt of test item 2015-10-13
Date(s) of performance of test 2015-10-13 to 2015-11-26
Test Result.....: Pass

Testing by	:	<u>Si feifei</u>	Date	:	<u>2015-11-26</u>
		(Si feifei)			
Check by	:	<u>Xie Lingling</u>	Date	:	<u>2015-11-30</u>
		(Xie Lingling)			
Approved by	:	<u>Xu Peng</u>	Date	:	<u>2015-12-30</u>
		(Xu Peng)			

Table of Contents	Page
1 . TEST SUMMARY	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 DESCRIPTION OF TEST SETUP	10
2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	11
2.5 EUT Exercise Software	11
3 . CONDUCTED EMISSION TEST	12
3.1 CONDUCTED EMISSION MEASUREMENT (Frequency Range 150KHz-30MHz)	12
3.2 TEST PROCEDURE	12
3.3 TEST SETUP	13
3.4 TEST INSTRUMENTS	13
3.5 EUT OPERATING CONDITIONS	13
3.6 TEST RESULTS	14
4 . RADIATED EMISSION MEASUREMENT	16
4.1 RADIATED EMISSION LIMIT (Frequency Range 9KHz-1000MHz)	16
4.2 TEST PROCEDURE	16
4.3 TEST SETUP	17
4.4 TEST INSTRUMENTS	18
4.5 EUT OPERATING CONDITIONS	18
4.6 TEST RESULTS	19
5 . OCCUPIED BANDWIDTH MEASUREMENT	34
5.1 LIMITS	34
5.2 TEST PROCEDURE	34
5.3 TEST SETUP	34
5.4 TEST INSTRUMENTS	34
5.5 EUT OPERATING CONDITIONS	34
5.6 TEST RESULTS	34
6 . POWER SPECTRAL DENSITY	43
6.1 LIMITS	43
6.2 TEST PROCEDURE	43

Table of Contents	Page
6.3 TEST SETUP	43
6.4 TEST INSTRUMENTS	43
6.5 EUT OPERATING CONDITIONS	43
6.6 TEST RESULTS	43
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	52
7.1 LIMITS	52
7.2 TEST PROCEDURE	52
7.3 TEST SETUP	52
7.4 TEST INSTRUMENTS	52
7.5 EUT OPERATING CONDITIONS	52
7.6 TEST RESULTS	52
8 . ANTENNA REQUIREMENT	69
8.1 REQUIREMENT	69
8.2 ANTENNA CONNECTOR CONSTRUCTION	69

1. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part 15 Subpart C (15.247)			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Conducted Emission	PASS	
15.247(d)	Antenna Conducted Spurious Emissions	PASS	
15.247(b)(3)	Output Power	PASS	
15.247(a)(2)	6dB RF Bandwidth	PASS	
15.247(e)	Power Spectral Density	PASS	
15.209/15.205	Transmitter Radiated Emissions	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) The test results of this report relate only to the tested sample(s) identified in this report.

1.1 TEST FACILITY

Shenzhen ATL Testing Technology Co., Ltd.

Add. : F/4, Building 10, Dayuan Industrial Zone, Xili Town, Nanshan District, Shenzhen, China

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

A. Conducted Emission :

The measurement uncertainty is evaluated as ± 3.2 dB.

B. Radiated Measurement :

The measurement uncertainty is evaluated as ± 3.7 dB.

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	WIFI Module
Model Name	W79M1110
Additional Model Number(s)	W79M1510S
Model Difference	The different models are identical in schematic, structure and critical component, the only different is the model name for commercial use.
Frequency Range	2400~2483.5 MHz
Modulation Type	802.11b: DSSS 802.11g: OFDM 802.11n: OFDM
Data Rate	802.11b: 1/2/5.5/11 Mbps 802.11g: 6/9/12/18/24/36/48/54 Mbps 802.11n: 450 Mbps
RF Output Power	802.11b: 19.68 dBm 802.11g: 15.89 dBm 802.11n(HT20): 16.28 dBm 802.11n(HT40): 14.87 dBm
Antenna Type	PIFA Antenna (Max. Gain: 3.0 dBi)
Power Source	DC Powered by host system.
Power Rating	DC 5V from USB interference.
Remark	More details EUT technical specifications, please refer to the User's Manual.

Note:

- (1) This Test Report is FCC Part 15 Subpart C, 15.247 for IEEE 802.11b/g/n. And the Test procedure follows the FCC KDB 558074 D01 DTS Meas Guidance v03r02.
- (2) Transmitting mode with antennas

Mode	TX Antenna (s)
802.11b	1
802.11g	1
802.11n(HT20)	2
802.11n(HT40)	2

(3) Channel List.

2.4 GHz Band				
Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

For 802.11b/g/n(HT20), use channel 1~11
 For 802.11n(HT40), use channel 3~9

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	WiFi TX Mode
Mode 2	WiFi TX 802.11b Mode
Mode 3	WiFi TX 802.11g Mode
Mode 4	WiFi TX 802.11n(HT20)Mode
Mode 5	WiFi TX 802.11n(HT40) Mode

For Conducted Test	
Final Test Mode	Description
Mode 2	WiFi TX Mode


For Radiated Test	
Final Test Mode	Description
Mode 1	WiFi TX Mode
Mode 2	WiFi TX 802.11b Mode
Mode 3	WiFi TX 802.11g Mode
Mode 4	WiFi TX 802.11n(HT20)Mode
Mode 5	WiFi TX 802.11n(HT40) Mode

Note:

- (1) Software used to control the EUT for staying in continuous transmitting mode was programmed. After verification, all tests were carried out with the worst case test modes as shown below.
- (2) IEEE 802.11b Mode:
Channel (2412/2437/2462 MHz) with 1Mbps data rate were chosen for full testing.
- (3) IEEE 802.11g Mode:
Channel (2412/2437/2462 MHz) with 6 Mbps data rate were chosen for full testing.
- (4) IEEE 802.11n(HT20) Mode:
Channel (2412/2437/2462 MHz) with MCS 0 data rate were chosen for full testing.
- (5) IEEE 802.11n(HT40) Mode:
Channel (2422/2437/2452 MHz) with MCS 0 data rate were chosen for full testing.
- (6) By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.

2.3 DESCRIPTION OF TEST SETUP

Radiated Emission



2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	WIFI Module	GSD	W79M1110	N/A	EUT
E-2	Notebook	LENOVO	P405	DOC	

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	15cm	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” means “shielded” “with core”; “NO” means “unshielded” “without core”.

2.5 EUT Exercise Software

Power Parameters for Testing			
Test Software Version	MT7601 USB V1.0.9.0.exe		
Mode	Frequency/ Parameters		
802.11b	2412 MHz	2437 MHz	2462 MHz
	DEF	DEF	DEF
802.11g	2412 MHz	2437 MHz	2462 MHz
	DEF	DEF	DEF
802.11n(HT20)	2412 MHz	2437 MHz	2462 MHz
	DEF	DEF	DEF
802.11n(HT40)	2422 MHz	2437 MHz	2452 MHz
	DEF	DEF	DEF

3. CONDUCTED EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Quasi-peak	Average
	dBuV	dBuV
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



- Note: 1.Support units were connected to second LISN.**
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.4 TEST INSTRUMENTS

Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
LISN	R&S	NSLK81	8126466	Jul. 05, 2015	Jul. 04. 2016	1 year
LISN	R&S	NSLK81	8126487	Dec. 24, 2014	Dec. 23, 2015	1 year
50Ω Switch	ANRITSU CORP	MP59B	6200983704	Jul. 05, 2015	Jul. 04. 2016	1 year
Test Cable	N/A	C01	N/A	Jul. 05, 2015	Jul. 04. 2016	1 year
Test Cable	N/A	C02	N/A	Jul. 05, 2015	Jul. 04. 2016	1 year
Test Cable	N/A	C03	N/A	Jul. 05, 2015	Jul. 04. 2016	1 year
EMI Test Receiver	R&S	ESCI	1166.595	Jul. 05, 2015	Jul. 04. 2016	1 year
Passive Voltage Probe	ESH2-Z3	R&S	100196	Jul. 05, 2015	Jul. 04. 2016	1 year


3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.6 TEST RESULTS


EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Terminal:	Line
Test Mode :	WIFI TX Mode (B 2412MHz)		
Test Voltage :	120V/ 60Hz		

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1952	34.93	9.68	44.61	63.81	-19.20	peak	
2		0.2590	27.38	9.69	37.07	61.46	-24.39	peak	
3		0.3266	24.29	9.70	33.99	59.54	-25.55	peak	
4		0.3910	20.61	9.70	30.31	58.04	-27.73	peak	
5		0.6975	21.95	9.71	31.66	56.00	-24.34	peak	
6		17.5553	20.89	10.76	31.65	60.00	-28.35	peak	



EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Terminal:	Neutral
Test Mode :	WIFI TX Mode (B 2412MHz)		
Test Voltage :	120V/ 60Hz		

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1952	34.89	9.68	44.57	63.81	-19.24	peak	
2		0.2582	27.72	9.69	37.41	61.49	-24.08	peak	
3		0.3267	24.99	9.70	34.69	59.53	-24.84	peak	
4		0.6975	20.34	9.71	30.05	56.00	-25.95	peak	
5		2.4141	21.05	9.90	30.95	56.00	-25.05	peak	
6		21.5194	20.29	11.07	31.36	60.00	-28.64	peak	



4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMIT (Frequency Range 9KHz-1000MHz)

20 dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a) and RSS-210 Section 2.2&A8.5, then the 15.209(a) and RSS-General limit in the table below has to be followed.

FREQUENCY (MHz)	Field Strength (uV/m at meter)	Measurement Distance (meters)
0.009 -0.490	2400/F(KHz)	300
0.490 -1.705	24000/F(KHz)	30
1.705 -30.0	30	30
30 -88	100	3
88 -216	150	3
216~960	200	3
Above 960	500	3

RADIATED EMISSION LIMITS (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m)(at 3 M)		Class B (dBuV/m)(at 3 M)	
	Peak	Average		Peak
Above 1000	80	60	74	54

Note:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)

The following table is the setting of the receiver

Receiver Parameter	Setting
Attenuation	Auto
Start Frequency~ Stop Frequency	9kHz~150kHz/ RB 200Hz for QP
Start Frequency~ Stop Frequency	150kHz~30MHz/ RB 9kHz for QP
Start Frequency~ Stop Frequency	30MHz~1000MHz/ RB120kHz for QP

The following table is the setting of the spectrum

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10 th carrier harmonic
RB/ VB (emission in restricted band)	1MHz/ 3 MHz for Peak, 1MHz/ 10Hz for Average

4.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.

- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured, above 1G Average detector mode will be instead.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


Note:

Both horizontal and vertical antenna polarities were tested.


And performed pretest to three orthogonal axis. The worst case emissions were reported.

4.3 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



4.4 TEST INSTRUMENTS

Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
Broadband Antenna	R&S	VULB 9168	VULB 9168-456	Jul. 05, 2015	Jul. 04. 2016	1 year
Test Cable	N/A	R-01	N/A	Dec. 24, 2014	Dec. 23, 2015	1 year
Test Cable	N/A	R-02	N/A	Dec. 24, 2014	Dec. 23, 2015	1 year
EMI Test Receiver	R&S	ESCI	101324	Jul. 05, 2015	Jul. 04. 2016	1 year
Antenna Mast	EM	SC100_1	N/A	N/A	N/A	N/A
Turn Table	EM	SC100	060531	N/A	N/A	N/A
50Ω Switch	Anritsu Corp	MP59B	6200983705	Jul. 05, 2015	Jul. 04. 2016	1 year
Spectrum Analyzer	R&S	FSP40	100154	Jul. 05, 2015	Jul. 04. 2016	1 year
Horn Antenna	R&S	HF906	10029	Jul. 05, 2015	Jul. 04. 2016	1 year
Amplifier	EM	EM-30180	060538	Jul. 05, 2015	Jul. 04. 2016	1 year

4.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

4.6.1 TEST RESULTS (Bellow 1GHz)

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (B 2412MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	79.4700	60.24	-27.48	32.76	40.00	-7.24	QP
2		118.2700	61.94	-26.65	35.29	43.50	-8.21	QP
3		183.2600	60.04	-25.28	34.76	43.50	-8.74	QP
4		376.2900	58.65	-21.80	36.85	46.00	-9.15	QP
5		502.3900	56.51	-18.00	38.51	46.00	-7.49	QP
6		725.4900	52.58	-15.69	36.89	46.00	-9.11	QP

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (B 2412MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		65.8500	53.90	-21.57	32.33	40.00	-7.67	QP
2	*	155.3400	56.71	-19.11	37.60	43.50	-5.90	QP
3		462.3400	54.89	-16.65	38.24	46.00	-7.76	QP
4		543.8200	52.19	-15.41	36.78	46.00	-9.22	QP
5		645.5100	50.56	-13.63	36.93	46.00	-9.07	QP
6		724.5600	50.24	-12.49	37.75	46.00	-8.25	QP

Remark:

Factor = Antenna Factor + Cable Loss.

4.6.2 TEST RESULTS (Above 1GHz)

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (B 2412MHz)		
Test Voltage :	DC 5V		

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	2390.000	47.09	0.77	47.86	74.00	-26.14	peak	
2	2390.000	38.28	0.77	39.05	54.00	-14.95	AVG	
3 *	2411.100	96.13	0.86	96.99	54.00	42.99	AVG	Fundamental Frequency
4 X	2411.300	105.7	0.86	106.64	74.00	32.64	peak	Fundamental Frequency

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	4824.560	48.04	5.72	53.76	74.00	-20.24	peak	
2 *	4824.560	42.14	5.72	47.86	54.00	-6.14	AVG	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (B 2412MHz)		
Test Voltage :	DC 5V		

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	2390.000	46.15	0.77	46.92	74.00	-27.08	peak	
2	2390.000	38.34	0.77	39.11	54.00	-14.89	AVG	
3 X	2411.300	104.7	0.86	105.56	74.00	31.56	peak	Fundamental Frequency
4 *	2411.500	94.92	0.86	95.78	54.00	41.78	AVG	Fundamental Frequency

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	4824.510	48.06	5.72	53.78	74.00	-20.22	peak	
2 *	4824.510	41.25	5.72	46.97	54.00	-7.03	AVG	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (B 2437MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4874.510	41.16	5.88	47.04	54.00	-6.96	AVG	
2		4874.530	47.01	5.88	52.89	74.00	-21.11	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (B 2437MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4874.590	40.87	5.88	46.75	54.00	-7.25	AVG	
2		4874.610	47.81	5.88	53.69	74.00	-20.31	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (B 2462MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	2461.100	95.65	1.06	96.71	54.00	42.71	AVG	Fundamental Frequency
2	X	2462.700	105.3	1.08	106.38	74.00	32.38	peak	Fundamental Frequency
3		2483.500	44.69	1.17	45.86	74.00	-28.14	peak	
4		2483.500	37.68	1.17	38.85	54.00	-15.15	AVG	

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4924.550	46.79	6.04	52.83	74.00	-21.17	peak	
2	*	4924.570	40.61	6.04	46.65	54.00	-7.35	AVG	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (B 2462MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2461.300	104.9	1.07	106.03	74.00	32.03	peak	Fundamental Frequency
2	*	2461.500	94.72	1.07	95.79	54.00	41.79	AVG	Fundamental Frequency
3		2483.500	45.36	1.17	46.53	74.00	-27.47	peak	
4		2483.500	37.48	1.17	38.65	54.00	-15.35	AVG	

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4924.650	47.85	6.04	53.89	74.00	-20.11	peak	
2	*	4924.670	41.83	6.04	47.87	54.00	-6.13	AVG	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (G 2412MHz)		
Test Voltage :	DC 5V		

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	2390.000	44.66	0.77	45.43	74.00	-28.57	peak	
2	2390.000	37.71	0.77	38.48	54.00	-15.52	AVG	
3 X	2409.000	94.97	0.85	95.82	74.00	21.82	peak	Fundamental Frequency
4 *	2410.100	85.88	0.85	86.73	54.00	32.73	AVG	Fundamental Frequency

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1 *	4824.420	36.73	5.72	42.45	54.00	-11.55	AVG	
2	4824.430	44.15	5.72	49.87	74.00	-24.13	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (G 2412MHz)		
Test Voltage :	DC 5V		

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	2390.000	44.84	0.77	45.61	74.00	-28.39	peak	
2	2390.000	37.68	0.77	38.45	54.00	-15.55	AVG	
3 *	2409.900	85.04	0.85	85.89	54.00	31.89	AVG	Fundamental Frequency
4 X	2410.600	93.52	0.86	94.38	74.00	20.38	peak	Fundamental Frequency

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1 *	4824.240	37.15	5.72	42.87	54.00	-11.13	AVG	
2	4824.360	44.87	5.72	50.59	74.00	-23.41	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (G 2437MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4874.510	36.07	5.88	41.95	54.00	-12.05	AVG	
2		4874.530	43.91	5.88	49.79	74.00	-24.21	peak	

Remark:
Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (G 2437MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4874.480	36.90	5.88	42.78	54.00	-11.22	AVG	
2		4874.610	45.19	5.88	51.07	74.00	-22.93	peak	

Remark:
Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (G 2462MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2459.700	94.03	1.06	95.09	74.00	21.09	peak	Fundamental Frequency
2	*	2460.000	85.81	1.06	86.87	54.00	32.87	AVG	Fundamental Frequency
3		2483.500	44.52	1.17	45.69	74.00	-28.31	peak	
4		2483.500	36.98	1.17	38.15	54.00	-15.85	AVG	

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4924.540	45.04	6.04	51.08	74.00	-22.92	peak	
2	*	4924.540	36.81	6.04	42.85	54.00	-11.15	AVG	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (G 2462MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	2459.200	84.61	1.06	85.67	54.00	31.67	AVG	Fundamental Frequency
2	X	2459.500	93.42	1.06	94.48	74.00	20.48	peak	Fundamental Frequency
3		2483.500	43.40	1.17	44.57	74.00	-29.43	peak	
4		2483.500	37.03	1.17	38.20	54.00	-15.80	AVG	

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4924.240	37.63	6.04	43.67	54.00	-10.33	AVG	
2		4924.280	45.55	6.04	51.59	74.00	-22.41	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (N20 2412MHz)		
Test Voltage :	DC 5V		

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	2390.000	44.16	0.77	44.93	74.00	-29.07	peak	
2	2390.000	37.73	0.77	38.50	54.00	-15.50	AVG	
3 X	2410.200	94.64	0.85	95.49	74.00	21.49	peak	Fundamental Frequency
4 *	2415.100	85.68	0.88	86.56	54.00	32.56	AVG	Fundamental Frequency

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1 *	4824.580	36.54	5.72	42.26	54.00	-11.74	AVG	
2	4824.780	44.30	5.72	50.02	74.00	-23.98	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (N20 2412MHz)		
Test Voltage :	DC 5V		

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	2390.000	44.14	0.77	44.91	74.00	-29.09	peak	
2	2390.000	37.66	0.77	38.43	54.00	-15.57	AVG	
3 X	2409.700	93.83	0.85	94.68	74.00	20.68	peak	Fundamental Frequency
4 *	2410.200	84.89	0.85	85.74	54.00	31.74	AVG	Fundamental Frequency

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1 *	4824.570	37.50	5.72	43.22	54.00	-10.78	AVG	
2	4824.640	44.86	5.72	50.58	74.00	-23.42	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (N20 2437MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4874.580	36.88	5.88	42.76	54.00	-11.24	AVG	
2		4874.610	44.08	5.88	49.96	74.00	-24.04	peak	

Remark:
Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (N20 2437MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4874.580	36.55	5.88	42.43	54.00	-11.57	AVG	
2		4874.780	45.07	5.88	50.95	74.00	-23.05	peak	

Remark:
Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (N20 2462MHz)		
Test Voltage :	DC 5V		

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1 *	2459.500	85.87	1.06	86.93	54.00	32.93	AVG	Fundamental Frequency
2 X	2464.500	94.77	1.08	95.85	74.00	21.85	peak	Fundamental Frequency
3	2483.500	43.89	1.17	45.06	74.00	-28.94	peak	
4	2483.500	37.17	1.17	38.34	54.00	-15.66	AVG	

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1 *	4924.490	36.54	6.04	42.58	54.00	-11.42	AVG	
2	4924.500	44.77	6.04	50.81	74.00	-23.19	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (N20 2462MHz)		
Test Voltage :	DC 5V		

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1 *	2458.700	84.73	1.06	85.79	54.00	31.79	AVG	Fundamental Frequency
2 X	2460.200	93.61	1.06	94.67	74.00	20.67	peak	Fundamental Frequency
3	2483.500	43.82	1.17	44.99	74.00	-29.01	peak	
4	2483.500	37.12	1.17	38.29	54.00	-15.71	AVG	

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1 *	4924.470	36.50	6.04	42.54	54.00	-11.46	AVG	
2	4924.530	43.53	6.04	49.57	74.00	-24.43	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (N40 2422MHz)		
Test Voltage :	DC 5V		

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	2390.000	43.98	0.77	44.75	74.00	-29.25	peak	
2	2390.000	37.87	0.77	38.64	54.00	-15.36	AVG	
3 X	2419.450	90.77	0.89	91.66	74.00	17.66	peak	Fundamental Frequency
4 *	2424.550	82.74	0.93	83.67	54.00	29.67	AVG	Fundamental Frequency

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1 *	4845.470	34.44	5.79	40.23	54.00	-13.77	AVG	
2	4846.450	42.82	5.79	48.61	74.00	-25.39	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (N40 2422MHz)		
Test Voltage :	DC 5V		

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	2390.000	44.20	0.77	44.97	74.00	-29.03	peak	
2	2390.000	37.83	0.77	38.60	54.00	-15.40	AVG	
3 *	2420.350	81.94	0.89	82.83	54.00	28.83	AVG	Fundamental Frequency
4 X	2425.000	91.40	0.93	92.33	74.00	18.33	peak	Fundamental Frequency

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1 *	4845.550	42.57	5.79	48.36	54.00	-5.64	AVG	
2	4846.520	34.65	5.79	40.44	74.00	-33.56	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (N40 2437MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4875.330	34.35	5.88	40.23	54.00	-13.77	AVG	
2		4875.510	42.88	5.88	48.76	74.00	-25.24	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (N40 2437MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4875.510	34.30	5.88	40.18	54.00	-13.82	AVG	
2		4876.520	43.02	5.88	48.90	74.00	-25.10	peak	

Remark:

Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Horizontal
Test Mode :	WIFI TX Mode (N40 2462MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2447.500	91.73	1.01	92.74	74.00	18.74	peak	Fundamental Frequency
2	*	2449.300	82.33	1.02	83.35	54.00	29.35	AVG	Fundamental Frequency
3		2483.500	44.57	1.17	45.74	74.00	-28.26	peak	
4		2483.500	37.04	1.17	38.21	54.00	-15.79	AVG	

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4925.680	34.13	6.04	40.17	54.00	-13.83	AVG	
2		4926.660	42.35	6.04	48.39	74.00	-25.61	peak	

Remark:
Factor = Antenna Factor + Cable Loss.

EUT :	WIFI Module	Model Name. :	W79M1110
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Ant. Pol.:	Vertical
Test Mode :	WIFI TX Mode (N40 2462MHz)		
Test Voltage :	DC 5V		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	2446.150	81.44	1.01	82.45	54.00	28.45	AVG	Fundamental Frequency
2	X	2447.950	91.26	1.02	92.28	74.00	18.28	peak	Fundamental Frequency
3		2483.500	43.66	1.17	44.83	74.00	-29.17	peak	
4		2483.500	37.03	1.17	38.20	54.00	-15.80	AVG	

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4925.570	34.23	6.04	40.27	54.00	-13.73	AVG	
2		4926.550	42.67	6.04	48.71	74.00	-25.29	peak	

Remark:
Factor = Antenna Factor + Cable Loss.

5. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT

5.1 LIMITS


FCC Part 15.247, subpart C	
Frequency Range (MHz)	2400~2483.5
Limits	30

5.2 TEST PROCEDURE

The measurement is according to section 9.1.2 of FCC KDB 558074 D01 DTS Meas Guidance v03r02.

The EUT was directly connected to the power meter and antenna output port as show in the block diagram as bellow.

5.3 TEST SETUP



5.4 TEST INSTRUMENTS

Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
P-Series Power Meter	Agilent	N1911A	MY45100482	Jul. 05, 2015	Jul. 04. 2016	1 year
Wideband Power Sensor	Agilent	N1921A	MY51200145	Jul. 05, 2015	Jul. 04. 2016	1 year

5.5 EUT OPERATING CONDITIONS

The EUT was set to continuously transmitting in the maximum power during the test.

5.6 TEST RESULTS

2.4 G Band Conducted Power					
802.11b Power					
Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)
		Ant. 1	Ant. 2	Total	
1	2412 MHz	19.43			30
6	2437 MHz	19.76			
11	2462 MHz	19.68			
802.11g Power					
Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)
		Ant. 1	Ant. 2	Total	
1	2412 MHz	15.47			30
6	2437 MHz	15.76			
11	2462 MHz	15.89			
802.11n(HT20) Power					
Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)
		Ant. 1	Ant. 2	Total	
1	2412 MHz	15.96			30
6	2437 MHz	16.15			
11	2462 MHz	16.28			
802.11n(HT40) Power					
Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)
		Ant. 1	Ant. 2	Total	
1	2412 MHz	14.16			30
6	2437 MHz	14.47			
11	2462 MHz	14.87			

6. OCCUPIED BANDWIDTH MEASUREMENT

6.1 LIMITS


FCC Part 15.247, subpart C	
Frequency Range (MHz)	2400~2483.5
Limits	6 dB Bandwidth>500 KHz

6.2 TEST PROCEDURE

The EUT was directly connected to the power meter and antenna output port as show in the block diagram as bellow.

Spectrum Parameters	Setting
Attenuation	Auto
Span	>6 dB Bandwidth
RBW	100 kHz
VBW	$\geq 3\text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.3 TEST SETUP



6.4 TEST INSTRUMENTS

Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
Spectrum Analyzer	R&S	FSP40	100154	Jul. 05, 2015	Jul. 06. 2016	1 year


6.5 EUT OPERATING CONDITIONS

The EUT was set to continuously transmitting in the maximum power during the test.

6.6 TEST RESULTS


801.11b Mode			
Frequency (MHz)	6dB Bandwidth (MHz)	99% OBW (MHz)	Limit
2412	9.96	15.32	≥500 kHz
2437	10.04	15.40	
2462	10.08	15.52	

B Mode 2412 MHz




Date: 24.NOV.2015 15:20:44

B Mode 2437 MHz



Date: 24.NOV.2015 15:24:21


B Mode 2462 MHz



Date: 24.NOV.2015 15:26:49


801.11g Mode			
Frequency (MHz)	6dB Bandwidth (MHz)	99% OBW (MHz)	Limit
2412	16.64	16.56	≥500 kHz
2437	16.64	16.56	
2462	16.64	16.56	

G Mode 2412 MHz




Date: 24.NOV.2015 15:38:40

G Mode 2437 MHz



Date: 24.NOV.2015 15:36:22


G Mode 2462 MHz



Date: 24.NOV.2015 15:34:33


801.11n(HT20) Mode			
Frequency (MHz)	6dB Bandwidth (MHz)	99% OBW (MHz)	Limit
2412	17.88	17.80	≥500 kHz
2437	17.88	17.80	
2462	17.84	17.80	

N Mode 2412 MHz




Date: 24.NOV.2015 15:43:01

N Mode 2437 MHz



Date: 24.NOV.2015 15:45:25


N Mode 2462 MHz



Date: 24.NOV.2015 15:48:15


801.11n(HT40) Mode			
Frequency (MHz)	6dB Bandwidth (MHz)	99% OBW (MHz)	Limit
2422	36.56	36.08	>=500 kHz
2437	36.64	36.16	
2452	36.56	36.08	

N Mode 2422 MHz




Date: 24.NOV.2015 15:57:30

N Mode 2437 MHz



Date: 24.NOV.2015 15:55:36

N Mode 2452 MHz



Date: 24.NOV.2015 15:54:02

7. POWER SPECTRAL DENSITY

7.1 LIMITS


FCC Part 15.247, Subpart C	
Frequency Range (MHz)	2400~2483.5
99% Occupied Bandwidth	8 dBm in any 3 kHz

7.2 TEST PROCEDURE

The EUT was directly connected to the power meter and antenna output port as show in the block diagram as bellow.

Spectrum Parameters	Setting
Attenuation	Auto
Span	Set the span to 1.5 times the DTS channel bandwidth
RBW	3 kHz
VBW	$\geq 3\text{RBW}$
Detector	Reak
Trace	Max Hold
Sweep Time	Auto

7.3 TEST SETUP



7.4 TEST INSTRUMENTS

Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
Spectrum Analyzer	R&S	FSP40	100154	Jul. 05, 2015	Jul. 04. 2016	1 year


7.5 EUT OPERATING CONDITIONS

The EUT was set to continuously transmitting in the maximum power during the test.

7.6 TEST RESULTS


801.11b Mode					
Frequency (MHz)	Power Density (3 kHz/dBm)			Limit (dBm/3KHz)	Result
	ANT 1	ANT 2	Total		
2412	-11.20			8	Pass
2437	-10.84				
2462	-10.92				

B Mode 2412 MHz




Date: 24.NOV.2015 16:09:46

B Mode 2437 MHz



Date: 24.NOV.2015 16:10:16


B Mode 2462 MHz



Date: 24.NOV.2015 16:10:37


801.11g Mode					
Frequency (MHz)	Power Density (3 kHz/dBm)			Limit (dBm/3KHz)	Result
	ANT 1	ANT 2	Total		
2412	-15.46	/	/	8	Pass
2437	-15.49	/	/		
2462	-15.34	/	/		

G Mode 2412 MHz-ANT 0




Date: 24.NOV.2015 16:18:57

G Mode 2437 MHz-ANT 0



Date: 24.NOV.2015 16:18:29


G Mode 2462 MHz-ANT 0



Date: 24.NOV.2015 16:18:01


801.11n(HT20) Mode					
Frequency (MHz)	Power Density (3 kHz/dBm)			Limit (dBm/3KHz)	Result
	ANT 1	ANT 2	Total		
2412	-15.19	/	/	8	Pass
2437	-15.33	/	/		
2462	-14.63	/	/		

N (HT20) Mode 2412 MHz-ANT 0




Date: 24.NOV.2015 16:14:23

N (HT20) 2437 MHz-ANT 0



Date: 24.NOV.2015 16:15:13


N (HT20) 2462 MHz-ANT 0



Date: 24.NOV.2015 16:15:45


801.11n(HT40) Mode					
Frequency (MHz)	Power Density (3 kHz/dBm)			Limit (dBm/3KHz)	Result
	ANT 1	ANT 2	Total		
2422	-18.71			8	Pass
2437	-18.92				
2452	-17.16				

N (HT40) Mode 2422 MHz-ANT 0




Date: 24.NOV.2015 16:06:17

N (HT40) 2437 MHz-ANT 0



Date: 24.NOV.2015 16:06:48

N (HT40) 2452 MHz-ANT 0



Date: 24.NOV.2015 16:07:25

8. ANTENNA CONDUCTED SPURIOUS EMISSION

8.1 LIMITS

FCC Part 15.247, Subpart C	
Frequency Range (MHz)	2400~2483.5
Limit	In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the desired power, based on either an RF conducted measurement, provide the transmitter demonstrates compliance with the peak conducted power limits.


8.2 TEST PROCEDURE

The EUT was directly connected to the power meter and antenna output port as show in the block diagram as bellow.

- Set frequency range to capture low band-edge from 2310 MHz up to 2390 MHz, and for up band-edge from 2483.5 MHz up to 2500 MHz
- For low band-edge set the equipment transmit at the lowest channel, and for up band-edge set the equipment transmit at the highest channel
- Set the VBW \geq 3 RBW (100kHz/ 300kHz) for conducted measurement
- For radiated measurements the RBW set to 1 MHz, and the VBW set to 1 MHz for peak measurements and 10 Hz for average measurement

8.3 TEST SETUP

Conducted Emission Test Setup



8.4 TEST INSTRUMENTS

Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
Spectrum Analyzer	R&S	FSP40	100154	Jul. 05, 2015	Jul. 04. 2016	1 year


8.5 EUT OPERATING CONDITIONS

The EUT was set to continuously transmitting in the maximum power during the test.

8.6 TEST RESULTS


Only showed the worst mode data of ANT 0 transmitting.

B Mode Low CH




Date: 1.DEC.2015 10:22:59

B Mode High CH




Date: 1.DEC.2015 10:27:59

B Mode Low CH (30MHz~1GHz)




Date: 1.DEC.2015 10:23:12

B Mode Low CH (1GHz~26.5GHz)




Date: 1.DEC.2015 10:23:28

B Mode Middle CH (30MHz~1GHz)




Date: 1.DEC.2015 10:26:23

B Mode Middle CH (1GHz~26.5GHz)




Date: 1.DEC.2015 10:26:36

B Mode High CH (30MHz~1GHz)




Date: 1.DEC.2015 10:28:10

B Mode High CH (1GHz~26.5GHz)




Date: 1.DEC.2015 10:28:27

G Mode Low CH




Date: 1.DEC.2015 10:31:54

B Mode High CH




Date: 1.DEC.2015 10:36:47

N(HT20) Mode Low CH




Date: 1.DEC.2015 10:01:53

N(HT20) Mode High CH




Date: 1.DEC.2015 10:06:26

N(HT20) Mode Low CH (30MHz~1GHz)




Date: 1.DEC.2015 10:02:06

N(HT20) Mode Low CH (1GHz~26.5GHz)




Date: 1.DEC.2015 10:02:18

N(HT20) Mode Middle CH (30MHz~1GHz)




Date: 1.DEC.2015 10:03:33

N(HT20) Mode Middle CH (1GHz~26.5GHz)




Date: 1.DEC.2015 10:03:45

N(HT20) Mode High CH (30MHz~1GHz)




Date: 1.DEC.2015 10:06:37

N(HT20) Mode High CH (1GHz~26.5GHz)




Date: 2.SEP.2015 15:32:58

N(HT40) Mode Low CH




Date: 1.DEC.2015 10:08:58

N(HT40) Mode High CH




Date: 1.DEC.2015 10:15:17

N(HT40) Mode Low CH (30MHz~1GHz)




Date: 1.DEC.2015 10:09:10

N(HT40) Mode Low CH (1GHz~26.5GHz)




Date: 1.DEC.2015 10:09:23

N(HT40) Mode Middle CH (30MHz~1GHz)




Date: 1.DEC.2015 10:11:38

N(HT40) Mode Middle CH (1GHz~26.5GHz)




Date: 1.DEC.2015 10:11:51

N(HT40) Mode High CH (30MHz~1GHz)



Date: 1.DEC.2015 10:15:30

N(HT40) Mode High CH (1GHz~26.5GHz)



Date: 1.DEC.2015 10:15:44

9. ANTENNA REQUIREMENT

9.1 REQUIREMENT

Antenna Requirement (15.203)	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
Antenna Requirement (15.247)	If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

9.2 ANTENNA CONNECTOR CONSTRUCTION

The EUT antenna is a PIFA Antenna. And the maximum gain of this antenna is 3.0 dBi. It complies with the standard requirement.