

FCC Part 15C Measurement and Test Report

For

Hui Zhou Gaoshengda Technology Co.,LTD

NO.75 Zhongkai Development Area, Huizhou, Guangdong, China

FCC ID: 2AC23- WC0FR2601

FCC Rule(s):	<u>FCC Part 15C</u>	
Product Description:	<u>WIFI Module</u>	
Tested Model:	<u>WC0FR2601</u>	
Report No.:	<u>FCC-ATL20161118887-1</u>	
Issued Date:	<u>2016-11-23</u>	
Tested By:	<u>Si feifei / Engineer</u>	<i>Si feifei</i>
Reviewed By:	<u>Xie Lingling / EMC Manager</u>	<i>Xie Lingling</i>
Approved & Authorized By:	<u>Xu Peng / PSQ Manager</u>	<i>Xu Peng</i>
Prepared By:	Shenzhen ATL Testing Technology Co., Ltd. F/4, Building 10, Dayuan Industrial Zone, Xili Town, Nanshan District, Shenzhen, China (518055) Tel.: +86-0755-26909822 Fax.: +86-0755-61605504 Website: www.atllab.org	

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen ATL Testing Technology Co., Ltd.. This document may be altered or revised by Shenzhen ATL Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample

TABLE OF CONTENTS

1. GENERAL INFORMATION.....3

 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3

 1.2 TEST STANDARDS.....4

 1.3 TEST METHODOLOGY.....4

 1.4 EUT SETUP AND TEST MODE.....4

 1.5 MEASUREMENT UNCERTAINTY.....5

 1.6 TEST EQUIPMENT LIST AND DETAILS.....6

2. SUMMARY OF TEST RESULTS7

3. RF EXPOSURE8

 3.1 STANDARD APPLICABLE.....8

 3.2 TEST RESULT.....8

4. ANTENNA REQUIREMENT9

 4.1 STANDARD APPLICABLE.....9

 4.2 EVALUATION INFORMATION.....9

5. POWER SPECTRAL DENSITY10

 5.1 STANDARD APPLICABLE.....10

 5.2 TEST PROCEDURE.....10

 5.3 ENVIRONMENTAL CONDITIONS.....10

 5.4 SUMMARY OF TEST RESULTS/PLOTS.....11

6. 6DB BANDWIDTH18

 6.1 STANDARD APPLICABLE.....18

 6.2 TEST PROCEDURE.....18

 6.3 ENVIRONMENTAL CONDITIONS.....18

 6.4 SUMMARY OF TEST RESULTS/PLOTS.....18

7. RF OUTPUT POWER25

 7.1 STANDARD APPLICABLE.....25

 7.2 TEST PROCEDURE.....25

 7.3 ENVIRONMENTAL CONDITIONS.....25

 7.4 SUMMARY OF TEST RESULTS/PLOTS.....26

8. FIELD STRENGTH OF SPURIOUS EMISSIONS27

 8.1 STANDARD APPLICABLE.....27

 8.2 TEST PROCEDURE.....27

 8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....28

 8.4 ENVIRONMENTAL CONDITIONS.....28

 8.5 SUMMARY OF TEST RESULTS/PLOTS.....29

9. OUT OF BAND EMISSIONS.....57

 9.1 STANDARD APPLICABLE.....57

 9.2 TEST PROCEDURE.....57

 9.3 ENVIRONMENTAL CONDITIONS.....58

 9.4 SUMMARY OF TEST RESULTS/PLOTS.....58

10. CONDUCTED EMISSIONS66

 10.1 TEST PROCEDURE.....66

 10.2 BASIC TEST SETUP BLOCK DIAGRAM.....66

 10.3 ENVIRONMENTAL CONDITIONS.....66

 10.4 TEST RECEIVER SETUP.....67

 10.5 SUMMARY OF TEST RESULTS/PLOTS.....67

 10.6 CONDUCTED EMISSIONS TEST DATA.....67

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Hui Zhou Gaoshengda Technology Co.,LTD
 Address of applicant: NO.75 Zhongkai Development Area, Huizhou, Guangdong, China
 Manufacturer: Hui Zhou Gaoshengda Technology Co.,LTD
 Address of manufacturer: NO.75 Zhongkai Development Area, Huizhou, Guangdong, China

General Description of EUT	
Product Name:	WIFI Module
Trade Name:	GSD
Model No.:	WC0FR2601
Adding Model(s):	/
Power Adapter Model:	/
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz
RF Output Power:	15.96 dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11
Channel Separation:	5MHz
Type of Antenna:	PIFA Antenna
Antenna Gain:	3 dBm
Lowest Internal Frequency	4MHz

1.2 Test Standards

The following report is prepared on behalf of the Hui Zhou Gaoshengda Technology Co.,LTD in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 v03r05 for digital transmission systems shall be performed also.

1.4 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz
TM2	802.11g	2412MHz, 2437MHz, 2462MHz
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz
TM4	802.11n-HT40	2422MHz, 2437MHz, 2452MHz

Accessories Equipment List and Details			
Description	Manufacturer	Model No.	Serial Number
Notebook	Lenovo	T410	/
Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
USB Cable	1.0	Unshielded	Without Ferrite
EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.5 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

1.6 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
Spectrum Analyzer	Agilent	E4407B	MY41440400	2016-06-04	2017-06-03
Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2016-06-04	2017-06-03
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2016-06-04	2017-06-03
Amplifier	Agilent	8447F	3113A06717	2016-06-04	2017-06-03
Amplifier	C&D	PAP-1G18	2002	2016-06-04	2017-06-03
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2016-06-04	2017-06-03
Horn Antenna	ETS	3117	00086197	2016-06-04	2017-06-03
Horn Antenna	ETS	3116B	00088203	2016-06-04	2017-06-03
Loop Antenna	Schwarz beck	FMZB 1516	9773	2016-06-04	2017-06-03
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2016-06-04	2017-06-03
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2016-06-04	2017-06-03
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2016-06-04	2017-06-03
Power Meter	R&S	NRVS	100444	2016-06-18	2017-06-17

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has an integral antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure

According to the KDB 558074 D01 v03r05, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b	2412	-13.53	8
	2437	-11.53	8
	2462	-11.90	8
802.11g	2412	-15.83	8
	2437	-14.17	8
	2462	-15.03	8
802.11n HT20	2412	-16.95	8
	2437	-16.61	8
	2462	-15.26	8
802.11n HT40	2422	-21.24	8
	2437	-20.87	8
	2452	-20.20	8

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



6. 6dB Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Environmental Conditions


Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

6.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	6 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz
802.11b	2412	9595	14960.9	≥ 500
	2437	9939	14931.8	≥ 500
	2462	10102	14987.9	≥ 500
802.11g	2412	16347	16443.4	≥ 500
	2437	16561	16481.3	≥ 500
	2462	16454	16408.5	≥ 500
802.11n-HT20	2412	17725	17638.4	≥ 500
	2437	17567	17591.3	≥ 500
	2462	17613	17605.2	≥ 500
802.11n-HT40	2422	35884	35873.4	≥ 500
	2437	35802	35934.4	≥ 500
	2452	35595	35846.0	≥ 500

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

According to the KDB-558074 D01 v03r05, 9.2.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle $< 98 \%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98 \%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.3 Environmental Conditions

Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results/Plots

Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b _ 11Mbps	2412	15.96	39.45	1000
	2437	15.54	35.81	1000
	2462	15.09	32.28	1000
802.11g_54Mbps	2412	15.65	36.73	1000
	2437	14.98	31.48	1000
	2462	14.87	30.69	1000
802.11n HT20_MCS7	2412	15.05	31.99	1000
	2437	15.76	37.67	1000
	2462	14.93	31.12	1000
802.11n HT40_MCS7	2422	14.70	29.51	1000
	2437	15.57	36.06	1000
	2452	15.06	32.06	1000

8. Field Strength of Spurious Emissions

8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

8.5 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: *WIFI Module*
 Tested Model: *WC0FR2601*
 Operating Condition: *802.11b Transmitting Low Channel-2412MHz*
 Comment: *AC 120V/60Hz; Connected to PC*

Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	54.2610	22.74	-8.86	13.88	40.00	-26.12	254	100	peak
2	104.5361	23.43	-11.02	12.41	43.50	-31.09	113	100	peak
3	163.1818	25.97	-12.13	13.84	43.50	-29.66	284	100	peak
4	193.7728	28.24	-9.48	18.76	43.50	-24.74	254	100	peak
5	262.8955	32.44	-6.83	25.61	46.00	-20.39	113	100	peak
6	909.6667	21.76	3.39	25.15	46.00	-20.85	284	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.0048	33.42	-9.04	24.38	40.00	-15.62	114	100	peak
2	77.3212	28.86	-12.21	16.65	40.00	-23.35	270	100	peak
3	157.5589	30.16	-12.31	17.85	43.50	-25.65	360	100	peak
4	261.0583	25.71	-6.91	18.80	46.00	-27.20	114	100	peak
5	636.1340	21.07	0.82	21.89	46.00	-24.11	270	100	peak
6	785.0935	22.03	2.65	24.68	46.00	-21.32	360	100	peak

Operating Condition: 802.11b Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz; Connected to PC

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	48.3318	22.48	-8.21	14.27	40.00	-25.73	178	100	peak
2	70.8315	24.52	-12.77	11.75	40.00	-28.25	224	100	peak
3	191.7450	28.22	-9.77	18.45	43.50	-25.05	160	100	peak
4	261.0583	32.87	-6.91	25.96	46.00	-20.04	178	100	peak
5	625.0780	21.22	1.11	22.33	46.00	-23.67	224	100	peak
6	916.0687	21.41	3.56	24.97	46.00	-21.03	160	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	36.2541	32.03	-8.69	23.34	40.00	-16.66	256	100	peak
2	78.6888	28.98	-12.10	16.88	40.00	-23.12	360	100	peak
3	157.5589	30.47	-12.31	18.16	43.50	-25.34	360	100	peak
4	261.9753	26.16	-6.87	19.29	46.00	-26.71	256	100	peak
5	462.3455	22.43	-2.50	19.93	46.00	-26.07	360	100	peak
6	771.4486	23.29	2.43	25.72	46.00	-20.28	360	100	peak

Operating Condition: 802.11b Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz; Connected to PC

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	41.5670	22.44	-7.77	14.67	40.00	-25.33	176	100	peak
2	105.6415	24.15	-11.05	13.10	43.50	-30.40	255	100	peak
3	157.5589	26.70	-12.31	14.39	43.50	-29.11	360	100	peak
4	194.4534	28.25	-9.40	18.85	43.50	-24.65	176	100	peak
5	254.7284	32.59	-7.31	25.28	46.00	-20.72	255	100	peak
6	779.6068	21.82	2.88	24.70	46.00	-21.30	360	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	36.0007	31.71	-8.76	22.95	40.00	-17.05	360	100	peak
2	77.5928	29.99	-12.20	17.79	40.00	-22.21	225	100	peak
3	157.5589	30.13	-12.31	17.82	43.50	-25.68	160	100	peak
4	381.2487	21.34	-2.17	19.17	46.00	-26.83	360	100	peak
5	771.4486	22.46	2.43	24.89	46.00	-21.11	225	100	peak
6	996.4996	20.88	4.64	25.52	54.00	-28.48	160	100	peak

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: *WIFI Module*
 Tested Model: *WC0FR2601*
 Operating Condition: *802.11g Transmitting Low Channel-2412MHz*
 Comment: *AC 120V/60Hz; Connected to PC*

Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	41.5670	21.70	-7.77	13.93	40.00	-26.07	174	100	peak
2	60.9176	23.13	-9.87	13.26	40.00	-26.74	160	100	peak
3	155.9101	28.32	-12.34	15.98	43.50	-27.52	320	100	peak
4	193.7728	30.64	-9.48	21.16	43.50	-22.34	174	100	peak
5	261.0583	32.92	-6.91	26.01	46.00	-19.99	160	100	peak
6	804.6028	24.22	1.81	26.03	46.00	-19.97	320	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.6240	32.22	-8.87	23.35	40.00	-16.65	177	100	peak
2	77.3212	28.67	-12.21	16.46	40.00	-23.54	90	100	peak
3	157.5589	29.36	-12.31	17.05	43.50	-26.45	336	100	peak
4	264.7457	25.62	-6.76	18.86	46.00	-27.14	177	100	peak
5	383.9318	21.43	-2.30	19.13	46.00	-26.87	90	100	peak
6	785.0935	22.96	2.65	25.61	46.00	-20.39	336	100	peak

Operating Condition: 802.11g Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz; Connected to PC

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	41.5670	21.22	-7.77	13.45	40.00	-26.55	270	100	peak
2	54.0711	22.71	-8.83	13.88	40.00	-26.12	164	100	peak
3	105.2718	22.66	-11.04	11.62	43.50	-31.88	228	200	peak
4	197.8928	27.69	-8.94	18.75	43.50	-24.75	270	100	peak
5	259.2338	32.11	-7.00	25.11	46.00	-20.89	164	100	peak
6	962.1623	21.10	3.61	24.71	54.00	-29.29	228	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.7491	33.48	-8.84	24.64	40.00	-15.36	360	100	peak
2	75.4464	28.62	-12.37	16.25	40.00	-23.75	255	100	peak
3	157.5589	29.10	-12.31	16.79	43.50	-26.71	270	100	peak
4	262.8955	26.24	-6.83	19.41	46.00	-26.59	360	100	peak
5	633.9073	21.03	0.87	21.90	46.00	-24.10	255	100	peak
6	785.0935	23.51	2.65	26.16	46.00	-19.84	270	100	peak

Operating Condition: 802.11g Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz; Connected to PC

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	47.4918	22.59	-8.16	14.43	40.00	-25.57	270	100	peak
2	101.6443	22.98	-10.94	12.04	43.50	-31.46	51	200	peak
3	193.7728	28.62	-9.48	19.14	43.50	-24.36	360	200	peak
4	254.7284	33.28	-7.31	25.97	46.00	-20.03	270	100	peak
5	543.2742	22.50	-1.72	20.78	46.00	-25.22	51	100	peak
6	636.1340	21.98	0.82	22.80	46.00	-23.20	360	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.3750	31.66	-8.93	22.73	40.00	-17.27	360	100	peak
2	77.5928	29.36	-12.20	17.16	40.00	-22.84	180	100	peak
3	157.5589	29.99	-12.31	17.68	43.50	-25.82	225	100	peak
4	264.7457	26.04	-6.76	19.28	46.00	-26.72	360	100	peak
5	482.2156	22.42	-1.17	21.25	46.00	-24.75	180	100	peak
6	785.0935	22.35	2.65	25.00	46.00	-21.00	225	100	peak

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: *WIFI Module*
 Tested Model: *WC0FR2601*
 Operating Condition: *802.11n-HT20 Transmitting Low Channel-2412MHz*
 Comment: *AC 120V/60Hz; Connected to PC*

Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	42.3022	21.96	-7.82	14.14	40.00	-25.86	260	100	peak
2	104.9033	23.30	-11.03	12.27	43.50	-31.23	131	200	peak
3	195.1365	28.15	-9.30	18.85	43.50	-24.65	285	200	peak
4	258.3264	32.85	-7.07	25.78	46.00	-20.22	260	100	peak
5	625.0780	21.68	1.11	22.79	46.00	-23.21	131	200	peak
6	962.1623	22.67	3.61	26.28	54.00	-27.72	285	200	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.0048	31.45	-9.04	22.41	40.00	-17.59	155	100	peak
2	42.7496	27.41	-7.84	19.57	40.00	-20.43	197	100	peak
3	77.8654	28.53	-12.17	16.36	40.00	-23.64	310	100	peak
4	157.5589	29.72	-12.31	17.41	43.50	-26.09	155	100	peak
5	262.8955	24.69	-6.83	17.86	46.00	-28.14	197	100	peak
6	878.3214	21.91	3.12	25.03	46.00	-20.97	310	100	peak

Operating Condition: 802.11n-HT20 Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz; Connected to PC

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	49.8814	22.45	-8.31	14.14	40.00	-25.86	274	100	peak
2	107.1337	23.09	-11.10	11.99	43.50	-31.51	116	100	peak
3	164.3302	26.96	-12.07	14.89	43.50	-28.61	82	100	peak
4	193.7728	29.95	-9.48	20.47	43.50	-23.03	274	100	peak
5	255.6231	33.95	-7.24	26.71	46.00	-19.29	116	100	peak
6	942.1305	21.35	4.19	25.54	46.00	-20.46	82	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.6240	32.90	-8.87	24.03	40.00	-15.97	264	100	peak
2	77.3212	29.06	-12.21	16.85	40.00	-23.15	110	100	peak
3	143.3261	29.62	-12.51	17.11	43.50	-26.39	136	100	peak
4	258.3264	26.70	-7.07	19.63	46.00	-26.37	264	100	peak
5	595.1329	22.49	-0.33	22.16	46.00	-23.84	110	100	peak
6	790.6188	23.22	2.37	25.59	46.00	-20.41	136	100	peak

Operating Condition: 802.11n-HT20 Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz; Connected to PC

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	38.4809	21.69	-8.08	13.61	40.00	-26.39	360	100	peak
2	105.6415	23.26	-11.05	12.21	43.50	-31.29	112	100	peak
3	158.1123	25.83	-12.30	13.53	43.50	-29.97	180	200	peak
4	189.0743	29.06	-10.12	18.94	43.50	-24.56	360	100	peak
5	254.7284	33.15	-7.31	25.84	46.00	-20.16	112	100	peak
6	787.8513	21.61	2.51	24.12	46.00	-21.88	180	200	peak


Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.6240	31.94	-8.87	23.07	40.00	-16.93	267	100	peak
2	78.4134	28.69	-12.12	16.57	40.00	-23.43	116	100	peak
3	143.3261	28.32	-12.51	15.81	43.50	-27.69	360	100	peak
4	157.5589	29.08	-12.31	16.77	43.50	-26.73	267	100	peak
5	259.2338	25.77	-7.00	18.77	46.00	-27.23	116	100	peak
6	782.3453	22.51	2.78	25.29	46.00	-20.71	360	100	peak


EUT: *WIFI Module*
 Tested Model: *WC0FR2601*
 Operating Condition: *802.11n-HT40 Transmitting Low Channel-2422MHz*
 Comment: *AC 120V/60Hz; Connected to PC*

Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	43.3534	22.09	-7.89	14.20	40.00	-25.80	267	100	peak
2	61.3463	23.20	-10.02	13.18	40.00	-26.82	114	200	peak
3	102.3597	24.52	-10.97	13.55	43.50	-29.95	35	200	peak
4	193.7728	29.05	-9.48	19.57	43.50	-23.93	267	100	peak
5	262.8955	32.45	-6.83	25.62	46.00	-20.38	114	200	peak
6	776.8778	20.78	2.73	23.51	46.00	-22.49	35	200	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.4993	32.53	-8.90	23.63	40.00	-16.37	360	100	peak
2	77.8654	29.16	-12.17	16.99	40.00	-23.01	258	100	peak
3	143.3261	28.65	-12.51	16.14	43.50	-27.36	347	100	peak
4	256.5211	26.21	-7.18	19.03	46.00	-26.97	360	100	peak
5	374.6226	22.52	-2.41	20.11	46.00	-25.89	258	100	peak
6	912.8620	23.98	3.49	27.47	46.00	-18.53	347	100	peak

Operating Condition: 802.11n-HT40 Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz; Connected to PC

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	46.9948	21.85	-8.13	13.72	40.00	-26.28	251	100	peak
2	102.3597	23.12	-10.97	12.15	43.50	-31.35	167	100	peak
3	193.7728	29.43	-9.48	19.95	43.50	-23.55	44	100	peak
4	260.1444	32.63	-6.95	25.68	46.00	-20.32	251	100	peak
5	387.9920	23.93	-2.51	21.42	46.00	-24.58	167	100	peak
6	857.0247	22.19	2.78	24.97	46.00	-21.03	44	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.8747	31.66	-8.79	22.87	40.00	-17.13	47	100	peak
2	77.0505	28.01	-12.24	15.77	40.00	-24.23	264	100	peak
3	143.3261	28.73	-12.51	16.22	43.50	-27.28	225	100	peak
4	261.0583	25.46	-6.91	18.55	46.00	-27.45	47	100	peak
5	633.9073	21.33	0.87	22.20	46.00	-23.80	264	100	peak
6	779.6068	22.18	2.88	25.06	46.00	-20.94	225	100	peak

Operating Condition: 802.11n-HT40 Transmitting High Channel-2452MHz


Comment: AC 120V/60Hz; Connected to PC

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	41.8596	21.93	-7.79	14.14	40.00	-25.86	360	100	peak
2	103.4421	23.04	-10.99	12.05	43.50	-31.45	287	100	peak
3	193.7728	28.72	-9.48	19.24	43.50	-24.26	168	100	peak
4	262.8955	32.09	-6.83	25.26	46.00	-20.74	360	100	peak
5	627.2738	22.50	1.05	23.55	46.00	-22.45	287	100	peak
6	916.0687	20.91	3.56	24.47	46.00	-21.53	168	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.4993	31.73	-8.90	22.83	40.00	-17.17	78	100	peak
2	77.8654	29.57	-12.17	17.40	40.00	-22.60	136	100	peak
3	157.5589	29.21	-12.31	16.90	43.50	-26.60	284	100	peak
4	265.6757	25.79	-6.71	19.08	46.00	-26.92	78	100	peak
5	771.4486	22.97	2.43	25.40	46.00	-20.60	136	100	peak
6	863.0562	23.56	2.97	26.53	46.00	-19.47	284	100	peak

Spurious Emissions Above 1GHz

Test Mode: 802.11b

Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
4824.000	56.91	-3.74	53.17	74	-20.83	H	PK
4824.000	46.37	-3.74	42.63	54	-11.37	H	AV
7236.000	42.98	1.47	44.45	74	-29.55	H	PK
7236.000	36.59	1.47	38.06	54	-15.94	H	AV
4824.000	51.62	-3.74	47.88	74	-26.12	V	PK
4824.000	41.93	-3.74	38.19	54	-15.81	V	AV
7236.000	44.92	1.47	46.39	74	-27.61	V	PK
7236.000	38.59	1.47	40.06	54	-13.94	V	AV
Middle Channel-2437MHz							
4874.000	54.16	-3.87	50.29	74	-23.71	H	PK
4874.000	42.48	-3.87	38.61	54	-15.39	H	AV
7311.000	48.74	1.14	49.88	74	-24.12	H	PK
7311.000	33.1	1.19	34.29	54	-19.71	H	AV
4874.000	54.92	-3.86	51.06	74	-22.94	V	PK
4874.000	42.62	-3.86	38.76	54	-15.24	V	AV
7311.000	48.49	1.1	49.59	74	-24.41	V	PK
7311.000	35.2	1.1	36.3	54	-17.7	V	AV
High Channel-2462MHz							
4924.000	54.00	-3.59	50.41	74	-23.59	H	PK
4924.000	40.75	-3.59	37.16	54	-16.84	H	AV
7386.000	47.18	1.79	48.97	74	-25.03	H	PK
7386.000	34.73	1.79	36.52	54	-17.48	H	AV
4924.000	56.11	-3.59	52.52	74	-21.48	V	PK
4924.000	42.69	-3.59	39.1	54	-14.9	V	AV
7386.000	48.58	1.79	50.37	74	-23.63	V	PK
7386.000	35.95	1.79	37.74	54	-16.26	V	AV

Test Mode: 802.11g

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	56.13	-3.87	52.26	74	-21.74	H	PK
4824.000	39.18	-3.87	35.31	54	-18.69	H	AV
7236.000	44.95	1.14	46.09	74	-27.91	H	PK
7236.000	33.21	1.19	34.4	54	-19.6	H	AV
4824.000	53.84	-3.86	49.98	74	-24.02	V	PK
4824.000	44.53	-3.86	40.67	54	-13.33	V	AV
7236.000	45.66	1.1	46.76	74	-27.24	V	PK
7236.000	40.73	1.1	41.83	54	-12.17	V	AV
Middle Channel-2437MHz							
4874.000	55.6	-3.74	51.86	74	-22.14	H	PK
4874.000	40.54	-3.74	36.8	54	-17.2	H	AV
7311.000	47.26	1.47	48.73	74	-25.27	H	PK
7311.000	34.44	1.47	35.91	54	-18.09	H	AV
4874.000	56.71	-3.74	52.97	74	-21.03	V	PK
4874.000	43.18	-3.74	39.44	54	-14.56	V	AV
7311.000	49.21	1.47	50.68	74	-23.32	V	PK
7311.000	35.77	1.47	37.24	54	-16.76	V	AV
High Channel-2462MHz							
4924.000	55.6	-3.59	52.01	74	-21.99	H	PK
4924.000	40.54	-3.59	36.95	54	-17.05	H	AV
7386.000	47.26	1.79	49.05	74	-24.95	H	PK
7386.000	34.44	1.79	36.23	54	-17.77	H	AV
4924.000	56.71	-3.59	53.12	74	-20.88	V	PK
4924.000	43.18	-3.59	39.59	54	-14.41	V	AV
7386.000	49.21	1.79	51	74	-23	V	PK
7386.000	35.77	1.79	37.56	54	-16.44	V	AV

Test Mode: 802.11n-HT20

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	54.18	-3.87	50.31	74	-23.69	H	PK
4824.000	47.57	-3.87	43.7	54	-10.3	H	AV
7236.000	45.63	1.14	46.77	74	-27.23	H	PK
7236.000	37.59	1.19	38.78	54	-15.22	H	AV
4824.000	55.64	-3.86	51.78	74	-22.22	V	PK
4824.000	41.32	-3.86	37.46	54	-16.54	V	AV
7236.000	47.61	1.1	48.71	74	-25.29	V	PK
7236.000	37.28	1.1	38.38	54	-15.62	V	AV
Middle Channel-2437MHz							
4874.000	53.74	-3.74	50	74	-24	H	PK
4874.000	44.53	-3.74	40.79	54	-13.21	H	AV
7311.000	46.79	1.47	48.26	74	-25.74	H	PK
7311.000	39.28	1.47	40.75	54	-13.25	H	AV
4874.000	55.67	-3.74	51.93	74	-22.07	V	PK
4874.000	45.62	-3.74	41.88	54	-12.12	V	AV
7311.000	46.37	1.47	47.84	74	-26.16	V	PK
7311.000	38.24	1.47	39.71	54	-14.29	V	AV
High Channel-2462MHz							
4924.000	49.95	-3.59	46.36	74	-27.64	H	PK
4924.000	39.57	-3.59	35.98	54	-18.02	H	AV
7386.000	48.74	1.79	50.53	74	-23.47	H	PK
7386.000	34.78	1.79	36.57	54	-17.43	H	AV
4924.000	56.53	-3.59	52.94	74	-21.06	V	PK
4924.000	43.89	-3.59	40.3	54	-13.7	V	AV
7386.000	48.49	1.79	50.28	74	-23.72	V	PK
7386.000	33.57	1.79	35.36	54	-18.64	V	AV

Test Mode: 802.11n-HT40

Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2422MHz							
4844.000	53.82	-3.9	49.92	74	-24.08	H	PK
4824.000	42.19	-3.9	38.29	54	-15.71	H	AV
7266.000	51.67	1.06	52.73	74	-21.27	H	PK
7266.000	43.59	1.06	44.65	54	-9.35	H	AV
4844.000	56.12	-3.9	52.22	74	-21.78	V	PK
4824.000	42.57	-3.9	38.67	54	-15.33	V	AV
7266.000	51.58	1.06	52.64	74	-21.36	V	PK
7266.000	41.62	1.06	42.68	54	-11.32	V	AV
Middle Channel-2437MHz							
4874.000	54.53	-3.74	50.79	74	-23.21	H	PK
4874.000	42.94	-3.74	39.2	54	-14.8	H	AV
7311.000	55.82	1.47	57.29	74	-16.71	H	PK
7311.000	43.67	1.47	45.14	54	-8.86	H	AV
4874.000	50.59	-3.74	46.85	74	-27.15	V	PK
4874.000	39.73	-3.74	35.99	54	-18.01	V	AV
7311.000	46.82	1.47	48.29	74	-25.71	V	PK
7311.000	37.67	1.47	39.14	54	-14.86	V	AV
High Channel-2452MHz							
4904.000	55.61	-3.63	51.98	74	-22.02	H	PK
4904.000	43.51	-3.63	39.88	54	-14.12	H	AV
7356.000	52.74	1.62	54.36	74	-19.64	H	PK
7356.000	43.52	1.62	45.14	54	-8.86	H	AV
4904.000	51.69	-3.63	48.06	74	-25.94	V	PK
4904.000	43.82	-3.63	40.19	54	-13.81	V	AV
7356.000	49.66	1.62	51.28	74	-22.72	V	PK
7356.000	41.53	1.62	43.15	54	-10.85	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074D01 v03r04, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 v03r05, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW \geq 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar


9.4 Summary of Test Results/Plots

802.11b-Lowest Bandedge

Vertical (Worst case)

802.11b-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	29.50	-3.71	25.79	54.00	-28.21	Average Detector
		42.81	-3.71	39.10	74.00	-34.90	Peak Detector
2	2390.000	31.27	-3.54	27.73	54.00	-26.27	Average Detector
		44.12	-3.54	40.58	74.00	-33.42	Peak Detector
3	2400.000	Delta =32.13dBc		45.68	/	/	Average Detector
				71.52	/	/	Peak Detector
4	2412.000	83.61	-3.49	80.12	/	/	Average Detector
		106.9	-3.49	103.41	/	/	Peak Detector


802.11b-Highest Bandedge

Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.600	87.03	-3.37	83.66	/	/	Average Detector
	2462.300	96.01	-3.36	92.65	/	/	Peak Detector
2	2483.500	Delta = 56.75dBc		24.67	54.00	-29.33	Average Detector
	2483.500			33.67	74.00	-40.33	Peak Detector
3	2500.000	29.17	-3.28	25.89	54.00	-28.11	Average Detector
	2500.000	41.43	-3.28	38.15	74.00	-35.85	Peak Detector

802.11g-Lowest Bandedge
Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	29.51	-3.71	25.80	54.00	-28.20	Average Detector
	2310.000	41.73	-3.71	38.02	74.00	-35.98	Peak Detector
2	2390.000	33.32	-3.54	29.78	54.00	-24.22	Average Detector
	2390.000	47.51	-3.54	43.97	74.00	-30.03	Peak Detector
3	2400.000	Delta =33.23dBc		42.18	/	/	Average Detector
	2400.000	Delta =33.23dBc		68.32	/	/	Peak Detector
4	2412.000	82.03	-3.49	78.54	/	/	Average Detector
	2412.000	104.8	-3.49	101.31	/	/	Peak Detector

802.11g-Highest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2460.700	80.70	-3.37	77.33	/	/	Average Detector
	2461.650	91.88	-3.36	88.52	/	/	Peak Detector
1	2483.500	Delta = 44.82dBc		30.33	54.00	-23.69	Average Detector
	2483.500	Delta = 44.82dBc		41.59	74.00	-32.41	Peak Detector
3	2500.000	29.60	-3.28	26.32	54.00	-27.68	Average Detector
	2500.000	42.55	-3.28	39.27	74.00	-34.73	Peak Detector


802.11n-HT20-Lowest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	29.43	-3.71	25.72	54.00	-28.28	Average Detector
	2310.000	42.34	-3.71	38.63	74.00	-35.37	Peak Detector
2	2390.000	34.55	-3.54	31.01	54.00	-22.99	Average Detector
	2390.000	51.10	-3.54	47.56	74.00	-26.44	Peak Detector
3	2400.000	Delta =33.02dBc		41.53	/	/	Average Detector
	2400.000	Delta =33.02dBc		67.54	/	/	Peak Detector
4	2412.000	82.04	-3.49	78.55	/	/	Average Detector
	2412.000	103.81	-3.49	100.32	/	/	Peak Detector


802.11n-HT20-Highest Bandedge

Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2460.620	80.29	-3.37	76.92	/	/	Average Detector
	2462.370	91.78	-3.37	88.41	/	/	Peak Detector
2	2483.500	Delta = 46.52dBc		28.67	54.00	-25.33	Average Detector
	2483.500			40.16	74.00	-33.84	Peak Detector
3	2500.000	29.63	-3.28	26.35	54.00	-27.65	Average Detector
	2500.000	41.59	-3.28	38.31	74.00	-35.69	Peak Detector

802.11n-HT40-Lowest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.92	-3.71	40.21	54.00	-14.09	Average Detector
	2310.000	54.98	-3.71	51.27	74.00	-22.93	Peak Detector
2	2390.000	46.52	-3.54	42.98	54.00	-11.02	Average Detector
	2390.000	69.13	-3.54	65.59	74.00	-8.41	Peak Detector
3	2400.000	Delta =35.54dBc		44.34	/	/	Average Detector
	2400.000	Delta =35.54dBc		68.23	/	/	Peak Detector
4	2412.000	87.02	-3.49	83.53	/	/	Average Detector
	2412.000	107.02	-3.49	103.53	/	/	Peak Detector

802.11n-HT40-Highest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2468.990	81.17	-3.37	77.80	/	/	Average Detector
	2467.660	92.12	-3.36	88.76	/	/	Peak Detector
2	2483.500	Delta = 37.53dBc		41.91	54.00	-12.09	Average Detector
	2483.500			52.87	74.00	-21.13	Peak Detector
3	2500.000	44.67	-3.20	41.47	54.00	-12.53	Average Detector
	2500.000	56.66	-3.20	53.46	74.00	-20.54	Peak Detector


10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram



10.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

10.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal

10.5 Summary of Test Results/Plots

According to the data in section 10.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:


-18.35 dB at 23.138 MHz in the Line mode, Average detector, 0.15-30MHz

10.6 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: *WIFI Module*
 Tested Model: *WC0FR2601*
 Operating Condition: *Transmitting(Wi-Fi)*
 Comment: *AC 120V/60Hz; Connected to PC*

Test Specification: *Neutral*



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1580	41.05	12.50	53.55	65.57	-12.02	peak
2	0.1580	23.91	12.50	36.41	55.57	-19.16	AVG
3	0.2380	38.31	12.50	50.81	62.17	-11.36	peak
4	0.2380	21.99	12.50	34.49	52.17	-17.68	AVG
5	0.5540	31.27	12.55	43.82	56.00	-12.18	peak
6	0.5540	17.04	12.55	29.59	46.00	-16.41	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.5700	35.75	12.57	48.32	56.00	-7.68	peak
2	0.5700	23.46	12.57	36.03	46.00	-9.97	AVG
3*	0.7900	37.24	12.79	50.03	56.00	-5.97	peak
4	0.8060	23.83	12.81	36.64	46.00	-9.36	AVG
5	1.9740	34.41	13.00	47.41	56.00	-8.59	peak
6	1.9740	19.86	13.00	32.86	46.00	-13.14	AVG

***** END OF REPORT *****