

# TEST REPORT

**Product Name:** WIFI+BT Module  
**Trade Mark:** GSD  
**Model No.:** WCT6LA2701  
**Report Number:** 170615002RFC-1  
**Test Standards:** FCC 47 CFR Part 15 Subpart C  
RSS-247 Issue 2  
RSS-Gen Issue 4  
**FCC ID:** 2AC23-WCT6LA2701  
**IC:** 12290A-WCT6LA2701  
**Test Result:** PASS  
**Date of Issue:** July 10, 2017


Prepared for:

**Hui Zhou Gaoshengda Technology Co.,LTD**  
**NO.75 Zhongkai Development Area, Huizhou, Guangdong, China**


Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
**16/F, Block A, Building 6, Baoneng Science and Technology Park,**  
**Qingxiang Road No.1, Longhua New District, Shenzhen, China**  
**TEL: +86-755-2823 0888**  
**FAX: +86-755-2823 0886**

Tested by:

  
Kevin Liang  
Senior Engineer

Reviewed by:

  
Jim Long  
Senior Supervisor

Approved by:

  
Billy Li  
Technical Director

Date:

July 10, 2017

**Version**

Version No.	Date	Description
V1.0	July 10, 2017	Original



## CONTENTS

<b>1. GENERAL INFORMATION</b>	<b>4</b>
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	5
1.5 DESCRIPTION OF SUPPORT UNITS	5
1.6 TEST LOCATION	5
1.7 TEST FACILITY	6
1.8 DEVIATION FROM STANDARDS	6
1.9 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.11 MEASUREMENT UNCERTAINTY	6
<b>2. TEST SUMMARY</b>	<b>7</b>
<b>3. EQUIPMENT LIST</b>	<b>8</b>
<b>4. TEST CONFIGURATION</b>	<b>9</b>
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	9
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	9
4.1.2 RECORD OF NORMAL ENVIRONMENT	9
4.2 TEST CHANNELS	9
4.3 EUT TEST STATUS	9
4.4 TEST SETUP	10
4.4.1 FOR RADIATED EMISSIONS TEST SETUP	10
4.4.2 FOR CONDUCTED EMISSIONS TEST SETUP	10
4.4.3 FOR CONDUCTED RF TEST SETUP	11
4.5 SYSTEM TEST CONFIGURATION	11
4.6 DUTY CYCLE	12
<b>5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION</b>	<b>13</b>
5.1 REFERENCE DOCUMENTS FOR TESTING	13
5.2 ANTENNA REQUIREMENT	13
5.3 CONDUCTED PEAK OUTPUT POWER	14
5.4 6 DB BANDWIDTH & OCCUPIED BANDWIDTH	15
5.5 POWER SPECTRAL DENSITY	18
5.6 CONDUCTED OUT OF BAND EMISSION	21
5.7 RADIATED SPURIOUS EMISSIONS	23
5.8 BAND EDGE MEASUREMENTS (RADIATED)	27
<b>APPENDIX 1 PHOTOGRAPHS OF TEST SETUP</b>	<b>30</b>
<b>APPENDIX 2 PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b>	<b>30</b>

## 1. GENERAL INFORMATION

### 1.1 CLIENT INFORMATION

<b>Applicant:</b>	Hui Zhou Gaoshengda Technology Co.,LTD
<b>Address of Applicant:</b>	NO.75 Zhongkai Development Area, Huizhou, Guangdong, China
<b>Manufacturer:</b>	Hui Zhou Gaoshengda Technology Co.,LTD
<b>Address of Manufacturer:</b>	NO.75 Zhongkai Development Area, Huizhou, Guangdong, China

### 1.2 EUT INFORMATION

#### 1.2.1 General Description of EUT

<b>Product Name:</b>	WIFI+BT Module		
<b>Model No.:</b>	WCT6LA2701		
<b>Add. Model No.:</b>	N/A		
<b>Trade Mark:</b>	GSD		
<b>DUT Stage:</b>	Identical Prototype		
<b>EUT Supports Function:</b>	2.4 GHz ISM Band:	IEEE 802.11b/g/n	
		Bluetooth: V3.0+EDR & V4.1 LE	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac
<b>Software Version:</b>	N/A		
<b>Hardware Version:</b>	94V-0		
<b>Sample Received Date:</b>	June 20, 2017		
<b>Sample Tested Date:</b>	June 20, 2017 to July 10, 2017		

#### 1.2.2 Description of Accessories

None.

### 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

<b>Frequency Range:</b>	2400 MHz to 2483.5 MHz
<b>Bluetooth Version:</b>	Bluetooth V4.1 LE
<b>Type of Modulation:</b>	GFSK
<b>Number of Channels:</b>	40
<b>Channel Separation:</b>	2 MHz
<b>Antenna Type:</b>	PIFA Antenna
<b>Antenna Gain:</b>	1.72 dBi
<b>Maximum Peak Power:</b>	0.5 dBm
<b>Normal Test Voltage:</b>	3.3 Vdc

### 1.4 OTHER INFORMATION

Operation Frequency Each of Channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402 MHz	10	2422 MHz	20	2442 MHz	30	2462 MHz
1	2404 MHz	11	2424 MHz	21	2444 MHz	31	2464 MHz
2	2406 MHz	12	2426 MHz	22	2446 MHz	32	2466 MHz
3	2408 MHz	13	2428 MHz	23	2448 MHz	33	2468 MHz
4	2410 MHz	14	2430 MHz	24	2450 MHz	34	2470 MHz
5	2412 MHz	15	2432 MHz	25	2452 MHz	35	2472 MHz
6	2414 MHz	16	2434 MHz	26	2454 MHz	36	2474 MHz
7	2416 MHz	17	2436 MHz	27	2456 MHz	37	2476 MHz
8	2418 MHz	18	2438 MHz	28	2458 MHz	38	2478 MHz
9	2420 MHz	19	2440 MHz	29	2460 MHz	39	2480 MHz

### 1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	Lenovo	E450	SL10G10780	UnionTrust
--	--	--	--	--

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable * 2	SMA	0.30 Meter	UnionTrust
2	USB Cable	USB	0.80 Meter	UnionTrust

### 1.6 TEST LOCATION

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109  
 Telephone: +86 (0) 755 2823 0888  
 Fax: +86 (0) 755 2823 0886

Tests were sub-contracted.

**Compliance Certification Services (Shenzhen) Inc.**

Address: No.10-1 Mingkeda Logistics Park, No.18 Huanguan South RD. Guan lan Town, Baoan Distr, Shenzhen, Guangdong, China.  
 Telephone: +86 (0) 755 28055000      Fax: +86 (0) 755 29055221

## 1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

**CNAS-Lab Code: L9069**

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

**IC-Registration No.: 21600-1**

The 3m Semi-anechoic chamber of Shenzhen UnionTrust Quality and Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 21600-1.

**A2LA-Lab Certificate No.: 4312.01**

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

**Compliance Certification Services (Shenzhen) Inc.**

FCC Registration Number is 441872.  
IC Registration Number is 23241-2.

## 1.8 DEVIATION FROM STANDARDS

None.

## 1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

## 1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

## 1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.2878 dB
2	Conducted emission 150KHz-30MHz	±3.2878 dB
3	Radiated emission 30MHz-200Hz	±3.8928 dB
4	Radiated emission 200MHz-1GHz	±3.8753 dB
5	Radiated emission 1GHz-8GHz	±5.3112 dB
6	Radiated emission Above 8GHz	±5.3493 dB



## 2. TEST SUMMARY

Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203/15.247 (c) RSS-Gen Issue 4, Section 8.3	ANSI C63.10-2013	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart C Section 15.207 RSS-Gen Issue 4, Section 8.8	ANSI C63.10-2013	N/A <sup>NOTE 2</sup>
Conducted Peak Output Power	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3) RSS-247 Issue 2, Section 5.4(d)	KDB 558074 D01 v04, Section 9.1.3	PASS
6dB Bandwidth	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2) RSS-247 Issue 2, Section 5.2(a)	KDB 558074 D01 v04, Section 8.1	PASS
Occupied Bandwidth	RSS-Gen section 6.6	RSS-Gen section 6.6	PASS
Power Spectral Density	FCC 47 CFR Part 15 Subpart C Section 15.247 (e) RSS-247 Issue 2, Section 5.2(b)	KDB 558074 D01 v04, Section 10.2	PASS
Conducted Out of Band Emission	FCC 47 CFR Part 15 Subpart C Section 15.247(d) RSS-247 Issue 2, Section 5.5	KDB 558074 D01 v04, Section 11	PASS
Radiated Spurious Emissions	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209 RSS-Gen Issue 4, Section 6.13/8.9/8.10	KDB 558074 D01 v04, Section 12.1	PASS*
Band Edge Measurements (Radiated)	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209 RSS-247 Issue 2, Section 5.5	KDB 558074 D01 v04, Section 12.1	PASS*
<b>Note:</b> 1) N/A: In this whole report not application. 2) This EUT is powered by DC. 3) “*”: In this whole report “*” means tests were sub-contracted Item.			

### 3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
<input checked="" type="checkbox"/>	PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	Feb. 17, 2017	Feb. 16, 2018
<input checked="" type="checkbox"/>	High Noise Amplifier	Agilent	8449B	3008A01838	Feb. 11, 2017	Feb. 10, 2018
<input checked="" type="checkbox"/>	Amplifier	HP	8447D	2944A08999	Feb. 12, 2017	Feb. 11, 2018
<input checked="" type="checkbox"/>	Antenna	SCHAFFNER	CBL6143	5082	Feb. 12, 2017	Feb. 11, 2018
<input checked="" type="checkbox"/>	Horn Antenna	SCHWARZBEC K	BBHA9120	D286	Feb. 12, 2017	Feb. 11, 2018
<input checked="" type="checkbox"/>	Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	Feb. 11, 2017	Feb. 10, 2018
<input checked="" type="checkbox"/>	Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
<input checked="" type="checkbox"/>	Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
<input checked="" type="checkbox"/>	Controller	CT	N/A	N/A	N.C.R	N.C.R
<input checked="" type="checkbox"/>	Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
<input checked="" type="checkbox"/>	Temp. / Humidity Meter	Anymetre	JR913	N/A	Feb. 15, 2017	Feb. 14, 2018

Conducted RF test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
<input checked="" type="checkbox"/>	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Dec. 22, 2016	Dec. 22, 2017
<input type="checkbox"/>	Receiver	R&S	ESR7	1316.3003K07 -101181-K3	Dec. 22, 2016	Dec. 22, 2017
<input checked="" type="checkbox"/>	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	Dec. 22, 2016	Dec. 22, 2017
<input type="checkbox"/>	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430023	Dec. 22, 2016	Dec. 22, 2017



## 4. TEST CONFIGURATION

### 4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

#### 4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	3.3	20 to 75
<b>Remark:</b>			
1) NV: Normal Voltage; NT: Normal Temperature			

#### 4.1.2 Record of Normal Environment

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (Kpa)	Tested by
AC Power Line Conducted Emission	N/A	N/A	N/A	N/A
Conducted Peak Output Power	24.7	49	100.3	Tiny You
6dB Bandwidth & Occupied Bandwidth	25.5	46	100.2	Tiny You
Power Spectral Density	25.5	46	100.2	Tiny You
Conducted Out of Band Emission	25.5	46	100.2	Tiny You
Radiated Spurious Emissions	25.2	53	99.94	Tiny You
Band Edge Measurements (Radiated)	25.2	54	99.94	Tiny You

## 4.2 TEST CHANNELS




Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

## 4.3 EUT TEST STATUS


Type of Modulation	Tx/Rx Function	Description
GFSK	1Tx/1Rx	1. Keep the EUT in continuously transmitting or receiving with modulation test single.

### 4.4 TEST SETUP


#### 4.4.1 For Radiated Emissions test setup



#### 4.4.2 For Conducted Emissions test setup



4.4.3 For Conducted RF test setup



4.5 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by a 3.3Vdc. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in (see table below) orientation.

Frequency	Mode	Antenna Port	Worst-case axis positioning
Above 1GHz	1TX	Chain 0	Z axis

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.


### 4.6 DUTY CYCLE

Type of Modulation	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)	Average Factor (dB)
GFSK	0.405	0.624	0.65	64.90	1.88	2.47	-3.75

**Remark:**

- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor = 10 \* log(1/ Duty cycle);
- 3) Average factor = 20 log<sub>10</sub> Duty Cycle.

The test plot as follows



## 5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

### 5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	RSS-247 Issue 2	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
4	RSS-Gen Issue 4	General Requirements for Compliance of Radio Apparatus
5	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
6	KDB 558074 D01 DTS Meas Guidance v04	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

### 5.2 ANTENNA REQUIREMENT

Standard Requirement
<p><b>15.203 requirement:</b> An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>
<p><b>15.247(b) (4) requirement:</b> The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>
<p><b>RSS-Gen Issue 4, Section 8.3 requirement:</b> According to RSS-Gen Issue 4, section 8.3, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns.</p>
<p><b>EUT Antenna:</b> Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is 1.72 dBi.</p>

### 5.3 CONDUCTED PEAK OUTPUT POWER

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3)  
 RSS-247 Issue 2, Section 5.4(d)

**Test Method:** KDB 558074 D01 v04, Section 9.1.3

**Limit:** For DTSs employing digital modulation techniques operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W

**Test Procedure:**

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter.
2. Measure out each test modes' peak output power, record the power level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

**Test Setup:** Refer to section 4.4.3 for details.

**Instruments Used:** Refer to section 3 for details

**Test Mode:** Transmitter mode

**Test Results:** Pass

**Test Data:**

**For maximum peak conducted output power**

Type of Modulation	Channel	Frequency (MHz)	Maximum peak conducted power (dBm)	Maximum peak conducted power (mW)	Limit (mW)	Pass/Fail
GFSK	0	2402	-0.2	0.95	1000	Pass
	19	2440	0.3	1.07	1000	Pass
	39	2480	<b>0.5</b>	<b>1.12</b>	1000	Pass

Note: The antenna gain of 1.72 dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.

**For maximum e.i.r.p.**

Type of Modulation	Channel	Frequency (MHz)	e.i.r.p. (dBm)	e.i.r.p. (mW)	Limit (mW)	Pass/Fail
GFSK	0	2402	1.52	1.42	4000	Pass
	19	2440	2.02	1.59	4000	Pass
	39	2480	<b>2.22</b>	<b>1.67</b>	4000	Pass

Note: e.i.r.p = maximum peak conducted output power + antenna gain



### 5.46 DB BANDWIDTH & OCCUPIED BANDWIDTH

FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2)

**Test Requirement:** RSS-247 Issue 2, Section 5.2(a)  
RSS-Gen Issue 4, Section 6.6

**Test Method:** KDB 558074 D01 v04, Section 8.1

**Limit:** For digital transmission systems, the minimum 6 dB bandwidth shall be 500 kHz.

**Test Procedure:** Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.  
Use the following spectrum analyzer settings:  
a) Set RBW = 100 kHz.  
b) Set the video bandwidth (VBW) ≥ 3 x RBW.  
c) Detector = Peak.  
d) Trace mode = max hold.  
e) Sweep = auto couple.  
f) Allow the trace to stabilize.  
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

**Test Setup:** Refer to section 4.4.3 for details.

**Instruments Used:** Refer to section 3 for details



**Test Mode:** Transmitter mode


**Test Results:** Pass

**Test Data:**

Type of Modulation	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Occupied Bandwidth (MHz)	6 dB Bandwidth Limit	Pass / Fail
GFSK	0	2402	0.6756	1.0945	> 500 kHz	Pass
	19	2440	0.6828	1.0938	> 500 kHz	Pass
	39	2480	0.6806	1.0941	> 500 kHz	Pass

The test plot as follows:





### 5.5 POWER SPECTRAL DENSITY

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.247 (e)  
 RSS-247 Issue 2, Section 5.2(b)

**Test Method:** KDB 558074 D01 v04, Section 10.2

**Limit:** For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

**Test Procedure:** Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.  
 Use the following spectrum analyzer settings:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

**Test Setup:** Refer to section 4.4.3 for details.

**Instruments Used:** Refer to section 3 for details



**Test Mode:** Transmitter mode


**Test Results:** Pass

**Test Data:**

Type of Modulation	Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Result (Pass / Fail)
GFSK	0	2402	-14.565	8	Pass
	19	2440	-14.153	8	Pass
	39	2480	-14.070	8	Pass

The test plot as follows:










## 5.6 CONDUCTED OUT OF BAND EMISSION

<b>Test Requirement:</b>	FCC 47 CFR Part 15 Subpart C Section 15.247(d) RSS-247 Issue 2, Section 5.5
<b>Test Method:</b>	KDB 558074 D01 v04, Section 11
<b>Limit:</b>	In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.
<b>Test Procedure:</b>	<p>Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.</p> <p>Use the following spectrum analyzer settings:</p> <p><b>Step 1: Reference level measurement</b></p> <ol style="list-style-type: none"> <li>a) Set instrument center frequency to DTS channel center frequency.</li> <li>b) Set the span to <math>\geq 1.5</math> times the DTS bandwidth.</li> <li>c) Set the RBW = 100 kHz.</li> <li>d) Set the VBW <math>\geq 3 \times</math> RBW.</li> <li>e) Detector = peak.</li> <li>f) Sweep time = auto couple.</li> <li>g) Trace mode = max hold.</li> <li>h) Allow trace to fully stabilize.</li> <li>i) Use the peak marker function to determine the maximum PSD level.</li> </ol> <p>Note that the channel found to contain the maximum PSD level can be used to establish the reference level.</p> <p><b>Step 2: Emission level measurement</b></p> <ol style="list-style-type: none"> <li>a) Set RBW = 1 MHz.</li> <li>b) Set VBW <math>\geq 3</math> MHz.</li> <li>c) Detector = peak.</li> <li>d) Sweep = auto couple.</li> <li>e) Trace Mode = max hold.</li> <li>f) Allow trace to fully stabilize.</li> <li>g) Use the peak marker function to determine the maximum amplitude level.</li> </ol> <p>Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.</p>
<b>Test Setup:</b>	Refer to section 4.4.3 for details.
<b>Instruments Used:</b>	Refer to section 3 for details
<b>Test Mode:</b>	Transmitter mode
<b>Test Results:</b>	Pass
<b>Test Data:</b>	

The test plot as follows:



### 5.7 RADIATED SPURIOUS EMISSIONS

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.205/15.209  
 RSS-Gen Issue 4, Section 6.13/8.9/8.10  
**Test Method:** KDB 558074 D01 v04, Section 12.1

**Receiver Setup:**

Frequency	Detector	RBW	VBW	Remark
0.009 MHz-0.090 MHz	Peak	10 kHz	30 KHz	Peak
0.009 MHz-0.090 MHz	Average	10 kHz	30 KHz	Average
0.090 MHz-0.110 MHz	Quasi-peak	10 kHz	30 KHz	Quasi-peak
0.110 MHz-0.490 MHz	Peak	10 kHz	30 KHz	Peak
0.110 MHz-0.490 MHz	Average	10 kHz	30 KHz	Average
0.490 MHz -30 MHz	Quasi-peak	10 kHz	30 kHz	Quasi-peak
30 MHz-1 GHz	Quasi-peak	100 kHz	300 KHz	Quasi-peak
Above 1 GHz	Peak	1 MHz	3 MHz	Peak
	Peak	1 MHz	10 Hz	Average

**Limits:**

**Spurious Emissions**

Frequency	Field strength (microvolt/meter)	Limit (dBµV/m )	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

**Remark:**

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

**Test Setup:** Refer to section 4.4.1 for details.

**Test Procedures:**

- From 30 MHz to 1GHz test procedure as below:
  - The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
  - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
  - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
  - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
  - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
  - If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and

then reported in a data sheet.

2. Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter( Above 18GHz the distance is 1 meter and table is 1.5 meter).
- 2) Test the EUT in the lowest channel ,middle channel, the Highest channel
- 3) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the Z axis positioning which it is worse case.
- 4) Repeat above procedures until all frequencies measured was complete.

**Equipment Used:** Refer to section 3 for details.

**Test Result:** Pass

**The measurement data as follows:**


**Radiated Emission Test Data (9 KHz ~ 30 MHz):**

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value need not be reported.


**Radiated Emission Test Data (30 MHz ~ 1 GHz):**

**Highest Channel**

**Horizontal**



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	94.979	41.31	-18.31	23.00	43.50	-20.50	QP
2	201.454	45.18	-15.44	29.74	43.50	-13.76	QP
3	288.284	46.04	-11.54	34.50	46.00	-11.50	QP
4	338.855	42.66	-10.12	32.54	46.00	-13.46	QP
5	409.651	38.51	-8.24	30.27	46.00	-15.73	QP
6*	689.051	27.63	-2.62	25.01	46.00	-20.99	QP



Radiated Emission Test Data (Above 1GHz):						
Lowest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polaxis	Remark
1	4804.00	43.13	74.00	-30.87	Peak	Horizontal
2	7206.00	45.31	74.00	-28.69	Peak	Horizontal
3	4804.00	40.02	74.00	-33.98	Peak	Vertical
4	7206.00	44.80	74.00	-29.20	Peak	Vertical

Middle Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polaxis	Remark
1	4880.00	41.28	74.00	-32.72	Peak	Horizontal
2	7320.00	45.90	74.00	-28.10	Peak	Horizontal
3	4880.00	38.91	74.00	-35.09	Peak	Vertical
4	7320.00	43.77	74.00	-30.23	Peak	Vertical

Highest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polaxis	Remark
1	4960.00	41.93	74.00	-32.07	Peak	Horizontal
2	7440.00	45.48	74.00	-28.52	Peak	Horizontal
3	4960.00	41.00	74.00	-33.00	Peak	Vertical
4	7440.00	44.16	74.00	-29.84	Peak	Vertical

**Remark:**

As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.



### 5.8 BAND EDGE MEASUREMENTS (RADIATED)

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.205/15.209  
 RSS-247 Issue 2, Section 5.5  
**Test Method:** KDB 558074 D01 v04, Section 12.1

**Limits:**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Frequency	Limit (dBµV/m @3m)	Remark
30 MHz-88 MHz	40.0	Quasi-peak Value
88 MHz-216 MHz	43.5	Quasi-peak Value
216 MHz-960 MHz	46.0	Quasi-peak Value
960 MHz-1 GHz	54.0	Quasi-peak Value
Above 1 GHz	54.0	Average Value
	74.0	Peak Value

**Test Setup:** Refer to section 4.4.1 for details.

**Test Procedures:**



Radiated band edge measurements at 2390 MHz and 2483.5 MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).



1. Use radiated spurious emission test procedure described in clause 5.10. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.

**Equipment Used:** Refer to section 3 for details.

**Test Result:** Pass

**The measurement data as follows:**





## APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

See test photographs attached in Appendix 1 for the actual connections between Product and support equipment.

## APPENDIX 2 PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photographs.

\*\*\* End of Report \*\*\*

---

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---