



Test Mode:	802.11n HT20	Frequency(MHz):	5700
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9189.000	37.38	10.46	47.84	74.00	-26.16	peak
2	11015.000	34.04	14.79	48.83	74.00	-25.17	peak
3	11785.000	32.15	17.30	49.45	74.00	-24.55	peak
4	12236.000	32.41	17.76	50.17	74.00	-23.83	peak
5	14172.000	28.69	21.16	49.85	74.00	-24.15	peak
6	17945.000	24.17	25.75	49.92	74.00	-24.08	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5720
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9310.000	37.65	10.54	48.19	74.00	-25.81	peak
2	10234.000	36.62	12.26	48.88	74.00	-25.12	peak
3	11070.000	34.23	15.01	49.24	74.00	-24.76	peak
4	12247.000	32.23	17.77	50.00	74.00	-24.00	peak
5	13919.000	28.98	21.68	50.66	74.00	-23.34	peak
6	17923.000	24.76	25.60	50.36	74.00	-23.64	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5720
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9189.000	38.11	10.46	48.57	74.00	-25.43	peak
2	10784.000	35.25	13.91	49.16	74.00	-24.84	peak
3	11730.000	33.54	17.19	50.73	74.00	-23.27	peak
4	12753.000	32.12	18.14	50.26	74.00	-23.74	peak
5	13919.000	28.67	21.68	50.35	74.00	-23.65	peak
6	17978.000	24.36	25.97	50.33	74.00	-23.67	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9112.000	38.17	10.41	48.58	74.00	-25.42	peak
2	11246.000	34.06	15.73	49.79	74.00	-24.21	peak
3	11455.000	33.65	16.58	50.23	74.00	-23.77	peak
4	12588.000	32.12	17.94	50.06	74.00	-23.94	peak
5	13600.000	29.49	20.89	50.38	74.00	-23.62	peak
6	17989.000	24.56	26.04	50.60	74.00	-23.40	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	37.20	9.90	47.10	74.00	-26.90	peak
2	11004.000	34.56	14.74	49.30	74.00	-24.70	peak
3	11840.000	32.18	17.40	49.58	74.00	-24.42	peak
4	12577.000	32.45	17.93	50.38	74.00	-23.62	peak
5	13919.000	28.67	21.68	50.35	74.00	-23.65	peak
6	17857.000	25.16	25.14	50.30	74.00	-23.70	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9189.000	37.44	10.46	47.90	74.00	-26.10	peak
2	10212.000	36.60	12.21	48.81	74.00	-25.19	peak
3	11048.000	34.71	14.91	49.62	74.00	-24.38	peak
4	11697.000	32.82	17.13	49.95	74.00	-24.05	peak
5	13512.000	29.76	20.68	50.44	74.00	-23.56	peak
6	17923.000	25.01	25.60	50.61	74.00	-23.39	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8595.000	40.78	7.54	48.32	74.00	-25.68	peak
2	9189.000	37.87	10.46	48.33	74.00	-25.67	peak
3	11213.000	34.73	15.59	50.32	74.00	-23.68	peak
4	13149.000	31.66	19.10	50.76	74.00	-23.24	peak
5	13963.000	28.78	21.78	50.56	74.00	-23.44	peak
6	17923.000	24.91	25.60	50.51	74.00	-23.49	peak


Test Mode:	802.11n HT20	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9255.000	36.94	10.51	47.45	74.00	-26.55	peak
2	9827.000	36.40	11.39	47.79	74.00	-26.21	peak
3	11268.000	33.37	15.83	49.20	74.00	-24.80	peak
4	12709.000	30.79	18.09	48.88	74.00	-25.12	peak
5	13897.000	28.20	21.62	49.82	74.00	-24.18	peak
6	17989.000	24.28	26.04	50.32	74.00	-23.68	peak




Test Mode:	802.11n HT20	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9343.000	37.58	10.55	48.13	74.00	-25.87	peak
2	11048.000	34.25	14.91	49.16	74.00	-24.84	peak
3	11785.000	32.68	17.30	49.98	74.00	-24.02	peak
4	12742.000	32.25	18.13	50.38	74.00	-23.62	peak
5	13963.000	28.15	21.78	49.93	74.00	-24.07	peak
6	17956.000	24.64	25.82	50.46	74.00	-23.54	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	37.95	6.64	44.59	74.00	-29.41	peak
2	8936.000	37.75	9.90	47.65	74.00	-26.35	peak
3	11026.000	34.16	14.82	48.98	74.00	-25.02	peak
4	12258.000	32.03	17.77	49.80	74.00	-24.20	peak
5	13600.000	29.73	20.89	50.62	74.00	-23.38	peak
6	17978.000	24.43	25.97	50.40	74.00	-23.60	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5190
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9134.000	37.24	10.41	47.65	74.00	-26.35	peak
2	10388.000	36.61	12.59	49.20	74.00	-24.80	peak
3	11422.000	32.98	16.46	49.44	74.00	-24.56	peak
4	12269.000	32.10	17.77	49.87	74.00	-24.13	peak
5	13127.000	30.54	19.01	49.55	74.00	-24.45	peak
6	18000.000	23.96	26.12	50.08	74.00	-23.92	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8947.000	37.25	9.98	47.23	74.00	-26.77	peak
2	10333.000	35.36	12.47	47.83	74.00	-26.17	peak
3	11059.000	33.83	14.96	48.79	74.00	-25.21	peak
4	12269.000	31.72	17.77	49.49	74.00	-24.51	peak
5	13116.000	30.31	18.96	49.27	74.00	-24.73	peak
6	17934.000	24.07	25.67	49.74	74.00	-24.26	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5230
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9189.000	37.23	10.46	47.69	74.00	-26.31	peak
2	10388.000	36.17	12.59	48.76	74.00	-25.24	peak
3	10916.000	34.90	14.39	49.29	74.00	-24.71	peak
4	12632.000	32.02	17.99	50.01	74.00	-23.99	peak
5	13644.000	29.25	20.99	50.24	74.00	-23.76	peak
6	17934.000	24.34	25.67	50.01	74.00	-23.99	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5270
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9134.000	38.09	10.41	48.50	74.00	-25.50	peak
2	10289.000	36.37	12.38	48.75	74.00	-25.25	peak
3	11884.000	32.28	17.48	49.76	74.00	-24.24	peak
4	12687.000	31.96	18.05	50.01	74.00	-23.99	peak
5	13138.000	30.22	19.05	49.27	74.00	-24.73	peak
6	17923.000	23.43	25.60	49.03	74.00	-24.97	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5270
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9662.000	36.34	11.01	47.35	74.00	-26.65	peak
2	10861.000	35.25	14.20	49.45	74.00	-24.55	peak
3	11719.000	32.73	17.18	49.91	74.00	-24.09	peak
4	12610.000	31.53	17.97	49.50	74.00	-24.50	peak
5	13985.000	27.73	21.85	49.58	74.00	-24.42	peak
6	18000.000	23.34	26.12	49.46	74.00	-24.54	peak


Test Mode:	802.11n HT40	Frequency(MHz):	5310
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9310.000	37.28	10.54	47.82	74.00	-26.18	peak
2	10608.000	37.66	13.23	50.89	74.00	-23.11	peak
3	11653.000	32.78	17.05	49.83	74.00	-24.17	peak
4	12621.000	31.57	17.98	49.55	74.00	-24.45	peak
5	14062.000	27.81	21.62	49.43	74.00	-24.57	peak
6	17670.000	25.10	23.86	48.96	74.00	-25.04	peak




Test Mode:	802.11n HT40	Frequency(MHz):	5310
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9574.000	36.98	10.81	47.79	74.00	-26.21	peak
2	11070.000	34.04	15.01	49.05	74.00	-24.95	peak
3	11576.000	32.21	16.91	49.12	74.00	-24.88	peak
4	12698.000	31.07	18.08	49.15	74.00	-24.85	peak
5	13919.000	27.49	21.68	49.17	74.00	-24.83	peak
6	17956.000	22.50	25.82	48.32	74.00	-25.68	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5510
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9354.000	38.10	10.56	48.66	74.00	-25.34	peak
2	10234.000	36.22	12.26	48.48	74.00	-25.52	peak
3	11785.000	32.27	17.30	49.57	74.00	-24.43	peak
4	13182.000	30.65	19.24	49.89	74.00	-24.11	peak
5	13919.000	28.72	21.68	50.40	74.00	-23.60	peak
6	17956.000	24.66	25.82	50.48	74.00	-23.52	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5510
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8903.000	38.17	9.66	47.83	74.00	-26.17	peak
2	9255.000	37.58	10.51	48.09	74.00	-25.91	peak
3	11015.000	41.46	14.79	56.25	74.00	-17.75	peak
4	11015.000	30.83	14.79	45.62	54.00	-8.38	AVG
5	12654.000	31.51	18.01	49.52	74.00	-24.48	peak
6	13402.000	29.43	20.20	49.63	74.00	-24.37	peak
7	17989.000	23.60	26.04	49.64	74.00	-24.36	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5550
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8925.000	37.37	9.82	47.19	74.00	-26.81	peak
2	10344.000	35.56	12.49	48.05	74.00	-25.95	peak
3	11521.000	32.94	16.82	49.76	74.00	-24.24	peak
4	12764.000	32.07	18.16	50.23	74.00	-23.77	peak
5	13996.000	28.45	21.87	50.32	74.00	-23.68	peak
6	17956.000	25.18	25.82	51.00	74.00	-23.00	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5550
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9343.000	38.09	10.55	48.64	74.00	-25.36	peak
2	11081.000	34.62	15.05	49.67	74.00	-24.33	peak
3	11532.000	33.27	16.83	50.10	74.00	-23.90	peak
4	12632.000	31.92	17.99	49.91	74.00	-24.09	peak
5	13864.000	28.70	21.53	50.23	74.00	-23.77	peak
6	17934.000	24.30	25.67	49.97	74.00	-24.03	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5670
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9354.000	37.41	10.56	47.97	74.00	-26.03	peak
2	11059.000	34.94	14.96	49.90	74.00	-24.10	peak
3	11906.000	32.24	17.52	49.76	74.00	-24.24	peak
4	13116.000	30.94	18.96	49.90	74.00	-24.10	peak
5	14007.000	28.25	21.85	50.10	74.00	-23.90	peak
6	17989.000	24.02	26.04	50.06	74.00	-23.94	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5670
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9189.000	37.45	10.46	47.91	74.00	-26.09	peak
2	10894.000	35.32	14.32	49.64	74.00	-24.36	peak
3	11345.000	34.27	16.14	50.41	74.00	-23.59	peak
4	11862.000	33.04	17.45	50.49	74.00	-23.51	peak
5	13875.000	28.53	21.57	50.10	74.00	-23.90	peak
6	17967.000	24.29	25.89	50.18	74.00	-23.82	peak


Test Mode:	802.11n HT40	Frequency(MHz):	5710
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9134.000	37.37	10.41	47.78	74.00	-26.22	peak
2	10465.000	35.52	12.75	48.27	74.00	-25.73	peak
3	11741.000	32.72	17.22	49.94	74.00	-24.06	peak
4	12621.000	32.73	17.98	50.71	74.00	-23.29	peak
5	14029.000	28.84	21.76	50.60	74.00	-23.40	peak
6	17934.000	24.34	25.67	50.01	74.00	-23.99	peak




Test Mode:	802.11n HT40	Frequency(MHz):	5710
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9244.000	37.82	10.49	48.31	74.00	-25.69	peak
2	10300.000	35.51	12.40	47.91	74.00	-26.09	peak
3	11862.000	33.30	17.45	50.75	74.00	-23.25	peak
4	12632.000	32.90	17.99	50.89	74.00	-23.11	peak
5	13864.000	28.55	21.53	50.08	74.00	-23.92	peak
6	18000.000	24.33	26.12	50.45	74.00	-23.55	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9123.000	37.85	10.42	48.27	74.00	-25.73	peak
2	11059.000	34.48	14.96	49.44	74.00	-24.56	peak
3	11785.000	33.16	17.30	50.46	74.00	-23.54	peak
4	12313.000	32.42	17.78	50.20	74.00	-23.80	peak
5	13589.000	29.14	20.86	50.00	74.00	-24.00	peak
6	17989.000	24.02	26.04	50.06	74.00	-23.94	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5755
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9189.000	37.94	10.46	48.40	74.00	-25.60	peak
2	10806.000	35.27	13.98	49.25	74.00	-24.75	peak
3	11521.000	33.04	16.82	49.86	74.00	-24.14	peak
4	12676.000	31.87	18.05	49.92	74.00	-24.08	peak
5	13611.000	29.27	20.92	50.19	74.00	-23.81	peak
6	17934.000	24.41	25.67	50.08	74.00	-23.92	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5795
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9068.000	37.47	10.39	47.86	74.00	-26.14	peak
2	10245.000	35.85	12.28	48.13	74.00	-25.87	peak
3	10828.000	35.17	14.07	49.24	74.00	-24.76	peak
4	12665.000	31.61	18.04	49.65	74.00	-24.35	peak
5	13633.000	28.66	20.97	49.63	74.00	-24.37	peak
6	17978.000	23.53	25.97	49.50	74.00	-24.50	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5795
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8727.000	38.84	8.45	47.29	74.00	-26.71	peak
2	9200.000	37.19	10.46	47.65	74.00	-26.35	peak
3	11059.000	34.96	14.96	49.92	74.00	-24.08	peak
4	12511.000	32.74	17.84	50.58	74.00	-23.42	peak
5	13050.000	31.51	18.66	50.17	74.00	-23.83	peak
6	17945.000	24.98	25.75	50.73	74.00	-23.27	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9112.000	37.76	10.41	48.17	74.00	-25.83	peak
2	11081.000	33.58	15.05	48.63	74.00	-25.37	peak
3	11598.000	32.21	16.96	49.17	74.00	-24.83	peak
4	12720.000	31.63	18.09	49.72	74.00	-24.28	peak
5	14139.000	28.12	21.30	49.42	74.00	-24.58	peak
6	18000.000	23.23	26.12	49.35	74.00	-24.65	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5210
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9244.000	38.37	10.49	48.86	74.00	-25.14	peak
2	10443.000	36.63	12.70	49.33	74.00	-24.67	peak
3	12236.000	32.40	17.76	50.16	74.00	-23.84	peak
4	13347.000	30.29	19.97	50.26	74.00	-23.74	peak
5	13853.000	28.71	21.52	50.23	74.00	-23.77	peak
6	17934.000	24.78	25.67	50.45	74.00	-23.55	peak


Test Mode:	802.11ac VHT80	Frequency(MHz):	5290
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9365.000	37.59	10.57	48.16	74.00	-25.84	peak
2	10861.000	35.51	14.20	49.71	74.00	-24.29	peak
3	11873.000	32.54	17.46	50.00	74.00	-24.00	peak
4	12698.000	32.94	18.08	51.02	74.00	-22.98	peak
5	13919.000	28.98	21.68	50.66	74.00	-23.34	peak
6	17934.000	24.78	25.67	50.45	74.00	-23.55	peak




Test Mode:	802.11ac VHT80	Frequency(MHz):	5290
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9563.000	37.48	10.79	48.27	74.00	-25.73	peak
2	10597.000	35.54	13.19	48.73	74.00	-25.27	peak
3	11455.000	33.04	16.58	49.62	74.00	-24.38	peak
4	12687.000	32.36	18.05	50.41	74.00	-23.59	peak
5	13974.000	28.27	21.82	50.09	74.00	-23.91	peak
6	17967.000	24.44	25.89	50.33	74.00	-23.67	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5530
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9343.000	37.05	10.55	47.60	74.00	-26.40	peak
2	10960.000	35.06	14.57	49.63	74.00	-24.37	peak
3	12687.000	32.22	18.05	50.27	74.00	-23.73	peak
4	13127.000	31.53	19.01	50.54	74.00	-23.46	peak
5	13996.000	28.44	21.87	50.31	74.00	-23.69	peak
6	17923.000	24.24	25.60	49.84	74.00	-24.16	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5530
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9266.000	37.69	10.51	48.20	74.00	-25.80	peak
2	10344.000	35.95	12.49	48.44	74.00	-25.56	peak
3	11070.000	34.54	15.01	49.55	74.00	-24.45	peak
4	12687.000	31.74	18.05	49.79	74.00	-24.21	peak
5	13435.000	29.51	20.35	49.86	74.00	-24.14	peak
6	18000.000	23.20	26.12	49.32	74.00	-24.68	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5610
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9112.000	37.45	10.41	47.86	74.00	-26.14	peak
2	10861.000	35.22	14.20	49.42	74.00	-24.58	peak
3	11741.000	33.12	17.22	50.34	74.00	-23.66	peak
4	12709.000	31.77	18.09	49.86	74.00	-24.14	peak
5	13446.000	29.67	20.41	50.08	74.00	-23.92	peak
6	17934.000	24.20	25.67	49.87	74.00	-24.13	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5610
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9134.000	37.37	10.41	47.78	74.00	-26.22	peak
2	11059.000	34.41	14.96	49.37	74.00	-24.63	peak
3	11532.000	32.87	16.83	49.70	74.00	-24.30	peak
4	12258.000	32.85	17.77	50.62	74.00	-23.38	peak
5	13908.000	29.17	21.66	50.83	74.00	-23.17	peak
6	17989.000	24.54	26.04	50.58	74.00	-23.42	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5690
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8859.000	38.30	9.36	47.66	74.00	-26.34	peak
2	10333.000	35.81	12.47	48.28	74.00	-25.72	peak
3	10938.000	34.34	14.48	48.82	74.00	-25.18	peak
4	11818.000	30.94	17.36	48.30	74.00	-25.70	peak
5	13589.000	28.34	20.86	49.20	74.00	-24.80	peak
6	17989.000	23.63	26.04	49.67	74.00	-24.33	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5690
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9189.000	36.96	10.46	47.42	74.00	-26.58	peak
2	10157.000	35.12	12.10	47.22	74.00	-26.78	peak
3	11048.000	34.25	14.91	49.16	74.00	-24.84	peak
4	11917.000	31.38	17.54	48.92	74.00	-25.08	peak
5	13919.000	28.69	21.68	50.37	74.00	-23.63	peak
6	17912.000	24.54	25.52	50.06	74.00	-23.94	peak


Test Mode:	802.11ac VHT80	Frequency(MHz):	5775
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	37.13	9.90	47.03	74.00	-26.97	peak
2	10212.000	35.57	12.21	47.78	74.00	-26.22	peak
3	11059.000	34.39	14.96	49.35	74.00	-24.65	peak
4	12709.000	31.48	18.09	49.57	74.00	-24.43	peak
5	14128.000	27.08	21.34	48.42	74.00	-25.58	peak
6	17934.000	24.13	25.67	49.80	74.00	-24.20	peak




Test Mode:	802.11ac VHT80	Frequency(MHz):	5775
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9178.000	38.22	10.45	48.67	74.00	-25.33	peak
2	10223.000	36.02	12.24	48.26	74.00	-25.74	peak
3	11048.000	33.89	14.91	48.80	74.00	-25.20	peak
4	12676.000	32.07	18.05	50.12	74.00	-23.88	peak
5	13798.000	28.83	21.38	50.21	74.00	-23.79	peak
6	17989.000	24.51	26.04	50.55	74.00	-23.45	peak


### 8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

Test Mode:	802.11a20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0100	77.72	-101.40	-23.68	47.60	-71.28	peak
2	0.0160	71.97	-101.37	-29.40	43.52	-72.92	peak
3	0.0221	70.63	-101.35	-30.72	40.71	-71.43	peak
4	0.0349	65.53	-101.41	-35.88	36.75	-72.63	peak
5	0.0551	61.95	-101.50	-39.55	32.78	-72.33	peak
6	0.0806	60.18	-101.63	-41.45	29.47	-70.92	peak

Test Mode:	802.11a20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1621	77.42	-101.65	-24.23	23.41	-47.64	peak
2	0.1794	75.27	-101.68	-26.41	22.53	-48.94	peak
3	0.2053	70.29	-101.73	-31.44	21.35	-52.79	peak
4	0.2472	66.95	-101.80	-34.85	19.74	-54.59	peak
5	0.3163	63.70	-101.87	-38.17	17.60	-55.77	peak
6	0.3573	61.08	-101.91	-40.83	16.54	-57.37	peak


Test Mode:	802.11a20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5039	65.93	-62.07	3.86	33.56	-29.70	peak
2	0.5917	65.74	-62.08	3.66	32.16	-28.50	peak
3	0.8898	62.95	-62.20	0.75	28.62	-27.87	peak
4	1.5564	59.18	-62.02	-2.84	23.76	-26.60	peak
5	3.7100	56.70	-61.41	-4.71	29.54	-34.25	peak
6	7.3361	54.58	-61.17	-6.59	29.54	-36.13	peak


### 8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18592.000	49.25	-5.31	43.94	74.00	-30.06	peak
2	19392.000	50.12	-5.57	44.55	74.00	-29.45	peak
3	21032.000	49.15	-4.87	44.28	74.00	-29.72	peak
4	21600.000	49.52	-4.54	44.98	74.00	-29.02	peak
5	23744.000	47.65	-3.20	44.45	74.00	-29.55	peak
6	25000.000	46.36	-2.10	44.26	74.00	-29.74	peak


Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18536.000	49.10	-5.27	43.83	74.00	-30.17	peak
2	19712.000	48.51	-5.29	43.22	74.00	-30.78	peak
3	20240.000	48.82	-5.61	43.21	74.00	-30.79	peak
4	21544.000	48.26	-4.63	43.63	74.00	-30.37	peak
5	23088.000	47.02	-3.41	43.61	74.00	-30.39	peak
6	25728.000	44.61	-0.72	43.89	74.00	-30.11	peak


### 8.6. SPURIOUS EMISSIONS(26 GHZ~40 GHZ)

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	28786.000	47.49	-0.64	46.85	74.00	-27.15	peak
2	31670.000	48.36	-1.21	47.15	74.00	-26.85	peak
3	32986.000	47.49	-0.69	46.80	74.00	-27.20	peak
4	34428.000	46.70	0.99	47.69	74.00	-26.31	peak
5	36262.000	45.10	3.28	48.38	74.00	-25.62	peak
6	39958.000	43.58	5.12	48.70	74.00	-25.30	peak

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	28828.000	48.13	-0.79	47.34	74.00	-26.66	peak
2	31320.000	48.11	-0.93	47.18	74.00	-26.82	peak
3	33602.000	47.51	0.46	47.97	74.00	-26.03	peak
4	34302.000	46.95	1.10	48.05	74.00	-25.95	peak
5	35828.000	45.25	3.67	48.92	74.00	-25.08	peak
6	37158.000	44.84	3.17	48.01	74.00	-25.99	peak




## 8.7. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	36.7900	38.42	-18.83	19.59	40.00	-20.41	QP
2	165.8000	33.98	-16.61	17.37	43.50	-26.13	QP
3	263.7700	39.68	-17.39	22.29	46.00	-23.71	QP
4	331.6700	43.30	-13.34	29.96	46.00	-16.04	QP
5	829.2800	34.79	-6.12	28.67	46.00	-17.33	QP
6	1000.0000	34.33	-3.66	30.67	54.00	-23.33	QP

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	35.8200	39.82	-18.70	21.12	40.00	-18.88	QP
2	166.7700	37.47	-16.55	20.92	43.50	-22.58	QP
3	343.3100	38.54	-12.82	25.72	46.00	-20.28	QP
4	743.9200	31.42	-6.82	24.60	46.00	-21.40	QP
5	830.2500	33.14	-6.12	27.02	46.00	-18.98	QP
6	999.0300	39.23	-3.67	35.56	54.00	-18.44	QP

## 9. AC POWER LINE CONDUCTED EMISSION

### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00


### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### TEST SETUP



### TEST ENVIRONMENT


Temperature	24.5°C	Relative Humidity	55.2%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

**TEST DATE / ENGINEER**

Test Date	December 13, 2023	Test By	Wite Chen
-----------	-------------------	---------	-----------

**TEST RESULTS**

Test Mode:	802.11a	Frequency(MHz):	5180
Line:	Line		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1621	40.21	9.51	49.72	65.36	-15.64	QP
2	0.1621	21.61	9.51	31.12	55.36	-24.24	AVG
3	0.4833	15.72	9.51	25.23	56.28	-31.05	QP
4	0.4833	7.66	9.51	17.17	46.28	-29.11	AVG
5	3.4738	18.21	9.61	27.82	56.00	-28.18	QP
6	3.4738	13.31	9.61	22.92	46.00	-23.08	AVG
7	5.0474	10.65	9.62	20.27	60.00	-39.73	QP
8	5.0474	1.21	9.62	10.83	50.00	-39.17	AVG
9	9.6006	13.48	9.62	23.10	60.00	-36.90	QP
10	9.6006	7.91	9.62	17.53	50.00	-32.47	AVG
11	14.9973	11.88	9.66	21.54	60.00	-38.46	QP
12	14.9973	6.79	9.66	16.45	50.00	-33.55	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

Test Mode:	802.11a	Frequency(MHz):	5180
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1533	40.81	9.50	50.31	65.82	-15.51	QP
2	0.1533	19.12	9.50	28.62	55.82	-27.20	AVG
3	0.1816	36.36	9.55	45.91	64.41	-18.50	QP
4	0.1816	15.62	9.55	25.17	54.41	-29.24	AVG
5	0.4692	15.02	9.51	24.53	56.53	-32.00	QP
6	0.4692	6.34	9.51	15.85	46.53	-30.68	AVG
7	3.4977	16.16	9.61	25.77	56.00	-30.23	QP
8	3.4977	11.74	9.61	21.35	46.00	-24.65	AVG
9	9.2091	14.12	9.62	23.74	60.00	-36.26	QP
10	9.2091	8.93	9.62	18.55	50.00	-31.45	AVG
11	15.1406	10.08	9.65	19.73	60.00	-40.27	QP
12	15.1406	4.66	9.65	14.31	50.00	-35.69	AVG

**Note:**

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

## 10. ANTENNA REQUIREMENT

### REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.407(a)

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### DESCRIPTION

Pass

## 11. TEST DATA

### 11.1. APPENDIX A: EMISSION BANDWIDTH




#### 11.1.1. Test Result


Test Mode	Antenna	Frequency[MHz]	26db EBW [MHz]	FL[MHz]	FH[MHz]	Verdict
11A	Ant1	5180	19.92	5170.00	5189.92	PASS
	Ant2	5180	20.04	5170.00	5190.04	PASS
	Ant1	5200	19.96	5189.96	5209.92	PASS
	Ant2	5200	20.12	5189.92	5210.04	PASS
	Ant1	5240	20.52	5229.72	5250.24	PASS
	Ant2	5240	20.28	5229.92	5250.20	PASS
	Ant1	5260	20.28	5249.72	5270.00	PASS
	Ant2	5260	19.96	5249.96	5269.92	PASS
	Ant1	5280	20.12	5269.92	5290.04	PASS
	Ant2	5280	20.24	5269.88	5290.12	PASS
	Ant1	5320	20.28	5309.84	5330.12	PASS
	Ant2	5320	20.12	5309.84	5329.96	PASS
	Ant1	5500	19.80	5490.16	5509.96	PASS
	Ant2	5500	20.04	5489.88	5509.92	PASS
	Ant1	5580	19.84	5570.08	5589.92	PASS
	Ant2	5580	20.12	5569.92	5590.04	PASS
	Ant1	5700	20.16	5689.92	5710.08	PASS
	Ant2	5700	20.24	5689.84	5710.08	PASS
	Ant1	5720	20.16	5709.84	5730.00	PASS
	Ant2	5720	20.04	5710.04	5730.08	PASS
	Ant1	5720_UNII-2C	15.16	5709.84	5725	PASS
	Ant2	5720_UNII-2C	14.96	5710.04	5725	PASS
	Ant1	5720_UNII-3	5.00	5725	5730.00	PASS
	Ant2	5720_UNII-3	5.08	5725	5730.08	PASS
	Ant1	5745	20.24	5734.76	5755.00	PASS
	Ant2	5745	20.00	5734.84	5754.84	PASS
	Ant1	5785	20.44	5774.64	5795.08	PASS
	Ant2	5785	19.88	5775.08	5794.96	PASS
	Ant1	5825	20.52	5814.64	5835.16	PASS
	Ant2	5825	21.92	5813.32	5835.24	PASS
11N20MIMO	Ant1	5180	20.04	5169.96	5190.00	PASS
	Ant2	5180	20.36	5169.76	5190.12	PASS
	Ant1	5200	20.60	5189.84	5210.44	PASS
	Ant2	5200	20.20	5189.92	5210.12	PASS
	Ant1	5240	20.32	5229.88	5250.20	PASS
	Ant2	5240	20.76	5229.68	5250.44	PASS
	Ant1	5260	20.56	5249.64	5270.20	PASS
	Ant2	5260	20.48	5249.84	5270.32	PASS
	Ant1	5280	20.28	5269.80	5290.08	PASS
	Ant2	5280	20.40	5269.84	5290.24	PASS
	Ant1	5320	20.28	5309.76	5330.04	PASS
	Ant2	5320	20.40	5309.80	5330.20	PASS
	Ant1	5500	20.16	5489.84	5510.00	PASS
	Ant2	5500	20.20	5489.80	5510.00	PASS
	Ant1	5580	20.52	5569.80	5590.32	PASS
	Ant2	5580	20.12	5569.84	5589.96	PASS
	Ant1	5700	20.56	5689.76	5710.32	PASS
	Ant2	5700	20.20	5689.88	5710.08	PASS
	Ant1	5720	20.08	5709.92	5730.00	PASS
	Ant2	5720	20.24	5709.84	5730.08	PASS
	Ant1	5720_UNII-2C	15.08	5709.92	5725	PASS
	Ant2	5720_UNII-2C	15.16	5709.84	5725	PASS
	Ant1	5720_UNII-3	5.00	5725	5730.00	PASS
	Ant2	5720_UNII-3	5.08	5725	5730.08	PASS
	Ant1	5745	20.36	5734.76	5755.12	PASS
	Ant2	5745	20.40	5734.80	5755.20	PASS

	Ant1	5785	19.96	5774.92	5794.88	PASS
	Ant2	5785	20.20	5774.92	5795.12	PASS
	Ant1	5825	20.16	5814.76	5834.92	PASS
	Ant2	5825	20.20	5814.84	5835.04	PASS
11N40MIMO	Ant1	5190	79.20	5150.64	5229.84	PASS
	Ant2	5190	41.36	5169.36	5210.72	PASS
	Ant1	5230	72.16	5190.00	5262.16	PASS
	Ant2	5230	41.92	5209.36	5251.28	PASS
	Ant1	5270	41.60	5249.04	5290.64	PASS
	Ant2	5270	48.72	5246.32	5295.04	PASS
	Ant1	5310	77.28	5272.32	5349.60	PASS
	Ant2	5310	41.12	5289.36	5330.48	PASS
	Ant1	5510	56.48	5474.48	5530.96	PASS
	Ant2	5510	40.88	5489.60	5530.48	PASS
	Ant1	5550	42.24	5528.80	5571.04	PASS
	Ant2	5550	41.36	5529.36	5570.72	PASS
	Ant1	5670	61.52	5646.88	5708.40	PASS
	Ant2	5670	41.28	5649.44	5690.72	PASS
	Ant1	5710	69.12	5680.48	5749.60	PASS
	Ant2	5710	40.88	5689.68	5730.56	PASS
	Ant1	5710_UNII-2C	44.52	5680.48	5725	PASS
	Ant2	5710_UNII-2C	35.32	5689.68	5725	PASS
	Ant1	5710_UNII-3	24.6	5725	5749.60	PASS
	Ant2	5710_UNII-3	5.56	5725	5730.56	PASS
	Ant1	5755	76.00	5719.00	5795.00	PASS
	Ant2	5755	40.80	5734.68	5775.48	PASS
	Ant1	5795	79.28	5755.32	5834.60	PASS
	Ant2	5795	41.28	5774.44	5815.72	PASS
11AC80MIMO	Ant1	5210	81.76	5168.88	5250.64	PASS
	Ant2	5210	81.12	5169.68	5250.80	PASS
	Ant1	5290	81.28	5249.36	5330.64	PASS
	Ant2	5290	80.96	5249.68	5330.64	PASS
	Ant1	5530	81.44	5489.36	5570.80	PASS
	Ant2	5530	81.28	5489.68	5570.96	PASS
	Ant1	5610	81.44	5569.52	5650.96	PASS
	Ant2	5610	81.28	5569.52	5650.80	PASS
	Ant1	5690	81.76	5649.20	5730.96	PASS
	Ant2	5690	81.12	5649.52	5730.64	PASS
	Ant1	5690_UNII-2C	75.8	5649.20	5725	PASS
	Ant2	5690_UNII-2C	75.48	5649.52	5725	PASS
	Ant1	5690_UNII-3	5.96	5725	5730.96	PASS
	Ant2	5690_UNII-3	5.64	5725	5730.64	PASS
	Ant1	5775	81.12	5734.52	5815.64	PASS
	Ant2	5775	80.80	5734.68	5815.48	PASS




### 11.1.2. Test Graphs






Date: 23.NOV.2023 07:39:16

11A\_Ant2\_5200




Date: 23.NOV.2023 07:26:48

11A\_Ant1\_5240






Date: 23.NOV.2023 07:40:12


11A\_Ant2\_5240




Date: 23.NOV.2023 07:27:32




### 11A\_Ant2\_5280




Date: 23.NOV.2023 07:28:58






Date: 23.NOV.2023 07:42:53




Date: 23.NOV.2023 07:30:49




Date: 23.NOV.2023 07:43:48




### 11A\_Ant1\_5700




Date: 23.NOV.2023 07:45:54




Date: 23.NOV.2023 07:33:38




Date: 23.NOV.2023 07:47:53




Date: 23.NOV.2023 07:35:11






Date: 23.NOV.2023 07:36:48

11A\_Ant1\_5825




Date: 23.NOV.2023 07:51:27

11A\_Ant2\_5825




Date: 23.NOV.2023 07:54:07





11N20MIMO\_Ant1\_5180





Date: 23.NOV.2023 07:57:08













Date: 23.NOV.2023 08:16:33

11N20MIMO\_Ant1\_5500




Date: 23.NOV.2023 08:16:57

11N20MIMO\_Ant2\_5500





Date: 23.NOV.2023 08:20:52

11N20MIMO\_Ant1\_5580




Date: 23.NOV.2023 08:21:16







Date: 23.NOV.2023 08:37:18




Date: 23.NOV.2023 08:41:03




Date: 23.NOV.2023 08:41:35




Date: 23.NOV.2023 08:43:21






Date: 23.NOV.2023 08:48:49

11N40MIMO\_Ant1\_5190




Date: 23.NOV.2023 08:49:23

11N40MIMO\_Ant2\_5190




Date: 23.NOV.2023 08:55:55

11N40MIMO\_Ant1\_5230



Date: 23.NOV.2023 08:54:29





11N40MIMO\_Ant1\_5310