


REPORT NO.: 4789769271-3 Page 124 of 141





REPORT NO.: 4789769271-3 Page 125 of 141






REPORT NO.: 4789769271-3 Page 126 of 141






REPORT NO.: 4789769271-3 Page 127 of 141






REPORT NO.: 4789769271-3 Page 128 of 141






REPORT NO.: 4789769271-3 Page 129 of 141






REPORT NO.: 4789769271-3 Page 130 of 141





REPORT NO.: 4789769271-3 Page 131 of 141






REPORT NO.: 4789769271-3 Page 132 of 141






REPORT NO.: 4789769271-3 Page 133 of 141






REPORT NO.: 4789769271-3 Page 134 of 141






REPORT NO.: 4789769271-3 Page 135 of 141






REPORT NO.: 4789769271-3 Page 136 of 141






REPORT NO.: 4789769271-3 Page 137 of 141





REPORT NO.: 4789769271-3 Page 138 of 141





11.7. Appendix G: Duty Cycle 11.7.1. Test Result

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
11B	8.38	8.41	0.9964	99.64	0.02	0.12	0.5
11G	1.39	1.43	0.9720	97.20	0.12	0.72	1
11N20MIMO	1.30	1.34	0.9701	97.01	0.13	0.77	1
11N40MIMO	0.65	0.68	0.9559	95.59	0.20	1.54	2

Note:

Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)

Where: T is On Time


If that calculated VBW is not available on the analyzer then the next higher value should be used.



11.7.2. Test Graphs







END OF REPORT