



**CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 ISSUE 2**

TEST REPORT

For

WIFI+BT Module

MODEL NUMBER: WXT05R2601

FCC ID: 2AC23-WXT05

IC: 12290A-WXT05

REPORT NUMBER: 4790390611.2-1-RF-2

ISSUE DATE: June 8, 2022

Prepared for

**Hui Zhou Gaoshengda Technology Co.,LTD
No.2,Jin-da Road,Huinan High-tech Industrial Park, Huizhou, Guangdong, China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



Revision History

| Rev. | Issue Date | Revisions | Revised By |
|------|--------------|---------------|------------|
| V0 | June 8, 2022 | Initial Issue | |



| Summary of Test Results | | | |
|--|---|---|--------------|
| Clause | Test Items | FCC/ISED Rules | Test Results |
| 1 | 20dB Bandwidth and 99% Occupied Bandwidth | FCC 15.247 (a) (1) RSS-247 Clause 5.1 (a) RSS-Gen Clause 6.7 | Pass |
| 2 | Conducted Output Power | FCC 15.247 (b) (1) RSS-247 Clause 5.1 (b) | Pass |
| 3 | Carrier Hopping Channel Separation | FCC 15.247 (a) (1) RSS-247 Clause 5.1 (b) | Pass |
| 4 | Number of Hopping Frequency | 15.247 (a) (1) III RSS-247 Clause 5.1 (d) | Pass |
| 5 | Time of Occupancy (Dwell Time) | 15.247 (a) (1) III RSS-247 Clause 5.1 (d) | Pass |
| 6 | Conducted Bandedge | FCC 15.247 (d) RSS-247 Clause 5.5 | Pass |
| 7 | Radiated Bandedge and Spurious | FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9 RSS-GEN Clause 8.10 | Pass |
| 8 | Conducted Emission Test for AC Power Port | FCC 15.207 RSS-GEN Clause 8.8 | Pass |
| 9 | Antenna Requirement | FCC 15.203 RSS-GEN Clause 6.8 | Pass |
| <p>Note:</p> <p>1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China.</p> <p>2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C >< ISED RSS-247 > when <Accuracy Method> decision rule is applied.</p> | | | |

CONTENTS

| | |
|--|-----------|
| 1. ATTESTATION OF TEST RESULTS | 6 |
| 2. TEST METHODOLOGY | 7 |
| 3. FACILITIES AND ACCREDITATION | 7 |
| 4. CALIBRATION AND UNCERTAINTY | 8 |
| 4.1. <i>MEASURING INSTRUMENT CALIBRATION</i> | 8 |
| 4.2. <i>MEASUREMENT UNCERTAINTY</i> | 8 |
| 5. EQUIPMENT UNDER TEST | 9 |
| 5.1. <i>DESCRIPTION OF EUT</i> | 9 |
| 5.2. <i>CHANNEL LIST</i> | 9 |
| 5.3. <i>MAXIMUM PEAK EIRP</i> | 10 |
| 5.4. <i>TEST CHANNEL CONFIGURATION</i> | 10 |
| 5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i> | 10 |
| 5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i> | 11 |
| 5.7. <i>SUPPORT UNITS FOR SYSTEM TEST</i> | 12 |
| 5.8. <i>SETUP DIAGRAM</i> | 12 |
| 6. MEASURING EQUIPMENT AND SOFTWARE USED | 13 |
| 7. ANTENNA PORT TEST RESULTS | 16 |
| 7.1. <i>CONDUCTED OUTPUT POWER</i> | 16 |
| 7.2. <i>20 DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH</i> | 17 |
| 7.3. <i>CARRIER HOPPING CHANNEL SEPARATION</i> | 18 |
| 7.4. <i>NUMBER OF HOPPING FREQUENCY</i> | 20 |
| 7.5. <i>TIME OF OCCUPANCY (DWELL TIME)</i> | 21 |
| 7.6. <i>CONDUCTED BANDEDGE AND SPURIOUS EMISSION</i> | 23 |
| 7.7. <i>DUTY CYCLE</i> | 25 |
| 8. RADIATED TEST RESULTS | 26 |
| 8.1. <i>BANDEDGE</i> | 35 |
| 8.2. <i>RADIATE SPURIOUS EMISSION</i> | 40 |
| 9. ANTENNA REQUIREMENT | 65 |
| 10. AC POWER LINE CONDUCTED EMISSION | 66 |
| 11. ST DATA | 69 |
| 11.1. <i>APPENDIX A: 20DB EMISSION BANDWIDTH</i> | 69 |
| 11.1.1. Test Result..... | 69 |
| 11.1.2. Test Graphs | 70 |



| | | |
|---------|--|----|
| 11.2. | <i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH</i> | 72 |
| 11.2.1. | Test Result..... | 72 |
| 11.2.2. | Test Graphs | 73 |
| 11.3. | <i>APPENDIX C: MAXIMUM CONDUCTED PEAK OUTPUT POWER</i> | 75 |
| 11.3.1. | Test Result..... | 75 |
| 11.4. | <i>APPENDIX D: CARRIER FREQUENCY SEPARATION</i> | 76 |
| 11.4.1. | Test Result..... | 76 |
| 11.4.2. | Test Graphs | 77 |
| 11.5. | <i>APPENDIX E: TIME OF OCCUPANCY</i> | 78 |
| 11.5.1. | Test Result..... | 78 |
| 11.5.2. | Test Graphs | 79 |
| 11.6. | <i>APPENDIX F: NUMBER OF HOPPING CHANNELS</i> | 81 |
| 11.6.1. | Test Result..... | 81 |
| 11.6.2. | Test Graphs | 82 |
| 11.7. | <i>APPENDIX G: BAND EDGE MEASUREMENTS</i> | 83 |
| 11.7.1. | Test Result..... | 83 |
| 11.7.2. | Test Graphs | 84 |
| 11.8. | <i>APPENDIX H: CONDUCTED SPURIOUS EMISSION</i> | 87 |
| 11.8.1. | Test Result..... | 87 |
| 11.8.2. | Test Graphs | 88 |
| 11.9. | <i>APPENDIX I: DUTY CYCLE</i> | 94 |
| 11.9.1. | Test Result..... | 94 |
| 11.9.2. | Test Graphs | 95 |



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD
Address: No.2,Jin-da Road,Huinan High-tech Industrial Park, Huizhou, Guangdong, China

Manufacturer Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD
Address: No.2,Jin-da Road,Huinan High-tech Industrial Park, Huizhou, Guangdong, China

EUT Information

EUT Name: WIFI+BT Module
Model: WXT05R2601
Brand: GSD
Sample Received Date: May 7, 2022
Sample Status: Normal
Sample ID: 4932467
Date of Tested: May 9, 2022 to June 7, 2022

| APPLICABLE STANDARDS | |
|--|--------------|
| STANDARD | TEST RESULTS |
| CFR 47 FCC PART 15 SUBPART C ISED RSS-247 ISSUE 2 | Pass |

Prepared By:

Kebo Zhang
Senior Project Engineer

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

| | |
|---------------------------|---|
| Accreditation Certificate | <p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p> |
|---------------------------|---|

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| PARAMETER | UNCERTAINTY |
|------------------------|----------------------|
| Radio Frequency | 3.5×10^{-7} |
| RF power, conducted | ± 2.5 dB |
| Temperature | ± 1 °C |
| Humidity | ± 5 % |
| Voltage (DC) | ± 1 % |
| Voltage (AC, < 10 kHz) | ± 2 % |

| Test Item | Uncertainty |
|---|------------------------|
| Uncertainty for Radiation Emission test | 4.62 dB (30 MHz-1 GHz) |
| | 3.50 dB (1 GHz-18 GHz) |

For the test methods, according to the present document the uncertainty figures shall be calculated according to the methods described in the TR 100 028 [i.4] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

| | |
|----------|----------------|
| EUT Name | WIFI+BT Module |
| Model | WXT05R2601 |

| | |
|-----------------------|---|
| Frequency Range: | 2402 MHz to 2480 MHz |
| Modulation Technique: | Frequency Hopping Spread Spectrum(FHSS) |
| Type of Modulation: | GFSK, $\Pi/4$ DQPSK, 8DPSK |
| Normal Test Voltage: | DC 3.3 V |

5.2. CHANNEL LIST

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| 00 | 2402 | 20 | 2422 | 40 | 2442 | 60 | 2462 |
| 01 | 2403 | 21 | 2423 | 41 | 2443 | 61 | 2463 |
| 02 | 2404 | 22 | 2424 | 42 | 2444 | 62 | 2464 |
| 03 | 2405 | 23 | 2425 | 43 | 2445 | 63 | 2465 |
| 04 | 2406 | 24 | 2426 | 44 | 2446 | 64 | 2466 |
| 05 | 2407 | 25 | 2427 | 45 | 2447 | 65 | 2467 |
| 06 | 2408 | 26 | 2428 | 46 | 2448 | 66 | 2468 |
| 07 | 2409 | 27 | 2429 | 47 | 2449 | 67 | 2469 |
| 08 | 2410 | 28 | 2430 | 48 | 2450 | 68 | 2470 |
| 09 | 2411 | 29 | 2431 | 49 | 2451 | 69 | 2471 |
| 10 | 2412 | 30 | 2432 | 50 | 2452 | 70 | 2472 |
| 11 | 2413 | 31 | 2433 | 51 | 2453 | 71 | 2473 |
| 12 | 2414 | 32 | 2434 | 52 | 2454 | 72 | 2474 |
| 13 | 2415 | 33 | 2435 | 53 | 2455 | 73 | 2475 |
| 14 | 2416 | 34 | 2436 | 54 | 2456 | 74 | 2476 |
| 15 | 2417 | 35 | 2437 | 55 | 2457 | 75 | 2477 |
| 16 | 2418 | 36 | 2438 | 56 | 2458 | 76 | 2478 |
| 17 | 2419 | 37 | 2439 | 57 | 2459 | 77 | 2479 |
| 18 | 2420 | 38 | 2440 | 58 | 2460 | 78 | 2480 |
| 19 | 2421 | 39 | 2441 | 59 | 2461 | / | / |

5.3. MAXIMUM PEAK EIRP

| Test Mode | Frequency (MHz) | Channel Number | Maximum Peak Output Power (dBm) | Maximum EIRP (dBm) |
|-----------|-----------------|----------------|---------------------------------|--------------------|
| GFSK | 2402 ~ 2480 | 0-78[79] | 8.31 | 10.31 |
| 8DPSK | 2402 ~ 2480 | 0-78[79] | 10.15 | 12.15 |

5.4. TEST CHANNEL CONFIGURATION

| Test Mode | Test Channel | Frequency |
|------------|--|------------------------------|
| GFSK-DH5 | CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel) | 2402 MHz, 2441 MHz, 2480 MHz |
| 8DPSK-3DH5 | CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel) | 2402 MHz, 2441 MHz, 2480 MHz |
| GFSK-DH5 | Hopping | 2402 MHz ~ 2480 MHz |
| 8DPSK-3DH5 | Hopping | 2402 MHz ~ 2480 MHz |

PACKET TYPE CONFIGURATION

| Test Mode | Packet Type | Setting (Packet Length) |
|-----------|-------------|-------------------------|
| GFSK | DH1 | 27 |
| | DH3 | 183 |
| | DH5 | 339 |
| π/4-DQPSK | 2-DH1 | 54 |
| | 2-DH3 | 367 |
| | 2-DH5 | 679 |
| 8DPSK | 3-DH1 | 83 |
| | 3-DH3 | 552 |
| | 3-DH5 | 1021 |

5.5. THE WORSE CASE POWER SETTING PARAMETER

WORST-CASE CONFIGURATIONS

| Bluetooth Mode | Modulation Technology | Modulation Type | Data Rate (Mbps) |
|----------------|-----------------------|-----------------|------------------|
| BR | FHSS | GFSK | 1Mbit/s |
| EDR | FHSS | 8DPSK | 3Mbit/s |

Note: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.



| The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band | | | | |
|--|-------------------------|-----------------------------|-------|-------|
| Test Software | | RTLBTAPP | | |
| Modulation Type | Transmit Antenna Number | Test Software setting value | | |
| | | CH 00 | CH 39 | CH 78 |
| GFSK | 1 | 0x4f | 0x4f | 0x4f |
| 8DPSK | 1 | 0x51 | 0x51 | 0x51 |

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

| Antenna | Frequency (MHz) | Antenna Type | MAX Antenna Gain (dBi) |
|---------|-----------------|--------------|------------------------|
| 1 | 2402-2480 | PIFA antenna | 2 |

| Test Mode | Transmit and Receive Mode | Description |
|---|--|--|
| GFSK | <input checked="" type="checkbox"/> 1TX, 1RX | Antenna 1 can be used as transmitting/receiving antenna. |
| 8DPSK | <input checked="" type="checkbox"/> 1TX, 1RX | Antenna 1 can be used as transmitting/receiving antenna. |
| Note: 1.BT&WLAN 2.4G, BT & WLAN 5G, WLAN 2.4G & WLAN 5G can't transmit simultaneously. (declared by client) | | |

Note: The value of the antenna gain was declared by customer.

5.7. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

| Item | Equipment | Brand Name | Model Name | Remarks |
|------|-----------|------------|-------------|---|
| 1 | Laptop | Lenovo | T460S | SL10K24796 JS |
| 2 | Adapter | Lenovo | ADLX65YCC3D | Input: 100~240 Vac, 50-60Hz Output:20 Vdc, 3.25 A, 65W |


I/O CABLES

| Cable No | Port | Connector Type | Cable Type | Cable Length(m) | Remarks |
|----------|------|----------------|------------|-----------------|---------|
| 1 | USB | / | / | 1.0 | / |

ACCESSORIES

| Item | Accessory | Brand Name | Model Name | Description |
|------|-----------|------------|------------|-------------|
| 1 | / | / | / | / |

5.8. SETUP DIAGRAM



Note: AC adapter only use for AC POWER LINE CONDUCTED EMISSIONS testing.

**6. MEASURING EQUIPMENT AND SOFTWARE USED**

| R&S TS 8997 Test System | | | | | |
|-------------------------------------|-----------------|-------------------------|------------------|--------------|--------------|
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due. Date |
| Vector Signal Generator | R&S | SMBV100A | 261637 | Oct.30, 2021 | Oct.29, 2022 |
| Signal Generator | R&S | SMB100A | 178553 | Oct.30, 2021 | Oct.29, 2022 |
| Signal Analyzer | R&S | FSV40 | 101118 | Oct.30, 2021 | Oct.29, 2022 |
| Software | | | | | |
| Description | Manufacturer | Name | | Version | |
| For R&S TS 8997 Test System | Rohde & Schwarz | EMC 32 | | 10.60.10 | |
| Tonsend RF Test System | | | | | |
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due. Date |
| Wideband Radio Communication Tester | R&S | CMW500 | 155523 | Oct.30, 2021 | Oct.29, 2022 |
| Wireless Connectivity Tester | R&S | CMW270 | 1201.0002N75-102 | Sep.29, 2021 | Sep.28, 2022 |
| PXA Signal Analyzer | Keysight | N9030A | MY55410512 | Oct.30, 2021 | Oct.29, 2022 |
| MXG Vector Signal Generator | Keysight | N5182B | MY56200284 | Oct.30, 2021 | Oct.29, 2022 |
| MXG Vector Signal Generator | Keysight | N5172B | MY56200301 | Oct.30, 2021 | Oct.29, 2022 |
| DC power supply | Keysight | E3642A | MY55159130 | Oct.30, 2021 | Oct.29, 2022 |
| Temperature & Humidity Chamber | SANMOOD | SG-80-CC-2 | 2088 | Nov.20,2020 | Nov.19,2022 |
| Software | | | | | |
| Description | Manufacturer | Name | | Version | |
| Tonsend SRD Test System | Tonsend | JS1120-3 RF Test System | | 2.6.77.0518 | |
| Conducted Emissions | | | | | |
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due Date |
| EMI Test Receiver | R&S | ESR3 | 101961 | Oct.30, 2021 | Oct.29, 2022 |
| Two-Line V-Network | R&S | ENV216 | 101983 | Oct.30, 2021 | Oct.29, 2022 |
| Artificial Mains Networks | Schwarzbeck | NSLK 8126 | 8126465 | Oct.30, 2021 | Oct.29, 2022 |
| Software | | | | | |
| Description | Manufacturer | Name | | Version | |



| Test Software for Conducted Emissions | | Farad | | EZ-EMC | Ver. UL-3A1 |
|---------------------------------------|---------------|-------------------------------------|---------------|---------------|---------------|
| Radiated Emissions | | | | | |
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due Date |
| MXE EMI Receiver | KESIGHT | N9038A | MY56400036 | Oct.30, 2021 | Oct.29, 2022 |
| Hybrid Log Periodic Antenna | TDK | HLP-3003C | 130959 | Aug.02, 2021 | Aug.01, 2024 |
| Preamplifier | HP | 8447D | 2944A09099 | Oct.30, 2021 | Oct.29, 2022 |
| EMI Measurement Receiver | R&S | ESR26 | 101377 | Oct.30, 2021 | Oct.29, 2022 |
| Horn Antenna | TDK | HRN-0118 | 130940 | July 20, 2021 | July 19, 2024 |
| Preamplifier | TDK | PA-02-0118 | TRS-305-00067 | Oct.30, 2021 | Oct.29, 2022 |
| Horn Antenna | Schwarzbeck | BBHA9170 | 697 | July 20, 2021 | July 19, 2024 |
| Preamplifier | TDK | PA-02-2 | TRS-307-00003 | Oct.31, 2021 | Oct.30, 2022 |
| Preamplifier | TDK | PA-02-3 | TRS-308-00002 | Oct.31, 2021 | Oct.30, 2022 |
| Loop antenna | Schwarzbeck | 1519B | 00008 | Dec.14, 2021 | Dec.13, 2024 |
| Preamplifier | TDK | PA-02-001-3000 | TRS-302-00050 | Oct.31, 2021 | Oct.30, 2022 |
| Preamplifier | Mini-Circuits | ZX60-83LN-S+ | SUP01201941 | Oct.31, 2021 | Oct.30, 2022 |
| High Pass Filter | Wi | WHKX10-2700-3000-18000-40SS | 23 | Oct.31, 2021 | Oct.30, 2022 |
| Highpass Filter | Wainwright | WHKX10-5850-6500-1800-40SS | 4 | Oct.31, 2021 | Oct.30, 2022 |
| Band Reject Filter | Wainwright | WRCJV12-5695-5725-5850-5880-40SS | 4 | Oct.31, 2021 | Oct.30, 2022 |
| Band Reject Filter | Wainwright | WRCJV20-5120-5150-5350-5380-60SS | 2 | Oct.31, 2021 | Oct.30, 2022 |
| Band Reject Filter | Wainwright | WRCJV20-5440-5470-5725-5755-60SS | 1 | Oct.31, 2021 | Oct.30, 2022 |
| Band Reject Filter | Wainwright | WRCJV8-2350-2400-2483.5-2533.5-40SS | 4 | Oct.31, 2021 | Oct.30, 2022 |
| Band Reject Filter | Wainwright | WRCD5-1879- | 1 | Oct.31, 2021 | Oct.30, 2022 |



| | | | | | |
|--------------------------------------|--------------|-----------------------------------|------------|---------------|---------------|
| | | 1879.85- 1880.15- 1881-40SS | | | |
| Notch Filter | Wainwright | WHJ10-882- 980-7000- 40SS | 1 | Oct.31, 2021 | Oct.30, 2022 |
| Software | | | | | |
| Description | | Manufacturer | Name | Version | |
| Test Software for Radiated Emissions | | Farad | EZ-EMC | Ver. UL-3A1 | |
| Other Instrument | | | | | |
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due Date |
| Temperature humidity probe | OMEGA | ITHX-SD-5 | 18470007 | Nov. 4, 2021 | Nov. 3, 2022 |
| Barometer | Yiyi | Baro | N/A | Nov. 15, 2021 | Nov. 14, 2022 |
| Power Sensor | Keysight | USB Wideband Power Sensor | MY5100022 | Oct.30, 2021 | Oct.29, 2022 |

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS


| CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2 | | | |
|--|--------------------------------|---|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC 15.247 (b) (1) ISED RSS-247 Clause 5.4 (b) | Peak Conducted Output Power | Hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel: 1 watt or 30 dBm; Hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel: 125 mW or 21 dBm | 2400-2483.5 |

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|--------|-------------------|----------|
| Temperature | 26.1°C | Relative Humidity | 65.1% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.3 V |

TEST RESULTS

Please refer to section "Test Data" - Appendix C

7.2. 20 DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

| CFR 47FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2 | | | |
|---|-------------------------|------------------------------------|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC 15.247 (a) (1) RSS-247 Clause 5.1 (a) | 20 dB Bandwidth | None; for reporting purposes only. | 2400-2483.5 |
| ISED RSS-Gen Clause 6.7 | 99 % Occupied Bandwidth | None; for reporting purposes only. | 2400-2483.5 |

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 6.9.2.

Connect the EUT to the spectrum analyser and use the following settings:

| | |
|------------------|---|
| Center Frequency | The center frequency of the channel under test |
| Detector | Peak |
| RBW | For 20 dB Bandwidth: 1 % to 5 % of the 20 dB bandwidth For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth |
| VBW | For 20 dB Bandwidth: approximately 3×RBW For 99 % Occupied Bandwidth: ≥ 3×RBW |
| Span | Approximately 2 to 3 times the 20dB bandwidth |
| Trace | Max hold |
| Sweep | Auto couple |

a) Use the occupied bandwidth function of the instrument, allow the trace to stabilize and report the measured 99 % occupied bandwidth and 20 dB Bandwidth.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|--------|-------------------|----------|
| Temperature | 26.1°C | Relative Humidity | 65.1% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.3 V |

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B

7.3. CARRIER HOPPING CHANNEL SEPARATION

LIMITS

| CFR 47 FCC Part15 (15.247), Subpart C ISSED RSS-247 ISSUE 2 | | | |
|--|------------------------------------|---|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC 15.247 (a) (1) ISED RSS-247 Clause 5.1 (b) | Carrier Frequency Separation | Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel. | 2400-2483.5 |

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.2.


Connect the EUT to the spectrum analyzer and use the following settings:

| | |
|------------------|--|
| Center Frequency | The center frequency of the channel under test |
| Span | wide enough to capture the peaks of two adjacent channels |
| Detector | Peak |
| RBW | Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel. |
| VBW | ≥RBW |
| Trace | Max hold |
| Sweep time | Auto couple |

Allow the trace to stabilize and use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|--------|-------------------|----------|
| Temperature | 26.1°C | Relative Humidity | 65.1% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.3 V |



TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. NUMBER OF HOPPING FREQUENCY

LIMITS

| CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2 | | |
|---|-----------------------------|------------------------------|
| Section | Test Item | Limit |
| CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 5.1 (d) | Number of Hopping Frequency | at least 15 hopping channels |

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 7.8.3.

Connect the EUT to the spectrum Analyzer and use the following settings:

| | |
|------------|--|
| Detector | Peak |
| RBW | To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller. |
| VBW | ≥RBW |
| Span | The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen. |
| Trace | Max hold |
| Sweep time | Auto couple |

Set EUT to transmit maximum output power and switch on frequency hopping function. then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer, count the quantity of peaks to get the number of hopping channels.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|--------|-------------------|----------|
| Temperature | 26.1°C | Relative Humidity | 65.1% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.3 V |

TEST RESULTS

Please refer to section "Test Data" - Appendix F

7.5. TIME OF OCCUPANCY (DWELL TIME)

LIMITS

| CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2 | | |
|---|--------------------------------------|---|
| Section | Test Item | Limit |
| CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 5.1 (d) | Time of Occupancy (Dwell Time) | The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed. |

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.4.

Connect the EUT to the spectrum Analyzer and use the following settings:

| | |
|------------------|--|
| Center Frequency | The center frequency of the channel under test |
| Detector | Peak |
| RBW | 1 MHz |
| VBW | ≥RBW |
| Span | Zero span, centered on a hopping channel |
| Trace | Max hold |
| Sweep time | As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel |

Use the marker-delta function to determine the transmit time per hop (Burst Width). If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

For FHSS Mode (79 Channel):

DH1/3DH1 Dwell Time: $\text{Burst Width} * (1600/2) * 31.6 / (\text{channel number})$

DH3/3DH3 Dwell Time: $\text{Burst Width} * (1600/4) * 31.6 / (\text{channel number})$

DH5/3DH5 Dwell Time: $\text{Burst Width} * (1600/6) * 31.6 / (\text{channel number})$


For AFHSS Mode (20 Channel):

DH1/3DH1 Dwell Time: $\text{Burst Width} * (1600/2) * 8 / (\text{channel number})$

DH3/3DH3 Dwell Time: $\text{Burst Width} * (1600/4) * 8 / (\text{channel number})$

DH5/3DH5 Dwell Time: $\text{Burst Width} * (1600/6) * 8 / (\text{channel number})$

TEST SETUP



**TEST ENVIRONMENT**

| | | | |
|---------------------|---------|-------------------|----------|
| Temperature | 26.1 °C | Relative Humidity | 65.1% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.3 V |

TEST RESULTS

Please refer to section "Test Data" - Appendix E

7.6. CONDUCTED BANDEDGE AND SPURIOUS EMISSION

LIMITS

| CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2 | | |
|---|--------------------------------|---|
| Section | Test Item | Limit |
| CFR 47 FCC §15.247 (d) ISED RSS-247 5.5 | Conducted Spurious Emission | at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power |

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.6 and 7.8.8.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

| | |
|------------------|--|
| Center Frequency | The center frequency of the channel under test |
| Detector | Peak |
| RBW | 100 kHz |
| VBW | $\geq 3 \times \text{RBW}$ |
| Span | 1.5 x DTS bandwidth |
| Trace | Max hold |
| Sweep time | Auto couple. |

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.


Change the settings for emission level measurement:

| | |
|--------------------|---|
| Span | Set the center frequency and span to encompass frequency range to be measured |
| Detector | Peak |
| RBW | 100 kHz |
| VBW | $\geq 3 \times \text{RBW}$ |
| measurement points | $\geq \text{span}/\text{RBW}$ |
| Trace | Max hold |
| Sweep time | Auto couple. |

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum



TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|---------|-------------------|----------|
| Temperature | 26.1 °C | Relative Humidity | 65.1% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.3 V |

TEST RESULTS

Please refer to section "Test Data" - Appendix G&H



7.7. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|--------|-------------------|----------|
| Temperature | 26.1°C | Relative Humidity | 65.1% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.3 V |

TEST RESULTS

Please refer to section "Test Data" - Appendix I



8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz-1 GHz)

| Emissions radiated outside of the specified frequency bands above 30 MHz | | | |
|--|------------------------------------|--------------------------------------|---------|
| Frequency Range (MHz) | Field Strength Limit (uV/m) at 3 m | Field Strength Limit (dBuV/m) at 3 m | |
| | | Quasi-Peak | |
| 30 - 88 | 100 | 40 | |
| 88 - 216 | 150 | 43.5 | |
| 216 - 960 | 200 | 46 | |
| Above 960 | 500 | 54 | |
| Above 1000 | 500 | Peak | Average |
| | | 74 | 54 |

| FCC Emissions radiated outside of the specified frequency bands below 30 MHz | | |
|--|-----------------------------------|-------------------------------|
| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |

ISED General field strength limits at frequencies below 30 MHz

| Table 6 – General field strength limits at frequencies below 30 MHz | | |
|---|--|--------------------------|
| Frequency | Magnetic field strength (H-Field) (uA/m) | Measurement distance (m) |
| 9 - 490 kHz ^{Note 1} | 6.37/F (F in kHz) | 300 |
| 490 - 1705 kHz | 63.7/F (F in kHz) | 30 |
| 1.705 - 30 MHz | 0.08 | 30 |

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.



ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

| Table 7 – Restricted frequency bands ^{Note 1} | | |
|--|-----------------------|---------------|
| MHz | MHz | GHz |
| 0.090 - 0.110 | 149.9 - 150.05 | 9.0 - 9.2 |
| 0.495 - 0.505 | 156.52475 - 156.52525 | 9.3 - 9.5 |
| 2.1735 - 2.1905 | 158.7 - 158.9 | 10.6 - 12.7 |
| 3.020 - 3.028 | 162.0125 - 167.17 | 13.25 - 13.4 |
| 4.125 - 4.128 | 167.72 - 173.2 | 14.47 - 14.5 |
| 4.17725 - 4.17775 | 240 - 285 | 15.35 - 16.2 |
| 4.20725 - 4.20775 | 322 - 335.4 | 17.7 - 21.4 |
| 5.877 - 5.883 | 399.9 - 410 | 22.01 - 23.12 |
| 6.215 - 6.218 | 608 - 614 | 23.6 - 24.0 |
| 6.26775 - 6.26825 | 960 - 1427 | 31.2 - 31.8 |
| 6.31175 - 6.31225 | 1435 - 1626.5 | 36.43 - 36.5 |
| 8.291 - 8.294 | 1645.5 - 1646.5 | Above 38.6 |
| 8.362 - 8.366 | 1660 - 1710 | |
| 8.37625 - 8.38675 | 1718.8 - 1722.2 | |
| 8.41425 - 8.41475 | 2200 - 2300 | |
| 12.29 - 12.293 | 2310 - 2390 | |
| 12.51975 - 12.52025 | 2483.5 - 2500 | |
| 12.57675 - 12.57725 | 2695 - 2900 | |
| 13.36 - 13.41 | 3260 - 3267 | |
| 16.42 - 16.423 | 3332 - 3339 | |
| 16.69475 - 16.69525 | 3345.8 - 3358 | |
| 16.80425 - 16.80475 | 3500 - 4400 | |
| 25.5 - 25.67 | 4500 - 5150 | |
| 37.5 - 38.25 | 5350 - 5490 | |
| 73 - 74.6 | 7250 - 7750 | |
| 74.8 - 75.2 | 8025 - 8500 | |
| 108 - 138 | | |

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

| MHz | MHz | MHz | GHz |
|--------------------------|---------------------|---------------|------------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| ¹ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (²) |
| 13.36-13.41 | | | |

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyser

| | |
|-------|--|
| RBW | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| VBW | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| Sweep | Auto |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.



Below 1 GHz and above 30 MHz

The setting of the spectrum analyser

| | |
|----------|----------|
| RBW | 120 kHz |
| VBW | 300 kHz |
| Sweep | Auto |
| Detector | Peak/QP |
| Trace | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.




Above 1 GHz

The setting of the spectrum analyser

| | |
|----------|--------------------------------|
| RBW | 1 MHz |
| VBW | PEAK: 3 MHz AVG: see note 6 |
| Sweep | Auto |
| Detector | Peak |
| Trace | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.7.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For bandedge note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.7.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Horizontal and Vertical have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 1 GHz-3 GHz note:

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
 5. For the transmitting duration, please refer to clause 7.7.
 6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 8. All modes and channels have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 3 GHz-18 GHz note:

- Note:
1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
 5. For the transmitting duration, please refer to clause 7.7.
 6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



For Radiate Spurious emission 9 kHz-30 MHz note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes and channels have been tested, only the worst data was recorded in the report.


For Radiate Spurious emission 18 GHz-26 GHz note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. All modes and channels have been tested, only the worst data was recorded in the report.


For Radiate Spurious emission 30 MHz-1 GHz note:

1. Result Level = Read Level + Correct Factor.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.
4. All modes and channels have been tested, only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1 GHz



**TEST ENVIRONMENT**


| | | | |
|---------------------|---------|-------------------|-----|
| Temperature | 24.3°C | Relative Humidity | 61% |
| Atmosphere Pressure | 1010kPa | Test Voltage | |

TEST RESULTS



8.1. BANDEDGE


| | | | |
|------------|------------|---------------|----------|
| Test Mode: | GFSK PK | Channel: | 2402 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 2390.000 | 13.09 | 32.66 | 45.75 | 74.00 | -28.25 | peak |




| | | | |
|------------|----------|---------------|----------|
| Test Mode: | GFSK PK | Channel: | 2402 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 2390.000 | 13.30 | 32.66 | 45.96 | 74.00 | -28.04 | peak |




| | | | |
|------------|------------|---------------|----------|
| Test Mode: | GFSK PK | Channel: | 2480 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 2483.500 | 15.20 | 33.10 | 48.30 | 74.00 | -25.70 | peak |




| | | | |
|------------|------------|---------------|----------|
| Test Mode: | 8DPSK PK | Channel: | 2402 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 2390.000 | 13.53 | 32.66 | 46.19 | 74.00 | -27.81 | peak |



| | | | |
|------------|------------|---------------|----------|
| Test Mode: | 8DPSK PK | Channel: | 2480 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 2483.500 | 14.75 | 33.10 | 47.85 | 74.00 | -26.15 | peak |



8.2. RADIATE SPURIOUS EMISSION


| 1GHz-3GHz | | | |
|------------|------------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2402 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1 | 1100.000 | 51.63 | -14.39 | 37.24 | 74.00 | -36.76 | peak |
| 2 | 1442.000 | 54.09 | -12.79 | 41.30 | 74.00 | -32.70 | peak |
| 3 | 1592.000 | 49.24 | -11.90 | 37.34 | 74.00 | -36.66 | peak |
| 4 | 2222.000 | 44.15 | -9.62 | 34.53 | 74.00 | -39.47 | peak |
| 5 | 2402.000 | 52.45 | -8.94 | 43.51 | / | / | Fundamental |
| 6 | 2576.000 | 44.41 | -8.61 | 35.80 | 74.00 | -38.20 | peak |




| 1GHz-3GHz | | | |
|------------|----------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2402 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1 | 1180.000 | 50.99 | -13.85 | 37.14 | 74.00 | -36.86 | peak |
| 2 | 1440.000 | 51.21 | -12.79 | 38.42 | 74.00 | -35.58 | peak |
| 3 | 1618.000 | 53.71 | -11.74 | 41.97 | 74.00 | -32.03 | peak |
| 4 | 1796.000 | 54.96 | -10.61 | 44.35 | 74.00 | -29.65 | peak |
| 5 | 1958.000 | 48.69 | -10.88 | 37.81 | 74.00 | -36.19 | peak |
| 6 | 2402.000 | 49.09 | -8.94 | 40.15 | / | / | Fundamental |




| 1GHz-3GHz | | | |
|------------|------------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2441 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1 | 1092.000 | 51.78 | -14.44 | 37.34 | 74.00 | -36.66 | peak |
| 2 | 1438.000 | 52.81 | -12.81 | 40.00 | 74.00 | -34.00 | peak |
| 3 | 1626.000 | 47.38 | -11.69 | 35.69 | 74.00 | -38.31 | peak |
| 4 | 2224.000 | 44.10 | -9.62 | 34.48 | 74.00 | -39.52 | peak |
| 5 | 2441.000 | 53.65 | -8.85 | 44.80 | / | / | Fundamental |
| 6 | 2774.000 | 43.15 | -7.79 | 35.36 | 74.00 | -38.64 | peak |




| 1GHz-3GHz | | | |
|------------|----------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2441 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1 | 1150.000 | 51.88 | -14.05 | 37.83 | 74.00 | -36.17 | peak |
| 2 | 1248.000 | 53.04 | -13.56 | 39.48 | 74.00 | -34.52 | peak |
| 3 | 1596.000 | 51.14 | -11.87 | 39.27 | 74.00 | -34.73 | peak |
| 4 | 1766.000 | 52.20 | -10.79 | 41.41 | 74.00 | -32.59 | peak |
| 5 | 2441.000 | 50.15 | -8.85 | 41.30 | / | / | Fundamental |
| 6 | 2594.000 | 47.92 | -8.57 | 39.35 | 74.00 | -34.65 | peak |




| 1GHz-3GHz | | | |
|------------|------------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2480 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1 | 1088.000 | 52.36 | -14.47 | 37.89 | 74.00 | -36.11 | peak |
| 2 | 1440.000 | 52.24 | -12.79 | 39.45 | 74.00 | -34.55 | peak |
| 3 | 1766.000 | 48.68 | -10.79 | 37.89 | 74.00 | -36.11 | peak |
| 4 | 2242.000 | 44.57 | -9.55 | 35.02 | 74.00 | -38.98 | peak |
| 5 | 2480.000 | 55.60 | -8.76 | 46.84 | / | / | Fundamental |
| 6 | 2708.000 | 43.62 | -8.08 | 35.54 | 74.00 | -38.46 | peak |




| 1GHz-3GHz | | | |
|------------|----------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2480 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|-------------|
| 1 | 1198.000 | 52.96 | -13.73 | 39.23 | 74.00 | -34.77 | peak |
| 2 | 1398.000 | 53.21 | -13.07 | 40.14 | 74.00 | -33.86 | peak |
| 3 | 1592.000 | 51.40 | -11.90 | 39.50 | 74.00 | -34.50 | peak |
| 4 | 1960.000 | 48.38 | -10.89 | 37.49 | 74.00 | -36.51 | peak |
| 5 | 2480.000 | 50.79 | -8.76 | 42.03 | / | / | Fundamental |
| 6 | 2598.000 | 47.29 | -8.57 | 38.72 | 74.00 | -35.28 | peak |




| 3GHz-18GHz | | | |
|------------|------------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2402 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4800.000 | 43.90 | -1.14 | 42.76 | 74.00 | -31.24 | peak |
| 2 | 7725.000 | 38.39 | 5.84 | 44.23 | 74.00 | -29.77 | peak |
| 3 | 9075.000 | 37.00 | 9.12 | 46.12 | 74.00 | -27.88 | peak |
| 4 | 11820.000 | 36.04 | 17.21 | 53.25 | 74.00 | -20.75 | peak |
| 5 | 13560.000 | 33.06 | 19.67 | 52.73 | 74.00 | -21.27 | peak |
| 6 | 17655.000 | 29.31 | 21.68 | 50.99 | 74.00 | -23.01 | peak |




| 3GHz-18GHz | | | |
|------------|----------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2402 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4800.000 | 40.51 | -1.14 | 39.37 | 74.00 | -34.63 | peak |
| 2 | 7710.000 | 38.07 | 5.80 | 43.87 | 74.00 | -30.13 | peak |
| 3 | 9060.000 | 37.03 | 9.20 | 46.23 | 74.00 | -27.77 | peak |
| 4 | 11685.000 | 35.69 | 16.49 | 52.18 | 74.00 | -21.82 | peak |
| 5 | 13905.000 | 32.19 | 20.57 | 52.76 | 74.00 | -21.24 | peak |
| 6 | 17985.000 | 27.60 | 23.64 | 51.24 | 74.00 | -22.76 | peak |




| 3GHz-18GHz | | | |
|------------|------------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2441 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4875.000 | 44.47 | -1.13 | 43.34 | 74.00 | -30.66 | peak |
| 2 | 8055.000 | 38.29 | 5.87 | 44.16 | 74.00 | -29.84 | peak |
| 3 | 8970.000 | 36.68 | 9.17 | 45.85 | 74.00 | -28.15 | peak |
| 4 | 11880.000 | 35.57 | 17.17 | 52.74 | 74.00 | -21.26 | peak |
| 5 | 13560.000 | 33.05 | 19.67 | 52.72 | 74.00 | -21.28 | peak |
| 6 | 17970.000 | 27.66 | 23.60 | 51.26 | 74.00 | -22.74 | peak |




| 3GHz-18GHz | | | |
|------------|----------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2441 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4875.000 | 41.77 | -1.13 | 40.64 | 74.00 | -33.36 | peak |
| 2 | 7275.000 | 37.40 | 5.36 | 42.76 | 74.00 | -31.24 | peak |
| 3 | 8985.000 | 36.93 | 9.34 | 46.27 | 74.00 | -27.73 | peak |
| 4 | 11835.000 | 35.63 | 17.20 | 52.83 | 74.00 | -21.17 | peak |
| 5 | 13980.000 | 32.49 | 20.63 | 53.12 | 74.00 | -20.88 | peak |
| 6 | 17715.000 | 29.61 | 22.31 | 51.92 | 74.00 | -22.08 | peak |




| 3GHz-18GHz | | | |
|------------|------------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2480 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4860.000 | 40.29 | -1.14 | 39.15 | 74.00 | -34.85 | peak |
| 2 | 8055.000 | 38.67 | 5.87 | 44.54 | 74.00 | -29.46 | peak |
| 3 | 9000.000 | 36.63 | 9.53 | 46.16 | 74.00 | -27.84 | peak |
| 4 | 11775.000 | 35.39 | 17.06 | 52.45 | 74.00 | -21.55 | peak |
| 5 | 13515.000 | 33.15 | 19.60 | 52.75 | 74.00 | -21.25 | peak |
| 6 | 17700.000 | 29.64 | 22.15 | 51.79 | 74.00 | -22.21 | peak |




| 3GHz-18GHz | | | |
|------------|----------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2480 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 3180.000 | 48.80 | -6.66 | 42.14 | 74.00 | -31.86 | peak |
| 2 | 7605.000 | 38.06 | 5.45 | 43.51 | 74.00 | -30.49 | peak |
| 3 | 9000.000 | 36.72 | 9.53 | 46.25 | 74.00 | -27.75 | peak |
| 4 | 11880.000 | 35.19 | 17.17 | 52.36 | 74.00 | -21.64 | peak |
| 5 | 13950.000 | 32.50 | 20.61 | 53.11 | 74.00 | -20.89 | peak |
| 6 | 18000.000 | 27.38 | 23.68 | 51.06 | 74.00 | -22.94 | peak |




| 3GHz-18GHz | | | |
|------------|------------|---------------|----------|
| Test Mode: | 8DPSK | Channel: | 2402 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4800.000 | 44.63 | -1.14 | 43.49 | 74.00 | -30.51 | peak |
| 2 | 7890.000 | 38.40 | 5.75 | 44.15 | 74.00 | -29.85 | peak |
| 3 | 9075.000 | 37.87 | 9.12 | 46.99 | 74.00 | -27.01 | peak |
| 4 | 11835.000 | 35.74 | 17.20 | 52.94 | 74.00 | -21.06 | peak |
| 5 | 13995.000 | 31.09 | 20.63 | 51.72 | 74.00 | -22.28 | peak |
| 6 | 18000.000 | 27.52 | 23.68 | 51.20 | 74.00 | -22.80 | peak |




| 3GHz-18GHz | | | |
|------------|----------|---------------|----------|
| Test Mode: | 8DPSK | Channel: | 2402 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4995.000 | 41.64 | -1.12 | 40.52 | 74.00 | -33.48 | peak |
| 2 | 7710.000 | 38.44 | 5.80 | 44.24 | 74.00 | -29.76 | peak |
| 3 | 8955.000 | 37.63 | 8.99 | 46.62 | 74.00 | -27.38 | peak |
| 4 | 11820.000 | 35.21 | 17.21 | 52.42 | 74.00 | -21.58 | peak |
| 5 | 13995.000 | 31.50 | 20.63 | 52.13 | 74.00 | -21.87 | peak |
| 6 | 17220.000 | 31.97 | 20.16 | 52.13 | 74.00 | -21.87 | peak |




| 3GHz-18GHz | | | |
|------------|------------|---------------|----------|
| Test Mode: | 8DPSK | Channel: | 2441 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4875.000 | 46.96 | -1.13 | 45.83 | 74.00 | -28.17 | peak |
| 2 | 7890.000 | 38.68 | 5.75 | 44.43 | 74.00 | -29.57 | peak |
| 3 | 9585.000 | 35.73 | 10.11 | 45.84 | 74.00 | -28.16 | peak |
| 4 | 11805.000 | 34.69 | 17.21 | 51.90 | 74.00 | -22.10 | peak |
| 5 | 13920.000 | 32.58 | 20.58 | 53.16 | 74.00 | -20.84 | peak |
| 6 | 17985.000 | 27.34 | 23.64 | 50.98 | 74.00 | -23.02 | peak |




| 3GHz-18GHz | | | |
|------------|----------|---------------|----------|
| Test Mode: | 8DPSK | Channel: | 2441 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4875.000 | 42.81 | -1.13 | 41.68 | 74.00 | -32.32 | peak |
| 2 | 8220.000 | 38.36 | 7.17 | 45.53 | 74.00 | -28.47 | peak |
| 3 | 8985.000 | 37.25 | 9.34 | 46.59 | 74.00 | -27.41 | peak |
| 4 | 11805.000 | 36.27 | 17.21 | 53.48 | 74.00 | -20.52 | peak |
| 5 | 13605.000 | 32.36 | 19.74 | 52.10 | 74.00 | -21.90 | peak |
| 6 | 17760.000 | 28.73 | 22.77 | 51.50 | 74.00 | -22.50 | peak |




| 3GHz-18GHz | | | |
|------------|------------|---------------|----------|
| Test Mode: | 8DPSK | Channel: | 2480 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4665.000 | 40.65 | -1.72 | 38.93 | 74.00 | -35.07 | peak |
| 2 | 8175.000 | 37.11 | 6.99 | 44.10 | 74.00 | -29.90 | peak |
| 3 | 9000.000 | 36.67 | 9.53 | 46.20 | 74.00 | -27.80 | peak |
| 4 | 11835.000 | 35.46 | 17.20 | 52.66 | 74.00 | -21.34 | peak |
| 5 | 13575.000 | 32.69 | 19.69 | 52.38 | 74.00 | -21.62 | peak |
| 6 | 17940.000 | 28.18 | 23.54 | 51.72 | 74.00 | -22.28 | peak |




| 3GHz-18GHz | | | |
|------------|----------|---------------|----------|
| Test Mode: | 8DPSK | Channel: | 2480 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 3195.000 | 48.58 | -6.62 | 41.96 | 74.00 | -32.04 | peak |
| 2 | 6375.000 | 43.21 | 2.39 | 45.60 | 74.00 | -28.40 | peak |
| 3 | 9060.000 | 37.28 | 9.20 | 46.48 | 74.00 | -27.52 | peak |
| 4 | 11820.000 | 34.34 | 17.21 | 51.55 | 74.00 | -22.45 | peak |
| 5 | 13590.000 | 32.44 | 19.70 | 52.14 | 74.00 | -21.86 | peak |
| 6 | 17955.000 | 28.02 | 23.57 | 51.59 | 74.00 | -22.41 | peak |




| 9 kHz-150 kHz | | | |
|---------------|------------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2402 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | FCC Result (dBuV/m) | FCC Limit (dBuV/m) | ISED Result (dBuA/m) | ISED Limit (dBuA/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|---------------------------|--------------------------|----------------------------|---------------------------|----------------|--------|
| 1 | 0.0106 | 73.88 | -101.39 | -27.51 | 47.09 | -79.01 | -4.41 | -74.60 | peak |
| 2 | 0.0171 | 68.88 | -101.36 | -32.48 | 42.94 | -83.98 | -8.56 | -75.42 | peak |
| 3 | 0.0279 | 66.67 | -101.38 | -34.71 | 38.69 | -86.21 | -12.81 | -73.40 | peak |
| 4 | 0.0427 | 61.64 | -101.45 | -39.81 | 34.99 | -91.31 | -16.51 | -74.80 | peak |
| 5 | 0.0636 | 60.31 | -101.54 | -41.23 | 31.53 | -92.73 | -19.97 | -72.76 | peak |
| 6 | 0.0981 | 58.27 | -101.78 | -43.51 | 27.77 | -95.01 | -23.73 | -71.28 | peak |




| 150 kHz-490 kHz | | | |
|-----------------|------------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2402 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | FCC Result (dBuV/m) | FCC Limit (dBuV/m) | ISED Result (dBuA/m) | ISED Limit (dBuA/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|---------------------------|--------------------------|----------------------------|---------------------------|----------------|--------|
| 1 | 0.1595 | 74.36 | -101.65 | -27.29 | 23.55 | -78.79 | -27.95 | -50.84 | peak |
| 2 | 0.2190 | 67.27 | -101.75 | -34.48 | 20.79 | -85.98 | -30.71 | -55.27 | peak |
| 3 | 0.2782 | 62.29 | -101.83 | -39.54 | 18.71 | -91.04 | -32.79 | -58.25 | peak |
| 4 | 0.3431 | 60.17 | -101.90 | -41.73 | 16.89 | -93.23 | -34.61 | -58.62 | peak |
| 5 | 0.3800 | 58.52 | -101.94 | -43.42 | 16.01 | -94.92 | -35.49 | -59.43 | peak |
| 6 | 0.4364 | 56.86 | -101.99 | -45.13 | 14.8 | -96.63 | -36.70 | -59.93 | peak |




| 490 kHz-30 MHz | | | |
|----------------|------------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2402 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | FCC Result (dBuV/m) | FCC Limit (dBuV/m) | ISED Result (dBuA/m) | ISED Limit (dBuA/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------|---------------------------|-----------------------|----------------------------|---------------------------|----------------|--------|
| 1 | 0.6671 | 62.75 | -62.10 | 0.65 | 31.12 | -50.85 | -20.38 | -30.47 | peak |
| 2 | 1.3810 | 57.47 | -62.10 | -4.63 | 24.80 | -56.13 | -26.70 | -29.43 | peak |
| 3 | 3.7100 | 54.20 | -61.41 | -7.21 | 29.54 | -58.71 | -21.96 | -36.75 | peak |
| 4 | 6.2445 | 54.13 | -61.32 | -7.19 | 29.54 | -58.69 | -21.96 | -36.73 | peak |
| 5 | 10.7299 | 53.48 | -60.83 | -7.35 | 29.54 | -58.85 | -21.96 | -36.89 | peak |
| 6 | 25.8978 | 52.76 | -60.36 | -7.60 | 29.54 | -59.10 | -21.96 | -37.14 | peak |




| 18GHz-26GHz | | | |
|-------------|------------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2402 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 18144.000 | 50.77 | -5.48 | 45.29 | 74.00 | -28.71 | peak |
| 2 | 19392.000 | 50.12 | -5.57 | 44.55 | 74.00 | -29.45 | peak |
| 3 | 19888.000 | 50.07 | -5.36 | 44.71 | 74.00 | -29.29 | peak |
| 4 | 22160.000 | 48.58 | -4.31 | 44.27 | 74.00 | -29.73 | peak |
| 5 | 23744.000 | 48.65 | -3.20 | 45.45 | 74.00 | -28.55 | peak |
| 6 | 24960.000 | 47.14 | -2.14 | 45.00 | 74.00 | -29.00 | peak |




| 18GHz-26GHz | | | |
|-------------|----------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2402 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 18536.000 | 49.10 | -5.27 | 43.83 | 74.00 | -30.17 | peak |
| 2 | 19800.000 | 49.77 | -5.29 | 44.48 | 74.00 | -29.52 | peak |
| 3 | 20240.000 | 49.82 | -5.61 | 44.21 | 74.00 | -29.79 | peak |
| 4 | 21544.000 | 48.26 | -4.63 | 43.63 | 74.00 | -30.37 | peak |
| 5 | 24376.000 | 46.62 | -2.57 | 44.05 | 74.00 | -29.95 | peak |
| 6 | 25312.000 | 46.70 | -1.70 | 45.00 | 74.00 | -29.00 | peak |




| 30Mhz-1GHz | | | |
|------------|------------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2402 |
| Polarity: | Horizontal | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 117.3000 | 57.10 | -20.03 | 37.07 | 43.50 | -6.43 | QP |
| 2 | 318.0900 | 44.89 | -14.83 | 30.06 | 46.00 | -15.94 | QP |
| 3 | 479.1100 | 44.01 | -11.82 | 32.19 | 46.00 | -13.81 | QP |
| 4 | 708.0300 | 39.50 | -8.26 | 31.24 | 46.00 | -14.76 | QP |
| 5 | 816.6700 | 40.32 | -6.98 | 33.34 | 46.00 | -12.66 | QP |
| 6 | 983.5100 | 41.98 | -4.32 | 37.66 | 54.00 | -16.34 | QP |



| 30MHz-1GHz | | | |
|------------|----------|---------------|----------|
| Test Mode: | GFSK | Channel: | 2402 |
| Polarity: | Vertical | Test Voltage: | DC 3.3 V |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 115.3600 | 51.38 | -20.15 | 31.23 | 43.50 | -12.27 | QP |
| 2 | 437.4000 | 40.27 | -12.60 | 27.67 | 46.00 | -18.33 | QP |
| 3 | 481.0500 | 42.94 | -11.78 | 31.16 | 46.00 | -14.84 | QP |
| 4 | 799.2100 | 36.89 | -7.33 | 29.56 | 46.00 | -16.44 | QP |
| 5 | 854.5000 | 37.98 | -6.14 | 31.84 | 46.00 | -14.16 | QP |
| 6 | 998.0600 | 41.64 | -4.18 | 37.46 | 54.00 | -16.54 | QP |



9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

N/A

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

| FREQUENCY (MHz) | Quasi-peak | Average |
|-----------------|------------|-----------|
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * |
| 0.50 -5.0 | 56.00 | 46.00 |
| 5.0 -30.0 | 60.00 | 50.00 |

TEST PROCEDURE


TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP




**TEST ENVIRONMENT**

| | | | |
|---------------------|--------|-------------------|----------|
| Temperature | 25.9°C | Relative Humidity | 63.7% |
| Atmosphere Pressure | 101kPa | Test Voltage | AC 120 V |

TEST RESULTS

| | | | |
|------------|------|----------|------|
| Test Mode: | GFSK | Channel: | 2402 |
| Line: | Line | | |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|-----|-----------------|----------------|--------------|---------------|--------------|-------------|--------|
| 1 | 0.1621 | 37.47 | 9.59 | 47.06 | 65.36 | -18.30 | QP |
| 2 | 0.1621 | 12.60 | 9.59 | 22.19 | 55.36 | -33.17 | AVG |
| 3 | 0.2693 | 27.99 | 9.52 | 37.51 | 61.14 | -23.63 | QP |
| 4 | 0.2693 | 11.48 | 9.52 | 21.00 | 51.14 | -30.14 | AVG |
| 5 | 0.3822 | 20.48 | 9.41 | 29.89 | 58.23 | -28.34 | QP |
| 6 | 0.3822 | 5.03 | 9.41 | 14.44 | 48.23 | -33.79 | AVG |
| 7 | 3.4984 | 21.51 | 9.61 | 31.12 | 56.00 | -24.88 | QP |
| 8 | 3.4984 | 13.17 | 9.61 | 22.78 | 46.00 | -23.22 | AVG |
| 9 | 5.0021 | 22.45 | 9.62 | 32.07 | 60.00 | -27.93 | QP |
| 10 | 5.0021 | 14.89 | 9.62 | 24.51 | 50.00 | -25.49 | AVG |
| 11 | 17.8672 | 27.71 | 9.74 | 37.45 | 60.00 | -22.55 | QP |
| 12 | 17.8672 | 22.45 | 9.74 | 32.19 | 50.00 | -17.81 | AVG |

Note: 1. Result = Reading + Correct Factor.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.



| | | | |
|------------|---------|----------|------|
| Test Mode: | GFSK | Channel: | 2402 |
| Line: | Neutral | | |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|-----|-----------------|----------------|--------------|---------------|--------------|-------------|--------|
| 1 | 0.1757 | 38.35 | 9.59 | 47.94 | 64.69 | -16.75 | QP |
| 2 | 0.1757 | 24.95 | 9.59 | 34.54 | 54.69 | -20.15 | AVG |
| 3 | 0.3062 | 25.10 | 9.48 | 34.58 | 60.07 | -25.49 | QP |
| 4 | 0.3062 | 14.78 | 9.48 | 24.26 | 50.07 | -25.81 | AVG |
| 5 | 1.6827 | 23.21 | 9.62 | 32.83 | 56.00 | -23.17 | QP |
| 6 | 1.6827 | 14.02 | 9.62 | 23.64 | 46.00 | -22.36 | AVG |
| 7 | 3.7947 | 23.57 | 9.61 | 33.18 | 56.00 | -22.82 | QP |
| 8 | 3.7947 | 12.57 | 9.61 | 22.18 | 46.00 | -23.82 | AVG |
| 9 | 4.8087 | 20.68 | 9.61 | 30.29 | 56.00 | -25.71 | QP |
| 10 | 4.8087 | 13.71 | 9.61 | 23.32 | 46.00 | -22.68 | AVG |
| 11 | 17.9318 | 26.19 | 9.74 | 35.93 | 60.00 | -24.07 | QP |
| 12 | 17.9318 | 20.98 | 9.74 | 30.72 | 50.00 | -19.28 | AVG |

- Note: 1. Result = Reading + Correct Factor.
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
 4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.




11. ST DATA


11.1. APPENDIX A: 20DB EMISSION BANDWIDTH

11.1.1. Test Result


| Test Mode | Antenna | Channel | 20db EBW[MHz] | FL[MHz] | FH[MHz] | Verdict |
|-----------|---------|---------|---------------|---------|---------|---------|
| DH5 | Ant1 | 2402 | 0.95 | 2401.54 | 2402.48 | PASS |
| | | 2441 | 0.95 | 2440.54 | 2441.48 | PASS |
| | | 2480 | 0.95 | 2479.54 | 2480.48 | PASS |
| 3DH5 | Ant1 | 2402 | 1.26 | 2401.36 | 2402.62 | PASS |
| | | 2441 | 1.26 | 2440.36 | 2441.62 | PASS |
| | | 2480 | 1.26 | 2479.36 | 2480.62 | PASS |

11.1.2. Test Graphs






3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480





11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH

11.2.1. Test Result


| Test Mode | Antenna | Channel | OCB [MHz] | FL[MHz] | FH[MHz] | Verdict |
|-----------|---------|---------|-----------|----------|----------|---------|
| DH5 | Ant1 | 2402 | 0.869 | 2401.562 | 2402.432 | PASS |
| | | 2441 | 0.875 | 2440.559 | 2441.435 | PASS |
| | | 2480 | 0.872 | 2479.559 | 2480.432 | PASS |
| 3DH5 | Ant1 | 2402 | 1.172 | 2401.413 | 2402.584 | PASS |
| | | 2441 | 1.172 | 2440.413 | 2441.584 | PASS |
| | | 2480 | 1.172 | 2479.413 | 2480.584 | PASS |

11.2.2. Test Graphs






3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



11.3. APPENDIX C: MAXIMUM CONDUCTED PEAK OUTPUT POWER

11.3.1. Test Result

| Test Mode | Antenna | Channel | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| DH5 | Ant1 | 2402 | 8.31 | ≤30 | PASS |
| | | 2441 | 7.49 | ≤30 | PASS |
| | | 2480 | 6.42 | ≤30 | PASS |
| 3DH5 | Ant1 | 2402 | 10.15 | ≤20.97 | PASS |
| | | 2441 | 9.39 | ≤20.97 | PASS |
| | | 2480 | 8.33 | ≤20.97 | PASS |




11.4. APPENDIX D: CARRIER FREQUENCY SEPARATION

11.4.1. Test Result

| Test Mode | Antenna | Channel | Result[MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| DH5 | Ant1 | Hop | 1.003 | ≥0.950 | PASS |
| 3DH5 | Ant1 | Hop | 1.009 | ≥0.840 | PASS |

11.4.2. Test Graphs






11.5. APPENDIX E: TIME OF OCCUPANCY


11.5.1. Test Result

| FHSS Mode | | | | | | |
|-----------|---------|---------|-----------------|-----------|------------|---------|
| Test Mode | Antenna | Channel | BurstWidth [ms] | Result[s] | Limit[s] | Verdict |
| DH1 | Ant1 | Hop | 0.38 | 0.122 | ≤ 0.4 | PASS |
| DH3 | Ant1 | Hop | 1.63 | 0.261 | ≤ 0.4 | PASS |
| DH5 | Ant1 | Hop | 2.87 | 0.306 | ≤ 0.4 | PASS |
| 3DH1 | Ant1 | Hop | 0.39 | 0.125 | ≤ 0.4 | PASS |
| 3DH3 | Ant1 | Hop | 1.63 | 0.261 | ≤ 0.4 | PASS |
| 3DH5 | Ant1 | Hop | 2.87 | 0.306 | ≤ 0.4 | PASS |


| AFHSS Mode | | | | | | |
|------------|---------|---------|-----------------|-----------|------------|---------|
| Test Mode | Antenna | Channel | BurstWidth [ms] | Result[s] | Limit[s] | Verdict |
| DH1 | Ant1 | Hop | 0.38 | 0.061 | ≤ 0.4 | PASS |
| DH3 | Ant1 | Hop | 1.63 | 0.130 | ≤ 0.4 | PASS |
| DH5 | Ant1 | Hop | 2.87 | 0.153 | ≤ 0.4 | PASS |
| 3DH1 | Ant1 | Hop | 0.39 | 0.062 | ≤ 0.4 | PASS |
| 3DH3 | Ant1 | Hop | 1.63 | 0.130 | ≤ 0.4 | PASS |
| 3DH5 | Ant1 | Hop | 2.87 | 0.153 | ≤ 0.4 | PASS |

11.5.2. Test Graphs






3DH1_Ant1_Hop



3DH3_Ant1_Hop



3DH5_Ant1_Hop




11.6. APPENDIX F: NUMBER OF HOPPING CHANNELS

11.6.1. Test Result

| Test Mode | Antenna | Channel | Result[Num] | Limit[Num] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| DH5 | Ant1 | Hop | 79 | ≥ 15 | PASS |
| 3DH5 | Ant1 | Hop | 79 | ≥ 15 | PASS |

11.6.2. Test Graphs






11.7. APPENDIX G: BAND EDGE MEASUREMENTS


11.7.1. Test Result

| Test Mode | Antenna | ChName | Channel | RefLevel [dBm] | Result [dBm] | Limit [dBm] | Verdict |
|-----------|---------|--------|----------|----------------|--------------|---------------|---------|
| DH5 | Ant1 | Low | 2402 | 8.09 | -45.96 | ≤ -11.91 | PASS |
| | | High | 2480 | 6.22 | -44.85 | ≤ -13.78 | PASS |
| | | Low | Hop_2402 | 7.53 | -46.06 | ≤ -12.47 | PASS |
| | | High | Hop_2480 | 6.35 | -44.63 | ≤ -13.65 | PASS |
| 3DH5 | Ant1 | Low | 2402 | 8.08 | -44.95 | ≤ -11.92 | PASS |
| | | High | 2480 | 6.14 | -44.29 | ≤ -13.86 | PASS |
| | | Low | Hop_2402 | 7.93 | -45.44 | ≤ -12.07 | PASS |
| | | High | Hop_2480 | 6.42 | -44.19 | ≤ -13.58 | PASS |


11.7.2. Test Graphs




DH5_Ant1_Low_2402




DH5_Ant1_High_2480




DH5_Ant1_Low_Hop_2402





DH5_Ant1_High_Hop_2480



3DH5_Ant1_Low_2402




3DH5_Ant1_High_2480




**11.8. APPENDIX H: CONDUCTED SPURIOUS EMISSION****11.8.1. Test Result**


| Test Mode | Antenna | Channel | FreqRange [MHz] | Result [dBm] | Limit [dBm] | Verdict |
|-----------|---------|---------|-----------------|--------------|---------------|---------|
| DH5 | Ant1 | 2402 | Reference | 8.16 | --- | PASS |
| | | | 30~1000 | -54.08 | ≤ -11.84 | PASS |
| | | | 1000~26500 | -49.75 | ≤ -11.84 | PASS |
| | | 2441 | Reference | 7.33 | --- | PASS |
| | | | 30~1000 | -54.45 | ≤ -12.67 | PASS |
| | | | 1000~26500 | -48.83 | ≤ -12.67 | PASS |
| | | 2480 | Reference | 6.26 | --- | PASS |
| | | | 30~1000 | -53.81 | ≤ -13.74 | PASS |
| | | | 1000~26500 | -49.62 | ≤ -13.74 | PASS |
| 3DH5 | Ant1 | 2402 | Reference | 8.09 | --- | PASS |
| | | | 30~1000 | -53.93 | ≤ -11.91 | PASS |
| | | | 1000~26500 | -49.33 | ≤ -11.91 | PASS |
| | | 2441 | Reference | 7.27 | --- | PASS |
| | | | 30~1000 | -54.69 | ≤ -12.73 | PASS |
| | | | 1000~26500 | -49.41 | ≤ -12.73 | PASS |
| | | 2480 | Reference | 6.18 | --- | PASS |
| | | | 30~1000 | -54.82 | ≤ -13.82 | PASS |
| | | | 1000~26500 | -48.9 | ≤ -13.82 | PASS |

11.8.2. Test Graphs







DH5_Ant1_2441_0~Reference




DH5_Ant1_2441_30~1000




DH5_Ant1_2441_1000~26500




DH5_Ant1_2480_0~Reference




DH5_Ant1_2480_30~1000




DH5_Ant1_2480_1000~26500




3DH5_Ant1_2402_0~Reference




3DH5_Ant1_2402_30~100




3DH5_Ant1_2402_1000~26500




3DH5_Ant1_2441_0~Reference




3DH5_Ant1_2441_30~100




3DH5_Ant1_2441_1000~26500



3DH5_Ant1_2480_0~Reference



3DH5_Ant1_2480_30~100



3DH5_Ant1_2480_1000~26500



11.9. APPENDIX I: DUTY CYCLE

11.9.1. Test Result

| Test Mode | On Time (msec) | Period (msec) | Duty Cycle x (Linear) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) | 1/T Minimum VBW (kHz) | Final setting For VBW (kHz) |
|-----------|----------------|---------------|-----------------------|----------------|-----------------------------------|-----------------------|-----------------------------|
| DH5 | 2.87 | 3.71 | 0.7736 | 77.36 | 1.11 | 0.35 | 0.5 |
| 3DH5 | 2.88 | 3.72 | 0.7742 | 77.42 | 1.11 | 0.35 | 0.5 |

Note:


Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)


Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

11.9.2. Test Graphs



DH5_Ant1_2441



3DH5_Ant1_2441

END OF REPORT