



Test Mode:	802.11n HT20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	36.51	11.57	48.08	74.00	-25.92	peak
2	10333.000	35.65	12.93	48.58	74.00	-25.42	peak
3	11389.000	32.37	16.51	48.88	74.00	-25.12	peak
4	12643.000	29.90	18.43	48.33	74.00	-25.67	peak
5	14194.000	28.34	21.96	50.30	74.00	-23.70	peak
6	17769.000	24.38	25.76	50.14	74.00	-23.86	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7891.000	37.36	6.85	44.21	74.00	-29.79	peak
2	8991.000	36.36	11.73	48.09	74.00	-25.91	peak
3	10443.000	35.36	13.35	48.71	74.00	-25.29	peak
4	11884.000	30.81	18.00	48.81	74.00	-25.19	peak
5	13930.000	28.06	22.50	50.56	74.00	-23.44	peak
6	17967.000	23.09	26.83	49.92	74.00	-24.08	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5200
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	35.70	11.73	47.43	74.00	-26.57	peak
2	10399.000	34.95	13.23	48.18	74.00	-25.82	peak
3	11389.000	32.82	16.51	49.33	74.00	-24.67	peak
4	12269.000	29.48	18.72	48.20	74.00	-25.80	peak
5	13919.000	27.06	22.49	49.55	74.00	-24.45	peak
6	17912.000	22.76	26.60	49.36	74.00	-24.64	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5200
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8221.000	37.36	8.53	45.89	74.00	-28.11	peak
2	8947.000	36.54	11.08	47.62	74.00	-26.38	peak
3	10311.000	35.25	12.83	48.08	74.00	-25.92	peak
4	11532.000	32.79	16.93	49.72	74.00	-24.28	peak
5	13864.000	26.06	22.45	48.51	74.00	-25.49	peak
6	17967.000	22.43	26.83	49.26	74.00	-24.74	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8474.000	37.29	8.24	45.53	74.00	-28.47	peak
2	8958.000	36.39	11.24	47.63	74.00	-26.37	peak
3	10300.000	35.63	12.78	48.41	74.00	-25.59	peak
4	11664.000	30.73	17.19	47.92	74.00	-26.08	peak
5	13633.000	27.11	21.59	48.70	74.00	-25.30	peak
6	17989.000	22.65	26.92	49.57	74.00	-24.43	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5240
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	35.94	11.73	47.67	74.00	-26.33	peak
2	10036.000	35.78	12.20	47.98	74.00	-26.02	peak
3	11708.000	31.54	17.31	48.85	74.00	-25.15	peak
4	13908.000	26.60	22.49	49.09	74.00	-24.91	peak
5	17384.000	24.17	23.34	47.51	74.00	-26.49	peak
6	17956.000	22.75	26.78	49.53	74.00	-24.47	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9255.000	37.27	10.22	47.49	74.00	-26.51	peak
2	10421.000	35.42	13.29	48.71	74.00	-25.29	peak
3	11070.000	34.69	15.04	49.73	74.00	-24.27	peak
4	13655.000	27.66	21.69	49.35	74.00	-24.65	peak
5	14403.000	27.49	20.77	48.26	74.00	-25.74	peak
6	18000.000	23.64	26.97	50.61	74.00	-23.39	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5260
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	36.40	11.73	48.13	74.00	-25.87	peak
2	11510.000	33.00	16.90	49.90	74.00	-24.10	peak
3	12170.000	30.55	18.58	49.13	74.00	-24.87	peak
4	13963.000	26.84	22.51	49.35	74.00	-24.65	peak
5	16988.000	25.45	21.60	47.05	74.00	-26.95	peak
6	17945.000	23.00	26.74	49.74	74.00	-24.26	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5280
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	35.94	11.57	47.51	74.00	-26.49	peak
2	10421.000	34.94	13.29	48.23	74.00	-25.77	peak
3	11433.000	32.18	16.68	48.86	74.00	-25.14	peak
4	13875.000	27.50	22.46	49.96	74.00	-24.04	peak
5	14777.000	28.88	19.30	48.18	74.00	-25.82	peak
6	17923.000	23.95	26.64	50.59	74.00	-23.41	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5280
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7341.000	36.76	8.00	44.76	74.00	-29.24	peak
2	9200.000	37.78	10.04	47.82	74.00	-26.18	peak
3	10245.000	36.43	12.54	48.97	74.00	-25.03	peak
4	11917.000	30.81	18.16	48.97	74.00	-25.03	peak
5	13875.000	27.73	22.46	50.19	74.00	-23.81	peak
6	18000.000	23.18	26.97	50.15	74.00	-23.85	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	35.60	11.73	47.33	74.00	-26.67	peak
2	10916.000	34.86	14.45	49.31	74.00	-24.69	peak
3	11433.000	32.35	16.68	49.03	74.00	-24.97	peak
4	13930.000	26.97	22.50	49.47	74.00	-24.53	peak
5	17263.000	24.93	22.92	47.85	74.00	-26.15	peak
6	17989.000	22.14	26.92	49.06	74.00	-24.94	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5320
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	36.50	11.57	48.07	74.00	-25.93	peak
2	10553.000	34.75	13.64	48.39	74.00	-25.61	peak
3	11400.000	32.71	16.57	49.28	74.00	-24.72	peak
4	12665.000	31.03	18.48	49.51	74.00	-24.49	peak
5	13897.000	27.82	22.47	50.29	74.00	-23.71	peak
6	17989.000	23.38	26.92	50.30	74.00	-23.70	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7352.000	36.78	8.07	44.85	74.00	-29.15	peak
2	9057.000	36.20	11.35	47.55	74.00	-26.45	peak
3	11455.000	31.58	16.74	48.32	74.00	-25.68	peak
4	11884.000	30.24	18.00	48.24	74.00	-25.76	peak
5	13908.000	26.74	22.49	49.23	74.00	-24.77	peak
6	17978.000	22.50	26.88	49.38	74.00	-24.62	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5500
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9079.000	36.38	11.15	47.53	74.00	-26.47	peak
2	11411.000	32.42	16.60	49.02	74.00	-24.98	peak
3	12247.000	30.12	18.68	48.80	74.00	-25.20	peak
4	13919.000	27.87	22.49	50.36	74.00	-23.64	peak
5	14436.000	28.01	20.63	48.64	74.00	-25.36	peak
6	17945.000	23.81	26.74	50.55	74.00	-23.45	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5580
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	36.08	11.73	47.81	74.00	-26.19	peak
2	10300.000	35.27	12.78	48.05	74.00	-25.95	peak
3	11785.000	31.05	17.52	48.57	74.00	-25.43	peak
4	13589.000	28.30	21.41	49.71	74.00	-24.29	peak
5	16900.000	26.65	21.40	48.05	74.00	-25.95	peak
6	17956.000	23.22	26.78	50.00	74.00	-24.00	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5580
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	36.56	10.91	47.47	74.00	-26.53	peak
2	10454.000	34.80	13.38	48.18	74.00	-25.82	peak
3	11400.000	32.62	16.57	49.19	74.00	-24.81	peak
4	13017.000	29.34	19.18	48.52	74.00	-25.48	peak
5	13853.000	27.35	22.46	49.81	74.00	-24.19	peak
6	17703.000	25.32	25.01	50.33	74.00	-23.67	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	35.86	11.57	47.43	74.00	-26.57	peak
2	10498.000	35.41	13.50	48.91	74.00	-25.09	peak
3	11400.000	32.64	16.57	49.21	74.00	-24.79	peak
4	12225.000	29.88	18.63	48.51	74.00	-25.49	peak
5	13963.000	27.40	22.51	49.91	74.00	-24.09	peak
6	17945.000	23.34	26.74	50.08	74.00	-23.92	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5700
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7869.000	37.76	6.85	44.61	74.00	-29.39	peak
2	8958.000	36.33	11.24	47.57	74.00	-26.43	peak
3	10465.000	35.35	13.41	48.76	74.00	-25.24	peak
4	11884.000	30.94	18.00	48.94	74.00	-25.06	peak
5	13864.000	27.34	22.45	49.79	74.00	-24.21	peak
6	17934.000	23.09	26.69	49.78	74.00	-24.22	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5720
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7341.000	36.61	8.00	44.61	74.00	-29.39	peak
2	8991.000	35.25	11.73	46.98	74.00	-27.02	peak
3	10344.000	34.93	12.98	47.91	74.00	-26.09	peak
4	11070.000	34.21	15.04	49.25	74.00	-24.75	peak
5	13886.000	27.14	22.48	49.62	74.00	-24.38	peak
6	17934.000	24.01	26.69	50.70	74.00	-23.30	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5720
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9354.000	37.40	10.53	47.93	74.00	-26.07	peak
2	10421.000	35.69	13.29	48.98	74.00	-25.02	peak
3	11796.000	31.64	17.55	49.19	74.00	-24.81	peak
4	13820.000	27.11	22.43	49.54	74.00	-24.46	peak
5	17296.000	24.30	23.04	47.34	74.00	-26.66	peak
6	17945.000	23.03	26.74	49.77	74.00	-24.23	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	36.14	11.57	47.71	74.00	-26.29	peak
2	10223.000	35.73	12.44	48.17	74.00	-25.83	peak
3	11323.000	31.96	16.10	48.06	74.00	-25.94	peak
4	12236.000	29.52	18.66	48.18	74.00	-25.82	peak
5	13864.000	27.37	22.45	49.82	74.00	-24.18	peak
6	17934.000	23.69	26.69	50.38	74.00	-23.62	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9376.000	37.36	10.60	47.96	74.00	-26.04	peak
2	10311.000	35.20	12.83	48.03	74.00	-25.97	peak
3	11873.000	30.13	17.94	48.07	74.00	-25.93	peak
4	13919.000	27.44	22.49	49.93	74.00	-24.07	peak
5	17714.000	25.12	25.14	50.26	74.00	-23.74	peak
6	18000.000	23.67	26.97	50.64	74.00	-23.36	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8925.000	37.63	10.75	48.38	74.00	-25.62	peak
2	11059.000	33.51	15.02	48.53	74.00	-25.47	peak
3	11422.000	32.33	16.64	48.97	74.00	-25.03	peak
4	12676.000	29.67	18.50	48.17	74.00	-25.83	peak
5	13853.000	27.15	22.46	49.61	74.00	-24.39	peak
6	17934.000	23.58	26.69	50.27	74.00	-23.73	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8232.000	38.31	8.49	46.80	74.00	-27.20	peak
2	9750.000	36.71	11.35	48.06	74.00	-25.94	peak
3	10421.000	35.28	13.29	48.57	74.00	-25.43	peak
4	11433.000	31.89	16.68	48.57	74.00	-25.43	peak
5	13875.000	27.07	22.46	49.53	74.00	-24.47	peak
6	17989.000	22.97	26.92	49.89	74.00	-24.11	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8969.000	36.27	11.40	47.67	74.00	-26.33	peak
2	10465.000	33.90	13.41	47.31	74.00	-26.69	peak
3	11642.000	31.34	17.13	48.47	74.00	-25.53	peak
4	12654.000	30.74	18.44	49.18	74.00	-24.82	peak
5	13853.000	27.65	22.46	50.11	74.00	-23.89	peak
6	17989.000	23.32	26.92	50.24	74.00	-23.76	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	37.29	10.91	48.20	74.00	-25.80	peak
2	11070.000	33.86	15.04	48.90	74.00	-25.10	peak
3	12038.000	30.43	18.60	49.03	74.00	-24.97	peak
4	13952.000	27.81	22.51	50.32	74.00	-23.68	peak
5	16878.000	26.86	21.35	48.21	74.00	-25.79	peak
6	17934.000	23.37	26.69	50.06	74.00	-23.94	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8232.000	37.07	8.49	45.56	74.00	-28.44	peak
2	8925.000	37.00	10.75	47.75	74.00	-26.25	peak
3	10399.000	34.84	13.23	48.07	74.00	-25.93	peak
4	12170.000	29.08	18.58	47.66	74.00	-26.34	peak
5	13864.000	27.67	22.45	50.12	74.00	-23.88	peak
6	17989.000	23.15	26.92	50.07	74.00	-23.93	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5190
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	35.76	11.57	47.33	74.00	-26.67	peak
2	10465.000	34.96	13.41	48.37	74.00	-25.63	peak
3	11422.000	31.62	16.64	48.26	74.00	-25.74	peak
4	12665.000	29.61	18.48	48.09	74.00	-25.91	peak
5	13919.000	27.43	22.49	49.92	74.00	-24.08	peak
6	17945.000	23.08	26.74	49.82	74.00	-24.18	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	36.32	11.73	48.05	74.00	-25.95	peak
2	10432.000	34.96	13.31	48.27	74.00	-25.73	peak
3	11026.000	33.84	14.95	48.79	74.00	-25.21	peak
4	12236.000	30.89	18.66	49.55	74.00	-24.45	peak
5	13952.000	27.60	22.51	50.11	74.00	-23.89	peak
6	17978.000	23.23	26.88	50.11	74.00	-23.89	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5230
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7352.000	36.46	8.07	44.53	74.00	-29.47	peak
2	8936.000	36.47	10.91	47.38	74.00	-26.62	peak
3	10465.000	34.68	13.41	48.09	74.00	-25.91	peak
4	11323.000	32.27	16.10	48.37	74.00	-25.63	peak
5	13908.000	26.29	22.49	48.78	74.00	-25.22	peak
6	17945.000	22.61	26.74	49.35	74.00	-24.65	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5270
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	37.19	10.91	48.10	74.00	-25.90	peak
2	10289.000	35.60	12.74	48.34	74.00	-25.66	peak
3	11455.000	32.20	16.74	48.94	74.00	-25.06	peak
4	12236.000	29.84	18.66	48.50	74.00	-25.50	peak
5	13864.000	26.85	22.45	49.30	74.00	-24.70	peak
6	17923.000	22.80	26.64	49.44	74.00	-24.56	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5270
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	35.95	11.57	47.52	74.00	-26.48	peak
2	10432.000	34.87	13.31	48.18	74.00	-25.82	peak
3	11059.000	34.23	15.02	49.25	74.00	-24.75	peak
4	12236.000	29.97	18.66	48.63	74.00	-25.37	peak
5	13875.000	27.70	22.46	50.16	74.00	-23.84	peak
6	17934.000	23.28	26.69	49.97	74.00	-24.03	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5310
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	36.85	7.73	44.58	74.00	-29.42	peak
2	8914.000	36.99	10.58	47.57	74.00	-26.43	peak
3	10234.000	35.66	12.49	48.15	74.00	-25.85	peak
4	11884.000	30.47	18.00	48.47	74.00	-25.53	peak
5	13864.000	26.82	22.45	49.27	74.00	-24.73	peak
6	17934.000	23.24	26.69	49.93	74.00	-24.07	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5310
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	37.62	7.73	45.35	74.00	-28.65	peak
2	9354.000	36.75	10.53	47.28	74.00	-26.72	peak
3	11059.000	33.46	15.02	48.48	74.00	-25.52	peak
4	11433.000	32.56	16.68	49.24	74.00	-24.76	peak
5	13875.000	28.00	22.46	50.46	74.00	-23.54	peak
6	17934.000	23.81	26.69	50.50	74.00	-23.50	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5510
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9112.000	37.06	10.85	47.91	74.00	-26.09	peak
2	10432.000	36.03	13.31	49.34	74.00	-24.66	peak
3	11400.000	32.50	16.57	49.07	74.00	-24.93	peak
4	12544.000	30.23	18.46	48.69	74.00	-25.31	peak
5	13908.000	27.29	22.49	49.78	74.00	-24.22	peak
6	17923.000	23.25	26.64	49.89	74.00	-24.11	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5510
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	37.49	7.73	45.22	74.00	-28.78	peak
2	9057.000	37.52	11.35	48.87	74.00	-25.13	peak
3	10333.000	35.17	12.93	48.10	74.00	-25.90	peak
4	11807.000	30.77	17.60	48.37	74.00	-25.63	peak
5	13963.000	27.55	22.51	50.06	74.00	-23.94	peak
6	17923.000	23.49	26.64	50.13	74.00	-23.87	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5550
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7891.000	37.75	6.85	44.60	74.00	-29.40	peak
2	9365.000	37.12	10.55	47.67	74.00	-26.33	peak
3	10300.000	35.49	12.78	48.27	74.00	-25.73	peak
4	12357.000	28.75	18.90	47.65	74.00	-26.35	peak
5	13864.000	27.19	22.45	49.64	74.00	-24.36	peak
6	17989.000	23.76	26.92	50.68	74.00	-23.32	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5550
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	36.79	7.73	44.52	74.00	-29.48	peak
2	8980.000	35.95	11.57	47.52	74.00	-26.48	peak
3	10300.000	36.08	12.78	48.86	74.00	-25.14	peak
4	11730.000	30.73	17.37	48.10	74.00	-25.90	peak
5	13875.000	27.31	22.46	49.77	74.00	-24.23	peak
6	17923.000	23.36	26.64	50.00	74.00	-24.00	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5670
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	36.43	11.57	48.00	74.00	-26.00	peak
2	10432.000	34.41	13.31	47.72	74.00	-26.28	peak
3	11389.000	31.71	16.51	48.22	74.00	-25.78	peak
4	12676.000	28.82	18.50	47.32	74.00	-26.68	peak
5	13875.000	27.58	22.46	50.04	74.00	-23.96	peak
6	17989.000	22.97	26.92	49.89	74.00	-24.11	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5670
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7352.000	36.56	8.07	44.63	74.00	-29.37	peak
2	9134.000	37.71	10.64	48.35	74.00	-25.65	peak
3	10443.000	34.63	13.35	47.98	74.00	-26.02	peak
4	11664.000	30.63	17.19	47.82	74.00	-26.18	peak
5	13875.000	27.40	22.46	49.86	74.00	-24.14	peak
6	17945.000	22.94	26.74	49.68	74.00	-24.32	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5710
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8012.000	38.71	6.99	45.70	74.00	-28.30	peak
2	8936.000	36.89	10.91	47.80	74.00	-26.20	peak
3	10300.000	34.96	12.78	47.74	74.00	-26.26	peak
4	11609.000	32.37	17.05	49.42	74.00	-24.58	peak
5	13996.000	27.37	22.54	49.91	74.00	-24.09	peak
6	17989.000	23.54	26.92	50.46	74.00	-23.54	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5710
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7891.000	37.78	6.85	44.63	74.00	-29.37	peak
2	8991.000	35.97	11.73	47.70	74.00	-26.30	peak
3	10432.000	34.28	13.31	47.59	74.00	-26.41	peak
4	11444.000	30.70	16.71	47.41	74.00	-26.59	peak
5	13985.000	25.98	22.53	48.51	74.00	-25.49	peak
6	17670.000	24.48	24.63	49.11	74.00	-24.89	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7341.000	36.18	8.00	44.18	74.00	-29.82	peak
2	8980.000	35.90	11.57	47.47	74.00	-26.53	peak
3	10366.000	34.72	13.08	47.80	74.00	-26.20	peak
4	11400.000	32.06	16.57	48.63	74.00	-25.37	peak
5	13963.000	27.65	22.51	50.16	74.00	-23.84	peak
6	17989.000	23.40	26.92	50.32	74.00	-23.68	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5755
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	36.65	11.73	48.38	74.00	-25.62	peak
2	10344.000	35.40	12.98	48.38	74.00	-25.62	peak
3	11829.000	31.13	17.71	48.84	74.00	-25.16	peak
4	13853.000	27.31	22.46	49.77	74.00	-24.23	peak
5	14447.000	27.82	20.58	48.40	74.00	-25.60	peak
6	17956.000	23.36	26.78	50.14	74.00	-23.86	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5795
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7341.000	36.30	8.00	44.30	74.00	-29.70	peak
2	9024.000	35.89	11.65	47.54	74.00	-26.46	peak
3	10289.000	35.10	12.74	47.84	74.00	-26.16	peak
4	11840.000	30.78	17.76	48.54	74.00	-25.46	peak
5	14238.000	28.64	21.72	50.36	74.00	-23.64	peak
6	17923.000	23.07	26.64	49.71	74.00	-24.29	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5795
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	36.38	11.73	48.11	74.00	-25.89	peak
2	10333.000	35.82	12.93	48.75	74.00	-25.25	peak
3	11444.000	32.60	16.71	49.31	74.00	-24.69	peak
4	13919.000	27.04	22.49	49.53	74.00	-24.47	peak
5	17010.000	25.74	21.70	47.44	74.00	-26.56	peak
6	17912.000	22.51	26.60	49.11	74.00	-24.89	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9057.000	35.70	11.35	47.05	74.00	-26.95	peak
2	10300.000	35.18	12.78	47.96	74.00	-26.04	peak
3	11290.000	32.49	15.89	48.38	74.00	-25.62	peak
4	12236.000	29.31	18.66	47.97	74.00	-26.03	peak
5	13930.000	27.49	22.50	49.99	74.00	-24.01	peak
6	17978.000	22.99	26.88	49.87	74.00	-24.13	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5210
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9057.000	36.54	11.35	47.89	74.00	-26.11	peak
2	11334.000	31.57	16.16	47.73	74.00	-26.27	peak
3	11840.000	31.13	17.76	48.89	74.00	-25.11	peak
4	13864.000	27.32	22.45	49.77	74.00	-24.23	peak
5	14436.000	28.38	20.63	49.01	74.00	-24.99	peak
6	17989.000	22.92	26.92	49.84	74.00	-24.16	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5290
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	36.43	7.73	44.16	74.00	-29.84	peak
2	8980.000	35.54	11.57	47.11	74.00	-26.89	peak
3	10454.000	34.97	13.38	48.35	74.00	-25.65	peak
4	11444.000	31.46	16.71	48.17	74.00	-25.83	peak
5	13809.000	26.54	22.43	48.97	74.00	-25.03	peak
6	17956.000	22.48	26.78	49.26	74.00	-24.74	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5290
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7352.000	36.37	8.07	44.44	74.00	-29.56	peak
2	8980.000	35.87	11.57	47.44	74.00	-26.56	peak
3	10443.000	34.37	13.35	47.72	74.00	-26.28	peak
4	11785.000	30.51	17.52	48.03	74.00	-25.97	peak
5	13908.000	26.56	22.49	49.05	74.00	-24.95	peak
6	17835.000	23.61	26.27	49.88	74.00	-24.12	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5530
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7495.000	36.69	7.61	44.30	74.00	-29.70	peak
2	9013.000	35.33	11.75	47.08	74.00	-26.92	peak
3	10432.000	34.11	13.31	47.42	74.00	-26.58	peak
4	12676.000	29.63	18.50	48.13	74.00	-25.87	peak
5	13864.000	27.43	22.45	49.88	74.00	-24.12	peak
6	17989.000	22.80	26.92	49.72	74.00	-24.28	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5530
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8958.000	36.43	11.24	47.67	74.00	-26.33	peak
2	10432.000	34.75	13.31	48.06	74.00	-25.94	peak
3	11400.000	32.31	16.57	48.88	74.00	-25.12	peak
4	13501.000	28.12	21.40	49.52	74.00	-24.48	peak
5	13919.000	27.32	22.49	49.81	74.00	-24.19	peak
6	17945.000	24.00	26.74	50.74	74.00	-23.26	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5610
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9057.000	36.09	11.35	47.44	74.00	-26.56	peak
2	10454.000	34.94	13.38	48.32	74.00	-25.68	peak
3	12621.000	29.43	18.38	47.81	74.00	-26.19	peak
4	13996.000	27.12	22.54	49.66	74.00	-24.34	peak
5	14447.000	29.31	20.58	49.89	74.00	-24.11	peak
6	17934.000	23.79	26.69	50.48	74.00	-23.52	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5610
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8947.000	36.32	11.08	47.40	74.00	-26.60	peak
2	10333.000	35.00	12.93	47.93	74.00	-26.07	peak
3	11389.000	31.62	16.51	48.13	74.00	-25.87	peak
4	12665.000	29.11	18.48	47.59	74.00	-26.41	peak
5	13666.000	27.65	21.75	49.40	74.00	-24.60	peak
6	17703.000	25.50	25.01	50.51	74.00	-23.49	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5690
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7341.000	36.24	8.00	44.24	74.00	-29.76	peak
2	8980.000	35.92	11.57	47.49	74.00	-26.51	peak
3	11400.000	31.49	16.57	48.06	74.00	-25.94	peak
4	13644.000	27.77	21.64	49.41	74.00	-24.59	peak
5	13930.000	26.96	22.50	49.46	74.00	-24.54	peak
6	17857.000	23.81	26.36	50.17	74.00	-23.83	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5690
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7341.000	36.24	8.00	44.24	74.00	-29.76	peak
2	8980.000	36.37	11.57	47.94	74.00	-26.06	peak
3	10454.000	35.24	13.38	48.62	74.00	-25.38	peak
4	11807.000	31.12	17.60	48.72	74.00	-25.28	peak
5	13985.000	26.27	22.53	48.80	74.00	-25.20	peak
6	17857.000	23.86	26.36	50.22	74.00	-23.78	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5775
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9068.000	37.06	11.25	48.31	74.00	-25.69	peak
2	10311.000	35.00	12.83	47.83	74.00	-26.17	peak
3	11455.000	30.50	16.74	47.24	74.00	-26.76	peak
4	12687.000	28.79	18.53	47.32	74.00	-26.68	peak
5	13864.000	27.44	22.45	49.89	74.00	-24.11	peak
6	18000.000	22.92	26.97	49.89	74.00	-24.11	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5775
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	36.62	10.91	47.53	74.00	-26.47	peak
2	10300.000	35.20	12.78	47.98	74.00	-26.02	peak
3	11048.000	32.88	14.99	47.87	74.00	-26.13	peak
4	11983.000	29.13	18.52	47.65	74.00	-26.35	peak
5	14007.000	25.76	22.53	48.29	74.00	-25.71	peak
6	18000.000	21.69	26.97	48.66	74.00	-25.34	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	36.35	10.91	47.26	74.00	-26.74	peak
2	10300.000	34.77	12.78	47.55	74.00	-26.45	peak
3	11334.000	31.93	16.16	48.09	74.00	-25.91	peak
4	12258.000	29.20	18.70	47.90	74.00	-26.10	peak
5	13952.000	27.45	22.51	49.96	74.00	-24.04	peak
6	17989.000	23.86	26.92	50.78	74.00	-23.22	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8925.000	37.09	10.75	47.84	74.00	-26.16	peak
2	10575.000	34.09	13.70	47.79	74.00	-26.21	peak
3	11400.000	31.72	16.57	48.29	74.00	-25.71	peak
4	12555.000	29.81	18.43	48.24	74.00	-25.76	peak
5	13919.000	27.47	22.49	49.96	74.00	-24.04	peak
6	17725.000	25.40	25.26	50.66	74.00	-23.34	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5200
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	36.65	7.73	44.38	74.00	-29.62	peak
2	9442.000	36.75	10.76	47.51	74.00	-26.49	peak
3	11422.000	31.68	16.64	48.32	74.00	-25.68	peak
4	12599.000	30.15	18.32	48.47	74.00	-25.53	peak
5	13974.000	27.41	22.53	49.94	74.00	-24.06	peak
6	17923.000	23.76	26.64	50.40	74.00	-23.60	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5200
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7341.000	36.36	8.00	44.36	74.00	-29.64	peak
2	8958.000	36.76	11.24	48.00	74.00	-26.00	peak
3	11059.000	33.47	15.02	48.49	74.00	-25.51	peak
4	14007.000	27.34	22.53	49.87	74.00	-24.13	peak
5	17373.000	25.46	23.30	48.76	74.00	-25.24	peak
6	17989.000	23.08	26.92	50.00	74.00	-24.00	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8914.000	37.44	10.58	48.02	74.00	-25.98	peak
2	10300.000	35.04	12.78	47.82	74.00	-26.18	peak
3	11851.000	30.50	17.83	48.33	74.00	-25.67	peak
4	13501.000	27.68	21.40	49.08	74.00	-24.92	peak
5	13908.000	26.84	22.49	49.33	74.00	-24.67	peak
6	17967.000	22.95	26.83	49.78	74.00	-24.22	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5240
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	35.99	11.73	47.72	74.00	-26.28	peak
2	10399.000	34.99	13.23	48.22	74.00	-25.78	peak
3	11356.000	33.06	16.30	49.36	74.00	-24.64	peak
4	12599.000	29.92	18.32	48.24	74.00	-25.76	peak
5	13919.000	27.20	22.49	49.69	74.00	-24.31	peak
6	17989.000	23.11	26.92	50.03	74.00	-23.97	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5260
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8958.000	36.32	11.24	47.56	74.00	-26.44	peak
2	10564.000	34.59	13.68	48.27	74.00	-25.73	peak
3	11455.000	32.66	16.74	49.40	74.00	-24.60	peak
4	13523.000	28.72	21.41	50.13	74.00	-23.87	peak
5	14150.000	27.97	22.09	50.06	74.00	-23.94	peak
6	17714.000	25.32	25.14	50.46	74.00	-23.54	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5260
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9387.000	37.39	10.63	48.02	74.00	-25.98	peak
2	10289.000	35.87	12.74	48.61	74.00	-25.39	peak
3	11389.000	32.69	16.51	49.20	74.00	-24.80	peak
4	12632.000	29.91	18.40	48.31	74.00	-25.69	peak
5	13963.000	27.42	22.51	49.93	74.00	-24.07	peak
6	17725.000	25.13	25.26	50.39	74.00	-23.61	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5280
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9134.000	37.05	10.64	47.69	74.00	-26.31	peak
2	10432.000	34.77	13.31	48.08	74.00	-25.92	peak
3	11323.000	32.44	16.10	48.54	74.00	-25.46	peak
4	12115.000	29.50	18.59	48.09	74.00	-25.91	peak
5	13996.000	27.45	22.54	49.99	74.00	-24.01	peak
6	17945.000	23.39	26.74	50.13	74.00	-23.87	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5280
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	36.29	11.57	47.86	74.00	-26.14	peak
2	10300.000	35.83	12.78	48.61	74.00	-25.39	peak
3	11796.000	31.75	17.55	49.30	74.00	-24.70	peak
4	12621.000	30.88	18.38	49.26	74.00	-24.74	peak
5	14172.000	27.69	22.03	49.72	74.00	-24.28	peak
6	17934.000	23.07	26.69	49.76	74.00	-24.24	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5320
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7341.000	37.53	8.00	45.53	74.00	-28.47	peak
2	8969.000	36.50	11.40	47.90	74.00	-26.10	peak
3	10399.000	34.76	13.23	47.99	74.00	-26.01	peak
4	11400.000	32.68	16.57	49.25	74.00	-24.75	peak
5	13787.000	27.38	22.36	49.74	74.00	-24.26	peak
6	17934.000	22.98	26.69	49.67	74.00	-24.33	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5320
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	37.17	7.73	44.90	74.00	-29.10	peak
2	8980.000	36.65	11.57	48.22	74.00	-25.78	peak
3	10366.000	35.08	13.08	48.16	74.00	-25.84	peak
4	12302.000	29.01	18.79	47.80	74.00	-26.20	peak
5	13875.000	26.61	22.46	49.07	74.00	-24.93	peak
6	17956.000	23.10	26.78	49.88	74.00	-24.12	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5500
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7352.000	36.45	8.07	44.52	74.00	-29.48	peak
2	9101.000	36.27	10.94	47.21	74.00	-26.79	peak
3	10487.000	34.62	13.46	48.08	74.00	-25.92	peak
4	11400.000	32.63	16.57	49.20	74.00	-24.80	peak
5	13886.000	27.63	22.48	50.11	74.00	-23.89	peak
6	17714.000	24.72	25.14	49.86	74.00	-24.14	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5500
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7352.000	36.34	8.07	44.41	74.00	-29.59	peak
2	8980.000	36.61	11.57	48.18	74.00	-25.82	peak
3	10443.000	34.41	13.35	47.76	74.00	-26.24	peak
4	12665.000	29.72	18.48	48.20	74.00	-25.80	peak
5	13886.000	26.92	22.48	49.40	74.00	-24.60	peak
6	17956.000	23.48	26.78	50.26	74.00	-23.74	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5580
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8925.000	37.02	10.75	47.77	74.00	-26.23	peak
2	10454.000	34.13	13.38	47.51	74.00	-26.49	peak
3	11400.000	32.22	16.57	48.79	74.00	-25.21	peak
4	13479.000	28.63	21.34	49.97	74.00	-24.03	peak
5	13930.000	27.37	22.50	49.87	74.00	-24.13	peak
6	17989.000	23.72	26.92	50.64	74.00	-23.36	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5580
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7352.000	36.80	8.07	44.87	74.00	-29.13	peak
2	8991.000	35.74	11.73	47.47	74.00	-26.53	peak
3	10344.000	34.50	12.98	47.48	74.00	-26.52	peak
4	11323.000	32.09	16.10	48.19	74.00	-25.81	peak
5	13798.000	27.32	22.41	49.73	74.00	-24.27	peak
6	17956.000	23.52	26.78	50.30	74.00	-23.70	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5700
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9310.000	36.98	10.39	47.37	74.00	-26.63	peak
2	10289.000	34.40	12.74	47.14	74.00	-26.86	peak
3	11752.000	30.93	17.43	48.36	74.00	-25.64	peak
4	12687.000	29.36	18.53	47.89	74.00	-26.11	peak
5	13798.000	27.22	22.41	49.63	74.00	-24.37	peak
6	17934.000	23.45	26.69	50.14	74.00	-23.86	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5700
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9101.000	37.81	10.94	48.75	74.00	-25.25	peak
2	11015.000	33.50	14.93	48.43	74.00	-25.57	peak
3	11422.000	32.19	16.64	48.83	74.00	-25.17	peak
4	12247.000	29.49	18.68	48.17	74.00	-25.83	peak
5	13853.000	27.49	22.46	49.95	74.00	-24.05	peak
6	17945.000	23.61	26.74	50.35	74.00	-23.65	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5720
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	36.70	10.91	47.61	74.00	-26.39	peak
2	10223.000	35.92	12.44	48.36	74.00	-25.64	peak
3	11334.000	33.16	16.16	49.32	74.00	-24.68	peak
4	12247.000	31.10	18.68	49.78	74.00	-24.22	peak
5	13853.000	27.90	22.46	50.36	74.00	-23.64	peak
6	17989.000	23.93	26.92	50.85	74.00	-23.15	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5720
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8958.000	36.24	11.24	47.48	74.00	-26.52	peak
2	10300.000	34.97	12.78	47.75	74.00	-26.25	peak
3	11719.000	31.12	17.34	48.46	74.00	-25.54	peak
4	12654.000	29.62	18.44	48.06	74.00	-25.94	peak
5	13853.000	27.72	22.46	50.18	74.00	-23.82	peak
6	17956.000	22.95	26.78	49.73	74.00	-24.27	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9277.000	36.98	10.28	47.26	74.00	-26.74	peak
2	10366.000	33.84	13.08	46.92	74.00	-27.08	peak
3	11884.000	30.16	18.00	48.16	74.00	-25.84	peak
4	13875.000	27.56	22.46	50.02	74.00	-23.98	peak
5	14227.000	27.82	21.79	49.61	74.00	-24.39	peak
6	17956.000	24.09	26.78	50.87	74.00	-23.13	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	36.06	11.57	47.63	74.00	-26.37	peak
2	10300.000	35.60	12.78	48.38	74.00	-25.62	peak
3	11763.000	31.70	17.46	49.16	74.00	-24.84	peak
4	13897.000	28.35	22.47	50.82	74.00	-23.18	peak
5	14733.000	28.36	19.45	47.81	74.00	-26.19	peak
6	17912.000	23.65	26.60	50.25	74.00	-23.75	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8947.000	36.38	11.08	47.46	74.00	-26.54	peak
2	10300.000	34.61	12.78	47.39	74.00	-26.61	peak
3	11389.000	32.17	16.51	48.68	74.00	-25.32	peak
4	13589.000	27.79	21.41	49.20	74.00	-24.80	peak
5	13919.000	27.56	22.49	50.05	74.00	-23.95	peak
6	17956.000	23.14	26.78	49.92	74.00	-24.08	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	35.74	11.73	47.47	74.00	-26.53	peak
2	10432.000	34.68	13.31	47.99	74.00	-26.01	peak
3	11411.000	31.10	16.60	47.70	74.00	-26.30	peak
4	13611.000	27.55	21.48	49.03	74.00	-24.97	peak
5	13985.000	27.29	22.53	49.82	74.00	-24.18	peak
6	18000.000	22.84	26.97	49.81	74.00	-24.19	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8947.000	37.12	11.08	48.20	74.00	-25.80	peak
2	10333.000	35.13	12.93	48.06	74.00	-25.94	peak
3	11444.000	31.14	16.71	47.85	74.00	-26.15	peak
4	12632.000	29.36	18.40	47.76	74.00	-26.24	peak
5	13963.000	27.71	22.51	50.22	74.00	-23.78	peak
6	17956.000	23.44	26.78	50.22	74.00	-23.78	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9057.000	36.01	11.35	47.36	74.00	-26.64	peak
2	10443.000	35.18	13.35	48.53	74.00	-25.47	peak
3	11378.000	32.44	16.43	48.87	74.00	-25.13	peak
4	12698.000	29.84	18.56	48.40	74.00	-25.60	peak
5	13864.000	27.78	22.45	50.23	74.00	-23.77	peak
6	17857.000	24.64	26.36	51.00	74.00	-23.00	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	37.40	11.73	49.13	74.00	-24.87	peak
2	9574.000	36.58	10.97	47.55	74.00	-26.45	peak
3	10454.000	34.68	13.38	48.06	74.00	-25.94	peak
4	11323.000	31.74	16.10	47.84	74.00	-26.16	peak
5	13842.000	26.88	22.44	49.32	74.00	-24.68	peak
6	18000.000	22.93	26.97	49.90	74.00	-24.10	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5190
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7341.000	37.32	8.00	45.32	74.00	-28.68	peak
2	8991.000	36.08	11.73	47.81	74.00	-26.19	peak
3	10234.000	36.34	12.49	48.83	74.00	-25.17	peak
4	11884.000	31.76	18.00	49.76	74.00	-24.24	peak
5	13864.000	26.79	22.45	49.24	74.00	-24.76	peak
6	17956.000	23.34	26.78	50.12	74.00	-23.88	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7352.000	36.61	8.07	44.68	74.00	-29.32	peak
2	8936.000	36.91	10.91	47.82	74.00	-26.18	peak
3	10597.000	35.00	13.77	48.77	74.00	-25.23	peak
4	12247.000	30.68	18.68	49.36	74.00	-24.64	peak
5	13919.000	27.66	22.49	50.15	74.00	-23.85	peak
6	17967.000	23.58	26.83	50.41	74.00	-23.59	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5230
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8232.000	37.30	8.49	45.79	74.00	-28.21	peak
2	8936.000	37.10	10.91	48.01	74.00	-25.99	peak
3	10168.000	36.15	12.32	48.47	74.00	-25.53	peak
4	11697.000	31.03	17.29	48.32	74.00	-25.68	peak
5	13611.000	28.14	21.48	49.62	74.00	-24.38	peak
6	17989.000	23.32	26.92	50.24	74.00	-23.76	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5270
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8144.000	37.27	8.12	45.39	74.00	-28.61	peak
2	8936.000	37.00	10.91	47.91	74.00	-26.09	peak
3	11422.000	31.59	16.64	48.23	74.00	-25.77	peak
4	13512.000	27.17	21.41	48.58	74.00	-25.42	peak
5	13864.000	27.24	22.45	49.69	74.00	-24.31	peak
6	17934.000	23.13	26.69	49.82	74.00	-24.18	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5270
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7352.000	37.43	8.07	45.50	74.00	-28.50	peak
2	8936.000	37.57	10.91	48.48	74.00	-25.52	peak
3	11059.000	34.00	15.02	49.02	74.00	-24.98	peak
4	11851.000	30.33	17.83	48.16	74.00	-25.84	peak
5	13897.000	27.04	22.47	49.51	74.00	-24.49	peak
6	17934.000	23.63	26.69	50.32	74.00	-23.68	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5310
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8243.000	37.04	8.44	45.48	74.00	-28.52	peak
2	8936.000	36.94	10.91	47.85	74.00	-26.15	peak
3	11059.000	33.81	15.02	48.83	74.00	-25.17	peak
4	13413.000	27.71	21.16	48.87	74.00	-25.13	peak
5	13875.000	27.70	22.46	50.16	74.00	-23.84	peak
6	17989.000	22.99	26.92	49.91	74.00	-24.09	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5310
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8507.000	37.37	8.45	45.82	74.00	-28.18	peak
2	8936.000	37.04	10.91	47.95	74.00	-26.05	peak
3	10300.000	35.76	12.78	48.54	74.00	-25.46	peak
4	11411.000	32.89	16.60	49.49	74.00	-24.51	peak
5	13809.000	26.67	22.43	49.10	74.00	-24.90	peak
6	18000.000	22.25	26.97	49.22	74.00	-24.78	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5510
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8122.000	37.72	7.93	45.65	74.00	-28.35	peak
2	8947.000	36.49	11.08	47.57	74.00	-26.43	peak
3	11059.000	33.70	15.02	48.72	74.00	-25.28	peak
4	13875.000	27.54	22.46	50.00	74.00	-24.00	peak
5	17219.000	25.24	22.76	48.00	74.00	-26.00	peak
6	17956.000	23.07	26.78	49.85	74.00	-24.15	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5510
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	37.25	7.73	44.98	74.00	-29.02	peak
2	9013.000	36.29	11.75	48.04	74.00	-25.96	peak
3	10300.000	35.45	12.78	48.23	74.00	-25.77	peak
4	11884.000	30.71	18.00	48.71	74.00	-25.29	peak
5	13644.000	28.31	21.64	49.95	74.00	-24.05	peak
6	17923.000	23.89	26.64	50.53	74.00	-23.47	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5550
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8166.000	36.65	8.32	44.97	74.00	-29.03	peak
2	9057.000	37.29	11.35	48.64	74.00	-25.36	peak
3	10575.000	35.12	13.70	48.82	74.00	-25.18	peak
4	11785.000	30.44	17.52	47.96	74.00	-26.04	peak
5	13919.000	27.19	22.49	49.68	74.00	-24.32	peak
6	17945.000	23.89	26.74	50.63	74.00	-23.37	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5550
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7308.000	37.43	7.73	45.16	74.00	-28.84	peak
2	8980.000	36.79	11.57	48.36	74.00	-25.64	peak
3	11059.000	33.41	15.02	48.43	74.00	-25.57	peak
4	11444.000	31.95	16.71	48.66	74.00	-25.34	peak
5	13853.000	27.26	22.46	49.72	74.00	-24.28	peak
6	17989.000	22.46	26.92	49.38	74.00	-24.62	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5670
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8078.000	37.36	7.56	44.92	74.00	-29.08	peak
2	8936.000	36.69	10.91	47.60	74.00	-26.40	peak
3	10278.000	35.14	12.69	47.83	74.00	-26.17	peak
4	11521.000	31.64	16.92	48.56	74.00	-25.44	peak
5	13864.000	27.85	22.45	50.30	74.00	-23.70	peak
6	17725.000	25.20	25.26	50.46	74.00	-23.54	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5670
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	36.05	11.73	47.78	74.00	-26.22	peak
2	10223.000	35.66	12.44	48.10	74.00	-25.90	peak
3	11026.000	34.31	14.95	49.26	74.00	-24.74	peak
4	13358.000	28.76	20.89	49.65	74.00	-24.35	peak
5	13941.000	27.67	22.50	50.17	74.00	-23.83	peak
6	17956.000	23.49	26.78	50.27	74.00	-23.73	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5710
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8232.000	37.20	8.49	45.69	74.00	-28.31	peak
2	8914.000	38.03	10.58	48.61	74.00	-25.39	peak
3	10300.000	36.10	12.78	48.88	74.00	-25.12	peak
4	11400.000	32.11	16.57	48.68	74.00	-25.32	peak
5	13864.000	27.32	22.45	49.77	74.00	-24.23	peak
6	17989.000	22.73	26.92	49.65	74.00	-24.35	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5710
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7869.000	38.41	6.85	45.26	74.00	-28.74	peak
2	9057.000	37.20	11.35	48.55	74.00	-25.45	peak
3	10388.000	35.12	13.18	48.30	74.00	-25.70	peak
4	11334.000	32.58	16.16	48.74	74.00	-25.26	peak
5	13952.000	27.64	22.51	50.15	74.00	-23.85	peak
6	17923.000	23.56	26.64	50.20	74.00	-23.80	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7880.000	38.28	6.86	45.14	74.00	-28.86	peak
2	8925.000	37.69	10.75	48.44	74.00	-25.56	peak
3	10377.000	35.23	13.13	48.36	74.00	-25.64	peak
4	11917.000	29.69	18.16	47.85	74.00	-26.15	peak
5	13919.000	27.17	22.49	49.66	74.00	-24.34	peak
6	17923.000	23.69	26.64	50.33	74.00	-23.67	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5755
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8166.000	36.51	8.32	44.83	74.00	-29.17	peak
2	8936.000	36.62	10.91	47.53	74.00	-26.47	peak
3	10300.000	36.03	12.78	48.81	74.00	-25.19	peak
4	11400.000	32.21	16.57	48.78	74.00	-25.22	peak
5	13523.000	28.52	21.41	49.93	74.00	-24.07	peak
6	17923.000	23.67	26.64	50.31	74.00	-23.69	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5795
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	36.18	11.57	47.75	74.00	-26.25	peak
2	11004.000	33.07	14.90	47.97	74.00	-26.03	peak
3	11411.000	31.95	16.60	48.55	74.00	-25.45	peak
4	13380.000	27.98	21.01	48.99	74.00	-25.01	peak
5	13864.000	26.92	22.45	49.37	74.00	-24.63	peak
6	17956.000	23.08	26.78	49.86	74.00	-24.14	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5795
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	36.99	10.91	47.90	74.00	-26.10	peak
2	10223.000	36.42	12.44	48.86	74.00	-25.14	peak
3	11334.000	32.00	16.16	48.16	74.00	-25.84	peak
4	13545.000	27.35	21.41	48.76	74.00	-25.24	peak
5	13919.000	27.57	22.49	50.06	74.00	-23.94	peak
6	17934.000	23.60	26.69	50.29	74.00	-23.71	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8958.000	36.82	11.24	48.06	74.00	-25.94	peak
2	11037.000	32.69	14.98	47.67	74.00	-26.33	peak
3	11510.000	31.17	16.90	48.07	74.00	-25.93	peak
4	13809.000	26.91	22.43	49.34	74.00	-24.66	peak
5	14777.000	28.93	19.30	48.23	74.00	-25.77	peak
6	17923.000	23.48	26.64	50.12	74.00	-23.88	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5210
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7352.000	36.84	8.07	44.91	74.00	-29.09	peak
2	9024.000	37.04	11.65	48.69	74.00	-25.31	peak
3	10223.000	35.79	12.44	48.23	74.00	-25.77	peak
4	11521.000	31.48	16.92	48.40	74.00	-25.60	peak
5	13919.000	28.10	22.49	50.59	74.00	-23.41	peak
6	18000.000	22.86	26.97	49.83	74.00	-24.17	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5290
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8925.000	38.12	10.75	48.87	74.00	-25.13	peak
2	10311.000	35.66	12.83	48.49	74.00	-25.51	peak
3	11796.000	31.23	17.55	48.78	74.00	-25.22	peak
4	13743.000	28.36	22.13	50.49	74.00	-23.51	peak
5	14447.000	29.51	20.58	50.09	74.00	-23.91	peak
6	17934.000	24.07	26.69	50.76	74.00	-23.24	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5290
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8276.000	36.57	8.32	44.89	74.00	-29.11	peak
2	8936.000	37.02	10.91	47.93	74.00	-26.07	peak
3	10223.000	35.94	12.44	48.38	74.00	-25.62	peak
4	12258.000	29.58	18.70	48.28	74.00	-25.72	peak
5	13919.000	28.18	22.49	50.67	74.00	-23.33	peak
6	17989.000	23.66	26.92	50.58	74.00	-23.42	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5530
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9057.000	36.49	11.35	47.84	74.00	-26.16	peak
2	10883.000	34.87	14.28	49.15	74.00	-24.85	peak
3	11422.000	32.68	16.64	49.32	74.00	-24.68	peak
4	13985.000	27.06	22.53	49.59	74.00	-24.41	peak
5	16779.000	25.76	21.07	46.83	74.00	-27.17	peak
6	17670.000	24.86	24.63	49.49	74.00	-24.51	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5530
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9068.000	36.47	11.25	47.72	74.00	-26.28	peak
2	10289.000	36.21	12.74	48.95	74.00	-25.05	peak
3	11411.000	31.81	16.60	48.41	74.00	-25.59	peak
4	12654.000	29.26	18.44	47.70	74.00	-26.30	peak
5	13875.000	26.89	22.46	49.35	74.00	-24.65	peak
6	17901.000	23.11	26.55	49.66	74.00	-24.34	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5610
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8991.000	35.85	11.73	47.58	74.00	-26.42	peak
2	10399.000	35.19	13.23	48.42	74.00	-25.58	peak
3	11356.000	31.31	16.30	47.61	74.00	-26.39	peak
4	12654.000	29.39	18.44	47.83	74.00	-26.17	peak
5	13864.000	28.20	22.45	50.65	74.00	-23.35	peak
6	17989.000	22.99	26.92	49.91	74.00	-24.09	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5610
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8958.000	36.95	11.24	48.19	74.00	-25.81	peak
2	10025.000	35.35	12.19	47.54	74.00	-26.46	peak
3	11873.000	30.37	17.94	48.31	74.00	-25.69	peak
4	13512.000	27.54	21.41	48.95	74.00	-25.05	peak
5	13919.000	27.45	22.49	49.94	74.00	-24.06	peak
6	17989.000	22.87	26.92	49.79	74.00	-24.21	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5690
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8045.000	37.72	7.27	44.99	74.00	-29.01	peak
2	8991.000	35.98	11.73	47.71	74.00	-26.29	peak
3	10223.000	36.02	12.44	48.46	74.00	-25.54	peak
4	11785.000	30.66	17.52	48.18	74.00	-25.82	peak
5	13864.000	27.00	22.45	49.45	74.00	-24.55	peak
6	17769.000	24.80	25.76	50.56	74.00	-23.44	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5690
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	36.67	10.91	47.58	74.00	-26.42	peak
2	10542.000	34.91	13.62	48.53	74.00	-25.47	peak
3	11389.000	32.47	16.51	48.98	74.00	-25.02	peak
4	12665.000	28.93	18.48	47.41	74.00	-26.59	peak
5	13886.000	26.81	22.48	49.29	74.00	-24.71	peak
6	17989.000	23.16	26.92	50.08	74.00	-23.92	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5775
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8221.000	37.61	8.53	46.14	74.00	-27.86	peak
2	8991.000	36.15	11.73	47.88	74.00	-26.12	peak
3	10223.000	36.01	12.44	48.45	74.00	-25.55	peak
4	12027.000	29.89	18.60	48.49	74.00	-25.51	peak
5	13963.000	27.48	22.51	49.99	74.00	-24.01	peak
6	17989.000	23.45	26.92	50.37	74.00	-23.63	peak


Test Mode:	802.11ax HE80	Frequency(MHz):	5775
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	36.86	11.57	48.43	74.00	-25.57	peak
2	10454.000	33.75	13.38	47.13	74.00	-26.87	peak
3	11422.000	32.28	16.64	48.92	74.00	-25.08	peak
4	12269.000	29.56	18.72	48.28	74.00	-25.72	peak
5	13842.000	27.40	22.44	49.84	74.00	-24.16	peak
6	17703.000	25.29	25.01	50.30	74.00	-23.70	peak


8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

Test Mode:	802.11a20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0100	75.22	-101.40	-26.18	47.60	-77.68	-3.90	-73.78	peak
2	0.0134	72.84	-101.39	-28.55	45.06	-80.05	-6.44	-73.61	peak
3	0.0279	67.17	-101.38	-34.21	38.69	-85.71	-12.81	-72.90	peak
4	0.0367	65.75	-101.42	-35.67	36.31	-87.17	-15.19	-71.98	peak
5	0.0475	61.94	-101.47	-39.53	34.07	-91.03	-17.43	-73.60	peak
6	0.0908	57.38	-101.72	-44.34	28.44	-95.84	-23.06	-72.78	peak

Test Mode:	802.11a20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1595	75.36	-101.65	-26.29	23.55	-77.79	-27.95	-49.84	peak
2	0.1794	72.27	-101.68	-29.41	22.53	-80.91	-28.97	-51.94	peak
3	0.2442	67.03	-101.79	-34.76	19.85	-86.26	-31.65	-54.61	peak
4	0.2782	64.79	-101.83	-37.04	18.71	-88.54	-32.79	-55.75	peak
5	0.3431	63.67	-101.90	-38.23	16.89	-89.73	-34.61	-55.12	peak
6	0.4707	56.23	-102.04	-45.81	14.15	-97.31	-37.35	-59.96	peak


Test Mode:	802.11a20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.8195	64.16	-62.16	2.00	29.33	-49.50	-22.17	-27.33	peak
2	1.5564	58.68	-62.02	-3.34	23.76	-54.84	-27.74	-27.10	peak
3	2.1463	58.27	-61.79	-3.52	29.54	-55.02	-21.96	-33.06	peak
4	5.9198	55.93	-61.36	-5.43	29.54	-56.93	-21.96	-34.97	peak
5	10.5234	53.31	-60.82	-7.51	29.54	-59.01	-21.96	-37.05	peak
6	29.9115	52.13	-59.98	-7.85	29.54	-59.35	-21.96	-37.39	peak


8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18232.000	49.75	-5.54	44.21	74.00	-29.79	peak
2	19392.000	50.12	-5.57	44.55	74.00	-29.45	peak
3	21120.000	48.69	-4.82	43.87	74.00	-30.13	peak
4	22024.000	48.54	-4.46	44.08	74.00	-29.92	peak
5	23800.000	48.41	-3.11	45.30	74.00	-28.70	peak
6	24960.000	46.64	-2.14	44.50	74.00	-29.50	peak


Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19080.000	49.60	-5.34	44.26	74.00	-29.74	peak
2	19784.000	49.07	-5.28	43.79	74.00	-30.21	peak
3	21088.000	48.78	-4.84	43.94	74.00	-30.06	peak
4	22192.000	48.43	-4.27	44.16	74.00	-29.84	peak
5	23992.000	46.36	-2.76	43.60	74.00	-30.40	peak
6	25144.000	45.70	-1.86	43.84	74.00	-30.16	peak


8.6. SPURIOUS EMISSIONS(26 GHZ~40 GHZ)

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	28660.000	48.15	-1.31	46.84	74.00	-27.16	peak
2	31670.000	48.86	-1.21	47.65	74.00	-26.35	peak
3	34218.000	45.96	1.13	47.09	74.00	-26.91	peak
4	36416.000	44.11	3.58	47.69	74.00	-26.31	peak
5	38320.000	44.06	3.77	47.83	74.00	-26.17	peak
6	39986.000	43.77	5.17	48.94	74.00	-25.06	peak


Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	28772.000	47.66	-0.59	47.07	74.00	-26.93	peak
2	30564.000	48.84	-0.97	47.87	74.00	-26.13	peak
3	32930.000	48.59	-0.82	47.77	74.00	-26.23	peak
4	35954.000	43.88	3.94	47.82	74.00	-26.18	peak
5	37130.000	44.53	3.17	47.70	74.00	-26.30	peak
6	39972.000	43.45	5.13	48.58	74.00	-25.42	peak


8.7. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.0000	37.66	-13.34	24.32	40.00	-15.68	QP
2	208.4800	36.88	-12.48	24.40	43.50	-19.10	QP
3	263.7700	42.03	-13.94	28.09	46.00	-17.91	QP
4	333.6099	38.97	-10.28	28.69	46.00	-17.31	QP
5	365.6200	38.96	-9.62	29.34	46.00	-16.66	QP
6	879.7200	28.32	-1.88	26.44	46.00	-19.56	QP

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.0000	39.86	-13.34	26.52	40.00	-13.48	QP
2	49.4000	41.80	-15.54	26.26	40.00	-13.74	QP
3	247.2800	42.74	-14.61	28.13	46.00	-17.87	QP
4	263.7700	37.93	-13.94	23.99	46.00	-22.01	QP
5	332.6400	35.90	-10.32	25.58	46.00	-20.42	QP
6	358.8299	37.20	-9.56	27.64	46.00	-18.36	QP

9. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00


TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT


Temperature	24.1°C	Relative Humidity	64.6%
Atmosphere Pressure	101kPa	Test Voltage	

TEST DATE / ENGINEER

Test Date	May 28, 2024	Test By	Wite Chen
-----------	--------------	---------	-----------

TEST RESULTS

Test Mode:	802.11a20	Frequency(MHz):	5180
Line:	Line		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1525	34.30	10.23	44.53	65.86	-21.33	QP
2	0.1525	18.80	10.23	29.03	55.86	-26.83	AVG
3	0.1916	32.87	10.16	43.03	63.97	-20.94	QP
4	0.1916	22.90	10.16	33.06	53.97	-20.91	AVG
5	0.3256	26.04	10.10	36.14	59.56	-23.42	QP
6	0.3256	13.16	10.10	23.26	49.56	-26.30	AVG
7	0.4784	28.50	10.05	38.55	56.37	-17.82	QP
8	0.4784	24.55	10.05	34.60	46.37	-11.77	AVG
9	0.6177	22.06	10.04	32.10	56.00	-23.90	QP
10	0.6177	15.11	10.04	25.15	46.00	-20.85	AVG
11	1.7944	20.01	10.00	30.01	56.00	-25.99	QP
12	1.7944	13.25	10.00	23.25	46.00	-22.75	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

Test Mode:	802.11a20	Frequency(MHz):	5180
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1513	43.30	10.24	53.54	65.93	-12.39	QP
2	0.1513	29.09	10.24	39.33	55.93	-16.60	AVG
3	0.1898	36.59	10.16	46.75	64.05	-17.30	QP
4	0.1898	25.91	10.16	36.07	54.05	-17.98	AVG
5	0.3252	32.43	10.10	42.53	59.57	-17.04	QP
6	0.3252	23.44	10.10	33.54	49.57	-16.03	AVG
7	0.4397	29.38	10.06	39.44	57.07	-17.63	QP
8	0.4397	16.92	10.06	26.98	47.07	-20.09	AVG
9	0.6094	23.14	10.04	33.18	56.00	-22.82	QP
10	0.6094	10.95	10.04	20.99	46.00	-25.01	AVG
11	4.2050	20.52	10.34	30.86	56.00	-25.14	QP
12	4.2050	11.38	10.34	21.72	46.00	-24.28	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

10. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.407(a)

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

11. TEST DATA

11.1. APPENDIX A: EMISSION BANDWIDTH




11.1.1. Test Result


Test Mode	Antenna	Frequency[MHz]	26db EBW [MHz]	FL[MHz]	FH[MHz]	
11A	Ant1	5180	23.20	5168.64	5191.84	
	Ant2	5180	24.36	5168.24	5192.60	
	Ant1	5200	24.96	5187.64	5212.60	
	Ant2	5200	24.84	5186.88	5211.72	
	Ant1	5240	19.96	5230.16	5250.12	
	Ant2	5240	20.12	5230.00	5250.12	
	Ant1	5260	25.28	5247.00	5272.28	
	Ant2	5260	23.76	5248.00	5271.76	
	Ant1	5280	25.28	5266.92	5292.20	
	Ant2	5280	24.52	5267.24	5291.76	
	Ant1	5320	24.92	5307.40	5332.32	
	Ant2	5320	25.16	5307.48	5332.64	
	Ant1	5500	23.80	5487.92	5511.72	
	Ant2	5500	23.84	5488.80	5512.64	
	Ant1	5580	23.44	5568.08	5591.52	
	Ant2	5580	23.80	5568.16	5591.96	
	Ant1	5700	23.64	5687.88	5711.52	
	Ant2	5700	23.04	5688.28	5711.32	
	Ant1	5720	23.88	5708.00	5731.88	
	Ant2	5720	22.80	5708.88	5731.68	
	Ant1	5720_UNII-2C	17	5708.00	5725	
	Ant2	5720_UNII-2C	16.12	5708.88	5725	
	Ant1	5720_UNII-3	6.88	5725	5731.88	
	Ant2	5720_UNII-3	6.68	5725	5731.68	
	Ant1	5745	24.12	5732.48	5756.60	
	Ant2	5745	24.92	5731.96	5756.88	
	Ant1	5785	23.56	5773.12	5796.68	
	Ant2	5785	25.08	5771.88	5796.96	
	Ant1	5825	22.56	5813.76	5836.32	
	Ant2	5825	23.52	5813.04	5836.56	
	11N20MIMO	Ant1	5180	25.80	5166.84	5192.64
		Ant2	5180	25.08	5167.92	5193.00
Ant1		5200	25.72	5187.36	5213.08	
Ant2		5200	23.36	5188.12	5211.48	
Ant1		5240	20.56	5229.68	5250.24	
Ant2		5240	19.92	5230.04	5249.96	
Ant1		5260	25.20	5246.84	5272.04	
Ant2		5260	23.44	5248.92	5272.36	
Ant1		5280	24.12	5267.76	5291.88	
Ant2		5280	23.20	5268.32	5291.52	
Ant1		5320	25.88	5307.28	5333.16	
Ant2		5320	23.88	5308.04	5331.92	
Ant1		5500	25.68	5486.92	5512.60	
Ant2		5500	23.92	5488.52	5512.44	
Ant1		5580	23.96	5567.88	5591.84	
Ant2		5580	24.88	5567.60	5592.48	
Ant1		5700	25.60	5686.92	5712.52	
Ant2		5700	23.64	5688.20	5711.84	
Ant1		5720	23.88	5708.40	5732.28	
Ant2		5720	23.32	5708.44	5731.76	
Ant1		5720_UNII-2C	16.6	5708.40	5725	
Ant2		5720_UNII-2C	16.56	5708.44	5725	
Ant1		5720_UNII-3	7.28	5725	5732.28	
Ant2		5720_UNII-3	6.76	5725	5731.76	
Ant1		5745	25.48	5731.84	5757.32	
Ant2		5745	24.52	5731.92	5756.44	

	Ant1	5785	25.52	5771.84	5797.36	
	Ant2	5785	23.72	5772.76	5796.48	
	Ant1	5825	25.52	5812.32	5837.84	
	Ant2	5825	24.44	5812.88	5837.32	
11N40MIMO	Ant1	5190	40.96	5169.52	5210.48	
	Ant2	5190	40.40	5169.84	5210.24	
	Ant1	5230	40.88	5209.52	5250.40	
	Ant2	5230	40.24	5210.00	5250.24	
	Ant1	5270	41.12	5249.52	5290.64	
	Ant2	5270	40.24	5249.84	5290.08	
	Ant1	5310	41.36	5289.36	5330.72	
	Ant2	5310	40.40	5289.68	5330.08	
	Ant1	5510	40.80	5489.60	5530.40	
	Ant2	5510	40.16	5489.92	5530.08	
	Ant1	5550	40.88	5529.60	5570.48	
	Ant2	5550	40.48	5529.68	5570.16	
	Ant1	5670	40.88	5649.68	5690.56	
	Ant2	5670	40.56	5649.84	5690.40	
	Ant1	5710	40.64	5689.76	5730.40	
	Ant2	5710	40.56	5689.76	5730.32	
	Ant1	5710_UNII-2C	35.24	5689.76	5725	
	Ant2	5710_UNII-2C	35.24	5689.76	5725	
	Ant1	5710_UNII-3	5.4	5725	5730.40	
	Ant2	5710_UNII-3	5.32	5725	5730.32	
	Ant1	5755	41.04	5734.52	5775.56	
	Ant2	5755	40.40	5734.84	5775.24	
	Ant1	5795	40.80	5774.68	5815.48	
	Ant2	5795	40.40	5774.84	5815.24	
11AC80MIMO	Ant1	5210	80.48	5169.84	5250.32	
	Ant2	5210	80.00	5170.00	5250.00	
	Ant1	5290	80.48	5249.84	5330.32	
	Ant2	5290	80.16	5250.00	5330.16	
	Ant1	5530	80.48	5489.68	5570.16	
	Ant2	5530	80.00	5490.00	5570.00	
	Ant1	5610	80.16	5570.00	5650.16	
	Ant2	5610	80.16	5570.00	5650.16	
	Ant1	5690	80.48	5649.84	5730.32	
	Ant2	5690	80.16	5650.00	5730.16	
	Ant1	5690_UNII-2C	75.16	5649.84	5725	
	Ant2	5690_UNII-2C	75	5650.00	5725	
	Ant1	5690_UNII-3	5.32	5725	5730.32	
	Ant2	5690_UNII-3	5.16	5725	5730.16	
	Ant1	5775	80.32	5735.00	5815.32	
	Ant2	5775	80.16	5735.00	5815.16	
	11AX20MIMO	Ant1	5180	21.28	5169.48	5190.76
		Ant2	5180	22.20	5169.20	5191.40
Ant1		5200	22.36	5189.08	5211.44	
Ant2		5200	21.28	5189.28	5210.56	
Ant1		5240	20.08	5229.92	5250.00	
Ant2		5240	20.04	5229.96	5250.00	
Ant1		5260	21.52	5249.20	5270.72	
Ant2		5260	21.92	5249.24	5271.16	
Ant1		5280	21.88	5269.20	5291.08	
Ant2		5280	22.16	5269.12	5291.28	
Ant1		5320	21.72	5309.24	5330.96	
Ant2		5320	21.36	5309.28	5330.64	
Ant1		5500	22.96	5488.60	5511.56	
Ant2		5500	21.80	5489.00	5510.80	
Ant1		5580	21.56	5569.08	5590.64	
Ant2		5580	21.12	5569.48	5590.60	
Ant1		5700	21.44	5689.16	5710.60	
Ant2		5700	21.72	5689.16	5710.88	
Ant1		5720	21.16	5709.48	5730.64	
Ant2		5720	22.28	5708.92	5731.20	


	Ant1	5720_UNII-2C	15.52	5709.48	5725
	Ant2	5720_UNII-2C	16.08	5708.92	5725
	Ant1	5720_UNII-3	5.64	5725	5730.64
	Ant2	5720_UNII-3	6.2	5725	5731.20
	Ant1	5745	21.08	5734.48	5755.56
	Ant2	5745	21.20	5734.52	5755.72
	Ant1	5785	22.20	5773.80	5796.00
	Ant2	5785	21.36	5774.28	5795.64
	Ant1	5825	21.68	5814.28	5835.96
	Ant2	5825	21.80	5813.84	5835.64
11AX40MIMO	Ant1	5190	39.76	5170.16	5209.92
	Ant2	5190	39.76	5170.08	5209.84
	Ant1	5230	39.84	5210.16	5250.00
	Ant2	5230	39.76	5210.24	5250.00
	Ant1	5270	39.76	5250.16	5289.92
	Ant2	5270	39.84	5250.16	5290.00
	Ant1	5310	40.00	5290.00	5330.00
	Ant2	5310	39.76	5290.16	5329.92
	Ant1	5510	39.92	5490.08	5530.00
	Ant2	5510	39.76	5490.16	5529.92
	Ant1	5550	39.92	5530.08	5570.00
	Ant2	5550	39.92	5530.08	5570.00
	Ant1	5670	39.84	5650.16	5690.00
	Ant2	5670	39.92	5650.08	5690.00
	Ant1	5710	39.92	5690.00	5729.92
	Ant2	5710	39.76	5690.16	5729.92
	Ant1	5710_UNII-2C	35	5690.00	5725
	Ant2	5710_UNII-2C	34.84	5690.16	5725
	Ant1	5710_UNII-3	4.92	5725	5729.92
	Ant2	5710_UNII-3	4.92	5725	5729.92
	Ant1	5755	39.92	5735.00	5774.92
	Ant2	5755	39.92	5735.08	5775.00
	Ant1	5795	40.00	5775.00	5815.00
	Ant2	5795	39.84	5775.08	5814.92
11AX80MIMO	Ant1	5210	80.64	5169.84	5250.48
	Ant2	5210	80.48	5169.84	5250.32
	Ant1	5290	80.96	5249.68	5330.64
	Ant2	5290	80.80	5249.68	5330.48
	Ant1	5530	80.48	5489.84	5570.32
	Ant2	5530	80.80	5489.68	5570.48
	Ant1	5610	80.64	5569.84	5650.48
	Ant2	5610	80.64	5569.84	5650.48
	Ant1	5690	80.64	5649.68	5730.32
	Ant2	5690	80.32	5650.00	5730.32
	Ant1	5690_UNII-2C	75.32	5649.68	5725
	Ant2	5690_UNII-2C	75	5650.00	5725
	Ant1	5690_UNII-3	5.32	5725	5730.32
	Ant2	5690_UNII-3	5.32	5725	5730.32
	Ant1	5775	80.80	5734.68	5815.48
	Ant2	5775	80.48	5734.84	5815.32

11.1.2. Test Graphs







Date: 18.MAY.2024 08:23:01






Date: 18.MAY.2024 08:21:20




Date: 18.MAY.2024 08:24:35




Date: 18.MAY.2024 07:46:47




11A_Ant2_5280




Date: 18.MAY.2024 07:50:01



Date: 18.MAY.2024 08:41:35



Date: 18.MAY.2024 07:51:09



Date: 18.MAY.2024 08:44:25

