

Measurement Results

1-0981/20-01-03_log2_conducted

[Test logging](#)

This addendum is electronically signed and valid without handwritten signature.
For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorized:

Andreas Kurzkurt
Testing Manager
Radio Communications & EMC

Table of Content

EUT Summary	3
1. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode	4
2. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode	6
3. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode	8
4. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode	10
5. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode	12
6. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode	14
7. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode	16
8. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode	18
9. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode	20
10. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode	22
11. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode	25
12. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode	28
13. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode	31
14. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode	34
15. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode	37
16. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode	40
17. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode	43
18. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode	46
19. FCC Part 15.247 TX Spurious Conduced ~ WLAN2G4 b-mode	49
20. FCC Part 15.247 TX Spurious Conduced ~ WLAN2G4 b-mode	51
21. FCC Part 15.247 TX Spurious Conduced ~ WLAN2G4 b-mode	53
22. FCC Part 15.247 TX Spurious Conduced ~ WLAN2G4 g-mode	55
23. FCC Part 15.247 TX Spurious Conduced ~ WLAN2G4 g-mode	57
24. FCC Part 15.247 TX Spurious Conduced ~ WLAN2G4 g-mode	59
25. FCC Part 15.247 TX Spurious Conduced ~ WLAN2G4 nHT20-mode	61
26. FCC Part 15.247 TX Spurious Conduced ~ WLAN2G4 nHT20-mode	63
27. FCC Part 15.247 TX Spurious Conduced ~ WLAN2G4 nHT20-mode	65
28. Common2G4 Peak OP 3MHz/3MHz ~ WLAN2G4 b-mode	67
29. Common2G4 Peak OP 3MHz/3MHz ~ WLAN2G4 b-mode	69
30. Common2G4 Peak OP 3MHz/3MHz ~ WLAN2G4 b-mode	71

EUT Summary

EUT DEFINITION	
Manufacturer	MEC electronics Entwicklung und Produktion GmbH
Type	Display Unit
Kind	DM1ALM
Serial Number Setup Number	1264999921080002
Version SW FW HW	NI NI NI
Comment 1 2	
Temperature [°C] Min Nom Max	-20 20 55
Voltage [V] Min Nom Max @Current Max [A]	5V

EUT Common Settings WLAN2G4	
Number of Antenna Ports	1
User Interaction	No

1. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 10:11:50
Ambit Temp [°C] Humidity [rel%]	24.3 28
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2412 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	--	--	16.77	dBm	PASS

TEST FINISHED	
General Verdict	PASS

2. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 10:22:28
Ambit Temp [°C] Humidity [rel%]	24.5 27
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2437 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	--	--	17.26	dBm	PASS

TEST FINISHED	
General Verdict	PASS

3. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 10:33:16
Ambit Temp [°C] Humidity [rel%]	24.5 26
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2462 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	--	--	16.75	dBm	PASS

TEST FINISHED	
General Verdict	PASS

4. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode

Test References	
TC Start	16.03.2021 10:44:06
Ambit Temp [°C] Humidity [rel%]	24.6 26
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2412 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	--	--	17.41	dBm	PASS

TEST FINISHED	
General Verdict	PASS

5. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode

Test References	
TC Start	16.03.2021 10:57:04
Ambit Temp [°C] Humidity [rel%]	24.6 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2437 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	--	--	17.89	dBm	PASS

TEST FINISHED	
General Verdict	PASS

6. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode

Test References	
TC Start	16.03.2021 11:07:39
Ambit Temp [°C] Humidity [rel%]	24.7 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2462 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	--	--	17.57	dBm	PASS

TEST FINISHED	
General Verdict	PASS

7. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	16.03.2021 11:18:33
Ambit Temp [°C] Humidity [rel%]	24.7 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 nHT20-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2412 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	--	--	17.22	dBm	PASS

TEST FINISHED	
General Verdict	PASS

8. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	16.03.2021 11:29:12
Ambit Temp [°C] Humidity [rel%]	24.7 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 nHT20-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2437 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	--	--	17.87	dBm	PASS

TEST FINISHED	
General Verdict	PASS

9. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	16.03.2021 11:41:26
Ambit Temp [°C] Humidity [rel%]	24.7 24
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 nHT20-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2462 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	--	--	17.28	dBm	PASS


TEST FINISHED	
General Verdict	PASS

10. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 10:10:53
Ambit Temp [°C] Humidity [rel%]	24.3 28
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - 8.7.3 Integration Method; ANSI C63.10-2013 11.13.3.4 Trace averaging across on- and off-times of the EUT transmissions followed by duty cycle correction
TC Version	0.0.1
My Description	FCC 15.247 Restricted Band Edge Cond. Avg DC corrected DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Antenna Gain Table	
Freq [MHz]	Gain [dBi]
2412	-7.4
2437	-3.2
2462	-2.3



Plot_GainTable_16032021_101059.png

Test at TX 2412 MHz

Duty Cycle evaluation					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode 2412 MHz - DutyCycle_16032021_101117.png

READ SA SETTINGS:	
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.77 16.35 20
Start [MHz] Stop [MHz]	2388.000 2390.000
RBW [MHz] VBW [MHz]	0.100000 0.500000
Detector TraceMode	RMS AVER
Sweep: Time [ms] Count Points per Section Type	32 300 32000 SWE

Antenna Gain	
Considered Antenna Gain: [dBi]:	-7.4 @ 2389.5MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Duty Cycle worst case	---	---	0	dB	INFO
Band Power Avg	---	---	-57.14	dBm	INFO
Band Power Avg DC corrected	---	---	-57.14	dBm	PASS



Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode_16032021_101145.png

TEST FINISHED

General Verdict


PASS

11. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 10:21:31
Ambit Temp [°C] Humidity [rel%]	24.5 27
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - 8.7.3 Integration Method; ANSI C63.10-2013 11.13.3.4 Trace averaging across on- and off-times of the EUT transmissions followed by duty cycle correction
TC Version	0.0.1
My Description	FCC 15.247 Restricted Band Edge Cond. Avg DC corrected DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Antenna Gain Table	
Freq [MHz]	Gain [dBi]
2412	-7.4
2437	-3.2
2462	-2.3



Plot_GainTable_16032021_102138.png

Test at TX 2437 MHz

Duty Cycle evaluation					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode 2437 MHz - DutyCycle_16032021_102155.png

READ SA SETTINGS:	
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	20.57 16.22 20
Start [MHz] Stop [MHz]	2388.000 2390.000
RBW [MHz] VBW [MHz]	0.100000 0.500000
Detector TraceMode	RMS AVER
Sweep: Time [ms] Count Points per Section Type	32 300 32000 SWE

Antenna Gain	
Considered Antenna Gain: [dBi]:	-7.4 @ 2389.5MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Duty Cycle worst case	---	---	0	dB	INFO
Band Power Avg	---	---	-58.85	dBm	INFO
Band Power Avg DC corrected	---	---	-58.85	dBm	PASS



Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode_16032021_102223.png

TEST FINISHED

General Verdict


PASS

12. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 10:32:19
Ambit Temp [°C] Humidity [rel%]	24.5 26
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - 8.7.3 Integration Method; ANSI C63.10-2013 11.13.3.4 Trace averaging across on- and off-times of the EUT transmissions followed by duty cycle correction
TC Version	0.0.1
My Description	FCC 15.247 Restricted Band Edge Cond. Avg DC corrected DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Antenna Gain Table	
Freq [MHz]	Gain [dBi]
2412	-7.4
2437	-3.2
2462	-2.3



Plot_GainTable_16032021_103226.png

Test at TX 2462 MHz

Duty Cycle evaluation					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode 2462 MHz - DutyCycle_16032021_103244.png

READ SA SETTINGS:	
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	20.00 16.12 20
Start [MHz] Stop [MHz]	2483.500 2485.500
RBW [MHz] VBW [MHz]	0.100000 0.500000
Detector TraceMode	RMS AVER
Sweep: Time [ms] Count Points per Section Type	32 300 32000 SWE

Antenna Gain	
Considered Antenna Gain: [dBi]:	-2.3 @ 2484MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Duty Cycle worst case	---	---	0	dB	INFO
Band Power Avg	---	---	-52.33	dBm	INFO
Band Power Avg DC corrected	---	---	-52.33	dBm	PASS



Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 b-mode_16032021_103311.png

TEST FINISHED

General Verdict


PASS

13. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode

Test References	
TC Start	16.03.2021 10:43:08
Ambit Temp [°C] Humidity [rel%]	24.6 26
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - 8.7.3 Integration Method; ANSI C63.10-2013 11.13.3.4 Trace averaging across on- and off-times of the EUT transmissions followed by duty cycle correction
TC Version	0.0.1
My Description	FCC 15.247 Restricted Band Edge Cond. Avg DC corrected DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Antenna Gain Table	
Freq [MHz]	Gain [dBi]
2412	-7.4
2437	-3.2
2462	-2.3



Plot_GainTable_16032021_104315.png

Test at TX 2412 MHz

Duty Cycle evaluation					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode 2412 MHz - DutyCycle_16032021_104333.png

READ SA SETTINGS:	
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.91 16.35 20
Start [MHz] Stop [MHz]	2388.000 2390.000
RBW [MHz] VBW [MHz]	0.100000 0.500000
Detector TraceMode	RMS AVER
Sweep: Time [ms] Count Points per Section Type	32 300 32000 SWE

Antenna Gain	
Considered Antenna Gain: [dBi]:	-7.4 @ 2389.5MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Duty Cycle worst case	---	---	0	dB	INFO
Band Power Avg	---	---	-50.77	dBm	INFO
Band Power Avg DC corrected	---	---	-50.77	dBm	PASS



Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode_16032021_104400.png

TEST FINISHED

General Verdict


PASS

14. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode

Test References	
TC Start	16.03.2021 10:56:07
Ambit Temp [°C] Humidity [rel%]	24.6 26
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - 8.7.3 Integration Method; ANSI C63.10-2013 11.13.3.4 Trace averaging across on- and off-times of the EUT transmissions followed by duty cycle correction
TC Version	0.0.1
My Description	FCC 15.247 Restricted Band Edge Cond. Avg DC corrected DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Antenna Gain Table	
Freq [MHz]	Gain [dBi]
2412	-7.4
2437	-3.2
2462	-2.3



Plot_GainTable_16032021_105614.png

Test at TX 2437 MHz

Duty Cycle evaluation					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode 2437 MHz - DutyCycle_16032021_105631.png

READ SA SETTINGS:	
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.37 16.22 20
Start [MHz] Stop [MHz]	2388.000 2390.000
RBW [MHz] VBW [MHz]	0.100000 0.500000
Detector TraceMode	RMS AVER
Sweep: Time [ms] Count Points per Section Type	32 300 32000 SWE

Antenna Gain	
Considered Antenna Gain: [dBi]:	-7.4 @ 2389.5MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Duty Cycle worst case	---	---	0	dB	INFO
Band Power Avg	---	---	-58.89	dBm	INFO
Band Power Avg DC corrected	---	---	-58.89	dBm	PASS



Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode_16032021_105658.png

TEST FINISHED

General Verdict


PASS

15. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode

Test References	
TC Start	16.03.2021 11:06:41
Ambit Temp [°C] Humidity [rel%]	24.6 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - 8.7.3 Integration Method; ANSI C63.10-2013 11.13.3.4 Trace averaging across on- and off-times of the EUT transmissions followed by duty cycle correction
TC Version	0.0.1
My Description	FCC 15.247 Restricted Band Edge Cond. Avg DC corrected DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Antenna Gain Table	
Freq [MHz]	Gain [dBi]
2412	-7.4
2437	-3.2
2462	-2.3



Plot_GainTable_16032021_110649.png

Test at TX 2462 MHz

Duty Cycle evaluation					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode 2462 MHz - DutyCycle_16032021_110706.png

READ SA SETTINGS:	
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.96 16.12 20
Start [MHz] Stop [MHz]	2483.500 2485.500
RBW [MHz] VBW [MHz]	0.100000 0.500000
Detector TraceMode	RMS AVER
Sweep: Time [ms] Count Points per Section Type	32 300 32000 SWE

Antenna Gain	
Considered Antenna Gain: [dBi]:	-2.3 @ 2484MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Duty Cycle worst case	---	---	0	dB	INFO
Band Power Avg	---	---	-46.35	dBm	INFO
Band Power Avg DC corrected	---	---	-46.35	dBm	PASS



Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 g-mode_16032021_110734.png

TEST FINISHED

General Verdict


PASS

16. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode

Test References	
TC Start	16.03.2021 11:17:34
Ambit Temp [°C] Humidity [rel%]	24.7 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - 8.7.3 Integration Method; ANSI C63.10-2013 11.13.3.4 Trace averaging across on- and off-times of the EUT transmissions followed by duty cycle correction
TC Version	0.0.1
My Description	FCC 15.247 Restricted Band Edge Cond. Avg DC corrected DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Antenna Gain Table	
Freq [MHz]	Gain [dBi]
2412	-7.4
2437	-3.2
2462	-2.3



Plot_GainTable_16032021_111742.png

Test at TX 2412 MHz

Duty Cycle evaluation					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode 2412 MHz - DutyCycle_16032021_111800.png

READ SA SETTINGS:	
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.33 16.35 20
Start [MHz] Stop [MHz]	2388.000 2390.000
RBW [MHz] VBW [MHz]	0.100000 0.500000
Detector TraceMode	RMS AVER
Sweep: Time [ms] Count Points per Section Type	32 300 32000 SWE

Antenna Gain	
Considered Antenna Gain: [dBi]:	-7.4 @ 2389.5MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Duty Cycle worst case	---	---	0	dB	INFO
Band Power Avg	---	---	-49.18	dBm	INFO
Band Power Avg DC corrected	---	---	-49.18	dBm	PASS



Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode_16032021_111827.png

TEST FINISHED

General Verdict


PASS

17. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode

Test References	
TC Start	16.03.2021 11:28:13
Ambit Temp [°C] Humidity [rel%]	24.7 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - 8.7.3 Integration Method; ANSI C63.10-2013 11.13.3.4 Trace averaging across on- and off-times of the EUT transmissions followed by duty cycle correction
TC Version	0.0.1
My Description	FCC 15.247 Restricted Band Edge Cond. Avg DC corrected DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Antenna Gain Table	
Freq [MHz]	Gain [dBi]
2412	-7.4
2437	-3.2
2462	-2.3



Plot_GainTable_16032021_112821.png

Test at TX 2437 MHz

Duty Cycle evaluation					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode 2437 MHz - DutyCycle_16032021_112838.png

READ SA SETTINGS:	
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.59 16.22 20
Start [MHz] Stop [MHz]	2388.000 2390.000
RBW [MHz] VBW [MHz]	0.100000 0.500000
Detector TraceMode	RMS AVER
Sweep: Time [ms] Count Points per Section Type	32 300 32000 SWE

Antenna Gain	
Considered Antenna Gain: [dBi]:	-7.4 @ 2389.5MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Duty Cycle worst case	---	---	0	dB	INFO
Band Power Avg	---	---	-58.9	dBm	INFO
Band Power Avg DC corrected	---	---	-58.9	dBm	PASS



Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode_16032021_112906.png

TEST FINISHED

General Verdict


PASS

18. FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode

Test References	
TC Start	16.03.2021 11:40:27
Ambit Temp [°C] Humidity [rel%]	24.7 24
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - 8.7.3 Integration Method; ANSI C63.10-2013 11.13.3.4 Trace averaging across on- and off-times of the EUT transmissions followed by duty cycle correction
TC Version	0.0.1
My Description	FCC 15.247 Restricted Band Edge Cond. Avg DC corrected DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Antenna Gain Table	
Freq [MHz]	Gain [dBi]
2412	-7.4
2437	-3.2
2462	-2.3



Plot_GainTable_16032021_114035.png

Test at TX 2462 MHz

Duty Cycle evaluation					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode 2462 MHz - DutyCycle_16032021_114053.png

READ SA SETTINGS:	
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.36 16.12 20
Start [MHz] Stop [MHz]	2483.500 2485.500
RBW [MHz] VBW [MHz]	0.100000 0.500000
Detector TraceMode	RMS AVER
Sweep: Time [ms] Count Points per Section Type	32 300 32000 SWE

Antenna Gain	
Considered Antenna Gain: [dBi]:	-2.3 @ 2484MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Duty Cycle worst case	---	---	0	dB	INFO
Band Power Avg	---	---	-44.82	dBm	INFO
Band Power Avg DC corrected	---	---	-44.82	dBm	PASS



Plot_FCC Part 15.247 Restricted Band Edge Conducted Avg DC corrected DTS (eirp) ~ WLAN2G4 nHT20-mode_16032021_114121.png

TEST FINISHED

General Verdict

PASS

19. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 10:04:48
Ambit Temp [°C] Humidity [rel%]	24.2 29
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2412 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.85 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2412.50 MHz	---	---	6.29	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 24962.167 MHz	0	---	20.93	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode 2412_16032021_101041.png



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode 2412_16032021_101046.png

TEST FINISHED

General Verdict

PASS

20. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 10:15:26
Ambit Temp [°C] Humidity [rel%]	24.4 28
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	10.57 0 30
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2437.50 MHz	---	---	5.92	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 30 MHz	0	---	-152.86	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode 2437_16032021_102119.png



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode 2437_16032021_102124.png

TEST FINISHED

General Verdict

PASS

21. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 10:26:14
Ambit Temp [°C] Humidity [rel%]	24.5 27
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2462 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.98 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2461.50 MHz	---	---	5.81	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 24953.167 MHz	0	---	20.21	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode 2462_16032021_103207.png



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode 2462_16032021_103212.png

TEST FINISHED

General Verdict

PASS

22. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 g-mode

Test References	
TC Start	16.03.2021 10:37:03
Ambit Temp [°C] Humidity [rel%]	24.5 26
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2412 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	8.62 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2410.67 MHz	---	---	-0.42	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 30 MHz	0	---	-148.14	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 g-mode 2412_16032021_104256.png



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 g-mode 2412_16032021_104301.png

TEST FINISHED

General Verdict

PASS

23. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 g-mode

Test References	
TC Start	16.03.2021 10:50:02
Ambit Temp [°C] Humidity [rel%]	24.6 26
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	8.19 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2442.00 MHz	---	---	-0.88	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 22919.5 MHz	0	---	13.66	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conduced ~ WLAN2G4 g-mode 2437_16032021_105554.png



Plot_FCC Part 15.247 TX Spurious Conduced ~ WLAN2G4 g-mode 2437_16032021_105600.png

TEST FINISHED

General Verdict

PASS

24. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 g-mode

Test References	
TC Start	16.03.2021 11:00:36
Ambit Temp [°C] Humidity [rel%]	24.6 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60



Test at TX 2462 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	7.97 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2455.83 MHz	---	---	-0.23	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 30 MHz	0	---	-147.88	dB	INFO



TEST FINISHED

General Verdict

PASS

25. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode

Test References	
TC Start	16.03.2021 11:11:29
Ambit Temp [°C] Humidity [rel%]	24.7 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2412 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	7.69 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2407.00 MHz	---	---	-0.31	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 2399.5 MHz	0	---	6.68	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode 2412_16032021_111722.png



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode 2412_16032021_111722.png

TEST FINISHED

General Verdict

PASS

26. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode

Test References	
TC Start	16.03.2021 11:22:08
Ambit Temp [°C] Humidity [rel%]	24.7 25
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	8.32 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2438.17 MHz	---	---	0.10	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 24262.833 MHz	0	---	14.39	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode 2437_16032021_112800.png



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode 2437_16032021_112806.png

TEST FINISHED

General Verdict

PASS

27. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode

Test References	
TC Start	16.03.2021 11:34:21
Ambit Temp [°C] Humidity [rel%]	24.7 24
System Version	2.0.0.4
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2462 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	7.53 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2467.00 MHz	---	---	-1.02	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 24180 MHz	0	---	13.41	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode 2462_16032021_114015.png



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode 2462_16032021_114021.png

TEST FINISHED

General Verdict

PASS

28. Common2G4 Peak OP 3MHz/3MHz ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 08:57:49
Ambit Temp [°C] Humidity [rel%]	23.6 26
System Version	2.0.0.4
Test Specification	None
Test Method	
TC Version	0.0.1
My Description	Peak Output Power conducted 3MHz/3MHz WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2412 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	27.10 16.35 30
Start [MHz] Stop [MHz]	2362.000 2462.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 10 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	17.07	dBm	Info
Peak Power	---	---	50.933087	mW	Info
Frequency at Peak	---	---	2412	MHz	Info



Plot_Common2G4 Peak OP 3MHz-3MHz ~ WLAN2G4 b-mode_16032021_085829.png

TEST FINISHED

General Verdict

PASS

29. Common2G4 Peak OP 3MHz/3MHz ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 08:58:34
Ambit Temp [°C] Humidity [rel%]	23.7 26
System Version	2.0.0.4
Test Specification	None
Test Method	
TC Version	0.0.1
My Description	Peak Output Power conducted 3MHz/3MHz WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	27.42 16.22 30
Start [MHz] Stop [MHz]	2387.000 2487.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 10 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	17.36	dBm	Info
Peak Power	---	---	54.450265	mW	Info
Frequency at Peak	---	---	2436.8	MHz	Info



Plot_Common2G4 Peak OP 3MHz-3MHz ~ WLAN2G4 b-mode_16032021_085921.png

TEST FINISHED

General Verdict

PASS

30. Common2G4 Peak OP 3MHz/3MHz ~ WLAN2G4 b-mode

Test References	
TC Start	16.03.2021 08:59:26
Ambit Temp [°C] Humidity [rel%]	23.7 26
System Version	2.0.0.4
Test Specification	None
Test Method	
TC Version	0.0.1
My Description	Peak Output Power conducted 3MHz/3MHz WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.7
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2462 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	26.73 16.12 30
Start [MHz] Stop [MHz]	2412.000 2512.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 10 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	16.57	dBm	Info
Peak Power	---	---	45.394162	mW	Info
Frequency at Peak	---	---	2461.9	MHz	Info



Plot_Common2G4 Peak OP 3MHz-3MHz ~ WLAN2G4 b-mode_16032021_090010.png

TEST FINISHED

General Verdict

PASS

- END OF DOCUMENT -