



TEST REPORT

Test report no.: 1-5071_22-01-04

BNetzA-CAB-02/21-102

Testing laboratory

CTC advanced GmbH

Untertuerkheimer Strasse 6 – 10

66117 Saarbruecken / Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

Internet: <https://www.ctcadvanced.com>

e-mail: mail@ctcadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkKS)

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate starting with the registration number: D-PL-12076-01.

Applicant

Building 36 Technologies, LLC

150 A Street, Suite 104

02494-0249 Needham / UNITED STATES

Phone: 781-474-0500

Contact: Daniel Goodman

e-mail: dan@building36.com

Manufacturer

MEC electronics Entwicklung und Produktion GmbH

Dresdner Straße 45

1200 Vienna (Wien) / AUSTRIA

Contact: DI Helmut Kraus

Test standard/s

FCC - Title 47 CFR Part 24 FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 24 - Personal communications services

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item: **Display**
Model name: **ADC-T40-HQ**
FCC ID: **2AC3T-B36T40HQRA**
ISED certification number: **12323A-B36T40HQRA**
Frequency: LTE band 2; 4; 12 and 13
Technology tested: LTE Cat M
Antenna: Integrated antenna
Power supply: 4.5 V to 5.5 V DC by external power supply
Temperature range: 5°C to 35°C

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorized:

Andreas Luckenbill
Head of Department
Radio Communications

Test performed:

Marco Bertolino
Lab Manager
Radio Communications

1 Table of contents

1	Table of contents.....	2
2	General information.....	4
2.1	Notes and disclaimer	4
2.2	Application details	4
2.3	Test laboratories sub-contracted	4
3	Test standard/s, references and accreditations	5
4	Reporting statements of conformity – decision rule	6
5	Test environment.....	7
6	Test item	7
6.1	General description	7
6.2	Additional information	7
7	Description of the test setup.....	8
7.1	Shielded semi anechoic chamber	9
7.2	Shielded fully anechoic chamber.....	10
7.3	Radiated measurements > 18 GHz	11
7.4	Conducted measurements normal and extreme conditions	12
8	Sequence of testing.....	13
8.1	Sequence of testing radiated spurious 9 kHz to 30 MHz	13
8.2	Sequence of testing radiated spurious 30 MHz to 1 GHz.....	14
8.3	Sequence of testing radiated spurious 1 GHz to 18 GHz.....	15
8.4	Sequence of testing radiated spurious above 18 GHz.....	16
9	Measurement uncertainty.....	17
10	Additional information and comments	17
11	Summary of measurement results	18
11.1	Part 24/RSS-133: LTE band 2	18
12	RF measurements	19
12.1	Description of test setup.....	19
12.2	Results LTE band 2	19
12.2.1	RF output power	19
12.2.2	Frequency stability.....	21
12.2.3	Spurious emissions radiated.....	23
12.2.4	Spurious emissions conducted.....	30
12.2.5	Block edge compliance	39
12.2.6	Occupied bandwidth	43
13	Summary of measurement results	51
13.1	Part 27/RSS-139: LTE band 4	51
13.2	Part 27/RSS-130: LTE band 12	52
13.3	Part 27/RSS-130: LTE band 13	52
14	RF measurements	53

14.1	Description of test setup.....	53
14.2	LTE technologies supported by EUT.....	53
14.3	Results LTE band 4	54
14.3.1	RF output power	54
14.3.2	Frequency stability	56
14.3.3	Spurious emissions radiated.....	58
14.3.4	Spurious emissions conducted.....	65
14.3.5	Block edge compliance	74
14.3.6	Occupied bandwidth	78
14.4	Results LTE band 12	86
14.4.1	RF output power	86
14.4.2	Frequency stability	89
14.4.3	Spurious emissions radiated.....	91
14.4.4	Spurious emissions conducted.....	97
14.4.5	Block edge compliance	105
14.4.6	Occupied bandwidth	108
14.5	Results LTE band 13	116
14.5.1	RF output power	116
14.5.2	Frequency stability	118
14.5.3	Spurious emissions radiated.....	120
14.5.4	Spurious emissions conducted.....	126
14.5.5	Block edge compliance	134
14.5.6	Occupied bandwidth	138
15	Observations.....	146
16	Glossary.....	147
17	Document history.....	148
18	Accreditation Certificate – D-PL-12076-01-04	148
19	Accreditation Certificate – D-PL-12076-01-05	149

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CTC advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTC advanced GmbH.

The testing service provided by CTC advanced GmbH has been rendered under the current "General Terms and Conditions for CTC advanced GmbH".

CTC advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CTC advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CTC advanced GmbH test report include or imply any product or service warranties from CTC advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CTC advanced GmbH.

All rights and remedies regarding vendor's products and services for which CTC advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by CTC advanced GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

2.2 Application details

Date of receipt of order:	2022-12-07
Date of receipt of test item:	2023-01-16
Start of test:*	2023-01-16
End of test:*	2023-02-29
Person(s) present during the test:	-/-

*Date of each measurement, if not shown in the plot, can be requested. Dates are stored in the measurement software.




2.3 Test laboratories sub-contracted

None

3 Test standard/s, references and accreditations

Test standard	Date	Description
FCC - Title 47 CFR Part 24	-/-	FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 24 - Personal communications services
FCC - Title 47 CFR Part 27	-/0	FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 27 - Miscellaneous wireless communications services
RSS - 133 Issue 6	January 2018	Spectrum Management and Telecommunications Policy - Radio Standards Specifications, 2 GHz Personal Communication Services
RSS - 130 Issue 2	February 2019	Equipment Operating in the Frequency Bands 617-652 MHz, 663-698 MHz, 698-756 MHz and 777-787 MHz
RSS - 139 Issue 4	September 2022	Advanced Wireless Services Equipment Operating in the Bands 1710-1780 MHz and 2110-2200 MHz

Guidance	Version	Description
ANSI C63.4-2014	-/-	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.26-2015	-/-	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
Power Meas License Systems: KDB 971168 D01	v03r01	Measurement Guidance for Certification of Licensed Digital Transmitters


Accreditation	Description	
D-PL-12076-01-04	Telecommunication and EMC Canada https://www.dakks.de/as/ast/d/D-PL-12076-01-04e.pdf	 
D-PL-12076-01-05	Telecommunication FCC requirements https://www.dakks.de/as/ast/d/D-PL-12076-01-05e.pdf	 

ISED Testing Laboratory Recognized Listing Number: DE0001
FCC designation number: DE0002

4 Reporting statements of conformity – decision rule

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3. The measurement uncertainty is mentioned in this test report, see chapter 9 but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong."

measured value, measurement uncertainty, verdict



7 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).


Each block diagram listed can contain several test setup configurations. All devices belonging to a test setup are identified with the same letter syntax. For example: Column Setup and all devices with an A.

Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlk!	Attention: extended calibration interval		
NK!	Attention: not calibrated	*)	next calibration ordered / currently in progress

7.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 30 MHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are conform to specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter; EMC32 software version: 10.59.00

FS = UR + CL + AF

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)


Example calculation:

FS [dB μ V/m] = 12.35 [dB μ V/m] + 1.90 [dB] + 16.80 [dB/m] = 31.05 [dB μ V/m] (35.69 μ V/m)

Equipment table:

No.	Setup	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Switch-Unit	3488A	HP	2719A14505	300000368	ev	-/-	-/-
2	A	Semi anechoic chamber	3000023	MWB AG	-/-	300000551	ne	-/-	-/-
3	A	Analyzer-Reference-System (Harmonics and Flicker)	ARS 16/1	SPS	A3509 07/0 0205	300003314	vKl!	29.12.2021	28.12.2023
4	A	Antenna Tower	Model 2175	ETS-Lindgren	64762	300003745	izw	-/-	-/-
5	A	Positioning Controller	Model 2090	ETS-Lindgren	64672	300003746	izw	-/-	-/-
6	A	Turntable Interface-Box	Model 105637	ETS-Lindgren	44583	300003747	izw	-/-	-/-
7	A	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck Mess - Elektronik	318	300003696	vKl!	30.09.2021	29.09.2023
8	A	Turntable	2089-4.0	EMCO	-/-	300004394	ne	-/-	-/-
9	A	PC	TecLine	F+W	-/-	300004388	ne	-/-	-/-
10	A	EMI Test Receiver	ESR3	Rohde & Schwarz	102587	300005771	k	09.12.2022	31.12.2023
11	A	Wideband radio communication tester	CMW500	Rohde & Schwarz	170616	300006251	k	16.09.2021	30.09.2023

7.2 Shielded fully anechoic chamber



Measurement distance: horn antenna 3 meter; loop antenna 3 meter

$$OP = AV + D - G + CA$$

(OP-radiated output power; AV-analyzer value; D-free field attenuation of measurement distance; G-antenna gain+amplifier gain; CA-loss signal path)


Example calculation:

$$OP [dBm] = -39.0 [dBm] + 57.0 [dB] - 12.0 [dBi] + (-36.0) [dB] = -30 [dBm] (1 \mu W)$$

Equipment table:

No.	Setup	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A, B, C	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	9107-3696	300001604	vKI!	12.03.2021	11.03.2023
2	A, B	Highpass Filter	WHK1.1/15G-10SS	Wainwright	37	400000148	ne	-/-	-/-
3	B	Band Reject Filter	WRCG1850/1910-1835/1925-40/8SS	Wainwright	23	400000149	ne	-/-	-/-
4	A, B	Highpass Filter	WHKX7.0/18G-8SS	Wainwright	18	300003789	ne	-/-	-/-
5	A	Band Reject Filter	WRCG824/849-810/863-60/9SS	Wainwright	6	300003791	ne	-/-	-/-
6	A, B	Broadband Amplifier 0.5-18 GHz	CBLU5184540	CERNEX	22051	300004483	ev	-/-	-/-
7	A, B, C	4U RF Switch Platform	L4491A	Agilent Technologies	MY50000032	300004510	ne	-/-	-/-
8	A, B, C	Computer	Intel Core i3 3220/3,3 GHz, Prozessor	-/-	2V2403033A 5421	300004591	ne	-/-	-/-
9	A, B, C	NEXIO EMV-Software	BAT EMC V3.21.0.27	EMCO	-/-	300004682	ne	-/-	-/-
10	A, B, C	Anechoic chamber	-/-	TDK	-/-	300003726	ne	-/-	-/-
11	A, B, C	EMI Test Receiver 9kHz-26,5GHz	ESR26	Rohde & Schwarz	101376	300005063	k	13.12.2022	31.12.2023
12	A, B	RF-Amplifier	AMF-6F06001800-30-10P-R	NARDA-MITEQ Inc	2011571	300005240	ev	-/-	-/-
13	A, B, C	Wideband radio communication tester	CMW500	Rohde & Schwarz	170616	300006251	k	16.09.2021	30.09.2023
14	A, B	Active Loop Antenna 9 kHz to 30 MHz	6502	EMCO	2210	300001015	vKI!	01.07.2021	31.07.2023

7.3 Radiated measurements > 18 GHz



Measurement distance: horn antenna 50 cm

$$OP = AV + D - G + CA$$

(OP-radiated output power; AV-analyzer value; D-free field attenuation of measurement distance; G-antenna gain+amplifier gain; CA-loss signal path)


Example calculation:

$$OP [dBm] = -59.0 [dBm] + 44.0 [dB] - 20.0 [dBi] + 5.0 [dB] = -30 [dBm] (1 \mu W)$$

Equipment table:

No.	Setup	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Microwave System Amplifier, 0.5-26.5 GHz	83017A	HP	00419	300002268	ev	-/-	-/-
2	A	Std. Gain Horn Antenna 18.0-26.5 GHz	638	Narda	01096	300000486	vIKI!	-/-	-/-
3	A	Signal analyzer	FSV40	Rohde&Schwarz	101042	300004517	k	12.12.2022	31.12.2023
4	A	RF-Cable	ST18/SMAm/SMAm /48	Huber & Suhner	Batch no. 127377	400001183	ev	-/-	-/-
5	A	DC-Blocker 0.1-40 GHz	8141A	Inmet	-/-	400001185	ev	-/-	-/-
6	A	Wideband radio communication tester	CMW500	Rohde & Schwarz	170616	300006251	k	16.09.2021	30.09.2023

7.4 Conducted measurements normal and extreme conditions



OP = AV + CA
 (OP-output power; AV-analyzer value; CA-loss signal path)

Example calculation:

OP [dBm] = 6.0 [dBm] + 11.7 [dB] = 17.7 [dBm] (58.88 mW)

Equipment table:

No.	Setup	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Temperature Test Chamber	VT 4002	Heraeus Voetsch	521/83761	300002326	g	-/-	-/-
2	A	Wideband radio communication tester	CMW500	Rohde & Schwarz	170616	300006251	k	16.09.2021	30.09.2023
3	A	Hygro-Thermometer	-/, 5-45°C, 20-100%rF	Thies Clima	-/-	400000108	ev	15.09.2022	30.09.2024
4	A	PC Tester R005	Intel Core i3 3220/3,3 GHz, Prozessor	-/-	2V2403033A4523	300004589	ne	-/-	-/-
5	A	Teststand	Teststand Custom Sequence Editor	National Instruments GmbH	-/-	300004590	ne	-/-	-/-
6	A	Resistive Power Dividers, DC-40 GHz, 1W	1575	MRC COMPONENTS	-/-	300004671	ne	-/-	-/-
7	A	USB-GPIB-Adapter	GPIB-USB-HS	National Instruments	1829974	400001136	ne	-/-	-/-
8	A	RF-Cable	ST18/SMAm/SMAm /72	Huber & Suhner	Batch no. 699714	400001184	ev	-/-	-/-
9	A	Signal analyzer	FSV40	Rohde&Schwarz	101042	300004517	k	12.12.2022	31.12.2023
10	A	RF-Cable	ST18/SMAm/SMAm /36	Huber & Suhner	Batch no. 601494	400001309	ev	-/-	-/-
11	A	DC-Blocker 0.1-40 GHz	8141A	Inmet	-/-	400001185	ev	-/-	-/-

8 Sequence of testing

8.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, it is placed on a table with 0.8 m height.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement*

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

Final measurement

- Identified emissions during the pre-measurement are maximized by the software by rotating the turntable from 0° to 360°.
- Loop antenna is rotated about its vertical axis for maximum response at each azimuth about the EUT. (For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT)
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

*Note: The sequence will be repeated three times with different EUT orientations.

8.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.3 Sequence of testing radiated spurious 1 GHz to 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.4 Sequence of testing radiated spurious above 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate (e.g. 0.5 m).
- The EUT is set into operation.

Premeasurement

- The test antenna is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.

Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

9 Measurement uncertainty

Measurement uncertainty		
Test case	Uncertainty	
Antenna gain	± 3 dB	
99 % bandwidth	± RBW	
-26 dB bandwidth	± RBW	
Frequency stability	10 ⁻⁶	
Maximum output power conducted	± 1.56 dB	
Block edge compliance	± 1.56 dB	
Spurious emissions conducted	> 3.6 GHz	± 1.56 dB
	> 7 GHz	± 1.56 dB
	> 18 GHz	± 2.31 dB
	≥ 40 GHz	± 2.97 dB
Spurious emissions radiated below 30 MHz	± 3 dB	
Spurious emissions radiated 30 MHz to 1 GHz	± 3 dB	
Spurious emissions radiated 1 GHz to 12.75 GHz	± 3.7 dB	
Spurious emissions radiated above 12.75 GHz	± 4.5 dB	

10 Additional information and comments

Reference documents: None

Special test descriptions: None

Configuration descriptions: None

- EUT selection:
- Only one device available
 - Devices selected by the customer
 - Devices selected by the laboratory (Randomly)

11 Summary of measurement results

<input checked="" type="checkbox"/>	No deviations from the technical specifications were ascertained
<input type="checkbox"/>	There were deviations from the technical specifications ascertained
<input type="checkbox"/>	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC: CFR Part 2 & Part 24 ISED: RSS-Gen, Issue 5 RSS 133, Issue 6 & SRSP-510, Issue 5	See table!	2023-03-24	-/-

11.1 Part 24/RSS-133: LTE band 2

Test Case	temperature conditions	power source voltages	C	NC	NA	NP	Remark
RF Output Power	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Frequency Stability	Extreme	Extreme	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Spurious Emissions Radiated	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Spurious Emissions Conducted	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Block Edge Compliance	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Occupied Bandwidth	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-

Notes:

C	Compliant	NC	Not compliant	NA	Not applicable	NP	Not performed
----------	-----------	-----------	---------------	-----------	----------------	-----------	---------------

12 RF measurements

12.1 Description of test setup

For the spurious measurements we use the substitution method according TIA/EIA 603.

12.2 Results LTE band 2

The EUT was set to transmit the maximum power.

12.2.1 RF output power

Description:

This paragraph contains average power, peak output power and EIRP measurements for the mobile station. In all cases, the peak output power is within the required mask (this mask is specified in the JTC standards, TIA PN3389 Vol. 1 Chap 7, and is no FCC requirement).

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

To determine the Peak-To-Average Power Ratio (PAPR) the measurement was performed with the Power Complementary Cumulative Distribution Function (CCDF).

Measurement parameters	
Detector:	Sample
AQT:	See plot
Resolution bandwidth:	1 MHz
Used equipment:	See chapter 7.2 setup C & 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure:	FCC: § 2.1046 ISED: RSS-Gen, 6.12

Limits:

FCC	ISED
§ 24.232(c)	RSS-133, 6.4 (referring to: SRSP-510, Issue 5)
(c) Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications. (d) In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	SRSP-510, 5.1: Mobile stations and hand-held portables are limited to 2 watts maximum e.i.r.p. RSS-133, 6.4: In addition, the transmitter's peak-to-average power ratio (PAPR) shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.
Power: 33 dBm EIRP PAPR: 13 dB	

Results:

Output Power (conducted)						
Bandwidth (MHz)	Channel No. / Frequency (MHz)	Resource block allocation	Average Output Power (dBm) QPSK	Peak to Average Ratio (dB)	Average Output Power (dBm) 16-QAM	Peak to Average Ratio (dB)
5	18625 / 1852.5	1 RB low	21.8	3.5	22.3	4.2
		1 RB high	22.2	3.4	22.3	4.2
		100% RB	21.3	4.5	20.4	5.4
	18900 / 1880.0	1 RB low	22.4	3.7	22.5	3.3
		1 RB high	22.3	3.8	22.4	3.2
		100% RB	21.4	5.1	20.5	4.3
	19175 / 1907.5	1 RB low	22.0	3.3	22.2	3.7
		1 RB high	22.0	3.4	22.2	3.7
		100% RB	21.3	4.1	20.4	5.0

The radiated output power is measured in the mode with the highest conducted output power.

Output Power (EIRP)			
Bandwidth (MHz)	Frequency (MHz)	Average Output Power (dBm) QPSK	Average Output Power (dBm) 16-QAM
5 100 % RB	1852.5	27.6	27.7
	1880.0	27.8	27.9
	1907.5	27.4	27.6

12.2.2 Frequency stability

Description:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the mobile station in a "call mode". This is accomplished with the use of a R&S CMW500 DIGITAL RADIOCOMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the mobile station to overnight soak at -30 C.
3. With the mobile station, powered with V_{nom} , connected to the CMW500 and in a simulated call on channel 9400 (centre channel), measure the carrier frequency. These measurements should be made within two minutes of powering up the mobile station, to prevent significant self warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with V_{nom} . Vary supply voltage from V_{min} to V_{max} , in 0.1 Volt steps remeasuring carrier frequency at each voltage. Pause at V_{nom} for 1.5 hours unpowered, to allow any self heating to stabilize, before continuing.
6. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

Measurement:

Measurement parameters	
Detector:	Measured with CMW500
Sweep time:	
Video bandwidth:	
Resolution bandwidth:	
Span:	
Trace-Mode:	
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure:	FCC: § 2.1055 ISED: RSS-Gen, 6.11

Limits:

FCC	ISED
§ 24.235	RSS-133, 6.3
The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.	The carrier frequency shall not depart from the reference frequency, in excess of ± 2.5 ppm for mobile stations and ± 1.0 ppm for base stations.
± 2.5 ppm (ISED only)	

Results:**AFC FREQ ERROR versus VOLTAGE**

Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
Tmin	-27	-0.0144
Tnom	-27	-0.0144
Tmax	-27	-0.0144

AFC FREQ ERROR versus TEMPERATURE

Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	25	0.0133
-20	30	0.0160
-10	33	0.0176
± 0	26	0.0138
10	-62	-0.0330
20	-27	-0.0144
30	-44	-0.0234
40	-57	-0.0303
50	-66	-0.0351

12.2.3 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2014 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE band II.

Measurement:

Measurement parameters	
Detector:	Peak / RMS
Sweep time:	2 sec.
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	100 MHz Steps
Trace mode:	Max Hold
Used equipment:	See chapter 7.1 setup A & 7.2 setup B
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1053 ISED: RSS-Gen, 6.13

Limits:

FCC	ISED
§ 24.238 (a) & (b)	RSS-133, 6.5
<p>(a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.</p> <p>(b) Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.</p>	<p>In the 1.0 MHz bands immediately outside and adjacent to the equipment's operating frequency block, the emission power per any 1% of the emission bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least 43 + 10 log(P) (watts).</p> <p>After the first 1.0 MHz, the emission power in any 1 MHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least 43 + 10 log(P) (watts). If the measurement is performed using 1% of the emission bandwidth, power integration over 1.0 MHz is required.</p>
-13 dBm	

Results Band 2:

QPSK:


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
All detected peaks are more than 10 dB below the limit.	815.9		-34.2 Peak		
			-35.7 AVG		
	5640		-17.4 Peak		
			-27.3 AVG		
	9400		-27.5 Peak		
			-44.0 AVG		
	13160		-24.2 Peak		
			-39.1 AVG		

16-QAM:


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
All detected peaks are more than 10 dB below the limit.	5640		-15.9 Peak		
			-24.0 AVG		
	All other detected peaks are more than 10 dB below the limit.				

QPSK


Plot 1: Mid channel (9 kHz - 30 MHz)



Plot 2: Mid channel (30 MHz – 1 GHz)




Plot 3: Mid channel (1 GHz – 18 GHz)




Carrier notched with 1.9 GHz rejection filter

Plot 4: Mid channel (18 GHz – 26 GHz)




16-QAM


Plot 1: Mid channel (9 kHz - 30 MHz)



Plot 2: Mid channel (30 MHz – 1 GHz)




Plot 3: Mid channel (1 GHz – 18 GHz)



Carrier notched with 1.9 GHz rejection filter

Plot 4: Mid channel (18 GHz – 26 GHz)



12.2.4 Spurious emissions conducted

Description:

The following steps outline the procedure used to measure the conducted emissions from the mobile station.

1. Determine frequency range for measurements: From § 2.1057 & RSS-Gen, 6.13.2 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency.
2. Determine mobile station transmits frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

Measurement:

Measurement parameters	
Detector:	Peak
Sweep time:	Auto
Video bandwidth:	300 kHz
Resolution bandwidth:	100 kHz
Span:	30 MHz – 19.5 GHz
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	see chapter 9
Measurement procedure	FCC: § 2.1051 ISED: RSS-Gen, 6.13

Limits:

FCC	IC
§ 24.238 (a) & (b)	RSS-133, 6.5
<p>(a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.</p> <p>(b) Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.</p>	<p>In the 1.0 MHz bands immediately outside and adjacent to the equipment's operating frequency block, the emission power per any 1% of the emission bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least 43 + 10 log(P) (watts).</p> <p>After the first 1.0 MHz, the emission power in any 1 MHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least 43 + 10 log(P) (watts). If the measurement is performed using 1% of the emission bandwidth, power integration over 1.0 MHz is required.</p>
<p>-13 dBm</p>	

Results: for 5 MHz channel bandwidth**QPSK:**


Spurious Emission Level								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	3701.4	-/-	2	3760.0	-/-	2	3818.6	-/-
3	5552.1	-/-	3	5640.0	-/-	3	5727.9	-/-
4	7402.8	-/-	4	7520.0	-/-	4	7637.2	-/-
5	9253.5	-/-	5	9400.0	-/-	5	9546.5	-/-
6	11104.2	-/-	6	11280.0	-/-	6	11455.8	-/-
7	12954.9	-/-	7	13160.0	-/-	7	13365.1	-/-
8	14805.6	-/-	8	15040.0	-/-	8	15274.4	-/-
9	16656.3	-/-	9	16920.0	-/-	9	17183.7	-/-
10	18507.0	-/-	10	18800.0	-/-	10	19093.0	-/-

16-QAM:


Spurious Emission Level								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	3701.4	-/-	2	3760.0	-/-	2	3818.6	-/-
3	5552.1	-/-	3	5640.0	-/-	3	5727.9	-/-
4	7402.8	-/-	4	7520.0	-/-	4	7637.2	-/-
5	9253.5	-/-	5	9400.0	-/-	5	9546.5	-/-
6	11104.2	-/-	6	11280.0	-/-	6	11455.8	-/-
7	12954.9	-/-	7	13160.0	-/-	7	13365.1	-/-
8	14805.6	-/-	8	15040.0	-/-	8	15274.4	-/-
9	16656.3	-/-	9	16920.0	-/-	9	17183.7	-/-
10	18507.0	-/-	10	18800.0	-/-	10	19093.0	-/-

Plots: QPSK with 5 MHz channel bandwidth


Plot 1: Lowest Channel (10 MHz – 19.5 GHz)



Plot 2: Middle Channel (10 MHz – 19.5 GHz)




Plot 3: Highest Channel (10 MHz – 19.5 GHz)




Plots: 16-QAM with 5 MHz channel bandwidth


Plot 1: Lowest Channel (10 MHz – 19.5 GHz)



Plot 2: Middle Channel (10 MHz – 19.5 GHz)



Plot 3: Highest Channel (10 MHz – 19.5 GHz)



12.2.5 Block edge compliance

Description:

The spectrum at the band edges must comply with the spurious emissions limits.

Measurement:


Measurement parameters	
Detector:	RMS
Sweep time:	180 sec.
Video bandwidth:	100 kHz
Resolution bandwidth:	20 kHz
Span:	1 MHz steps
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1051 ISED: RSS-Gen, 6.13

Limits:


FCC	ISED
§ 24.238 (a) & (b)	RSS-133, 6.5
<p>(a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.</p> <p>(b) Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.</p>	<p>In the 1.0 MHz bands immediately outside and adjacent to the equipment's operating frequency block, the emission power per any 1% of the emission bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least 43 + 10 log(P) (watts).</p> <p>After the first 1.0 MHz, the emission power in any 1 MHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least 43 + 10 log(P) (watts). If the measurement is performed using 1% of the emission bandwidth, power integration over 1.0 MHz is required.</p>
<p style="text-align: center;">-13 dBm</p> <p style="text-align: center;">Correction factor according to KDB 890810 if RBW < 1 % emission bandwidth: <input checked="" type="checkbox"/> N/A here <input type="checkbox"/> $10 \log (RBW1/RBW2) = X \text{ dB}$; whereas: $RBW1 = Y$, $RBW2 = Z$</p>	

Results: 5 MHz channel bandwidth


Plot 1: Lowest channel – QPSK




Plot 2: Highest channel – QPSK



Plot 3: Lowest channel – 16-QAM



Plot 4: Highest channel – 16-QAM



12.2.6 Occupied bandwidth

Description:

Measurement of the occupied bandwidth of the transmitted signal.

Measurement:

Similar to conducted emissions, occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the LTE band II frequency band. The table below lists the measured 99% power and -26dBc occupied bandwidths. Spectrum analyser plots are included on the following pages.

Measurement parameters	
Detector:	Peak
Sweep time:	180s
Video bandwidth:	100 kHz
Resolution bandwidth:	30 kHz
Span:	2 x nominal bandwidth
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1049 ISED: RSS-Gen, 6.7

Limits:

FCC	ISED
§ 2.1049	RSS-Gen, 6.7
Reporting only	


Results:

Occupied Bandwidth – QPSK		
Frequency (MHz)	99% OBW (kHz)	-26 dBc BW (kHz)
1850.7	1133.9	1668.9
1880.0	1124.9	1465.0
1909.3	1111.9	1413.9


Occupied Bandwidth – 16-QAM		
Frequency (MHz)	99% OBW (kHz)	-26 dBc BW (kHz)
1850.7	1132.9	1562.9
1880.0	1113.9	1428.9
1909.3	1126.9	1520.8

Plots: QPSK


Plot 1: low channel (99% - OBW)




Plot 2: low channel (-26 dBc BW)




Plot 3: mid channel (99% - OBW)




Plot 4: mid channel (-26 dBc BW)



Plot 5: high channel (99% - OBW)




Plot 6: high channel (-26 dBc BW)




Plots: 16-QAM


Plot 1: low channel (99% - OBW)




Plot 2: low channel (-26 dBc BW)




Plot 3: mid channel (99% - OBW)




Plot 4: mid channel (-26 dBc BW)



Plot 5: high channel (99% - OBW)



Plot 6: high channel (-26 dBc BW)



13 Summary of measurement results

<input checked="" type="checkbox"/>	No deviations from the technical specifications were ascertained
<input type="checkbox"/>	There were deviations from the technical specifications ascertained
<input type="checkbox"/>	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC: CFR Part 2 & Part 27 ISED: RSS-Gen, Issue 5 RSS-130, Issue 2 (LTE Bands 12, 13) RSS-139, Issue 4 (LTE Band 4)	See table!	2023-03-24	-/-

13.1 Part 27/RSS-139: LTE band 4

Test Case	temperature conditions	power source voltages	C	NC	NA	NP	Remark
RF Output Power	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Frequency Stability	Extreme	Extreme	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Spurious Emissions Radiated	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Spurious Emissions Conducted	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Block Edge Compliance	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Occupied Bandwidth	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-

Notes:

C	Compliant	NC	Not compliant	NA	Not applicable	NP	Not performed
----------	-----------	-----------	---------------	-----------	----------------	-----------	---------------

13.2 Part 27/RSS-130: LTE band 12

Test Case	temperature conditions	power source voltages	C	NC	NA	NP	Remark
RF Output Power	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Frequency Stability	Extreme	Extreme	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Spurious Emissions Radiated	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Spurious Emissions Conducted	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Block Edge Compliance	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Occupied Bandwidth	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-

Notes:

C	Compliant	NC	Not compliant	NA	Not applicable	NP	Not performed
----------	-----------	-----------	---------------	-----------	----------------	-----------	---------------

13.3 Part 27/RSS-130: LTE band 13

Test Case	temperature conditions	power source voltages	C	NC	NA	NP	Remark
RF Output Power	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Frequency Stability	Extreme	Extreme	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Spurious Emissions Radiated	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Spurious Emissions Conducted	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Block Edge Compliance	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Occupied Bandwidth	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-

Notes:

C	Compliant	NC	Not compliant	NA	Not applicable	NP	Not performed
----------	-----------	-----------	---------------	-----------	----------------	-----------	---------------

14 RF measurements

14.1 Description of test setup

For the spurious measurements we use the substitution method according TIA/EIA 603.

14.2 LTE technologies supported by EUT

Channel bandwidth

	Band 4	Band 12	Band 13	-/-
[MHz]				-/-
1.4	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
3	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
5	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
20	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	

14.3 Results LTE band 4

The EUT was set to transmit the maximum power.

14.3.1 RF output power

Description:

This paragraph contains average power, peak output power and EIRP measurements for the mobile station. In all cases, the peak output power is within the required mask (this mask is specified in the JTC standards, TIA PN3389 Vol. 1 Chap 7, and is no FCC requirement).

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

To determine the Peak-To-Average Power Ratio (PAPR) the measurement was performed with the Power Complementary Cumulative Distribution Function (CCDF).

Measurement parameters	
Detector:	Sample
AQT:	See plot
Resolution bandwidth:	1 MHz
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1046 ISED: RSS-Gen, 6.12

Limits:

FCC	ISED
§ 27.50(d)(4) & (5)	RSS-139, 5.5
(4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. (5) In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	30 dBm e.i.r.p./channel bandwidth In addition, the peak to average power ratio (PAPR) of the equipment shall not exceed 13 dB for more than 0.1% of the time, using a signal that corresponds to the highest PAPR during periods of continuous transmission.
Power: 30 dBm EIRP PAPR: 13 dB	

Results:

Output Power (conducted)						
Bandwidth (MHz)	Channel No. / Frequency (MHz)	Resource block allocation	Average Output Power (dBm) QPSK	Peak to Average Ratio (dB)	Average Output Power (dBm) 16-QAM	Peak to Average Ratio (dB)
5	19975 / 1712.5	1 RB low	21.7	4.0	22.3	4.4
		1 RB high	22.1	3.9	22.2	4.3
		100% RB	21.2	4.7	20.4	5.3
	20175 / 1732.5	1 RB low	22.0	4.3	22.2	3.9
		1 RB high	22.1	4.3	22.2	3.7
		100% RB	21.2	5.5	20.3	4.6
	20375 / 1752.5	1 RB low	22.2	3.7	22.2	4.5
		1 RB high	22.2	3.9	22.3	4.5
		100% RB	21.2	4.8	20.3	5.7

The radiated output power is measured in the mode with the highest conducted output power.

Output Power (EIRP)			
Bandwidth (MHz)	Frequency (MHz)	Average Output Power (dBm) QPSK	Average Output Power (dBm) 16-QAM
5 100% RB	1712.5	24.5	24.7
	1732.5	24.5	24.6
	1752.5	24.6	24.7

14.3.2 Frequency stability

Description:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the mobile station in a "call mode". This is accomplished with the use of a R&S CMW500 DIGITAL RADIOCOMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the mobile station to overnight soak at -30 C.
3. With the mobile station, powered with V_{nom} , connected to the CMW500 and in a simulated call on channel 1412 (centre channel), measure the carrier frequency. These measurements should be made within two minutes of powering up the mobile station, to prevent significant self warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with V_{nom} . Vary supply voltage from V_{min} to V_{max} , in 0.1 Volt steps remeasuring carrier frequency at each voltage. Pause at V_{nom} for 1.5 hours unpowered, to allow any self heating to stabilize, before continuing.
6. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

This measurement was performed with the highest channel bandwidth supported from the EUT on the middle channel

Measurement:

Measurement parameters	
Detector:	Measured with CMW500
Sweep time:	
Video bandwidth:	
Resolution bandwidth:	
Span:	
Trace-Mode:	
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1055 ISED: RSS-Gen, 6.11

Limits:

FCC	ISED
§ 27.54	RSS-139, 5.4
The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.	The frequency stability shall be sufficient to ensure that the occupied bandwidth stays within the operating frequency block when tested to the temperature and supply voltage variations specified in RSS-Gen.

Results:**FREQ ERROR versus VOLTAGE**

Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
Tmin	-31	-0.0179
Tnom	-31	-0.0179
Tmax	-31	-0.0179

FREQ ERROR versus TEMPERATURE

Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	36	0.0208
-20	24	0.0139
-10	16	0.0092
± 0	-30	-0.0173
10	-18	-0.0104
20	-31	-0.0179
30	-62	-0.0358
40	-24	-0.0139
50	-56	-0.0232

14.3.3 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2014 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1750 MHz. Measurement made up to 18 GHz. The resolution bandwidth is set as outlined in Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE band 4.

Measurement:

Measurement parameters	
Detector:	Peak / RMS
Sweep time:	2 sec.
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	100 MHz Steps
Trace mode:	Max Hold
Used equipment:	See chapter 7.2 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1053 ISED: RSS-Gen, 6.13

Limits:

FCC	ISED
§ 27.53(h)(1) & (3)	RSS-139, 5.6
<p>(1) Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.</p> <p>(3) Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.</p>	<p>Offset from the edge of the frequency block or frequency block group of 1 MHz: -13 dBm/(1% of OB*)</p> <p>Offset from the edge of the frequency block or frequency block group of > 1 MHz: -13 dBm/MHz</p>
-13 dBm	

Results Band 4:

QPSK:


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
All detected peaks are more than 10 dB below the limit.		5197.5	-19.1 Peak		
			-30.0 AVG		
		8662.5	-28.0 Peak		
			-43.6 AVG		
		12127.5	-30.5 Peak		
-47.0 AVG					
		All other detected peaks are more than 10 dB below the limit.			

16-QAM:


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
All detected peaks are more than 10 dB below the limit.		3465.0	-25.7 Peak		
			-34.7 AVG		
		5197.5	-19.6 Peak		
			-29.4 AVG		

QPSK


Plot 1: Mid channel (9 kHz - 30 MHz)



Plot 2: Mid channel (30 MHz – 1 GHz)




Plot 3: Mid channel (1 GHz – 18 GHz)




Carrier notched with 1.7 GHz rejection filter

16-QAM


Plot 1: Mid channel (9 kHz - 30 MHz)



Plot 2: Mid channel (30 MHz – 1 GHz)



Plot 3: Mid channel (1 GHz – 18 GHz)



Carrier notched with 1.7 GHz rejection filter

14.3.4 Spurious emissions conducted

Description:

The following steps outline the procedure used to measure the conducted emissions from the mobile station.

1. Determine frequency range for measurements: From § 2.1057 & RSS-Gen, 6.13.2 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency.
2. Determine mobile station transmits frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

For the measurement the lowest, middle and highest channel bandwidth was used. If spurious were found the other bandwidths were measured, too.

Measurement:

Measurement parameters	
Detector:	Peak
Sweep time:	Auto
Video bandwidth:	300 kHz
Resolution bandwidth:	100 kHz
Span:	10 MHz – 18 GHz
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1051 ISED: RSS-Gen, 6.13

Limits:

FCC	ISED
§ 27.53(h)(1) & (3)	RSS-139, 5.6
<p>(1) Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.</p> <p>(3) Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.</p>	<p>Offset from the edge of the frequency block or frequency block group of 1 MHz: -13 dBm/(1% of OB*)</p> <p>Offset from the edge of the frequency block or frequency block group of > 1 MHz: -13 dBm/MHz</p>
-13 dBm	

Results: for 5 MHz channel bandwidth

QPSK


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
3421.4	-/-	3465.0	-/-	3508.6	-/-
5132.1	-/-	5197.5	-/-	5262.9	-/-
6842.8	-/-	6930.0	-/-	7017.2	-/-
8553.5	-/-	8662.5	-/-	8771.5	-/-
10264.2	-/-	10395.0	-/-	10525.8	-/-
11974.9	-/-	12127.5	-/-	12280.1	-/-
13685.6	-/-	13860.0	-/-	14034.4	-/-
15396.3	-/-	15592.5	-/-	15788.7	-/-
17107.0	-/-	17325.0	-/-	17543.0	-/-

16-QAM


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
3421.4	-/-	3465.0	-/-	3508.6	-/-
5132.1	-/-	5197.5	-/-	5262.9	-/-
6842.8	-/-	6930.0	-/-	7017.2	-/-
8553.5	-/-	8662.5	-/-	8771.5	-/-
10264.2	-/-	10395.0	-/-	10525.8	-/-
11974.9	-/-	12127.5	-/-	12280.1	-/-
13685.6	-/-	13860.0	-/-	14034.4	-/-
15396.3	-/-	15592.5	-/-	15788.7	-/-
17107.0	-/-	17325.0	-/-	17543.0	-/-

Plots for 5 MHz channel bandwidth, QPSK


Plot 1: Lowest channel, 10 MHz to 18 GHz



Plot 2: Middle channel, 10 MHz to 18 GHz




Plot 3: Highest channel, 10 MHz to 18 GHz




Plots for 5 MHz channel bandwidth, 16-QAM


Plot 1: Lowest channel, 10 MHz to 18 GHz



Plot 2: Middle channel, 10 MHz to 18 GHz



Plot 3: Highest channel, 10 MHz to 18 GHz



14.3.5 Block edge compliance

Description:

The spectrum at the band edges must comply with the spurious emissions limits.

For the measurement the lowest, middle and highest channel bandwidth was used. If spurious were found the other bandwidths were measured, too.

Measurement:


Measurement parameters	
Detector:	RMS
Sweep time:	180s
Video bandwidth:	100 kHz
Resolution bandwidth:	20 kHz
Span:	1 MHz
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.2 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1051 ISED: RSS-Gen, 6.13

Limits:


FCC	ISED
§ 27.53(h)(1) & (3)	RSS-139, 5.6
<p>(1) Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.</p> <p>(3) Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.</p>	<p>Offset from the edge of the frequency block or frequency block group of 1 MHz: -13 dBm/(1% of OB*)</p> <p>Offset from the edge of the frequency block or frequency block group of > 1 MHz: -13 dBm/MHz</p>
<p style="text-align: center;">-13 dBm</p> <p style="text-align: center;">Correction factor according to KDB 890810 if RBW < 1 % emission bandwidth: <input checked="" type="checkbox"/> N/A here <input type="checkbox"/> $10 \log(RBW1/RBW2) = X$ dB; whereas: RBW1 = Y, RBW2 = Z</p>	

Results: 5 MHz channel bandwidth


Plot 1: Lowest channel, QPSK modulation




Plot 2: Highest channel, QPSK modulation



Plot 3: Lowest channel, 16 – QAM modulation



Plot 4: Highest channel, 16 – QAM modulation



14.3.6 Occupied bandwidth

Description:

Measurement of the occupied bandwidth of the transmitted signal.

Measurement:

Similar to conducted emissions, occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the mid frequencies of the LTE band 4 frequency band. The table below lists the measured 99% power and -26dBc occupied bandwidths. Spectrum analyzer plots are included on the following pages.

Part 27.53 requires a measurement bandwidth of at least 1% of the occupied bandwidth.

Measurement parameters	
Detector:	Peak
Sweep time:	180s
Video bandwidth:	100 kHz
Resolution bandwidth:	30 kHz
Span:	2 x nominal bandwidth
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1049 ISED: RSS-Gen, 6.7

Limits:

FCC	ISED
§ 2.1049	RSS-Gen, 6.7
Reporting only	


Results:

Occupied Bandwidth – QPSK		
Frequency (MHz)	99% OBW (kHz)	-26 dBc BW (kHz)
1710.7	1109.9	1419.8
1732.5	1112.9	1411.9
1754.3	1110.9	1414.9


Occupied Bandwidth – 16-QAM		
Frequency (MHz)	99% OBW (kHz)	-26 dBc BW (kHz)
1710.7	1117.9	1395.8
1732.5	1108.9	1387.8
1754.3	1110.9	1458.9

Plots: QPSK


Plot 1: low channel, 99% OBW




Plot 2: low channel, -26 dBc OBW




Plot 3: mid channel, 99% OBW




Plot 4: mid channel, -26 dBc OBW



Plot 5: high channel, 99% OBW




Plot 6: high channel, -26 dBc OBW




Plots: 16-QAM


Plot 1: low channel, 99% OBW




Plot 2: low channel, -26 dBc OBW




Plot 3: mid channel, 99% OBW




Plot 4: mid channel, -26 dBc OBW



Plot 5: high channel, 99% OBW



Plot 6: high channel, -26 dBc OBW



14.4 Results LTE band 12

The EUT was set to transmit the maximum power.

14.4.1 RF output power

Description:

This paragraph contains average power, peak output power and EIRP measurements for the mobile station. In all cases, the peak output power is within the required mask (this mask is specified in the JTC standards, TIA PN3389 Vol. 1 Chap 7, and is no FCC requirement).

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

To determine the Peak-To-Average Power Ratio (PAPR) the measurement was performed with the Power Complementary Cumulative Distribution Function (CCDF).

Measurement parameters	
Detector:	Sample
AQT:	See plot
Resolution bandwidth:	1 MHz
Used equipment:	See chapter 7.2 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1046 ISED: RSS-Gen, 6.12

Limits:

FCC	ISED
47 CFR 27.50(c)(9)	RSS-130, 4.6.1 & 4.6.3
<p>Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.</p>	<p>4.6.1: The transmitter output power shall be measured in terms of average power. In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time and shall use a signal corresponding to the highest PAPR during periods of continuous transmission.</p> <p>4.6.3: The e.r.p. shall not exceed 30 watts for mobile equipment and outdoor fixed subscriber equipment. The e.r.p. shall not exceed 3 watts for portable equipment and indoor fixed subscriber equipment.</p>
<p>Power: 34.77 dBm ERP PAPR: 13 dB (ISED only)</p>	

Results:

Output Power (conducted)						
Bandwidth (MHz)	Channel No. / Frequency (MHz)	Resource block allocation	Average Output Power (dBm) QPSK	Peak to Average Ratio (dB)	Average Output Power (dBm) 16-QAM	Peak to Average Ratio (dB)
5	23035 / 701.5	1 RB low	19.1	3.8	19.4	4.2
		1 RB high	19.4	3.3	19.5	4.0
		100% RB	18.5	4.6	17.8	5.1
	23095 / 707.5	1 RB low	19.5	4.0	19.6	3.7
		1 RB high	19.4	3.8	19.6	3.3
		100% RB	18.6	5.2	17.7	4.3
	23155 / 713.5	1 RB low	19.3	3.3	19.4	3.9
		1 RB high	19.2	3.3	19.4	3.8
		100% RB	18.4	4.2	17.6	5.1

The radiated output power is measured in the mode with the highest conducted output power.

Output Power (ERP)			
Bandwidth (MHz)	Frequency (MHz)	Average Output Power (dBm) QPSK	Average Output Power (dBm) 16-QAM
5 100% RB	701.5	13.2	13.3
	707.5	13.3	13.4
	713.5	13.1	13.2

14.4.2 Frequency stability

Description:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the mobile station in a "call mode". This is accomplished with the use of a R&S CMW500 DIGITAL RADIOCOMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the mobile station to overnight soak at -30 C.
3. With the mobile station, powered with V_{nom} , connected to the CMW500 and in a simulated call on channel 1412 (centre channel), measure the carrier frequency. These measurements should be made within two minutes of powering up the mobile station, to prevent significant self warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with V_{nom} . Vary supply voltage from V_{min} to V_{max} , in 0.1 Volt steps remeasuring carrier frequency at each voltage. Pause at V_{nom} for 1.5 hours unpowered, to allow any self heating to stabilize, before continuing.
6. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

This measurement was performed with the highest channel bandwidth supported from the EUT on the middle channel

Measurement:

Measurement parameters	
Detector:	Measured with CMW500
Sweep time:	
Video bandwidth:	
Resolution bandwidth:	
Span:	
Trace-Mode:	
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1055 ISED: RSS-Gen, 6.11

Limits:

FCC	ISED
§ 27.54	RSS-130, 4.5
The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.	The frequency stability shall be sufficient to ensure that the occupied bandwidth remains within each frequency block range when tested at the temperature and supply voltage variations specified in RSS-Gen.

Results:

FREQ ERROR versus VOLTAGE

Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
T _{min}	-16	-0.0226
T _{nom}	-16	-0.0226
T _{max}	-16	-0.0226

FREQ ERROR versus TEMPERATURE

Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	17	0.0240
-20	18	0.0254
-10	20	0.0283
± 0	-16	-0.0226
10	-11	-0.0155
20	-16	-0.0226
30	-15	-0.0212
40	-37	-0.0523
50	-24	-0.0339

Additional measurements for RSS-130 (4.3 b)

$f_L = 699.047104 \text{ MHz}$	$f_H = 715.943104 \text{ MHz}$
$f_L - (\text{max freq. error}) = 699.047067 \text{ MHz}$	$f_H + (\text{max freq. error}) = 715.943141 \text{ MHz}$

14.4.3 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2014 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 711 MHz. Measured up to 8 GHz. The resolution bandwidth is set as outlined in Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE band 12.

Measurement:

Measurement parameters	
Detector:	Peak / RMS
Sweep time:	2 sec.
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	100 MHz Steps
Trace mode:	Max Hold
Used equipment:	See chapter 7.2 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1053 ISED: RSS-Gen, 6.13

Limits:

FCC	ISED
§ 27.53(g)	RSS-130, 4.7.1
For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.	The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log(10^{-10} \text{ (watts)})$ dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.
-13 dBm	

Results Band 12:

QPSK:


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
All detected peaks are more than 10 dB below the limit.	1415.0	-41.3 Peak -43.1 AVG	All other detected peaks are more than 10 dB below the limit.	All detected peaks are more than 10 dB below the limit.	
	2830.0	-31.5 Peak -39.4 AVG			

16-QAM:


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
All detected peaks are more than 10 dB below the limit.	1415.0	-42.3 Peak -44.4 AVG	All other detected peaks are more than 10 dB below the limit.	All detected peaks are more than 10 dB below the limit.	
	2830.0	-33.2 Peak -39.5 AVG			

QPSK


Plot 1: Mid channel (9 kHz - 30 MHz)



Plot 2: Mid channel (30 MHz – 1 GHz)




Plot 3: Mid channel (1 GHz – 12.75 GHz)




16-QAM


Plot 1: Mid channel (9 kHz - 30 MHz)



Plot 2: Mid channel (30 MHz – 1 GHz)



Plot 3: Mid channel (1 GHz – 12.75 GHz)



14.4.4 Spurious emissions conducted

Description:

The following steps outline the procedure used to measure the conducted emissions from the mobile station.

1. Determine frequency range for measurements: From § 2.1057 & RSS-Gen, 6.13.2 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency.
2. Determine mobile station transmits frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

Measurement:

Measurement parameters	
Detector:	Peak
Sweep time:	Auto
Video bandwidth:	300 kHz
Resolution bandwidth:	100 kHz
Span:	10 MHz – 7.5 GHz
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1051 ISED: RSS-Gen, 6.13

Limits:

FCC	ISED
§ 27.53(g)	RSS-130, 4.7.1
For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.	The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10}(P)$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.
-13 dBm	

Results: for 5 MHz channel bandwidth

QPSK


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
1399.4	-/-	1415.0	-/-	1430.6	-/-
2099.1	-/-	2122.5	-/-	2145.9	-/-
2798.8	-/-	2830.0	-/-	2861.2	-/-
3498.5	-/-	3537.5	-/-	3576.5	-/-
4198.2	-/-	4245.0	-/-	4291.8	-/-
4897.9	-/-	4952.5	-/-	5007.1	-/-
5597.6	-/-	5660.0	-/-	5722.4	-/-
6297.3	-/-	6367.5	-/-	6437.7	-/-
6997.0	-/-	7075.0	-/-	7153.0	-/-

16-QAM


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
1399.4	-/-	1415.0	-/-	1430.6	-/-
2099.1	-/-	2122.5	-/-	2145.9	-/-
2798.8	-/-	2830.0	-/-	2861.2	-/-
3498.5	-/-	3537.5	-/-	3576.5	-/-
4198.2	-/-	4245.0	-/-	4291.8	-/-
4897.9	-/-	4952.5	-/-	5007.1	-/-
5597.6	-/-	5660.0	-/-	5722.4	-/-
6297.3	-/-	6367.5	-/-	6437.7	-/-
6997.0	-/-	7075.0	-/-	7153.0	-/-

Plots for 5 MHz channel bandwidth, QPSK


Plot 1: Lowest channel, 10 MHz to 7.5 GHz



Plot 2: Middle channel, 10 MHz to 7.5 GHz




Plot 3: Highest channel, 10 MHz to 7.5 GHz




Plots for 5 MHz channel bandwidth, 16-QAM


Plot 1: Lowest channel, 10 MHz to 7.5 GHz



Plot 2: Middle channel, 10 MHz to 7.5 GHz



Plot 3: Highest channel, 10 MHz to 7.5 GHz



14.4.5 Block edge compliance

Description:

The spectrum at the band edges must comply with the spurious emissions limits.

Measurement:


Measurement parameters	
Detector:	RMS
Sweep time:	180s
Video bandwidth:	300 kHz
Resolution bandwidth:	100 kHz
Span:	1 MHz
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1051 ISED: RSS-Gen, 6.13

Limits:


FCC	ISED
§ 27.53(g)	RSS-130, 4.7.1
For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.	The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10}(P)$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.
-13 dBm	
Correction factor according to KDB 890810 if $RBW < 1\%$ emission bandwidth: <input checked="" type="checkbox"/> N/A here <input type="checkbox"/> $10 \log(RBW1/RBW2) = X$ dB; whereas: $RBW1 = Y, RBW2 = Z$	

Results: 5 MHz channel bandwidth


Plot 1: Lowest channel, QPSK modulation




Plot 2: Highest channel, QPSK modulation



Plot 3: Lowest channel, 16 – QAM modulation



Plot 4: Highest channel, 16 – QAM modulation



14.4.6 Occupied bandwidth

Description:

Measurement of the occupied bandwidth of the transmitted signal.

Measurement:

Similar to conducted emissions, occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the mid frequencies of the LTE band 12 frequency band. The table below lists the measured 99% power and -26dBc occupied bandwidths. Spectrum analyser plots are included on the following pages.

Part 27.53 requires a measurement bandwidth of at least 1% of the occupied bandwidth.

Measurement parameters	
Detector:	Peak
Sweep time:	180s
Video bandwidth:	100 kHz
Resolution bandwidth:	30 kHz
Span:	2 x nominal bandwidth
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1049 ISED: RSS-Gen, 6.7

Limits:

FCC	ISED
§ 2.1049	RSS-Gen, 6.7
Reporting only	


Results:

Occupied Bandwidth – QPSK		
Frequency (MHz)	99% OBW (kHz)	-26 dBc BW (kHz)
699.7	1127.9	1574.8
707.5	1155.9	2041.8
715.3	1261.9	2159.8


Occupied Bandwidth – 16-QAM		
Frequency (MHz)	99% OBW (kHz)	-26 dBc BW (kHz)
699.7	1136.9	1581.8
707.5	1145.9	2055.8
715.3	1244.9	2426.8

Plots: QPSK


Plot 1: low channel, 99% OBW




Plot 2: low channel, -26 dBc OBW




Plot 3: mid channel, 99% OBW




Plot 4: mid channel, -26 dBc OBW



Plot 5: high channel, 99% OBW




Plot 6: high channel, -26 dBc OBW




Plots: 16-QAM


Plot 1: low channel, 99% OBW




Plot 2: low channel, -26 dBc OBW




Plot 3: mid channel, 99% OBW




Plot 4: mid channel, -26 dBc OBW



Plot 5: high channel, 99% OBW



Plot 6: high channel, -26 dBc OBW



14.5 Results LTE band 13

The EUT was set to transmit the maximum power.

14.5.1 RF output power

Description:

This paragraph contains average power, peak output power and EIRP measurements for the mobile station. In all cases, the peak output power is within the required mask (this mask is specified in the JTC standards, TIA PN3389 Vol. 1 Chap 7, and is no FCC requirement).

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

To determine the Peak-To-Average Power Ratio (PAPR) the measurement was performed with the Power Complementary Cumulative Distribution Function (CCDF).

Measurement parameters	
Detector:	Sample
AQT:	See plot
Resolution bandwidth:	1 MHz
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1046 ISED: RSS-Gen, 6.12

Limits:

FCC	ISED
§ 27.50(b)(10)	RSS-130, 4.6.1 & 4.6.3
Portable stations (hand-held devices) transmitting in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.	4.6.1: The transmitter output power shall be measured in terms of average power. In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time and shall use a signal corresponding to the highest PAPR during periods of continuous transmission. 4.6.3: The e.r.p. shall not exceed 30 watts for mobile equipment and outdoor fixed subscriber equipment. The e.r.p. shall not exceed 3 watts for portable equipment and indoor fixed subscriber equipment.
Power: 34.77 dBm ERP PAPR: 13 dB (ISED only)	

Results:

Output Power (conducted)						
Bandwidth (MHz)	Channel No. / Frequency (MHz)	Resource block allocation	Average Output Power (dBm) QPSK	Peak to Average Ratio (dB)	Average Output Power (dBm) 16-QAM	Peak to Average Ratio (dB)
5	23205 / 779.5	1 RB low	19.8	3.6	20.0	4.1
		1 RB high	20.3	3.3	20.3	3.9
		100% RB	19.2	4.3	18.4	5.0
	23230 / 782	1 RB low	20.1	4.0	20.2	3.6
		1 RB high	20.3	3.8	20.4	3.4
		100% RB	19.4	5.3	18.4	4.3
	23255 / 784.5	1 RB low	20.3	3.3	20.4	3.9
		1 RB high	20.5	3.3	20.5	3.8
		100% RB	19.5	4.1	18.6	5.1

The radiated output power is measured in the mode with the highest conducted output power.

Output Power (ERP)			
Bandwidth (MHz)	Frequency (MHz)	Average Output Power (dBm) QPSK	Average Output Power (dBm) 16-QAM
5	779.5	15.3	15.3
	782.0	15.3	15.4
	784.5	15.5	15.5

14.5.2 Frequency stability

Description:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the mobile station in a "call mode". This is accomplished with the use of a R&S CMW500 DIGITAL RADIOCOMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the mobile station to overnight soak at -30 C.
3. With the mobile station, powered with V_{nom} , connected to the CMW500 and in a simulated call on channel 1412 (centre channel), measure the carrier frequency. These measurements should be made within two minutes of powering up the mobile station, to prevent significant self warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with V_{nom} . Vary supply voltage from V_{min} to V_{max} , in 0.1 Volt steps remeasuring carrier frequency at each voltage. Pause at V_{nom} for 1.5 hours unpowered, to allow any self heating to stabilize, before continuing.
6. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

This measurement was performed with the highest channel bandwidth supported from the EUT on the middle channel

Measurement:

Measurement parameters	
Detector:	Measured with CMW500
Sweep time:	
Video bandwidth:	
Resolution bandwidth:	
Span:	
Trace-Mode:	
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1055 ISED: RSS-Gen, 6.11

Limits:

FCC	ISED
§ 27.54	RSS-130, 4.5
The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.	The frequency stability shall be sufficient to ensure that the occupied bandwidth remains within each frequency block range when tested at the temperature and supply voltage variations specified in RSS-Gen.

Results:**FREQ ERROR versus VOLTAGE**

Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
T _{min}	-60	-0.0767
T _{nom}	-60	-0.0767
T _{max}	-60	-0.0767

FREQ ERROR versus TEMPERATURE

Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-30	32	0.0409
-20	31	0.0396
-10	27	0.0345
± 0	16	0.0205
10	19	0.0243
20	-60	-0.0767
30	-39	-0.0499
40	-30	-0.0384
50	-37	-0.0473

Additional measurements for RSS-130 (4.3 b)

$f_L = 777.065216$ MHz	$f_H = 783.636096$ MHz
$f_L - (\text{max freq. error}) = 777.065156$ MHz	$f_H + (\text{max freq. error}) = 783.636156$ MHz

14.5.3 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2014 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 782 MHz. Measured up to 8 GHz. The resolution bandwidth is set as outlined in Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE band 13.

Measurement:

Measurement parameters	
Detector:	Peak / RMS
Sweep time:	2 sec.
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	100 MHz Steps
Trace mode:	Max Hold
Used equipment:	See chapter 7.2 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1053 ISED: RSS-Gen, 6.13

Limits:

FCC	ISED
§ 27.53(c)	RSS-130, 4.7.1
(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following: (c)(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.	The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10}(P)$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.
-13 dBm	

Results Band 13:

QPSK:


Spurious Emission Level						
Lowest channel		Middle channel		Highest channel		
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	
2338.5	8.8 Peak	1564	-29.4 Peak	1569	-31.2 Peak	
	-17.6 AVG		-42.5 AVG		-44.5 AVG	
All other detected peaks are more than 10 dB below the limit.		2346	9.4 Peak	2353.5	8.4 Peak	
			-16.8 AVG		-18.0 AVG	
		3910	-13.2 Peak	All other detected peaks are more than 10 dB below the limit.		
			-40.4 AVG			
		4692	-31.4 Peak			
			-37.4 AVG			
		6256	-24.4 Peak			
			-32.8 AVG			

16-QAM:


Spurious Emission Level						
Lowest channel		Middle channel		Highest channel		
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	
2338.5	8.4 Peak	1564	-29.6 Peak	1569	-31.1 Peak	
	-18.2 AVG		-42.9 AVG		-45.5 AVG	
All other detected peaks are more than 10 dB below the limit.		2346	9.0 Peak	2353.5	8.0 Peak	
			-17.6 AVG		-18.6 AVG	
		3910	-14.2 Peak	All other detected peaks are more than 10 dB below the limit.		
			-43.4 AVG			
		4692	-32.0 Peak			
			-37.8 AVG			
		6256	-25.9 Peak			
			-33.1 AVG			

QPSK


Plot 1: Mid channel (9 kHz - 30 MHz)



Plot 2: Mid channel (30 MHz – 1 GHz)




Plot 3: Mid channel (1 GHz – 12.75 GHz)




16-QAM


Plot 1: Mid channel (9 kHz - 30 MHz)



Plot 2: Mid channel (30 MHz – 1 GHz)



Plot 3: Mid channel (1 GHz – 12.75 GHz)



14.5.4 Spurious emissions conducted

Description:

The following steps outline the procedure used to measure the conducted emissions from the mobile station.

1. Determine frequency range for measurements: From § 2.1057 & RSS-Gen, 6.13.2 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested data taken from 10 MHz to 8 GHz.
2. Determine mobile station transmits frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

Measurement:

Measurement parameters	
Detector:	Peak
Sweep time:	Auto
Video bandwidth:	300 kHz
Resolution bandwidth:	100 kHz
Span:	10 MHz – 8 GHz
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1051 ISED: RSS-Gen, 6.13

Limits:

FCC	ISED
§ 27.53(c)	RSS-130, 4.7.1
(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee’s frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following: (c)(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB.	The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10} p$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment’s frequency block range, a resolution bandwidth of 30 kHz may be employed.
-13 dBm	

Results: for 5 MHz channel bandwidth

QPSK


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
1559.0	-/-	1564.0	-/-	1569.0	-/-
2338.5	-/-	2346.0	-/-	2353.5	-/-
3118.0	-/-	3128.0	-/-	3138.0	-/-
3897.5	-/-	3910.0	-/-	3922.5	-/-
4677.0	-/-	4692.0	-/-	4707.0	-/-
5456.5	-/-	5474.0	-/-	5491.5	-/-
6236.0	-/-	6256.0	-/-	6276.0	-/-
7015.5	-/-	7038.0	-/-	7060.5	-/-
7795.0	-/-	7820.0	-/-	7845.0	-/-

16-QAM


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
1559.0	-/-	1564.0	-/-	1569.0	-/-
2338.5	-/-	2346.0	-/-	2353.5	-/-
3118.0	-/-	3128.0	-/-	3138.0	-/-
3897.5	-/-	3910.0	-/-	3922.5	-/-
4677.0	-/-	4692.0	-/-	4707.0	-/-
5456.5	-/-	5474.0	-/-	5491.5	-/-
6236.0	-/-	6256.0	-/-	6276.0	-/-
7015.5	-/-	7038.0	-/-	7060.5	-/-
7795.0	-/-	7820.0	-/-	7845.0	-/-

Plots for 5 MHz channel bandwidth, QPSK


Plot 1: Lowest channel, 10 MHz to 8 GHz



Plot 2: Middle channel, 10 MHz to 8 GHz




Plot 3: Highest channel, 10 MHz to 8 GHz




Plots for 5 MHz channel bandwidth, 16-QAM


Plot 1: Lowest channel, 10 MHz to 8 GHz



Plot 2: Middle channel, 10 MHz to 8 GHz



Plot 3: Highest channel, 10 MHz to 8 GHz



14.5.5 Block edge compliance

Description:

The spectrum at the band edges must comply with the spurious emissions limits.

Measurement:


Measurement parameters	
Detector:	RMS
Sweep time:	180s
Video bandwidth:	300 kHz
Resolution bandwidth:	100 kHz
Span:	1 MHz
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.2 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1051 ISED: RSS-Gen, 6.13

Limits:


FCC	ISED
<p style="text-align: center;">§ 27.53(c)</p>	<p style="text-align: center;">RSS-130, 4.7.1</p>
<p>(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:</p> <p>(c)(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.</p> <p>On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;</p>	<p>The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10}(P)$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.</p> <p>a. the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:</p> <ul style="list-style-type: none"> i. $76 + 10 \log_{10}(P)$ (watts), dB, for base and fixed equipment and ii. $65 + 10 \log_{10}(P)$ (watts), dB, for mobile and portable equipment
<p>-13 dBm</p> <p>Correction factor according to KDB 890810 if RBW < 1 % emission bandwidth: <input checked="" type="checkbox"/> N/A here <input type="checkbox"/> $10 \log(RBW1/RBW2) = X$ dB; whereas: RBW1 = Y, RBW2 = Z</p>	

Results: 5 MHz channel bandwidth


Plot 1: Lowest channel, QPSK modulation




Plot 2: Highest channel, QPSK modulation



Plot 3: Lowest channel, 16 – QAM modulation



Plot 4: Highest channel, 16 – QAM modulation



14.5.6 Occupied bandwidth

Description:

Measurement of the occupied bandwidth of the transmitted signal.

Measurement:

Similar to conducted emissions, occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the mid frequencies of the LTE band 13 frequency band. The table below lists the measured 99% power and -26dBc occupied bandwidths. Spectrum analyser plots are included on the following pages.

Part 27.53 requires a measurement bandwidth of at least 1% of the occupied bandwidth.

Measurement parameters	
Detector:	Peak
Sweep time:	180s
Video bandwidth:	100 kHz
Resolution bandwidth:	300 kHz
Span:	2 x nominal bandwidth
Trace-Mode:	Max Hold
Used equipment:	See chapter 7.4 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1049 ISED: RSS-Gen, 6.7

Limits:

FCC	ISED
§ 2.1049	RSS-Gen, 6.7
Reporting only	


Results:

Occupied Bandwidth - QPSK		
Frequency (MHz)	99% OBW (kHz)	-26 dBc BW (kHz)
779.5	1186.9	2220.7
782.0	1200.9	2064.8
784.5	1167.9	2185.8


Occupied Bandwidth – 16-QAM		
Frequency (MHz)	99% OBW (kHz)	-26 dBc BW (kHz)
779.5	1179.9	2532.7
782.0	1188.9	2123.8
784.5	1162.9	1968.8

Plots: QPSK


Plot 1: low channel, 99% OBW




Plot 2: low channel, -26 dBc OBW




Plot 3: mid channel, 99% OBW




Plot 4: mid channel, -26 dBc OBW



Plot 5: high channel, 99% OBW




Plot 6: high channel, -26 dBc OBW




Plots: 16-QAM


Plot 1: low channel, 99% OBW




Plot 2: low channel, -26 dBc OBW




Plot 3: mid channel, 99% OBW




Plot 4: mid channel, -26 dBc OBW



Plot 5: high channel, 99% OBW



Plot 6: high channel, -26 dBc OBW



15 Observations

No observations except those reported with the single test cases have been made.

16 Glossary

EUT	Equipment under test
DUT	Device under test
UUT	Unit under test
GUE	GNSS User Equipment
ETSI	European Telecommunications Standards Institute
EN	European Standard
FCC	Federal Communications Commission
FCC ID	Company Identifier at FCC
IC	Industry Canada
PMN	Product marketing name
HMN	Host marketing name
HVIN	Hardware version identification number
FVIN	Firmware version identification number
EMC	Electromagnetic Compatibility
HW	Hardware
SW	Software
Inv. No.	Inventory number
S/N or SN	Serial number
C	Compliant
NC	Not compliant
NA	Not applicable
NP	Not performed
PP	Positive peak
QP	Quasi peak
AVG	Average
OC	Operating channel
OCW	Operating channel bandwidth
OBW	Occupied bandwidth
OOB	Out of band
DFS	Dynamic frequency selection
CAC	Channel availability check
OP	Occupancy period
NOP	Non occupancy period
DC	Duty cycle
PER	Packet error rate
CW	Clean wave
MC	Modulated carrier
WLAN	Wireless local area network
RLAN	Radio local area network
DSSS	Dynamic sequence spread spectrum
OFDM	Orthogonal frequency division multiplexing
FHSS	Frequency hopping spread spectrum
GNSS	Global Navigation Satellite System
C/N₀	Carrier to noise-density ratio, expressed in dB-Hz

17 Document history

Version	Applied changes	Date of release
-/-	Initial release	2023-03-24

18 Accreditation Certificate – D-PL-12076-01-04

first page	last page
 <p>DAkKS Deutsche Akkreditierungsstelle</p> <p>Deutsche Akkreditierungsstelle GmbH</p> <p>Entrusted according to Section 8 subsection 1 AkkStelleG in connection with Section 1 subsection 1 AkkStelleGBV Signatory to the Multilateral Agreements of EA, ILAC and IAF for Mutual Recognition</p> <p>Accreditation </p> <p>The Deutsche Akkreditierungsstelle GmbH attests that the testing laboratory CTC advanced GmbH Untertürkheimer Straße 6-10, 66117 Saarbrücken is competent under the terms of DIN EN ISO/IEC 17025:2018 to carry out tests in the following fields: Telecommunication (TC) and Electromagnetic Compatibility (EMC) for Canadian Standards</p> <p>The accreditation certificate shall only apply in connection with the notice of accreditation of 09.06.2020 with the accreditation number D-PL-12076-01. It comprises the cover sheet, the reverse side of the cover sheet and the following annex with a total of 07 pages.</p> <p>Registration number of the certificate: D-PL-12076-01-04</p> <p>Frankfurt am Main, 09.06.2020</p> <p>by order:  Frank Egner Head of Division</p> <p><small>The certificate together with its annex reflects the status at the time of the date of issue. The current status of the scope of accreditation can be found in the database of accredited bodies of Deutsche Akkreditierungsstelle GmbH. https://www.dakks.de/en/content/accredited-bodies-dakks See also annex.</small></p>	 <p>Deutsche Akkreditierungsstelle GmbH</p> <p>Office Berlin Spittelmarkt 10 10117 Berlin</p> <p>Office Frankfurt am Main Europa-Allee 52 60527 Frankfurt am Main</p> <p>Office Braunschweig Bundesallee 100 38116 Braunschweig</p> <p>The publication of extracts of the accreditation certificate is subject to the prior written approval by Deutsche Akkreditierungsstelle GmbH (DAKKS). Exempted is the unchanged form of separate disseminations of the cover sheet by the conformity assessment body mentioned overleaf.</p> <p>No impression shall be made that the accreditation also extends to fields beyond the scope of accreditation attested by DAKKS.</p> <p>The accreditation was granted pursuant to the Act on the Accreditation Body (AkkStelleG) of 31 July 2009 (Federal Law Gazette I p. 2625) and the Regulation (EC) No 765/2008 of the European Parliament and of the Council of 9 July 2008 setting out the requirements for accreditation and market surveillance relating to the marketing of products (Official Journal of the European Union L 218 of 9 July 2008, p. 30). DAKKS is a signatory to the Multilateral Agreements for Mutual Recognition of the European co-operation for Accreditation (EA), International Accreditation Forum (IAF) and International Laboratory Accreditation Cooperation (ILAC). The signatories to these agreements recognise each other's accreditations.</p> <p>The up-to-date state of membership can be retrieved from the following websites: EA: www.european-accreditation.org ILAC: www.ilac.org IAF: www.iaf.nu</p>

Note: The current certificate annex is published on the websites (link see below).

<https://www.dakks.de/files/data/as/pdf/D-PL-12076-01-04e.pdf>

or

https://ctcadvanced.com/app/uploads/2020/06/D-PL-12076-01-04_Canada_TCEMC.pdf

19 Accreditation Certificate – D-PL-12076-01-05

first page	last page			
 <p>Deutsche Akkreditierungsstelle GmbH</p> <p>Entrusted according to Section 8 subsection 1 AkkStelleG in connection with Section 1 subsection 1 AkkStelleGBV Signatory to the Multilateral Agreements of EA, ILAC and IAF for Mutual Recognition</p> <p>Accreditation </p> <p>The Deutsche Akkreditierungsstelle GmbH attests that the testing laboratory</p> <p>CTC advanced GmbH Untertürkheimer Straße 6-10, 66117 Saarbrücken</p> <p>is competent under the terms of DIN EN ISO/IEC 17025:2018 to carry out tests in the following fields:</p> <p>Telecommunication (FCC Requirements)</p> <p>The accreditation certificate shall only apply in connection with the notice of accreditation of 09.06.2020 with the accreditation number D-PL-12076-01. It comprises the cover sheet, the reverse side of the cover sheet and the following annex with a total of 05 pages.</p> <p>Registration number of the certificate: D-PL-12076-01-05</p> <p>Frankfurt am Main, 09.06.2020  by Dr.-Ing. (FH) Michael Egner Head of Division</p> <p><small>The certificate together with its annex reflects the status at the time of the date of issue. The current status of the scope of accreditation can be found in the database of accredited bodies of Deutsche Akkreditierungsstelle GmbH. https://www.dakks.de/en/content/accredited-bodies-dakks See notes involved.</small></p>	<p>Deutsche Akkreditierungsstelle GmbH</p> <table border="0"> <tr> <td>Office Berlin Spittelmarkt 10 10117 Berlin</td> <td>Office Frankfurt am Main Europa-Allee 52 60327 Frankfurt am Main</td> <td>Office Braunschweig Bundesallee 100 38116 Braunschweig</td> </tr> </table> <p>The publication of extracts of the accreditation certificate is subject to the prior written approval by Deutsche Akkreditierungsstelle GmbH (DAkKS). Exempted is the unchanged form of separate disseminations of the cover sheet by the conformity assessment body mentioned overleaf.</p> <p>No impression shall be made that the accreditation also extends to fields beyond the scope of accreditation attested by DAkKS.</p> <p><small>The accreditation was granted pursuant to the Act on the Accreditation Body (AkkStelleG) of 31 July 2009 (Federal Law Gazette I p. 2625) and the Regulation (EC) No 765/2008 of the European Parliament and of the Council of 9 July 2008 setting out the requirements for accreditation and market surveillance relating to the marketing of products (Official Journal of the European Union L 218 of 9 July 2008, p. 30). DAkKS is a signatory to the Multilateral Agreements for Mutual Recognition of the European co-operation for Accreditation (EA), International Accreditation Forum (IAF) and International Laboratory Accreditation Cooperation (ILAC). The signatories to these agreements recognise each other's accreditations.</small></p> <p><small>The up-to-date state of membership can be retrieved from the following websites: EA: www.european-accreditation.org ILAC: www.ilac.org IAF: www.iaf.nu</small></p>	Office Berlin Spittelmarkt 10 10117 Berlin	Office Frankfurt am Main Europa-Allee 52 60327 Frankfurt am Main	Office Braunschweig Bundesallee 100 38116 Braunschweig
Office Berlin Spittelmarkt 10 10117 Berlin	Office Frankfurt am Main Europa-Allee 52 60327 Frankfurt am Main	Office Braunschweig Bundesallee 100 38116 Braunschweig		

Note: The current certificate annex is published on the websites (link see below).

<https://www.dakks.de/files/data/as/pdf/D-PL-12076-01-05e.pdf>

or

https://ctcadvanced.com/app/uploads/2020/06/D-PL-12076-01-05_TCB_USA.pdf

END OF TEST REPORT