

RF Exposure Evaluation

FCC ID: 2AC5EIW-6215BT

1. Client Information

Applicant : HIGH HIT ENTERPRISE CO.,LTD.
Address : 6F-3, NO.29-1, LANE 169, KANG-NING ST., SHI-CHIH CITY, TAIPEI
HSIEN, TAIWAN
Manufacturer : HIGH HIT ELECTRONICS(SHENZHEN)CO.,LTD
Address : BUILDING 25, AREA C, BUYONG INDUSTRIAL RD., SHAJING TOWN,
BAOAN ZONE, SHENZHEN, CHINA

2. General Description of EUT

EUT Name	:	WALL BLUETOOTH SPEAKER	
Models No.	:	IW-6215BT, IW-8215BT, IC-6215BT, IC8215BT, RBT-402, RBT-802, ROCK-RS4-BTL, ROCK-541-BTL, ROCK-621-BTL, ROCK-821-BTL, HP-5240AUBTO, HP-6250AUBTO, HP-4230AUbt	
Model Difference	:	All models are identical in the same PCB layout interior structure and electrical circuits, The only difference is model name for commercial purpose and output power.	
Product Description	:	Operation Frequency:	Bluetooth: 2402~2480 MHz
		RF Output Power:	Bluetooth: 3.358dBm(GFSK)
		Antenna Gain:	0dBi PCB Antenna
Power Supply	:	DC Voltage supplied by AC/DC Adapter	
Power Rating	:	AC/DC Adapter Model(ZF120-1502400) Input: AC 100V-24V 50Hz/60Hz 1.5A Output: DC 15V/2.4A	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)] * $\sqrt{f_{\text{GHz}}}$] ≤ 3.0 for 1-g SAR

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)] * $\sqrt{f_{\text{GHz}}}$] $\leq 7.5.0$ for 10-g SAR

2. Calculation:

Test separation: 5mm						
Bluetooth Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	2.546	3 ± 1	4	2.512	0.779	3.0
2.441	3.158	3 ± 1	4	2.512	0.785	3.0
2.480	3.358	3 ± 1	4	2.512	0.791	3.0
Bluetooth Mode ($\pi/4$ -DQPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	2.138	2 ± 1	3	1.995	0.618	3.0
2.441	2.812	2 ± 1	3	1.995	0.623	3.0
2.480	2.970	2 ± 1	3	1.995	0.628	3.0
Bluetooth Mode (8-DPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	2.500	3 ± 1	4	2.512	0.779	3.0
2.441	3.123	3 ± 1	4	2.512	0.785	3.0
2.480	3.305	3 ± 1	4	2.512	0.791	3.0

So standalone SAR measurements are not required.

-----END OF REPORT-----