



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.247

Report Reference No......: **GTS20210613011-1-1**

FCC ID.....: **2AC5R-SC-2322BT**

Compiled by
(position+printed name+signature)..: File administrators Jimmy Wang

Supervised by
(position+printed name+signature)..: Test Engineer Aaron Tan



Approved by
(position+printed name+signature)..: Manager Jason Hu

Date of issue.....: June 21, 2021

Representative Laboratory Name .: **Shenzhen Global Test Service Co., Ltd.**

Address.....: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name.....: **SUPERSONIC INC**

Address: 6555 BANDINI BOULEVARD COMMERCE CA 90040-3119 USA
Los Angeles California United States

Test specification

Standard: **FCC Part 15.247**

TRF Originator: Shenzhen Global Test Service Co.,Ltd.

Master TRF: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: **BLUETOOTH SPEAKER**

Trade Mark: N/A

Manufacturer.....: **SUPERSONIC INC**

Model/Type reference.....: SC-2322BT

Listed Models: N/A

Ratings: 5V==1A

Modulation: GFSK, $\pi/4$ DQPSK,

Hardware version: TG-189-AC6825F-HT8699R-V2.0

Software version: V1.0

Frequency.....: From 2402MHz to 2480MHz

Result.....: **PASS**

TEST REPORT

| | | |
|--------------------------|---------------------------|---------------|
| Test Report No. : | GTS20210613011-1-1 | June 21, 2021 |
| | | Date of issue |

Equipment under Test : BLUETOOTH SPEAKER

Model /Type : SC-2322BT

Listed Models : N/A

Applicant : **SUPERSONIC INC**

Address : 6555 BANDINI BOULEVARD COMMERCE CA 90040-3119
USA Los Angeles California United States

Manufacturer : **SUPERSONIC INC**

Address : 6555 BANDINI BOULEVARD COMMERCE CA 90040-3119
USA Los Angeles California United States

| | |
|---------------------|-------------|
| Test Result: | PASS |
|---------------------|-------------|

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

| | | |
|-----------------|---|------------------|
| <u>1</u> | <u>TEST STANDARDS</u> | <u>4</u> |
| <u>2</u> | <u>SUMMARY</u> | <u>5</u> |
| 2.1 | General Remarks | 5 |
| 2.2 | Product Description | 5 |
| 2.3 | Test Sample | 5 |
| 2.4 | Equipment Under Test | 5 |
| 2.5 | Short description of the Equipment under Test (EUT) | 5 |
| 2.6 | EUT operation mode | 6 |
| 2.7 | Block Diagram of Test Setup | 6 |
| 2.8 | Special Accessories | 6 |
| 2.9 | Related Submittal(s) / Grant (s) | 6 |
| 2.10 | Modifications | 6 |
| <u>3</u> | <u>TEST ENVIRONMENT</u> | <u>7</u> |
| 3.1 | Address of the test laboratory | 7 |
| 3.2 | Test Facility | 7 |
| 3.3 | Environmental conditions | 7 |
| 3.4 | Summary of measurement results | 8 |
| 3.5 | Statement of the measurement uncertainty | 8 |
| 3.6 | Equipments Used during the Test | 9 |
| <u>4</u> | <u>TEST CONDITIONS AND RESULTS</u> | <u>10</u> |
| 4.1 | AC Power Conducted Emission | 10 |
| 4.2 | Radiated Emission | 13 |
| 4.3 | Maximum Peak Output Power | 19 |
| 4.4 | 20dB Bandwidth | 20 |
| 4.5 | Frequency Separation | 23 |
| 4.6 | Number of hopping frequency | 25 |
| 4.7 | Time of Occupancy (Dwell Time) | 27 |
| 4.8 | Out-of-band Emissions | 30 |
| 4.9 | Pseudorandom Frequency Hopping Sequence | 36 |
| 4.10 | Antenna Requirement | 37 |
| <u>5</u> | <u>TEST SETUP PHOTOS OF THE EUT</u> | <u>38</u> |
| <u>6</u> | <u>PHOTOS OF THE EUT</u> | <u>39</u> |

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

2 SUMMARY

2.1 General Remarks

| | | |
|--------------------------------|---|---------------|
| Date of receipt of test sample | : | June 07, 2021 |
| | | |
| Testing commenced on | : | June 08, 2021 |
| | | |
| Testing concluded on | : | June 21, 2021 |

2.2 Product Description

| | |
|-----------------------|--|
| Product Description: | BLUETOOTH SPEAKER |
| Model/Type reference: | SC-2322BT |
| Power supply: | DC 3.7V from battery |
| Sample ID: | GTS20210613011-1-1#/ GTS20210613011-1-2# |
| Bluetooth : | |
| Supported Type: | Bluetooth BR/EDR |
| Modulation: | GFSK, $\pi/4$ DQPSK |
| Operation frequency: | 2402MHz~2480MHz |
| Channel number: | 79 |
| Channel separation: | 1MHz |
| Antenna type: | PCB antenna |
| Antenna gain: | 0 dBi |

2.3 Test Sample

The application provides 2 samples to meet requirement.

| Sample Number | Description |
|---------------------|---------------------------------------|
| GTS20210613011-1-1# | Engineer sample – continuous transmit |
| GTS20210613011-1-2# | Normal sample – Intermittent transmit |

2.4 Equipment Under Test

Power supply system utilised

| | | | |
|----------------------|---|---|-----------------------------------|
| Power supply voltage | : | <input type="radio"/> 230V / 50 Hz | <input type="radio"/> 120V / 60Hz |
| | | <input type="radio"/> 12 V DC | <input type="radio"/> 24 V DC |
| | | <input checked="" type="radio"/> Other (specified in blank below) | |

DC 3.7V from battery

2.5 Short description of the Equipment under Test (EUT)

This is a BLUETOOTH SPEAKER.

For more details, refer to the user's manual of the EUT.


2.6 EUT operation mode

The Applicant provides communication tools software(Fcc assist 1.0.0.2) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

Operation Frequency:

| Channel | Frequency (MHz) |
|---------|-----------------|
| 00 | 2402 |
| 01 | 2403 |
| ⋮ | ⋮ |
| 38 | 2440 |
| 39 | 2441 |
| 40 | 2442 |
| ⋮ | ⋮ |
| 77 | 2479 |
| 78 | 2480 |

2.7 Block Diagram of Test Setup



2.8 Special Accessories

Follow auxiliary equipment(s) test with EUT that provided by the manufacturer or laboratory is listed as follow:

| Description | Manufacturer | Model | Technical Parameters | Certificate | Provided by |
|---------------|--------------|------------|---|-------------|-------------|
| AC-DC Adapter | MOSO | EP-TA10CBC | Input:AC100-240V-50/60Hz, 0.5A Output:DC 5V,1A | FCC | Laboratory |
| / | / | / | / | / | / |
| / | / | / | / | / | / |
| / | / | / | / | / | / |

2.9 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the device filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.10 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 165725 Designation Number: CN1234

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 4758.01

Shenzhen Global Test Service Co.,Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

CNAS-Lab Code: L8169

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2024.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|-----------------------|--------------|
| Temperature: | 15-35 ° C |
| Humidity: | 30-60 % |
| Atmospheric pressure: | 950-1050mbar |

3.4 Summary of measurement results

| Test Specification clause | Test case | Test Sample | Test Mode | Test Channel | Recorded In Report | | Test result |
|---------------------------|---|----------------------|------------------|---|--------------------|---|-------------|
| §15.247(a)(1) | Carrier Frequency separation | GTS20210613 011-1-1# | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Middle | Compliant |
| §15.247(a)(1) | Number of Hopping channels | GTS20210613 011-1-1# | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Full | GFSK | <input checked="" type="checkbox"/> Full | Compliant |
| §15.247(a)(1) | Time of Occupancy (dwell time) | GTS20210613 011-1-1# | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Middle | Compliant |
| §15.247(a)(1) | Spectrum bandwidth of aFHSS system 20dB bandwidth | GTS20210613 011-1-1# | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | Compliant |
| §15.247(b)(1) | Maximum output power | GTS20210613 011-1-1# | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | Compliant |
| §15.247(d) | Band edge compliance conducted | GTS20210613 011-1-1# | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest | Compliant |
| §15.205 | Band edge compliance radiated | GTS20210613 011-1-1# | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest | GFSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest | Compliant |
| §15.247(d) | TX spurious emissions conducted | GTS20210613 011-1-1# | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | Compliant |
| §15.209(a) | TX spurious emissions Radiated above 1GHz | GTS20210613 011-1-1# | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | GFSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | Compliant |
| §15.209(a) | TX spurious Emissions radiated Below 1GHz | GTS20210613 011-1-2# | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | GFSK | <input checked="" type="checkbox"/> Middle | Compliant |
| §15.107(a) §15.207 | Conducted Emissions 9KHz-30 MHz | GTS20210613 011-1-2# | GFSK Π/4DQPSK | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | GFSK | <input checked="" type="checkbox"/> Middle | Compliant |

Remark:

1. The measurement uncertainty is not included in the test result.
2. We tested all test mode and recorded worst case in report

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

| Test | Range | Measurement Uncertainty | Notes |
|-----------------------|------------|-------------------------|-------|
| Radiated Emission | 30~1000MHz | 4.10 dB | (1) |
| Radiated Emission | 1~18GHz | 4.32 dB | (1) |
| Radiated Emission | 18-40GHz | 5.54 dB | (1) |
| Conducted Disturbance | 0.15~30MHz | 3.12 dB | (1) |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test


| Test Equipment | Manufacturer | Model No. | Serial No. | Calibration Date | Calibration Due Date |
|----------------------------|-----------------------------------|-----------------------|-----------------|------------------|----------------------|
| LISN | R&S | ENV216 | 3560.6550.08 | 2020/09/19 | 2021/09/18 |
| LISN | R&S | ESH2-Z5 | 893606/008 | 2020/09/19 | 2021/09/18 |
| EMI Test Receiver | R&S | ESPI3 | 101841-cd | 2020/09/19 | 2021/09/18 |
| EMI Test Receiver | R&S | ESCI7 | 101102 | 2020/09/19 | 2021/09/18 |
| Spectrum Analyzer | Agilent | N9020A | MY48010425 | 2020/09/19 | 2021/09/18 |
| Spectrum Analyzer | R&S | FSV40 | 100019 | 2020/09/19 | 2021/09/18 |
| Vector Signal generator | Agilent | N5181A | MY49060502 | 2020/09/19 | 2021/09/18 |
| Spectrum Analyzer | Agilent | E4421B | 3610AO1069 | 2020/09/19 | 2021/09/18 |
| Climate Chamber | ESPEC | EL-10KA | A20120523 | 2020/09/19 | 2021/09/18 |
| Controller | EM Electronics | Controller EM 1000 | N/A | N/A | N/A |
| Horn Antenna | Schwarzbeck | BBHA 9120D | 01622 | 2020/09/19 | 2021/09/18 |
| Active Loop Antenna | Beijing Da Ze Technology Co.,Ltd. | ZN30900C | 15006 | 2020/10/11 | 2021/10/10 |
| Bilog Antenna | Schwarzbeck | VULB9163 | 000976 | 2021/05/25 | 2022/05/24 |
| Broadband Horn Antenna | SCHWARZBECK | BBHA 9170 | 791 | 2020/09/19 | 2021/09/18 |
| Amplifier | Schwarzbeck | BBV 9743 | #202 | 2020/09/19 | 2021/09/18 |
| Amplifier | Schwarzbeck | BBV9179 | 9719-025 | 2020/09/19 | 2021/09/18 |
| Amplifier | EMCI | EMC051845B | 980355 | 2020/09/19 | 2021/09/18 |
| Temperature/Humidity Meter | Gangxing | CTH-608 | 02 | 2020/09/19 | 2021/09/18 |
| High-Pass Filter | K&L | 9SH10-2700/X12750-O/O | KL142031 | 2020/09/19 | 2021/09/18 |
| High-Pass Filter | K&L | 41H10-1375/U12750-O/O | KL142032 | 2020/09/19 | 2021/09/18 |
| RF Cable(below 1GHz) | HUBER+SUHNER | RG214 | RE01 | 2020/09/19 | 2021/09/18 |
| RF Cable(above 1GHz) | HUBER+SUHNER | RG214 | RE02 | 2020/09/19 | 2021/09/18 |
| Data acquisition card | Agilent | U2531A | TW53323507 | 2020/09/19 | 2021/09/18 |
| Power Sensor | Agilent | U2021XA | MY5365004 | 2020/09/19 | 2021/09/18 |
| Test Control Unit | Tonscend | JS0806-1 | 178060067 | 2021/06/18 | 2022/06/17 |
| Automated filter bank | Tonscend | JS0806-F | 19F8060177 | 2021/06/18 | 2022/06/17 |
| EMI Test Software | Tonscend | JS1120-1 | Ver 2.6.8.0518 | / | / |
| EMI Test Software | Tonscend | JS1120-3 | Ver 2.5.77.0418 | / | / |
| EMI Test Software | Tonscend | JS32-CE | Ver 2.5 | / | / |
| EMI Test Software | Tonscend | JS32-RE | Ver 2.5.1.8 | / | / |

Note: The Cal.Interval was one year.

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

| Frequency range (MHz) | Limit (dBuV) | |
|-----------------------|--------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

TEST RESULTS


| | | | |
|---------------|----------|----------------|-----|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | BT |

Remark:

- All modes of GFSK, Pi/4 DQPSK, and were test at Low, Middle, and High channel; only the worst result of GFSK Middle Channel was reported as below:
- Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

| | | | |
|---------------|--------------------------|--------------|---|
| Power supply: | AC 120V/60Hz(adapter) | Polarization | L |
|---------------|--------------------------|--------------|---|

Test Graph



Suspected List


| NO. | Frequency [MHz] | Reading [dBµV] | Factor [dB] | Result [dBµV] | Limit [dBµV] | Margin [dB] | Detector | Line | Remark |
|-----|-----------------|----------------|-------------|---------------|--------------|-------------|----------|------|--------|
| 1 | 0.4515 | 38.27 | 10.04 | 48.31 | 56.85 | 8.54 | PK | L1 | PASS |
| 2 | 0.4515 | 33.14 | 10.04 | 43.18 | 46.85 | 3.67 | AV | L1 | PASS |
| 3 | 0.6405 | 30.88 | 10.06 | 40.94 | 46.00 | 5.06 | AV | L1 | PASS |
| 4 | 0.6405 | 38.63 | 10.06 | 48.69 | 56.00 | 7.31 | PK | L1 | PASS |
| 5 | 1.3560 | 38.75 | 10.10 | 48.85 | 56.00 | 7.15 | PK | L1 | PASS |
| 6 | 1.3560 | 37.22 | 10.10 | 47.32 | 46.00 | 1.32 | AV | L1 | PASS |
| 7 | 2.2560 | 36.53 | 10.18 | 46.71 | 46.00 | 0.71 | AV | L1 | PASS |
| 8 | 2.2560 | 36.31 | 10.18 | 46.49 | 56.00 | 9.51 | PK | L1 | PASS |
| 9 | 3.1605 | 34.82 | 10.30 | 45.12 | 46.00 | 0.88 | AV | L1 | PASS |
| 10 | 3.1605 | 36.69 | 10.30 | 46.99 | 56.00 | 9.01 | PK | L1 | PASS |
| 11 | 4.0650 | 35.76 | 10.41 | 46.17 | 46.00 | 0.17 | AV | L1 | PASS |
| 12 | 4.0650 | 34.75 | 10.41 | 45.16 | 56.00 | 10.84 | PK | L1 | PASS |

Note:1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

| | | | |
|---------------|--------------------------|--------------|---|
| Power supply: | AC 120V/60Hz(adapter) | Polarization | N |
|---------------|--------------------------|--------------|---|

Test Graph



Suspected List

| NO. | Frequency [MHz] | Reading [dBµV] | Factor [dB] | Result [dBµV] | Limit [dBµV] | Margin [dB] | Detector | Line | Remark |
|-----|-----------------|----------------|-------------|---------------|--------------|-------------|----------|------|--------|
| 1 | 0.4560 | 43.35 | 10.05 | 53.40 | 56.77 | 3.37 | PK | N | PASS |
| 2 | 0.4560 | 36.06 | 10.05 | 40.11 | 46.77 | 6.66 | AV | N | PASS |
| 3 | 1.3650 | 35.35 | 10.10 | 39.45 | 46.00 | 6.55 | AV | N | PASS |
| 4 | 1.3695 | 42.59 | 10.10 | 52.69 | 56.00 | 3.31 | PK | N | PASS |
| 5 | 1.5585 | 36.01 | 10.12 | 40.13 | 46.00 | 5.87 | AV | N | PASS |
| 6 | 1.5585 | 41.59 | 10.12 | 51.71 | 56.00 | 4.29 | PK | N | PASS |
| 7 | 2.2740 | 38.04 | 10.19 | 42.23 | 46.00 | 3.77 | AV | N | PASS |
| 8 | 2.2740 | 39.83 | 10.19 | 50.02 | 56.00 | 5.98 | PK | N | PASS |
| 9 | 3.1875 | 37.36 | 10.31 | 41.67 | 46.00 | 4.33 | AV | N | PASS |
| 10 | 3.1875 | 39.67 | 10.31 | 49.98 | 56.00 | 6.02 | PK | N | PASS |
| 11 | 4.0965 | 39.82 | 10.41 | 50.23 | 56.00 | 5.77 | PK | N | PASS |
| 12 | 4.0965 | 36.17 | 10.41 | 40.58 | 46.00 | 5.42 | AV | N | PASS |


Note:1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).


4.2 Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type | Test Distance |
|----------------------|----------------------------|---------------|
| 9KHz-30MHz | Active Loop Antenna | 3 |
| 30MHz-1GHz | Ultra-Broadband Antenna | 3 |
| 1GHz-18GHz | Double Ridged Horn Antenna | 3 |
| 18GHz-25GHz | Horn Antenna | 1 |

7. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting | Detector |
|----------------------|---|----------|
| 9KHz-150KHz | RBW=200Hz/VBW=3KHz,Sweep time=Auto | QP |
| 150KHz-30MHz | RBW=9KHz/VBW=100KHz,Sweep time=Auto | QP |
| 30MHz-1GHz | RBW=120KHz/VBW=1000KHz,Sweep time=Auto | QP |
| 1GHz-40GHz | Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto | Peak |

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

| | |
|---------------------------|--|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude | AG = Amplifier Gain |
| AF = Antenna Factor | |

Transd=AF +CL-AG

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

| Frequency (MHz) | Distance (Meters) | Radiated (dBµV/m) | Radiated (µV/m) |
|-----------------|-------------------|----------------------------------|-----------------|
| 0.009-0.49 | 3 | 20log(2400/F(KHz))+40log(300/3) | 2400/F(KHz) |
| 0.49-1.705 | 3 | 20log(24000/F(KHz))+ 40log(30/3) | 24000/F(KHz) |
| 1.705-30 | 3 | 20log(30)+ 40log(30/3) | 30 |
| 30-88 | 3 | 40.0 | 100 |
| 88-216 | 3 | 43.5 | 150 |
| 216-960 | 3 | 46.0 | 200 |
| Above 960 | 3 | 54.0 | 500 |


TEST RESULTS


| | | | |
|---------------|----------|----------------|-----|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | BT |

Remark:

1. We measured Radiated Emission at GFSK, $\pi/4$ DQPSK and mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
2. For below 1GHz testing recorded worst at GFSK DH5 middle channel.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz





For 1GHz to 25GHz

Note: GFSK, Pi/4 DQPSK and all have been tested, only worse case GFSK is reported.

GFSK (above 1GHz)

| Frequency(MHz): | | | 2402 | | Polarity: | | HORIZONTAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4804.00 | 55.25 | PK | 74 | 18.75 | 53.35 | 31.42 | 6.98 | 36.50 | 1.90 |
| 4804.00 | 46.77 | AV | 54 | 7.23 | 44.87 | 31.42 | 6.98 | 36.50 | 1.90 |
| 7206.00 | 45.26 | PK | 74 | 28.74 | 34.66 | 37.03 | 8.87 | 35.30 | 10.60 |
| 7206.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| Frequency(MHz): | | | 2402 | | Polarity: | | VERTICAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4804.00 | 56.75 | PK | 74 | 17.25 | 54.85 | 31.42 | 6.98 | 36.50 | 1.90 |
| 4804.00 | 47.67 | AV | 54 | 6.33 | 45.77 | 31.42 | 6.98 | 36.50 | 1.90 |
| 7206.00 | 46.36 | PK | 74 | 27.64 | 35.76 | 37.03 | 8.87 | 35.30 | 10.60 |
| 7206.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| Frequency(MHz): | | | 2441 | | Polarity: | | HORIZONTAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4882.00 | 54.86 | PK | 74 | 19.14 | 52.80 | 30.98 | 7.58 | 36.50 | 2.06 |
| 4882.00 | 46.06 | AV | 54 | 7.94 | 44.00 | 30.98 | 7.58 | 36.50 | 2.06 |
| 7323.00 | 45.00 | PK | 74 | 29.00 | 34.08 | 37.66 | 8.56 | 35.30 | 10.92 |
| 7323.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| Frequency(MHz): | | | 2441 | | Polarity: | | VERTICAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4882.00 | 56.26 | PK | 74 | 17.74 | 54.20 | 30.98 | 7.58 | 36.50 | 2.06 |
| 4882.00 | 46.66 | AV | 54 | 7.34 | 44.60 | 30.98 | 7.58 | 36.50 | 2.06 |
| 7323.00 | 46.20 | PK | 74 | 27.80 | 35.28 | 37.66 | 8.56 | 35.30 | 10.92 |
| 7323.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| Frequency(MHz): | | | 2480 | | Polarity: | | HORIZONTAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4960.00 | 56.43 | PK | 74 | 17.57 | 53.36 | 31.47 | 7.80 | 36.20 | 3.07 |
| 4960.00 | 47.20 | AV | 54 | 6.80 | 44.13 | 31.47 | 7.80 | 36.20 | 3.07 |
| 7440.00 | 46.17 | PK | 74 | 27.83 | 34.43 | 38.32 | 8.72 | 35.30 | 11.74 |
| 7440.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| Frequency(MHz): | | | 2480 | | Polarity: | | VERTICAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4960.00 | 57.23 | PK | 74 | 16.77 | 54.16 | 31.47 | 7.80 | 36.20 | 3.07 |
| 4960.00 | 47.80 | AV | 54 | 6.20 | 44.73 | 31.47 | 7.80 | 36.20 | 3.07 |
| 7440.00 | 47.27 | PK | 74 | 26.73 | 35.53 | 38.32 | 8.72 | 35.30 | 11.74 |
| 7440.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

Results of Band Edges Test (Radiated)

Note: GFSK, Pi/4 DQPSK and all have been tested, only worse case GFSK is reported.

GFSK

| Frequency(MHz): | | | 2402 | | Polarity: | | HORIZONTAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2390.00 | 49.02 | PK | 74.00 | 24.98 | 54.43 | 27.49 | 3.32 | 36.22 | -5.41 |
| 2390.00 | -- | AV | 54.00 | -- | -- | -- | -- | -- | -- |
| Frequency(MHz): | | | 2402 | | Polarity: | | VERTICAL | | |
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2390.00 | 50.02 | PK | 74.00 | 23.98 | 55.43 | 27.49 | 3.32 | 36.22 | -5.41 |
| 2390.00 | -- | AV | 54.00 | -- | -- | -- | -- | -- | -- |
| Frequency(MHz): | | | 2480 | | Polarity: | | HORIZONTAL | | |
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2483.50 | 47.11 | PK | 74.00 | 26.89 | 52.62 | 27.45 | 3.38 | 36.34 | -5.51 |
| 2483.50 | -- | AV | 54.00 | -- | -- | -- | -- | -- | -- |
| Frequency(MHz): | | | 2480 | | Polarity: | | VERTICAL | | |
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2483.50 | 49.11 | PK | 74.00 | 24.89 | 54.62 | 27.45 | 3.38 | 36.34 | -5.51 |
| 2483.50 | -- | AV | 54.00 | -- | -- | -- | -- | -- | -- |

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.

4.3 Maximum Peak Output Power


Limit

The Maximum Peak Output Power Measurement is 125mW (20.97).

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the powersensor.

Test Configuration



Test Results

| | | | |
|---------------|----------|----------------|-----|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | BT |

| Type | Channel | Output power (dBm) | Limit (dBm) | Result |
|----------|---------|--------------------|-------------|--------|
| GFSK | 00 | -4.07 | 20.97 | Pass |
| | 39 | -3.10 | | |
| | 78 | -2.85 | | |
| π/4DQPSK | 00 | -3.35 | 20.97 | Pass |
| | 39 | -2.38 | | |
| | 78 | -2.15 | | |

Note: 1.The test results including the cable lose.

Test plot as follows:

4.4 20dB Bandwidth

Limit


For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Configuration



Test Results

| | | | |
|---------------|----------|----------------|-----|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | BT |

| Modulation | Channel | 20dB bandwidth (MHz) | Result |
|------------|---------|----------------------|--------|
| GFSK | CH00 | 0.954 | Pass |
| | CH39 | 0.957 | |
| | CH78 | 0.957 | |
| π/4DQPSK | CH00 | 1.314 | |
| | CH39 | 1.317 | |
| | CH78 | 1.320 | |

Test plot as follows:

GFSK Modulation



CH00



CH39



CH78

$\pi/4$ DQPSK Modulation



CH00



CH39



CH78

4.5 Frequency Separation


LIMIT

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the $2/3 * 20\text{dB}$ bandwidth of the hopping channel, whichever is greater.

TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW.

TEST CONFIGURATION



TEST RESULTS

| | | | |
|---------------|----------|----------------|-----|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | BT |


| Modulation | Channel | Channel Separation (MHz) | Limit(MHz) | Result |
|---------------------|---------|--------------------------|--|--------|
| GFSK | CH39 | 0.998 | 25KHz or $2/3 * 20\text{dB}$ bandwidth | Pass |
| | CH40 | | | |
| $\pi/4\text{DQPSK}$ | CH39 | 0.998 | 25KHz or $2/3 * 20\text{dB}$ bandwidth | Pass |
| | CH40 | | | |

Note:

We have tested all mode at high, middle and low channel, and recorded worst case at middle

Test plot as follows:

Frequency Separation



GFSK



$\pi/4$ DQPSK

4.6 Number of hopping frequency


Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 2400MHz to 2483.5MHz with 100 KHz RBW and 300 KHz VBW.


Test Configuration




Test Results

| | | | |
|---------------|---------------------------|----------------|--------|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | BT |
| Modulation | Number of Hopping Channel | Limit | Result |
| GFSK | 79 | ≥15 | Pass |
| π/4DQPSK | 79 | | |

Test plot as follows:



GFSK Modulation



$\pi/4$ DQPSK Modulation

4.7 Time of Occupancy (Dwell Time)


Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with 1MHz RBW and 1MHz VBW, Span 0Hz.

Test Configuration





Test Results

| | | | |
|---------------|----------|----------------|-----|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | BT |



| Modulation | Packet | BurstWidth [ms] | TotalHops [Num] | Result[s] | Limit (s) | Result |
|---------------|--------|-----------------|-----------------|-----------|-----------|--------|
| GFSK | DH1 | 0.37 | 320 | 0.120 | 0.40 | Pass |
| | DH3 | 1.63 | 130 | 0.212 | | |
| | DH5 | 2.88 | 110 | 0.317 | | |
| $\pi/4$ DQPSK | 2-DH1 | 0.38 | 320 | 0.123 | 0.40 | Pass |
| | 2-DH3 | 1.64 | 150 | 0.245 | | |
| | 2-DH5 | 2.88 | 70 | 0.202 | | |

Test plot as follows:



DH1 Ant1 Hop





DH3 Ant1 Hop





DH5 Ant1 Hop





2DH1_Ant1_Hop



2DH3_Ant1_Hop



2DH5_Ant1_Hop



4.8 Out-of-band Emissions


Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, bandedge and out-of-band emissions.

Test Configuration



Test Results

| | | | |
|---------------|----------|----------------|-----|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | BT |

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.

We measured all conditions (DH1, DH3, DH5) and recorded worst case at DH5

Test plot as follows:

GFSK CH00



Reference

GFSK CH39



Reference



30MHz-3GHz



30MHz-3GHz



3GHz-25GHz



3GHz-25GHz

GFSK CH78

π /4DQPSK CH00



Reference

Reference



30MHz-3GHz

30MHz-3GHz



3GHz-25GHz

3GHz-25GHz

π /4DQPSK CH39

π /4DQPSK CH78



Reference

Reference



30MHz-3GHz

30MHz-3GHz




3GHz-25GHz


3GHz-25GHz

Band-edge Measurements for RF Conducted Emissions:

GFSK




Left Band edge hopping off



RightBand edge hopping off




Left Band edge hopping on



RightBand edge hopping on


$\pi/4$ DQPSK




Left Band edge hopping off



RightBand edge hopping off



Left Band edge hopping on



Right Band edge hopping on

4.9 Pseudorandom Frequency Hopping Sequence

TEST APPLICABLE


For 47 CFR Part 15C section 15.247 (a) (1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence Requirement


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:2⁹-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

4.10 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The maximum gain of antenna was 0dBi.


5 Test Setup Photos of the EUT




6 Photos of the EUT



External photos









Internal photos





***** End of Report *****