

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	10.1inch Tablet PC
Model Name	SC-4032WKB, SC-2107, SC-1032WKB
FCC ID	2AC5R-SC-4032WKB

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

BT:

$P_t = -2.688 \text{ dBm} = 0.54 \text{ mW}$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (0.54 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.441(\text{GHz})}] = 0.17 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

2.4G WIFI:

$P_t = 9.63 \text{ dBm} = 9.18 \text{ mW}$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (9.18 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.412(\text{GHz})}] = 2.85 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Note: The BT and 2.4GHz WIFI cannot transmit simultaneously.

### 4. CONCLUSION

The SAR evaluation is not required.