



REPORT No.: SZ18090337W03

# TEST REPORT

**APPLICANT** : Jiangsu SEUIC Technology Co.,Ltd.

**PRODUCT NAME** : Portable Data Collection Terminal

**MODEL NAME** : CRUISE 1

**BRAND NAME** : CRUISE/SEUIC

**FCC ID** : 2AC68-CRUISE1P

**STANDARD(S)** : 47 CFR Part 15 Subpart C

**RECEIPT DATE** : 2018-10-15

**TEST DATE** : 2018-10-25 to 2018-10-30

**ISSUE DATE** : 2018-12-19

Edited by:

  
Zeng Xiaoying (Rapporteur)

Approved by:



Peng Huarui ( Supervisor )

**NOTE:** This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.  
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





## DIRECTORY

<b>1. Technical Information .....</b>	<b>4</b>
<b>1.1. Applicant and Manufacturer Information .....</b>	<b>4</b>
<b>1.2. Equipment Under Test (EUT) Description .....</b>	<b>4</b>
<b>1.3. Test Standards and Results .....</b>	<b>6</b>
<b>1.4. Environmental Conditions .....</b>	<b>6</b>
<b>2. 47 CFR Part 15C Requirements .....</b>	<b>7</b>
<b>2.1. Antenna requirement .....</b>	<b>7</b>
<b>2.2. Duty Cycle Of Test Signal .....</b>	<b>7</b>
<b>2.3. Peak Output Power .....</b>	<b>11</b>
<b>2.4. Bandwidth .....</b>	<b>14</b>
<b>2.5. Conducted Spurious Emissions and Band Edge .....</b>	<b>21</b>
<b>2.6. Power spectral density (PSD) .....</b>	<b>31</b>
<b>2.7. Conducted Emission .....</b>	<b>38</b>
<b>2.8. Restricted Frequency Bands .....</b>	<b>42</b>
<b>2.9. Radiated Emission .....</b>	<b>51</b>
<b>Annex A Test Uncertainty .....</b>	<b>64</b>
<b>Annex B Testing Laboratory Information .....</b>	<b>65</b>



REPORT No.: SZ18090337W03

Change History		
Version	Date	Reason for change
1.0	2018-12-19	First edition



# 1. Technical Information

**Note:** Provide by applicant.

## 1.1. Applicant and Manufacturer Information

<b>Applicant:</b>	Jiangsu SEUIC Technology Co.,Ltd.
<b>Applicant Address:</b>	NO.15 Xinghuo Road,Nanjing New & High Technology Industry Development Zone,210061,Nanjing City,Jiangsu Province,China
<b>Manufacturer:</b>	Jiangsu SEUIC Technology Co.,Ltd.
<b>Manufacturer Address:</b>	NO.15 Xinghuo Road,Nanjing New & High Technology Industry Development Zone,210061,Nanjing City,Jiangsu Province,China

## 1.2. Equipment Under Test (EUT) Description

<b>Product Name:</b>	Portable Data Collection Terminal	
<b>Serial No:</b>	(N/A, marked #1 by test site)	
<b>Hardware Version:</b>	SLB761_MB_V1.02_PCB	
<b>Software Version:</b>	D700P_I_V1.1.5	
<b>Modulation Type:</b>	DSSS, OFDM	
<b>Operating Frequency Range:</b>	802.11b/g/ n(HT20): 2.412GHz - 2.462GHz	
<b>Channel Number:</b>	802.11b/g/ n(HT20): 11	
<b>Antenna Type:</b>	PIFA Antenna	
<b>Antenna Gain:</b>	-2.5 dBi	
<b>Accessory Information:</b>	Battery	
	<b>Brand Name:</b>	N/A
	<b>Model No.:</b>	BT01700CRUISE
	<b>Serial No.:</b>	(N/A, marked #1 by test site)
	<b>Capacity:</b>	4500mAh
	<b>Rated Voltage:</b>	3.8V
	<b>Charge Limit:</b>	4.35V



<b>Accessory Information:</b>	AC Adapter	
	Brand Name:	SHENZHEN TIANYIN ELECTRONICS CO.,LTD
	Model No.:	TPA-23A050200UU01
	Serial No.:	(N/A, marked #1 by test site)
	Rated Input:	100-240V ~ 50/60Hz 0.3A
	Rated Output:	5V=2.0A

**Note1:** The EUT is operating at 2.4GHz ISM; it supports 802.11b, 802.11g, 802.11n and they are all tested in this report.

For 802.11b/g/n(HT20) (2.4GHz band), the frequencies allocated is  $F \text{ (MHz)} = 2412 + 5 * (n - 1)$  ( $1 \leq n \leq 11$ ). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 1 (2412MHz), 6 (2437MHz) and 11 (2462MHz).

**Note 2:** The EUT connected to the serial port of the computer with a serial communication cable, we use the dedicated software to control the EUT continuous transmission.

**Note 3:** For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



### 1.3. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 15 (10-1-15 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result
1	15.203	Antenna Requirement	N/A	N/A	PASS
2	N/A	Duty Cycle Of Test Signal	Oct 25, 2018	Wang Meng	PASS
3	15.247(b)	Peak Output Power	Oct 25, 2018	Wang Meng	PASS
4	15.247(a)	Bandwidth	Oct 25, 2018	Wang Meng	PASS
5	15.247(d)	Conducted Spurious Emission and Band Edge	Oct 25, 2018	Wang Meng	PASS
6	15.247(e)	Power spectral density (PSD)	Oct 25, 2018	Wang Meng	PASS
7	15.207	Conducted Emission	Oct 27, 2018	Wang Dalong	PASS
8	15.247(d)	Restricted Frequency Bands	Oct 30, 2018	Wang Dalong	PASS
9	15.209, 15.247(d)	Radiated Emission	Oct 30, 2018	Wang Dalong	PASS

**Note1:** The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10 2013 and KDB558074 D01 v05.

**Note2:** The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 11dB contains two parts that cable loss 1dB and Attenuator 10dB.

### 1.4. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106



## 2. 47 CFR Part 15C Requirements

### 2.1. Antenna requirement

#### 2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

### 2.2. Duty Cycle Of Test Signal


#### 2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this subclause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than  $\pm 2\%$ ; otherwise, the duty cycle is considered to be nonconstant.

### 2.2.2. Test Description

#### A. Test Set:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.

#### B. Equipments List:

Please refer ANNEX B(4).

### 2.2.3. Test Result


#### A. Test Verdict:

Test Mode	Duty Cycle (%) (D)	Duty Factor (10*lg[1/D])
802.11b	97.50	0.11
802.11g	86.86	0.61
802.11n(HT20)	86.05	0.65







## B. Test Plots



(Channel 1, 2412MHz, 802.11b)



(Channel 1, 2412MHz, 802.11g)



(Channel 1, 2412MHz, 802.11 n(HT20))

## 2.3. Peak Output Power


### 2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

### 2.3.2. Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

#### A. Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

#### B. Equipments List:

Please refer ANNEX B(4).

**2.3.3. Test Result****2.3.3.1 802.11b Test Mode**

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	13.88	0.024	30	1	PASS
6	2437	14.12	0.026			PASS
11	2462	13.70	0.023			PASS

Channel	Frequency (MHz)	Measured Output Average Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	11.04	0.013	30	1	PASS
6	2437	11.14	0.013			PASS
11	2462	10.82	0.012			PASS

**2.3.3.2 802.11g Test mode**

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	22.38	0.173	30	1	PASS
6	2437	23.61	0.230			PASS
11	2462	22.94	0.197			PASS

Channel	Frequency (MHz)	Measured Output Average Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	11.82	0.015	30	1	PASS
6	2437	12.19	0.017			PASS
11	2462	11.87	0.015			PASS

**2.3.3.3 802.11n(HT20) Test mode**

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	22.41	0.174	30	1	PASS
6	2437	23.33	0.215			PASS
11	2462	23.02	0.200			PASS

Channel	Frequency (MHz)	Measured Output Average Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	11.82	0.015	30	1	PASS
6	2437	12.15	0.016			PASS
11	2462	12.51	0.018			PASS


## 2.4. Bandwidth

### 2.4.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 2.4.2. Test Description

#### A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

KDB 558074 Section 8.1 Option 1 was used in order to prove compliance.

#### B. Equipments List:

Please refer ANNEX B(4).




### 2.4.3. Test Result

#### 2.4.3.1 802.11b Test mode

##### A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	8.523	≥500	PASS
6	2437	8.079	≥500	PASS
11	2462	8.548	≥500	PASS

##### B. Test Plots



(Channel 1, 2412MHz, 802.11b)



(Channel 6, 2437 MHz, 802.11b)



(Channel 11, 2462MHz, 802.11b)






### 2.4.3.2 802.11g Test mode


#### A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	16.40	≥500	PASS
6	2437	16.42	≥500	PASS
11	2462	16.41	≥500	PASS

#### B. Test Plots:



(Channel 1, 2412MHz, 802.11g)



(Channel 6, 2437MHz, 802.11g)



(Channel 11, 2462MHz, 802.11g)




### 2.4.3.3 802.11n(HT20) Test mode


#### A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	17.58	≥500	PASS
6	2437	17.62	≥500	PASS
11	2462	17.61	≥500	PASS


#### B. Test Plots:



(Channel 1, 2412MHz, 802.11n(HT20))



(Channel 6, 2437MHz, 802.11n(HT20))



(Channel 11, 2462MHz, 802.11n(HT20))


## 2.5. Conducted Spurious Emissions and Band Edge

### 2.5.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 2.5.2. Test Description

#### A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

KDB 558074 Section 11.0 was used in order to prove compliance.

#### B. Equipments List:

Please refer ANNEX B(4).



### 2.5.3. Test Result


#### 2.5.3.1 802.11b Test mode

##### A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-44.56	2.79	-17.21	PASS
6	2437	-42.32	1.33	-18.67	PASS
11	2462	-43.16	2.28	-17.72	PASS

##### B. Test Plots:


**Note:** The power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)




(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)






### 2.5.3.2 802.11g Test mode

#### A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-44.94	2.80	-17.20	PASS
6	2437	-43.11	3.45	-16.55	PASS
11	2462	-42.90	-0.24	-20.24	PASS

#### B. Test Plots:


**Note:** The power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)




(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)




### 2.5.3.3 802.11n(HT20) Test mode

#### A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-43.14	-1.46	-21.46	PASS
6	2437	-43.28	-0.30	-20.30	PASS
11	2462	-44.39	-0.36	-20.36	PASS

#### B. Test Plots:


**Note:** The power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)




(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)

## 2.6. Power spectral density (PSD)

### 2.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


### 2.6.2. Test Description

#### A. Test procedure

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- Set analyzer center frequency to channel center frequency.
- Set the span to 1.5 times DTS
- Set the RBW to 3 kHz
- Set the VBW to 10 kHz
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

#### B. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

KDB 558074 Section 10.2 was used in order to prove compliance.

#### C. Equipments List:

Please refer ANNEX B(4).



### 2.6.3. Test Result

#### 2.6.3.1 802.11b Test mode

##### A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-11.42	8	PASS
6	2437	-11.04	8	PASS
11	2462	-11.25	8	PASS

##### B. Test Plots:



(Channel = 1, 802.11b)





(Channel = 6, 802.11b)



(Channel = 11, 802.11b)




### 2.6.3.2 802.11g Test mode


#### A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-12.36	8	PASS
6	2437	-13.37	8	PASS
11	2462	-13.23	8	PASS


#### B. Test Plots:



(Channel = 1, 802.11g)



(Channel = 6, 802.11g)



(Channel = 11, 802.11g)




### 2.6.3.3 802.11n(HT20) Test mode


#### A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-13.44	8	PASS
6	2437	-13.28	8	PASS
11	2462	-12.24	8	PASS


#### B. Test Plots:



(Channel = 1, 802.11n(HT20))



(Channel = 6, 802.11n(HT20))



(Channel = 11, 802.11n(HT20))

## 2.7. Conducted Emission

### 2.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

#### NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 2.7.2. Test Description

#### A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10 2013.



## B. Equipments List:

Please refer ANNEX B(4).

### 2.7.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

**Note:** Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

#### A. Test setup:

Test Mode: EUT+ Earphone + Battery + USB Cable+ Adapter+ WLAN TX

Test Voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

$U_R$ : Receiver Reading

$A_{\text{Factor}}$ : Voltage division factor of LISN


## B. Test Plots:



(L Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2760	41.39	32.91	60.93	50.93	Line	PASS
2	0.6223	47.50	35.17	56.00	46.00		PASS
3	0.6772	47.77	38.61	56.00	46.00		PASS
4	2.1771	37.48	28.58	56.00	46.00		PASS
5	4.1823	34.93	24.79	56.00	46.00		PASS
6	14.1118	36.58	24.12	60.00	50.00		PASS





(N Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2623	45.22	32.71	61.36	51.36	Neutral	PASS
2	0.4781	43.57	32.41	56.37	46.37		PASS
3	0.5825	44.94	33.85	56.00	46.00		PASS
4	1.7658	31.43	23.39	56.00	46.00		PASS
5	4.2826	29.37	19.23	56.00	46.00		PASS
6	13.3431	31.15	19.29	60.00	50.00		PASS


## 2.8. Restricted Frequency Bands

### 2.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 2.8.2. Test Description

#### A. Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

KDB 558074 Section 12.1 was used in order to prove compliance.

**B. Equipments List:**

Please refer ANNEX B(4).

**2.8.3. Test Result**

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m


**Note:** Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

**2.7.3.1 802.11b Test mode****A. Test Verdict:**


Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dBuV)	$A_T$ (dB)	$A_{\text{Factor}}$ (dB@3m)	Max. Emission E (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Verdict
		PK/ AV						
1	2354.54	PK	52.31	-29.67	32.56	55.20	74	PASS
1	2359.14	AV	33.88	-29.67	32.56	36.77	54	PASS
11	2496.01	PK	48.51	-29.67	32.56	51.40	74	PASS
11	2483.93	AV	33.31	-29.67	32.56	36.20	54	PASS




## B. Test Plots:




(Channel = 1 PEAK, 802.11b)



(Channel = 1 AVG, 802.11b)



(Channel = 11 PEAK, 802.11b)



(Channel = 11 AVG, 802.11b)




### 2.7.3.2 802.11g Test mode


#### A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dBuV)	$A_T$ (dB)	$A_{Factor}$ (dB@3m)	Max. Emission E (dBuV/m)	Limit (dBuV/m)	Verdict
		PK/ AV						
1	2386.91	PK	59.26	-29.67	32.56	62.15	74	PASS
1	2390.00	AV	38.17	-29.67	32.56	41.06	54	PASS
11	2483.50	PK	57.96	-29.67	32.56	60.85	74	PASS
11	2483.50	AV	35.39	-29.67	32.56	38.28	54	PASS


#### B. Test Plots:




(Channel = 1 PEAK, 802.11g)



(Channel = 1 AVG, 802.11g)



(Channel = 11 PEAK, 802.11g)



(Channel = 11 AVG, 802.11g)


### 2.7.3.3 802.11n(HT20) Test mode

#### A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dBuV)	$A_T$ (dB)	$A_{Factor}$ (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2388.48	PK	58.29	-29.67	32.56	61.18	74	PASS
1	2390.00	AV	38.17	-29.67	32.56	41.06	54	PASS
11	2484.31	PK	52.61	-29.67	32.56	55.50	74	PASS
11	2483.50	AV	34.34	-29.67	32.56	37.23	54	PASS




## B. Test Plots:




(Channel = 1 PEAK, 802.11n(HT20))



(Channel = 1 AVG, 802.11n(HT20))



(Channel = 11 PEAK, 802.11n(HT20))



(Channel = 11 AVG, 802.11n(HT20))



## 2.9. Radiated Emission

### 2.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ )	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.


For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


## 2.9.2. Test Description

### A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



### 3) For radiated emissions above 1GHz



The RF absorbing material used on the reference ground plane and on the turntable have a maximum height (thickness) of 30 cm (12 in) and have a minimum-rated attenuation of 20 dB at all frequencies from 1 GHz to 18 GHz. Test site have a minimum area of the ground plane covered with RF absorbing material as specified in Figure 6 of ANSI C63.4: 2014.

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10 (2013). For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading



For the Test Antenna:

(a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Place the test antenna at 3m away from area of the EUT, while keeping the test antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The test antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final test antenna elevation shall be that which maximizes the emissions. The test antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emission levels at both horizontal and vertical polarizations should be tested.

#### A. Equipments List:

Please refer ANNEX B(4).

#### 2.9.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m

During the test, the total correction Factor  $A_T$  and  $A_{\text{Factor}}$  were built in test software.

**Note1:** All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

**Note2:** For the frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**Note3:** For the frequency, which started from 25GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.




### 2.9.3.1 802.11b Test mode

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
94.343	19.13	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
187.822	29.90	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
361.427	17.86	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2860.702	45.19	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5402.546	46.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8628.732	47.46	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
74.919	20.38	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
190.250	29.67	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1345.098	39.24	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2917.730	44.47	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5663.248	45.39	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10592.144	46.38	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




### Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
95.557	19.35	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
195.106	28.87	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1552.541	40.07	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3300.636	44.42	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5655.101	47.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9284.561	47.73	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
95.557	20.93	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
191.464	28.52	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2293.958	43.74	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5634.734	45.18	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11924.168	46.51	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
16445.717	49.05	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)



Plot for Channel = 11

Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
95.557	19.68	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
190.250	29.83	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1517.327	40.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4371.959	45.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8600.218	46.48	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12156.356	47.75	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
95.557	22.96	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
195.106	27.35	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1913.005	40.82	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5671.395	46.11	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10298.854	45.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12160.429	46.73	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)


**2.9.3.2 802.11g Test mode**

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
78.561	14.87	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
178.110	29.54	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2811.820	44.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
6734.570	45.12	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11736.789	46.57	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
16034.297	48.62	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
77.347	22.60	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
191.464	31.95	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2372.069	44.28	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4514.530	45.33	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11125.768	46.91	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
16197.236	49.37	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

### Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
95.557	17.31	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
187.822	28.32	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2208.163	43.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4718.203	45.35	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7072.668	44.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12498.527	46.16	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
76.133	23.70	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
190.250	32.09	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2025.690	41.96	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4449.354	45.18	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7887.361	46.48	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12119.694	47.27	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)

### Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
94.343	15.03	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
180.538	30.23	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2077.551	42.55	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3870.922	44.16	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8469.867	46.56	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12135.988	47.56	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
76.133	22.61	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
191.464	31.97	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
539.887	19.42	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1672.269	40.36	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3870.922	44.17	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8616.512	46.90	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)


### 2.9.3.3 802.11n(HT20) Test mode

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
178.110	29.94	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
3284.343	43.92	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
6974.905	44.60	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9150.136	45.92	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12869.213	46.17	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
14999.636	46.41	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
74.919	22.82	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
191.464	29.74	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2068.587	42.40	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4653.028	44.97	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8013.639	46.38	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13993.490	45.70	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)

### Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
95.557	17.56	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
180.538	27.59	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2040.416	41.91	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4714.130	44.74	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
6950.464	44.51	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10364.030	47.16	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
74.919	20.90	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
191.464	28.92	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2771.086	41.12	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4624.514	45.50	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7027.860	45.07	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8587.998	46.26	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




## Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
31.214	23.90	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
178.110	30.03	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1369.428	39.37	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2505.882	43.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3300.636	43.46	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5174.432	44.61	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
76.133	22.50	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
190.250	28.12	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2991.053	44.28	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5630.660	45.52	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8693.908	45.79	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10347.736	45.92	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

## Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power spectral density (PSD)	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{ dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$





## Annex B Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

<b>Laboratory Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
<b>Laboratory Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
<b>Telephone:</b>	+86 755 36698555
<b>Facsimile:</b>	+86 755 36698525

### 2. Identification of the Responsible Testing Location

<b>Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
<b>Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



#### 4. Test Equipments Utilized

##### 4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Attenuator 1	(N/A.)	10dB	Resnet	2018.04.17	2019.04.16
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2018.11.06	2019.11.05
USB Wideband Power Sensor	MY54210011	U2021XA	Agilent	2018.04.17	2019.04.16
RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial cable	CB02	RF02	Morlab	N/A	N/A
SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A
Computer	T430i	Think Pad	Lenovo	N/A	N/A

##### 4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY56400093	N9038A	KEYSIGHT	2018.05.08	2019.05.07
LISN	812744	NSLK 8127	Schwarzbeck	2018.05.08	2019.05.07
Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2018.05.08	2019.05.07
Coaxial cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A

##### 4.3 List of Software Used

Description	Manufacturer	Software Version
Test system	Tonscend	V2.6
Power Panel	Agilent	V3.8
MORLAB EMCR V1.2	MORLAB	V 1.0

**4.4 Radiated Test Equipments**

<b>Equipment Name</b>	<b>Serial No.</b>	<b>Type</b>	<b>Manufacturer</b>	<b>Cal. Date</b>	<b>Cal. Due</b>
Receiver	MY54130016	N9038A	Agilent	2018.08.04	2019.08.03
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2018.05.18	2019.05.17
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2018.03.03	2019.03.02
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2018.08.06	2019.08.05
Test Antenna – Horn	BBHA9170 #774	BBHA9170	Schwarzbeck	2018.08.02	2019.08.01
Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde& Schwarz	2018.05.08	2019.05.07
18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde& Schwarz	2018.05.08	2019.05.07
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2018.12.01	2019.11.30
Anechoic Chamber	N/A	9m*6m*6m	CRT	2017.11.19	2020.11.18

————— END OF REPORT —————