福贝特国际〈香港〉有限公司

Forbet International (Hong Kong) Limited 6th Floor, Jihao Building, No. 1086, Shennan East Road, Luohu District, Shenzhen, China



Antenna specification

Notes for antenna installation





Notes for antenna installation

Electronic wire installation recommendations:

1:The electron line length is in the 24.60mm.


2: The electronic wire is installed on the side of the horn.

3: The end of the electronic wire is fixed with adhesive

paper to make the consistency of the batch production good.



Antenna parameters



Freq	2.4GHz	2.5GHz	spce
VSWR	1.48	1.79	<2
Log Mag	-14.15	-10.93	<-10



Antenna Efficiency and Gain

Frequency/Mhz	Efficiency / %	Gain/dBi
2400	4.2	-7.13
2410	4.21	-7.3
2420	4.33	-7.43
2430	4.38	-7.69
2440	4.4	-7.9
2450	4.66	-7.84
2460	4.8	-7.75
2470	5.01	-7.56
2480	4.7	-7.7
2490	4.65	-7.62
2500	4.29	-7.99



The measured distance on the roof of the building

Project	T11-N	Test date	2024.5.9	
Software release		Test location	The measured distance on the roof of the building	
Model	Measuring distance	Metal watchband	Non-metallic watchband	
	Positive effective distance (≥15m)	18	17	
	Back effective distance (≥10m)	10	6	
Android	Positive effective distance (≥15m)	18	18	
	Back effective distance (≥10m)	9	9	