



FCC RF Test Report

APPLICANT : Espressif Systems (Shanghai) Co.,Ltd.
EQUIPMENT : 2.4GHz Wi-Fi & BLE IoT Module
BRAND NAME : ESPRESSIF
MODEL NAME : ESP8684-WROOM-03
FCC ID : 2AC7Z-ESP868403
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : May 11, 2024 ~ Feb. 14, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	5
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	14
3.5 Radiated Band Edges and Spurious Emission Measurement	15
3.6 AC Conducted Emission Measurement.....	19
3.7 Antenna Requirements.....	21
4 LIST OF MEASURING EQUIPMENT.....	22
5 MEASUREMENT UNCERTAINTY.....	23
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR440706A	Rev. 01	Initial issue of report	Feb. 17, 2025

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 1.13 dB at 2483.50 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 13.40 dB at 0.1810 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Espressif Systems (Shanghai) Co.,Ltd.

Suite 204, Block 2, 690 Bibo Road, Zhang Jiang Hi-Tech Park, Shanghai, China

1.2 Manufacturer

Espressif Systems (Shanghai) Co.,Ltd.

Suite 204, Block 2, 690 Bibo Road, Zhang Jiang Hi-Tech Park, Shanghai, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	2.4GHz Wi-Fi & BLE IoT Module
Brand Name	ESPRESSIF
Model Name	ESP8684-WROOM-03
FCC ID	2AC7Z-ESP868403
HW Version	V1.1
SW Version	v1.1.3.4
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	BLE 1Mbps: 16.83 dBm (0.0482 W) BLE 2Mbps: 19.74 dBm (0.0942 W) BLE 125kbps: 16.69 dBm (0.0467 W) BLE 500kbps: 16.75 dBm (0.0473 W)
99% Occupied Bandwidth	BLE 1Mbps:1.087MHz BLE 2Mbps:2.062MHz
Antenna Type / Gain	PCB Antenna type with gain 3.96 dBi
Type of Modulation	Bluetooth LE : GFSK

Note: For BLE 1Mbps/2Mbps/125kbps/500kbps mode, the whole testing have assessed only BLE 1Mbps/2Mbps by referring to the higher output power.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH03-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH03-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps
	Mode 6: Bluetooth Tx CH38_2478 MHz_BLE 2Mbps
	Mode 7: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
	Mode 8: Bluetooth Tx CH00_2402 MHz_BLE 125kbps
	Mode 9: Bluetooth Tx CH19_2440 MHz_BLE 125kbps
	Mode 10: Bluetooth Tx CH39_2480 MHz_BLE 125kbps
	Mode 11: Bluetooth Tx CH00_2402 MHz_BLE 500kbps
	Mode 12: Bluetooth Tx CH19_2440 MHz_BLE 500kbps
	Mode 13: Bluetooth Tx CH39_2480 MHz_BLE 500kbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps
	Mode 4: Bluetooth Tx CH01_2404 MHz_BLE 2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps
	Mode 6: Bluetooth Tx CH38_2478 MHz_BLE 2Mbps
	Mode 7: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
AC Conducted Emission	Mode 1: Bluetooth Tx + Powered from Test Jig
Remark: For Radiated Test Cases, The tests were performed with Test jig.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
2.	Test Jig	N/A	N/A	N/A	N/A	N/A
3.	Router	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
4.	Hard DISK	WD	C6B	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 1.56 dB and 20dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 1.56 + 20 = 21.56 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1% to 5% of the 99% OBW and the VBW is set to 3 times of the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C&.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Jul. 08, 2024~ Feb. 14, 2025	Oct. 10, 2024	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024		Oct. 09, 2025	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2024	Jul. 08, 2024~ Feb. 14, 2025	Jan. 01, 2025	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2025		Jan. 01, 2026	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2024	Jul. 08, 2024~ Feb. 14, 2025	Jan. 01, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2025		Jan. 01, 2026	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 10, 2023	Jul. 10, 2024	Oct. 09, 2024	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz~44GHz	Oct. 11, 2023	Jul. 10, 2024	Oct. 10, 2024	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 10, 2023	Jul. 10, 2024	Oct. 09, 2024	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz~1GHz	Dec. 20, 2023	Jul. 10, 2024	Dec. 19, 2024	Radiation (03CH03-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Dec. 21, 2023	Jul. 10, 2024	Dec. 20, 2024	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101116	18GHz~40GHz	Oct. 10, 2023	Jul. 10, 2024	Oct. 09, 2024	Radiation (03CH03-KS)
Amplifier	SONOMA	310N	413740	30MHz~1000MHz	Jan. 05, 2024	Jul. 10, 2024	Jan. 04, 2025	Radiation (03CH03-KS)
Amplifier	EM	EM18G40GA	060851	18~40GHz	Jan. 05, 2024	Jul. 10, 2024	Jan. 04, 2025	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2082394	1Ghz-18Ghz	Jan. 05, 2024	Jul. 10, 2024	Jan. 04, 2025	Radiation (03CH03-KS)
Amplifier	Keysight	83017A	MY53270319	1GHz~26.5GHz	Oct. 10, 2023	Jul. 10, 2024	Oct. 09, 2024	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jul. 10, 2024	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jul. 10, 2024	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jul. 10, 2024	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 18, 2024	May 11, 2024	Apr. 17, 2025	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 11, 2023	May 11, 2024	Oct. 10, 2024	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Apr. 18, 2024	May 11, 2024	Apr. 17, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 11, 2023	May 11, 2024	Oct. 10, 2024	Conduction (CO01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.46 dB
Conducted Power Spectral Density	±0.88 dB
Frequency	±0.4 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.84 dB
---	---------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.08 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.18 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.22 dB
---	---------

----- THE END -----



Appendix A. Conducted Test Results



Ambient Condition: 25 °C, 45 %RH

Test Date: 2024/7/8~2025/2/14

Test Engineer: Jacob Zhang


DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.66	2401.64	2402.31	0.5	PASS
		2440	0.66	2439.64	2440.30	0.5	PASS
		2480	0.65	2479.65	2480.30	0.5	PASS
BLE_2M	Ant1	2402	1.12	2401.41	2402.53	0.5	PASS
		2440	1.12	2439.43	2440.55	0.5	PASS
		2478	1.10	2477.42	2478.53	0.5	PASS
		2480	1.11	2479.41	2480.52	0.5	PASS




Test Graphs






BLE_1M_Ant1_2480




BLE_2M_Ant1_2402







BLE_2M_Ant1_2440



BLE_2M_Ant1_2478








Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.087	2401.4286	2402.5155	---	---
		2440	1.083	2439.4326	2440.5155	---	---
		2480	1.083	2479.4366	2480.5195	---	---
BLE_2M	Ant1	2402	2.062	2400.9491	2403.0110	---	---
		2440	2.062	2438.9610	2441.0230	---	---
		2478	2.058	2476.9530	2479.0110	---	---
		2480	2.058	2478.9491	2481.0070	---	---




Test Graphs








BLE_1M_Ant1_2480



BLE_2M_Ant1_2402







Maximum conducted output power

Test Result Peak

TestMode	Antenna	CH.	Peak Conducted Power (dBm)	Conducted Power Limit	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit	Power setting	Pass/Fail
BLE1M	Ant1	0	16.79	30.00	3.96	20.75	36.00	13	Pass
		19	16.83	30.00	3.96	20.79	36.00	13	Pass
		39	13.85	30.00	3.96	17.81	36.00	12	Pass
BLE2M	Ant1	0	19.74	30.00	3.96	23.70	36.00	14	Pass
		19	19.49	30.00	3.96	23.45	36.00	14	Pass
		38	16.60	30.00	3.96	20.56	36.00	13	Pass
		39	14.12	30.00	3.96	18.08	36.00	12	Pass
BLE 125K	Ant1	0	16.69	30.00	3.96	20.65	36.00	13	Pass
		19	16.68	30.00	3.96	20.64	36.00	13	Pass
		39	13.77	30.00	3.96	17.73	36.00	12	Pass
BLE 500K	Ant1	0	16.75	30.00	3.96	20.71	36.00	13	Pass
		19	16.71	30.00	3.96	20.67	36.00	13	Pass
		39	13.80	30.00	3.96	17.76	36.00	12	Pass

Test Result Average

TestMode	Antenna	CH.	Duty Factor (dB)	Average Conducted Power (dBm)
BLE 1M	Ant1	0	0.20	15.84
		19	0.20	15.91
		39	0.20	13.12
BLE 2M	Ant1	0	0.45	18.64
		19	0.45	18.44
		38	0.45	15.56
		39	0.45	12.90
BLE 125K	Ant1	0	0.03	15.75
		19	0.03	15.72
		39	0.03	13.04
BLE 500K	Ant1	0	0.44	15.86
		19	0.44	15.79
		39	0.44	13.11




Maximum power spectral density


Test Result


TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	6.33	≤8.00	PASS
		2440	3.18	≤8.00	PASS
		2480	0.46	≤8.00	PASS
BLE_2M	Ant1	2402	3.67	≤8.00	PASS
		2440	3.45	≤8.00	PASS
		2478	0.7	≤8.00	PASS
		2480	-2.13	≤8.00	PASS




Test Graphs











Reference level measurement

Test Result


TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm/100KHz]
BLE_1M	Ant1	2402	2401.98	19.52
		2440	2439.99	16.42
		2480	2479.98	13.85
BLE_2M	Ant1	2402	2401.98	19.36
		2440	2439.99	19.15
		2478	2477.99	16.48
		2480	2479.98	13.69




Test Graphs












Band edge measurements


Test Result


TestMode	Antenna	ChName	Freq(M Hz)	RefLevel[dBm/1 00KHz]	Result[dBm/100 KHz]	Limit[dBm/100K Hz]	Verdict
BLE_1M	Ant1	Low	2402	19.52	-30.57	≤-0.48	PASS
		High	2480	13.85	-33.12	≤-6.15	PASS
BLE_2M	Ant1	Low	2402	19.36	-28.57	≤-0.64	PASS
		High	2478	16.48	-35.93	≤-3.52	PASS
			2480	13.69	-32.32	≤-6.31	PASS



Test Graphs










Conducted Spurious Emission


Test Result


TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm/100KHz]	Result [dBm/100KHz]	Limit [dBm/100KHz]	Verdict
BLE_1M	Ant1	2402	30~1000	19.52	-40.36	≤-0.48	PASS
			1000~26500	19.52	-32.68	≤-0.48	PASS
		2440	30~1000	16.42	-40.52	≤-3.58	PASS
			1000~26500	16.42	-32.61	≤-3.58	PASS
		2480	30~1000	13.85	-40.56	≤-6.15	PASS
			1000~26500	13.85	-32.41	≤-6.15	PASS
BLE_2M	Ant1	2402	30~1000	19.36	-39.71	≤-0.64	PASS
			1000~26500	19.36	-33.47	≤-0.64	PASS
		2440	30~1000	19.15	-56.09	≤-0.85	PASS
			1000~26500	19.15	-37.91	≤-0.85	PASS
		2478	30~1000	16.48	-56.04	≤-3.52	PASS
			1000~26500	16.48	-43.03	≤-3.52	PASS
		2480	30~1000	13.69	-40.5	≤-6.31	PASS
			1000~26500	13.69	-33.69	≤-6.31	PASS





Test Graphs


















BLE_2M_Ant1_2480_30~1000




BLE_2M_Ant1_2480_1000~26500





Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-L 2023 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.171	44.96	-19.94	64.90	34.50	0.04	10.42	QP
2	0.171	27.26	-27.64	54.90	16.80	0.04	10.42	Average
3 *	0.191	50.04	-13.94	63.98	39.60	0.03	10.41	QP
4	0.191	35.64	-18.34	53.98	25.20	0.03	10.41	Average
5	0.244	44.61	-17.34	61.95	34.20	0.04	10.37	QP
6	0.244	30.71	-21.24	51.95	20.30	0.04	10.37	Average
7	3.584	36.77	-19.23	56.00	26.80	-0.10	10.07	QP
8	3.584	25.17	-20.83	46.00	15.20	-0.10	10.07	Average
9	3.779	38.76	-17.24	56.00	28.80	-0.11	10.07	QP
10	3.779	26.56	-19.44	46.00	16.60	-0.11	10.07	Average
11	5.774	38.14	-21.86	60.00	28.20	-0.14	10.08	QP
12	5.774	23.14	-26.86	50.00	13.20	-0.14	10.08	Average



Test Engineer :	Amos	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-N 2023 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.181	51.06	-13.40	64.46	40.60	0.05	10.41	QP
2	0.181	32.76	-21.70	54.46	22.30	0.05	10.41	Average
3	0.198	50.06	-13.65	63.71	39.60	0.05	10.41	QP
4	0.198	33.36	-20.35	53.71	22.90	0.05	10.41	Average
5	0.244	43.58	-18.37	61.95	33.20	0.01	10.37	QP
6	0.244	27.58	-24.37	51.95	17.20	0.01	10.37	Average
7	3.759	37.14	-18.86	56.00	27.20	-0.13	10.07	QP
8	3.759	26.54	-19.46	46.00	16.60	-0.13	10.07	Average
9	4.027	38.13	-17.87	56.00	28.20	-0.13	10.06	QP
10	4.027	27.23	-18.77	46.00	17.30	-0.13	10.06	Average
11	5.683	39.16	-20.84	60.00	29.20	-0.12	10.08	QP
12	5.683	23.76	-26.24	50.00	13.80	-0.12	10.08	Average

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Chris	Relative Humidity :	41 ~ 42 %
		Temperature :	22 ~ 23 °C





Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	Bluetooth-LE_GSFK	00	2402	1Mbps	-	-
Mode 2	2400-2483.5	1	Bluetooth-LE_GSFK	19	2440	1Mbps	-	-
Mode 3	2400-2483.5	1	Bluetooth-LE_GSFK	39	2480	1Mbps	-	-
Mode 4	2400-2483.5	1	Bluetooth-LE_GSFK	00	2402	2Mbps	-	-
Mode 5	2400-2483.5	1	Bluetooth-LE_GSFK	19	2440	2Mbps	-	-
Mode 6	2400-2483.5	1	Bluetooth-LE_GSFK	39	2480	2Mbps	-	-
Mode 17	2400-2483.5	1	Bluetooth-LE_GSFK	38	2478	2Mbps	-	-





Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth-LE_GSFK	00	2389.95	43.82	54.00	-10.18	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE_GSFK	00	4003.50	49.50	54.00	-4.50	V	Average	Pass	Harmonic
2	Bluetooth-LE_GSFK	19	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE_GSFK	19	4880.00	50.15	54.00	-3.85	V	AVERAGE	Pass	Harmonic
3	Bluetooth-LE_GSFK	39	2483.50	52.87	54.00	-1.13	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE_GSFK	39	4960.00	50.59	54.00	-3.41	H	AVERAGE	Pass	Harmonic
4	Bluetooth-LE_GSFK	00	2389.95	44.79	54.00	-9.21	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE_GSFK	00	4804.00	47.80	54.00	-6.20	H	AVERAGE	Pass	Harmonic
5	Bluetooth-LE_GSFK	19	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE_GSFK	19	4880.00	50.73	54.00	-3.27	V	AVERAGE	Pass	Harmonic
6	Bluetooth-LE_GSFK	39	2483.50	52.33	54.00	-1.67	H	AVERAGE	Pass	Band Edge
6	Bluetooth-LE_GSFK	39	4960.00	49.07	54.00	-4.93	H	AVERAGE	Pass	Harmonic
17	Bluetooth-LE_GSFK	38	2483.50	51.38	54.00	-2.62	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE_GSFK	38	4956.00	46.69	54.00	-7.31	V	AVERAGE	Pass	Harmonic





Mode	1																																																							
	Band Edge																																																							
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																							
ANT	1																																																							
Pol.	Horizontal						Fundamental																																																	
Peak																																																								
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.78</td><td>52.80</td><td>74.00</td><td>-21.20</td><td>44.68</td><td>31.82</td><td>7.16</td><td>36.86</td><td>6.00</td><td>323</td><td>154</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2388.78	52.80	74.00	-21.20	44.68	31.82	7.16	36.86	6.00	323	154	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2388.78	52.80	74.00	-21.20	44.68	31.82	7.16	36.86	6.00	323	154	PEAK																																												
																																																								
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>110.92</td><td>-----</td><td>-----</td><td>102.69</td><td>31.91</td><td>7.18</td><td>36.86</td><td>6.00</td><td>323</td><td>154</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	110.92	-----	-----	102.69	31.91	7.18	36.86	6.00	323	154	PEAK	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2402.00	110.92	-----	-----	102.69	31.91	7.18	36.86	6.00	323	154	PEAK																																												
Avg																																																								
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>42.22</td><td>54.00</td><td>-11.78</td><td>34.09</td><td>31.83</td><td>7.16</td><td>36.86</td><td>6.00</td><td>323</td><td>154</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.95	42.22	54.00	-11.78	34.09	31.83	7.16	36.86	6.00	323	154	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2389.95	42.22	54.00	-11.78	34.09	31.83	7.16	36.86	6.00	323	154	AVERAGE																																												
																																																								
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>109.45</td><td>-----</td><td>-----</td><td>101.22</td><td>31.91</td><td>7.18</td><td>36.86</td><td>6.00</td><td>323</td><td>154</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	109.45	-----	-----	101.22	31.91	7.18	36.86	6.00	323	154	AVERAGE	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2402.00	109.45	-----	-----	101.22	31.91	7.18	36.86	6.00	323	154	AVERAGE																																												





Mode	1																																																																																																														
	Band Edge																																																																																																														
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																																														
ANT	1																																																																																																														
Pol.	Vertical						Fundamental																																																																																																								
Peak																																																																																																															
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.78</td><td>55.42</td><td>74.00</td><td>-18.58</td><td>47.30</td><td>31.82</td><td>7.16</td><td>36.86</td><td>6.00</td><td>100</td><td>125</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2388.78	55.42	74.00	-18.58	47.30	31.82	7.16	36.86	6.00	100	125	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>112.98</td><td>-----</td><td>-----</td><td>104.75</td><td>31.91</td><td>7.18</td><td>36.86</td><td>6.00</td><td>100</td><td>125</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	112.98	-----	-----	104.75	31.91	7.18	36.86	6.00	100	125
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2388.78	55.42	74.00	-18.58	47.30	31.82	7.16	36.86	6.00	100	125	PEAK																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2402.00	112.98	-----	-----	104.75	31.91	7.18	36.86	6.00	100	125	PEAK																																																																																																			
Avg																																																																																																															
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>43.82</td><td>54.00</td><td>-10.18</td><td>35.69</td><td>31.83</td><td>7.16</td><td>36.86</td><td>6.00</td><td>100</td><td>125</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.95	43.82	54.00	-10.18	35.69	31.83	7.16	36.86	6.00	100	125	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>111.53</td><td>-----</td><td>-----</td><td>103.30</td><td>31.91</td><td>7.18</td><td>36.86</td><td>6.00</td><td>100</td><td>125</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	111.53	-----	-----	103.30	31.91	7.18	36.86	6.00	100	125
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2389.95	43.82	54.00	-10.18	35.69	31.83	7.16	36.86	6.00	100	125	AVERAGE																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2402.00	111.53	-----	-----	103.30	31.91	7.18	36.86	6.00	100	125	AVERAGE																																																																																																			







Mode	1																																																																																																																																																																																																																																																														
	Harmonic																																																																																																																																																																																																																																																														
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																																																																																																																																																																																														
ANT	1																																																																																																																																																																																																																																																														
Pol.	Horizontal						Vertical																																																																																																																																																																																																																																																								
Peak Avg																																																																																																																																																																																																																																																															
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3202.50</td><td>43.28</td><td>90.20</td><td>-46.92</td><td>64.95</td><td>33.19</td><td>8.32</td><td>63.18</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4003.50</td><td>49.80</td><td>74.00</td><td>-24.20</td><td>70.77</td><td>33.39</td><td>9.32</td><td>63.68</td><td>0.00</td><td>309</td><td>110</td><td>Peak</td></tr><tr><td>3</td><td>4003.50</td><td>45.46</td><td>54.00</td><td>-8.54</td><td>66.43</td><td>33.39</td><td>9.32</td><td>63.68</td><td>0.00</td><td>309</td><td>110</td><td>Average</td></tr><tr><td>4</td><td>4804.00</td><td>52.27</td><td>74.00</td><td>-21.73</td><td>71.39</td><td>34.09</td><td>10.27</td><td>63.48</td><td>0.00</td><td>101</td><td>292</td><td>PEAK</td></tr><tr><td>5</td><td>4804.00</td><td>48.69</td><td>54.00</td><td>-5.31</td><td>67.81</td><td>34.09</td><td>10.27</td><td>63.48</td><td>0.00</td><td>101</td><td>292</td><td>AVERAGE</td></tr><tr><td>6</td><td>7207.50</td><td>55.70</td><td>90.20</td><td>-34.50</td><td>71.10</td><td>35.60</td><td>12.61</td><td>63.61</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>7</td><td>9607.50</td><td>48.35</td><td>90.20</td><td>-41.85</td><td>59.02</td><td>36.72</td><td>14.78</td><td>62.17</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3202.50	43.28	90.20	-46.92	64.95	33.19	8.32	63.18	0.00	--	--	Peak	2	4003.50	49.80	74.00	-24.20	70.77	33.39	9.32	63.68	0.00	309	110	Peak	3	4003.50	45.46	54.00	-8.54	66.43	33.39	9.32	63.68	0.00	309	110	Average	4	4804.00	52.27	74.00	-21.73	71.39	34.09	10.27	63.48	0.00	101	292	PEAK	5	4804.00	48.69	54.00	-5.31	67.81	34.09	10.27	63.48	0.00	101	292	AVERAGE	6	7207.50	55.70	90.20	-34.50	71.10	35.60	12.61	63.61	0.00	--	--	Peak	7	9607.50	48.35	90.20	-41.85	59.02	36.72	14.78	62.17	0.00	--	--	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3202.50</td><td>46.03</td><td>91.89</td><td>-45.86</td><td>67.70</td><td>33.19</td><td>8.32</td><td>63.18</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4003.50</td><td>52.82</td><td>74.00</td><td>-21.18</td><td>73.79</td><td>33.39</td><td>9.32</td><td>63.68</td><td>0.00</td><td>312</td><td>187</td><td>Peak</td></tr><tr><td>3</td><td>4003.50</td><td>49.50</td><td>54.00</td><td>-4.50</td><td>70.47</td><td>33.39</td><td>9.32</td><td>63.68</td><td>0.00</td><td>312</td><td>187</td><td>Average</td></tr><tr><td>4</td><td>4804.00</td><td>49.47</td><td>74.00</td><td>-24.53</td><td>68.59</td><td>34.09</td><td>10.27</td><td>63.48</td><td>0.00</td><td>300</td><td>57</td><td>PEAK</td></tr><tr><td>5</td><td>4804.00</td><td>45.14</td><td>54.00</td><td>-8.86</td><td>64.26</td><td>34.09</td><td>10.27</td><td>63.48</td><td>0.00</td><td>300</td><td>57</td><td>AVERAGE</td></tr><tr><td>6</td><td>7206.00</td><td>58.09</td><td>91.89</td><td>-33.80</td><td>73.49</td><td>35.60</td><td>12.61</td><td>63.61</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>7</td><td>9607.50</td><td>48.75</td><td>91.89</td><td>-43.14</td><td>59.42</td><td>36.72</td><td>14.78</td><td>62.17</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3202.50	46.03	91.89	-45.86	67.70	33.19	8.32	63.18	0.00	--	--	Peak	2	4003.50	52.82	74.00	-21.18	73.79	33.39	9.32	63.68	0.00	312	187	Peak	3	4003.50	49.50	54.00	-4.50	70.47	33.39	9.32	63.68	0.00	312	187	Average	4	4804.00	49.47	74.00	-24.53	68.59	34.09	10.27	63.48	0.00	300	57	PEAK	5	4804.00	45.14	54.00	-8.86	64.26	34.09	10.27	63.48	0.00	300	57	AVERAGE	6	7206.00	58.09	91.89	-33.80	73.49	35.60	12.61	63.61	0.00	--	--	Peak	7	9607.50	48.75	91.89	-43.14	59.42	36.72	14.78	62.17	0.00	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																					
1	3202.50	43.28	90.20	-46.92	64.95	33.19	8.32	63.18	0.00	--	--	Peak																																																																																																																																																																																																																																																			
2	4003.50	49.80	74.00	-24.20	70.77	33.39	9.32	63.68	0.00	309	110	Peak																																																																																																																																																																																																																																																			
3	4003.50	45.46	54.00	-8.54	66.43	33.39	9.32	63.68	0.00	309	110	Average																																																																																																																																																																																																																																																			
4	4804.00	52.27	74.00	-21.73	71.39	34.09	10.27	63.48	0.00	101	292	PEAK																																																																																																																																																																																																																																																			
5	4804.00	48.69	54.00	-5.31	67.81	34.09	10.27	63.48	0.00	101	292	AVERAGE																																																																																																																																																																																																																																																			
6	7207.50	55.70	90.20	-34.50	71.10	35.60	12.61	63.61	0.00	--	--	Peak																																																																																																																																																																																																																																																			
7	9607.50	48.35	90.20	-41.85	59.02	36.72	14.78	62.17	0.00	--	--	Peak																																																																																																																																																																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																					
1	3202.50	46.03	91.89	-45.86	67.70	33.19	8.32	63.18	0.00	--	--	Peak																																																																																																																																																																																																																																																			
2	4003.50	52.82	74.00	-21.18	73.79	33.39	9.32	63.68	0.00	312	187	Peak																																																																																																																																																																																																																																																			
3	4003.50	49.50	54.00	-4.50	70.47	33.39	9.32	63.68	0.00	312	187	Average																																																																																																																																																																																																																																																			
4	4804.00	49.47	74.00	-24.53	68.59	34.09	10.27	63.48	0.00	300	57	PEAK																																																																																																																																																																																																																																																			
5	4804.00	45.14	54.00	-8.86	64.26	34.09	10.27	63.48	0.00	300	57	AVERAGE																																																																																																																																																																																																																																																			
6	7206.00	58.09	91.89	-33.80	73.49	35.60	12.61	63.61	0.00	--	--	Peak																																																																																																																																																																																																																																																			
7	9607.50	48.75	91.89	-43.14	59.42	36.72	14.78	62.17	0.00	--	--	Peak																																																																																																																																																																																																																																																			







Mode	2																																																																																																																																																																																																																																																																																																							
	Harmonic																																																																																																																																																																																																																																																																																																							
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																																																																																																																																																																																																																																																																							
ANT	1																																																																																																																																																																																																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																																																																																																																																																																																																	
Peak Avg																																																																																																																																																																																																																																																																																																								
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th colspan="2">Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>3253.50</td><td>42.01</td><td>87.77</td><td>-45.76</td><td>63.97</td><td>32.88</td><td>8.42</td><td>63.26</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4066.50</td><td>48.61</td><td>74.00</td><td>-25.39</td><td>69.57</td><td>33.27</td><td>9.41</td><td>63.64</td><td>0.00</td><td>100</td><td>114</td><td>Peak</td></tr><tr><td>3</td><td>4066.50</td><td>44.74</td><td>54.00</td><td>-9.26</td><td>65.70</td><td>33.27</td><td>9.41</td><td>63.64</td><td>0.00</td><td>100</td><td>114</td><td>Average</td></tr><tr><td>4</td><td>4880.00</td><td>51.79</td><td>74.00</td><td>-22.21</td><td>70.98</td><td>33.94</td><td>10.35</td><td>63.48</td><td>0.00</td><td>300</td><td>318</td><td>PEAK</td></tr><tr><td>5</td><td>4880.00</td><td>48.13</td><td>54.00</td><td>-5.87</td><td>67.32</td><td>33.94</td><td>10.35</td><td>63.48</td><td>0.00</td><td>300</td><td>318</td><td>AVERAGE</td></tr><tr><td>6</td><td>7320.00</td><td>50.36</td><td>74.00</td><td>-23.64</td><td>65.65</td><td>35.60</td><td>12.79</td><td>63.68</td><td>0.00</td><td>100</td><td>233</td><td>PEAK</td></tr><tr><td>7</td><td>7320.00</td><td>44.92</td><td>54.00</td><td>-9.08</td><td>60.21</td><td>35.60</td><td>12.79</td><td>63.68</td><td>0.00</td><td>100</td><td>233</td><td>AVERAGE</td></tr><tr><td>8</td><td>9760.50</td><td>48.11</td><td>87.77</td><td>-39.66</td><td>58.50</td><td>36.96</td><td>14.87</td><td>62.22</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>								Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq		Level	Line Margin	Level	Factor	Loss Factor	Factor	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	3253.50	42.01	87.77	-45.76	63.97	32.88	8.42	63.26	0.00	--	--	Peak	2	4066.50	48.61	74.00	-25.39	69.57	33.27	9.41	63.64	0.00	100	114	Peak	3	4066.50	44.74	54.00	-9.26	65.70	33.27	9.41	63.64	0.00	100	114	Average	4	4880.00	51.79	74.00	-22.21	70.98	33.94	10.35	63.48	0.00	300	318	PEAK	5	4880.00	48.13	54.00	-5.87	67.32	33.94	10.35	63.48	0.00	300	318	AVERAGE	6	7320.00	50.36	74.00	-23.64	65.65	35.60	12.79	63.68	0.00	100	233	PEAK	7	7320.00	44.92	54.00	-9.08	60.21	35.60	12.79	63.68	0.00	100	233	AVERAGE	8	9760.50	48.11	87.77	-39.66	58.50	36.96	14.87	62.22	0.00	--	--	Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th colspan="2">Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>3253.50</td><td>46.84</td><td>91.86</td><td>-45.02</td><td>68.00</td><td>32.88</td><td>8.42</td><td>63.26</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4066.50</td><td>49.26</td><td>74.00</td><td>-24.74</td><td>70.22</td><td>33.27</td><td>9.41</td><td>63.64</td><td>0.00</td><td>300</td><td>182</td><td>Peak</td></tr><tr><td>3</td><td>4066.50</td><td>45.05</td><td>54.00</td><td>-8.95</td><td>66.01</td><td>33.27</td><td>9.41</td><td>63.64</td><td>0.00</td><td>300</td><td>182</td><td>Average</td></tr><tr><td>4</td><td>4880.00</td><td>53.89</td><td>74.00</td><td>-20.11</td><td>73.08</td><td>33.94</td><td>10.35</td><td>63.48</td><td>0.00</td><td>283</td><td>45</td><td>PEAK</td></tr><tr><td>5</td><td>4880.00</td><td>50.15</td><td>54.00</td><td>-3.85</td><td>69.34</td><td>33.94</td><td>10.35</td><td>63.48</td><td>0.00</td><td>283</td><td>45</td><td>AVERAGE</td></tr><tr><td>6</td><td>7320.00</td><td>50.90</td><td>74.00</td><td>-23.10</td><td>66.19</td><td>35.60</td><td>12.79</td><td>63.68</td><td>0.00</td><td>112</td><td>307</td><td>PEAK</td></tr><tr><td>7</td><td>7320.00</td><td>45.46</td><td>54.00</td><td>-8.54</td><td>60.75</td><td>35.60</td><td>12.79</td><td>63.68</td><td>0.00</td><td>112</td><td>307</td><td>AVERAGE</td></tr><tr><td>8</td><td>9760.50</td><td>46.82</td><td>91.86</td><td>-45.04</td><td>57.21</td><td>36.96</td><td>14.87</td><td>62.22</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>								Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq		Level	Line Margin	Level	Factor	Loss Factor	Factor	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	3253.50	46.84	91.86	-45.02	68.00	32.88	8.42	63.26	0.00	--	--	Peak	2	4066.50	49.26	74.00	-24.74	70.22	33.27	9.41	63.64	0.00	300	182	Peak	3	4066.50	45.05	54.00	-8.95	66.01	33.27	9.41	63.64	0.00	300	182	Average	4	4880.00	53.89	74.00	-20.11	73.08	33.94	10.35	63.48	0.00	283	45	PEAK	5	4880.00	50.15	54.00	-3.85	69.34	33.94	10.35	63.48	0.00	283	45	AVERAGE	6	7320.00	50.90	74.00	-23.10	66.19	35.60	12.79	63.68	0.00	112	307	PEAK	7	7320.00	45.46	54.00	-8.54	60.75	35.60	12.79	63.68	0.00	112	307	AVERAGE	8	9760.50	46.82	91.86	-45.04	57.21	36.96	14.87	62.22	0.00	--	--	Peak
			Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																																																																											
Freq		Level	Line Margin	Level	Factor	Loss Factor	Factor	Factor	Factor																																																																																																																																																																																																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																																																													
1	3253.50	42.01	87.77	-45.76	63.97	32.88	8.42	63.26	0.00	--	--	Peak																																																																																																																																																																																																																																																																																												
2	4066.50	48.61	74.00	-25.39	69.57	33.27	9.41	63.64	0.00	100	114	Peak																																																																																																																																																																																																																																																																																												
3	4066.50	44.74	54.00	-9.26	65.70	33.27	9.41	63.64	0.00	100	114	Average																																																																																																																																																																																																																																																																																												
4	4880.00	51.79	74.00	-22.21	70.98	33.94	10.35	63.48	0.00	300	318	PEAK																																																																																																																																																																																																																																																																																												
5	4880.00	48.13	54.00	-5.87	67.32	33.94	10.35	63.48	0.00	300	318	AVERAGE																																																																																																																																																																																																																																																																																												
6	7320.00	50.36	74.00	-23.64	65.65	35.60	12.79	63.68	0.00	100	233	PEAK																																																																																																																																																																																																																																																																																												
7	7320.00	44.92	54.00	-9.08	60.21	35.60	12.79	63.68	0.00	100	233	AVERAGE																																																																																																																																																																																																																																																																																												
8	9760.50	48.11	87.77	-39.66	58.50	36.96	14.87	62.22	0.00	--	--	Peak																																																																																																																																																																																																																																																																																												
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																																																																												
Freq		Level	Line Margin	Level	Factor	Loss Factor	Factor	Factor	Factor																																																																																																																																																																																																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																																																													
1	3253.50	46.84	91.86	-45.02	68.00	32.88	8.42	63.26	0.00	--	--	Peak																																																																																																																																																																																																																																																																																												
2	4066.50	49.26	74.00	-24.74	70.22	33.27	9.41	63.64	0.00	300	182	Peak																																																																																																																																																																																																																																																																																												
3	4066.50	45.05	54.00	-8.95	66.01	33.27	9.41	63.64	0.00	300	182	Average																																																																																																																																																																																																																																																																																												
4	4880.00	53.89	74.00	-20.11	73.08	33.94	10.35	63.48	0.00	283	45	PEAK																																																																																																																																																																																																																																																																																												
5	4880.00	50.15	54.00	-3.85	69.34	33.94	10.35	63.48	0.00	283	45	AVERAGE																																																																																																																																																																																																																																																																																												
6	7320.00	50.90	74.00	-23.10	66.19	35.60	12.79	63.68	0.00	112	307	PEAK																																																																																																																																																																																																																																																																																												
7	7320.00	45.46	54.00	-8.54	60.75	35.60	12.79	63.68	0.00	112	307	AVERAGE																																																																																																																																																																																																																																																																																												
8	9760.50	46.82	91.86	-45.04	57.21	36.96	14.87	62.22	0.00	--	--	Peak																																																																																																																																																																																																																																																																																												



Mode	3																																																						
	Band Edge																																																						
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																						
ANT	1																																																						
Pol.	Horizontal						Fundamental																																																
Peak																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>66.66</td><td>74.00</td><td>-7.34</td><td>57.95</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>229</td><td>175</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	66.66	74.00	-7.34	57.95	32.23	7.33	36.85	6.00	229	175
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2483.50	66.66	74.00	-7.34	57.95	32.23	7.33	36.85	6.00	229	175	PEAK																																											
Peak																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>107.70</td><td>-----</td><td>-----</td><td>99.01</td><td>32.22</td><td>7.32</td><td>36.85</td><td>6.00</td><td>229</td><td>175</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	107.70	-----	-----	99.01	32.22	7.32	36.85	6.00	229	175
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2480.00	107.70	-----	-----	99.01	32.22	7.32	36.85	6.00	229	175	PEAK																																											
Avg																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>51.39</td><td>54.00</td><td>-2.61</td><td>42.68</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>229</td><td>175</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	51.39	54.00	-2.61	42.68	32.23	7.33	36.85	6.00	229	175
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2483.50	51.39	54.00	-2.61	42.68	32.23	7.33	36.85	6.00	229	175	AVERAGE																																											
Avg																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>106.30</td><td>-----</td><td>-----</td><td>97.69</td><td>32.22</td><td>7.32</td><td>36.85</td><td>6.00</td><td>229</td><td>175</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	106.30	-----	-----	97.69	32.22	7.32	36.85	6.00	229	175
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2480.00	106.30	-----	-----	97.69	32.22	7.32	36.85	6.00	229	175	AVERAGE																																											







Mode	3																																																																																																														
	Band Edge																																																																																																														
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																														
ANT	1																																																																																																														
Pol.	Vertical						Fundamental																																																																																																								
Peak																																																																																																															
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.56</td><td>68.37</td><td>74.00</td><td>-5.63</td><td>59.66</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>109</td><td>124</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.56	68.37	74.00	-5.63	59.66	32.23	7.33	36.85	6.00	109	124	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>109.30</td><td>-----</td><td>-----</td><td>100.61</td><td>32.22</td><td>7.32</td><td>36.85</td><td>6.00</td><td>109</td><td>124</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	109.30	-----	-----	100.61	32.22	7.32	36.85	6.00	109	124
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2483.56	68.37	74.00	-5.63	59.66	32.23	7.33	36.85	6.00	109	124	PEAK																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2480.00	109.30	-----	-----	100.61	32.22	7.32	36.85	6.00	109	124	PEAK																																																																																																			
Avg																																																																																																															
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>52.87</td><td>54.00</td><td>-1.13</td><td>44.16</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>109</td><td>124</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	52.87	54.00	-1.13	44.16	32.23	7.33	36.85	6.00	109	124	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>107.95</td><td>-----</td><td>-----</td><td>99.26</td><td>32.22</td><td>7.32</td><td>36.85</td><td>6.00</td><td>109</td><td>124</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	107.95	-----	-----	99.26	32.22	7.32	36.85	6.00	109	124
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2483.50	52.87	54.00	-1.13	44.16	32.23	7.33	36.85	6.00	109	124	AVERAGE																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2480.00	107.95	-----	-----	99.26	32.22	7.32	36.85	6.00	109	124	AVERAGE																																																																																																			







		3																																																																																																																																																																																																																																																												
Mode	Harmonic																																																																																																																																																																																																																																																													
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																																																																																																																																																																													
ANT	1																																																																																																																																																																																																																																																													
Pol.	Horizontal						Vertical																																																																																																																																																																																																																																																							
Peak Avg																																																																																																																																																																																																																																																														
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3306.00</td><td>41.53</td><td>86.03</td><td>-44.50</td><td>63.75</td><td>32.60</td><td>8.52</td><td>63.34</td><td>0.00</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4131.68</td><td>43.32</td><td>74.00</td><td>-30.68</td><td>64.12</td><td>33.30</td><td>9.50</td><td>63.60</td><td>0.00</td><td>--</td><td>PEAK</td></tr><tr><td>3</td><td>4960.00</td><td>53.59</td><td>74.00</td><td>-20.41</td><td>72.67</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>100</td><td>267 PEAK</td></tr><tr><td>4</td><td>4960.00</td><td>50.59</td><td>54.00</td><td>-3.41</td><td>69.67</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>100</td><td>267 AVERAGE</td></tr><tr><td>5</td><td>7440.00</td><td>51.17</td><td>74.00</td><td>-22.83</td><td>66.35</td><td>35.64</td><td>12.93</td><td>63.75</td><td>0.00</td><td>108</td><td>97 PEAK</td></tr><tr><td>6</td><td>7440.00</td><td>46.09</td><td>54.00</td><td>-7.91</td><td>61.27</td><td>35.64</td><td>12.93</td><td>63.75</td><td>0.00</td><td>108</td><td>97 AVERAGE</td></tr><tr><td>7</td><td>9921.00</td><td>46.06</td><td>86.03</td><td>-39.97</td><td>56.26</td><td>37.10</td><td>14.98</td><td>62.28</td><td>0.00</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3306.00	41.53	86.03	-44.50	63.75	32.60	8.52	63.34	0.00	--	Peak	2	4131.68	43.32	74.00	-30.68	64.12	33.30	9.50	63.60	0.00	--	PEAK	3	4960.00	53.59	74.00	-20.41	72.67	33.96	10.44	63.48	0.00	100	267 PEAK	4	4960.00	50.59	54.00	-3.41	69.67	33.96	10.44	63.48	0.00	100	267 AVERAGE	5	7440.00	51.17	74.00	-22.83	66.35	35.64	12.93	63.75	0.00	108	97 PEAK	6	7440.00	46.09	54.00	-7.91	61.27	35.64	12.93	63.75	0.00	108	97 AVERAGE	7	9921.00	46.06	86.03	-39.97	56.26	37.10	14.98	62.28	0.00	--	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3307.50</td><td>40.17</td><td>87.68</td><td>-47.51</td><td>62.38</td><td>32.60</td><td>8.53</td><td>63.34</td><td>0.00</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4134.00</td><td>48.25</td><td>74.00</td><td>-25.75</td><td>69.05</td><td>33.30</td><td>9.50</td><td>63.60</td><td>0.00</td><td>103</td><td>116 Peak</td></tr><tr><td>3</td><td>4134.00</td><td>44.40</td><td>54.00</td><td>-9.60</td><td>65.20</td><td>33.30</td><td>9.50</td><td>63.60</td><td>0.00</td><td>103</td><td>116 Average</td></tr><tr><td>4</td><td>4960.50</td><td>50.48</td><td>74.00</td><td>-23.52</td><td>69.56</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>100</td><td>264 Peak</td></tr><tr><td>5</td><td>4960.50</td><td>45.02</td><td>54.00</td><td>-8.98</td><td>64.10</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>100</td><td>264 Average</td></tr><tr><td>6</td><td>7440.00</td><td>52.51</td><td>74.00</td><td>-21.49</td><td>67.69</td><td>35.64</td><td>12.93</td><td>63.75</td><td>0.00</td><td>109</td><td>155 PEAK</td></tr><tr><td>7</td><td>7440.00</td><td>47.73</td><td>54.00</td><td>-6.27</td><td>62.91</td><td>35.64</td><td>12.93</td><td>63.75</td><td>0.00</td><td>109</td><td>155 AVERAGE</td></tr><tr><td>8</td><td>9919.50</td><td>44.27</td><td>87.68</td><td>-43.41</td><td>54.47</td><td>37.10</td><td>14.98</td><td>62.28</td><td>0.00</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3307.50	40.17	87.68	-47.51	62.38	32.60	8.53	63.34	0.00	--	Peak	2	4134.00	48.25	74.00	-25.75	69.05	33.30	9.50	63.60	0.00	103	116 Peak	3	4134.00	44.40	54.00	-9.60	65.20	33.30	9.50	63.60	0.00	103	116 Average	4	4960.50	50.48	74.00	-23.52	69.56	33.96	10.44	63.48	0.00	100	264 Peak	5	4960.50	45.02	54.00	-8.98	64.10	33.96	10.44	63.48	0.00	100	264 Average	6	7440.00	52.51	74.00	-21.49	67.69	35.64	12.93	63.75	0.00	109	155 PEAK	7	7440.00	47.73	54.00	-6.27	62.91	35.64	12.93	63.75	0.00	109	155 AVERAGE	8	9919.50	44.27	87.68	-43.41	54.47	37.10	14.98	62.28	0.00	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																				
1	3306.00	41.53	86.03	-44.50	63.75	32.60	8.52	63.34	0.00	--	Peak																																																																																																																																																																																																																																																			
2	4131.68	43.32	74.00	-30.68	64.12	33.30	9.50	63.60	0.00	--	PEAK																																																																																																																																																																																																																																																			
3	4960.00	53.59	74.00	-20.41	72.67	33.96	10.44	63.48	0.00	100	267 PEAK																																																																																																																																																																																																																																																			
4	4960.00	50.59	54.00	-3.41	69.67	33.96	10.44	63.48	0.00	100	267 AVERAGE																																																																																																																																																																																																																																																			
5	7440.00	51.17	74.00	-22.83	66.35	35.64	12.93	63.75	0.00	108	97 PEAK																																																																																																																																																																																																																																																			
6	7440.00	46.09	54.00	-7.91	61.27	35.64	12.93	63.75	0.00	108	97 AVERAGE																																																																																																																																																																																																																																																			
7	9921.00	46.06	86.03	-39.97	56.26	37.10	14.98	62.28	0.00	--	Peak																																																																																																																																																																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																				
1	3307.50	40.17	87.68	-47.51	62.38	32.60	8.53	63.34	0.00	--	Peak																																																																																																																																																																																																																																																			
2	4134.00	48.25	74.00	-25.75	69.05	33.30	9.50	63.60	0.00	103	116 Peak																																																																																																																																																																																																																																																			
3	4134.00	44.40	54.00	-9.60	65.20	33.30	9.50	63.60	0.00	103	116 Average																																																																																																																																																																																																																																																			
4	4960.50	50.48	74.00	-23.52	69.56	33.96	10.44	63.48	0.00	100	264 Peak																																																																																																																																																																																																																																																			
5	4960.50	45.02	54.00	-8.98	64.10	33.96	10.44	63.48	0.00	100	264 Average																																																																																																																																																																																																																																																			
6	7440.00	52.51	74.00	-21.49	67.69	35.64	12.93	63.75	0.00	109	155 PEAK																																																																																																																																																																																																																																																			
7	7440.00	47.73	54.00	-6.27	62.91	35.64	12.93	63.75	0.00	109	155 AVERAGE																																																																																																																																																																																																																																																			
8	9919.50	44.27	87.68	-43.41	54.47	37.10	14.98	62.28	0.00	--	Peak																																																																																																																																																																																																																																																			





Mode	4																																																						
	Band Edge																																																						
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																						
ANT	1																																																						
Pol.	Horizontal						Fundamental																																																
Peak																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.69</td><td>55.56</td><td>74.00</td><td>-18.44</td><td>47.43</td><td>31.83</td><td>7.16</td><td>36.86</td><td>6.00</td><td>322</td><td>153</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.69	55.56	74.00	-18.44	47.43	31.83	7.16	36.86	6.00	322	153
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2389.69	55.56	74.00	-18.44	47.43	31.83	7.16	36.86	6.00	322	153	PEAK																																											
Peak																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>113.93</td><td>-----</td><td>-----</td><td>105.70</td><td>31.91</td><td>7.18</td><td>36.86</td><td>6.00</td><td>322</td><td>153</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	113.93	-----	-----	105.70	31.91	7.18	36.86	6.00	322	153
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2402.00	113.93	-----	-----	105.70	31.91	7.18	36.86	6.00	322	153	PEAK																																											
Avg																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.82</td><td>43.74</td><td>54.00</td><td>-10.26</td><td>35.61</td><td>31.83</td><td>7.16</td><td>36.86</td><td>6.00</td><td>322</td><td>153</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.82	43.74	54.00	-10.26	35.61	31.83	7.16	36.86	6.00	322	153
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2389.82	43.74	54.00	-10.26	35.61	31.83	7.16	36.86	6.00	322	153	AVERAGE																																											
Avg																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>111.00</td><td>-----</td><td>-----</td><td>102.77</td><td>31.91</td><td>7.18</td><td>36.86</td><td>6.00</td><td>322</td><td>153</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	111.00	-----	-----	102.77	31.91	7.18	36.86	6.00	322	153
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2402.00	111.00	-----	-----	102.77	31.91	7.18	36.86	6.00	322	153	AVERAGE																																											



Mode	4																																																																																																														
	Band Edge																																																																																																														
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																																														
ANT	1																																																																																																														
Pol.	Vertical						Fundamental																																																																																																								
Peak																																																																																																															
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.56</td><td>55.81</td><td>74.00</td><td>-18.19</td><td>47.68</td><td>31.83</td><td>7.16</td><td>36.86</td><td>6.00</td><td>100</td><td>121</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.56	55.81	74.00	-18.19	47.68	31.83	7.16	36.86	6.00	100	121	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>115.93</td><td>-----</td><td>-----</td><td>107.70</td><td>31.91</td><td>7.18</td><td>36.86</td><td>6.00</td><td>100</td><td>121</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	115.93	-----	-----	107.70	31.91	7.18	36.86	6.00	100	121
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2389.56	55.81	74.00	-18.19	47.68	31.83	7.16	36.86	6.00	100	121	PEAK																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2402.00	115.93	-----	-----	107.70	31.91	7.18	36.86	6.00	100	121	PEAK																																																																																																			
Avg																																																																																																															
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>44.79</td><td>54.00</td><td>-9.21</td><td>36.66</td><td>31.83</td><td>7.16</td><td>36.86</td><td>6.00</td><td>100</td><td>121</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.95	44.79	54.00	-9.21	36.66	31.83	7.16	36.86	6.00	100	121	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>113.03</td><td>-----</td><td>-----</td><td>104.80</td><td>31.91</td><td>7.18</td><td>36.86</td><td>6.00</td><td>100</td><td>121</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	113.03	-----	-----	104.80	31.91	7.18	36.86	6.00	100	121
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2389.95	44.79	54.00	-9.21	36.66	31.83	7.16	36.86	6.00	100	121	AVERAGE																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2402.00	113.03	-----	-----	104.80	31.91	7.18	36.86	6.00	100	121	AVERAGE																																																																																																			







Mode	4																																																																																																																																																																																																																																												
	Harmonic																																																																																																																																																																																																																																												
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																																																																																																																																																																												
ANT	1																																																																																																																																																																																																																																												
Pol.	Horizontal						Vertical																																																																																																																																																																																																																																						
Peak Avg																																																																																																																																																																																																																																													
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>3202.50</td><td>41.48</td><td>93.24</td><td>-51.76</td><td>63.15</td><td>33.19</td><td>8.32</td><td>63.18</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4003.50</td><td>50.67</td><td>74.00</td><td>-23.33</td><td>71.64</td><td>33.39</td><td>9.32</td><td>63.68</td><td>0.00</td><td>126</td><td>257</td><td>Peak</td></tr><tr><td>3</td><td>4003.50</td><td>46.49</td><td>54.00</td><td>-7.51</td><td>67.46</td><td>33.39</td><td>9.32</td><td>63.68</td><td>0.00</td><td>126</td><td>257</td><td>Average</td></tr><tr><td>4</td><td>4804.00</td><td>53.15</td><td>74.00</td><td>-20.85</td><td>72.27</td><td>34.09</td><td>10.27</td><td>63.48</td><td>0.00</td><td>156</td><td>76</td><td>PEAK</td></tr><tr><td>5</td><td>4804.00</td><td>47.80</td><td>54.00</td><td>-6.20</td><td>66.92</td><td>34.09</td><td>10.27</td><td>63.48</td><td>0.00</td><td>156</td><td>76</td><td>AVERAGE</td></tr><tr><td>6</td><td>7206.00</td><td>49.12</td><td>93.24</td><td>-44.12</td><td>64.52</td><td>35.60</td><td>12.61</td><td>63.61</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>								Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	3202.50	41.48	93.24	-51.76	63.15	33.19	8.32	63.18	0.00	--	--	Peak	2	4003.50	50.67	74.00	-23.33	71.64	33.39	9.32	63.68	0.00	126	257	Peak	3	4003.50	46.49	54.00	-7.51	67.46	33.39	9.32	63.68	0.00	126	257	Average	4	4804.00	53.15	74.00	-20.85	72.27	34.09	10.27	63.48	0.00	156	76	PEAK	5	4804.00	47.80	54.00	-6.20	66.92	34.09	10.27	63.48	0.00	156	76	AVERAGE	6	7206.00	49.12	93.24	-44.12	64.52	35.60	12.61	63.61	0.00	--	--	Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>3202.50</td><td>43.49</td><td>95.42</td><td>-51.93</td><td>65.16</td><td>33.19</td><td>8.32</td><td>63.18</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4002.00</td><td>50.75</td><td>74.00</td><td>-23.25</td><td>71.71</td><td>33.40</td><td>9.32</td><td>63.68</td><td>0.00</td><td>300</td><td>182</td><td>Peak</td></tr><tr><td>3</td><td>4002.00</td><td>46.05</td><td>54.00</td><td>-7.95</td><td>67.01</td><td>33.40</td><td>9.32</td><td>63.68</td><td>0.00</td><td>300</td><td>182</td><td>Average</td></tr><tr><td>4</td><td>4804.00</td><td>53.93</td><td>74.00</td><td>-20.07</td><td>73.05</td><td>34.09</td><td>10.27</td><td>63.48</td><td>0.00</td><td>296</td><td>156</td><td>PEAK</td></tr><tr><td>5</td><td>4804.00</td><td>46.89</td><td>54.00</td><td>-7.11</td><td>66.01</td><td>34.09</td><td>10.27</td><td>63.48</td><td>0.00</td><td>296</td><td>156</td><td>AVERAGE</td></tr><tr><td>6</td><td>7206.00</td><td>52.61</td><td>95.42</td><td>-42.81</td><td>68.01</td><td>35.60</td><td>12.61</td><td>63.61</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>								Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	3202.50	43.49	95.42	-51.93	65.16	33.19	8.32	63.18	0.00	--	--	Peak	2	4002.00	50.75	74.00	-23.25	71.71	33.40	9.32	63.68	0.00	300	182	Peak	3	4002.00	46.05	54.00	-7.95	67.01	33.40	9.32	63.68	0.00	300	182	Average	4	4804.00	53.93	74.00	-20.07	73.05	34.09	10.27	63.48	0.00	296	156	PEAK	5	4804.00	46.89	54.00	-7.11	66.01	34.09	10.27	63.48	0.00	296	156	AVERAGE	6	7206.00	52.61	95.42	-42.81	68.01	35.60	12.61	63.61	0.00	--	--
		Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																																																			
1	3202.50	41.48	93.24	-51.76	63.15	33.19	8.32	63.18	0.00	--	--	Peak																																																																																																																																																																																																																																	
2	4003.50	50.67	74.00	-23.33	71.64	33.39	9.32	63.68	0.00	126	257	Peak																																																																																																																																																																																																																																	
3	4003.50	46.49	54.00	-7.51	67.46	33.39	9.32	63.68	0.00	126	257	Average																																																																																																																																																																																																																																	
4	4804.00	53.15	74.00	-20.85	72.27	34.09	10.27	63.48	0.00	156	76	PEAK																																																																																																																																																																																																																																	
5	4804.00	47.80	54.00	-6.20	66.92	34.09	10.27	63.48	0.00	156	76	AVERAGE																																																																																																																																																																																																																																	
6	7206.00	49.12	93.24	-44.12	64.52	35.60	12.61	63.61	0.00	--	--	Peak																																																																																																																																																																																																																																	
		Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																																																			
1	3202.50	43.49	95.42	-51.93	65.16	33.19	8.32	63.18	0.00	--	--	Peak																																																																																																																																																																																																																																	
2	4002.00	50.75	74.00	-23.25	71.71	33.40	9.32	63.68	0.00	300	182	Peak																																																																																																																																																																																																																																	
3	4002.00	46.05	54.00	-7.95	67.01	33.40	9.32	63.68	0.00	300	182	Average																																																																																																																																																																																																																																	
4	4804.00	53.93	74.00	-20.07	73.05	34.09	10.27	63.48	0.00	296	156	PEAK																																																																																																																																																																																																																																	
5	4804.00	46.89	54.00	-7.11	66.01	34.09	10.27	63.48	0.00	296	156	AVERAGE																																																																																																																																																																																																																																	
6	7206.00	52.61	95.42	-42.81	68.01	35.60	12.61	63.61	0.00	--	--	Peak																																																																																																																																																																																																																																	







Mode	5																																																																																																																																																			
	Harmonic																																																																																																																																																			
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																																																																																																																			
ANT	1																																																																																																																																																			
Pol.	Horizontal																																																																																																																																																			
Peak Avg																																																																																																																																																				
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3253.50</td><td>41.01</td><td>91.88</td><td>-50.87</td><td>62.97</td><td>32.88</td><td>8.42</td><td>63.26</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4066.50</td><td>51.60</td><td>74.00</td><td>-22.40</td><td>72.56</td><td>33.27</td><td>9.41</td><td>63.64</td><td>0.00</td><td>117</td><td>135</td><td>Peak</td></tr><tr><td>3</td><td>4066.50</td><td>47.05</td><td>54.00</td><td>-6.95</td><td>68.01</td><td>33.27</td><td>9.41</td><td>63.64</td><td>0.00</td><td>117</td><td>135</td><td>Average</td></tr><tr><td>4</td><td>4880.00</td><td>56.10</td><td>74.00</td><td>-17.90</td><td>75.29</td><td>33.94</td><td>10.35</td><td>63.48</td><td>0.00</td><td>100</td><td>14</td><td>PEAK</td></tr><tr><td>5</td><td>4880.00</td><td>50.67</td><td>54.00</td><td>-3.33</td><td>69.86</td><td>33.94</td><td>10.35</td><td>63.48</td><td>0.00</td><td>100</td><td>14</td><td>AVERAGE</td></tr><tr><td>6</td><td>7320.00</td><td>56.97</td><td>74.00</td><td>-17.03</td><td>72.26</td><td>35.60</td><td>12.79</td><td>63.68</td><td>0.00</td><td>120</td><td>100</td><td>Peak</td></tr><tr><td>7</td><td>7320.00</td><td>50.02</td><td>54.00</td><td>-3.98</td><td>65.31</td><td>35.60</td><td>12.79</td><td>63.68</td><td>0.00</td><td>120</td><td>100</td><td>Average</td></tr><tr><td>8</td><td>9760.50</td><td>48.06</td><td>91.88</td><td>-43.82</td><td>58.45</td><td>36.96</td><td>14.87</td><td>62.22</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3253.50	41.01	91.88	-50.87	62.97	32.88	8.42	63.26	0.00	--	--	Peak	2	4066.50	51.60	74.00	-22.40	72.56	33.27	9.41	63.64	0.00	117	135	Peak	3	4066.50	47.05	54.00	-6.95	68.01	33.27	9.41	63.64	0.00	117	135	Average	4	4880.00	56.10	74.00	-17.90	75.29	33.94	10.35	63.48	0.00	100	14	PEAK	5	4880.00	50.67	54.00	-3.33	69.86	33.94	10.35	63.48	0.00	100	14	AVERAGE	6	7320.00	56.97	74.00	-17.03	72.26	35.60	12.79	63.68	0.00	120	100	Peak	7	7320.00	50.02	54.00	-3.98	65.31	35.60	12.79	63.68	0.00	120	100	Average	8	9760.50	48.06	91.88	-43.82	58.45	36.96	14.87	62.22	0.00	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																										
1	3253.50	41.01	91.88	-50.87	62.97	32.88	8.42	63.26	0.00	--	--	Peak																																																																																																																																								
2	4066.50	51.60	74.00	-22.40	72.56	33.27	9.41	63.64	0.00	117	135	Peak																																																																																																																																								
3	4066.50	47.05	54.00	-6.95	68.01	33.27	9.41	63.64	0.00	117	135	Average																																																																																																																																								
4	4880.00	56.10	74.00	-17.90	75.29	33.94	10.35	63.48	0.00	100	14	PEAK																																																																																																																																								
5	4880.00	50.67	54.00	-3.33	69.86	33.94	10.35	63.48	0.00	100	14	AVERAGE																																																																																																																																								
6	7320.00	56.97	74.00	-17.03	72.26	35.60	12.79	63.68	0.00	120	100	Peak																																																																																																																																								
7	7320.00	50.02	54.00	-3.98	65.31	35.60	12.79	63.68	0.00	120	100	Average																																																																																																																																								
8	9760.50	48.06	91.88	-43.82	58.45	36.96	14.87	62.22	0.00	--	--	Peak																																																																																																																																								
Peak Avg																																																																																																																																																				
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4066.50</td><td>52.61</td><td>74.00</td><td>-21.39</td><td>73.57</td><td>33.27</td><td>9.41</td><td>63.64</td><td>0.00</td><td>322</td><td>176</td><td>PEAK</td></tr><tr><td>2</td><td>4066.50</td><td>48.62</td><td>54.00</td><td>-5.38</td><td>69.58</td><td>33.27</td><td>9.41</td><td>63.64</td><td>0.00</td><td>322</td><td>176</td><td>AVERAGE</td></tr><tr><td>3</td><td>4880.00</td><td>54.92</td><td>74.00</td><td>-19.08</td><td>74.11</td><td>33.94</td><td>10.35</td><td>63.48</td><td>0.00</td><td>343</td><td>85</td><td>PEAK</td></tr><tr><td>4</td><td>4880.00</td><td>50.73</td><td>54.00</td><td>-3.27</td><td>69.92</td><td>33.94</td><td>10.35</td><td>63.48</td><td>0.00</td><td>343</td><td>85</td><td>AVERAGE</td></tr><tr><td>5</td><td>7320.00</td><td>53.73</td><td>74.00</td><td>-20.27</td><td>69.02</td><td>35.60</td><td>12.79</td><td>63.68</td><td>0.00</td><td>300</td><td>149</td><td>Peak</td></tr><tr><td>6</td><td>7320.00</td><td>49.89</td><td>54.00</td><td>-4.11</td><td>65.18</td><td>35.60</td><td>12.79</td><td>63.68</td><td>0.00</td><td>300</td><td>149</td><td>Average</td></tr><tr><td>7</td><td>9760.50</td><td>47.06</td><td>94.74</td><td>-47.68</td><td>57.45</td><td>36.96</td><td>14.87</td><td>62.22</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4066.50	52.61	74.00	-21.39	73.57	33.27	9.41	63.64	0.00	322	176	PEAK	2	4066.50	48.62	54.00	-5.38	69.58	33.27	9.41	63.64	0.00	322	176	AVERAGE	3	4880.00	54.92	74.00	-19.08	74.11	33.94	10.35	63.48	0.00	343	85	PEAK	4	4880.00	50.73	54.00	-3.27	69.92	33.94	10.35	63.48	0.00	343	85	AVERAGE	5	7320.00	53.73	74.00	-20.27	69.02	35.60	12.79	63.68	0.00	300	149	Peak	6	7320.00	49.89	54.00	-4.11	65.18	35.60	12.79	63.68	0.00	300	149	Average	7	9760.50	47.06	94.74	-47.68	57.45	36.96	14.87	62.22	0.00	--	--	Peak													
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																										
1	4066.50	52.61	74.00	-21.39	73.57	33.27	9.41	63.64	0.00	322	176	PEAK																																																																																																																																								
2	4066.50	48.62	54.00	-5.38	69.58	33.27	9.41	63.64	0.00	322	176	AVERAGE																																																																																																																																								
3	4880.00	54.92	74.00	-19.08	74.11	33.94	10.35	63.48	0.00	343	85	PEAK																																																																																																																																								
4	4880.00	50.73	54.00	-3.27	69.92	33.94	10.35	63.48	0.00	343	85	AVERAGE																																																																																																																																								
5	7320.00	53.73	74.00	-20.27	69.02	35.60	12.79	63.68	0.00	300	149	Peak																																																																																																																																								
6	7320.00	49.89	54.00	-4.11	65.18	35.60	12.79	63.68	0.00	300	149	Average																																																																																																																																								
7	9760.50	47.06	94.74	-47.68	57.45	36.96	14.87	62.22	0.00	--	--	Peak																																																																																																																																								



Mode	6																																																						
	Band Edge																																																						
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																						
ANT	1																																																						
Pol.	Horizontal						Fundamental																																																
Peak																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.62</td><td>66.04</td><td>74.00</td><td>-7.96</td><td>57.33</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>231</td><td>175</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.62	66.04	74.00	-7.96	57.33	32.23	7.33	36.85	6.00	231	175
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2483.62	66.04	74.00	-7.96	57.33	32.23	7.33	36.85	6.00	231	175	PEAK																																											
Peak																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>110.66</td><td>-----</td><td>-----</td><td>101.97</td><td>32.22</td><td>7.32</td><td>36.85</td><td>6.00</td><td>231</td><td>175</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	110.66	-----	-----	101.97	32.22	7.32	36.85	6.00	231	175
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2480.00	110.66	-----	-----	101.97	32.22	7.32	36.85	6.00	231	175	PEAK																																											
Avg																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>52.33</td><td>54.00</td><td>-1.67</td><td>43.62</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>231</td><td>175</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	52.33	54.00	-1.67	43.62	32.23	7.33	36.85	6.00	231	175
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2483.50	52.33	54.00	-1.67	43.62	32.23	7.33	36.85	6.00	231	175	AVERAGE																																											
Avg																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>107.81</td><td>-----</td><td>-----</td><td>99.12</td><td>32.22</td><td>7.32</td><td>36.85</td><td>6.00</td><td>231</td><td>175</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	107.81	-----	-----	99.12	32.22	7.32	36.85	6.00	231	175
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2480.00	107.81	-----	-----	99.12	32.22	7.32	36.85	6.00	231	175	AVERAGE																																											







Mode	6																																																													
	Band Edge																																																													
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																													
ANT	1																																																													
Pol.	Vertical						Fundamental																																																							
Peak																																																														
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2483.50</td><td>70.50</td><td>74.00</td><td>-3.50</td><td>61.79</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>109</td><td>122</td><td>PEAK</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2483.50	70.50	74.00	-3.50	61.79	32.23	7.33	36.85	6.00	109	122
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																			
1	2483.50	70.50	74.00	-3.50	61.79	32.23	7.33	36.85	6.00	109	122	PEAK																																																		
Fundamental																																																														
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>109.31</td><td>-----</td><td>-----</td><td>100.62</td><td>32.22</td><td>7.32</td><td>36.85</td><td>6.00</td><td>109</td><td>122</td><td>PEAK</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2480.00	109.31	-----	-----	100.62	32.22	7.32	36.85	6.00	109	122
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																			
1	2480.00	109.31	-----	-----	100.62	32.22	7.32	36.85	6.00	109	122	PEAK																																																		
Avg																																																														
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2483.56</td><td>51.41</td><td>54.00</td><td>-2.59</td><td>42.70</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>109</td><td>122</td><td>AVERAGE</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2483.56	51.41	54.00	-2.59	42.70	32.23	7.33	36.85	6.00	109	122
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																			
1	2483.56	51.41	54.00	-2.59	42.70	32.23	7.33	36.85	6.00	109	122	AVERAGE																																																		
Fundamental																																																														
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>106.44</td><td>-----</td><td>-----</td><td>97.75</td><td>32.22</td><td>7.32</td><td>36.85</td><td>6.00</td><td>109</td><td>122</td><td>AVERAGE</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2480.00	106.44	-----	-----	97.75	32.22	7.32	36.85	6.00	109	122
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																			
1	2480.00	106.44	-----	-----	97.75	32.22	7.32	36.85	6.00	109	122	AVERAGE																																																		







		6																																																																																																																																																																																																																																																																																							
Mode	Harmonic																																																																																																																																																																																																																																																																																								
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																																																																																																																																																																																																								
ANT	1																																																																																																																																																																																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																																																																																																																																																																																		
Peak Avg																																																																																																																																																																																																																																																																																									
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3256.50</td><td>39.22</td><td>86.01</td><td>-46.79</td><td>61.20</td><td>32.06</td><td>8.43</td><td>63.27</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4134.00</td><td>48.60</td><td>74.00</td><td>-25.40</td><td>69.40</td><td>33.30</td><td>9.50</td><td>63.60</td><td>0.00</td><td>111</td><td>136</td><td>Peak</td></tr><tr><td>3</td><td>4134.00</td><td>43.37</td><td>54.00</td><td>-10.63</td><td>64.17</td><td>33.30</td><td>9.50</td><td>63.60</td><td>0.00</td><td>111</td><td>136</td><td>Average</td></tr><tr><td>4</td><td>4960.00</td><td>54.19</td><td>74.00</td><td>-19.81</td><td>73.27</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>100</td><td>268</td><td>PEAK</td></tr><tr><td>5</td><td>4960.00</td><td>49.07</td><td>54.00</td><td>-4.93</td><td>68.15</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>100</td><td>268</td><td>AVERAGE</td></tr><tr><td>6</td><td>7438.50</td><td>51.33</td><td>74.00</td><td>-22.67</td><td>66.51</td><td>35.64</td><td>12.93</td><td>63.75</td><td>0.00</td><td>105</td><td>98</td><td>Peak</td></tr><tr><td>7</td><td>7438.50</td><td>44.62</td><td>54.00</td><td>-9.38</td><td>59.80</td><td>35.64</td><td>12.93</td><td>63.75</td><td>0.00</td><td>105</td><td>98</td><td>Average</td></tr><tr><td>8</td><td>9919.50</td><td>43.99</td><td>86.01</td><td>-42.02</td><td>54.19</td><td>37.10</td><td>14.98</td><td>62.28</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3256.50	39.22	86.01	-46.79	61.20	32.06	8.43	63.27	0.00	--	--	Peak	2	4134.00	48.60	74.00	-25.40	69.40	33.30	9.50	63.60	0.00	111	136	Peak	3	4134.00	43.37	54.00	-10.63	64.17	33.30	9.50	63.60	0.00	111	136	Average	4	4960.00	54.19	74.00	-19.81	73.27	33.96	10.44	63.48	0.00	100	268	PEAK	5	4960.00	49.07	54.00	-4.93	68.15	33.96	10.44	63.48	0.00	100	268	AVERAGE	6	7438.50	51.33	74.00	-22.67	66.51	35.64	12.93	63.75	0.00	105	98	Peak	7	7438.50	44.62	54.00	-9.38	59.80	35.64	12.93	63.75	0.00	105	98	Average	8	9919.50	43.99	86.01	-42.02	54.19	37.10	14.98	62.28	0.00	--	--	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3306.00</td><td>42.38</td><td>89.09</td><td>-46.71</td><td>64.60</td><td>32.60</td><td>8.52</td><td>63.34</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4133.91</td><td>50.55</td><td>74.00</td><td>-23.45</td><td>71.35</td><td>33.30</td><td>9.50</td><td>63.60</td><td>0.00</td><td>294</td><td>172</td><td>PEAK</td></tr><tr><td>3</td><td>4133.91</td><td>46.68</td><td>54.00</td><td>-7.32</td><td>67.48</td><td>33.30</td><td>9.50</td><td>63.60</td><td>0.00</td><td>294</td><td>172</td><td>AVERAGE</td></tr><tr><td>4</td><td>4960.00</td><td>51.04</td><td>74.00</td><td>-22.96</td><td>70.12</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>319</td><td>35</td><td>PEAK</td></tr><tr><td>5</td><td>4960.00</td><td>46.02</td><td>54.00</td><td>-7.98</td><td>65.10</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>319</td><td>35</td><td>AVERAGE</td></tr><tr><td>6</td><td>7440.00</td><td>51.94</td><td>74.00</td><td>-22.06</td><td>67.12</td><td>35.64</td><td>12.93</td><td>63.75</td><td>0.00</td><td>100</td><td>156</td><td>PEAK</td></tr><tr><td>7</td><td>7440.00</td><td>46.01</td><td>54.00</td><td>-7.99</td><td>61.19</td><td>35.64</td><td>12.93</td><td>63.75</td><td>0.00</td><td>100</td><td>156</td><td>AVERAGE</td></tr><tr><td>8</td><td>9919.50</td><td>46.87</td><td>89.09</td><td>-42.22</td><td>57.07</td><td>37.10</td><td>14.98</td><td>62.28</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3306.00	42.38	89.09	-46.71	64.60	32.60	8.52	63.34	0.00	--	--	Peak	2	4133.91	50.55	74.00	-23.45	71.35	33.30	9.50	63.60	0.00	294	172	PEAK	3	4133.91	46.68	54.00	-7.32	67.48	33.30	9.50	63.60	0.00	294	172	AVERAGE	4	4960.00	51.04	74.00	-22.96	70.12	33.96	10.44	63.48	0.00	319	35	PEAK	5	4960.00	46.02	54.00	-7.98	65.10	33.96	10.44	63.48	0.00	319	35	AVERAGE	6	7440.00	51.94	74.00	-22.06	67.12	35.64	12.93	63.75	0.00	100	156	PEAK	7	7440.00	46.01	54.00	-7.99	61.19	35.64	12.93	63.75	0.00	100	156	AVERAGE	8	9919.50	46.87	89.09	-42.22	57.07	37.10	14.98	62.28	0.00	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																																															
1	3256.50	39.22	86.01	-46.79	61.20	32.06	8.43	63.27	0.00	--	--	Peak																																																																																																																																																																																																																																																																													
2	4134.00	48.60	74.00	-25.40	69.40	33.30	9.50	63.60	0.00	111	136	Peak																																																																																																																																																																																																																																																																													
3	4134.00	43.37	54.00	-10.63	64.17	33.30	9.50	63.60	0.00	111	136	Average																																																																																																																																																																																																																																																																													
4	4960.00	54.19	74.00	-19.81	73.27	33.96	10.44	63.48	0.00	100	268	PEAK																																																																																																																																																																																																																																																																													
5	4960.00	49.07	54.00	-4.93	68.15	33.96	10.44	63.48	0.00	100	268	AVERAGE																																																																																																																																																																																																																																																																													
6	7438.50	51.33	74.00	-22.67	66.51	35.64	12.93	63.75	0.00	105	98	Peak																																																																																																																																																																																																																																																																													
7	7438.50	44.62	54.00	-9.38	59.80	35.64	12.93	63.75	0.00	105	98	Average																																																																																																																																																																																																																																																																													
8	9919.50	43.99	86.01	-42.02	54.19	37.10	14.98	62.28	0.00	--	--	Peak																																																																																																																																																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																																															
1	3306.00	42.38	89.09	-46.71	64.60	32.60	8.52	63.34	0.00	--	--	Peak																																																																																																																																																																																																																																																																													
2	4133.91	50.55	74.00	-23.45	71.35	33.30	9.50	63.60	0.00	294	172	PEAK																																																																																																																																																																																																																																																																													
3	4133.91	46.68	54.00	-7.32	67.48	33.30	9.50	63.60	0.00	294	172	AVERAGE																																																																																																																																																																																																																																																																													
4	4960.00	51.04	74.00	-22.96	70.12	33.96	10.44	63.48	0.00	319	35	PEAK																																																																																																																																																																																																																																																																													
5	4960.00	46.02	54.00	-7.98	65.10	33.96	10.44	63.48	0.00	319	35	AVERAGE																																																																																																																																																																																																																																																																													
6	7440.00	51.94	74.00	-22.06	67.12	35.64	12.93	63.75	0.00	100	156	PEAK																																																																																																																																																																																																																																																																													
7	7440.00	46.01	54.00	-7.99	61.19	35.64	12.93	63.75	0.00	100	156	AVERAGE																																																																																																																																																																																																																																																																													
8	9919.50	46.87	89.09	-42.22	57.07	37.10	14.98	62.28	0.00	--	--	Peak																																																																																																																																																																																																																																																																													





Mode	17																																																						
	Band Edge																																																						
	2400-2483.5_Bluetooth-LE_GSKF_CH38_2478MHz																																																						
ANT	1																																																						
Pol.	Horizontal						Fundamental																																																
Peak																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.56</td><td>58.86</td><td>74.00</td><td>-15.14</td><td>50.15</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>146</td><td>360</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.56	58.86	74.00	-15.14	50.15	32.23	7.33	36.85	6.00	146	360
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2483.56	58.86	74.00	-15.14	50.15	32.23	7.33	36.85	6.00	146	360	PEAK																																											
Peak																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>110.14</td><td>-----</td><td>-----</td><td>101.46</td><td>32.21</td><td>7.32</td><td>36.85</td><td>6.00</td><td>146</td><td>360</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	110.14	-----	-----	101.46	32.21	7.32	36.85	6.00	146	360
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2478.00	110.14	-----	-----	101.46	32.21	7.32	36.85	6.00	146	360	PEAK																																											
Avg																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>47.36</td><td>54.00</td><td>-6.64</td><td>38.65</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>146</td><td>360</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	47.36	54.00	-6.64	38.65	32.23	7.33	36.85	6.00	146	360
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2483.50	47.36	54.00	-6.64	38.65	32.23	7.33	36.85	6.00	146	360	AVERAGE																																											
Avg																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>107.32</td><td>-----</td><td>-----</td><td>98.64</td><td>32.21</td><td>7.32</td><td>36.85</td><td>6.00</td><td>146</td><td>360</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	107.32	-----	-----	98.64	32.21	7.32	36.85	6.00	146	360
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2478.00	107.32	-----	-----	98.64	32.21	7.32	36.85	6.00	146	360	AVERAGE																																											



Mode	17																																																					
	Band Edge																																																					
	2400-2483.5_Bluetooth-LE_GSKF_CH38_2478MHz																																																					
ANT	1																																																					
Pol.	Vertical						Fundamental																																															
Peak																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.68</td><td>61.97</td><td>74.00</td><td>-12.03</td><td>53.26</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>149</td><td>0 PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.68	61.97	74.00	-12.03	53.26	32.23	7.33	36.85	6.00	149
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2483.68	61.97	74.00	-12.03	53.26	32.23	7.33	36.85	6.00	149	0 PEAK																																											
Peak																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>114.59</td><td>-----</td><td>-----</td><td>105.91</td><td>32.21</td><td>7.32</td><td>36.85</td><td>6.00</td><td>149</td><td>0 PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	114.59	-----	-----	105.91	32.21	7.32	36.85	6.00	149
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2478.00	114.59	-----	-----	105.91	32.21	7.32	36.85	6.00	149	0 PEAK																																											
Avg																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>51.38</td><td>54.00</td><td>-2.62</td><td>42.67</td><td>32.23</td><td>7.33</td><td>36.85</td><td>6.00</td><td>149</td><td>0 AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	51.38	54.00	-2.62	42.67	32.23	7.33	36.85	6.00	149
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2483.50	51.38	54.00	-2.62	42.67	32.23	7.33	36.85	6.00	149	0 AVERAGE																																											
Avg																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>111.63</td><td>-----</td><td>-----</td><td>102.95</td><td>32.21</td><td>7.32</td><td>36.85</td><td>6.00</td><td>149</td><td>0 AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	111.63	-----	-----	102.95	32.21	7.32	36.85	6.00	149
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2478.00	111.63	-----	-----	102.95	32.21	7.32	36.85	6.00	149	0 AVERAGE																																											





		17																																																																																																																																																																																																											
Mode	Harmonic																																																																																																																																																																																																												
	2400-2483.5_Bluetooth-LE_GSKF_CH38_2478MHz																																																																																																																																																																																																												
ANT	1																																																																																																																																																																																																												
Pol.	Horizontal						Vertical																																																																																																																																																																																																						
Peak Avg																																																																																																																																																																																																													
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4129.50</td><td>41.92</td><td>74.00</td><td>-32.08</td><td>62.73</td><td>33.29</td><td>9.50</td><td>63.60</td><td>0.00</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4956.00</td><td>50.84</td><td>74.00</td><td>-23.16</td><td>69.92</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>100</td><td>61 PEAK</td></tr><tr><td>3</td><td>4956.00</td><td>45.40</td><td>54.00</td><td>-8.60</td><td>64.48</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>100</td><td>61 AVERAGE</td></tr><tr><td>4</td><td>7434.00</td><td>43.69</td><td>74.00</td><td>-30.31</td><td>58.88</td><td>35.63</td><td>12.93</td><td>63.75</td><td>0.00</td><td>--</td><td>PEAK</td></tr><tr><td>5</td><td>9912.00</td><td>46.11</td><td>88.45</td><td>-42.34</td><td>56.32</td><td>37.10</td><td>14.97</td><td>62.28</td><td>0.00</td><td>--</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4129.50	41.92	74.00	-32.08	62.73	33.29	9.50	63.60	0.00	--	PEAK	2	4956.00	50.84	74.00	-23.16	69.92	33.96	10.44	63.48	0.00	100	61 PEAK	3	4956.00	45.40	54.00	-8.60	64.48	33.96	10.44	63.48	0.00	100	61 AVERAGE	4	7434.00	43.69	74.00	-30.31	58.88	35.63	12.93	63.75	0.00	--	PEAK	5	9912.00	46.11	88.45	-42.34	56.32	37.10	14.97	62.28	0.00	--	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3304.50</td><td>41.49</td><td>92.97</td><td>-51.48</td><td>63.71</td><td>32.60</td><td>8.52</td><td>63.34</td><td>0.00</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4129.50</td><td>44.13</td><td>74.00</td><td>-29.87</td><td>64.94</td><td>33.29</td><td>9.50</td><td>63.60</td><td>0.00</td><td>--</td><td>PEAK</td></tr><tr><td>3</td><td>4956.00</td><td>52.06</td><td>74.00</td><td>-21.94</td><td>71.14</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>266</td><td>91 PEAK</td></tr><tr><td>4</td><td>4956.00</td><td>46.69</td><td>54.00</td><td>-7.31</td><td>65.77</td><td>33.96</td><td>10.44</td><td>63.48</td><td>0.00</td><td>266</td><td>91 AVERAGE</td></tr><tr><td>5</td><td>7434.00</td><td>46.01</td><td>74.00</td><td>-27.99</td><td>61.19</td><td>35.64</td><td>12.93</td><td>63.75</td><td>0.00</td><td>--</td><td>PEAK</td></tr><tr><td>6</td><td>9912.00</td><td>47.09</td><td>92.97</td><td>-45.88</td><td>57.30</td><td>37.10</td><td>14.97</td><td>62.28</td><td>0.00</td><td>--</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	3304.50	41.49	92.97	-51.48	63.71	32.60	8.52	63.34	0.00	--	PEAK	2	4129.50	44.13	74.00	-29.87	64.94	33.29	9.50	63.60	0.00	--	PEAK	3	4956.00	52.06	74.00	-21.94	71.14	33.96	10.44	63.48	0.00	266	91 PEAK	4	4956.00	46.69	54.00	-7.31	65.77	33.96	10.44	63.48	0.00	266	91 AVERAGE	5	7434.00	46.01	74.00	-27.99	61.19	35.64	12.93	63.75	0.00	--	PEAK	6	9912.00	47.09	92.97	-45.88	57.30	37.10	14.97	62.28	0.00	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																			
1	4129.50	41.92	74.00	-32.08	62.73	33.29	9.50	63.60	0.00	--	PEAK																																																																																																																																																																																																		
2	4956.00	50.84	74.00	-23.16	69.92	33.96	10.44	63.48	0.00	100	61 PEAK																																																																																																																																																																																																		
3	4956.00	45.40	54.00	-8.60	64.48	33.96	10.44	63.48	0.00	100	61 AVERAGE																																																																																																																																																																																																		
4	7434.00	43.69	74.00	-30.31	58.88	35.63	12.93	63.75	0.00	--	PEAK																																																																																																																																																																																																		
5	9912.00	46.11	88.45	-42.34	56.32	37.10	14.97	62.28	0.00	--	PEAK																																																																																																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																			
1	3304.50	41.49	92.97	-51.48	63.71	32.60	8.52	63.34	0.00	--	PEAK																																																																																																																																																																																																		
2	4129.50	44.13	74.00	-29.87	64.94	33.29	9.50	63.60	0.00	--	PEAK																																																																																																																																																																																																		
3	4956.00	52.06	74.00	-21.94	71.14	33.96	10.44	63.48	0.00	266	91 PEAK																																																																																																																																																																																																		
4	4956.00	46.69	54.00	-7.31	65.77	33.96	10.44	63.48	0.00	266	91 AVERAGE																																																																																																																																																																																																		
5	7434.00	46.01	74.00	-27.99	61.19	35.64	12.93	63.75	0.00	--	PEAK																																																																																																																																																																																																		
6	9912.00	47.09	92.97	-45.88	57.30	37.10	14.97	62.28	0.00	--	PEAK																																																																																																																																																																																																		



Mode	3	
	18-25G	
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz	
ANT	1	
Pol.	Horizontal	Vertical
Peak		
Avg		




Mode	3																																																																																																								
	LF																																																																																																								
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																								
ANT	1																																																																																																								
Pol.	Horizontal																																																																																																								
Peak QP																																																																																																									
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>30.00</td><td>21.51</td><td>-18.49</td><td>40.00</td><td>28.29</td><td>24.83</td><td>0.50</td><td>32.11</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2 p</td><td>159.98</td><td>30.94</td><td>-12.56</td><td>43.50</td><td>44.77</td><td>16.43</td><td>1.83</td><td>32.09</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>299.66</td><td>31.90</td><td>-14.10</td><td>46.00</td><td>42.25</td><td>19.18</td><td>2.54</td><td>32.07</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>626.55</td><td>27.58</td><td>-18.42</td><td>46.00</td><td>29.89</td><td>26.36</td><td>3.65</td><td>32.32</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>772.05</td><td>29.99</td><td>-16.01</td><td>46.00</td><td>29.70</td><td>28.24</td><td>4.04</td><td>31.99</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>986.42</td><td>33.70</td><td>-20.30</td><td>54.00</td><td>28.96</td><td>30.79</td><td>4.57</td><td>30.62</td><td>---</td><td>---</td><td>Peak</td></tr></table>												Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	30.00	21.51	-18.49	40.00	28.29	24.83	0.50	32.11	---	---	Peak	2 p	159.98	30.94	-12.56	43.50	44.77	16.43	1.83	32.09	---	---	Peak	3	299.66	31.90	-14.10	46.00	42.25	19.18	2.54	32.07	---	---	Peak	4	626.55	27.58	-18.42	46.00	29.89	26.36	3.65	32.32	---	---	Peak	5	772.05	29.99	-16.01	46.00	29.70	28.24	4.04	31.99	---	---	Peak	6	986.42	33.70	-20.30	54.00	28.96	30.79	4.57	30.62	---	---	Peak
		Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																														
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																														
	1	30.00	21.51	-18.49	40.00	28.29	24.83	0.50	32.11	---	---	Peak																																																																																													
	2 p	159.98	30.94	-12.56	43.50	44.77	16.43	1.83	32.09	---	---	Peak																																																																																													
	3	299.66	31.90	-14.10	46.00	42.25	19.18	2.54	32.07	---	---	Peak																																																																																													
	4	626.55	27.58	-18.42	46.00	29.89	26.36	3.65	32.32	---	---	Peak																																																																																													
	5	772.05	29.99	-16.01	46.00	29.70	28.24	4.04	31.99	---	---	Peak																																																																																													
	6	986.42	33.70	-20.30	54.00	28.96	30.79	4.57	30.62	---	---	Peak																																																																																													
Vertical																																																																																																									
Peak QP																																																																																																									
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 p</td><td>33.88</td><td>25.81</td><td>-14.19</td><td>40.00</td><td>34.53</td><td>22.95</td><td>0.55</td><td>32.22</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>96.93</td><td>19.38</td><td>-24.12</td><td>43.50</td><td>34.49</td><td>15.54</td><td>1.42</td><td>32.07</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>417.03</td><td>26.80</td><td>-19.20</td><td>46.00</td><td>33.40</td><td>22.54</td><td>2.98</td><td>32.12</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>524.70</td><td>28.52</td><td>-17.48</td><td>46.00</td><td>33.21</td><td>24.24</td><td>3.33</td><td>32.26</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>675.05</td><td>30.54</td><td>-15.46</td><td>46.00</td><td>32.49</td><td>26.48</td><td>3.80</td><td>32.23</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>975.75</td><td>33.49</td><td>-20.51</td><td>54.00</td><td>28.76</td><td>30.91</td><td>4.54</td><td>30.72</td><td>---</td><td>---</td><td>Peak</td></tr></table>												Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1 p	33.88	25.81	-14.19	40.00	34.53	22.95	0.55	32.22	---	---	Peak	2	96.93	19.38	-24.12	43.50	34.49	15.54	1.42	32.07	---	---	Peak	3	417.03	26.80	-19.20	46.00	33.40	22.54	2.98	32.12	---	---	Peak	4	524.70	28.52	-17.48	46.00	33.21	24.24	3.33	32.26	---	---	Peak	5	675.05	30.54	-15.46	46.00	32.49	26.48	3.80	32.23	---	---	Peak	6	975.75	33.49	-20.51	54.00	28.76	30.91	4.54	30.72	---	---	Peak
		Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																														
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																														
	1 p	33.88	25.81	-14.19	40.00	34.53	22.95	0.55	32.22	---	---	Peak																																																																																													
	2	96.93	19.38	-24.12	43.50	34.49	15.54	1.42	32.07	---	---	Peak																																																																																													
	3	417.03	26.80	-19.20	46.00	33.40	22.54	2.98	32.12	---	---	Peak																																																																																													
	4	524.70	28.52	-17.48	46.00	33.21	24.24	3.33	32.26	---	---	Peak																																																																																													
	5	675.05	30.54	-15.46	46.00	32.49	26.48	3.80	32.23	---	---	Peak																																																																																													
	6	975.75	33.49	-20.51	54.00	28.76	30.91	4.54	30.72	---	---	Peak																																																																																													

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth LE 1Mbps	95.39	2.1014	0.4759	0.51kHz
Bluetooth LE 2Mbps	90.12	1.0580	0.9452	1kHz

Bluetooth - LE1Mbps



Bluetooth – LE2Mbps

