		SYSTEMS (SH	IANGHAI) CO., LTD /2AC7Z				
FCC ID							
	Section 15.212 Modular Transmitters						
Request	for Modular Approval		est for Limited Modular Approval				
	Requirements		EUT Conditions	Comply (Y/N)			
			pproval Requirements				
1	The radio elements of the modular		The radio portion of this module is	Ν			
	transmitter must have their own		unshielded, please see exhibition				
	shielding. The physical cryst		external photos.				
	tuning capacitors may be located						
	external to the shielded radio elements.						
2	The modular transmitter must have		The module has buffer modulation/data	Y			
	buffered modulation/data inputs (if such		inputs.				
	inputs are provided) to ensur						
	module will comply with Pa						
	requirements under conditions of excessive data rates or over-modulation.						
3	The modular transmitter mus		The module has its own power supply	Y			
5	own power supply regulation		regulation. Please see the schem.pdf	1			
4	The modular transmitter mus		The module has no connector between	N			
т	with the antenna and transmi	1 2	antenna. Please refer to the Test Report	1			
	system requirements of Sections 15.203,		exhibition.				
	15.204(b) and 15.204(c). Th						
	must either be permanently a						
	employ a "unique" antenna o						
	all connections between the						
	the antenna, including the ca	ble). The					
	"professional installation" pr						
	Section 15.203 is not applica						
	modules but can apply to lin						
	modular approvals under paragraph (b)						
	of this section.						
5	The modular transmitter mus		Please refer to the Setup Photo	Y			
	in a stand-alone configuratio	, ,	exhibition for the stand-alone test				
	module must not be inside an		configuration.				
	device during testing for con with Part 15 requirements. U						
	transmitter module will be b						
	powered, it must comply with						
	line conducted requirements						
	Section 15.207. AC or DC p						
	and data input/output lines c						
	the module must not contain						
	unless they will be marketed with the						
	module (see Section 15.27(a)). The						
	length of these lines shall be the length						
	typical of actual use or, if that length is						
	unknown, at least 10 centime						
	insure that there is no coupli						
	the case of the module and s	upporting					

	· · · · · · · · · · · · · · · · · · ·		
	equipment. Any accessories, peripherals,		
	or support equipment connected to the		
	module during testing shall be		
	unmodified and commercially available		
	(see Section 15.31(i)).		
6	The modular transmitter must be	The Module will put label in user	Ν
	equipped with either a permanently	manual since limited space, and the	
	affixed label or must be capable of	instruction on the labeling rule of the	
	electronically displaying its FCC	end product has been stated in the User	
	identification number.	Manual of this module. Please refer to	
	(A) If using a permanently affixed label, the	the Label declaration and User Manual	
	modular transmitter must be labeled with its own	exhibition.	
	FCC identification number, and, if the FCC	exhibition.	
	identification number is not visible when the		
	module is installed inside another device, then		
	the outside of the device into which the module is		
	installed must also display a label referring to		
	the enclosed module. This exterior label can use		
	wording such as the following: "Contains Transmitter Module		
	FCC ID: XYZMODEL1" or "Contains FCC ID:		
	XYZMODEL1." Any similar wording		
	that expresses the same meaning may be used.		
	The Grantee may either provide such a label, an		
	example of which must be included in the		
	application for equipment		
	authorization, or, must provide adequate instructions along with the module which explain		
	this requirement. In the latter case, a copy of		
	these instructions must be included in the		
	application for equipment authorization.		
	(B) If the modular transmitter uses an electronic		
	display of the FCC identification number, the		
	information must be readily accessible and visible on the modular transmitter or on the		
	device in which it is installed. If the module is		
	installed inside another device, then the outside		
	of the device into which the module is installed		
	must display a label referring to the enclosed		
	module. This exterior label can use wording such		
	as the following:		
	"Contains FCC certified transmitter module(s)."		
	Any similar wording that expresses the same meaning may be used. The user manual must		
	include instructions on how to access the		
	electronic display. A copy of these instructions		
	must be included in the application for		
	equipment authorization.		
7	The modular transmitter must comply	The required FCC rule has been fulfilled	Y
	with any specific rules or operating	and all the instructions for maintaining	
	requirements that	compliance have been clearly stated in	
	ordinarily apply to a complete	the User Manual.	
	transmitter and the manufacturer must		
	provide adequate instructions along with		
	the module to explain any such		
	requirements. A copy of these		
	instructions must be included in the		
	application for equipment authorization.		

8	The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	Please refer exhibition RF Exposure for the compliance of MPE RF exposure rule.	Y		
Mix 2	har				

Contact Person: Mia Zhou E-mail: zhoumiaomiao@espressif.com