Applicant/Grantee ESPRESSIF SYSTEMS (SHANGHAI) CO., LTD /2AC7Z							
	FCC ID: 2AC7Z-ESPS2SOLO2						
Section 15.212 Modular Transmitters							
Request for Modular Approval Request for Limited Modular Approval							
•	Requirements	EUT Conditions	Comply (Y/N)				
Single Modular Approval Requirements							
1	The radio elements of the modular		Y				
	transmitter must have their own	shielded, please see exhibition external					
	shielding. The physical crystal and						
	tuning capacitors may be located						
	external to the shielded radio elem	ents.					
2	The modular transmitter must hav	The module has buffer modulation/data	Y				
	buffered modulation/data inputs (i	f such inputs.					
	inputs are provided) to ensure that	the					
	module will comply with Part 15						
	requirements under conditions of						
	excessive data rates or over-modu						
3	The modular transmitter must hav	F F F F	Y				
	own power supply regulation.	regulation. Please see the schem.pdf					
4	The modular transmitter must con		Y				
	with the antenna and transmission	and spurious emission have been					
	system requirements of Sections 1						
	15.204(b) and 15.204(c). The ante						
	must either be permanently attach						
	employ a "unique" antenna couple						
	all connections between the modu						
	the antenna, including the cable).						
	"professional installation" provisi						
	Section 15.203 is not applicable to						
	modules but can apply to limited	h (h)					
	modular approvals under paragraph of this section.	n (b)					
5	The modular transmitter must be t	ested Please refer to the Setup Photo	Y				
3	in a stand-alone configuration, <i>i.e.</i>	1	1				
	module must not be inside another						
	device during testing for compliar						
	with Part 15 requirements. Unless						
	transmitter module will be battery						
	powered, it must comply with the	AC					
	line conducted requirements found						
	Section 15.207. AC or DC power						
	and data input/output lines connec						
	the module must not contain ferrit						
	unless they will be marketed with						
	module (see Section 15.27(a)). Th						
	length of these lines shall be the le						
	typical of actual use or, if that leng						
	unknown, at least 10 centimeters to						
	insure that there is no coupling be						
	the case of the module and suppor	ting					

	equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available		
	(see Section 15.31(i)).	The Median will be 1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	*7
6	The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number. (A) If using a permanently affixed label, the modular transmitter must be labeled with its own FCC identification number, and, if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. (B) If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions	The Module will be labeled with its own FCC ID, and the instruction on the labeling rule of the end product has been stated in the User Manual of this module. Please refer to the Label and User Manual exhibition.	Y
	must be included in the application for equipment authorization.		
7	The modular transmitter must comply	The required FCC rule has been fulfilled	Y
	with any specific rules or operating	and all the instructions for maintaining	
	requirements that	compliance have been clearly stated in	
	ordinarily apply to a complete	the User Manual.	
	transmitter and the manufacturer must		
	provide adequate instructions along with		
	the module to explain any such		
	requirements. A copy of these		
	instructions must be included in the		
	application for equipment authorization.		

8	The modular transmitter must comply	Please refer exhibition RF Exposure for	Y
	with any applicable RF exposure	the compliance of MPE RF exposure	
	requirements in its final configuration.	rule.	

Mia shou

Contact Person: Mia Zhou

E-mail: zhoumiaomiao@espressif.com