



## TEST REPORT

**Application No.:** SZEM1911020336CR  
**Applicant:** Clare Controls  
**Address of Applicant:** 7519 Pennsylvania Av Suite 104, Sarasota, Florida, 34243, United States  
**Manufacturer:** Clare Controls  
**Address of Manufacturer:** 7519 Pennsylvania Av Suite 104, Sarasota, Florida, 34243, United States  
**Factory:** SYBER SENSE IOT COMPANY LIMITED  
**Address of Factory:** 3/F, Building A, Hanhaida High-tech Park, Datian Yang C District, Shiwei Community, Matian Street, Guangming New District, Shenzhen, China.  
**Equipment Under Test (EUT):**  
**EUT Name:** Wireless Security and Smart Home Panel  
**Model No.:** CLR-C1-PNL1  
**Trade mark:** ClareOne  
**FCC ID:** 2AC9I-C1-PNL1  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.249  
**Date of Receipt:** 2019-11-19  
**Date of Test:** 2019-11-19 to 2019-11-26  
**Date of Issue:** 2019-11-27

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu  
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

| Revision Record |         |            |          |          |
|-----------------|---------|------------|----------|----------|
| Version         | Chapter | Date       | Modifier | Remark   |
| 01              |         | 2019-11-27 |          | Original |
|                 |         |            |          |          |
|                 |         |            |          |          |

|                                 |  |   |  |
|---------------------------------|--|---|--|
| <b>Authorized for issue by:</b> |  |   |  |
|                                 |  |    |  |
|                                 |  | Harry Wu /Project Engineer  |  |
|                                 |  |  |  |
|                                 |  | Eric Fu /Reviewer   |  |

## 2 Test Summary

| Radio Spectrum Technical Requirement |                                  |        |                                  |        |
|--------------------------------------|----------------------------------|--------|----------------------------------|--------|
| Item                                 | Standard                         | Method | Requirement                      | Result |
| Antenna Requirement                  | 47 CFR Part 15, Subpart C 15.249 | N/A    | 47 CFR Part 15, Subpart C 15.203 | Pass   |

| Radio Spectrum Matter Part                           |                                  |  |   |        |
|--|----------------------------------|--|---|--------|
| Item   | Standard                         | Method                                 | Requirement   | Result |
| Conducted Emissions at AC Power Line (150kHz-30MHz)  | 47 CFR Part 15, Subpart C 15.249 | ANSI C63.10 (2013) Section 6.2         | 47 CFR Part 15, Subpart C 15.207                      | Pass   |
| 20dB Bandwidth                                       | 47 CFR Part 15, Subpart C 15.249 | ANSI C63.10 (2013) Section 6.9         | 47 CFR Part 15, Subpart C 15.215                      | Pass   |
| Field Strength of the Fundamental Signal (15.249(a)) | 47 CFR Part 15, Subpart C 15.249 | ANSI C63.10 (2013) Section 6.5&6.6     | 47 CFR Part 15, Subpart C 15.249(a)                   | Pass   |
| Restricted Band Around Fundamental Frequency         | 47 CFR Part 15, Subpart C 15.249 | ANSI C63.10 (2013) Section 6.4&6.5&6.6 | 47 CFR Part 15, Subpart C 15.205 & 15.249(d) & 15.209 | Pass   |
| Radiated Emissions                                   | 47 CFR Part 15, Subpart C 15.249 | ANSI C63.10 (2013) Section 6.4&6.5&6.6 | 47 CFR Part 15, Subpart C 15.209 & 15.249 (a),(d)     | Pass   |

### 3 Contents

|   | Page |
|---|------|
| 1 COVER PAGE .....  | 1    |
| 2 TEST SUMMARY .....  | 3    |
| 3 CONTENTS .....  | 4    |
| 4 GENERAL INFORMATION .....                                   | 5    |
| 4.1 DETAILS OF E.U.T. ....                                    | 5    |
| 4.2 DESCRIPTION OF SUPPORT UNITS .....                        | 5    |
| 4.3 MEASUREMENT UNCERTAINTY .....                             | 5    |
| 4.4 TEST LOCATION.....  | 6    |
| 4.5 TEST FACILITY.....  | 6    |
| 4.6 DEVIATION FROM STANDARDS.....                             | 6    |
| 4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....              | 6    |
| 5 EQUIPMENT LIST.....   | 7    |
| 6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....                  | 10   |
| 6.1 ANTENNA REQUIREMENT .....                                 | 10   |
| 6.1.1 Test Requirement: .....                                 | 10   |
| 6.1.2 Conclusion .....  | 10   |
| 7 RADIO SPECTRUM MATTER TEST RESULTS.....                     | 11   |
| 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....  | 11   |
| 7.1.1 E.U.T. Operation .....                                  | 11   |
| 7.1.2 Measurement Procedure and Data.....                     | 11   |
| 7.2 20DB BANDWIDTH .....                                      | 14   |
| 7.2.1 E.U.T. Operation .....                                  | 14   |
| 7.2.2 Test Setup Diagram.....                                 | 14   |
| 7.2.3 Measurement Procedure and Data.....                     | 14   |
| 7.3 FIELD STRENGTH OF THE FUNDAMENTAL SIGNAL (15.249(A))..... | 16   |
| 7.3.1 E.U.T. Operation .....                                  | 16   |
| 7.3.2 Test Setup Diagram.....                                 | 16   |
| 7.3.3 Measurement Procedure and Data.....                     | 17   |
| 7.4 RESTRICTED BAND AROUND FUNDAMENTAL FREQUENCY .....        | 20   |
| 7.4.1 E.U.T. Operation .....                                  | 20   |
| 7.4.2 Test Setup Diagram.....                                 | 20   |
| 7.4.3 Measurement Procedure and Data.....                     | 21   |
| 7.5 RADIATED EMISSIONS .....                                  | 24   |
| 7.5.1 E.U.T. Operation .....                                  | 25   |
| 7.5.2 Test Setup Diagram.....                                 | 25   |
| 7.5.3 Measurement Procedure and Data.....                     | 25   |
| 8 PHOTOGRAPHS.....  | 30   |
| 8.1 TEST SETUP.....   | 30   |
| 8.2 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS).....              | 30   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch / 深圳分公司 / CSTC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 4 General Information

### 4.1 Details of E.U.T.

|                      |   |
|----------------------|---|
| Power Supply:        | Rechargeable Battery: DC3.8V, 19.76Wh<br>Or AC/DC Adapter, Model: SW-120250<br>Input: AC100-240V, 50/60Hz, 0.68A Max.<br>Output: DC 12.0V, 2.5A |
| Cable:               | DC Cable: 180cm, Unshielded   |
| Operation Frequency: | 908.4MHz  |
| Modulation Type:     | ASK   |
| Number of Channels:  | 1   |
| Antenna Type:        | Integral Antenna  |
| Antenna Gain:        | 0.67dBi   |

### 4.2 Description of Support Units

The EUT has been tested as an independent unit.

### 4.3 Measurement Uncertainty

| No. | Item                            | Measurement Uncertainty              |
|-----|---------------------------------|--------------------------------------|
| 1   | Radio Frequency                 | $\pm 7.25 \times 10^{-8}$            |
| 2   | Duty cycle                      | $\pm 0.37\%$                         |
| 3   | Occupied Bandwidth              | $\pm 3\%$                            |
| 4   | Conduction emission             | $\pm 3.0\text{dB}$ (150kHz to 30MHz) |
| 5   | RF conducted power              | $\pm 0.75\text{dB}$                  |
| 6   | Conducted Spurious emissions    | $\pm 0.75\text{dB}$                  |
| 7   | RF Radiated power               | $\pm 4.5\text{dB}$ (Below 1GHz)      |
|     |                                 | $\pm 4.8\text{dB}$ (Above 1GHz)      |
| 8   | Radiated Spurious emission test | $\pm 4.5\text{dB}$ (Below 1GHz)      |
|     |                                 | $\pm 4.8\text{dB}$ (Above 1GHz)      |
| 9   | Temperature test                | $\pm 1^\circ\text{C}$                |
| 10  | Humidity test                   | $\pm 3\%$                            |
| 11  | Supply voltages                 | $\pm 1.5\%$                          |
| 12  | Time                            | $\pm 3\%$                            |



#### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

#### 4.6 Deviation from Standards

None

#### 4.7 Abnormalities from Standard Conditions

None

## 5 Equipment List

| Conducted Emissions at AC Power Line (150kHz-30MHz) |                  |                 |              |            |              |
|---|------------------|-----------------|--------------|------------|--------------|
| Equipment   | Manufacturer     | Model No        | Inventory No | Cal Date   | Cal Due Date |
| Shielding Room                                      | ZhongYu Electron | GB-88           | SEM001-06    | 2019-06-13 | 2022-06-12   |
| Measurement Software                                | AUDIX            | e3 V8.2014-6-27 | N/A          | N/A        | N/A          |
| Coaxial Cable                                       | SGS              | N/A             | SEM024-01    | 2019-07-11 | 2020-07-10   |
| LISN  | Rohde & Schwarz  | ENV216          | SEM007-01    | 2019-09-24 | 2020-09-23   |
| LISN  | ETS-LINDGREN     | 3816/2          | SEM007-02    | 2019-04-01 | 2020-03-31   |
| EMI Test Receiver                                   | Rohde & Schwarz  | ESCI            | SEM004-02    | 2019-04-01 | 2020-03-31   |

| 20dB Bandwidth                       |                      |                      |              |            |              |
|--------------------------------------|----------------------|----------------------|--------------|------------|--------------|
| Equipment                            | Manufacturer         | Model No             | Inventory No | Cal Date   | Cal Due Date |
| Shielding Room                       | SAEMC                | MSR733               | SEM001-09    | 2019-06-13 | 2022-06-12   |
| DC Power Supply                      | Zhao Xin             | KXN-6020D            | SEM011-08    | 2019-09-24 | 2020-09-23   |
| Spectrum Analyzer                    | Rohde & Schwarz      | FSP                  | SEM004-06    | 2019-09-24 | 2020-09-23   |
| Measurement Software                 | JS Tonscend          | JS1120-2 BT/WIFI V2. | N/A          | N/A        | N/A          |
| Coaxial Cable                        | SGS                  | N/A                  | SEM031-02    | 2019-07-11 | 2020-07-10   |
| Attenuator                           | Weinschel Associates | WA41                 | SEM021-09    | N/A        | N/A          |
| Signal Generator                     | KEYSIGHT             | N5173B               | SEM006-05    | 2019-09-24 | 2020-09-23   |
| Power Meter                          | Rohde & Schwarz      | NRVS                 | SEM014-02    | 2019-09-24 | 2020-09-23   |
| Electric and Magnetic Field Analyzer | Narda                | NBM-550/EHP-50F      | EMC2143      | 2018-02-07 | 2020-02-06   |
| Electric Field Probe (100KHz-3GHz)   | WANDEL & GOLTERMANN  | EMR-20               | EMC0907      | 2019-05-21 | 2020-05-20   |
| EMF Tester                           | Narda                | ELT-400              | SZE039-4     | 2019-07-08 | 2020-07-07   |

| Field Strength of the Fundamental Signal (15.249(a)) |                      |                 |              |            |              |
|--|----------------------|-----------------|--------------|------------|--------------|
| Equipment  | Manufacturer         | Model No        | Inventory No | Cal Date   | Cal Due Date |
| 3m Semi-Anechoic Chamber                             | ETS-LINDGREN         | N/A             | SEM001-01    | 2017-08-05 | 2020-08-04   |
| Measurement Software                                 | AUDIX                | e3 V8.2014-6-27 | N/A          | N/A        | N/A          |
| Coaxial Cable  | SGS                  | N/A             | SEM025-01    | 2019-07-11 | 2020-07-10   |
| EMI Test Receiver                                    | Agilent Technologies | N9038A          | SEM004-05    | 2019-09-24 | 2020-09-23   |
| BiConiLog Antenna (26-3000MHz)                       | ETS-LINDGREN         | 3142C           | SEM003-01    | 2017-06-27 | 2020-06-26   |
| Pre-amplifier (0.1-1300MHz)                          | Agilent Technologies | 8447D           | SEM005-01    | 2019-04-01 | 2020-03-31   |

| Restricted Band Around Fundamental Frequency |                                    |                 |              |            |              |
|--|------------------------------------|-----------------|--------------|------------|--------------|
| Equipment                                    | Manufacturer                       | Model No        | Inventory No | Cal Date   | Cal Due Date |
| 3m Semi-Anechoic Chamber                     | AUDIX                              | N/A             | SEM001-02    | 2018-03-13 | 2021-03-12   |
| Measurement Software                         | AUDIX                              | e3 V8.2014-6-27 | N/A          | N/A        | N/A          |
| Coaxial Cable                                | SGS                                | N/A             | SEM026-01    | 2019-07-11 | 2020-07-10   |
| EXA Spectrum Analyzer                        | AgilentTechnologies Inc            | N9010A          | SEM004-12    | 2019-04-12 | 2020-04-11   |
| Horn Antenna (1-18GHz)                       | Rohde & Schwarz                    | HF907           | SEM003-07    | 2018-04-13 | 2021-04-12   |
| Horn Antenna (15GHz-40GHz)                   | Schwarzbeck                        | BBHA 9170       | SEM003-15    | 2017-10-17 | 2020-10-16   |
| Pre-Amplifier (0.1-26.5GHz)                  | Compliance Directions Systems Inc. | PAP-0126        | SEM004-11    | 2019-09-24 | 2020-09-23   |
| Pre-amplifier(18-26GHz)                      | Rohde & Schwarz                    | CH14-H052       | SEM005-17    | 2019-04-01 | 2020-03-31   |
| Pre-amplifier (26GHz-40GHz)                  | Compliance Directions Systems Inc. | PAP-2640-50     | SEM005-08    | 2019-04-01 | 2020-03-31   |
| DC Power Supply                              | Zhao Xin                           | KXN-6020D       | SEM011-08    | 2019-09-24 | 2020-09-23   |
| Active Loop Antenna                          | ETS-Lindgren                       | 6502            | SEM003-08    | 2017-08-22 | 2020-08-21   |

| Radiated Spurious Emissions |                                    |                 |              |            |              |
|-----------------------------|------------------------------------|-----------------|--------------|------------|--------------|
| Equipment                   | Manufacturer                       | Model No        | Inventory No | Cal Date   | Cal Due Date |
| 3m Semi-Anechoic Chamber    | AUDIX                              | N/A             | SEM001-02    | 2018-03-13 | 2021-03-12   |
| Measurement Software        | AUDIX                              | e3 V8.2014-6-27 | N/A          | N/A        | N/A          |
| Coaxial Cable               | SGS                                | N/A             | SEM026-01    | 2019-07-11 | 2020-07-10   |
| EXA Spectrum Analyzer       | AgilentTechnologies Inc            | N9010A          | SEM004-12    | 2019-04-12 | 2020-04-11   |
| Horn Antenna (1-18GHz)      | Rohde & Schwarz                    | HF907           | SEM003-07    | 2018-04-13 | 2021-04-12   |
| Horn Antenna (15GHz-40GHz)  | Schwarzbeck                        | BBHA 9170       | SEM003-15    | 2017-10-17 | 2020-10-16   |
| Pre-Amplifier (0.1-26.5GHz) | Compliance Directions Systems Inc. | PAP-0126        | SEM004-11    | 2019-09-24 | 2020-09-23   |
| Pre-amplifier(18-26GHz)     | Rohde & Schwarz                    | CH14-H052       | SEM005-17    | 2019-04-01 | 2020-03-31   |
| Pre-amplifier (26GHz-40GHz) | Compliance Directions Systems Inc. | PAP-2640-50     | SEM005-08    | 2019-04-01 | 2020-03-31   |
| DC Power Supply             | Zhao Xin                           | KXN-6020D       | SEM011-08    | 2019-09-24 | 2020-09-23   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (SGS-CSTC) Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



|                     |              |      |           |            |            |
|---------------------|--------------|------|-----------|------------|------------|
| Active Loop Antenna | ETS-Lindgren | 6502 | SEM003-08 | 2017-08-22 | 2020-08-21 |
|---------------------|--------------|------|-----------|------------|------------|

| Radiated Emissions             |                      |                 |              |            |              |
|--------------------------------|----------------------|-----------------|--------------|------------|--------------|
| Equipment                      | Manufacturer         | Model No        | Inventory No | Cal Date   | Cal Due Date |
| 3m Semi-Anechoic Chamber       | ETS-LINDGREN         | N/A             | SEM001-01    | 2017-08-05 | 2020-08-04   |
| Measurement Software           | AUDIX                | e3 V8.2014-6-27 | N/A          | N/A        | N/A          |
| Coaxial Cable                  | SGS                  | N/A             | SEM025-01    | 2019-07-11 | 2020-07-10   |
| EMI Test Receiver              | Agilent Technologies | N9038A          | SEM004-05    | 2019-09-24 | 2020-09-23   |
| BiConiLog Antenna (26-3000MHz) | ETS-LINDGREN         | 3142C           | SEM003-01    | 2017-06-27 | 2020-06-26   |
| Pre-amplifier (0.1-1300MHz)    | Agilent Technologies | 8447D           | SEM005-01    | 2019-04-01 | 2020-03-31   |

| General used equipment          |   |          |              |            |              |
|---------------------------------|---|----------|--------------|------------|--------------|
| Equipment                       | Manufacturer                              | Model No | Inventory No | Cal Date   | Cal Due Date |
| Humidity/ Temperature Indicator | Shanghai Meteorological Industry Factory  | ZJ1-2B   | SEM002-03    | 2019-09-26 | 2020-09-25   |
| Humidity/ Temperature Indicator | Shanghai Meteorological Industry Factory  | ZJ1-2B   | SEM002-04    | 2019-09-26 | 2020-09-25   |
| Humidity/ Temperature Indicator | Mingle                                    | N/A      | SEM002-08    | 2019-09-26 | 2020-09-25   |
| Barometer                       | Changchun Meteorological Industry Factory | DYM3     | SEM002-01    | 2019-04-04 | 2020-04-03   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (Central Service EEC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.67dBi.

Antenna location: Refer to Appendix(Internal photos)





## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207  
Test Method: ANSI C63.10 (2013) Section 6.2  
Limit:

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 20.7 °C Humidity: 56.9 % RH Atmospheric Pressure: 1015 mbar  
Test mode e:Charge + TX mode(908.4MHz)\_Keep the EUT in charging and transmitting with modulation mode.

#### 7.1.2 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode:e; Line:Live Line




Site : Shielding Room  
Condition: Line  
Job No. : 20336CR  
Test mode: e

|    | Freq  | Cable Loss | LISN Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|----|-------|------------|-------------|------------|-------|------------|------------|---------|
|    | MHz   | dB         | dB          | dBuV       | dBuV  | dBuV       | dB         |         |
| 1  | 0.20  | 0.02       | 9.51        | 14.65      | 24.18 | 53.67      | -29.49     | Average |
| 2  | 0.20  | 0.02       | 9.51        | 31.86      | 41.39 | 63.67      | -22.28     | QP      |
| 3  | 0.25  | 0.03       | 9.53        | 20.13      | 29.69 | 51.69      | -22.00     | Average |
| 4  | 0.25  | 0.03       | 9.53        | 28.06      | 37.62 | 61.69      | -24.07     | QP      |
| 5  | 0.41  | 0.05       | 9.58        | 17.84      | 27.47 | 47.55      | -20.08     | Average |
| 6  | 0.41  | 0.05       | 9.58        | 27.58      | 37.21 | 57.55      | -20.34     | QP      |
| 7  | 1.15  | 0.10       | 9.64        | 19.17      | 28.91 | 46.00      | -17.09     | Average |
| 8  | 1.15  | 0.10       | 9.64        | 27.19      | 36.93 | 56.00      | -19.07     | QP      |
| 9  | 2.31  | 0.16       | 9.65        | 13.02      | 22.83 | 46.00      | -23.17     | Average |
| 10 | 2.31  | 0.16       | 9.65        | 18.34      | 28.15 | 56.00      | -27.85     | QP      |
| 11 | 11.38 | 0.18       | 9.83        | 22.84      | 32.85 | 50.00      | -17.15     | Average |
| 12 | 11.38 | 0.18       | 9.83        | 28.32      | 38.33 | 60.00      | -21.67     | QP      |



Mode:e; Line:Neutral Line



Site : Shielding Room  
Condition: Neutral  
Job No. : 20336CR  
Test mode: e

|    | Freq  | Cable Loss | LISN Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|----|-------|------------|-------------|------------|-------|------------|------------|---------|
|    | MHz   | dB         | dB          | dBuV       | dBuV  | dBuV       | dB         |         |
| 1  | 0.20  | 0.02       | 9.45        | 14.45      | 23.92 | 53.54      | -29.62     | Average |
| 2  | 0.20  | 0.02       | 9.45        | 29.24      | 38.71 | 63.54      | -24.83     | QP      |
| 3  | 0.26  | 0.03       | 9.48        | 12.70      | 22.21 | 51.29      | -29.08     | Average |
| 4  | 0.26  | 0.03       | 9.48        | 26.23      | 35.74 | 61.29      | -25.55     | QP      |
| 5  | 0.99  | 0.09       | 9.66        | 18.34      | 28.09 | 46.00      | -17.91     | Average |
| 6  | 0.99  | 0.09       | 9.66        | 25.76      | 35.51 | 56.00      | -20.49     | QP      |
| 7  | 1.16  | 0.10       | 9.67        | 23.60      | 33.37 | 46.00      | -12.63     | Average |
| 8  | 1.16  | 0.10       | 9.67        | 33.50      | 43.27 | 56.00      | -12.73     | QP      |
| 9  | 2.04  | 0.16       | 9.70        | 15.16      | 25.02 | 46.00      | -20.98     | Average |
| 10 | 2.04  | 0.16       | 9.70        | 20.10      | 29.96 | 56.00      | -26.04     | QP      |
| 11 | 11.62 | 0.18       | 9.93        | 18.57      | 28.68 | 50.00      | -21.32     | Average |
| 12 | 11.62 | 0.18       | 9.93        | 24.52      | 34.63 | 60.00      | -25.37     | QP      |



## 7.2 20dB Bandwidth


Test Requirement 47 CFR Part 15, Subpart C 15.215  
Test Method: ANSI C63.10 (2013) Section 6.9  
Limit: N/A

### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 21.6 °C Humidity: 43.8 % RH Atmospheric Pressure: 1015 mbar  
Test mode d:TX mode(908.4MHz)\_Keep the EUT in transmitting with modulation mode.


### 7.2.2 Test Setup Diagram



### 7.2.3 Measurement Procedure and Data



| Test channel | 20dB Bandwidth (KHz) | Limit (KHz) |
|--------------|----------------------|-------------|
| 904.8MHz     | 87.019               | N/A         |



### 7.3 Field Strength of the Fundamental Signal (15.249(a))

Test Requirement 47 CFR Part 15, Subpart C 15.249(a)  
 Test Method: ANSI C63.10 (2013) Section 6.5&6.6  
 Measurement Distance: 3m  
 Limit:

| Fundamental frequency(MHz) | Field strength of fundamental(millivolts/meter) | Field strength of harmonics(microvolts/meter) |
|----------------------------|---|---|
| 902-928                    | 50  | 500   |
| 2400-2483.5                | 50  | 500   |
| 5725-5875                  | 50  | 500   |
| 24000-24250                | 250   | 2500  |


Remark: The frequencies above 1000MHz are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.  
 For fundamental frequency in "902-928MHz", the field strength of fundamental is based on Quasi-Peak.

#### 7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C Humidity: 55 % RH Atmospheric Pressure: 1015 mbar  
 Pretest these d:TX mode(908.4MHz)\_Keep the EUT in transmitting with modulation mode.  
 modes to find e:Charge + TX mode(908.4MHz)\_Keep the EUT in charging and transmitting with  
 the worst case: modulation mode.  
 The worst case e:Charge + TX mode(908.4MHz)\_Keep the EUT in charging and transmitting with  
 for final test: modulation mode.

#### 7.3.2 Test Setup Diagram







### 7.3.3 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Mode: e; Polarization: Horizontal; Detector:QP




Condition: 3m HORIZONTAL

Job No. : 20336CR

Test mode: TX

|      | Freq   | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over   |
|------|--------|------------|------------|---------------|------------|--------|--------|--------|
|      | MHz    | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m | dB     |
| 1    | 902.00 | 3.60       | 29.81      | 27.28         | 26.82      | 32.95  | 46.00  | -13.05 |
| 2 pp | 908.40 | 3.61       | 29.84      | 27.26         | 83.19      | 89.38  | 94.00  | -4.62  |
| 3    | 928.00 | 3.63       | 29.95      | 27.18         | 26.57      | 32.97  | 46.00  | -13.03 |

Mode :e; Polarization: Vertical, Detector:QP



Condition: 3m VERTICAL

Job No. : 20336CR

Test mode: TX

|      |        | Cable | Ant    | Preamp | Read  |        | Limit  | Over   |
|------|--------|-------|--------|--------|-------|--------|--------|--------|
|      | Freq   | Loss  | Factor | Factor | Level | Level  | Line   | Limit  |
|      | MHz    | dB    | dB/m   | dB     | dBuV  | dBuV/m | dBuV/m | dB     |
| 1 pp | 902.00 | 3.60  | 29.81  | 27.28  | 28.01 | 34.14  | 46.00  | -11.86 |
| 2    | 908.40 | 3.61  | 29.84  | 27.26  | 75.71 | 81.90  | 94.00  | -12.10 |
| 3    | 928.00 | 3.63  | 29.95  | 27.18  | 27.50 | 33.90  | 46.00  | -12.10 |

## 7.4 Restricted Band Around Fundamental Frequency

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.249(d) & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6

Limit:

| Frequency     | Limit (dBuV/m @3m) | Remark           |
|---------------|--------------------|------------------|
| 30MHz-88MHz   | 40.0               | Quasi-peak Value |
| 88MHz-216MHz  | 43.5               | Quasi-peak Value |
| 216MHz-960MHz | 46.0               | Quasi-peak Value |
| 960MHz-1GHz   | 54.0               | Quasi-peak Value |
| Above 1GHz    | 54.0               | Average Value    |
| Above 1GHz    | 74.0               | Peak Value       |

Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

### 7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 23 °C Humidity: 55 % RH Atmospheric Pressure: 1015 mbar

Pretest these d:TX mode(908.4MHz)\_Keep the EUT in transmitting with modulation mode.

the worst case: e:Charge + TX mode(908.4MHz)\_Keep the EUT in charging and transmitting with modulation mode.

### 7.4.2 Test Setup Diagram







#### 7.4.3 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Mode: e; Polarization: Horizontal; Detector:QP




Condition: 3m HORIZONTAL

Job No. : 20336CR

Test mode: TX

|      | Freq   | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over   |
|------|--------|------------|------------|---------------|------------|--------|--------|--------|
|      | MHz    | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m | dB     |
| 1    | 902.00 | 3.60       | 29.81      | 27.28         | 26.82      | 32.95  | 46.00  | -13.05 |
| 2 pp | 908.40 | 3.61       | 29.84      | 27.26         | 83.19      | 89.38  | 94.00  | -4.62  |
| 3    | 928.00 | 3.63       | 29.95      | 27.18         | 26.57      | 32.97  | 46.00  | -13.03 |

Mode :e; Polarization: Vertical,Detector:QP



Condition: 3m VERTICAL

Job No. : 20336CR

Test mode: TX

|      |        | Cable | Ant    | Preamp | Read  |        | Limit  | Over   |
|------|--------|-------|--------|--------|-------|--------|--------|--------|
|      | Freq   | Loss  | Factor | Factor | Level | Level  | Line   | Limit  |
|      | MHz    | dB    | dB/m   | dB     | dBuV  | dBuV/m | dBuV/m | dB     |
| 1 pp | 902.00 | 3.60  | 29.81  | 27.28  | 28.01 | 34.14  | 46.00  | -11.86 |
| 2    | 908.40 | 3.61  | 29.84  | 27.26  | 75.71 | 81.90  | 94.00  | -12.10 |
| 3    | 928.00 | 3.63  | 29.95  | 27.18  | 27.50 | 33.90  | 46.00  | -12.10 |



## 7.5 Radiated Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.249 (a),(d)  
Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6  
Limit:

| Frequency(MHz) | Field strength<br>(microvolts/meter) | Limit<br>(dBuV/m) | Detector | Measurement Distance<br>(meters) |
|----------------|--------------------------------------|-------------------|----------|----------------------------------|
| 0.009-0.490    | 2400/F(kHz)                          | -                 | -        | 300                              |
| 0.490-1.705    | 24000/F(kHz)                         | -                 | -        | 30                               |
| 1.705-30       | 30                                   | -                 | -        | 30                               |
| 30-88          | 100                                  | 40.0              | QP       | 3                                |
| 88-216         | 150                                  | 43.5              | QP       | 3                                |
| 216-960        | 200                                  | 46.0              | QP       | 3                                |
| 960-1000       | 500                                  | 54.0              | QP       | 3                                |
| Above 1000     | 500                                  | 54.0              | AV       | 3                                |





### 7.5.1 E.U.T. Operation

Operating Environment:


Temperature: 23 °C Humidity: 55 % RH Atmospheric Pressure: 1015 mbar

Pretest these d:TX mode(908.4MHz)\_Keep the EUT in transmitting with modulation mode.

modes to find e:Charge + TX mode(908.4MHz)\_Keep the EUT in charging and transmitting with the worst case: modulation mode.

The worst case e:Charge + TX mode(908.4MHz)\_Keep the EUT in charging and transmitting with for final test: modulation mode.

### 7.5.2 Test Setup Diagram




### 7.5.3 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.

### Below 1GHz

QP value:

Mode: e; Polarization: Horizontal;




Condition: 3m HORIZONTAL

Job No. : 20336CR

Test mode: e

|      | Freq   | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over  |
|------|--------|------------|------------|---------------|------------|--------|--------|-------|
|      | MHz    | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m | dB    |
| 1    | 65.34  | 0.80       | 12.98      | 27.67         | 47.02      | 33.13  | 40.00  | -6.87 |
| 2    | 121.98 | 1.26       | 13.16      | 27.50         | 51.11      | 38.03  | 43.50  | -5.47 |
| 3    | 137.90 | 1.29       | 13.64      | 27.42         | 47.20      | 34.71  | 43.50  | -8.79 |
| 4    | 176.89 | 1.36       | 15.84      | 27.25         | 46.19      | 36.14  | 43.50  | -7.36 |
| 5 pp | 258.33 | 1.71       | 19.08      | 26.99         | 48.08      | 41.88  | 46.00  | -4.12 |
| 6    | 377.26 | 2.14       | 21.83      | 27.31         | 41.95      | 38.61  | 46.00  | -7.39 |

Mode :e; Polarization: Vertical



Condition: 3m VERTICAL


Job No. : 20336CR

Test mode: e

|      | Freq   | Cable | Ant    | Preamp | Read  | Limit  | Over   |
|------|--------|-------|--------|--------|-------|--------|--------|
|      | MHz    | Loss  | Factor | Factor | Level | Line   | Limit  |
|      | MHz    | dB    | dB/m   | dB     | dBuV  | dBuV/m | dBuV/m |
| 1    | 50.23  | 0.80  | 14.17  | 27.69  | 49.03 | 36.31  | 40.00  |
| 2 pp | 65.34  | 0.80  | 12.98  | 27.67  | 50.22 | 36.33  | 40.00  |
| 3    | 108.65 | 1.22  | 13.59  | 27.58  | 51.16 | 38.39  | 43.50  |
| 4    | 137.90 | 1.29  | 13.64  | 27.42  | 48.99 | 36.50  | 43.50  |
| 5    | 178.76 | 1.37  | 15.88  | 27.24  | 49.34 | 39.35  | 43.50  |
| 6    | 255.62 | 1.70  | 19.04  | 27.00  | 42.44 | 36.18  | 46.00  |

**Above 1GHz**

Mode: e; Polarization: Horizontal;




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20336CR  
Mode : e

|   | Freq     | Cable Loss | Ant Factor | Preamplifier Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|----------|------------|------------|---------------------|------------|--------|------------|------------|--------|
|   | MHz      | dB         | dB/m       | dB                  | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 1093.580 | 3.98       | 24.09      | 40.19               | 50.33      | 38.21  | 74.00      | -35.79     | Peak   |
| 2 | 1879.802 | 5.02       | 27.37      | 40.73               | 48.53      | 40.19  | 74.00      | -33.81     | Peak   |
| 3 | 3498.705 | 6.46       | 31.70      | 41.71               | 49.28      | 45.73  | 74.00      | -28.27     | Peak   |
| 4 | 4112.010 | 7.12       | 32.91      | 42.25               | 50.48      | 48.26  | 74.00      | -25.74     | Peak   |
| 5 | 5582.046 | 9.14       | 34.69      | 42.50               | 49.00      | 50.33  | 74.00      | -23.67     | Peak   |
| 6 | 8286.731 | 10.14      | 36.87      | 40.70               | 47.48      | 53.79  | 74.00      | -20.21     | Peak   |



Mode :e; Polarization: Vertical



Site : chamber  
Condition: 3m VERTICAL  
Job No : 20336CR  
Mode : e

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over Limit | Remark |
|---|----------|------------|------------|---------------|------------|--------|--------|------------|--------|
|   | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m | dB         |        |
| 1 | 1307.831 | 4.83       | 25.06      | 40.37         | 50.56      | 40.08  | 74.00  | -33.92     | Peak   |
| 2 | 2458.463 | 5.57       | 28.63      | 41.00         | 48.72      | 41.92  | 74.00  | -32.08     | Peak   |
| 3 | 3649.669 | 6.62       | 32.01      | 41.85         | 49.32      | 46.10  | 74.00  | -27.90     | Peak   |
| 4 | 4761.303 | 7.84       | 33.92      | 42.74         | 48.96      | 47.98  | 74.00  | -26.02     | Peak   |
| 5 | 7748.995 | 9.97       | 36.50      | 41.32         | 47.89      | 53.04  | 74.00  | -20.96     | Peak   |
| 6 | 9198.327 | 10.52      | 37.36      | 39.20         | 45.22      | 53.90  | 74.00  | -20.10     | Peak   |



## 8 Photographs

### 8.1 Test Setup

Please refer to setup photos.

### 8.2 EUT Constructional Details (EUT Photos)

Please refer to external and internal photos for details.

- End of the Report -

