



Shenzhen CTL Testing Technology Co., Ltd.  
Tel: +86-755-89486194 Fax: +86-755-26636041

## FCC PART 15 SUBPART C TEST REPORT

### FCC PART 15.247

Report Reference No.: **CTL1507171986-WF**

Compiled by:  
( position+printed name+signature) **Jacky Chen**  
(File administrators)

Tested by:  
( position+printed name+signature) **Allen Wang**  
(Test Engineer)

Approved by:  
( position+printed name+signature) **Tracy Qi**  
(Manager)

*Jacky Chen*

*Allen Wang*

*Tracy Qi*

**Product Name**: Mighty Bluetooth Speaker

**Model/Type reference**: 136796

**List Model(s)**: /

**Trade Mark**: /

**FCC ID**: 2AC9N-136796

**Applicant's name**: Cotton On USA Inc

**Address of applicant**: 16511, Trojan Way, La Miranda, California 90638, United States

**Test Firm**: Shenzhen CTL Testing Technology Co., Ltd.

**Address of Test Firm**: Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

**Test specification**:

**Standard**: FCC Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz.

**TRF Originator**: Shenzhen CTL Testing Technology Co., Ltd.

**Master TRF**: Dated 2011-01

**Date of Receipt**: July 15, 2015

**Date of Test Date**: July 16, 2015 –July 23, 2015

**Data of Issue**: July 24, 2015

**Result**: Positive

**Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

# TEST REPORT

<b>Test Report No. :</b>	<b>CTL1507171986-WF</b>	July, 24, 2015 Date of issue
--------------------------	-------------------------	---------------------------------

Equipment under Test : Mighty Bluetooth Speaker

Model /Type : 136796

Listed Models : /

**Applicant** : **Cotton On USA Inc**

Address : 16511, Trojan Way, La Mirinda, California 90638,  
United States

**Manufacturer** : **Cotton On USA Inc**

Address : 16511, Trojan Way, La Mirinda, California 90638,  
United States

<b>Test result</b>	<b>Pass *</b>
--------------------	---------------

\*In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## **\*\* Modified History \*\***



	Table of Contents	Page
<b>1. SUMMARY.....</b>		<b>5</b>
1.1. TEST STANDARDS.....		5
1.2. TEST DESCRIPTION.....		5
1.3. TEST FACILITY .....		6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....		6
<b>2. GENERAL INFORMATION.....</b>		<b>7</b>
2.1. ENVIRONMENTAL CONDITIONS .....		7
2.2. GENERAL DESCRIPTION OF EUT .....		7
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY.....		7
2.4. EQUIPMENTS USED DURING THE TEST .....		8
2.5. RELATED SUBMITTAL(S) / GRANT (S) .....		8
2.6. MODIFICATIONS.....		8
<b>3. TEST CONDITIONS AND RESULTS .....</b>		<b>9</b>
3.1. CONDUCTED EMISSIONS TEST .....		9
3.2. RADIATED EMISSIONS AND BAND EDGE .....		12
3.3. MAXIMUM PEAK OUTPUT POWER .....		18
3.4. 20DB BANDWIDTH.....		19
3.5. FREQUENCY SEPARATION .....		22
3.6. NUMBER OF HOPPING FREQUENCY.....		24
3.7. TIME OF OCCUPANCY (DWELL TIME).....		26
3.8. OUT-OF-BAND EMISSIONS .....		29
3.9. PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....		34
3.10. ANTENNA REQUIREMENT.....		35
<b>4. TEST SETUP PHOTOS OF THE EUT .....</b>		<b>36</b>
<b>5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</b>		<b>38</b>



# 1. SUMMARY

## 1.1. TEST STANDARDS


The tests were performed according to following standards:

**FCC Rules Part 15.247:** Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

**ANSI C63.10:** American National Standard for Testing Unlicensed Wireless Devices

## 1.2. Test Description

<b>FCC PART 15.247</b>		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(1)(i)	20dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Peak Output Power	PASS
FCC Part 15.247(b)	Pseudorandom Frequency Hopping Sequence	PASS
FCC Part 15.247(a)(1)(iii)	Number of hopping frequency& Time of Occupancy	PASS
FCC Part 15.247(a)(1)	Frequency Separation	PASS
FCC Part 15.205/15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge Compliance of RF Emission	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS



## 1.3. Test Facility

### 1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

### 1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

#### IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

#### FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

## 1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)
Conducted Disturbance 0.15~30MHz	±3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2. GENERAL INFORMATION

### 2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

### 2.2. General Description of EUT

Product Name:	Mighty Bluetooth Speaker
Model/Type reference:	136796
Power supply:	DC 3.7V from adapter
<b>Bluetooth :</b>	
Version:	Supported BT2.1+EDR
Modulation:	GFSK, π/4DQPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PCB Antenna
Antenna gain:	-0.68dBi

Note: For more details, please refer to the user's manual of the EUT.

### 2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

#### Operation Frequency :

Channel	Frequency (MHz)
00	2402
01	2403
:	:
38	2440
39	2441
40	2442
:	:
77	2479
78	2480

Preliminary tests were performed in each mode and packet length of BT, and found worst case as bellow, finally test were conducted at those mode and recorded in this report.

Test Items	Worst case
Conducted Emissions	DH5 Middle channel
Radiated Emissions and Band Edge	DH5
Maximum Conducted Output Power	DH5/2DH5
20dB Bandwidth	DH5/2DH5
Frequency Separation	DH5/2DH5 Middle channel
Number of hopping frequency	DH5/2DH5
Time of Occupancy (Dwell Time)	DH1/DH3/DH5 Middle channel 2DH1/2DH3/2DH5 Middle channel
Out-of-band Emissions	DH5/2DH5

## 2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2015/06/02	2016/06/01
EMI Test Receiver	R&S	ESCI	103710	2015/06/02	2016/06/01
Spectrum Analyzer	Agilent	E4407B	MY41440676	2015/05/21	2016/05/20
Power Meter	Anritsu	ML2487B	110553	2015/06/02	2016/06/01
Power Sensor	Anritsu	MA2411B	100345	2015/05/21	2016/05/20
Controller	EM Electronics	Controller EM 1000	N/A	2015/05/21	2016/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2015/05/19	2016/05/18
Active Loop Antenna	SCHWARZBEC K	FMZB1519	1519-037	2015/05/19	2016/05/18
LISN	R&S	ENV216	3560.6550.12	2015/06/02	2016/06/01
LISN	R&S	ESH2-Z5	860014/010	2015/06/02	2016/06/01
Amplifier	Agilent	8349B	3008A02306	2015/05/19	2016/05/18
Amplifier	Agilent	8447D	2944A10176	2015/05/19	2016/05/18
Transient Limiter	SCHWARZCECK	VTSD 9561F	9666	2015/06/02	2016/06/01
Temperature/Humidity Meter	Gangxing	CTH-608	02	2015/05/20	2016/05/19

The calibration interval was one year

## 2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID:2AC9N-136796 filing to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

## 2.6. Modifications

No modifications were implemented to meet testing criteria.

### 3. TEST CONDITIONS AND RESULTS

#### 3.1. Conducted Emissions Test


##### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

##### TEST CONFIGURATION




##### TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

**TEST RESULTS**

**SCAN TABLE: "Voltage (9K-30M) FIN"**  
 Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "CTL150720500\_fin"**

7/20/2015 2:12PM


Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Detector	Line	PE
0.177001	42.60	10.2	65	22.0	QP	L1	GND
0.217501	33.80	10.2	63	29.1	QP	L1	GND
0.226501	36.40	10.2	63	26.2	QP	L1	GND
0.276001	38.50	10.2	61	22.4	QP	L1	GND
0.361501	32.80	10.2	59	25.9	QP	L1	GND
24.243001	26.60	11.1	60	33.4	QP	L1	GND

**MEASUREMENT RESULT: "CTL150720500\_fin2"**

7/20/2015 2:12PM

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Detector	Line	PE
1.252501	28.50	10.3	46	17.5	AV	L1	GND
2.089501	29.00	10.4	46	17.0	AV	L1	GND
2.926501	28.30	10.4	46	17.7	AV	L1	GND
3.759001	27.10	10.4	46	18.9	AV	L1	GND
23.707501	19.90	11.1	50	30.1	AV	L1	GND
24.238501	25.20	11.1	50	24.8	AV	L1	GND

**SCAN TABLE: "Voltage (9K-30M) FIN"**  
 Short Description: 150K-30M Voltage



**MEASUREMENT RESULT: "CTL150720501\_fin"**

7/20/2015 2:16PM

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Detector	Line	PE
0.159001	43.50	10.2	66	22.0	QP	N	GND
0.181501	43.50	10.2	64	20.9	QP	N	GND
0.271501	36.30	10.2	61	24.8	QP	N	GND
22.506001	29.20	11.0	60	30.8	QP	N	GND
23.824501	37.00	11.1	60	23.0	QP	N	GND
26.416501	31.40	11.2	60	28.6	QP	N	GND

**MEASUREMENT RESULT: "CTL150720501\_fin2"**

7/20/2015 2:16PM

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Detector	Line	PE
0.420001	27.60	10.2	47	19.8	AV	N	GND
1.252501	28.10	10.3	46	17.9	AV	N	GND
2.089501	28.80	10.4	46	17.2	AV	N	GND
2.926501	28.90	10.4	46	17.1	AV	N	GND
3.763501	28.70	10.4	46	17.3	AV	N	GND
4.600501	28.10	10.4	46	17.9	AV	N	GND

### 3.2. Radiated Emissions and Band Edge

#### Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB $\mu$ V/m)	Radiated ( $\mu$ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

#### TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



## (C) Radiated Emission Test Set-Up, Frequency above 1000MHz

**Test Procedure**

1. The EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.

**TEST RESULTS**

Remark:

1. We tested three channels (lowest/middle/highest) of each mode and recorded worst case at DH5 low channel for measurement below 1GHz.
2. We tested three channels (lowest/middle/highest) of each mode and recorded worst case at DH5 mode above 1GHz.

**For 9 KHz-30MHz**


Frequency (MHz)	Corrected Reading (dBuV/m)@3m	FCC Limit (dBuV/m) @3m	Margin (dB)	Detector	Result
0.16	48.26	103.52	55.26	QP	PASS
1.55	54.54	63.80	9.26	QP	PASS
15.69	56.98	69.54	12.56	QP	PASS
25.78	48.22	69.54	21.32	QP	PASS

## For 30MHz-1GHz

## Horizontal

**SWEEP TABLE: "test (30M-1G)"**

Start Frequency	Stop Frequency	Detector	Meas.	IF Time	Transducer	Field Strength
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	JB1	

Level [dB $\mu$ V/m]

x x x MES CTL150718125\_red

**MEASUREMENT RESULT: "CTL150718125\_red"**


7/18/2015 2:34PM

Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
127.000000	34.50	15.0	43.5	9.0	---	0.0	0.00	HORIZONTAL
297.720000	41.70	15.4	46.0	4.3	---	0.0	0.00	HORIZONTAL
346.220000	40.30	16.8	46.0	5.7	---	0.0	0.00	HORIZONTAL
361.740000	41.20	17.4	46.0	4.8	---	0.0	0.00	HORIZONTAL
373.380000	40.50	17.7	46.0	5.5	---	0.0	0.00	HORIZONTAL
480.080000	40.70	20.1	46.0	5.3	---	0.0	0.00	HORIZONTAL

## Vertical

**SWEEP TABLE: "test (30M-1G)"**

Start Frequency	Stop Frequency	Detector	Meas.	IF Time	Transducer	Field Strength
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	JB1	

Level [dB $\mu$ V/m]

x x x MES CTL150718126\_red

**MEASUREMENT RESULT: "CTL150718126\_red"**

7/18/2015 2:36PM

Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
68.800000	32.70	8.4	40.0	7.3	---	0.0	0.00	VERTICAL
95.960000	34.40	10.6	43.5	9.1	---	0.0	0.00	VERTICAL
109.540000	37.30	13.7	43.5	6.2	---	0.0	0.00	VERTICAL
303.540000	37.40	15.5	46.0	8.6	---	0.0	0.00	VERTICAL
315.180000	36.80	15.8	46.0	9.2	---	0.0	0.00	VERTICAL
530.520000	37.30	20.5	46.0	8.7	---	0.0	0.00	VERTICAL

For 1GHz to 25GHz

**GFSK (above 1GHz)**

Frequency(MHz):			2402		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2402.00	93.26 PK	--	--	59.86	28.78	4.61	0.00	33.40
1	2402.00	84.58 AV	--	--	51.18	28.78	4.61	0.00	33.40
2	2390.00	36.47 PK	74	37.53	3.15	28.72	4.60	0.00	33.32
2	2390.00	-- AV	54	--	--	--	--	--	--
3	2400.00	43.65 PK	74	30.35	10.26	28.78	4.61	0.00	33.39
3	2400.00	-- AV	54	--	--	--	--	--	--
4	4804.00	55.26 PK	74	18.74	50.75	33.49	6.91	35.89	4.51
4	4804.00	43.45 AV	54	10.55	38.94	33.49	6.91	35.89	4.51
5	5025.50	45.14 PK	74	28.86	38.26	34.07	7.05	34.24	6.88
5	5025.50	-- AV	54	--	--	--	--	--	--
6	7206.00	48.45 PK	74	25.55	37.34	36.95	9.18	35.03	11.11
6	7206.00	-- AV	54	--	--	--	--	--	--

**GFSK (above 1GHz)**

Frequency(MHz):			2402		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2402.00	94.44 PK	--	--	61.04	28.78	4.61	0.00	33.40
1	2402.00	85.98 AV	--	--	52.58	28.78	4.61	0.00	33.40
2	2390.00	37.65 PK	74	36.35	4.33	28.72	4.60	0.00	33.32
2	2390.00	-- AV	54	--	--	--	--	--	--
3	2400.00	44.20 PK	74	29.8	10.81	28.78	4.61	0.00	33.39
3	2400.00	-- AV	54	--	--	--	--	--	--
4	4804.00	55.74 PK	74	18.26	51.23	33.49	6.91	35.89	4.51
4	4804.00	46.35 AV	54	7.65	41.84	33.49	6.91	35.89	4.51
5	5115.20	43.84 PK	74	30.16	36.65	34.36	7.10	34.27	7.19
5	5115.20	-- AV	54	--	--	--	--	--	--
6	7206.00	46.87 PK	74	27.13	35.76	36.95	9.18	35.03	11.11
6	7206.00	-- AV	54	--	--	--	--	--	--

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

Frequency(MHz):			2441		Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)	
1	2441.00	94.65	PK	--	--	61.14	28.85	4.66	0.00	33.51
1	2441.00	84.12	AV	--	--	50.61	28.85	4.66	0.00	33.51
2	3510.25	40.98	PK	74	33.02	38.34	31.94	5.84	35.14	2.64
2	3510.25	--	AV	54	--	--	--	--	--	--
3	4882.00	55.26	PK	74	18.74	48.90	33.60	6.95	34.19	6.36
3	4882.00	43.36	AV	54	10.64	37.00	33.60	6.95	34.19	6.36
4	5350.50	43.45	PK	74	30.55	35.56	34.69	7.23	34.03	7.89
4	5350.50	--	AV	54	--	--	--	--	--	--
5	7323.00	46.33	PK	74	27.67	34.63	37.46	9.23	35.00	11.70
5	7323.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2441		Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)	
1	2441.00	95.66	PK	--	--	62.15	28.85	4.66	0.00	33.51
1	2441.00	84.45	AV	--	--	50.94	28.85	4.66	0.00	33.51
2	3250.75	40.32	PK	74	33.68	38.72	31.39	5.53	35.32	1.60
2	3250.75	--	AV	54	--	--	--	--	--	--
3	4882.00	56.48	PK	74	17.52	50.12	33.60	6.95	34.19	6.36
3	4882.00	45.48	AV	54	8.52	39.12	33.60	6.95	34.19	6.36
4	5375.25	42.65	PK	74	31.35	34.71	34.72	7.25	34.02	7.94
4	5375.25	--	AV	54	--	--	--	--	--	--
5	7323.00	48.20	PK	74	25.8	36.50	37.46	9.23	35.00	11.70
5	7323.00	--	AV	54	--	--	--	--	--	--

## REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

Frequency(MHz):			2480		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	93.36 PK	--	--	59.74	28.92	4.70	0.00	33.62
1	2480.00	84.14 AV	--	--	50.52	28.92	4.70	0.00	33.62
2	2483.50	46.26 PK	74	27.74	12.63	28.93	4.70	0.00	33.63
2	2483.50	-- AV	54	--	--	--	--	--	--
3	2500.00	39.48 PK	74	34.52	5.80	28.96	4.72	0.00	33.68
3	2500.00	-- AV	54	--	--	--	--	--	--
4	4960.00	55.23 PK	74	18.77	50.31	33.84	7.00	35.92	4.92
4	4960.00	42.51 AV	54	11.49	37.59	33.84	7.00	35.92	4.92
5	5375.75	43.20 PK	74	30.8	35.60	34.72	7.25	34.37	7.60
5	5375.75	-- AV	54	--	--	--	--	--	--
6	7440.00	45.23 PK	74	28.77	33.28	37.64	9.28	34.97	11.95
6	7440.00	-- AV	54	--	--	--	--	--	--

Frequency(MHz):			2480		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	94.36 PK	--	--	60.74	28.92	4.70	0.00	33.62
1	2480.00	85.21 AV	--	--	51.59	28.92	4.70	0.00	33.62
2	2483.50	46.52 PK	74	27.48	12.89	28.93	4.70	0.00	33.63
2	2483.50	-- AV	54	--	--	--	--	--	--
3	2500.00	38.70 PK	74	35.3	5.02	28.96	4.72	0.00	33.68
3	2500.00	-- AV	54	--	--	--	--	--	--
4	4960.00	55.45 PK	74	18.55	50.53	33.84	7.00	35.92	4.92
4	4960.00	43.65 AV	54	10.35	38.73	33.84	7.00	35.92	4.92
5	5360.20	42.15 PK	74	31.85	34.57	34.70	7.24	34.36	7.58
5	5360.20	-- AV	54	--	--	--	--	--	--
6	7440.00	45.70 PK	74	28.3	33.75	37.64	9.28	34.97	11.95
6	7440.00	-- AV	54	--	--	--	--	--	--

## REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

### 3.3. Maximum Peak Output Power

#### Limit

The Maximum Peak Output Power Measurement is 30dBm.

#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

#### Test Configuration



#### Test Results

Type	Channel	Output power (dBm)	Limit (dBm)	Result
GFSK	00	-0.081	30.00	Pass
	39	0.288		
	78	0.216		
$\pi/4$ DQPSK	00	-0.651	30.00	Pass
	39	-0.328		
	78	-0.330		

Note: 1.The test results including the cable lose.

### 3.4. 20dB Bandwidth

#### Limit

For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

#### Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.




#### Test Configuration




#### Test Results

Modulation	Channel	20dB bandwidth (MHz)	99% OBW(MHz)	Result
GFSK	CH00	0.885	0.827	Pass
	CH39	0.886	0.827	
	CH78	0.886	0.829	
$\pi/4$ DQPSK	CH00	1.308	1.185	Pass
	CH39	1.309	1.188	
	CH78	1.302	1.185	

Test plot as follows:

**GFSK Modulation****CH00****CH39****CH78**



### 3.5. Frequency Separation

#### LIMIT

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 2/3\*20dB bandwidth of the hopping channel, whichever is greater.

#### TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW.

#### TEST CONFIGURATION




#### TEST RESULTS

Modulation	Channel	Channel Separation (MHz)	Limit(MHz)	Result
GFSK	CH38	1.005	25KHz or 2/3*20dB bandwidth	Pass
	CH39			
$\pi/4$ DQPSK	CH38	1.005	25KHz or 2/3*20dB bandwidth	Pass
	CH39			

Note:

We have tested all mode at high, middle and low channel, and recorded worst case at middle

Test plot as follows:



### 3.6. Number of hopping frequency


#### Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

#### Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 2400MHz to 2483.5MHz with 100 KHz RBW and 300 KHz VBW.


#### Test Configuration



#### Test Results

Modulation	Number of Hopping Channel	Limit	Result
GFSK	79	≥15	
π/4DQPSK	79		Pass

#### Test plot as follows:



### 3.7. Time of Occupancy (Dwell Time)


#### Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with 1MHz RBW and 1MHz VBW, Span 0Hz.

#### Test Configuration




#### Test Results


Modulation	Packet	Dwell time (second)	Limit (second)	Result
GFSK	DH1	0.125	0.40	Pass
	DH3	0.267		
	DH5	0.315		
$\pi/4$ DQPSK	2-DH1	0.125	0.40	Pass
	2-DH3	0.267		
	2-DH5	0.312		

Note:

1. We have tested all mode at high, middle and low channel, and recorded worst case at middle channel.
2. Dwell time=Pulse time (ms)  $\times$   $(1600 \div 2 \div 79) \times 31.6$  Second for DH1, 2-DH1  
 Dwell time=Pulse time (ms)  $\times$   $(1600 \div 4 \div 79) \times 31.6$  Second for DH3, 2-DH3  
 Dwell time=Pulse time (ms)  $\times$   $(1600 \div 6 \div 79) \times 31.6$  Second for DH5, 2-DH5

#### Test plot as follows:





### 3.8. Out-of-band Emissions

#### Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

#### Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector , and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.

#### Test Configuration







#### Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandage measurement data.




We measured all conditions (DH1, DH3, DH5) and recorded worst case at DH5

Test plot as follows:

**GFSK****CH00****CH39****CH78**




CH00



Left Band edge hoping off

Right Band edge hoping off



### 3.9. Pseudorandom Frequency Hopping Sequence

#### TEST APPLICABLE


For 47 CFR Part 15C section 15.247 (a) (1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

#### EUT Pseudorandom Frequency Hopping Sequence Requirement


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5<sup>th</sup> and 9<sup>th</sup> stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence: $2^9 - 1 = 511$  bits
- Longest sequence of zeros:8(non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

### 3.10. Antenna Requirement

#### Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

#### **Refer to statement below for compliance**


The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

#### Antenna Connected Construction

The maximum gain of WIFI antenna was -0.68dBi.




#### 4. Test Setup Photos of the EUT








## 5. External and Internal Photos of the EUT

### External Photos of EUT





Internal Photos of EUT



\*\*\*\*\* End of Report \*\*\*\*\*