RF EXPOSURE TEST FCC ID: 2ACCHHD-1380

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz 5 10 15 20 25 mm 150 39 77 116 155 194 300 27 55 82 110 137 450 22 45 67 89 112 835 16 33 49 66 82 900 16 32 47 63 79 1500 12 24 37 49 61 1900 11 22 33 44 54 1900 10 19 29 38 48 3600 8 16 24 32 40 5200 7 13 20 26 33 5400 6 13 19 26 32 5800 6 12 19 25 31 MHz 30 35 40 45 50 mm 450							
300 27 55 82 110 137	mm	25	20	15	10	5	MHz
A50		194	155	116	77	39	150
835 16 33 49 66 82 900 16 32 47 63 79 1500 12 24 37 49 61 1900 11 22 33 44 54 1900 10 19 29 38 48 3600 8 16 24 32 40 5200 7 13 20 26 33 5400 6 13 19 26 32 5800 6 12 19 25 31 MHz 30 35 40 45 50 mm 150 232 271 310 349 387 300 164 192 219 246 274 450 134 157 179 201 224 835 98 115 131 148 164 900		137	110	82	55	27	300
SAR Test Exclusion Threshold (mW)		112	89	67	45	22	450
1500		82	66	49	33	16	835
1500	6 4 D . T	79	63	47	32	16	900
1900		61	49	37	24	12	1500
2450 10 19 29 38 48 3600 8 16 24 32 40 5200 7 13 20 26 33 5400 6 13 19 26 32 5800 6 12 19 25 31 MHz 30 35 40 45 50 mm 150 232 271 310 349 387 300 164 192 219 246 274 450 134 157 179 201 224 835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 1900 65 76 87 98 19 2		54	44	33	22	11	1900
5200 7 13 20 26 33 5400 6 13 19 26 32 5800 6 12 19 25 31 MHz 30 35 40 45 50 mm 150 232 271 310 349 387 300 164 192 219 246 274 450 134 157 179 201 224 835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400	(48	38	29	19	10	2450
5400 6 13 19 26 32 5800 6 12 19 25 31 MHz 30 35 40 45 50 mm 150 232 271 310 349 387 300 164 192 219 246 274 450 134 157 179 201 224 835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400 39 45 52 58 65		40	32	24	16	8	3600
5800 6 12 19 25 31 MHz 30 35 40 45 50 mm 150 232 271 310 349 387 300 164 192 219 246 274 450 134 157 179 201 224 835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400 39 45 52 58 65		33	26	20	13	7	5200
MHz 30 35 40 45 50 mm 150 232 271 310 349 387 300 164 192 219 246 274 450 134 157 179 201 224 835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400 39 45 52 58 65		32	26	19	13	6	5400
150 232 271 310 349 387 300 164 192 219 246 274 450 134 157 179 201 224 835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400 39 45 52 58 65		31	25	19	12	6	5800
300 164 192 219 246 274 450 134 157 179 201 224 835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400 39 45 52 58 65	mm	50	45	40	35	30	MHz
450 134 157 179 201 224 835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400 39 45 52 58 65		387	349	310	271	232	150
835 98 115 131 148 164 900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400 39 45 52 58 65		507					
900 95 111 126 142 158 1500 73 86 98 110 122 1900 65 76 87 98 109 2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400 39 45 52 58 65			246	219	192	164	300
1500 73 86 98 110 122 SAR Test Exclusion Threshold (mW) 1900 65 76 87 98 109 Threshold (mW) 2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400 39 45 52 58 65		274					
1500		274 224	201	179	157	134	450
1900 65 76 87 98 109 2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400 39 45 52 58 65	GAP T	274 224 164	201 148	179 131	157 115	134 98	450 835
2450 57 67 77 86 96 3600 47 55 63 71 79 5200 39 46 53 59 66 5400 39 45 52 58 65		274 224 164 158	201 148 142	179 131 126	157 115 111	134 98 95	450 835 900
5200 39 46 53 59 66 5400 39 45 52 58 65	Exclusion	274 224 164 158 122	201 148 142 110	179 131 126 98	157 115 111 86	134 98 95 73	450 835 900 1500
5400 39 45 52 58 65	Exclusion	274 224 164 158 122 109 96	201 148 142 110 98	179 131 126 98 87	157 115 111 86 76	134 98 95 73 65	450 835 900 1500 1900
	Exclusion	274 224 164 158 122 109 96	201 148 142 110 98 86	179 131 126 98 87 77	157 115 111 86 76 67	134 98 95 73 65 57	450 835 900 1500 1900 2450
5800 37 44 50 56 62	Exclusion	274 224 164 158 122 109 96 79	201 148 142 110 98 86 71	179 131 126 98 87 77 63	157 115 111 86 76 67 55	134 98 95 73 65 57 47	450 835 900 1500 1900 2450 3600
	Exclusion	274 224 164 158 122 109 96 79 66	201 148 142 110 98 86 71 59	179 131 126 98 87 77 63 53	157 115 111 86 76 67 55 46	134 98 95 73 65 57 47 39	450 835 900 1500 1900 2450 3600 5200

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

\leq 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] •
$[\sqrt{f_{\text{(GHz)}}}] \le 3.0 \text{ for } 1\text{-g SAR and} \le 7.5 \text{ for } 10\text{-g extremity SAR,}_{16} \text{ where}$
\square f _(GHz) is the RF channel transmit frequency in GHz
☐ Power and distance are rounded to the nearest mW and mm before calculation 17
☐ The result is rounded to one decimal place for comparison
The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation

distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

GFSK			
			Maximum
	frequency	Maximum Peak Conducted Output Power	Conducted
	range	(dBm)	Output Power
			(mW)
	2402	4.52	2.83
	2441	3.89	2.45
	2480	3.91	2.46

8-DPSK

frequency range	Maximum Peak Conducted Output Power (dBm)	Maximum Conducted Output Power (mW)
2402	2.47	1.77
2441	2.31	1.70
2480	2.42	1.75

Result:

frequency range	Maximum E.I.R.P (mW)	Result (Mw/MHz)	Limit (Mw/MHz)		
2402(GFSK)	2.83	0.879	3.0		
2441(GFSK)	2.45	0.765	3.0		
2480(GFSK)	2.46	0.775	3.0		
2402(8-DPSK)	1.77	0.550	3.0		
2441(8-DPSK)	1.70	0.531	3.0		
2480(8-DPSK)	1.75	0.551	3.0		
Conclusion: Desult < Limiter so SAP is required					

Conclusion: Result ≤ Limiter, so SAR is required.

Note: Result = (E.I.R.P/5)* √Frequency