

Fig.A.6.1.61 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 7.5 GHz-10 GHz)




Fig.A.6.1.62 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 10 GHz-15 GHz)




Fig.A.6.1.63 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 15 GHz-20 GHz)




Fig.A.6.1.64 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 20 GHz-26 GHz)




Fig.A.6.1.65 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, Center Frequency)




Fig.A.6.1.66 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 30 MHz-1 GHz)




Fig.A.6.1.67 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 1 GHz-2.5 GHz)




Fig.A.6.1.68 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 2.5 GHz-7.5 GHz)




Fig.A.6.1.69 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 7.5 GHz-10 GHz)




Fig.A.6.1.70 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 10 GHz-15 GHz)




Fig.A.6.1.71 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 15 GHz-20 GHz)




Fig.A.6.1.72 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 20 GHz-26 GHz)




Fig.A.6.1.73 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, Center Frequency)




Fig.A.6.1.74 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 30 MHz-1 GHz)




Fig.A.6.1.75 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 1 GHz-2.5 GHz)




Fig.A.6.1.76 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 2.5 GHz-7.5 GHz)




Fig.A.6.1.77 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 7.5 GHz-10 GHz)




Fig.A.6.1.78 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 10 GHz-15 GHz)




Fig.A.6.1.79 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 15 GHz-20 GHz)




Fig.A.6.1.80 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 20 GHz-26 GHz)




Fig.A.6.1.81 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, Center Frequency)




Fig.A.6.1.82 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 30 MHz-1 GHz)




Fig.A.6.1.83 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 1 GHz-2.5 GHz)




Fig.A.6.1.84 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 2.5 GHz-7.5 GHz)




Fig.A.6.1.85 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 7.5 GHz-10 GHz)




Fig.A.6.1.86 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 10 GHz-15 GHz)




Fig.A.6.1.87 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 15 GHz-20 GHz)




Fig.A.6.1.88 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 20 GHz-26 GHz)




Fig.A.6.1.89 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, Center Frequency)




Fig.A.6.1.90 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 30 MHz-1 GHz)




Fig.A.6.1.91 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 1 GHz-2.5 GHz)




Fig.A.6.1.92 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 2.5 GHz-7.5 GHz)




Fig.A.6.1.93 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 7.5 GHz-10 GHz)




Fig.A.6.1.94 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 10 GHz-15 GHz)




Fig.A.6.1.95 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 15 GHz-20 GHz)




Fig.A.6.1.96 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 20 GHz-26 GHz)

A.6.2 Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 &6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Frequency (MHz)	Field strength(µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

EUT ID: EUT1

Measurement Results:

802.11b mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11b	Power	2.38GHz ~2.45GHz	Fig.A.6.2.1	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.2	P

802.11g mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11g	Power	2.38GHz ~2.43GHz	Fig.A.6.2.3	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.4	P

802.11n-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT20)	Power	2.38GHz ~2.45GHz	Fig.A.6.2.5	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.6	P

802.11n-HT40 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT40)	Power	2.38GHz ~2.45GHz	Fig.A.6.2.7	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.8	P

Conclusion: Pass

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

$$\text{Result} = P_{Mea} + A_{Rpl} = P_{Mea} + \text{Cable Loss} + \text{Antenna Factor}$$

AVERAGE

802.11b

Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2380.790	46.3	2.9	32.1	11.35	54.0	7.7	H
2385.102	46.3	2.9	32.0	11.41	54.0	7.7	H
4822.500	39.25	-32.8	34.5	37.51	54.0	14.8	H
7236.000	37.85	-31.7	36.1	33.49	54.0	16.2	H
9648.000	40.36	-30.4	37.0	33.68	54.0	13.6	H
12060.000	43.43	-29.6	39.3	33.76	54.0	10.6	H

Ch6

Frequency (MHz)	Measurement Result	Cable loss	Antenna Factor	Receiver eading	Limit (dBμV/m)	Margin (dB)	Antenna Pol.
-----------------	--------------------	------------	----------------	-----------------	----------------	-------------	--------------

	(dBμV/m)	(dB)	(dB/m)	(dBμV)			(H/V)
2385.460	46.6	2.9	32.0	11.72	54.0	7.4	H
2486.370	46.8	2.9	32.7	11.19	54.0	7.2	H
4873.500	39.31	-32.7	34.5	37.52	54.0	14.7	H
7311.000	37.64	-31.9	36.1	33.48	54.0	16.4	H
9748.500	40.10	-30.7	37.2	33.57	54.0	13.9	H
12184.500	43.63	-29.4	39.2	33.84	54.0	10.4	H

Ch11

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.123	47.3	2.9	32.7	11.59	54.0	6.7	H
2487.740	47.2	2.9	32.6	11.58	54.0	6.8	H
4924.500	36.99	-33.1	34.5	35.58	54.0	17.0	H
7386.000	37.85	-31.8	36.0	33.64	54.0	16.2	H
9847.500	40.81	-30.1	37.3	33.56	54.0	13.2	H
12310.500	43.51	-29.7	39.2	34.03	54.0	10.5	H

802.11g

Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2380.710	46.4	2.9	32.1	11.53	54.0	7.6	H
2387.930	46.5	2.9	32.0	11.69	54.0	7.5	H
4824.000	35.29	-32.8	34.5	33.54	54.0	18.7	H
7236.000	37.84	-31.7	36.1	33.48	54.0	16.2	H
9648.000	40.30	-30.4	37.0	33.61	54.0	13.7	H
12060.000	43.34	-29.6	39.3	33.67	54.0	10.7	H

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2386.490	46.7	2.9	32.0	11.87	54.0	7.3	H
2485.640	46.8	2.9	32.7	11.20	54.0	7.2	H
4873.500	35.33	-32.7	34.5	33.54	54.0	18.7	H
7311.000	37.56	-31.9	36.1	33.39	54.0	16.4	H
9748.500	40.09	-30.7	37.2	33.56	54.0	13.9	H
12184.500	43.58	-29.4	39.2	33.78	54.0	10.4	H

Ch11

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2483.640	47.5	2.9	32.8	47.49	2.9	32.8	H
2487.160	47.2	2.9	32.7	47.25	2.9	32.7	H
4924.500	35.29	-33.1	34.5	35.29	-33.1	34.5	H
7386.000	37.81	-31.8	36.0	37.81	-31.8	36.0	H
9847.500	40.80	-30.1	37.3	40.80	-30.1	37.3	H
12310.500	43.51	-29.7	39.2	43.51	-29.7	39.2	H

802.11n-HT20

Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2386.902	47.0	2.9	32.0	12.13	54.0	7.0	H
2389.740	47.5	2.9	32.0	12.64	54.0	6.5	H
4824.000	35.27	-32.8	34.5	33.52	54.0	18.7	H
7236.000	37.85	-31.7	36.1	33.49	54.0	16.1	H
9648.000	40.26	-30.4	37.0	33.58	54.0	13.7	H
12060.000	43.38	-29.6	39.3	33.71	54.0	10.6	H

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2383.750	47.1	2.9	32.0	12.23	54.0	6.9	H
2486.490	47.2	2.9	32.7	11.57	54.0	6.8	H
4873.500	35.35	-32.7	34.5	33.56	54.0	18.7	H
7311.000	37.58	-31.9	36.1	33.42	54.0	16.4	H
9748.500	40.08	-30.7	37.2	33.55	54.0	13.9	H
12184.500	43.67	-29.4	39.2	33.88	54.0	10.3	H

Ch11

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.420	47.3	2.9	32.7	11.63	54.0	6.7	H
2485.950	47.2	2.9	32.7	11.57	54.0	6.8	H
4924.500	35.17	-33.1	34.5	33.76	54.0	18.8	H
7386.000	37.85	-31.8	36.0	33.65	54.0	16.1	H
9847.500	40.87	-30.1	37.3	33.62	54.0	13.1	H
12310.500	43.50	-29.7	39.2	34.02	54.0	10.5	H

802.11n-HT40

Ch3

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2381.560	46.3	2.9	32.0	11.40	54.0	7.7	H
2387.940	46.4	2.9	32.0	11.51	54.0	7.6	H
4843.500	35.28	-32.7	34.5	33.47	54.0	18.7	H
7266.000	37.80	-31.9	36.1	33.56	54.0	16.2	H
9688.500	39.95	-30.7	37.1	33.57	54.0	14.0	H
12109.500	43.43	-29.5	39.3	33.66	54.0	10.6	H

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2384.550	46.7	2.9	32.0	11.80	54.0	7.3	H
2488.620	46.9	2.9	32.6	11.34	54.0	7.1	H
4873.500	35.36	-32.7	34.5	33.57	54.0	18.6	H
7311.000	37.60	-31.9	36.1	33.43	54.0	16.4	H
9748.500	40.10	-30.7	37.2	33.57	54.0	13.9	H
12184.500	43.58	-29.4	39.2	33.79	54.0	10.4	H

Ch9

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.120	47.2	2.9	32.7	11.56	54.0	6.8	H
2486.630	47.2	2.9	32.7	11.56	54.0	6.8	H
4903.500	35.45	-32.9	34.5	33.84	54.0	18.6	H
7356.000	37.87	-31.9	36.1	33.72	54.0	16.1	H
9808.500	40.38	-30.3	37.3	33.46	54.0	13.6	H
12259.500	43.60	-29.6	39.2	33.98	54.0	10.4	H

PEAK

802.11b

Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2386.314	60.8	2.9	32.0	25.91	74.0	13.2	H
2387.798	59.7	2.9	32.0	24.86	74.0	14.3	H
4824.000	46.5	-32.8	34.5	44.78	74.0	27.5	H

7236.000	42.3	-31.7	36.1	37.96	74.0	31.7	V
9648.000	45.6	-30.4	37.0	38.89	74.0	28.4	H
12060.000	46.6	-29.6	39.3	36.94	74.0	27.4	H

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2351.203	50.0	-27.8	31.7	46.07	74.0	24.0	H
2922.842	53.7	-25.4	34.0	45.07	74.0	20.3	H
4873.500	49.0	-32.7	34.5	47.23	74.0	25.0	H
7311.000	40.7	-31.9	36.1	36.50	74.0	33.3	V
9747.750	44.3	-30.7	37.2	37.81	74.0	29.7	H
12185.250	46.3	-29.4	39.2	36.52	74.0	27.7	H

Ch11

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.712	59.8	2.9	32.7	24.10	74.0	14.2	H
2485.860	59.7	2.9	32.7	24.07	74.0	14.3	H
4923.750	45.7	-33.1	34.5	44.28	74.0	28.3	H
7386.000	42.1	-31.8	36.0	37.89	74.0	31.9	V
9848.250	43.9	-30.1	37.3	36.65	74.0	30.1	V
12309.750	44.9	-29.7	39.2	35.46	74.0	29.1	H

802.11g

Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2385.610	60.0	2.9	32.0	25.16	74.0	14.0	H
2388.316	60.8	2.9	32.0	25.95	74.0	13.2	H
4824.000	39.0	-32.8	34.5	37.21	74.0	35.0	V
7236.000	41.0	-31.7	36.1	36.60	74.0	33.0	H
9648.000	44.0	-30.4	37.0	37.35	74.0	30.0	V
12060.000	46.0	-29.6	39.3	36.35	74.0	28.0	H

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2370.620	49.9	-27.0	32.0	44.82	74.0	24.1	H



2535.800	51.5	-26.8	32.9	45.44	74.0	22.5	H
4874.250	40.4	-32.7	34.5	38.60	74.0	33.6	H
7311.000	41.4	-31.9	36.1	37.27	74.0	32.6	H
9747.750	43.5	-30.7	37.2	36.93	74.0	30.5	H
12185.250	45.3	-29.4	39.2	35.50	74.0	28.7	V

Ch11

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2485.340	60.2	2.9	32.7	24.54	74.0	13.8	H
2490.510	60.4	2.9	32.6	24.85	74.0	13.6	H
4923.750	40.0	-33.1	34.5	38.58	74.0	34.0	V
7386.000	41.3	-31.8	36.0	37.10	74.0	32.7	H
9848.250	45.3	-30.1	37.3	38.02	74.0	28.7	V
12309.750	44.5	-29.7	39.2	35.03	74.0	29.5	V

802.11n-HT20

Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2389.324	64.2	2.9	32.0	29.40	74.0	9.8	H
2387.182	63.2	2.9	32.0	28.38	74.0	10.8	H
4824.000	40.2	-32.8	34.5	38.46	74.0	33.8	H
7236.000	41.1	-31.7	36.1	36.74	74.0	32.9	V
9648.000	43.3	-30.4	37.0	36.57	74.0	30.7	H
12060.000	45.8	-29.6	39.3	36.11	74.0	28.2	H

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2364.210	49.6	-27.3	31.9	45.01	74.0	24.4	H
2912.450	53.2	-25.4	34.0	44.60	74.0	20.8	H
4874.250	39.3	-32.7	34.5	37.53	74.0	34.7	V
7311.000	40.7	-31.9	36.1	36.55	74.0	33.3	V
9747.750	43.2	-30.7	37.2	36.68	74.0	30.8	V
12185.250	46.9	-29.4	39.2	37.08	74.0	27.1	H

Ch11

Frequency (MHz)	Measurement Result	Cable loss	Antenna Factor	Receiver eading	Limit (dBμV/m)	Margin (dB)	Antenna Pol.
-----------------	--------------------	------------	----------------	-----------------	----------------	-------------	--------------

	(dBμV/m)	(dB)	(dB/m)	(dBμV)			(H/V)
2483.970	61.9	2.9	32.7	26.21	74.0	12.1	H
2484.280	61.8	2.9	32.7	26.14	74.0	12.2	H
4923.750	39.4	-33.1	34.5	37.95	74.0	34.6	V
7386.000	41.5	-31.8	36.0	37.25	74.0	32.5	V
9848.250	45.0	-30.1	37.3	37.70	74.0	29.0	V
12309.750	44.6	-29.7	39.2	35.10	74.0	29.4	H

802.11n-HT40

Ch3

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2380.960	59.9	2.9	32.1	24.98	74.0	14.1	H
2386.146	59.1	2.9	32.0	24.18	74.0	14.9	H
4844.250	40.1	-32.7	34.5	38.33	74.0	33.9	V
7266.000	40.8	-31.9	36.1	36.52	74.0	33.2	V
9687.750	44.5	-30.7	37.1	38.15	74.0	29.5	V
12110.250	46.0	-29.5	39.3	36.18	74.0	28.0	V

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2369.425	49.6	-27.0	32.0	44.64	74.0	24.4	H
2646.450	51.6	-26.7	33.6	44.65	74.0	22.4	H
4874.250	40.1	-32.7	34.5	38.26	74.0	33.9	V
7311.000	41.0	-31.9	36.1	36.84	74.0	33.0	V
9747.750	43.7	-30.7	37.2	37.19	74.0	30.3	V
12185.250	46.0	-29.4	39.2	36.20	74.0	28.0	H

Ch9

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver eading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
2483.745	64.6	2.9	32.8	28.96	74.0	9.4	H
2485.920	64.3	2.9	32.7	28.65	74.0	9.7	H
4904.250	39.9	-32.9	34.5	38.30	74.0	34.1	H
7356.000	41.2	-31.9	36.1	37.03	74.0	32.8	V
9807.750	43.3	-30.4	37.3	36.34	74.0	30.7	V
12260.250	45.2	-29.6	39.2	35.57	74.0	28.8	V

Test graphs as below:




Fig.A.6.2.1 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch1, 2.38 GHz – 2.45GHz




Fig.A.6.2.2 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch11, 2.45 GHz - 2.50GHz

RE - Power-2.38GHz-2.45GHz




Fig.A.6.2.3 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch1, 2.38 GHz - 2.45GHz

RE - Power-2.45GHz-2.5GHz




Fig.A.6.2.4 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch11, 2.45 GHz - 2.50GHz




Fig.A.6.2.5 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch1, 2.38 GHz - 2.45GHz




Fig.A.6.2.6 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch11, 2.45 GHz - 2.50GHz

RE - Power-2.38GHz-2.45GHz




Fig.A.6.2.7 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch3, 2.38 GHz - 2.45GHz

RE - Power-2.45GHz-2.5GHz




Fig.A.6.2.8 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch9, 2.45 GHz - 2.50GHz

A.7. AC Power-line Conducted Emission

Method of Measurement: See ANSI C63.10-2013-clause 6.2

- 1 The one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
- 2 If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
- 3 The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
- 4 If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.
- 5 If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.³⁶ Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	66 to 56	Fig.A.7.1	Fig.A.7.2	P
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	56 to 46	Fig.A.7.1	Fig.A.7.2	P
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Conclusion: Pass

Test graphs as below:




Fig.A.7.1 AC Powerline Conducted Emission-802.11b

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
2.404500	43.4	GND	L1	10.3	12.6	56.0
2.463000	43.7	GND	L1	10.3	12.3	56.0
2.571000	44.1	GND	L1	10.3	11.9	56.0
2.620500	44.1	GND	L1	10.3	11.9	56.0
2.647500	44.3	GND	L1	10.3	11.7	56.0
2.769000	42.5	GND	L1	10.3	13.5	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
2.112000	32.2	GND	L1	10.3	13.8	46.0
2.463000	32.4	GND	L1	10.3	13.6	46.0
2.571000	33.0	GND	L1	10.3	13.0	46.0
2.755500	32.5	GND	L1	10.3	13.5	46.0
2.913000	31.7	GND	L1	10.3	14.3	46.0
3.538500	31.9	GND	L1	10.3	14.1	46.0




Fig.A.7.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
2.179500	43.4	GND	L1	10.3	12.6	56.0
2.215500	43.9	GND	L1	10.3	12.1	56.0
2.530500	44.0	GND	L1	10.3	12.0	56.0
2.571000	44.3	GND	L1	10.3	11.7	56.0
2.629500	44.3	GND	L1	10.3	11.7	56.0
3.021000	44.1	GND	L1	10.3	11.9	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
2.373000	25.8	GND	L1	10.3	20.2	46.0
2.629500	33.3	GND	L1	10.3	12.7	46.0
2.755500	28.5	GND	L1	10.3	17.5	46.0
2.814000	31.7	GND	L1	10.3	14.3	46.0
2.980500	32.6	GND	L1	10.3	13.4	46.0
3.057000	32.7	GND	L1	10.3	13.3	46.0

END OF REPORT