

GFSK Ch 39 - Average

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
17860.000	39.1	-18.5	45.6	12.000	H
17850.500	39.1	-18.5	45.6	12.000	H
17865.000	39.1	-18.5	45.6	12.000	V
17750.500	39.0	-18.5	45.6	11.900	H
17880.500	39.0	-18.5	45.6	11.900	H
17845.000	38.9	-18.5	45.6	11.800	H

GFSK Ch 78 - Average

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2486.160	41.0	-38.9	27.7	52.2	H
17873.000	39.2	-18.5	45.6	12.1	H
17840.500	39.1	-18.5	45.6	12.0	V
17752.500	39.1	-18.5	45.6	12.0	H
17792.000	39.0	-18.5	45.6	11.9	H
17747.500	39.0	-18.5	45.6	11.9	H

$\pi/4$ DQPSK Ch 0 - Average

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2389.920	40.8	-38.8	27.7	51.9	H
17872.500	39.0	-18.5	45.6	11.9	H
17864.000	38.9	-18.5	45.6	11.8	V
17842.500	38.9	-18.5	45.6	11.8	H
17907.500	38.9	-18.5	45.6	11.8	H
17873.000	38.8	-18.5	45.6	11.7	H

$\pi/4$ DQPSK Ch 39 - Average

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
17747.000	39.0	-18.5	45.6	11.9	H
17854.000	39.0	-18.5	45.6	11.9	H
17844.000	38.9	-18.5	45.6	11.8	V
17909.000	38.9	-18.5	45.6	11.8	H
17824.000	38.9	-18.5	45.6	11.8	H
17855.500	38.9	-18.5	45.6	11.8	H

$\pi/4$ DQPSK Ch 78 - Average

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dB μ V)	Polarization
2484.146	40.8	-38.9	27.7	52.0	H
17863.000	39.3	-18.5	45.6	12.2	H
17852.500	39.1	-18.5	45.6	12.0	V
17879.500	39.1	-18.5	45.6	12.0	H
17881.500	39.0	-18.5	45.6	11.9	H
17833.500	39.0	-18.5	45.6	11.9	H

8DPSK Ch 0 - Average

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dB μ V)	Polarization
2388.245	41.2	-38.8	27.7	52.3	H
17857.000	39.0	-18.5	45.6	11.9	H
17864.000	39.0	-18.5	45.6	11.9	V
17758.500	39.0	-18.5	45.6	11.9	H
17901.000	38.9	-18.5	45.6	11.8	H
17787.000	38.9	-18.5	45.6	11.8	H

8DPSK Ch 39 - Average

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dB μ V)	Polarization
17876.500	39.2	-18.5	45.6	12.1	H
17853.000	39.1	-18.5	45.6	12.0	H
17867.500	39.0	-18.5	45.6	11.9	V
17879.500	39.0	-18.5	45.6	11.9	H
17889.000	39.0	-18.5	45.6	11.9	H
17861.500	39.0	-18.5	45.6	11.9	H

8DPSK Ch 78 - Average

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dB μ V)	Polarization
2484.595	41.0	-38.9	27.7	52.2	H
17854.000	39.1	-18.5	45.6	12.0	H
17753.000	39.0	-18.5	45.6	11.9	V
17895.000	38.9	-18.5	45.6	11.8	H
17878.500	38.9	-18.5	45.6	11.8	H
17879.500	38.9	-18.5	45.6	11.8	H

GFSK Ch 0 – Peak

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2387.975	53.9	-38.8	27.7	65.0	H
17956.000	51.0	-17.7	45.6	23.1	H
17867.000	50.9	-18.5	45.6	23.8	V
17618.000	50.7	-18.9	45.6	24.0	H
17883.000	50.7	-18.5	45.6	23.6	H
17402.500	50.6	-19.2	41.5	28.3	H

GFSK Ch 39 - Peak

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
17809.000	51.3	-18.5	45.6	24.2	H
17640.000	51.2	-18.9	45.6	24.5	H
17863.500	50.7	-18.5	45.6	23.6	V
17949.500	50.5	-17.7	45.6	22.6	H
17833.000	50.5	-18.5	45.6	23.4	H
17507.500	50.5	-19.2	45.6	24.1	H

GFSK Ch 78 - Peak

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2483.935	53.4	-38.9	27.7	64.6	H
17898.000	51.9	-18.5	45.6	24.8	H
17779.500	51.2	-18.5	45.6	24.1	V
17455.500	51.1	-19.2	41.5	28.8	H
17767.000	51.0	-18.5	45.6	23.9	H
17462.500	51.0	-19.2	41.5	28.7	H

π/4 DQPSK Ch 0 - Peak

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2389.935	52.3	-38.8	27.7	63.400	H
17544.500	51.1	-19.2	45.6	24.700	H
17441.500	50.7	-19.2	41.5	28.400	V
17649.500	50.7	-18.9	45.6	24.000	H
17615.500	50.6	-18.9	45.6	23.900	H
17708.500	50.6	-18.9	45.6	23.900	H

$\pi/4$ DQPSK Ch 39 - Peak

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dB μ V)	Polarization
17854.000	50.9	-18.5	45.6	23.800	H
17922.500	50.8	-17.7	45.6	22.900	H
17873.000	50.8	-18.5	45.6	23.700	V
17425.500	50.7	-19.2	41.5	28.400	H
17352.500	50.7	-19.5	41.5	28.700	H
17886.000	50.6	-18.5	45.6	23.500	H

$\pi/4$ DQPSK Ch 78 - Peak

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dB μ V)	Polarization
2484.025	52.6	-38.9	27.7	63.8	H
17818.500	51.5	-18.5	45.6	24.4	H
17984.500	51.1	-17.7	45.6	23.2	V
17836.000	51.0	-18.5	45.6	23.9	H
17663.000	51.0	-18.9	45.6	24.3	H
17855.000	51.0	-18.5	45.6	23.9	H

8DPSK Ch 0 - Peak

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dB μ V)	Polarization
2389.430	52.4	-38.8	27.7	63.5	H
17426.000	50.8	-19.2	41.5	28.5	H
17418.000	50.8	-19.2	41.5	28.5	V
17869.000	50.7	-18.5	45.6	23.6	H
17642.000	50.6	-18.9	45.6	23.9	H
17868.000	50.6	-18.5	45.6	23.5	H

8DPSK Ch 39 - Peak

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dB μ V)	Polarization
17485.500	51.8	-19.2	41.5	29.5	H
17331.500	51.2	-19.5	41.5	29.2	H
17788.000	50.9	-18.5	45.6	23.8	V
17731.500	50.9	-18.9	45.6	24.2	H
17432.500	50.8	-19.2	41.5	28.5	H
17867.500	50.8	-18.5	45.6	23.7	H

8DPSK Ch 78 - Peak

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	Receiver Reading (dBμV)	Polarization
2484.325	53.1	-38.9	27.7	64.3	H
17426.500	51.0	-19.2	41.5	28.7	H
17824.000	51.0	-18.5	45.6	23.9	V
17753.500	50.9	-18.5	45.6	23.8	H
17396.500	50.8	-19.2	41.5	28.5	H
17758.000	50.8	-18.5	45.6	23.7	H

Conclusion: PASS

Test graphs as below for Set.1:




Fig.58. Radiated emission (Power): GFSK, low channel




Fig.59. Radiated emission (Power) GFSK, high channel




Fig.60. Radiated emission (Power): $\pi/4$ DQPSK, low channel




Fig.61. Radiated emission (Power): $\pi/4$ DQPSK, high channel




Fig.62. Radiated emission (Power): 8DPSK, low channel




Fig.63. Radiated emission (Power): 8DPSK, high channel

A.6. Time of Occupancy (Dwell Time)

Method of Measurement: See ANSI C63.10-clause 7.8.4

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW \geq RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

Measurement Result:

For GFSK

Channel	Packet	Dwell Time (ms)		Conclusion
39	DH1	Fig.64	118.95	P
		Fig.65		
	DH3	Fig.66	172.80	P
		Fig.67		
	DH5	Fig.68	166.95	P
		Fig.69		

For $\pi/4$ DQPSK

Channel	Packet	Dwell Time (ms)		Conclusion
39	DH1	Fig.70	121.26	P
		Fig.71		
	DH3	Fig.72	164.98	P
		Fig.73		
	DH5	Fig.74	135.43	P
		Fig.75		

For 8DPSK

Channel	Packet	Dwell Time (ms)		Conclusion
39	DH1	Fig.76	117.59	P
		Fig.77		
	DH3	Fig.78	194.33	P

		Fig.79		
	DH5	Fig.80	195.56	P
		Fig.81		

Conclusion: PASS

Test graphs as below:




Fig.64. Time of occupancy (Dwell Time): Channel 39, Packet DH1




Fig.65. Number of Transmissions Measurement: Channel 39,Packet DH1




Fig.66. Time of occupancy (Dwell Time): Channel 39, Packet DH3




Fig.67. Number of Transmissions Measurement: Channel 39,Packet DH3



Fig.68. Time of occupancy (Dwell Time): Channel 39, Packet DH5




Fig.69. Number of Transmissions Measurement: Channel 39,Packet DH5




Fig.70. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1




Fig.71. Number of Transmissions Measurement: Channel 39,Packet 2-DH1




Fig.72. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3




Fig.73. Number of Transmissions Measurement: Channel 39,Packet 2-DH3




Fig.74. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5




Fig.75. Number of Transmissions Measurement: Channel 39,Packet 2-DH5




Fig.76. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1




Fig.77. Number of Transmissions Measurement: Channel 39,Packet 3-DH1




Fig.78. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3




Fig.79. Number of Transmissions Measurement: Channel 39,Packet 3-DH3




Fig.80. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5




Fig.81. Number of Transmissions Measurement: Channel 39,Packet 3-DH5



A.7. 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 6.9.2

Measurement Procedure - Unwanted Emissions

1. Set RBW = 30kHz.
2. Set VBW = 100 kHz.
3. Set span to 3MHz
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

Use NdB Down function of the SA to measure the 20dB Bandwidth

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for “carrier frequency separation” test case, in Annex A.8.

Measurement Results:

For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.82	947.25	NA
39	Fig.83	945.75	NA
78	Fig.84	947.25	NA

For $\pi/4$ DQPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.85	1264.50	NA
39	Fig.86	1263.75	NA
78	Fig.87	1293.75	NA

For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.88	1287.00	NA
39	Fig.89	1287.75	NA
78	Fig.90	1265.25	NA

Conclusion: NA

Test graphs as below:




Fig.82. 20dB Bandwidth: GFSK, Channel 0




Fig.83. 20dB Bandwidth: GFSK, Channel 39




Fig.84. 20dB Bandwidth: GFSK, Channel 78




Fig.85. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 0




Fig.86. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 39




Fig.87. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 78




Fig.88. 20dB Bandwidth: 8DPSK, Channel 0




Fig.89. 20dB Bandwidth: 8DPSK, Channel 39




Fig.90. 20dB Bandwidth: 8DPSK, Channel 78



A.8. Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

* Comment: This limit should be over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth, whichever is greater.

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)	Conclusion	
39	Fig.91	1023.75	P

For $\pi/4$ DQPSK

Channel	Carrier frequency separation (kHz)	Conclusion	
39	Fig.92	999.75	P

For 8DPSK

Channel	Carrier frequency separation (kHz)	Conclusion	
39	Fig.93	1128.75	P

Conclusion: PASS

Test graphs as below:




Fig.91. Carrier frequency separation measurement: GFSK, Channel 39




Fig.92. Carrier frequency separation measurement: $\pi/4$ DQPSK, Channel 39




Fig.93. Carrier frequency separation measurement: 8DPSK, Channel 39

A.9. Number of Hopping Channels

Method of Measurement: See ANSI C63.10-clause 7.8.3

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = the frequency band of operation
- RBW = 500kHz
- VBW = 500kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii)	At least 15 non-overlapping channels

Measurement Result:

For GFSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.94	79	P
40~78	Fig.95		

For $\pi/4$ DQPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.96	79	P
40~78	Fig.97		

For 8DPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.98	79	P
40~78	Fig.99		

Conclusion: PASS

Test graphs as below:




Fig.94. Number of hopping frequencies: GFSK, Channel 0 - 39




Fig.95. Number of hopping frequencies: GFSK, Channel 40 - 78




Fig.96. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 0 - 39




Fig.97. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 40 - 78




Fig.98. Number of hopping frequencies: 8DPSK, Channel 0 - 39




Fig.99. Number of hopping frequencies: 8DPSK, Channel 40 - 78

A.10. AC Powerline Conducted Emission

Method of Measurement: See ANSI C63.10-clause 6.2

1. the one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
2. If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
3. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
4. If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.
5. If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.³⁶ Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

Test Condition

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Conclusion
0.15 to 0.5	66 to 56	P
0.5 to 5	56	
5 to 30	60	

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.



Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dB μ V)	Conclusion
0.15 to 0.5	56 to 46	P
0.5 to 5	46	
5 to 30	50	


NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

The measurement is made according to ANSI C63.10

Conclusion: PASS

Test graphs as below:

Traffic: Set.1




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (h)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	57.8	2000.0	9.000	On	L1	20.2	8.2	66.0
0.258000	46.9	2000.0	9.000	On	L1	19.9	14.6	61.5
0.582000	41.3	2000.0	9.000	On	L1	19.9	14.7	56.0
1.099500	35.6	2000.0	9.000	On	L1	19.8	20.4	56.0
3.525000	36.1	2000.0	9.000	On	L1	19.7	19.9	56.0
4.465500	36.5	2000.0	9.000	On	L1	19.7	19.5	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (h)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.204000	32.2	2000.0	9.000	On	N	19.8	21.2	53.4
0.348000	32.5	2000.0	9.000	On	N	19.9	16.5	49.0
0.505500	35.8	2000.0	9.000	On	N	19.9	10.2	46.0
1.639500	29.0	2000.0	9.000	On	N	19.7	17.0	46.0
2.616000	29.5	2000.0	9.000	On	N	19.7	16.5	46.0
3.624000	28.3	2000.0	9.000	On	N	19.7	17.7	46.0

Traffic: Set.2




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth h	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.222000	43.5	2000.0	9.000	On	L1	19.9	19.2	62.7
0.375000	43.3	2000.0	9.000	On	N	19.9	15.1	58.4
0.753000	44.0	2000.0	9.000	On	L1	19.9	12.0	56.0
1.648500	39.6	2000.0	9.000	On	N	19.7	16.4	56.0
2.184000	41.5	2000.0	9.000	On	L1	19.7	14.5	56.0
4.150500	37.7	2000.0	9.000	On	L1	19.7	18.3	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth h	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.181500	36.1	2000.0	9.000	On	L1	19.9	18.3	54.4
0.690000	35.3	2000.0	9.000	On	L1	19.9	10.7	46.0
0.753000	37.1	2000.0	9.000	On	L1	19.9	8.9	46.0
1.261500	35.4	2000.0	9.000	On	L1	19.8	10.6	46.0
2.305500	35.3	2000.0	9.000	On	L1	19.7	10.7	46.0
3.781500	31.4	2000.0	9.000	On	L1	19.7	14.6	46.0

Idle: Set.1



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth h	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.199500	46.2	2000.0	9.000	On	L1	19.8	17.4	63.6
0.271500	37.6	2000.0	9.000	On	L1	19.9	23.5	61.1
0.501000	42.2	2000.0	9.000	On	L1	19.9	13.8	56.0
1.576500	34.5	2000.0	9.000	On	L1	19.7	21.5	56.0
2.530500	34.9	2000.0	9.000	On	L1	19.7	21.1	56.0
4.479000	36.4	2000.0	9.000	On	L1	19.7	19.6	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth h	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.199500	36.0	2000.0	9.000	On	L1	19.8	17.7	53.6
0.505500	31.6	2000.0	9.000	On	N	19.9	14.4	46.0
0.739500	29.2	2000.0	9.000	On	N	19.9	16.8	46.0
1.626000	29.2	2000.0	9.000	On	N	19.7	16.8	46.0
2.616000	24.8	2000.0	9.000	On	N	19.7	21.2	46.0
3.615000	29.0	2000.0	9.000	On	N	19.7	17.0	46.0

ANNEX E: Accreditation Certificate

<p>United States Department of Commerce National Institute of Standards and Technology</p>  <hr/> <p>Certificate of Accreditation to ISO/IEC 17025:2005</p> <hr/> <p>NVLAP LAB CODE: 600118-0</p> <p>Telecommunication Technology Labs, CAICT Beijing China</p> <p><i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i></p> <p>Electromagnetic Compatibility & Telecommunications</p> <p><i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i></p> <hr/> <table border="0" style="width: 100%;"><tr><td style="width: 40%; text-align: center;"><p>2016-09-29 through 2017-09-30 <i>Effective Dates</i></p></td><td style="width: 20%; text-align: center;"></td><td style="width: 40%; text-align: center;"> <i>For the National Voluntary Laboratory Accreditation Program</i></td></tr></table>		<p>2016-09-29 through 2017-09-30 <i>Effective Dates</i></p>		 <i>For the National Voluntary Laboratory Accreditation Program</i>
<p>2016-09-29 through 2017-09-30 <i>Effective Dates</i></p>		 <i>For the National Voluntary Laboratory Accreditation Program</i>		

END OF REPORT