



# TEST REPORT

## No. I19Z61094-WMD02

for

**TCL Communication Ltd.**

**Smart Phone**

**Model Name: 5032W**

**FCC ID: 2ACCJB111**

with

**Hardware Version: 06**

**Software Version: 3E5H**

**Issued Date: 2019-09-12**



**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

**Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: [ctl\\_terminals@caict.ac.cn](mailto:ctl_terminals@caict.ac.cn), website: [www.caict.ac.cn](http://www.caict.ac.cn)

## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I19Z61094-WMD02	Rev.0	1 <sup>st</sup> edition	2019-09-04
I19Z61094-WMD02	Rev.1	2 <sup>nd</sup> edition Added the results of 16QAM modulation	2019-09-12



## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. INTRODUCTION &amp; ACCREDITATION.....</b>	<b>4</b>
<b>1.2. TESTING LOCATION .....</b>	<b>4</b>
<b>1.3. TESTING ENVIRONMENT .....</b>	<b>4</b>
<b>1.4. PROJECT DATA .....</b>	<b>4</b>
<b>1.5. SIGNATURE.....</b>	<b>5</b>
<b>2. CLIENT INFORMATION.....</b>	<b>6</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>6</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>6</b>
<b>3. EQUIPMENT UNDERTEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>7</b>
<b>3.1. ABOUT EUT .....</b>	<b>7</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>7</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>7</b>
<b>3.4. NORMAL ACCESSORY SETTING.....</b>	<b>7</b>
<b>3.5. GENERAL DESCRIPTION .....</b>	<b>7</b>
<b>4. REFERENCE DOCUMENTS.....</b>	<b>8</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING.....</b>	<b>8</b>
<b>5. LABORATORY ENVIRONMENT.....</b>	<b>9</b>
<b>6. SUMMARY OF TEST RESULT .....</b>	<b>10</b>
<b>7. TESTEQUIPMENTS UTILIZED .....</b>	<b>12</b>
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>13</b>
<b>A.1 OUTPUT POWER .....</b>	<b>13</b>
<b>A.2 EMISSION LIMIT .....</b>	<b>19</b>
<b>A.3 FREQUENCY STABILITY.....</b>	<b>25</b>
<b>A.4 OCCUPIED BANDWIDTH .....</b>	<b>29</b>
<b>A.5 EMISSION BANDWIDTH.....</b>	<b>42</b>
<b>A.6 BAND EDGE COMPLIANCE .....</b>	<b>54</b>
<b>A.7 CONDUCTED SPURIOUS EMISSION .....</b>	<b>61</b>
<b>A.8 PEAK-TO-AVERAGE POWER RATIO.....</b>	<b>68</b>
<b>ANNEX B: ACCREDITATION CERTIFICATE.....</b>	<b>69</b>



## **1. Test Laboratory**

### **1.1. Introduction & Accreditation**

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0 and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

### **1.2. Testing Location**

Location 1: CTTL (huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China 100191

Location 2: CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,  
Haidian District, Beijing, P. R. China 100191

Location 3:CTTL (BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology  
Development Area, Beijing, P. R. China 100176

### **1.3. Testing Environment**

Normal Temperature: 15-35°C

Relative Humidity: 20-75%

### **1.4. Project data**

Testing Start Date: 2019-07-25

Testing End Date: 2019-09-03

**1.5. Signature**



---

**Dong Yuan**  
**(Prepared this test report)**



---

**Zhou Yu**  
**(Reviewed this test report)**



---

**Zhao Hui Lin**  
**Deputy Director of the laboratory**  
**(Approved this test report)**



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCL Communication Ltd.  
7/F, Block F4, TCL Communication Technology Building, TCL  
Address /Post: International E City, Zhong Shan Yuan Road, Nanshan District,  
Shenzhen, Guangdong, P.R. China 518052  
Contact: Gong Zhizhou  
Email: zhizhou.gong@tcl.com  
Telephone: 0086-755-36611722  
Fax: NA

### **2.2. Manufacturer Information**

Company Name: TCL Communication Ltd.  
7/F, Block F4, TCL Communication Technology Building, TCL  
Address /Post: International E City, Zhong Shan Yuan Road, Nanshan District,  
Shenzhen, Guangdong, P.R. China 518052  
Contact: Gong Zhizhou  
Email: zhizhou.gong@tcl.com  
Telephone: 0086-755-36611722  
Fax: NA



### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	Smart Phone
Model Name	5032W
FCC ID	2ACCJB111
Antenna	Embedded
Output power	25.31dBm maximum EIRP measured for WCDMA Band II
Extreme vol. Limits	3.65VDC to 4.4VDC (nominal: 3.8VDC)
Extreme temp. Tolerance	-20°C to +60°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>IMEI</b>	<b>HW Version</b>	<b>SW Version</b>	<b>Date of receipt</b>
UT19a	015552000001472	06	3E5H	2019-07-25
UT62a	015552000001498	06	3E5H	2019-07-25

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>
AE1	Battery
AE1	
Model	TLp038B1
Manufacturer	BYD
Capacitance	4000mAh

\*AE ID: is used to identify the test sample in the lab internally.

#### **3.4. Normal Accessory setting**

Fully charged battery was used during the test.

#### **3.5. General Description**

The Equipment Under Test (EUT) is a model of Smart Phone with embedded antenna. Manual and specifications of the EUT were provided to fulfil the test.



## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-18 Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-18 Edition
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES	10-1-18 Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2016
ANSI/TIA-102.CAAA -E	DIGITAL C4FMCQPSK TRANSCEIVER MEASUREMENT METHODS	2016
ANSI C63.26	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services	2015
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS	v03r01



## 5. LABORATORY ENVIRONMENT

**Control room / conducted chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber 2** (8.6 meters X 6.1 meters X 3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 1 Ω
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

**Semi-anechoic chamber 2 / Fully-anechoic chamber 3** (10 meters X 6.7 meters X 6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz



## 6. SUMMARY OF TEST RESULT

### WCDMA Band II

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	24.232	P
2	Emission Limit	2.1051/24.238	P
3	Frequency Stability	2.1055	P
4	Occupied Bandwidth	2.1049	P
5	Emission Bandwidth	24.238	P
6	Band Edge Compliance	24.238	P
7	Conducted Spurious Emission	24.238	P
8	Peak-to-Average Power Ratio	24.232	P

### WCDMA Band V

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	22.913	P
2	Emission Limit	2.1051/22.917	P
3	Frequency Stability	2.1055	P
4	Occupied Bandwidth	2.1049	P
5	Emission Bandwidth	22.917	P
6	Band Edge Compliance	22.917	P
7	Conducted Spurious Emission	22.917	P

### WCDMA Band IV

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	P
2	Emission Limit	2.1051/27.53	P
3	Frequency Stability	2.1055	P
4	Occupied Bandwidth	2.1049	P
5	Emission Bandwidth	27.53	P
6	Band Edge Compliance	27.53	P
7	Conducted Spurious Emission	27.53	P
8	Peak-to-Average Power Ratio	27.50	P



Terms used in Verdict column

P	Pass. The EUT complies with the essential requirements in the standard.
NP	Not Performed The test was not performed by CTTL.
NA	Not Applicable. The test was not applicable.
BR	Re-use test data from basic model report.
F	Fail. The EUT does not comply with the essential requirements in the standard.



## 7. TestEquipments Utilized

NO.	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	Test Receiver	ESU26	100235	R&S	2020-02-14	1 year
2	Test Receiver	ESU26	100376	R&S	2019-11-17	1 year
3	EMI Antenna	3117	00058889	ETS-Lindgren	2020-01-12	3 year
4	Universal Radio Communication Tester	CMU200	108646	R&S	2020-01-03	1 year
5	Spectrum Analyzer	FSU26	200030	R&S	2020-06-03	1 year
6	EMI Antenna	VULB9163	9163-235	2019-11-20	2019-11-20	1 year
7	Signal Generator	SMF100A	101295	R&S	2019-11-27	1 year
8	Climate chamber	SH-242	93008556	ESPEC	2019-12-21	2 year
10	Wireless Communication Test Set	E5515E	MY5321101 2	Agilent	2020-08-06	1 year

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 OUTPUT POWER**

#### **A.1.1 Summary**

During the process of testing, the EUT was controlled via communication tester to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### **A.1.2 Conducted**

##### **A.1.2.1 Method of Measurements**

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II; 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V; 1712.4MHz, 1732.4MHz and 1752.6MHz for WCDMA Band IV (bottom, middle and top of operational frequency range).

#### **WCDMA Band II**

##### **Measurement result-QPSK**

	CH	Frequency (MHz)	output power(dBm)
WCDMA (Band II)	9262	1852.4	23.57
	9400	1880.0	23.64
	9538	1907.6	23.68

##### **Measurement result-16QAM**

	CH	Frequency (MHz)	output power (dBm)
WCDMA (Band II)	9262	1852.4	22.07
	9400	1880.0	22.20
	9538	1907.6	22.07

#### **WCDMA Band V**

##### **Measurement result-QPSK**

	CH	Frequency (MHz)	output power(dBm)
WCDMA (Band V)	4132	826.4	23.48
	4183	836.6	23.51
	4233	846.6	23.53

##### **Measurement result-16QAM**

	CH	Frequency (MHz)	output power (dBm)
WCDMA (Band V)	4132	826.4	21.78
	4183	836.6	21.99
	4233	846.6	22.08



**WCDMA Band IV**

**Measurement result-QPSK**

WCDMA (Band IV)	CH	Frequency (MHz)	output power(dBm)
	1312	1712.4	23.58
	1412	1732.4	23.55
	1513	1752.6	23.61

**Measurement result-16QAM**

WCDMA (Band IV)	CH	Frequency (MHz)	output power (dBm)
	1312	1712.4	21.69
	1412	1732.4	21.87
	1513	1752.6	21.80

### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."


Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Rule Part 27.50(d)(2) specifies, "Fixed, mobile, and portable (handheld)stations operating in the 1710–1755MHz band are limited to a peak EIRP of 1 watt."


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5-meter-high non-conductive stand at a 3-meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360°and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the

reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the Amplifier and the Substitution Antenna. The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .





**WCDMA Band II-EIRP**

**Limits**

	Burst Peak EIRP (dBm)
WCDMA Band II	≤33dBm (2W)

**Measurement result-QPSK**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>ci</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.40	-21.65	2.84	43.75	4.87	24.13	33.00	8.87	H
1880.00	-20.64	2.85	43.75	4.82	25.08	33.00	7.92	H
1907.60	-20.35	2.88	43.77	4.77	25.31	33.00	7.69	H

**Measurement result-16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>ci</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.40	-22.62	2.84	43.75	4.87	23.16	33.00	9.84	H
1880.00	-21.68	2.85	43.75	4.82	24.04	33.00	8.96	H
1907.60	-21.36	2.88	43.77	4.77	24.30	33.00	8.70	H

**ANALYZER SETTINGS: RBW = VBW = 5MHz**

Frequency: 1907.60MHz

Peak EIRP (dBm)=P<sub>Mea</sub>(-20.35)-P<sub>ci</sub>(2.88dB)-P<sub>Ag</sub>(-43.77dB)-G<sub>a</sub> (-4.77dB)= 25.31dBm

**WCDMA Band V-ERP**

**Limits**

	Burst Peak ERP (dBm)
WCDMA Band V	≤38.45dBm

**Measurement result-QPSK**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>ci</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.40	-21.82	2.25	45.76	0.93	2.15	20.47	38.45	17.98	H
836.60	-21.70	2.26	45.66	0.82	2.15	20.37	38.45	18.08	H
846.60	-22.95	2.26	45.56	0.81	2.15	19.01	38.45	19.44	H

**Measurement result-16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>ci</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.40	-22.72	2.25	45.76	0.93	2.15	19.57	38.45	18.88	H
836.60	-22.61	2.26	45.66	0.82	2.15	19.46	38.45	18.99	H
846.60	-23.83	2.26	45.56	0.81	2.15	18.13	38.45	20.32	H

**ANALYZER SETTINGS: RBW = VBW = 5MHz**

Frequency: 826.40MHz

Peak ERP (dBm)=P<sub>Mea</sub>(-21.82dBm)-P<sub>ci</sub>(2.25dB)-P<sub>Ag</sub>(-45.76dB)-G<sub>a</sub> (-0.93dB)-2.15dB= 20.47dBm



**WCDMA Band IV-EIRP**

**Limits**

	Burst Peak EIRP (dBm)
WCDMA Band IV	30dBm (1W)

**Measurement result-QPSK**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.40	-21.88	3.66	44.10	5.12	23.68	30.00	6.32	H
1732.40	-23.11	3.31	44.13	5.08	22.80	30.00	7.20	H
1752.60	-20.99	3.85	44.14	5.05	24.35	30.00	5.65	H

**Measurement result-16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.40	-22.90	3.66	44.10	5.12	22.66	30.00	7.34	H
1732.40	-23.95	3.31	44.13	5.08	21.96	30.00	8.04	H
1752.60	-21.88	3.85	44.14	5.05	23.46	30.00	6.54	H

**ANALYZER SETTINGS: RBW = VBW = 5MHz**

Frequency: 1752.60MHz

Peak EIRP (dBm)=P<sub>Mea</sub>(-20.99dBm)-P<sub>cl</sub>(3.85dB)-P<sub>Ag</sub>(-44.14dB)-G<sub>a</sub> (-5.05dB)= 24.35dBm

**Note: The EUT is tested in vertical polarization mode**

## **A.2 EMISSION LIMIT**


### **A.2.1 Measurement Method**

The measurements procedures in TIA-603E-2016 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238, Part 22.917, Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II, WCDMA Band V and WCDMA Band IV.

#### **The procedure of radiated spurious emissions is as follows:**

1. EUT was placed on a 1.5-meter-high non-conductive stand at a 3-meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the

substitution antenna and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_{pl}$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

An amplifier should be connected in for the test.

The Path loss ( $P_{pl}$ ) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{Mea} - P_{pl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

### A.2.2 Measurement Limit

Part 24.238, Part 22.917 and Part 27.53 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power ( $P$ ) by a factor of at least  $43 + 10\log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power ( $P$ ) by at least  $43 + 10\log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of WCDMA Band II (1852.4 MHz, 1880.0MHz and 1907.6MHz), WCDMA Band V (826.4MHz, 836.6MHz and 846.6MHz) and WCDMA Band IV (1712.4MHz, 1732.4MHz and 1752.6MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II, WCDMA Band V and WCDMA Band IV into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.



**A.2.4 Measurement Results Table**

Frequency	Channel	Frequency Range	Result
WCDMA Band V	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
WCDMA Band II	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass
WCDMA Band IV	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

**A.2.5 Sweep Table**

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
WCDMA Band V	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
WCDMA Band II	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
WCDMA Band IV	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2



**WCDMA BAND II Mode Channel 9262/1852.4MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
7408.01	-53.22	8.14	12.09	-49.27	-13.00	36.27	H
9270.01	-53.33	9.08	13.26	-49.15	-13.00	36.15	V
11120.01	-50.53	9.75	13.18	-47.10	-13.00	34.10	H
12943.01	-49.63	10.49	13.47	-46.65	-13.00	33.65	H
14809.00	-45.69	11.13	14.15	-42.67	-13.00	29.67	H
16692.00	-42.70	11.75	13.68	-40.77	-13.00	27.77	V

**WCDMA BAND II Mode Channel 9400/1880MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
7520.01	-53.28	8.31	12.22	-49.37	-13.00	36.37	H
9415.01	-53.43	9.11	13.35	-49.19	-13.00	36.19	H
11288.01	-49.96	9.92	13.14	-46.74	-13.00	33.74	H
13148.01	-48.22	10.73	13.71	-45.24	-13.00	32.24	H
15015.00	-45.28	11.24	13.99	-42.53	-13.00	29.53	V
16940.00	-42.29	12.15	13.78	-40.66	-13.00	27.66	V

**WCDMA BAND II Mode Channel 9538/1907.6MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
7632.01	-52.21	8.12	12.31	-48.02	-13.00	35.02	H
9539.01	-51.24	9.40	13.36	-47.28	-13.00	34.28	H
11483.01	-50.23	9.85	13.10	-46.98	-13.00	33.98	H
13349.01	-47.97	10.57	13.99	-44.55	-13.00	31.55	H
15301.00	-45.75	11.28	13.82	-43.21	-13.00	30.21	H
17209.00	-43.24	12.35	14.26	-41.33	-13.00	28.33	V



**WCDMA BAND V Mode Channel 4132/826.4MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
1662.01	-60.13	3.57	5.21	2.15	-60.64	-13.00	47.64	V
2467.00	-53.56	4.59	6.00	2.15	-54.30	-13.00	41.30	V
3309.02	-55.47	5.29	7.74	2.15	-55.17	-13.00	42.17	H
4122.02	-55.61	6.04	9.02	2.15	-54.78	-13.00	41.78	H
4962.01	-54.26	6.67	9.86	2.15	-53.22	-13.00	40.22	H
5757.01	-53.70	7.25	10.55	2.15	-52.55	-13.00	39.55	H

**WCDMA BAND V Mode Channel 4183/836.6MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
1661.01	-60.02	3.57	5.21	2.15	-60.53	-13.00	47.53	H
2510.00	-53.71	4.63	6.12	2.15	-54.37	-13.00	41.37	H
3347.02	-54.56	5.32	7.83	2.15	-54.20	-13.00	41.20	H
4191.02	-54.52	6.19	9.09	2.15	-53.77	-13.00	40.77	V
5017.01	-55.51	6.57	9.92	2.15	-54.31	-13.00	41.31	V
5860.01	-53.77	7.27	10.53	2.15	-52.66	-13.00	39.66	V

**WCDMA BAND V Mode Channel 4233/846.6MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
1713.01	-59.97	3.61	5.12	2.15	-60.61	-13.00	47.61	V
2545.00	-52.63	4.66	6.18	2.15	-53.26	-13.00	40.26	H
3379.02	-55.23	5.34	7.91	2.15	-54.81	-13.00	41.81	V
4262.02	-54.99	6.23	9.16	2.15	-54.21	-13.00	41.21	H
5083.01	-55.62	6.72	10.02	2.15	-54.47	-13.00	41.47	H
5935.01	-52.93	7.47	10.51	2.15	-52.04	-13.00	39.04	H



**WCDMA BAND IV Mode Channel 1312/1712.4MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
8716.01	-54.61	8.41	13.04	-49.98	-13.00	36.98	H
10454.01	-51.65	9.72	13.08	-48.29	-13.00	35.29	V
12167.01	-49.10	10.15	13.07	-46.18	-13.00	33.18	V
13935.01	-47.79	10.82	14.46	-44.15	-13.00	31.15	V
15654.00	-45.50	11.55	13.70	-43.35	-13.00	30.35	H
17400.00	-43.22	12.50	14.68	-41.04	-13.00	28.04	V

**WCDMA BAND IV Mode Channel 1412/1732.4MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
8663.01	-54.51	8.41	13.03	-49.89	-13.00	36.89	H
10404.01	-49.30	9.80	13.06	-46.04	-13.00	33.04	H
12117.01	-49.20	10.30	13.05	-46.45	-13.00	33.45	H
13866.01	-48.36	10.74	14.42	-44.68	-13.00	31.68	V
15574.00	-46.60	11.50	13.70	-44.40	-13.00	31.40	H
17342.00	-42.37	12.43	14.55	-40.25	-13.00	27.25	H

**WCDMA BAND IV Mode Channel 1513/1752.6MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
8708.01	-55.41	8.38	13.04	-50.75	-13.00	37.75	H
10433.01	-51.34	9.75	13.07	-48.02	-13.00	35.02	V
12185.01	-49.23	10.10	13.07	-46.26	-13.00	33.26	H
13935.01	-47.87	10.82	14.46	-44.23	-13.00	31.23	V
15672.00	-45.13	11.57	13.70	-43.00	-13.00	30.00	H
17404.00	-42.59	12.51	14.69	-40.41	-13.00	27.41	H



### **A.3 FREQUENCY STABILITY**

#### **A.3.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER and Agilent E5515E Wireless Communication Test Set.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -20°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 or E5515E and in a simulated call on mid channel of WCDMA Band II, WCDMA Band IV and WCDMA Band V, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -20°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 or E5515E and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10°C increments from -20°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.65VDC and 4.4VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.

**A.3.2 Measurement results****Frequency Error vs Voltage-QPSK**

Voltage (V)	Frequency error (Hz)	Frequency error (ppm)
3.65	-19.33	0.0103
3.8	-16.48	0.0088
4.4	-18.20	0.0097

**Frequency Error vs Temperature-QPSK**

Temperature (°C)	Frequency error (Hz)	Frequency error (ppm)
-20	-17.07	0.0091
-10	-15.26	0.0081
0	-15.85	0.0084
10	-13.85	0.0074
20	-13.02	0.0069
30	-13.84	0.0074
40	-14.16	0.0075
50	-13.87	0.0074

**Frequency Error vs Voltage-16QAM**

Voltage (V)	Frequency error (Hz)	Frequency error (ppm)
3.65	-13.22	0.0070
3.8	-16.09	0.0086
4.4	-14.41	0.0077

**Frequency Error vs Temperature-16QAM**

Temperature (°C)	Frequency error (Hz)	Frequency error (ppm)
-20	-16.21	0.0086
-10	-14.00	0.0074
0	-16.86	0.0090
10	-13.33	0.0071
20	-17.72	0.0094
30	-8.86	0.0047
40	-13.41	0.0071
50	-15.23	0.0081



**WCDMA Band V**

**Frequency Error vs Voltage-QPSK**

Voltage (V)	Frequency error (Hz)	Frequency error (ppm)
3.65	-14.54	0.0174
3.8	-12.99	0.0155
4.4	-10.76	0.0129

**Frequency Error vs Temperature-QPSK**

Temperature (°C)	Frequency error (Hz)	Frequency error (ppm)
-20	-12.12	0.0145
-10	-7.97	0.0095
0	-6.09	0.0073
10	-12.30	0.0147
20	-6.81	0.0081
30	-11.00	0.0131
40	-6.68	0.0080
50	-9.87	0.0118

**Frequency Error vs Voltage-16QAM**

Voltage (V)	Frequency error (Hz)	Frequency error (ppm)
3.65	-3.72	0.0044
3.8	-5.93	0.0071
4.4	-9.61	0.0115

**Frequency Error vs Temperature-16QAM**

Temperature (°C)	Frequency error (Hz)	Frequency error (ppm)
-20	-15.40	0.0184
-10	-7.39	0.0088
0	-10.01	0.0120
10	-7.13	0.0085
20	-8.53	0.0102
30	-14.49	0.0173
40	-6.12	0.0073
50	-8.34	0.0100



**WCDMA Band IV**

**Frequency Error vs Voltage-QPSK**

Voltage (V)	Frequency error (Hz)	Frequency error (ppm)
3.65	-14.02	0.0081
3.8	-14.40	0.0083
4.4	-12.34	0.0071

**Frequency Error vs Temperature-QPSK**

Temperature (°C)	Frequency error (Hz)	Frequency error (ppm)
-20	-13.93	0.0080
-10	-15.79	0.0091
0	-14.76	0.0085
10	-16.68	0.0096
20	-13.40	0.0077
30	-10.31	0.0060
40	-11.28	0.0065
50	-7.13	0.0041

**Frequency Error vs Voltage-16QAM**

Voltage (V)	Frequency error (Hz)	Frequency error (ppm)
3.65	-13.52	0.0078
3.8	-5.40	0.0031
4.4	-11.16	0.0064

**Frequency Error vs Temperature-16QAM**

Temperature (°C)	Frequency error (Hz)	Frequency error (ppm)
-20	-7.53	0.0043
-10	-4.16	0.0024
0	-8.49	0.0049
10	-9.81	0.0057
20	-9.70	0.0056
30	-13.08	0.0076
40	-3.43	0.0020
50	-17.89	0.0103



## **A.4 OCCUPIED BANDWIDTH**

### **A.4.1 Occupied Bandwidth Results**

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from KDB 971168 4.2:


- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least  $10\log(\text{OBW} / \text{RBW})$  below the reference level.
- d) Set the detection mode to peak, and the trace mode to max hold.
- e) Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

**WCDMA Band II (99% BW)-QPSK**

Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)
1852.4	4182.69
1880.0	4182.69
1907.6	4182.69

**WCDMA Band II**


**Channel 9262-Occupied Bandwidth (99% BW)**



Date: 26.JUL.2019 08:35:51




### Channel 9400-Occupied Bandwidth (99% BW)



Date: 26.JUL.2019 08:37:02

### Channel 9538-Occupied Bandwidth (99% BW)



Date: 26.JUL.2019 08:38:12




**WCDMA Band II (99% BW)-16QAM**

Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)
1852.4	4166.67
1880.0	4166.67
1907.6	4182.69

**WCDMA Band II**


**Channel 9262-Occupied Bandwidth (99% BW)**



Date: 11.SEP.2019 14:16:55




### Channel 9400-Occupied Bandwidth (99% BW)



Date: 11.SEP.2019 14:18:06

### Channel 9538-Occupied Bandwidth (99% BW)



Date: 11.SEP.2019 14:19:18




**WCDMA Band V(99% BW)-QPSK**

Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)
826.4	4182.69
836.6	4182.69
846.6	4182.69

**WCDMA Band V**


**Channel 4132-Occupied Bandwidth (99% BW)**



Date: 26.JUL.2019 08:44:32




### Channel 4183-Occupied Bandwidth (99% BW)



Date: 26.JUL.2019 08:45:43

### Channel 4233-Occupied Bandwidth (99% BW)



Date: 26.JUL.2019 08:46:54




**WCDMA Band V (99% BW)-16QAM**

Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)
826.4	4182.69
836.6	4166.67
846.6	4166.67


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth (99% BW)**




Date: 11.SEP.2019 14:27:19

### Channel 4183-Occupied Bandwidth (99% BW)



Date: 11.SEP.2019 14:28:30

### Channel 4233-Occupied Bandwidth (99% BW)



Date: 11.SEP.2019 14:29:42




**WCDMA Band IV (99% BW)-QPSK**

Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)
1712.4	4182.69
1732.4	4182.69
1752.6	4182.69


**WCDMA Band IV**

**Channel 1312-Occupied Bandwidth (99% BW)**




Date: 26.JUL.2019 08:40:02

### Channel 1412-Occupied Bandwidth (99% BW)



Date: 26.JUL.2019 08:41:13

### Channel 1513-Occupied Bandwidth (99% BW)



Date: 26.JUL.2019 08:42:24




**WCDMA Band IV (99% BW)-16QAM**

Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)
1712.4	4166.67
1732.4	4182.69
1752.6	4182.69

**WCDMA Band IV**


**Channel 1312-Occupied Bandwidth (99% BW)**



Date: 11.SEP.2019 14:21:36




### Channel 1412-Occupied Bandwidth (99% BW)



Date: 11.SEP.2019 14:22:48

### Channel 1513-Occupied Bandwidth (99% BW)



Date: 11.SEP.2019 14:23:59



## A.5 EMISSION BANDWIDTH

### A.5.1 Emission Bandwidth Results


The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

#### WCDMA Band II-QPSK

Frequency (MHz)	Emission Bandwidth (kHz)
1852.4	4711.54
1880.0	4711.54
1907.6	4695.51


#### WCDMA Band II

##### Channel 9262-Emission Bandwidth




Date: 26.JUL.2019 08:48:56

### Channel 9400-Emission Bandwidth



Date: 26.JUL.2019 08:50:07

### Channel 9538-Emission Bandwidth



Date: 26.JUL.2019 08:51:18




**WCDMA Band II -16QAM**

Frequency (MHz)	Emission Bandwidth (kHz)
1852.4	4679.49
1880.0	4679.49
1907.6	4663.46

**WCDMA Band II**


**Channel 9262-Emission Bandwidth**



Date: 11.SEP.2019 14:33:03




### Channel 9400-Emission Bandwidth



Date: 11.SEP.2019 14:34:15

### Channel 9538-Emission Bandwidth



Date: 11.SEP.2019 14:35:27




**WCDMA Band V-QPSK**

Frequency (MHz)	Emission Bandwidth (kHz)
826.40	4711.54
836.60	4711.54
846.60	4711.54


**WCDMA Band V**

**Channel 4132-Emission Bandwidth**




Date: 26.JUL.2019 08:57:23

### Channel 4183-Emission Bandwidth



Date: 26.JUL.2019 08:58:34

### Channel 4233-Emission Bandwidth



Date: 26.JUL.2019 08:59:46




**WCDMA Band V-16QAM**

Frequency (MHz)	Emission Bandwidth (kHz)
826.40	4663.46
836.60	4663.46
846.60	4647.44

**WCDMA Band V**

**Channel 4132-Emission Bandwidth**




Date: 11.SEP.2019 14:42:03






### Channel 4183-Emission Bandwidth



Date: 11.SEP.2019 14:43:15

### Channel 4233-Emission Bandwidth



Date: 11.SEP.2019 14:44:26




**WCDMA Band IV-QPSK**

Frequency (MHz)	Emission Bandwidth (kHz)
1712.4	4695.51
1732.4	4679.49
1752.6	4695.51

**WCDMA Band IV**


**Channel 1312-Emission Bandwidth**



Date: 26.JUL.2019 08:53:10




### Channel 1412-Emission Bandwidth



Date: 26.JUL.2019 08:54:21

### Channel 1513-Emission Bandwidth



Date: 26.JUL.2019 08:55:33




**WCDMA Band IV-16QAM**

Frequency (MHz)	Emission Bandwidth (kHz)
1712.4	4695.51
1732.4	4663.46
1752.6	4679.49


**WCDMA Band IV**

**Channel 1312-Emission Bandwidth**




Date: 11.SEP.2019 14:37:33

### Channel 1412-Emission Bandwidth



Date: 11.SEP.2019 14:38:45

### Channel 1513-Emission Bandwidth



Date: 11.SEP.2019 14:39:57



## **A.6 BAND EDGE COMPLIANCE**


### **A.6.1 Measurement limit**

On any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power ( $P$ , in Watts) by at least  $43+10\text{Log}(P)$  dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm. According to KDB 971168 6.0, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

### A.6.2 Measurement result


#### WCDMA Band II-QPSK

#### LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262



Date: 26.JUL.2019 10:00:50


#### HIGH BAND EDGE BLOCK-C (WCDMA Band II) -Channel 9538



Date: 26.JUL.2019 10:01:09




### WCDMA Band II-16QAM LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262



Date: 11.SEP.2019 14:45:47

### HIGH BAND EDGE BLOCK-C (WCDMA Band II) -Channel 9538




Date: 11.SEP.2019 14:46:07






### WCDMA Band V-QPSK LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132



Date: 26.JUL.2019 10:03:25

### HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233




Date: 26.JUL.2019 10:03:45




### WCDMA Band V-16QAM

### LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132



Date: 11.SEP.2019 14:48:55


### HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233



Date: 11.SEP.2019 14:49:15




### WCDMA Band IV-QPSK LOW BAND EDGE BLOCK-A (WCDMA Band IV)-Channel 1312



Date: 26.JUL.2019 10:02:08


### HIGH BAND EDGE BLOCK-C (WCDMA Band IV) -Channel 1513



Date: 26.JUL.2019 10:02:27




### WCDMA Band IV-16QAM LOW BAND EDGE BLOCK-A (WCDMA Band IV)-Channel 1312



Date: 11.SEP.2019 14:47:21

### HIGH BAND EDGE BLOCK-C (WCDMA Band IV) –Channel 1513



Date: 11.SEP.2019 14:47:41

## **A.7 CONDUCTED SPURIOUS EMISSION**

### **A.7.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
2. Determine EUT transmit frequencies below outlines the band edge frequencies pertinent to conducted emissions testing.
3. According to KDB 971168 6.0, the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz)

#### **WCDMA Band II Transmitter**

Channel	Frequency (MHz)
9262	1852.40
9400	1880.00
9538	1907.60

#### **WCDMA Band IV Transmitter**

Channel	Frequency (MHz)
1312	1712.40
1412	1732.40
1513	1752.60

#### **WCDMA Band V Transmitter**

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60

### **A. 7.2 Measurement Limit**

Part 24.238, Part 22.917 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A.7.3 Measurement result

#### WCDMA Band II

#### Channel 9262: 30MHz – 19.15GHz


Spurious emission limit –13dBm.



Date: 26.JUL.2019 09:04:57

#### Channel 9400: 30MHz – 19.15GHz


Spurious emission limit –13dBm.



Date: 26.JUL.2019 09:05:12




**Channel 9538: 30MHz –19.15GHz**  
Spurious emission limit –13dBm.



Date: 26.JUL.2019 09:05:27




**WCDMA Band IV**  
**Channel 1312: 30MHz –17.80GHz**  
Spurious emission limit –13dBm.



Date: 26.JUL.2019 09:06:21

**WCDMA Band IV**  
**Channel 1412: 30MHz –17.80GHz**  
Spurious emission limit –13dBm.




Date: 26.JUL.2019 09:06:36






**WCDMA Band IV**  
**Channel 1513: 30MHz -17.80GHz**  
Spurious emission limit -13dBm.




Date: 26.JUL.2019 09:06:52

**WCDMA Band V**  
**Channel 4132: 30MHz –8.49GHz**  
Spurious emission limit –13dBm.



Date: 26.JUL.2019 09:07:46


**Channel 4183: 30MHz –8.49GHz**  
Spurious emission limit –13dBm.



Date: 26.JUL.2019 09:08:01



**Channel 4233: 30MHz –8.49GHz**  
Spurious emission limit –13dBm.



Date: 26.JUL.2019 09:08:16

## **A.8 PEAK-TO-AVERAGE POWER RATIO**

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

According to KDB 971168:

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e) Record the maximum PAPR level associated with a probability of 0.1%

### **A.8.1 Measurement limit**

not exceed 13 dB

### **A.8.2 Measurement results**

#### **WCDMA Band II-QPSK**

##### **Measurement result**

CH	Frequency (MHz)	PAPR (dB)
9400	1880.0	3.69

#### **WCDMA Band II-16QAM**

##### **Measurement result**

CH	Frequency (MHz)	PAPR (dB)
9400	1880.0	5.03

#### **WCDMA Band IV-QPSK**

##### **Measurement result**

CH	Frequency (MHz)	PAPR (dB)
1412	1732.4	3.56

#### **WCDMA Band IV-16QAM**

##### **Measurement result**

CH	Frequency (MHz)	PAPR (dB)
1412	1732.4	4.58



**ANNEX B: Accreditation Certificate**

United States Department of Commerce  
National Institute of Standards and Technology

**NVLAP**<sup>®</sup>

---

**Certificate of Accreditation to ISO/IEC 17025:2005**

---

NVLAP LAB CODE: 600118-0

**Telecommunication Technology Labs, CAICT**  
Beijing  
China

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,  
listed on the Scope of Accreditation, for:*

**Electromagnetic Compatibility & Telecommunications**

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.  
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality  
management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).*

2018-09-28 through 2019-09-30  
*Effective Dates*



  
*For the National Voluntary Laboratory Accreditation Program*

\*\*\*END OF REPORT\*\*\*