



# TEST REPORT

No. I20N02192-BLE

TCL Communication Ltd.

LTE/UMTS/GSM Smartphone

Model Name: 5030M, 5130M

with

Hardware Version: FS180-MB-V1.0A

Software Version: 5030M\_OFAR\_1SIM\_V1.0\_20200804\_UNLOCK

FCC ID: 2ACCJB118

Issued Date: 2020-08-17

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

**Test Laboratory:**

**Shenzhen Academy of Information and Communications Technology**

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518026.

Tel: +86(0)755-33322000, Fax: +86(0)755-33322001

Email: yewu@caict.ac.cn, website: [www.cszit.com](http://www.cszit.com)

## **CONTENTS**

<b>1. SUMMARY OF TEST REPORT.....</b>	<b>3</b>
1.1. TEST ITEMS.....	3
1.2. TEST STANDARDS .....	3
1.3. TEST RESULT .....	3
1.4. TESTING LOCATION .....	3
1.5. PROJECT DATA .....	3
1.6. SIGNATURE .....	3
<b>2. CLIENT INFORMATION.....</b>	<b>4</b>
2.1. APPLICANT INFORMATION .....	4
2.2. MANUFACTURER INFORMATION .....	4
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>5</b>
3.1. ABOUT EUT .....	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....	5
3.4. GENERAL DESCRIPTION.....	6
<b>4. REFERENCE DOCUMENTS .....</b>	<b>7</b>
4.1. DOCUMENTS SUPPLIED BY APPLICANT .....	7
4.2. REFERENCE DOCUMENTS FOR TESTING.....	7
<b>5. TEST RESULTS .....</b>	<b>8</b>
5.1. TESTING ENVIRONMENT.....	8
5.2. TEST RESULTS .....	8
5.3. STATEMENTS.....	8
<b>6. TEST EQUIPMENTS UTILIZED .....</b>	<b>9</b>
<b>7. LABORATORY ENVIRONMENT .....</b>	<b>10</b>
<b>8. MEASUREMENT UNCERTAINTY .....</b>	<b>11</b>
<b>ANNEX A: DETAILED TEST RESULTS.....</b>	<b>12</b>
A.0 ANTENNA REQUIREMENT .....	12
A.1 MAXIMUM PEAK OUTPUT POWER .....	13
A.2 PEAK POWER SPECTRAL DENSITY .....	14
A.3 6dB BANDWIDTH.....	16
A.4 BAND EDGES COMPLIANCE .....	18
A.5 TRANSMITTER SPURIOUS EMISSION - CONDUCTED .....	20
A.6 TRANSMITTER SPURIOUS EMISSION - RADIATED .....	27
A.7 AC POWER LINE CONDUCTED EMISSION .....	37

## 1. Summary of Test Report

### 1.1. Test Items

Description	LTE/UMTS/GSM Smartphone
Model Name	5030M, 5130M
Applicant's name	TCL Communication Ltd.
Manufacturer's Name	TCL Communication Ltd.

### 1.2. Test Standards

FCC Part15-2019; ANSI C63.10-2013

### 1.3. Test Result

**Pass**


### 1.4. Testing Location

Address: Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China

### 1.5. Project data

Testing Start Date:	2020-03-20
Testing End Date:	2020-03-27

### 1.6. Signature



---

Lin Kanfeng  
(Prepared this test report)



---

Tang Weisheng  
(Reviewed this test report)



---

Zhang Bojun  
(Approved this test report)



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCL Communication Ltd.  
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong  
Contact Person: Gong Zhizhou  
E-Mail: zhizhou.gong@tcl.com  
Telephone: 0086-755-36611722  
Fax: 0086-755-36612000-81722

### **2.2. Manufacturer Information**

Company Name: TCL Communication Ltd.  
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong  
Contact Person: Gong Zhizhou  
E-Mail: zhizhou.gong@tcl.com  
Telephone: 0086-755-36611722  
Fax: 0086-755-36612000-81722

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	LTE/UMTS/GSM Smartphone
Model Name	5030M, 5130M
Brand Name	Alcatel, TCL
Frequency Range	2400MHz~2483.5MHz
Type of Modulation	GFSK/π /4 DQPSK/8DPSK
Number of Channels	79
Antenna Type	Integrated
Antenna Gain	-1.2dBi
Power Supply	3.85V DC by Battery
FCC ID	2ACCJB118
Condition of EUT as received	No abnormality in appearance

Note1: According to the customer's description, 5030M is a variant product of 5030J, and it only changes memory. All results were from the initial model. The initial model report number is I20N00391-BLE.

Note2: According to the customer's description, 5130M is a variant product of 5030M. All test results suit for both models.

Note3: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Shenzhen Academy of Information and Communications Technology.

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>IMEI</b>	<b>HW Version</b>	<b>SW Version</b>	<b>Receive Date</b>
EUT1	354827110000146	FS180-MB-V1.0A	5030M_OFAR_1SIM_V1.0_20200804_UNLOCK	2020-03-13
EUT2	354827110000161	FS180-MB-V1.0A	5030M_OFAR_1SIM_V1.0_20200804_UNLOCK	2020-03-13

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>	<b>SN</b>
AE1	Battery	CAC3860025C7
AE2	Battery	CAC3860032CA
AE3	Charger	/
AE4	Charger	/

AE1

Model	TLp038D7
Manufacturer	VENKE



Capacity	4000mAh
Nominal Voltage	3.85v

## AE2

Model	TLp038DA
Manufacturer	TIANMAO
Capacitance	4000mAh
Nominal Voltage	3.85v

## AE3

Model	UC13US/CBA0059AGAC7
Manufacturer	CHENYANG

## AE4

Model	UC13US/CBA0059AGAC5
Manufacturer	PUAN

\*AE ID: is used to identify the test sample in the lab internally.

### **3.4. General Description**

The Equipment under Test (EUT) is a model of LTE/UMTS/GSM Smartphone with integrated antenna and battery.

It consists of normal options: Lithium Battery, Charger and Headset.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.



#### **4. Reference Documents**

##### **4.1. Documents supplied by applicant**

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

##### **4.2. Reference Documents for testing**

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz	2019
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	2013

## 5. Test Results

### 5.1. Testing Environment

Normal Temperature: 15~35°C

Relative Humidity: 20~75%

### 5.2. Test Results

No	Test cases	Sub-clause of Part 15C	Verdict
0	Antenna Requirement	15.203	P
1	Maximum Peak Output Power	15.247 (b)	P
2	Peak Power Spectral Density	15.247 (e)	P
3	6dB Bandwidth	15.247 (a)	P
4	Band Edges Compliance	15.247 (d)	P
5	Transmitter Spurious Emission - Conducted	15.247 (d)	P
6	Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	P
7	AC Power line Conducted Emission	15.107, 15.207	P

See **ANNEX A** for details.

### 5.3. Statements

SAICT has evaluated the test cases requested by the applicant/manufacture as listed in section 5.2 of this report, for the EUT specified in section 3, according to the standards or reference documents listed in section 4.2.



## 6. Test Equipments Utilized

### Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Date	Calibration Period
1	Vector Signal Analyzer	FSV40	100903	Rohde & Schwarz	2021-01-15	1 year
2	Power Sensor	U2021XA	MY55430013	Agilent	2021-01-15	1 year
3	Data Acquisition	U2531A	TW55443507	Agilent	/	/

### Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Date	Calibration Period
1	LISN	ESH2-Z5	100196	R&S	2021-01-02	1 year
2	Test Receiver	ESCI	100701	R&S	2020-08-06	1 year
3	Loop Antenna	HLA6120	35779	TESEQ	2022-05-01	3 year
4	BiLog Antenna	VULB9163	9163 329	Schwarzbeck	2021-02-16	3 year
5	Horn Antenna	3117	00066585	ETS-Lindgren	2022-03-04	3 year
6	Test Receiver	ESR7	101675	R&S	2020-07-18	1 year
7	Spectrum Analyzer	FSP 40	100378	R&S	2020-12-12	1 year
8	Chamber	FACT5-2.0	4166	ETS-Lindgren	2021-05-12	3 year
9	Antenna	QSH-SL-1 8-26-S-20	17013	Q-par	2021-01-14	3 year
10	Antenna	QSH-SL-2 6-40-K-20	17014	Q-par	2021-01-10	3 year

### Test software

No.	Equipment	Manufacturer	Version
1	TechMgr Software	CAICT	2.1.1
2	EMC32	Rohde & Schwarz	8.53.0
3	EMC32	Rohde & Schwarz	10.01.00

EUT is engineering software provided by the customer to control the transmitting signal.

The EUT was programmed to be in continuously transmitting mode.

### Anechoic chamber

Fully anechoic chamber by ETS-Lindgren

## 7. Laboratory Environment

### Semi-anechoic chambe

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ±4 dB, 3 m distance, from 30 to 1000 MHz

### Shielded room

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-1000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω

### Fully-anechoic chamber

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 18 GHz, 3 m distance
Uniformity of field strength	Between 0 and 6 dB, from 80 to 6000 MHz

## 8. Measurement Uncertainty

Test Name	Uncertainty ( $k=2$ )	
1. RF Output Power - Conducted	1.32dB	
2. Power Spectral Density - Conducted	2.32dB	
3. Occupied channel bandwidth - Conducted	66Hz	
4. Transmitter Spurious Emission - Conducted	$30\text{MHz} \leq f \leq 1\text{GHz}$	1.41dB
	$1\text{GHz} \leq f \leq 7\text{GHz}$	1.92dB
	$7\text{GHz} \leq f \leq 13\text{GHz}$	2.31dB
	$13\text{GHz} \leq f \leq 26\text{GHz}$	2.61dB
5. Transmitter Spurious Emission - Radiated	$9\text{kHz} \leq f \leq 30\text{MHz}$	1.70dB
	$30\text{MHz} \leq f \leq 1\text{GHz}$	4.90dB
	$1\text{GHz} \leq f \leq 18\text{GHz}$	4.60dB
	$18\text{GHz} \leq f \leq 40\text{GHz}$	4.10dB
6. AC Power line Conducted Emission	$150\text{kHz} \leq f \leq 30\text{MHz}$	3.00dB

## **ANNEX A: Detailed Test Results**

### **A.0 Antenna requirement**

#### **Measurement Limit:**

<b>Standard</b>	<b>Requirement</b>
FCC CRF Part 15.203	<p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.</p>

Conclusion: The Directional gains of antenna used for transmitting is -1.2 dBi. The RF transmitter uses an integrate antenna without connector.



### A.1 Maximum Peak Output Power

**Method of Measurement: See ANSI C63.10-clause 11.9.1.3**

The maximum peak conducted output power may be measured using a broadband peak RF power meter.

**Measurement Limit:**

Standard	Limit (dBm)	E.I.R.P Limit (dBm)
FCC CRF Part 15.247(b)	< 30	< 36

**Measurement Results:**

**LE-1M**

Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)	E.I.R.P (dBm)	Conclusion
GFSK	2402 (CH0)	-7.67	-8.87	<b>P</b>
	2440 (CH19)	-6.20	-7.40	<b>P</b>
	2480 (CH39)	-6.26	-7.46	<b>P</b>

**Conclusion: Pass**

## A.2 Peak Power Spectral Density

Method of Measurement: See ANSI C63.10-clause 11.10.2

Measurement Limit:

Standard	Limit
FCC CRF Part 15.247(e)	< 8 dBm/3 kHz

Measurement Results:

Mode	Frequency (MHz)	Peak Power Spectral Density (dBm)	Conclusion
LE-1M	2402 (CH0)	Fig.1	P
	2440 (CH19)	Fig.2	P
	2480 (CH39)	Fig.3	P

See below for test graphs.

Conclusion: PASS






Fig.1 Power Spectral Density (Ch 0), LE 1M



**Fig.2 Power Spectral Density (Ch 19), LE 1M**



**Fig.3 Power Spectral Density (Ch 39), LE 1M**

### A.3 6dB Bandwidth

#### Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500

#### Measurement Result:

Mode	Frequency (MHz)	Test Results (kHz)		Conclusion
LE-1M	2402 (CH0)	Fig.4	666.00	P
	2440 (CH19)	Fig.5	677.50	P
	2480 (CH39)	Fig.6	663.50	P

See below for test graphs.

Conclusion: PASS




Fig.4 6dB Bandwidth (Ch 0), LE 1M





**Fig.5 6dB Bandwidth (Ch 19), LE 1M**



**Fig.6 6dB Bandwidth (Ch 39), LE 1M**

### A.4 Band Edges Compliance

Measurement Limit:

Standard	Limit (dB)
FCC 47 CFR Part 15.247 (d)	> 20

Measurement Result:

Mode	Frequency (MHz)	Test Results (dB)		Conclusion
LE-1M	2402 (CH0)	Fig.10	56.60	P
	2480 (CH39)	Fig.11	56.57	P

See below for test graphs.

Conclusion: Pass



Fig.7 Band Edges (Ch 0), LE 1M



Fig.8 Band Edges (Ch 39), LE 1M

### A.5 Transmitter Spurious Emission - Conducted

#### Measurement Limit:


Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100kHz bandwidth

#### Measurement Results:


MODE	Channel	Frequency Range	Test Results	Conclusion
LE-1M	0	2.402 GHz	Fig.12	P
		1 GHz ~ 3 GHz	Fig.13	P
		3 GHz ~ 10 GHz	Fig.14	P
	19	2.440 GHz	Fig.15	P
		1 GHz ~ 3 GHz	Fig.16	P
		3 GHz ~ 10 GHz	Fig.17	P
	39	2.480 GHz	Fig.18	P
		1 GHz ~ 3 GHz	Fig.19	P
		3 GHz ~ 10 GHz	Fig.20	P
	All channels	30 MHz ~ 1 GHz	Fig.21	P
10 GHz ~ 26 GHz		Fig.22	P	
LE-2M	0	2.402 GHz	Fig.23	P
		1 GHz ~ 3 GHz	Fig.24	P
		3 GHz ~ 10 GHz	Fig.25	P
	19	2.440 GHz	Fig.26	P
		1 GHz ~ 3 GHz	Fig.27	P
		3 GHz ~ 10 GHz	Fig.28	P
	39	2.480 GHz	Fig.29	P
		1 GHz ~ 3 GHz	Fig.30	P
		3 GHz ~ 10 GHz	Fig.31	P
	All channels	30 MHz ~ 1 GHz	Fig.32	P
		10 GHz ~ 26 GHz	Fig.33	P

See below for test graphs.

Conclusion: Pass



**Fig.9 Conducted Spurious Emission (Ch0, Center Frequency), LE 1M**



**Fig.10 Conducted Spurious Emission (Ch0, 1 GHz-3 GHz), LE 1M**




Fig.11 Conducted Spurious Emission (Ch0, 3 GHz-10 GHz), LE 1M






Fig.12 Conducted Spurious Emission (Ch19, Center Frequency), LE 1M



**Fig.13 Conducted Spurious Emission (Ch19, 1 GHz-3 GHz), LE 1M**



**Fig.14 Conducted Spurious Emission (Ch19, 3 GHz-10 GHz), LE 1M**




Fig.15 Conducted Spurious Emission (Ch39, Center Frequency), LE 1M




Fig.16 Conducted Spurious Emission (Ch39, 1 GHz-3 GHz), LE 1M






Fig.17 Conducted Spurious Emission (Ch39, 3 GHz-10 GHz), LE 1M




Fig.18 Conducted Spurious Emission (All channels, 30 MHz-1 GHz), LE 1M




Fig.19 Conducted Spurious Emission (All channels, 10 GHz-26 GHz), LE 1M

## A.6 Transmitter Spurious Emission - Radiated

### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

### Limit in restricted band:

Frequency of emission (MHz)	Field strength ( $\mu\text{V}/\text{m}$ )	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

### Test Condition:

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time (s)
30-1000	120kHz/300kHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Note: According to the performance evaluation, the radiated emission margin of EUT is over 20dB in the band from 9kHz to 30MHz. Therefore, the measurement starts from 30MHz to tenth harmonic. The measurement results include the horizontal polarization and vertical polarization measurements.

**Measurement Results:**

Mode	Channel	Frequency Range	Test Results	Conclusion
LE-1M	0	1 GHz ~ 3 GHz	Fig.34	P
		3 GHz ~ 18 GHz	Fig.35	P
	19	9 kHz ~ 30 MHz	Fig.36	P
		30 MHz ~ 1 GHz	Fig.37	P
		1 GHz ~ 3 GHz	Fig.38	P
		3 GHz ~ 18 GHz	Fig.39	P
	39	18 GHz ~ 26.5 GHz	Fig.40	P
		1 GHz ~ 3 GHz	Fig.41	P
	Restricted Band(CH0)	3 GHz ~ 18 GHz	Fig.42	P
		2.38 GHz ~ 2.45 GHz	Fig.43	P
Restricted Band(CH39)	2.45 GHz ~ 2.5 GHz	Fig.44	P	
LE-2M	0	1 GHz ~ 3 GHz	Fig.45	P
		3 GHz ~ 18 GHz	Fig.46	P
	19	9 kHz ~ 30 MHz	Fig.47	P
		30 MHz ~ 1 GHz	Fig.48	P
		1 GHz ~ 3 GHz	Fig.49	P
		3 GHz ~ 18 GHz	Fig.50	P
	39	18 GHz ~ 26.5 GHz	Fig.51	P
		1 GHz ~ 3 GHz	Fig.52	P
	Restricted Band(CH0)	3 GHz ~ 18 GHz	Fig.53	P
		2.38 GHz ~ 2.45 GHz	Fig.54	P
Restricted Band(CH39)	2.45 GHz ~ 2.5 GHz	Fig.55	P	

See below for test graphs.

**Conclusion: Pass**

**LE-1M**
**GFSK CH0 (3-18GHz)**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
9903.00	48.87	74.00	25.13	H	4.5
10760.50	49.07	74.00	24.93	H	5
11596.50	50.48	74.00	23.52	H	6.6
12524.00	51.39	74.00	22.61	V	8.0
14535.00	52.60	74.00	21.40	V	11.4
17131.50	55.54	74.00	18.46	H	15.0

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
6405.50	36.69	54.00	17.31	H	2
10463.00	36.58	54.00	17.42	V	5
12510.50	38.44	54.00	15.56	H	8.0
14456.00	40.64	54.00	13.36	V	11.2
16624.50	42.66	54.00	11.34	V	14.9
17910.00	43.34	54.00	10.66	H	16.3

**GFSK CH19 (3-18GHz)**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
10480.50	48.68	74.00	25.32	H	5
11565.00	50.17	74.00	23.83	V	6.5
13025.00	50.44	74.00	23.56	H	8.2
14374.00	52.31	74.00	21.69	H	10.9
16508.00	54.70	74.00	19.30	H	14.7
17834.00	55.34	74.00	18.66	V	16.3

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
6506.50	38.42	54.00	15.58	H	2
11685.50	38.17	54.00	15.83	V	7.1
12928.00	38.86	54.00	15.14	H	8.6
14493.00	40.39	54.00	13.61	V	11.4
16714.00	42.85	54.00	11.15	V	14.9
17912.00	43.34	54.00	10.66	H	16.3

**GFSK CH39 (3-18GHz)**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
10402.00	48.52	74.00	25.48	H	5
11617.50	50.33	74.00	23.67	V	6.8
14463.50	52.23	74.00	21.77	V	11.2
16303.50	54.07	74.00	19.93	H	14.3
17077.50	54.42	74.00	19.58	V	15.0
17893.00	55.09	74.00	18.91	H	16.2


Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
6613.50	38.53	54.00	15.47	H	2
10203.50	36.57	54.00	17.43	H	5.1
12493.00	38.14	54.00	15.86	V	8
14463.00	40.45	54.00	13.55	H	11.2
16698.00	42.75	54.00	11.25	V	14.9
17912.50	43.23	54.00	10.77	H	16.3

**Note:**


A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss", and Antenna Factor, the gain of the preamplifier, the cable loss.  $P_{Mea}$  is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result =  $P_{Mea}$  + Cable Loss + Antenna Factor - Gain of the preamplifier



**Fig.20 Radiated Spurious Emission (Ch0, 1 GHz - 3 GHz), 1M**



**Fig.21 Radiated Spurious Emission (Ch0, 3 GHz - 18 GHz), 1M**




Fig.22 Radiated Spurious Emission (Ch19, 9 kHz - 30 MHz), 1M




Fig.23 Radiated Spurious Emission (Ch19, 30 MHz - 1 GHz), 1M






Fig.24 Radiated Spurious Emission (Ch19, 1 GHz - 3 GHz), 1M






Fig.25 Radiated Spurious Emission (Ch19, 3 GHz - 18 GHz), 1M



**Fig.26 Radiated Spurious Emission (Ch19, 18 GHz - 26.5 GHz), 1M**



**Fig.27 Radiated Spurious Emission (Ch39, 1 GHz - 3 GHz), 1M**




Fig.28 Radiated Spurious Emission (Ch39, 3 GHz - 18 GHz), 1M




Fig.29 Radiated Band Edges (Ch0, 2380GHz - 2450GHz), 1M




Fig.30 Radiated Band Edges (Ch39, 2450GHz - 2500GHz), 1M

### A.7 AC Power line Conducted Emission

#### Test Condition:

Voltage (V)	Frequency (Hz)
120	60

#### Measurement Result and limit:

##### LE-1M

BLE (Quasi-peak Limit) - AE3

Frequency range (MHz)	Quasi-peak Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		Traffic	Idle	
0.15 to 0.5	66 to 56	Fig.31	Fig.32	P
0.5 to 5	56			
5 to 30	60			

Note: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

BLE (Average Limit) - AE3

Frequency range (MHz)	Average-peak Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		Traffic	Idle	
0.15 to 0.5	56 to 46	Fig.31	Fig.32	P
0.5 to 5	46			
5 to 30	50			

Note: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

#### Test Condition:

Voltage (V)	Frequency (Hz)
240	60

#### Measurement Result and limit:

##### LE-1M

BLE (Quasi-peak Limit) - AE3

Frequency range (MHz)	Quasi-peak Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		Traffic	Idle	
0.15 to 0.5	66 to 56	Fig.33	Fig.34	P
0.5 to 5	56			
5 to 30	60			

Note: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.



BLE (Average Limit) - AE3

Frequency range (MHz)	Average-peak Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		Traffic	Idle	
0.15 to 0.5	56 to 46	Fig.33	Fig.34	P
0.5 to 5	46			
5 to 30	50			

Note: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note: The measurement results include the L1 and N measurements.

See below for test graphs.

Conclusion: Pass




Fig.31 AC Power line Conducted Emission (Traffic, AE3, 120V), 1M

**Measurement Results: Quasi Peak**

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.190	44.48	64.04	19.55	N	ON	9.6
0.440	41.47	57.06	15.59	N	ON	9.6
0.572	41.36	56.00	14.64	L1	ON	9.6
1.240	40.65	56.00	15.35	L1	ON	9.7
2.340	32.51	56.00	23.49	N	ON	9.7
4.932	29.24	56.00	26.76	L1	ON	9.7

**Measurement Results: Average**

Frequency (MHz)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.190	29.10	54.04	24.93	N	ON	9.6
0.296	29.37	50.35	20.98	N	ON	9.6
0.524	29.80	46.00	16.20	N	ON	9.6
1.088	24.74	46.00	21.26	L1	ON	9.7
2.244	23.22	46.00	22.78	N	ON	9.7
3.760	20.97	46.00	25.03	N	ON	9.7




Fig.32 AC Power line Conducted Emission (Idle, AE3, 120V), 1M

**Measurement Results: Quasi Peak**

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.232	42.64	62.38	19.73	N	ON	9.6
0.324	41.42	59.60	18.19	N	ON	9.6
0.516	44.96	56.00	11.04	N	ON	9.6
1.036	39.45	56.00	16.55	L1	ON	9.7
1.824	32.06	56.00	23.94	N	ON	9.7
3.688	29.72	56.00	26.28	L1	ON	9.7

**Measurement Results: Average**

Frequency (MHz)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.276	30.68	50.94	20.25	N	ON	9.6
0.324	29.76	49.60	19.84	N	ON	9.6
0.604	31.45	46.00	14.55	N	ON	9.6
0.932	27.14	46.00	18.86	N	ON	9.7
2.172	22.41	46.00	23.59	N	ON	9.7
3.556	20.75	46.00	25.25	N	ON	9.7






Fig.33 AC Power line Conducted Emission (Traffic, AE3, 240V), 1M

**Measurement Results: Quasi Peak**

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154	47.25	65.78	18.53	N	ON	9.6
0.576	42.73	56.00	13.27	L1	ON	9.6
1.028	34.78	56.00	21.22	L1	ON	9.7
1.584	35.71	56.00	20.29	L1	ON	9.7
2.504	35.51	56.00	20.49	L1	ON	9.7
4.308	35.54	56.00	20.46	L1	ON	9.7

**Measurement Results: Average**

Frequency (MHz)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.206	39.17	53.37	14.20	L1	ON	9.6
0.584	37.10	46.00	8.90	L1	ON	9.6
1.168	31.17	46.00	14.83	L1	ON	9.7
2.548	29.48	46.00	16.52	L1	ON	9.7
3.452	29.07	46.00	16.93	L1	ON	9.7
4.880	27.76	46.00	18.24	L1	ON	9.7




Fig.34 AC Power line Conducted Emission (Idle, AE3, 240V), 1M

**Measurement Results: Quasi Peak**

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150	48.16	66.00	17.84	N	ON	9.6
0.508	39.00	56.00	17.00	N	ON	9.6
0.600	45.43	56.00	10.57	N	ON	9.6
1.220	37.05	56.00	18.95	L1	ON	9.7
2.356	34.41	56.00	21.59	N	ON	9.7
4.844	33.27	56.00	22.73	N	ON	9.7

**Measurement Results: Average**

Frequency (MHz)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150	30.18	56.00	25.82	L1	ON	9.6
0.588	32.55	46.00	13.45	N	ON	9.6
1.008	26.58	46.00	19.42	N	ON	9.7
1.400	22.63	46.00	23.37	L1	ON	9.7
2.752	22.61	46.00	23.39	N	ON	9.7
4.416	22.77	46.00	23.23	N	ON	9.7

\*\*\*END OF REPORT\*\*\*