



The Photos of SAR test

No. I20Z60999-SEM01

For

TCL Communication Ltd.

Tablet PC

Model name: 9032W

With

Hardware Version: 03

Software Version: 1CS09000

FCC ID: 2ACCJB129



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504


Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn




Picture 1: Constituents of the sample

Test positions for body:


The Body SAR is tested at the following 10 test positions all with the distance =0/8/10/12/15mm between the EUT and the phantom bottom:



Picture 2: Rear with 15mm



Picture 3: Rear with 0mm




Picture 4: Left with 8mm




Picture 5: Left with 0mm



Picture 6: Right with 10mm




Picture 7: Right with 0mm



Picture 8: Top edge with 12mm



Picture 9: Top edge with 0mm



Picture 3: Rear with headset 0mm