



# TEST REPORT

No.I20N01406-SAR

For

**TCL Communication Ltd.**

**Tablet PC**

**Model Name: 9032T**

With

**Hardware Version: PIO**

**Software Version: 1A57**

**FCC ID: 2ACCJB130**

**Issued Date: 2020-07-22**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

**Test Laboratory:**

**SAICT, Shenzhen Academy of Information and Communications Technology**

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518026.

Tel: +86(0)755-33322000, Fax: +86(0)755-33322001

Email: [yewu@caict.ac.cn](mailto:yewu@caict.ac.cn), [www.saict.ac.cn](http://www.saict.ac.cn)



No. I20N01406-SAR

## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I20N01406-SAR	Rev.0	1st edition	2020-07-22



## TCONTENTS

<b>1. SUMMARY OF TEST REPORT .....</b>	<b>5</b>
1.1. TEST ITEMS .....	5
1.2. TEST STANDARDS .....	5
1.3. TEST RESULT.....	5
1.4. TESTING LOCATION .....	5
1.5. PROJECT DATA .....	5
1.6. SIGNATURE .....	5
<b>2. STATEMENT OF COMPLIANCE .....</b>	<b>6</b>
<b>3. CLIENT INFORMATION .....</b>	<b>8</b>
3.1. APPLICANT INFORMATION.....	8
3.2. MANUFACTURER INFORMATION .....	8
<b>4. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>9</b>
4.1. ABOUT EUT .....	9
4.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	10
4.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....	10
<b>5. TEST METHODOLOGY .....</b>	<b>11</b>
5.1. APPLICABLE LIMIT REGULATIONS.....	11
5.2. APPLICABLE MEASUREMENT STANDARDS .....	11
<b>6. SPECIFIC ABSORPTION RATE (SAR).....</b>	<b>12</b>
6.1. INTRODUCTION.....	12
6.2. SAR DEFINITION.....	12
<b>7. TISSUE SIMULATING LIQUIDS .....</b>	<b>13</b>
7.1. TARGETS FOR TISSUE SIMULATING LIQUID .....	13
7.2. DIELECTRIC PERFORMANCE .....	13
<b>8. SYSTEM VERIFICATION .....</b>	<b>18</b>
8.1. SYSTEM SETUP.....	18
8.2. SYSTEM VERIFICATION .....	19
<b>9. MEASUREMENT PROCEDURES .....</b>	<b>20</b>
9.1. TESTS TO BE PERFORMED.....	20
9.2. GENERAL MEASUREMENT PROCEDURE .....	22
9.3. WCDMA MEASUREMENT PROCEDURES FOR SAR .....	23
9.4. LTE MEASUREMENT PROCEDURES FOR SAR.....	24
9.5. BLUETOOTH & WLAN MEASUREMENT PROCEDURES FOR SAR.....	24
9.6. POWER DRIFT.....	25
<b>10. CONDUCTED OUTPUT POWER .....</b>	<b>26</b>
10.1. GSM MEASUREMENT RESULT .....	26
10.2. WCDMA MEASUREMENT RESULT .....	28
10.3. LTE MEASUREMENT RESULT.....	31
10.4. BLUETOOTH AND WLAN MEASUREMENT RESULT .....	83



<b>11. SIMULTANEOUS TX SAR CONSIDERATIONS</b> .....	<b>84</b>
11.1. INTRODUCTION.....	84
11.2. TRANSMIT ANTENNA SEPARATION DISTANCES.....	84
11.3. SAR MEASUREMENT POSITIONS.....	85
11.4. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....	85
<b>12. EVALUATION OF SIMULTANEOUS</b> .....	<b>86</b>
<b>13. SUMMARY OF TEST RESULTS</b> .....	<b>94</b>
13.1. TESTING ENVIRONMENT.....	94
13.2. SAR RESULTS.....	95
13.3. WLAN EVALUATION FOR 2.4G.....	104
13.4. WLAN EVALUATION FOR 5G.....	105
<b>14. SAR MEASUREMENT VARIABILITY</b> .....	<b>106</b>
<b>15. MEASUREMENT UNCERTAINTY</b> .....	<b>108</b>
15.1. MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (300MHZ~3GHZ).....	108
15.2. MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (3GHZ~6GHZ).....	109
<b>16. MAIN TEST INSTRUMENTS</b> .....	<b>110</b>
<b>ANNEX A: GRAPH RESULTS</b> .....	<b>111</b>
<b>ANNEX B: SYSTEMVERIFICATION RESULTS</b> .....	<b>124</b>
<b>ANNEX C: SAR MEASUREMENT SETUP</b> .....	<b>133</b>
C.1. MEASUREMENT SET-UP.....	133
C.2. DASY5 E-FIELD PROBE SYSTEM.....	134
C.3. E-FIELD PROBE CALIBRATION.....	134
C.4. OTHER TEST EQUIPMENT.....	135
<b>ANNEX D: POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM</b> .....	<b>139</b>
D.1. GENERAL CONSIDERATIONS.....	139
D.2. BODY-WORN DEVICE.....	140
D.3. DESKTOP DEVICE.....	140
D.4. DUT SETUP PHOTOS.....	141
<b>ANNEX E: EQUIVALENT MEDIA RECIPES</b> .....	<b>142</b>
<b>ANNEX F: SYSTEM VALIDATION</b> .....	<b>143</b>
<b>ANNEX G: DAE CALIBRATION CERTIFICATE</b> .....	<b>144</b>
<b>ANNEX H: PROBE CALIBRATION CERTIFICATE</b> .....	<b>147</b>
<b>ANNEX I: DIPOLE CALIBRATION CERTIFICATE</b> .....	<b>157</b>
<b>ANNEX J: EXTENDED CALIBRATION SAR DIPOLE</b> .....	<b>219</b>
<b>ANNEX K: ACCREDITATION CERTIFICATE</b> .....	<b>222</b>



## 1. Summary of Test Report

### 1.1. Test Items

Description: Tablet PC  
Model Name: 9032T  
Applicant's name: TCL Communication Ltd.  
Manufacturer's Name: TCL Communication Ltd.

### 1.2. Test Standards

ANSI C95.1-1992, IEEE 1528-2013

### 1.3. Test Result

Pass. Please refer to "13. Summary of Test Results"

### 1.4. Testing Location

Address: Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China

### 1.5. Project Data

Testing Start Date: 2020-06-08

Testing End Date: 2020-07-18

### 1.6. Signature

Li yongfu  
(Prepared this test report)

Zhang Yunzhan  
(Reviewed this test report)

Cao Junfei  
(Approved this test report)



## 2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for TCL Communication Ltd. Tablet PC 9032T are as follows:

**Table 2.1: Highest Reported SAR for Body (1g)**

Exposure Configuration	Technology Band	Highest Reported SAR 1g(W/Kg)	Equipment Class
Body	GSM850	1.08	PCE
	GSM1900	1.13	
	WCDMA Band 2	0.86	
	WCDMA Band 4	1.09	
	WCDMA Band 5	0.93	
	LTE Band 2	0.94	
	LTE Band 5	1.01	
	LTE Band 7	<b>1.18</b>	
	LTE Band 12	0.70	
	LTE Band 17	0.96	
	LTE Band 66	1.03	
	WLAN 2.4GHz	0.62	DTS
	WLAN 5GHz	0.64	NII

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1g tissue according to the ANSI C95.1-1992.

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.

The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report.

The highest reported SAR value is obtained at the case of (Table 2.1), and the value is: **1.18 W/kg (1g)**.

**Table2.2: The sum of reported SAR values for main antenna and WLAN**

<i>/</i>	Position	Main Antenna (W/kg)	WLAN (W/kg)	Sum (W/kg)
Highest reported SAR value for Body	Top	1.18	0.41	1.59

Note: the test positions of above tables are for the worse case that has been evaluated.

**Table2.3: The sum of reported SAR values for main antenna and Bluetooth**

<i>/</i>	Position	Main Antenna (W/kg)	Bluetooth (W/kg)	Sum (W/kg)
Highest reported SAR value for Body	Top	1.18	0.37	1.55

Note: the test positions of above tables are for the worse case that has been evaluated.

According to the above tables, the highest sum of reported SAR values is **1.59 W/kg (1g)**.

The detail for simultaneous transmission consideration is described in chapter 12.



### 3. Client Information

#### 3.1. Applicant Information

Company Name:	TCL Communication Ltd.
Address /Post:	5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
City:	/
Country:	/
Telephone:	0086-755-36611722

#### 3.2. Manufacturer Information

Company Name:	TCL Communication Ltd.
Address /Post:	5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
City:	/
Country:	/
Telephone:	0086-755-36611722



## 4. Equipment under Test (EUT) and Ancillary Equipment (AE)

### 4.1. About EUT

Description:	Tablet PC
Model Name:	9032T
Marketing Name:	/
Operating mode(s):	GSM850/1900, WCDMA Band2/4/5, LTE Band2/4/5/7/12/17/66, Bluetooth, WLAN 2.4G/5G
Condition of EUT as received:	No obvious damage in appearance
Tested Tx Frequency:	825 – 848.8MHz (GSM 850)
	1850.2 – 1910MHz (GSM 1900)
	1852.4 – 1907.6MHz (WCDMA Band 2)
	1712.4 – 1752.6MHz (WCDMA Band 4)
	826.4 – 846.6MHz (WCDMA Band 5)
	1850.7 – 1909.3MHz (LTE Band 2)
	1710.7 – 1754.3MHz (LTE Band 4)
	824.7 – 848.3MHz (LTE Band 5)
	2502.5 – 2567.5MHz (LTE Band 7)
	699.7 – 715.3MHz (LTE Band 12)
	706.5 – 713.5MHz (LTE Band 17)
	1710.7 – 1779.3MHz (LTE Band 66)
	2402 – 2480MHz (Bluetooth)
2412 – 2462MHz (WLAN 2.4G)	
5180 – 5320MHz, 5745 – 5825MHz (WLAN 5G)	
GPRS / EGPRS Multislot Class:	12
GPRS capability Class:	B
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Product Dimensions:	Long 209.4mm; Wide 125.2mm; Overall Diagonal 235mm



#### 4.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version
UT08aa	350583090000192	PIO	1A57
UT09aa	350583090000200	PIO	1A57
UT10aa	350583090000242	PIO	1A57

\*EUT ID: is used to identify the test sample in the lab internally.

**Note:** It is performed to test SAR with the UT 08aa & 09aa, and conducted power with the UT10aa.

#### 4.3. Internal Identification of AE used during the test

AE ID*	Description	Type	Manufacturer
AE1	Battery	TLp040M7	VEKEN

\*AE ID: is used to identify the test sample in the lab internally.



## 5. Test Methodology

### 5.1. Applicable Limit Regulations

**ANSI C95.1–1992:** IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.60 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

### 5.2. Applicable Measurement Standards

**IEEE 1528–2013:** Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Experimental Techniques.

**KDB 447498 D01 General RF Exposure Guidance v06:** Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

**KDB 616217 D04 SAR for laptop and tablets v01r02:** SAR Evaluation Considerations for Laptop, Notebook, Notebook and Tablet Computers.

**KDB 941225 D01 SAR test for 3G devices v03r01:** SAR Measurement Procedures for 3G Devices

**KDB 941225 D05 SAR for LTE Devices v02r05:** SAR Evaluation Considerations for LTE Devices

**KDB 248227 D01 802.11 Wi-Fi SAR v02r02:** SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters.

**KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04:** SAR Measurement Requirements for 100 MHz to 6 GHz.

**KDB 865664 D02 RF Exposure Reporting v01r02:** RF Exposure Compliance Reporting and Documentation Considerations

**TCB workshop April 2019; RF Exposure Procedures (Tissue Simulating Liquids)**

## 6. Specific Absorption Rate (SAR)

### 6.1. Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### 6.2. SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy ( $dW$ ) absorbed by (dissipated in) an incremental mass ( $dm$ ) contained in a volume element ( $dv$ ) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c \left( \frac{\delta T}{\delta t} \right)$$

Where:  $C$  is the specific heat capacity,  $\delta T$  is the temperature rise and  $\delta t$  is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of tissue and  $E$  is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

## 7. Tissue Simulating Liquids

### 7.1. Targets for tissue simulating liquid

**Table 7.1: Targets for tissue simulating liquid**

Frequency (MHz)	Liquid Type	Conductivity ( $\sigma$ )	$\pm 5\%$ Range	Permittivity ( $\epsilon$ )	$\pm 5\%$ Range
750	Head	0.89	0.85~0.93	41.9	39.8~44.0
835	Head	0.90	0.86~0.95	41.5	39.4~43.6
1750	Head	1.37	1.30~1.44	40.1	38.1~42.1
1900	Head	1.40	1.33~1.47	40.0	38.0~42.0
2450	Head	1.80	1.71~1.89	39.2	37.2~41.2
2550	Head	1.91	1.81~2.01	39.1	37.1~41.0
5250	Head	4.71	4.47~4.95	35.9	34.1~37.7
5750	Head	5.22	4.96~5.48	35.4	33.6~37.1

### 7.2. Dielectric Performance

**Table 7.2: Dielectric Performance of Tissue Simulating Liquid**

Measurement Date (yyyy-mm-dd)	Type	Frequency	Conductivity $\sigma$ (S/m)	Drift (%)	Permittivity $\epsilon$	Drift (%)
2020-06-08	Head	750	0.903	1.46	40.99	-2.17
2020-07-18	Head	750	0.913	2.58	40.45	-3.46
2020-06-09	Head	835	0.884	-1.78	41.83	0.80
2020-06-13	Head	1750	1.385	1.09	39.45	-1.62
2020-06-15	Head	1900	1.377	-1.64	39.18	-2.05
2020-06-29	Head	2450	1.838	2.11	38.26	-2.40
2020-06-30	Head	2550	1.949	2.04	37.84	-3.22
2020-06-29	Head	5250	4.626	-1.78	36.95	2.92
2020-06-29	Head	5750	5.148	-1.38	35.86	1.30


Note: The liquid temperature is 22.0°C.




**Picture 7-1: Liquid depth in the Flat Phantom (750MHz)**



**Picture 7-2: Liquid depth in the Flat Phantom (835MHz)**



**Picture 7-3: Liquid depth in the Flat Phantom (1750MHz)**



**Picture 7-4: Liquid depth in the Flat Phantom (1900MHz)**



Picture 7-5: Liquid depth in the Flat Phantom(2450MHz)



Picture 7-6: Liquid depth in the Flat Phantom(2550MHz)






**Picture 7-7: Liquid depth in the Flat Phantom(5GHz)**

## 8. System verification

### 8.1. System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup

## 8.2. System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device.

**Table 8.1: System Verification of Head**

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation (%)	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2020-06-08	750 MHz	5.70	8.53	5.88	8.92	3.16	4.57
2020-07-18	750 MHz	5.70	8.53	5.80	8.84	1.75	3.63
2020-06-09	835 MHz	6.29	9.62	6.20	9.24	-1.43	-3.95
2020-06-13	1750 MHz	19.30	36.40	19.76	37.92	2.38	4.18
2020-06-15	1900 MHz	21.00	40.50	20.48	38.72	-2.48	-4.40
2020-06-29	2450 MHz	24.10	52.00	24.44	53.20	1.41	2.31
2020-06-30	2550 MHz	26.50	57.80	27.28	60.00	2.94	3.81
2020-06-29	5250 MHz	22.30	78.00	21.60	74.80	-3.14	-4.10
2020-06-29	5750 MHz	22.20	78.40	21.90	75.70	-1.35	-3.44

## 9. Measurement Procedures

### 9.1. Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.


**Step 1:** The tests described in 9.2 shall be performed at the channel that is closest to the center of the transmit frequency band ( $f_c$ ) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),
- b) all configurations for each device position in a), e.g., antenna extended and retracted, and
- c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e.,  $N_c > 3$ ), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

**Step 2:** For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

**Step 3:** Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.



Picture 9.1 Block diagram of the tests to be performed

## 9.2. General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013. The results should be documented as part of the system validation records and may be requested to support test results when all the measurement parameters in the following table are not satisfied.

		$\leq 3$ GHz	$> 3$ GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		$5 \pm 1$ mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location		$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{Area}$ , $\Delta y_{Area}$		$\leq 2$ GHz: $\leq 15$ mm 2 – 3 GHz: $\leq 12$ mm	3 – 4 GHz: $\leq 12$ mm 4 – 6 GHz: $\leq 10$ mm
		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}$ , $\Delta y_{Zoom}$		$\leq 2$ GHz: $\leq 8$ mm 2 – 3 GHz: $\leq 5$ mm*	3 – 4 GHz: $\leq 5$ mm* 4 – 6 GHz: $\leq 4$ mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	$\leq 5$ mm	3 – 4 GHz: $\leq 4$ mm 4 – 5 GHz: $\leq 3$ mm 5 – 6 GHz: $\leq 2$ mm
	graded grid $\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	$\leq 4$ mm	3 – 4 GHz: $\leq 3$ mm 4 – 5 GHz: $\leq 2.5$ mm 5 – 6 GHz: $\leq 2$ mm
	$\Delta z_{Zoom}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	$\geq 30$ mm	3 – 4 GHz: $\geq 28$ mm 4 – 5 GHz: $\geq 25$ mm 5 – 6 GHz: $\geq 22$ mm
Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is $\leq 1.4$ W/kg, $\leq 8$ mm, $\leq 7$ mm and $\leq 5$ mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.			

### 9.3. WCDMA Measurement Procedures for SAR

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCH<sub>n</sub>), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

#### For Release 5 HSDPA Data Devices:

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c / \beta_d$	$\beta_{hs}$	CM/dB
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15	15/15	64	12/15	24/25	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

#### For Release 6 HSPA Data Devices

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c / \beta_d$	$\beta_{hs}$	$\beta_{ec}$	$\beta_{ed}$	$\beta_{ed}$ (SF)	$\beta_{ed}$ (codes)	CM (dB)	MPR (dB)	AG Index	E-TFCI
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}:47/15$ $\beta_{ed2}:47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	3.0	2.0	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	1.0	0.0	21	81

#### 9.4. LTE Measurement Procedures for SAR

SAR tests for LTE are performed with a base station simulator, Anristu MT8820C. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. All powers were measured with the Anristu MT8820C. It is performed for conducted power and SAR based on the KDB941225 D05.

SAR is evaluated separately according to the following procedures for the different test positions in each exposure condition – head, body, body-worn accessories and other use conditions. The procedures in the following subsections are applied separately to test each LTE frequency band.

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is  $> 1.45$  W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.

#### 9.5. Bluetooth & WLAN Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.





## 9.6. Power Drift

To control the output power stability during the SAR test, DASY5 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in Section 14 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

## 9.7. Proximity Sensor Considerations

This device uses a proximity sensor that share the same metallic electrode as the transmitting antenna to facilitate triggering in typical user interactivity with the device. Due to the operating configurations and exposure conditions required by the device, the proximity sensor is used to indicate when the tablet is held close to a user's body exposure condition. It utilizes the proximity sensor to reduce the output power in specific wireless and operating modes to ensure SAR compliance for the following scenarios: To reduce the output power of main antennas during body operating configurations. . It is also set an output power leveled to the lowest one to make sure that in any case of SAR sensor hardware failure the SAR requirements can still be satisfied.

Sensor triggering distance summary data is included in Appendix K.

## 10. Conducted Output Power

### 10.1. GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

**Table 10.1: The conducted power measurement results for GPRS and EGPRS**

Full Power								
GPRS850/ EGPRS850	Tune up	Measured Power (dBm)			calculation	Average Power (dBm)		
		251	190	128		251	190	128
1Tx-slots	<b>33.5</b>	32.94	33.05	32.90	-9.03dB	23.91	24.02	23.87
<b>2Tx-slots</b>	<b>32.0</b>	<b>31.03</b>	<b>31.29</b>	<b>31.11</b>	<b>-6.02dB</b>	<b>25.01</b>	<b>25.27</b>	<b>25.09</b>
3Tx-slots	<b>30.0</b>	29.02	29.24	29.11	-4.26dB	24.76	24.98	24.85
4Tx-slots	<b>28.5</b>	27.45	27.70	27.67	-3.01dB	24.44	24.69	24.66
EGPRS 850 (8PSK)	Tune up	Measured Power (dBm)			calculation	Measured Power (dBm)		
		251	190	128		251	190	128
1Tx-slots	<b>27.5</b>	27.01	27.14	27.22	-9.03dB	17.98	18.11	18.19
2Tx-slots	<b>26.5</b>	26.05	26.01	26.03	-6.02dB	20.03	19.99	20.01
3Tx-slots	<b>25.5</b>	24.83	24.98	25.02	-4.26dB	20.57	20.72	20.76
4Tx-slots	<b>24.5</b>	23.76	23.88	24.03	-3.01dB	20.75	20.87	21.02
Sensor on								
GPRS850/ EGPRS850	Tune up	Measured Power (dBm)			calculation	Average Power (dBm)		
		251	190	128		251	190	128
1Tx-slots	<b>23.0</b>	22.17	22.53	22.52	-9.03dB	13.14	13.50	13.49
2Tx-slots	<b>23.0</b>	22.13	22.46	22.66	-6.02dB	16.11	16.44	16.94
3Tx-slots	<b>23.0</b>	22.05	22.39	22.38	-4.26dB	17.79	18.13	18.12
<b>4Tx-slots</b>	<b>23.0</b>	<b>22.00</b>	<b>22.34</b>	<b>22.36</b>	<b>-3.01dB</b>	<b>18.99</b>	<b>19.33</b>	<b>19.35</b>
EGPRS 850 (8PSK)	Tune up	Measured Power (dBm)			calculation	Measured Power (dBm)		
		251	190	128		251	190	128
1Tx-slots	<b>17.0</b>	16.19	16.21	16.33	-9.03dB	7.16	7.18	7.30
2Tx-slots	<b>17.0</b>	16.11	16.10	16.25	-6.02dB	10.09	10.08	10.23
3Tx-slots	<b>17.0</b>	16.02	16.07	16.18	-4.26dB	11.76	11.81	11.92
4Tx-slots	<b>17.0</b>	15.86	16.02	16.11	-3.01dB	12.85	13.01	13.10

Full Power								
GPRS1900/ EGPRS1900	Tune up	Measured Power (dBm)			calculation	Average Power (dBm)		
		810	661	512		810	661	512
1Tx-slots	<b>31.5</b>	30.72	30.78	30.61	-9.03dB	21.69	21.75	21.58
<b>2Tx-slots</b>	<b>30.0</b>	<b>29.22</b>	<b>29.18</b>	<b>28.92</b>	<b>-6.02dB</b>	<b>23.20</b>	<b>23.16</b>	<b>22.90</b>
3Tx-slots	<b>28.0</b>	27.23	27.16	26.83	-4.26dB	22.97	22.90	22.57
4Tx-slots	<b>26.5</b>	25.81	25.66	25.37	-3.01dB	22.80	22.65	22.36
EGPRS1900 (8PSK)	Tune up	Measured Power (dBm)			calculation	Measured Power (dBm)		
		810	661	512		810	661	512
1Tx-slots	<b>27.5</b>	26.89	26.78	26.67	-9.03dB	17.86	17.75	17.64
2Tx-slots	<b>26.5</b>	25.98	25.89	25.75	-6.02dB	19.96	19.87	19.73
3Tx-slots	<b>25.5</b>	25.04	24.85	24.64	-4.26dB	20.78	20.59	20.38
4Tx-slots	<b>24.5</b>	23.96	23.78	23.64	-3.01dB	20.95	20.77	20.63
Sensor on								
GPRS1900/ EGPRS1900	Tune up	Measured Power (dBm)			calculation	Average Power (dBm)		
		810	661	512		810	661	512
1Tx-slots	<b>20.5</b>	19.91	19.57	19.25	-9.03dB	10.88	10.54	10.22
2Tx-slots	<b>20.5</b>	19.87	19.51	19.21	-6.02dB	13.85	13.49	13.19
3Tx-slots	<b>20.5</b>	19.82	19.46	19.15	-4.26dB	15.56	15.20	14.89
<b>4Tx-slots</b>	<b>20.5</b>	<b>19.76</b>	<b>19.41</b>	<b>19.09</b>	<b>-3.01dB</b>	<b>16.75</b>	<b>16.40</b>	<b>16.08</b>
EGPRS1900 (8PSK)	Tune up	Measured Power (dBm)			calculation	Measured Power (dBm)		
		810	661	512		810	661	512
1Tx-slots	<b>16.0</b>	15.57	15.33	15.36	-9.03dB	6.54	6.30	6.33
2Tx-slots	<b>16.0</b>	15.52	15.28	15.30	-6.02dB	9.50	9.26	9.28
3Tx-slots	<b>16.0</b>	15.48	15.19	15.27	-4.26dB	11.22	10.93	11.01
4Tx-slots	<b>16.0</b>	15.42	15.13	15.22	-3.01dB	12.41	12.12	12.21

Note:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

**According to the conducted power as above, the body measurements are performed with 2Txslots for 850MHz and 1900MHz; 4Txslots for 850MHz Sensor-on mode and 4Txslots for 1900MHz Sensor-on mode.**

## 10.2. WCDMA Measurement result

Table 10.2: T The conducted power measurement results WCDMA

<b>Full Power</b>					
Item	band	WCDMA Band 2			
	ARFCN	Tune up	9538 (1907.6MHz)	9400 (1880MHz)	9262 (1852.4MHz)
WCDMA	\	<b>24.5</b>	24.0	23.9	23.9
HSUPA	1	<b>22.0</b>	21.5	21.4	21.4
	2	<b>21.5</b>	21.0	20.9	20.9
	3	<b>22.5</b>	22.0	21.9	22.0
	4	<b>21.0</b>	20.5	20.4	20.5
	5	<b>22.5</b>	22.0	21.9	22.0
HSDPA	1	<b>23.5</b>	23.0	22.9	23.0
	2	<b>23.5</b>	23.0	22.9	22.9
	3	<b>23.0</b>	22.5	22.4	22.4
	4	<b>23.0</b>	22.5	22.4	22.4
DC-HSDPA	1	<b>23.5</b>	22.8	22.9	23.0
	2	<b>23.5</b>	22.9	22.9	22.9
	3	<b>23.0</b>	22.5	22.4	22.3
	4	<b>23.0</b>	22.4	22.4	22.4
<b>Sensor on</b>					
Item	band	WCDMA Band 2			
	ARFCN	Tune up	9538 (1907.6MHz)	9400 (1880MHz)	9262 (1852.4MHz)
WCDMA	\	<b>17.0</b>	16.5	16.4	16.4
HSUPA	1	<b>16.5</b>	16.0	15.9	15.9
	2	<b>16.0</b>	15.1	15.4	15.3
	3	<b>16.5</b>	16.1	16.0	16.1
	4	<b>16.5</b>	15.7	15.8	15.9
	5	<b>17.0</b>	16.5	16.6	16.6
HSDPA	1	<b>17.0</b>	16.5	16.5	16.5
	2	<b>17.0</b>	16.4	16.4	16.5
	3	<b>17.0</b>	16.4	16.4	16.4
	4	<b>17.0</b>	16.7	16.6	16.3
DC-HSDPA	1	<b>17.0</b>	16.4	16.4	16.4
	2	<b>17.0</b>	16.3	16.4	16.5
	3	<b>17.0</b>	16.2	16.3	16.4
	4	<b>17.0</b>	16.4	16.4	16.3



<b>Full Power</b>					
Item	band	WCDMA Band 4			
	ARFCN	Tune up	1513 (1752.6MHz)	1413 (1732.6MHz)	1312 (1712.4MHz)
WCDMA	\	24.5	23.9	24.0	23.9
HSUPA	1	22.0	21.5	21.5	21.4
	2	21.5	20.9	21.0	21.0
	3	22.5	21.9	22.0	22.0
	4	21.0	20.5	20.6	20.5
	5	22.5	21.9	22.0	21.9
HSDPA	1	23.5	22.9	23.0	22.9
	2	23.5	22.9	23.0	22.9
	3	23.0	22.3	22.5	22.4
	4	23.0	22.4	22.5	22.4
DC-HSDPA	1	23.5	22.9	22.9	22.9
	2	23.5	22.8	23.0	22.9
	3	23.0	22.2	22.3	22.4
	4	23.0	22.3	22.4	22.4
<b>Sensor on</b>					
Item	band	WCDMA Band 4			
	ARFCN	Tune up	1513 (1752.6MHz)	1413 (1732.6MHz)	1312 (1712.4MHz)
WCDMA	\	17.0	16.3	16.2	16.3
HSUPA	1	15.0	14.3	14.4	14.3
	2	16.5	15.6	15.9	15.8
	3	16.5	15.7	15.4	15.5
	4	16.0	15.3	15.6	15.4
	5	16.0	15.1	15.2	15.3
HSDPA	1	16.5	16.0	16.1	16.2
	2	16.5	16.2	16.2	16.3
	3	16.5	15.6	15.7	15.8
	4	16.5	15.7	15.7	15.8
DC-HSDPA	1	16.5	16.1	16.1	16.1
	2	16.5	16.1	16.2	16.3
	3	16.5	15.7	15.7	15.8
	4	16.5	15.6	15.7	15.8

<b>Full Power</b>					
Item	band	WCDMA Band 5			
	ARFCN	Tune up	4233 (846.6MHz)	4182 (836.4MHz)	4132 (826.4MHz)
WCDMA	\	24.5	23.9	23.9	23.9
HSUPA	1	22.0	21.4	21.4	21.5
	2	21.5	20.9	21.0	20.9
	3	22.5	21.9	21.9	21.9
	4	21.0	20.4	20.5	20.5
	5	22.5	21.8	22.0	21.9
HSDPA	1	23.5	23.0	23.0	22.9
	2	23.5	22.9	22.9	22.9
	3	23.0	22.4	22.5	22.4
	4	23.0	22.4	22.4	22.4
DC-HSDPA	1	23.5	22.8	22.9	22.9
	2	23.5	22.7	22.8	22.9
	3	23.0	22.3	22.4	22.5
	4	23.0	22.4	22.5	22.4
<b>Sensor on</b>					
Item	band	WCDMA Band 5			
	ARFCN	Tune up	4233 (846.6MHz)	4182 (836.4MHz)	4132 (826.4MHz)
WCDMA	\	17.0	16.4	16.3	16.4
HSUPA	1	16.5	16.0	15.9	15.8
	2	15.0	14.4	14.3	14.3
	3	15.5	14.9	14.9	14.8
	4	15.0	14.2	14.1	14.0
	5	16.0	15.5	15.4	15.4
HSDPA	1	17.0	16.4	16.5	16.5
	2	17.0	15.9	15.9	16.0
	3	17.0	15.9	16.0	15.8
	4	17.0	16.0	15.9	15.8
DC-HSDPA	1	17.0	16.4	16.4	16.4
	2	17.0	16.2	16.3	16.3
	3	17.0	15.8	15.9	15.8
	4	17.0	15.9	15.9	15.9

### 10.3. LTE Measurement result

According to April 2015 TCB workshop, SAR Test exclusion can be applied for testing overlapping LTE Bands as follows:

- The maximum out power, including tolerance, for the smaller band must be  $\leq$  the larger band to qualify for SAR test exclusion.
- The channel bandwidth and other operating parameters for the smaller band must be fully supported by the larger band.

LTE Band 4 (1710-1755 MHz) is covered by LTE Band 66 (1710-1780 MHz)

**Table 10.3: The conducted Power for LTE**

Full Power								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
1.4 MHz	1RB_5	1909.3MHz	23.42	22.64	/	24.5	23.5	/
		1880MHz	23.42	22.68	/	24.5	23.5	/
		1850.7MHz	23.49	22.68	/	24.5	23.5	/
	1RB_3	1909.3MHz	23.16	22.77	/	24.5	23.5	/
		1880MHz	23.51	22.76	/	24.5	23.5	/
		1850.7MHz	23.54	22.80	/	24.5	23.5	/
	1RB_0	1909.3MHz	23.42	22.66	/	24.5	23.5	/
		1880MHz	23.40	22.63	/	24.5	23.5	/
		1850.7MHz	23.47	22.68	/	24.5	23.5	/
	3RB_3	1909.3MHz	23.52	22.42	/	24.5	23.5	/
		1880MHz	23.52	22.51	/	24.5	23.5	/
		1850.7MHz	23.57	22.56	/	24.5	23.5	/
	3RB_1	1909.3MHz	23.59	22.49	/	24.5	23.5	/
		1880MHz	23.61	22.55	/	24.5	23.5	/
		1850.7MHz	23.59	22.63	/	24.5	23.5	/
	3RB_0	1909.3MHz	23.54	22.43	/	24.5	23.5	/
		1880MHz	23.50	22.47	/	24.5	23.5	/
		1850.7MHz	23.59	22.59	/	24.5	23.5	/
6RB_0	1909.3MHz	22.60	21.59	/	23.5	22.5	/	
	1880MHz	22.53	21.65	/	23.5	22.5	/	
	1850.7MHz	22.59	21.73	/	23.5	22.5	/	



Full Power								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
3 MHz	1RB_14	1908.5MHz	23.50	22.56	/	24.5	23.5	/
		1880MHz	23.46	22.70	/	24.5	23.5	/
		1851.5MHz	23.54	22.71	/	24.5	23.5	/
	1RB_7	1908.5MHz	23.63	22.74	/	24.5	23.5	/
		1880MHz	23.69	22.79	/	24.5	23.5	/
		1851.5MHz	23.69	22.79	/	24.5	23.5	/
	1RB_0	1908.5MHz	23.48	22.60	/	24.5	23.5	/
		1880MHz	23.49	22.66	/	24.5	23.5	/
		1851.5MHz	23.59	22.74	/	24.5	23.5	/
	8RB_7	1908.5MHz	22.58	21.63	/	23.5	22.5	/
		1880MHz	22.56	21.58	/	23.5	22.5	/
		1851.5MHz	22.57	21.64	/	23.5	22.5	/
	8RB_4	1908.5MHz	22.59	21.63	/	23.5	22.5	/
		1880MHz	22.52	21.63	/	23.5	22.5	/
		1851.5MHz	22.58	21.71	/	23.5	22.5	/
	8RB_0	1908.5MHz	22.53	21.57	/	23.5	22.5	/
		1880MHz	22.50	21.57	/	23.5	22.5	/
		1851.5MHz	22.62	21.67	/	23.5	22.5	/
	15RB_0	1908.5MHz	22.59	21.63	/	23.5	22.5	/
		1880MHz	22.57	21.56	/	23.5	22.5	/
		1851.5MHz	22.60	21.60	/	23.5	22.5	/





Full Power								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	1907.5MHz	23.46	22.61	/	24.5	23.5	/
		1880MHz	23.47	22.71	/	24.5	23.5	/
		1852.5MHz	23.53	22.64	/	24.5	23.5	/
	1RB_12	1907.5MHz	23.63	22.91	/	24.5	23.5	/
		1880MHz	23.68	22.88	/	24.5	23.5	/
		1852.5MHz	23.70	22.91	/	24.5	23.5	/
	1RB_0	1907.5MHz	23.45	22.68	/	24.5	23.5	/
		1880MHz	23.48	22.64	/	24.5	23.5	/
		1852.5MHz	23.56	22.70	/	24.5	23.5	/
	12RB_13	1907.5MHz	22.61	21.59	/	23.5	22.5	/
		1880MHz	22.61	21.61	/	23.5	22.5	/
		1852.5MHz	22.64	21.65	/	23.5	22.5	/
	12RB_6	1907.5MHz	22.65	21.59	/	23.5	22.5	/
		1880MHz	22.63	21.64	/	23.5	22.5	/
		1852.5MHz	22.68	21.69	/	23.5	22.5	/
	12RB_0	1907.5MHz	22.61	21.58	/	23.5	22.5	/
		1880MHz	22.58	21.61	/	23.5	22.5	/
		1852.5MHz	22.61	21.65	/	23.5	22.5	/
	25RB_0	1907.5MHz	22.62	21.59	/	23.5	22.5	/
		1880MHz	22.56	21.64	/	23.5	22.5	/
		1852.5MHz	22.69	21.66	/	23.5	22.5	/



Full Power								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	1905MHz	23.62	22.74	/	24.5	23.5	/
		1880MHz	23.63	22.78	/	24.5	23.5	/
		1855MHz	23.61	22.81	/	24.5	23.5	/
	1RB_24	1905MHz	23.75	22.88	/	24.5	23.5	/
		1880MHz	23.75	22.89	/	24.5	23.5	/
		1855MHz	23.82	23.30	/	24.5	23.5	/
	1RB_0	1905MHz	23.61	22.81	/	24.5	23.5	/
		1880MHz	23.62	22.85	/	24.5	23.5	/
		1855MHz	23.71	22.91	/	24.5	23.5	/
	25RB_25	1905MHz	22.77	21.72	/	23.5	22.5	/
		1880MHz	22.78	21.73	/	23.5	22.5	/
		1855MHz	22.78	21.74	/	23.5	22.5	/
	25RB_12	1905MHz	22.72	21.72	/	23.5	22.5	/
		1880MHz	22.72	21.70	/	23.5	22.5	/
		1855MHz	22.72	21.68	/	23.5	22.5	/
	25RB_0	1905MHz	22.78	21.79	/	23.5	22.5	/
		1880MHz	22.71	21.69	/	23.5	22.5	/
		1855MHz	22.73	21.69	/	23.5	22.5	/
	50RB_0	1905MHz	22.78	21.75	/	23.5	22.5	/
		1880MHz	22.74	21.69	/	23.5	22.5	/
		1855MHz	22.75	21.76	/	23.5	22.5	/



Full Power								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
15 MHz	1RB_74	1902.5MHz	23.64	22.83	/	24.5	23.5	/
		1880MHz	23.57	23.29	/	24.5	23.5	/
		1857.5MHz	23.57	22.73	/	24.5	23.5	/
	1RB_37	1902.5MHz	23.71	22.97	/	24.5	23.5	/
		1880MHz	23.72	22.91	/	24.5	23.5	/
		1857.5MHz	23.74	22.89	/	24.5	23.5	/
	1RB_0	1902.5MHz	23.64	22.85	/	24.5	23.5	/
		1880MHz	23.63	22.86	/	24.5	23.5	/
		1857.5MHz	23.72	22.84	/	24.5	23.5	/
	36RB_38	1902.5MHz	22.78	21.82	/	23.5	22.5	/
		1880MHz	22.79	21.78	/	23.5	22.5	/
		1857.5MHz	22.78	21.72	/	23.5	22.5	/
	36RB_19	1902.5MHz	22.81	21.81	/	23.5	22.5	/
		1880MHz	22.75	21.78	/	23.5	22.5	/
		1857.5MHz	22.82	21.73	/	23.5	22.5	/
	36RB_0	1902.5MHz	22.85	21.81	/	23.5	22.5	/
		1880MHz	22.79	21.73	/	23.5	22.5	/
		1857.5MHz	22.77	21.71	/	23.5	22.5	/
	75RB_0	1902.5MHz	22.82	21.77	/	23.5	22.5	/
		1880MHz	22.80	21.76	/	23.5	22.5	/
		1857.5MHz	22.77	21.76	/	23.5	22.5	/



Full Power								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
20 MHz	1RB_99	1900MHz	23.61	22.72	/	24.5	23.5	/
		1880MHz	23.49	22.54	/	24.5	23.5	/
		1860MHz	23.73	22.77	/	24.5	23.5	/
	1RB_50	1900MHz	23.94	23.02	/	24.5	23.5	/
		1880MHz	23.86	22.98	/	24.5	23.5	/
		1860MHz	23.96	23.09	/	24.5	23.5	/
	1RB_0	1900MHz	23.55	22.72	/	24.5	23.5	/
		1880MHz	23.57	22.72	/	24.5	23.5	/
		1860MHz	23.66	22.83	/	24.5	23.5	/
	50RB_50	1900MHz	22.84	21.77	/	23.5	22.5	/
		1880MHz	23.00	21.91	/	23.5	22.5	/
		1860MHz	22.85	21.80	/	23.5	22.5	/
	50RB_25	1900MHz	22.92	21.89	/	23.5	22.5	/
		1880MHz	22.90	21.87	/	23.5	22.5	/
		1860MHz	22.89	21.88	/	23.5	22.5	/
	50RB_0	1900MHz	23.02	21.98	/	23.5	22.5	/
		1880MHz	22.84	21.83	/	23.5	22.5	/
		1860MHz	22.83	21.80	/	23.5	22.5	/
	100RB_0	1900MHz	22.96	21.88	/	23.5	22.5	/
		1880MHz	22.91	21.90	/	23.5	22.5	/
		1860MHz	22.83	21.78	/	23.5	22.5	/



Sensor on								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
1.4 MHz	1RB_5	1909.3MHz	16.74	16.80	/	17.5	17.5	/
		1880MHz	16.73	16.92	/	17.5	17.5	/
		1850.7MHz	16.77	17.01	/	17.5	17.5	/
	1RB_3	1909.3MHz	16.76	16.94	/	17.5	17.5	/
		1880MHz	16.80	16.95	/	17.5	17.5	/
		1850.7MHz	16.92	17.13	/	17.5	17.5	/
	1RB_0	1909.3MHz	16.79	16.84	/	17.5	17.5	/
		1880MHz	16.73	16.87	/	17.5	17.5	/
		1850.7MHz	16.76	16.99	/	17.5	17.5	/
	3RB_3	1909.3MHz	16.86	16.70	/	17.5	17.5	/
		1880MHz	16.80	16.76	/	17.5	17.5	/
		1850.7MHz	16.88	16.87	/	17.5	17.5	/
	3RB_1	1909.3MHz	16.88	16.79	/	17.5	17.5	/
		1880MHz	16.88	16.83	/	17.5	17.5	/
		1850.7MHz	16.93	16.90	/	17.5	17.5	/
	3RB_0	1909.3MHz	16.82	16.73	/	17.5	17.5	/
		1880MHz	16.78	16.72	/	17.5	17.5	/
		1850.7MHz	16.87	16.84	/	17.5	17.5	/
	6RB_0	1909.3MHz	16.87	16.85	/	17.5	17.5	/
		1880MHz	16.82	16.85	/	17.5	17.5	/
		1850.7MHz	16.92	16.97	/	17.5	17.5	/



Sensor on								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
3 MHz	1RB_14	1908.5MHz	16.78	16.89	/	17.5	17.5	/
		1880MHz	16.72	16.96	/	17.5	17.5	/
		1851.5MHz	16.81	17.08	/	17.5	17.5	/
	1RB_7	1908.5MHz	16.93	16.89	/	17.5	17.5	/
		1880MHz	16.85	17.14	/	17.5	17.5	/
		1851.5MHz	16.83	17.24	/	17.5	17.5	/
	1RB_0	1908.5MHz	16.78	16.93	/	17.5	17.5	/
		1880MHz	16.78	16.93	/	17.5	17.5	/
		1851.5MHz	16.84	17.16	/	17.5	17.5	/
	8RB_7	1908.5MHz	16.80	16.82	/	17.5	17.5	/
		1880MHz	16.79	16.80	/	17.5	17.5	/
		1851.5MHz	16.90	16.81	/	17.5	17.5	/
	8RB_4	1908.5MHz	16.86	16.82	/	17.5	17.5	/
		1880MHz	16.83	16.83	/	17.5	17.5	/
		1851.5MHz	16.87	16.84	/	17.5	17.5	/
	8RB_0	1908.5MHz	16.81	16.78	/	17.5	17.5	/
		1880MHz	16.82	16.76	/	17.5	17.5	/
		1851.5MHz	16.88	16.87	/	17.5	17.5	/
	15RB_0	1908.5MHz	16.85	16.76	/	17.5	17.5	/
		1880MHz	16.80	16.75	/	17.5	17.5	/
		1851.5MHz	16.84	16.86	/	17.5	17.5	/



Sensor on								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	1907.5MHz	16.63	16.81	/	17.5	17.5	/
		1880MHz	16.62	16.85	/	17.5	17.5	/
		1852.5MHz	16.69	16.87	/	17.5	17.5	/
	1RB_12	1907.5MHz	16.87	17.06	/	17.5	17.5	/
		1880MHz	17.03	16.98	/	17.5	17.5	/
		1852.5MHz	16.92	17.10	/	17.5	17.5	/
	1RB_0	1907.5MHz	16.63	16.80	/	17.5	17.5	/
		1880MHz	16.68	16.82	/	17.5	17.5	/
		1852.5MHz	16.79	16.93	/	17.5	17.5	/
	12RB_13	1907.5MHz	16.81	16.73	/	17.5	17.5	/
		1880MHz	16.82	16.74	/	17.5	17.5	/
		1852.5MHz	16.84	16.79	/	17.5	17.5	/
	12RB_6	1907.5MHz	16.84	16.75	/	17.5	17.5	/
		1880MHz	16.89	16.78	/	17.5	17.5	/
		1852.5MHz	16.94	16.83	/	17.5	17.5	/
	12RB_0	1907.5MHz	16.82	16.72	/	17.5	17.5	/
		1880MHz	16.83	16.74	/	17.5	17.5	/
		1852.5MHz	16.86	16.80	/	17.5	17.5	/
	25RB_0	1907.5MHz	16.83	16.74	/	17.5	17.5	/
		1880MHz	16.81	16.82	/	17.5	17.5	/
		1852.5MHz	16.87	16.83	/	17.5	17.5	/



Sensor on								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	1905MHz	16.79	16.93	/	17.5	17.5	/
		1880MHz	16.67	16.91	/	17.5	17.5	/
		1855MHz	16.79	17.00	/	17.5	17.5	/
	1RB_24	1905MHz	16.85	17.15	/	17.5	17.5	/
		1880MHz	16.92	17.10	/	17.5	17.5	/
		1855MHz	16.92	17.18	/	17.5	17.5	/
	1RB_0	1905MHz	16.79	16.98	/	17.5	17.5	/
		1880MHz	16.78	17.04	/	17.5	17.5	/
		1855MHz	16.88	17.07	/	17.5	17.5	/
	25RB_25	1905MHz	16.83	16.78	/	17.5	17.5	/
		1880MHz	16.86	16.77	/	17.5	17.5	/
		1855MHz	16.87	16.85	/	17.5	17.5	/
	25RB_12	1905MHz	16.87	16.79	/	17.5	17.5	/
		1880MHz	16.89	16.83	/	17.5	17.5	/
		1855MHz	16.93	16.90	/	17.5	17.5	/
	25RB_0	1905MHz	16.89	16.83	/	17.5	17.5	/
		1880MHz	16.84	16.85	/	17.5	17.5	/
		1855MHz	16.93	16.89	/	17.5	17.5	/
	50RB_0	1905MHz	16.86	16.82	/	17.5	17.5	/
		1880MHz	16.87	16.83	/	17.5	17.5	/
		1855MHz	16.89	16.91	/	17.5	17.5	/





Sensor on								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
15 MHz	1RB_74	1902.5MHz	16.73	16.89	/	17.5	17.5	/
		1880MHz	16.61	16.91	/	17.5	17.5	/
		1857.5MHz	16.67	16.93	/	17.5	17.5	/
	1RB_37	1902.5MHz	16.76	17.01	/	17.5	17.5	/
		1880MHz	16.78	16.97	/	17.5	17.5	/
		1857.5MHz	16.84	17.09	/	17.5	17.5	/
	1RB_0	1902.5MHz	16.69	16.93	/	17.5	17.5	/
		1880MHz	16.68	16.96	/	17.5	17.5	/
		1857.5MHz	16.83	17.10	/	17.5	17.5	/
	36RB_38	1902.5MHz	16.78	16.70	/	17.5	17.5	/
		1880MHz	16.82	16.75	/	17.5	17.5	/
		1857.5MHz	16.83	16.80	/	17.5	17.5	/
	36RB_19	1902.5MHz	16.84	16.76	/	17.5	17.5	/
		1880MHz	16.87	16.80	/	17.5	17.5	/
		1857.5MHz	16.92	16.85	/	17.5	17.5	/
	36RB_0	1902.5MHz	16.89	16.80	/	17.5	17.5	/
		1880MHz	16.85	16.82	/	17.5	17.5	/
		1857.5MHz	16.91	16.84	/	17.5	17.5	/
	75RB_0	1902.5MHz	16.85	16.78	/	17.5	17.5	/
		1880MHz	16.84	16.78	/	17.5	17.5	/
		1857.5MHz	16.88	16.83	/	17.5	17.5	/



Sensor on								
LTE Band 2			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
20 MHz	1RB_99	1900MHz	16.52	16.69	/	17.5	17.5	/
		1880MHz	16.67	16.59	/	17.5	17.5	/
		1860MHz	16.48	16.73	/	17.5	17.5	/
	1RB_50	1900MHz	16.88	17.03	/	17.5	17.5	/
		1880MHz	16.81	17.00	/	17.5	17.5	/
		1860MHz	16.92	17.16	/	17.5	17.5	/
	1RB_0	1900MHz	16.52	16.75	/	17.5	17.5	/
		1880MHz	16.57	16.85	/	17.5	17.5	/
		1860MHz	16.66	16.88	/	17.5	17.5	/
	50RB_50	1900MHz	16.74	16.68	/	17.5	17.5	/
		1880MHz	16.85	16.77	/	17.5	17.5	/
		1860MHz	16.79	16.76	/	17.5	17.5	/
	50RB_25	1900MHz	16.85	16.82	/	17.5	17.5	/
		1880MHz	16.88	16.86	/	17.5	17.5	/
		1860MHz	16.94	16.91	/	17.5	17.5	/
	50RB_0	1900MHz	16.96	16.95	/	17.5	17.5	/
		1880MHz	16.88	16.83	/	17.5	17.5	/
		1860MHz	16.98	16.88	/	17.5	17.5	/
	100RB_0	1900MHz	16.90	16.82	/	17.5	17.5	/
		1880MHz	16.86	16.78	/	17.5	17.5	/
		1860MHz	16.86	16.78	/	17.5	17.5	/



Full Power								
LTE Band 5			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
1.4 MHz	1RB_5	848.3MHz	23.19	22.24	/	24.5	23.5	/
		836.5MHz	23.17	22.38	/	24.5	23.5	/
		824.7MHz	23.15	22.46	/	24.5	23.5	/
	1RB_3	848.3MHz	23.16	22.35	/	24.5	23.5	/
		836.5MHz	23.26	22.49	/	24.5	23.5	/
		824.7MHz	23.21	22.52	/	24.5	23.5	/
	1RB_0	848.3MHz	23.19	22.25	/	24.5	23.5	/
		836.5MHz	23.16	22.32	/	24.5	23.5	/
		824.7MHz	23.11	22.38	/	24.5	23.5	/
	3RB_3	848.3MHz	23.27	22.13	/	24.5	23.5	/
		836.5MHz	23.30	22.19	/	24.5	23.5	/
		824.7MHz	23.25	22.26	/	24.5	23.5	/
	3RB_1	848.3MHz	23.22	22.19	/	24.5	23.5	/
		836.5MHz	23.35	22.25	/	24.5	23.5	/
		824.7MHz	23.28	22.28	/	24.5	23.5	/
	3RB_0	848.3MHz	23.26	22.12	/	24.5	23.5	/
		836.5MHz	23.28	22.17	/	24.5	23.5	/
		824.7MHz	23.22	22.27	/	24.5	23.5	/
	6RB_0	848.3MHz	22.27	21.34	/	23.5	22.5	/
		836.5MHz	22.27	21.37	/	23.5	22.5	/
		824.7MHz	22.29	21.28	/	23.5	22.5	/



Full Power								
LTE Band 5			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
3 MHz	1RB_14	847.5MHz	21.35	22.35	/	24.5	23.5	/
		836.5MHz	23.30	22.44	/	24.5	23.5	/
		825.5MHz	23.19	22.54	/	24.5	23.5	/
	1RB_7	847.5MHz	21.34	22.50	/	24.5	23.5	/
		836.5MHz	23.37	22.58	/	24.5	23.5	/
		825.5MHz	23.54	22.60	/	24.5	23.5	/
	1RB_0	847.5MHz	21.36	22.33	/	24.5	23.5	/
		836.5MHz	23.26	22.38	/	24.5	23.5	/
		825.5MHz	23.22	22.47	/	24.5	23.5	/
	8RB_7	847.5MHz	23.34	21.25	/	23.5	22.5	/
		836.5MHz	22.30	21.32	/	23.5	22.5	/
		825.5MHz	22.30	21.30	/	23.5	22.5	/
	8RB_4	847.5MHz	23.26	21.30	/	23.5	22.5	/
		836.5MHz	22.30	21.37	/	23.5	22.5	/
		825.5MHz	22.32	21.32	/	23.5	22.5	/
	8RB_0	847.5MHz	23.24	21.22	/	23.5	22.5	/
		836.5MHz	22.30	21.28	/	23.5	22.5	/
		825.5MHz	22.33	21.30	/	23.5	22.5	/
	15RB_0	847.5MHz	22.35	21.22	/	23.5	22.5	/
		836.5MHz	22.34	21.29	/	23.5	22.5	/
		825.5MHz	22.33	21.28	/	23.5	22.5	/



Full Power								
LTE Band 5			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	846.5MHz	23.08	22.33	/	24.5	23.5	/
		836.5MHz	23.11	22.35	/	24.5	23.5	/
		826.5MHz	23.12	22.36	/	24.5	23.5	/
	1RB_12	846.5MHz	23.30	22.52	/	24.5	23.5	/
		836.5MHz	23.43	22.69	/	24.5	23.5	/
		826.5MHz	23.38	22.59	/	24.5	23.5	/
	1RB_0	846.5MHz	23.00	22.23	/	24.5	23.5	/
		836.5MHz	23.10	22.38	/	24.5	23.5	/
		826.5MHz	23.07	22.36	/	24.5	23.5	/
	12RB_13	846.5MHz	22.18	21.19	/	23.5	22.5	/
		836.5MHz	22.29	21.22	/	23.5	22.5	/
		826.5MHz	22.27	21.23	/	23.5	22.5	/
	12RB_6	846.5MHz	22.30	21.25	/	23.5	22.5	/
		836.5MHz	22.32	21.32	/	23.5	22.5	/
		826.5MHz	22.36	21.31	/	23.5	22.5	/
	12RB_0	846.5MHz	22.22	21.18	/	23.5	22.5	/
		836.5MHz	22.27	21.23	/	23.5	22.5	/
		826.5MHz	22.28	21.23	/	23.5	22.5	/
	25RB_0	846.5MHz	22.26	21.23	/	23.5	22.5	/
		836.5MHz	22.31	21.29	/	23.5	22.5	/
		826.5MHz	22.32	21.29	/	23.5	22.5	/



Full Power								
LTE Band 5			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	844MHz	23.24	22.42	/	24.5	23.5	/
		836.5MHz	23.24	22.43	/	24.5	23.5	/
		829MHz	23.31	22.70	/	24.5	23.5	/
	1RB_24	844MHz	23.26	22.47	/	24.5	23.5	/
		836.5MHz	23.41	22.60	/	24.5	23.5	/
		829MHz	23.32	22.63	/	24.5	23.5	/
	1RB_0	844MHz	23.20	22.42	/	24.5	23.5	/
		836.5MHz	23.27	22.50	/	24.5	23.5	/
		829MHz	23.24	22.44	/	24.5	23.5	/
	25RB_25	844MHz	22.32	21.27	/	23.5	22.5	/
		836.5MHz	22.42	21.38	/	23.5	22.5	/
		829MHz	22.43	21.40	/	23.5	22.5	/
	25RB_12	844MHz	22.36	21.32	/	23.5	22.5	/
		836.5MHz	22.44	21.29	/	23.5	22.5	/
		829MHz	22.39	21.30	/	23.5	22.5	/
	25RB_0	844MHz	22.37	21.33	/	23.5	22.5	/
		836.5MHz	22.38	21.36	/	23.5	22.5	/
		829MHz	22.40	21.32	/	23.5	22.5	/
50RB_0	844MHz	22.32	21.30	/	23.5	22.5	/	
	836.5MHz	22.39	21.34	/	23.5	22.5	/	
	829MHz	22.40	21.38	/	23.5	22.5	/	



Sensor on								
LTE Band 5			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
1.4 MHz	1RB_5	848.3MHz	16.65	16.79	/	17.5	17.5	/
		836.5MHz	16.63	16.87	/	17.5	17.5	/
		824.7MHz	16.63	16.87	/	17.5	17.5	/
	1RB_3	848.3MHz	16.72	16.91	/	17.5	17.5	/
		836.5MHz	16.73	16.93	/	17.5	17.5	/
		824.7MHz	16.80	17.02	/	17.5	17.5	/
	1RB_0	848.3MHz	16.60	16.79	/	17.5	17.5	/
		836.5MHz	16.63	16.81	/	17.5	17.5	/
		824.7MHz	16.61	16.81	/	17.5	17.5	/
	3RB_3	848.3MHz	16.72	16.64	/	17.5	17.5	/
		836.5MHz	16.81	16.71	/	17.5	17.5	/
		824.7MHz	16.80	16.65	/	17.5	17.5	/
	3RB_1	848.3MHz	16.78	16.70	/	17.5	17.5	/
		836.5MHz	16.80	16.79	/	17.5	17.5	/
		824.7MHz	16.80	16.71	/	17.5	17.5	/
	3RB_0	848.3MHz	16.72	16.64	/	17.5	17.5	/
		836.5MHz	16.82	16.72	/	17.5	17.5	/
		824.7MHz	16.67	16.68	/	17.5	17.5	/
	6RB_0	848.3MHz	16.75	16.79	/	17.5	17.5	/
		836.5MHz	16.80	16.82	/	17.5	17.5	/
		824.7MHz	16.63	16.75	/	17.5	17.5	/



Sensor on								
LTE Band 5			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
3 MHz	1RB_14	847.5MHz	16.71	16.86	/	17.5	17.5	/
		836.5MHz	16.67	16.89	/	17.5	17.5	/
		825.5MHz	16.62	16.96	/	17.5	17.5	/
	1RB_7	847.5MHz	16.87	17.00	/	17.5	17.5	/
		836.5MHz	17.05	17.09	/	17.5	17.5	/
		825.5MHz	16.94	17.13	/	17.5	17.5	/
	1RB_0	847.5MHz	16.70	16.91	/	17.5	17.5	/
		836.5MHz	16.74	16.92	/	17.5	17.5	/
		825.5MHz	16.66	16.92	/	17.5	17.5	/
	8RB_7	847.5MHz	16.69	16.67	/	17.5	17.5	/
		836.5MHz	16.75	16.75	/	17.5	17.5	/
		825.5MHz	16.70	16.74	/	17.5	17.5	/
	8RB_4	847.5MHz	16.74	16.72	/	17.5	17.5	/
		836.5MHz	16.77	16.76	/	17.5	17.5	/
		825.5MHz	16.71	16.74	/	17.5	17.5	/
	8RB_0	847.5MHz	16.69	16.71	/	17.5	17.5	/
		836.5MHz	16.77	16.82	/	17.5	17.5	/
		825.5MHz	16.68	16.74	/	17.5	17.5	/
	15RB_0	847.5MHz	16.70	16.69	/	17.5	17.5	/
		836.5MHz	16.74	16.76	/	17.5	17.5	/
		825.5MHz	16.82	16.72	/	17.5	17.5	/





Sensor on								
LTE Band 5			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	846.5MHz	16.57	16.73	/	17.5	17.5	/
		836.5MHz	16.60	16.87	/	17.5	17.5	/
		826.5MHz	16.61	16.94	/	17.5	17.5	/
	1RB_12	846.5MHz	16.79	17.04	/	17.5	17.5	/
		836.5MHz	16.86	17.17	/	17.5	17.5	/
		826.5MHz	16.95	17.11	/	17.5	17.5	/
	1RB_0	846.5MHz	16.63	16.73	/	17.5	17.5	/
		836.5MHz	16.65	16.89	/	17.5	17.5	/
		826.5MHz	16.61	16.87	/	17.5	17.5	/
	12RB_13	846.5MHz	16.69	16.60	/	17.5	17.5	/
		836.5MHz	16.74	16.68	/	17.5	17.5	/
		826.5MHz	16.76	16.67	/	17.5	17.5	/
	12RB_6	846.5MHz	16.76	16.67	/	17.5	17.5	/
		836.5MHz	16.82	16.75	/	17.5	17.5	/
		826.5MHz	16.81	16.72	/	17.5	17.5	/
	12RB_0	846.5MHz	16.71	16.64	/	17.5	17.5	/
		836.5MHz	16.81	16.68	/	17.5	17.5	/
		826.5MHz	16.74	16.66	/	17.5	17.5	/
	25RB_0	846.5MHz	16.74	16.66	/	17.5	17.5	/
		836.5MHz	16.87	16.72	/	17.5	17.5	/
		826.5MHz	16.76	16.71	/	17.5	17.5	/



Sensor on								
LTE Band 5			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	844MHz	16.73	17.03	/	17.5	17.5	/
		836.5MHz	16.70	16.93	/	17.5	17.5	/
		829MHz	16.76	17.00	/	17.5	17.5	/
	1RB_24	844MHz	16.76	17.04	/	17.5	17.5	/
		836.5MHz	16.94	17.07	/	17.5	17.5	/
		829MHz	16.84	17.11	/	17.5	17.5	/
	1RB_0	844MHz	16.64	16.91	/	17.5	17.5	/
		836.5MHz	16.68	16.96	/	17.5	17.5	/
		829MHz	16.68	16.94	/	17.5	17.5	/
	25RB_25	844MHz	16.78	16.72	/	17.5	17.5	/
		836.5MHz	16.84	16.80	/	17.5	17.5	/
		829MHz	16.84	16.84	/	17.5	17.5	/
	25RB_12	844MHz	16.87	16.75	/	17.5	17.5	/
		836.5MHz	16.89	16.80	/	17.5	17.5	/
		829MHz	16.86	16.79	/	17.5	17.5	/
	25RB_0	844MHz	16.86	16.78	/	17.5	17.5	/
		836.5MHz	16.88	16.83	/	17.5	17.5	/
		829MHz	16.83	16.78	/	17.5	17.5	/
	50RB_0	844MHz	16.77	16.76	/	17.5	17.5	/
		836.5MHz	16.87	16.82	/	17.5	17.5	/
		829MHz	16.85	16.79	/	17.5	17.5	/



Full Power								
LTE Band 7			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	2567.4MHz	21.30	20.62	/	22.5	21.5	/
		2535MHz	21.31	20.61	/	22.5	21.5	/
		2502.5MHz	21.28	20.93	/	22.5	21.5	/
	1RB_12	2567.4MHz	21.49	20.90	/	22.5	21.5	/
		2535MHz	21.50	20.80	/	22.5	21.5	/
		2502.5MHz	21.35	20.91	/	22.5	21.5	/
	1RB_0	2567.4MHz	21.32	20.69	/	22.5	21.5	/
		2535MHz	21.18	20.53	/	22.5	21.5	/
		2502.5MHz	21.36	20.57	/	22.5	21.5	/
	12RB_13	2567.4MHz	20.32	19.36	/	21.5	20.5	/
		2535MHz	20.31	19.30	/	21.5	20.5	/
		2502.5MHz	20.36	19.31	/	21.5	20.5	/
	12RB_6	2567.4MHz	20.55	19.47	/	21.5	20.5	/
		2535MHz	20.32	19.36	/	21.5	20.5	/
		2502.5MHz	20.36	19.41	/	21.5	20.5	/
	12RB_0	2567.4MHz	20.43	19.46	/	21.5	20.5	/
		2535MHz	20.27	19.28	/	21.5	20.5	/
		2502.5MHz	20.30	19.30	/	21.5	20.5	/
	25RB_0	2567.4MHz	20.30	19.53	/	21.5	20.5	/
		2535MHz	20.33	19.33	/	21.5	20.5	/
		2502.5MHz	20.32	19.33	/	21.5	20.5	/



Full Power								
LTE Band 7			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	2565MHz	21.43	20.75	/	22.5	21.5	/
		2535MHz	21.39	20.70	/	22.5	21.5	/
		2505MHz	21.40	21.10	/	22.5	21.5	/
	1RB_24	2565MHz	21.52	20.84	/	22.5	21.5	/
		2535MHz	21.42	20.76	/	22.5	21.5	/
		2505MHz	21.45	20.91	/	22.5	21.5	/
	1RB_0	2565MHz	21.39	20.68	/	22.5	21.5	/
		2535MHz	21.18	20.68	/	22.5	21.5	/
		2505MHz	21.40	20.76	/	22.5	21.5	/
	25RB_25	2565MHz	20.39	19.40	/	21.5	20.5	/
		2535MHz	20.32	19.37	/	21.5	20.5	/
		2505MHz	20.38	19.39	/	21.5	20.5	/
	25RB_12	2565MHz	20.46	19.48	/	21.5	20.5	/
		2535MHz	20.33	19.43	/	21.5	20.5	/
		2505MHz	20.39	19.41	/	21.5	20.5	/
	25RB_0	2565MHz	20.45	19.49	/	21.5	20.5	/
		2535MHz	20.35	19.39	/	21.5	20.5	/
		2505MHz	20.37	19.47	/	21.5	20.5	/
	50RB_0	2565MHz	20.44	19.50	/	21.5	20.5	/
		2535MHz	20.36	19.39	/	21.5	20.5	/
		2505MHz	20.41	19.41	/	21.5	20.5	/



Full Power								
LTE Band 7			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
15 MHz	1RB_74	2562.5MHz	21.37	20.73	/	22.5	21.5	/
		2535MHz	21.29	20.60	/	22.5	21.5	/
		2507.5MHz	21.34	20.81	/	22.5	21.5	/
	1RB_37	2562.5MHz	21.44	20.74	/	22.5	21.5	/
		2535MHz	21.31	20.61	/	22.5	21.5	/
		2507.5MHz	21.36	20.67	/	22.5	21.5	/
	1RB_0	2562.5MHz	21.33	20.67	/	22.5	21.5	/
		2535MHz	21.21	20.52	/	22.5	21.5	/
		2507.5MHz	21.27	20.50	/	22.5	21.5	/
	36RB_38	2562.5MHz	20.43	19.47	/	21.5	20.5	/
		2535MHz	20.36	19.36	/	21.5	20.5	/
		2507.5MHz	20.46	19.46	/	21.5	20.5	/
	36RB_19	2562.5MHz	20.47	19.55	/	21.5	20.5	/
		2535MHz	20.39	19.41	/	21.5	20.5	/
		2507.5MHz	20.40	19.48	/	21.5	20.5	/
	36RB_0	2562.5MHz	20.47	19.52	/	21.5	20.5	/
		2535MHz	20.40	19.42	/	21.5	20.5	/
		2507.5MHz	20.43	19.43	/	21.5	20.5	/
	75RB_0	2562.5MHz	20.41	19.46	/	21.5	20.5	/
		2535MHz	20.34	19.40	/	21.5	20.5	/
		2507.5MHz	20.44	19.46	/	21.5	20.5	/



Full Power								
LTE Band 7			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
20 MHz	1RB_99	2560MHz	21.16	20.59	/	<b>22.5</b>	<b>21.5</b>	/
		2535MHz	21.24	20.46	/	<b>22.5</b>	<b>21.5</b>	/
		2510MHz	21.17	20.58	/	<b>22.5</b>	<b>21.5</b>	/
	1RB_50	2560MHz	<b>21.54</b>	20.75	/	<b>22.5</b>	<b>21.5</b>	/
		2535MHz	21.36	20.71	/	<b>22.5</b>	<b>21.5</b>	/
		2510MHz	21.43	20.86	/	<b>22.5</b>	<b>21.5</b>	/
	1RB_0	2560MHz	21.14	20.48	/	<b>22.5</b>	<b>21.5</b>	/
		2535MHz	21.01	20.37	/	<b>22.5</b>	<b>21.5</b>	/
		2510MHz	21.08	20.46	/	<b>22.5</b>	<b>21.5</b>	/
	50RB_50	2560MHz	20.37	19.43	/	<b>21.5</b>	<b>20.5</b>	/
		2535MHz	20.32	19.38	/	<b>21.5</b>	<b>20.5</b>	/
		2510MHz	<b>20.51</b>	19.54	/	<b>21.5</b>	<b>20.5</b>	/
	50RB_25	2560MHz	20.47	19.55	/	<b>21.5</b>	<b>20.5</b>	/
		2535MHz	20.36	19.37	/	<b>21.5</b>	<b>20.5</b>	/
		2510MHz	20.39	19.39	/	<b>21.5</b>	<b>20.5</b>	/
	50RB_0	2560MHz	20.37	19.39	/	<b>21.5</b>	<b>20.5</b>	/
		2535MHz	20.38	19.36	/	<b>21.5</b>	<b>20.5</b>	/
		2510MHz	20.41	19.40	/	<b>21.5</b>	<b>20.5</b>	/
	100RB_0	2560MHz	20.37	19.41	/	<b>21.5</b>	<b>20.5</b>	/
		2535MHz	20.29	19.38	/	<b>21.5</b>	<b>20.5</b>	/
		2510MHz	20.45	19.49	/	<b>21.5</b>	<b>20.5</b>	/



Sensor on								
LTE Band 7			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	2567.4MHz	12.33	12.47	/	13.0	13.0	/
		2535MHz	12.20	12.50	/	13.0	13.0	/
		2502.5MHz	12.29	12.53	/	13.0	13.0	/
	1RB_12	2567.4MHz	12.44	12.67	/	13.0	13.0	/
		2535MHz	12.39	12.64	/	13.0	13.0	/
		2502.5MHz	12.49	12.70	/	13.0	13.0	/
	1RB_0	2567.4MHz	12.31	12.51	/	13.0	13.0	/
		2535MHz	12.18	12.41	/	13.0	13.0	/
		2502.5MHz	12.25	12.60	/	13.0	13.0	/
	12RB_13	2567.4MHz	12.37	12.32	/	13.0	13.0	/
		2535MHz	12.34	12.36	/	13.0	13.0	/
		2502.5MHz	12.37	12.33	/	13.0	13.0	/
	12RB_6	2567.4MHz	12.46	12.46	/	13.0	13.0	/
		2535MHz	12.36	12.34	/	13.0	13.0	/
		2502.5MHz	12.37	12.41	/	13.0	13.0	/
	12RB_0	2567.4MHz	12.42	12.42	/	13.0	13.0	/
		2535MHz	12.30	12.31	/	13.0	13.0	/
		2502.5MHz	12.30	12.33	/	13.0	13.0	/
	25RB_0	2567.4MHz	12.47	12.42	/	13.0	13.0	/
		2535MHz	12.34	12.36	/	13.0	13.0	/
		2502.5MHz	12.40	12.33	/	13.0	13.0	/



Sensor on								
LTE Band 7			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	2565MHz	12.38	12.65	/	13.0	13.0	/
		2535MHz	12.34	12.61	/	13.0	13.0	/
		2505MHz	12.35	12.63	/	13.0	13.0	/
	1RB_24	2565MHz	12.50	12.72	/	13.0	13.0	/
		2535MHz	12.35	12.59	/	13.0	13.0	/
		2505MHz	12.40	12.66	/	13.0	13.0	/
	1RB_0	2565MHz	12.36	12.62	/	13.0	13.0	/
		2535MHz	12.31	12.55	/	13.0	13.0	/
		2505MHz	12.32	12.60	/	13.0	13.0	/
	25RB_25	2565MHz	12.45	12.45	/	13.0	13.0	/
		2535MHz	12.43	12.41	/	13.0	13.0	/
		2505MHz	12.45	12.42	/	13.0	13.0	/
	25RB_12	2565MHz	12.51	12.51	/	13.0	13.0	/
		2535MHz	12.39	12.37	/	13.0	13.0	/
		2505MHz	12.41	12.39	/	13.0	13.0	/
	25RB_0	2565MHz	12.51	12.51	/	13.0	13.0	/
		2535MHz	12.39	12.40	/	13.0	13.0	/
		2505MHz	12.40	12.42	/	13.0	13.0	/
	50RB_0	2565MHz	12.52	12.49	/	13.0	13.0	/
		2535MHz	12.46	12.43	/	13.0	13.0	/
		2505MHz	12.46	12.44	/	13.0	13.0	/





Sensor on								
LTE Band 7			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
15 MHz	1RB_74	2562.5MHz	12.35	12.69	/	13.0	13.0	/
		2535MHz	12.30	12.63	/	13.0	13.0	/
		2507.5MHz	12.36	12.64	/	13.0	13.0	/
	1RB_37	2562.5MHz	12.41	12.72	/	13.0	13.0	/
		2535MHz	12.33	12.62	/	13.0	13.0	/
		2507.5MHz	12.37	12.65	/	13.0	13.0	/
	1RB_0	2562.5MHz	12.32	12.65	/	13.0	13.0	/
		2535MHz	12.24	12.49	/	13.0	13.0	/
		2507.5MHz	12.25	12.58	/	13.0	13.0	/
	36RB_38	2562.5MHz	12.56	12.49	/	13.0	13.0	/
		2535MHz	12.43	12.39	/	13.0	13.0	/
		2507.5MHz	12.52	12.51	/	13.0	13.0	/
	36RB_19	2562.5MHz	12.52	12.53	/	13.0	13.0	/
		2535MHz	12.40	12.39	/	13.0	13.0	/
		2507.5MHz	12.48	12.46	/	13.0	13.0	/
	36RB_0	2562.5MHz	12.48	12.48	/	13.0	13.0	/
		2535MHz	12.43	12.37	/	13.0	13.0	/
		2507.5MHz	12.45	12.43	/	13.0	13.0	/
	75RB_0	2562.5MHz	12.54	12.48	/	13.0	13.0	/
		2535MHz	12.43	12.41	/	13.0	13.0	/
		2507.5MHz	12.49	12.45	/	13.0	13.0	/



Sensor on								
LTE Band 7			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
20 MHz	1RB_99	2560MHz	12.22	12.58	/	13.0	13.0	/
		2535MHz	12.16	12.50	/	13.0	13.0	/
		2510MHz	12.16	12.52	/	13.0	13.0	/
	1RB_50	2560MHz	<b>12.52</b>	12.72	/	13.0	13.0	/
		2535MHz	12.37	12.64	/	13.0	13.0	/
		2510MHz	12.50	12.78	/	13.0	13.0	/
	1RB_0	2560MHz	12.12	12.42	/	13.0	13.0	/
		2535MHz	12.08	12.42	/	13.0	13.0	/
		2510MHz	12.12	12.47	/	13.0	13.0	/
	50RB_50	2560MHz	12.50	12.45	/	13.0	13.0	/
		2535MHz	12.43	12.39	/	13.0	13.0	/
		2510MHz	12.51	12.50	/	13.0	13.0	/
	50RB_25	2560MHz	<b>12.56</b>	12.51	/	13.0	13.0	/
		2535MHz	12.44	12.41	/	13.0	13.0	/
		2510MHz	12.45	12.43	/	13.0	13.0	/
	50RB_0	2560MHz	12.43	12.41	/	13.0	13.0	/
		2535MHz	12.37	12.33	/	13.0	13.0	/
		2510MHz	12.40	12.38	/	13.0	13.0	/
	100RB_0	2560MHz	12.46	12.46	/	13.0	13.0	/
		2535MHz	12.38	12.37	/	13.0	13.0	/
		2510MHz	12.45	12.48	/	13.0	13.0	/



Full Power								
LTE Band 12			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
1.4 MHz	1RB_5	715.3MHz	22.89	22.13	/	24.5	23.5	/
		707.5MHz	22.96	22.15	/	24.5	23.5	/
		699.7MHz	22.94	22.10	/	24.5	23.5	/
	1RB_3	715.3MHz	23.02	22.25	/	24.5	23.5	/
		707.5MHz	23.06	22.34	/	24.5	23.5	/
		699.7MHz	23.05	22.20	/	24.5	23.5	/
	1RB_0	715.3MHz	22.96	22.18	/	24.5	23.5	/
		707.5MHz	22.92	22.15	/	24.5	23.5	/
		699.7MHz	22.56	22.11	/	24.5	23.5	/
	3RB_3	715.3MHz	23.00	21.91	/	24.5	23.5	/
		707.5MHz	23.08	21.97	/	24.5	23.5	/
		699.7MHz	23.06	22.00	/	24.5	23.5	/
	3RB_1	715.3MHz	23.08	22.06	/	24.5	23.5	/
		707.5MHz	23.07	22.00	/	24.5	23.5	/
		699.7MHz	23.07	21.95	/	24.5	23.5	/
	3RB_0	715.3MHz	23.05	21.97	/	24.5	23.5	/
		707.5MHz	23.03	21.96	/	24.5	23.5	/
		699.7MHz	23.02	21.94	/	24.5	23.5	/
	6RB_0	715.3MHz	22.05	21.07	/	23.5	22.5	/
		707.5MHz	22.05	21.09	/	23.5	22.5	/
		699.7MHz	21.99	21.10	/	23.5	22.5	/



Full Power								
LTE Band 12			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
3 MHz	1RB_14	714.5MHz	22.97	22.21	/	24.5	23.5	/
		707.5MHz	23.04	22.29	/	24.5	23.5	/
		700.5MHz	23.04	22.22	/	24.5	23.5	/
	1RB_7	714.5MHz	23.24	22.46	/	24.5	23.5	/
		707.5MHz	23.11	22.30	/	24.5	23.5	/
		700.5MHz	23.17	22.31	/	24.5	23.5	/
	1RB_0	714.5MHz	22.99	22.25	/	24.5	23.5	/
		707.5MHz	22.98	22.20	/	24.5	23.5	/
		700.5MHz	22.95	22.12	/	24.5	23.5	/
	8RB_7	714.5MHz	22.04	21.09	/	23.5	22.5	/
		707.5MHz	22.04	21.11	/	23.5	22.5	/
		700.5MHz	22.07	21.09	/	23.5	22.5	/
	8RB_4	714.5MHz	22.08	21.14	/	23.5	22.5	/
		707.5MHz	22.12	21.11	/	23.5	22.5	/
		700.5MHz	22.08	21.11	/	23.5	22.5	/
	8RB_0	714.5MHz	22.04	21.13	/	23.5	22.5	/
		707.5MHz	22.03	21.09	/	23.5	22.5	/
		700.5MHz	21.99	21.12	/	23.5	22.5	/
	15RB_0	714.5MHz	22.04	21.05	/	23.5	22.5	/
		707.5MHz	22.08	21.06	/	23.5	22.5	/
		700.5MHz	22.03	21.05	/	23.5	22.5	/



Full Power								
LTE Band 12			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	713.5MHz	22.89	22.15	/	24.5	23.5	/
		707.5MHz	22.94	22.33	/	24.5	23.5	/
		701.5MHz	22.95	22.19	/	24.5	23.5	/
	1RB_12	713.5MHz	23.17	22.47	/	24.5	23.5	/
		707.5MHz	23.18	22.37	/	24.5	23.5	/
		701.5MHz	23.18	22.28	/	24.5	23.5	/
	1RB_0	713.5MHz	22.88	22.07	/	24.5	23.5	/
		707.5MHz	22.84	22.14	/	24.5	23.5	/
		701.5MHz	22.83	22.00	/	24.5	23.5	/
	12RB_13	713.5MHz	22.07	20.96	/	23.5	22.5	/
		707.5MHz	22.03	20.97	/	23.5	22.5	/
		701.5MHz	22.05	21.05	/	23.5	22.5	/
	12RB_6	713.5MHz	22.12	21.04	/	23.5	22.5	/
		707.5MHz	22.11	21.07	/	23.5	22.5	/
		701.5MHz	22.05	21.10	/	23.5	22.5	/
	12RB_0	713.5MHz	22.00	20.95	/	23.5	22.5	/
		707.5MHz	22.05	21.00	/	23.5	22.5	/
		701.5MHz	22.02	20.98	/	23.5	22.5	/
	25RB_0	713.5MHz	22.07	21.00	/	23.5	22.5	/
		707.5MHz	22.05	21.04	/	23.5	22.5	/
		701.5MHz	22.04	21.02	/	23.5	22.5	/



Full Power								
LTE Band 12			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	711MHz	22.98	22.23	/	<b>24.5</b>	<b>23.5</b>	/
		707.5MHz	23.03	22.29	/	<b>24.5</b>	<b>23.5</b>	/
		704MHz	23.06	22.25	/	<b>24.5</b>	<b>23.5</b>	/
	1RB_24	711MHz	<b>23.10</b>	22.37	/	<b>24.5</b>	<b>23.5</b>	/
		707.5MHz	23.05	22.35	/	<b>24.5</b>	<b>23.5</b>	/
		704MHz	23.09	22.35	/	<b>24.5</b>	<b>23.5</b>	/
	1RB_0	711MHz	22.93	22.27	/	<b>24.5</b>	<b>23.5</b>	/
		707.5MHz	22.88	22.10	/	<b>24.5</b>	<b>23.5</b>	/
		704MHz	22.87	22.11	/	<b>24.5</b>	<b>23.5</b>	/
	25RB_25	711MHz	22.14	21.14	/	<b>23.5</b>	<b>22.5</b>	/
		707.5MHz	22.09	21.07	/	<b>23.5</b>	<b>22.5</b>	/
		704MHz	22.13	21.14	/	<b>23.5</b>	<b>22.5</b>	/
	25RB_12	711MHz	22.12	21.12	/	<b>23.5</b>	<b>22.5</b>	/
		707.5MHz	22.08	21.11	/	<b>23.5</b>	<b>22.5</b>	/
		704MHz	22.09	21.08	/	<b>23.5</b>	<b>22.5</b>	/
	25RB_0	711MHz	<b>22.16</b>	21.10	/	<b>23.5</b>	<b>22.5</b>	/
		707.5MHz	22.09	21.11	/	<b>23.5</b>	<b>22.5</b>	/
		704MHz	22.04	21.03	/	<b>23.5</b>	<b>22.5</b>	/
	50RB_0	711MHz	22.15	21.12	/	<b>23.5</b>	<b>22.5</b>	/
		707.5MHz	22.10	21.08	/	<b>23.5</b>	<b>22.5</b>	/
		704MHz	22.08	21.10	/	<b>23.5</b>	<b>22.5</b>	/



Sensor on								
LTE Band 12			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
1.4 MHz	1RB_5	715.3MHz	15.93	16.17	/	17.5	17.5	/
		707.5MHz	16.00	16.24	/	17.5	17.5	/
		699.7MHz	15.96	16.22	/	17.5	17.5	/
	1RB_3	715.3MHz	16.07	16.32	/	17.5	17.5	/
		707.5MHz	16.13	16.23	/	17.5	17.5	/
		699.7MHz	16.08	16.44	/	17.5	17.5	/
	1RB_0	715.3MHz	15.98	16.27	/	17.5	17.5	/
		707.5MHz	15.96	16.35	/	17.5	17.5	/
		699.7MHz	15.92	16.36	/	17.5	17.5	/
	3RB_3	715.3MHz	16.06	16.06	/	17.5	17.5	/
		707.5MHz	16.10	16.07	/	17.5	17.5	/
		699.7MHz	16.09	16.07	/	17.5	17.5	/
	3RB_1	715.3MHz	16.08	16.16	/	17.5	17.5	/
		707.5MHz	16.09	16.07	/	17.5	17.5	/
		699.7MHz	16.08	16.02	/	17.5	17.5	/
	3RB_0	715.3MHz	16.03	16.11	/	17.5	17.5	/
		707.5MHz	16.05	16.06	/	17.5	17.5	/
		699.7MHz	16.02	16.06	/	17.5	17.5	/
	6RB_0	715.3MHz	16.06	16.16	/	17.5	17.5	/
		707.5MHz	16.08	16.18	/	17.5	17.5	/
		699.7MHz	16.04	16.13	/	17.5	17.5	/



Sensor on								
LTE Band 12			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
3 MHz	1RB_14	714.5MHz	16.03	16.30	/	17.5	17.5	/
		707.5MHz	16.10	16.35	/	17.5	17.5	/
		700.5MHz	16.06	16.35	/	17.5	17.5	/
	1RB_7	714.5MHz	16.20	16.44	/	17.5	17.5	/
		707.5MHz	16.22	16.58	/	17.5	17.5	/
		700.5MHz	16.20	16.51	/	17.5	17.5	/
	1RB_0	714.5MHz	16.06	16.33	/	17.5	17.5	/
		707.5MHz	16.06	16.37	/	17.5	17.5	/
		700.5MHz	15.99	16.40	/	17.5	17.5	/
	8RB_7	714.5MHz	16.10	16.14	/	17.5	17.5	/
		707.5MHz	16.10	16.16	/	17.5	17.5	/
		700.5MHz	16.10	16.14	/	17.5	17.5	/
	8RB_4	714.5MHz	16.13	16.16	/	17.5	17.5	/
		707.5MHz	16.16	16.23	/	17.5	17.5	/
		700.5MHz	16.12	16.16	/	17.5	17.5	/
	8RB_0	714.5MHz	16.08	16.10	/	17.5	17.5	/
		707.5MHz	16.10	16.14	/	17.5	17.5	/
		700.5MHz	15.99	16.10	/	17.5	17.5	/
	15RB_0	714.5MHz	16.06	16.05	/	17.5	17.5	/
		707.5MHz	16.11	16.12	/	17.5	17.5	/
		700.5MHz	16.08	16.06	/	17.5	17.5	/





Sensor on								
LTE Band 12			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	713.5MHz	15.97	16.19	/	17.5	17.5	/
		707.5MHz	15.98	16.33	/	17.5	17.5	/
		701.5MHz	15.97	16.31	/	17.5	17.5	/
	1RB_12	713.5MHz	16.22	16.41	/	17.5	17.5	/
		707.5MHz	16.20	16.63	/	17.5	17.5	/
		701.5MHz	16.25	16.55	/	17.5	17.5	/
	1RB_0	713.5MHz	15.93	16.19	/	17.5	17.5	/
		707.5MHz	15.94	16.18	/	17.5	17.5	/
		701.5MHz	15.87	16.16	/	17.5	17.5	/
	12RB_13	713.5MHz	16.13	16.03	/	17.5	17.5	/
		707.5MHz	16.04	16.04	/	17.5	17.5	/
		701.5MHz	16.12	16.07	/	17.5	17.5	/
	12RB_6	713.5MHz	16.16	16.16	/	17.5	17.5	/
		707.5MHz	16.18	16.16	/	17.5	17.5	/
		701.5MHz	16.13	16.12	/	17.5	17.5	/
	12RB_0	713.5MHz	16.04	16.08	/	17.5	17.5	/
		707.5MHz	16.07	16.07	/	17.5	17.5	/
		701.5MHz	16.05	16.06	/	17.5	17.5	/
	25RB_0	713.5MHz	16.06	16.13	/	17.5	17.5	/
		707.5MHz	16.08	16.07	/	17.5	17.5	/
		701.5MHz	16.04	16.11	/	17.5	17.5	/



Sensor on								
LTE Band 12			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	711MHz	16.07	16.43	/	17.5	17.5	/
		707.5MHz	16.08	16.38	/	17.5	17.5	/
		704MHz	16.14	16.33	/	17.5	17.5	/
	1RB_24	711MHz	<b>16.18</b>	16.33	/	17.5	17.5	/
		707.5MHz	16.10	16.45	/	17.5	17.5	/
		704MHz	16.17	16.40	/	17.5	17.5	/
	1RB_0	711MHz	15.99	16.17	/	17.5	17.5	/
		707.5MHz	15.97	16.27	/	17.5	17.5	/
		704MHz	15.95	16.20	/	17.5	17.5	/
	25RB_25	711MHz	16.15	16.15	/	17.5	17.5	/
		707.5MHz	16.12	16.11	/	17.5	17.5	/
		704MHz	16.14	16.14	/	17.5	17.5	/
	25RB_12	711MHz	16.15	16.13	/	17.5	17.5	/
		707.5MHz	16.16	16.10	/	17.5	17.5	/
		704MHz	16.09	16.12	/	17.5	17.5	/
	25RB_0	711MHz	<b>16.17</b>	16.16	/	17.5	17.5	/
		707.5MHz	16.06	16.14	/	17.5	17.5	/
		704MHz	16.07	16.02	/	17.5	17.5	/
	50RB_0	711MHz	16.22	16.21	/	17.5	17.5	/
		707.5MHz	16.10	16.09	/	17.5	17.5	/
		704MHz	16.16	16.10	/	17.5	17.5	/



Full Power								
LTE Band 17			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	713.5MHz	23.13	22.35	/	24.5	23.5	/
		710MHz	23.18	22.41	/	24.5	23.5	/
		706.5MHz	23.20	22.43	/	24.5	23.5	/
	1RB_12	713.5MHz	23.44	22.58	/	24.5	23.5	/
		710MHz	23.44	22.60	/	24.5	23.5	/
		706.5MHz	23.41	22.69	/	24.5	23.5	/
	1RB_0	713.5MHz	23.12	22.29	/	24.5	23.5	/
		710MHz	23.12	22.32	/	24.5	23.5	/
		706.5MHz	23.11	22.34	/	24.5	23.5	/
	12RB_13	713.5MHz	22.25	21.22	/	23.5	22.5	/
		710MHz	22.32	21.28	/	23.5	22.5	/
		706.5MHz	22.27	21.23	/	23.5	22.5	/
	12RB_6	713.5MHz	22.33	21.26	/	23.5	22.5	/
		710MHz	22.29	21.27	/	23.5	22.5	/
		706.5MHz	22.27	21.24	/	23.5	22.5	/
	12RB_0	713.5MHz	22.23	21.19	/	23.5	22.5	/
		710MHz	22.28	21.22	/	23.5	22.5	/
		706.5MHz	22.27	21.22	/	23.5	22.5	/
	25RB_0	713.5MHz	22.21	21.20	/	23.5	22.5	/
		710MHz	22.25	21.19	/	23.5	22.5	/
		706.5MHz	22.21	21.23	/	23.5	22.5	/



Full Power								
LTE Band 17			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	711MHz	23.28	22.63	/	24.5	23.5	/
		710MHz	23.26	22.45	/	24.5	23.5	/
		709MHz	23.31	22.40	/	24.5	23.5	/
	1RB_24	711MHz	23.40	22.58	/	24.5	23.5	/
		710MHz	23.42	22.64	/	24.5	23.5	/
		709MHz	23.35	22.59	/	24.5	23.5	/
	1RB_0	711MHz	23.20	22.44	/	24.5	23.5	/
		710MHz	23.19	22.40	/	24.5	23.5	/
		709MHz	23.21	22.38	/	24.5	23.5	/
	25RB_25	711MHz	22.36	21.32	/	23.5	22.5	/
		710MHz	22.38	21.31	/	23.5	22.5	/
		709MHz	22.40	21.39	/	23.5	22.5	/
	25RB_12	711MHz	22.38	21.35	/	23.5	22.5	/
		710MHz	22.41	21.32	/	23.5	22.5	/
		709MHz	22.39	21.31	/	23.5	22.5	/
	25RB_0	711MHz	22.36	21.31	/	23.5	22.5	/
		710MHz	22.36	21.29	/	23.5	22.5	/
		709MHz	22.34	21.26	/	23.5	22.5	/
	50RB_0	711MHz	22.35	21.32	/	23.5	22.5	/
		710MHz	22.32	21.33	/	23.5	22.5	/
		709MHz	22.36	21.32	/	23.5	22.5	/



Sensor on								
LTE Band 17			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	713.5MHz	16.52	16.89	/	17.5	17.5	/
		710MHz	16.54	16.81	/	17.5	17.5	/
		706.5MHz	16.54	16.79	/	17.5	17.5	/
	1RB_12	713.5MHz	16.71	16.98	/	17.5	17.5	/
		710MHz	16.73	17.00	/	17.5	17.5	/
		706.5MHz	16.76	17.12	/	17.5	17.5	/
	1RB_0	713.5MHz	16.49	16.84	/	17.5	17.5	/
		710MHz	16.47	16.71	/	17.5	17.5	/
		706.5MHz	16.46	16.81	/	17.5	17.5	/
	12RB_13	713.5MHz	16.63	16.62	/	17.5	17.5	/
		710MHz	16.65	16.66	/	17.5	17.5	/
		706.5MHz	16.62	16.64	/	17.5	17.5	/
	12RB_6	713.5MHz	16.67	16.66	/	17.5	17.5	/
		710MHz	16.67	16.70	/	17.5	17.5	/
		706.5MHz	16.66	16.65	/	17.5	17.5	/
	12RB_0	713.5MHz	16.62	16.62	/	17.5	17.5	/
		710MHz	16.65	16.65	/	17.5	17.5	/
		706.5MHz	16.65	16.61	/	17.5	17.5	/
	25RB_0	713.5MHz	16.65	16.61	/	17.5	17.5	/
		710MHz	16.69	16.67	/	17.5	17.5	/
		706.5MHz	16.64	16.63	/	17.5	17.5	/



Sensor on								
LTE Band 17			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	711MHz	16.66	16.85	/	17.5	17.5	/
		710MHz	16.66	16.88	/	17.5	17.5	/
		709MHz	16.64	16.91	/	17.5	17.5	/
	1RB_24	711MHz	16.75	16.97	/	17.5	17.5	/
		710MHz	16.76	16.93	/	17.5	17.5	/
		709MHz	16.71	16.92	/	17.5	17.5	/
	1RB_0	711MHz	16.56	16.76	/	17.5	17.5	/
		710MHz	16.56	16.79	/	17.5	17.5	/
		709MHz	16.58	16.82	/	17.5	17.5	/
	25RB_25	711MHz	16.71	16.68	/	17.5	17.5	/
		710MHz	16.73	16.72	/	17.5	17.5	/
		709MHz	16.74	16.72	/	17.5	17.5	/
	25RB_12	711MHz	16.74	16.71	/	17.5	17.5	/
		710MHz	16.79	16.68	/	17.5	17.5	/
		709MHz	16.77	16.72	/	17.5	17.5	/
	25RB_0	711MHz	16.76	16.71	/	17.5	17.5	/
		710MHz	16.71	16.67	/	17.5	17.5	/
		709MHz	16.67	16.69	/	17.5	17.5	/
	50RB_0	711MHz	16.70	16.72	/	17.5	17.5	/
		710MHz	16.71	16.72	/	17.5	17.5	/
		709MHz	16.69	16.72	/	17.5	17.5	/



Full Power								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
1.4 MHz	1RB_5	1779.3MHz	23.39	22.53	/	24.5	23.5	/
		1745MHz	23.30	22.59	/	24.5	23.5	/
		1710.7MHz	23.25	22.41	/	24.5	23.5	/
	1RB_3	1779.3MHz	23.49	22.65	/	24.5	23.5	/
		1745MHz	23.47	22.77	/	24.5	23.5	/
		1710.7MHz	23.37	22.60	/	24.5	23.5	/
	1RB_0	1779.3MHz	23.37	22.61	/	24.5	23.5	/
		1745MHz	23.32	22.65	/	24.5	23.5	/
		1710.7MHz	23.25	22.49	/	24.5	23.5	/
	3RB_3	1779.3MHz	23.47	22.43	/	24.5	23.5	/
		1745MHz	23.48	22.46	/	24.5	23.5	/
		1710.7MHz	23.36	22.41	/	24.5	23.5	/
	3RB_1	1779.3MHz	23.54	22.49	/	24.5	23.5	/
		1745MHz	23.53	22.52	/	24.5	23.5	/
		1710.7MHz	23.43	22.45	/	24.5	23.5	/
	3RB_0	1779.3MHz	23.47	22.40	/	24.5	23.5	/
		1745MHz	23.52	22.54	/	24.5	23.5	/
		1710.7MHz	23.37	22.39	/	24.5	23.5	/
	6RB_0	1779.3MHz	22.46	21.59	/	23.5	22.5	/
		1745MHz	22.46	21.62	/	23.5	22.5	/
		1710.7MHz	22.42	21.49	/	23.5	22.5	/



Full Power								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
3 MHz	1RB_14	1778.5MHz	23.32	22.63	/	24.5	23.5	/
		1745MHz	23.38	22.74	/	24.5	23.5	/
		1711.5MHz	23.30	22.59	/	24.5	23.5	/
	1RB_7	1778.5MHz	23.35	22.80	/	24.5	23.5	/
		1745MHz	23.52	22.78	/	24.5	23.5	/
		1711.5MHz	23.52	22.65	/	24.5	23.5	/
	1RB_0	1778.5MHz	23.22	22.63	/	24.5	23.5	/
		1745MHz	23.40	22.71	/	24.5	23.5	/
		1711.5MHz	23.34	22.57	/	24.5	23.5	/
	8RB_7	1778.5MHz	23.41	21.49	/	23.5	22.5	/
		1745MHz	22.42	21.60	/	23.5	22.5	/
		1711.5MHz	22.41	21.57	/	23.5	22.5	/
	8RB_4	1778.5MHz	23.37	21.58	/	23.5	22.5	/
		1745MHz	22.45	21.65	/	23.5	22.5	/
		1711.5MHz	22.41	21.56	/	23.5	22.5	/
	8RB_0	1778.5MHz	23.32	21.55	/	23.5	22.5	/
		1745MHz	22.45	21.63	/	23.5	22.5	/
		1711.5MHz	22.38	21.52	/	23.5	22.5	/
	15RB_0	1778.5MHz	22.41	21.48	/	23.5	22.5	/
		1745MHz	22.44	21.51	/	23.5	22.5	/
		1711.5MHz	22.42	21.47	/	23.5	22.5	/





Full Power								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	1777.5MHz	23.24	22.53	/	24.5	23.5	/
		1745MHz	23.23	22.58	/	24.5	23.5	/
		1712.5MHz	23.18	22.46	/	24.5	23.5	/
	1RB_12	1777.5MHz	23.47	23.09	/	24.5	23.5	/
		1745MHz	23.54	22.87	/	24.5	23.5	/
		1712.5MHz	23.45	22.83	/	24.5	23.5	/
	1RB_0	1777.5MHz	23.31	22.50	/	24.5	23.5	/
		1745MHz	23.28	22.61	/	24.5	23.5	/
		1712.5MHz	23.23	22.48	/	24.5	23.5	/
	12RB_13	1777.5MHz	22.38	21.43	/	23.5	22.5	/
		1745MHz	22.40	21.52	/	23.5	22.5	/
		1712.5MHz	22.41	21.44	/	23.5	22.5	/
	12RB_6	1777.5MHz	22.46	21.47	/	23.5	22.5	/
		1745MHz	22.48	21.57	/	23.5	22.5	/
		1712.5MHz	22.44	21.49	/	23.5	22.5	/
	12RB_0	1777.5MHz	22.45	21.46	/	23.5	22.5	/
		1745MHz	22.46	21.49	/	23.5	22.5	/
		1712.5MHz	22.37	21.36	/	23.5	22.5	/
	25RB_0	1777.5MHz	22.44	21.44	/	23.5	22.5	/
		1745MHz	22.45	21.54	/	23.5	22.5	/
		1712.5MHz	22.43	21.44	/	23.5	22.5	/



Full Power								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	1715MHz	23.31	22.53	/	24.5	23.5	/
		1715MHz	23.29	22.63	/	24.5	23.5	/
		1715MHz	23.26	22.56	/	24.5	23.5	/
	1RB_24	1715MHz	23.50	22.61	/	24.5	23.5	/
		1715MHz	23.46	22.74	/	24.5	23.5	/
		1715MHz	23.37	22.61	/	24.5	23.5	/
	1RB_0	1715MHz	23.39	22.56	/	24.5	23.5	/
		1715MHz	23.37	22.71	/	24.5	23.5	/
		1715MHz	23.30	22.58	/	24.5	23.5	/
	25RB_25	1715MHz	22.45	21.48	/	23.5	22.5	/
		1715MHz	22.45	21.49	/	23.5	22.5	/
		1715MHz	22.52	21.54	/	23.5	22.5	/
	25RB_12	1715MHz	22.51	21.50	/	23.5	22.5	/
		1715MHz	22.46	21.56	/	23.5	22.5	/
		1715MHz	22.44	21.45	/	23.5	22.5	/
	25RB_0	1715MHz	22.55	21.56	/	23.5	22.5	/
		1715MHz	22.45	21.52	/	23.5	22.5	/
		1715MHz	22.38	21.37	/	23.5	22.5	/
	50RB_0	1715MHz	22.53	21.55	/	23.5	22.5	/
		1715MHz	22.44	21.51	/	23.5	22.5	/
		1715MHz	22.52	21.52	/	23.5	22.5	/



Full Power								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
15 MHz	1RB_74	1772.5MHz	23.29	22.56	/	24.5	23.5	/
		1745MHz	23.25	22.52	/	24.5	23.5	/
		1717.5MHz	23.24	22.56	/	24.5	23.5	/
	1RB_37	1772.5MHz	23.48	22.61	/	24.5	23.5	/
		1745MHz	23.40	22.82	/	24.5	23.5	/
		1717.5MHz	23.29	22.60	/	24.5	23.5	/
	1RB_0	1772.5MHz	23.37	22.57	/	24.5	23.5	/
		1745MHz	23.36	22.67	/	24.5	23.5	/
		1717.5MHz	23.32	22.61	/	24.5	23.5	/
	36RB_38	1772.5MHz	22.49	21.49	/	23.5	22.5	/
		1745MHz	22.43	21.43	/	23.5	22.5	/
		1717.5MHz	22.50	21.47	/	23.5	22.5	/
	36RB_19	1772.5MHz	22.54	21.50	/	23.5	22.5	/
		1745MHz	22.44	21.48	/	23.5	22.5	/
		1717.5MHz	22.43	21.42	/	23.5	22.5	/
	36RB_0	1772.5MHz	22.54	21.54	/	23.5	22.5	/
		1745MHz	22.52	21.55	/	23.5	22.5	/
		1717.5MHz	22.42	21.40	/	23.5	22.5	/
	75RB_0	1772.5MHz	22.48	21.48	/	23.5	22.5	/
		1745MHz	22.45	21.55	/	23.5	22.5	/
		1717.5MHz	22.44	21.42	/	23.5	22.5	/



Full Power								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
20 MHz	1RB_99	1770MHz	23.06	22.31	/	24.5	23.5	/
		1745MHz	22.99	22.41	/	24.5	23.5	/
		1720MHz	23.02	22.50	/	24.5	23.5	/
	1RB_50	1770MHz	23.46	22.70	/	24.5	23.5	/
		1745MHz	23.47	22.75	/	24.5	23.5	/
		1720MHz	23.33	22.78	/	24.5	23.5	/
	1RB_0	1770MHz	23.10	22.47	/	24.5	23.5	/
		1745MHz	23.13	22.45	/	24.5	23.5	/
		1720MHz	23.11	22.50	/	24.5	23.5	/
	50RB_50	1770MHz	22.45	21.51	/	23.5	22.5	/
		1745MHz	22.34	21.45	/	23.5	22.5	/
		1720MHz	22.43	21.47	/	23.5	22.5	/
	50RB_25	1770MHz	22.46	21.49	/	23.5	22.5	/
		1745MHz	22.48	21.49	/	23.5	22.5	/
		1720MHz	22.41	21.39	/	23.5	22.5	/
	50RB_0	1770MHz	22.43	21.49	/	23.5	22.5	/
		1745MHz	22.51	21.57	/	23.5	22.5	/
		1720MHz	22.26	21.27	/	23.5	22.5	/
	100RB_0	1770MHz	22.46	21.45	/	23.5	22.5	/
		1745MHz	22.42	21.49	/	23.5	22.5	/
		1720MHz	22.34	21.32	/	23.5	22.5	/



Sensor on								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
1.4 MHz	1RB_5	1779.3MHz	16.24	16.48	/	17.0	17.0	/
		1745MHz	16.24	16.61	/	17.0	17.0	/
		1710.7MHz	16.20	16.36	/	17.0	17.0	/
	1RB_3	1779.3MHz	16.35	16.60	/	17.0	17.0	/
		1745MHz	16.34	16.65	/	17.0	17.0	/
		1710.7MHz	16.30	16.63	/	17.0	17.0	/
	1RB_0	1779.3MHz	16.21	16.48	/	17.0	17.0	/
		1745MHz	16.22	16.60	/	17.0	17.0	/
		1710.7MHz	16.24	16.50	/	17.0	17.0	/
	3RB_3	1779.3MHz	16.28	16.23	/	17.0	17.0	/
		1745MHz	16.31	16.27	/	17.0	17.0	/
		1710.7MHz	16.31	16.29	/	17.0	17.0	/
	3RB_1	1779.3MHz	16.33	16.29	/	17.0	17.0	/
		1745MHz	16.36	16.35	/	17.0	17.0	/
		1710.7MHz	16.34	16.37	/	17.0	17.0	/
	3RB_0	1779.3MHz	16.33	16.24	/	17.0	17.0	/
		1745MHz	16.28	16.27	/	17.0	17.0	/
		1710.7MHz	16.29	16.30	/	17.0	17.0	/
	6RB_0	1779.3MHz	16.31	16.35	/	17.0	17.0	/
		1745MHz	16.30	16.42	/	17.0	17.0	/
		1710.7MHz	16.28	16.42	/	17.0	17.0	/



Sensor on								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
3 MHz	1RB_14	1778.5MHz	16.22	16.56	/	17.0	17.0	/
		1745MHz	16.24	16.62	/	17.0	17.0	/
		1711.5MHz	16.24	16.49	/	17.0	17.0	/
	1RB_7	1778.5MHz	16.40	16.73	/	17.0	17.0	/
		1745MHz	16.44	16.75	/	17.0	17.0	/
		1711.5MHz	16.44	16.65	/	17.0	17.0	/
	1RB_0	1778.5MHz	16.22	16.59	/	17.0	17.0	/
		1745MHz	16.27	16.62	/	17.0	17.0	/
		1711.5MHz	16.25	16.50	/	17.0	17.0	/
	8RB_7	1778.5MHz	16.26	16.30	/	17.0	17.0	/
		1745MHz	16.27	16.32	/	17.0	17.0	/
		1711.5MHz	16.29	16.33	/	17.0	17.0	/
	8RB_4	1778.5MHz	16.34	16.33	/	17.0	17.0	/
		1745MHz	16.34	16.37	/	17.0	17.0	/
		1711.5MHz	16.31	16.37	/	17.0	17.0	/
	8RB_0	1778.5MHz	16.31	16.32	/	17.0	17.0	/
		1745MHz	16.26	16.35	/	17.0	17.0	/
		1711.5MHz	16.29	16.37	/	17.0	17.0	/
	15RB_0	1778.5MHz	16.34	16.36	/	17.0	17.0	/
		1745MHz	16.24	16.35	/	17.0	17.0	/
		1711.5MHz	16.29	16.31	/	17.0	17.0	/



Sensor on								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5 MHz	1RB_24	1777.5MHz	16.13	16.32	/	17.0	17.0	/
		1745MHz	16.11	16.42	/	17.0	17.0	/
		1712.5MHz	16.09	16.37	/	17.0	17.0	/
	1RB_12	1777.5MHz	16.50	16.70	/	17.0	17.0	/
		1745MHz	16.38	16.59	/	17.0	17.0	/
		1712.5MHz	16.41	16.56	/	17.0	17.0	/
	1RB_0	1777.5MHz	16.16	16.35	/	17.0	17.0	/
		1745MHz	16.18	16.48	/	17.0	17.0	/
		1712.5MHz	16.12	16.44	/	17.0	17.0	/
	12RB_13	1777.5MHz	16.28	16.22	/	17.0	17.0	/
		1745MHz	16.26	16.23	/	17.0	17.0	/
		1712.5MHz	16.28	16.22	/	17.0	17.0	/
	12RB_6	1777.5MHz	16.36	16.30	/	17.0	17.0	/
		1745MHz	16.31	16.35	/	17.0	17.0	/
		1712.5MHz	16.31	16.32	/	17.0	17.0	/
	12RB_0	1777.5MHz	16.29	16.27	/	17.0	17.0	/
		1745MHz	16.27	16.29	/	17.0	17.0	/
		1712.5MHz	16.23	16.24	/	17.0	17.0	/
	25RB_0	1777.5MHz	16.28	16.27	/	17.0	17.0	/
		1745MHz	16.28	16.27	/	17.0	17.0	/
		1712.5MHz	16.31	16.33	/	17.0	17.0	/



Sensor on								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10 MHz	1RB_49	1715MHz	16.25	16.39	/	17.0	17.0	/
		1715MHz	16.19	16.45	/	17.0	17.0	/
		1715MHz	16.15	16.36	/	17.0	17.0	/
	1RB_24	1715MHz	16.30	16.52	/	17.0	17.0	/
		1715MHz	16.32	16.58	/	17.0	17.0	/
		1715MHz	16.34	16.51	/	17.0	17.0	/
	1RB_0	1715MHz	16.29	16.50	/	17.0	17.0	/
		1715MHz	16.24	16.56	/	17.0	17.0	/
		1715MHz	16.28	16.44	/	17.0	17.0	/
	25RB_25	1715MHz	16.27	16.29	/	17.0	17.0	/
		1715MHz	16.27	16.25	/	17.0	17.0	/
		1715MHz	16.30	16.26	/	17.0	17.0	/
	25RB_12	1715MHz	16.36	16.36	/	17.0	17.0	/
		1715MHz	16.32	16.34	/	17.0	17.0	/
		1715MHz	16.31	16.29	/	17.0	17.0	/
	25RB_0	1715MHz	16.40	16.36	/	17.0	17.0	/
		1715MHz	16.33	16.33	/	17.0	17.0	/
		1715MHz	16.21	16.25	/	17.0	17.0	/
	50RB_0	1715MHz	16.37	16.36	/	17.0	17.0	/
		1715MHz	16.29	16.30	/	17.0	17.0	/
		1715MHz	16.30	16.32	/	17.0	17.0	/





Sensor on								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
15 MHz	1RB_74	1772.5MHz	16.20	16.39	/	17.0	17.0	/
		1745MHz	16.14	16.40	/	17.0	17.0	/
		1717.5MHz	16.15	16.46	/	17.0	17.0	/
	1RB_37	1772.5MHz	16.32	16.54	/	17.0	17.0	/
		1745MHz	16.31	16.62	/	17.0	17.0	/
		1717.5MHz	16.24	16.55	/	17.0	17.0	/
	1RB_0	1772.5MHz	16.31	16.51	/	17.0	17.0	/
		1745MHz	16.24	16.58	/	17.0	17.0	/
		1717.5MHz	16.20	16.56	/	17.0	17.0	/
	36RB_38	1772.5MHz	16.29	16.28	/	17.0	17.0	/
		1745MHz	16.29	16.28	/	17.0	17.0	/
		1717.5MHz	16.33	16.25	/	17.0	17.0	/
	36RB_19	1772.5MHz	16.39	16.33	/	17.0	17.0	/
		1745MHz	16.29	16.31	/	17.0	17.0	/
		1717.5MHz	16.28	16.27	/	17.0	17.0	/
	36RB_0	1772.5MHz	16.36	16.36	/	17.0	17.0	/
		1745MHz	16.36	16.37	/	17.0	17.0	/
		1717.5MHz	16.29	16.24	/	17.0	17.0	/
	75RB_0	1772.5MHz	16.34	16.31	/	17.0	17.0	/
		1745MHz	16.34	16.32	/	17.0	17.0	/
		1717.5MHz	16.25	16.28	/	17.0	17.0	/



Sensor on								
LTE Band 66			Actual output Power (dBm)			Tune up		
Band -width	RB No. / RB offset	Frequency	Modulation			Modulation		
			QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
20 MHz	1RB_99	1770MHz	16.03	16.19	/	17.0	17.0	/
		1745MHz	15.95	16.20	/	17.0	17.0	/
		1720MHz	16.02	16.27	/	17.0	17.0	/
	1RB_50	1770MHz	16.43	16.52	/	17.0	17.0	/
		1745MHz	<b>16.45</b>	16.62	/	17.0	17.0	/
		1720MHz	16.36	16.47	/	17.0	17.0	/
	1RB_0	1770MHz	16.07	16.23	/	17.0	17.0	/
		1745MHz	16.11	16.36	/	17.0	17.0	/
		1720MHz	16.08	16.37	/	17.0	17.0	/
	50RB_50	1770MHz	16.40	16.32	/	17.0	17.0	/
		1745MHz	16.31	16.29	/	17.0	17.0	/
		1720MHz	16.35	16.27	/	17.0	17.0	/
	50RB_25	1770MHz	16.41	16.37	/	17.0	17.0	/
		1745MHz	16.35	16.34	/	17.0	17.0	/
		1720MHz	16.36	16.25	/	17.0	17.0	/
	50RB_0	1770MHz	16.42	16.39	/	17.0	17.0	/
		1745MHz	<b>16.44</b>	16.42	/	17.0	17.0	/
		1720MHz	16.26	16.26	/	17.0	17.0	/
	100RB_0	1770MHz	16.38	16.31	/	17.0	17.0	/
		1745MHz	16.37	16.31	/	17.0	17.0	/
		1720MHz	16.29	16.26	/	17.0	17.0	/

## 10.4. Bluetooth and WLAN Measurement result

**Table 10.5: The conducted Power measurement results for Bluetooth**

Bluetooth	Tune up	Averaged Power (dBm)		
Mode		Ch.0 (2402 MHz)	Ch39 (2441 MHz)	Ch78 (2480 MHz)
GFSK	<b>9.5</b>	9.07	8.85	8.92
EDR2M-4_DQPSK	<b>8.5</b>	8.12	7.24	8.04
EDR3M-8DPSK	<b>8.5</b>	8.11	7.29	8.05
/	/	Ch0 (2402MHz)	Ch19 (2440MHz)	Ch39 (2480MHz)
BLE	<b>-2.5</b>	-3.82	-3.47	-3.89

**Table 10.6: The conducted Power measurement results for WLAN 2.4G**

WLAN 2.4GHz	Tune up	Averaged Power (dBm) Duty Cycle: 100%		
Mode		Ch.1(2412 MHz)	Ch.6(2437Mhz)	Ch.11(2462MHz)
802.11b	<b>12.0</b>	11.35	<b>11.56</b>	11.23
802.11g	<b>12.0</b>	11.21	11.33	11.05
802.11n(20MHz)	<b>12.0</b>	11.02	11.32	10.93
/	/	Ch.3(2422 MHz)	Ch.6(2437Mhz)	Ch.9(2452MHz)
802.11n(40MHz)	<b>12.0</b>	11.13	11.24	11.08

**Table 10.7: The conducted Power measurement results for WLAN 5G**

Averaged Power (dBm) Duty Cycle: 100%								
Mode	802.11a	802.11n -20MHz	802.11ac -20MHz	Mode	802.11n -40MHz	802.11ac -40MHz	Mode	802.11ac -80MHz
Channel	6Mbps	MCS0	MCS0	Channel	MCS0	MCS0	Channel	MCS0
<b>&lt;U-NII-1&gt;</b>								
<b>Tune up</b>	<b>10</b>	<b>9.5</b>	<b>9.5</b>	/	<b>9.5</b>	<b>9.5</b>	/	<b>9.5</b>
36(5180MHz)	8.70	8.62	8.64	38(5190MHz)	8.40	8.41	42(5210MHz)	8.29
40(5200MHz)	8.79	8.58	8.59	46(5230MHz)	8.52	8.54	/	/
44(5240MHz)	8.88	8.70	8.67	/	/	/	/	/
<b>&lt;U-NII-2A&gt;</b>								
<b>Tune up</b>	<b>10</b>	<b>9.5</b>	<b>9.5</b>	/	<b>9.5</b>	<b>9.5</b>	/	<b>9.5</b>
52(5260MHz)	8.87	8.74	8.79	54(5270MHz)	8.61	8.62	58(5290MHz)	8.39
56(5280MHz)	8.97	8.86	8.88	62(5310MHz)	8.69	8.66	/	/
64(5320MHz)	<b>9.17</b>	8.96	8.97	/	/	/	/	/
<b>&lt;U-NII-3&gt;</b>								
<b>Tune up</b>	<b>8.5</b>	<b>8.0</b>	<b>8.0</b>	/	<b>8.0</b>	<b>8.0</b>	/	<b>8.0</b>
149(5745MHz)	7.69	7.55	7.53	151(5755MHz)	7.41	7.40	155(5775MHz)	7.00
157(5785MHz)	7.62	7.48	7.47	159(5795MHz)	7.43	7.43	/	/
165(5825MHz)	<b>7.71</b>	7.57	7.56	/	/	/	/	/


## 11. Simultaneous TX SAR Considerations

### 11.1. Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

For this device, the BT and WLAN can transmit simultaneous with other transmitters.

### 11.2. Transmit Antenna Separation Distances



Picture 11.1 Antenna Locations (Back View)

### 11.3 SAR Measurement Positions

SAR measurement positions					
Antenna	Rear	Left edge	Right edge	Top edge	Bottom edge
WWAN	Yes	No	Yes	Yes	No
WLAN	Yes	Yes	No	Yes	No

Note:

1. Per KDB 447498 D01v06, the 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

2. Per KDB 447498 D01v06, For 100 MHz to 6 GHz and *test separation distances*  $> 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following

1)  $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\}$  mW, for 100 MHz to 1500 MHz

2)  $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\}$  mW, for  $> 1500$  MHz and  $\leq 6$  GHz

### 11.4. Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

**Table 11.1: Standalone SAR test exclusion considerations**

Band/Mode	f(GHz)	Position	SAR test exclusion threshold (mW)	RF output power		SAR test exclusion
				dBm	mW	
Bluetooth	2.4	Body	9.60	9.5	8.91	Yes
WLAN 2.4GHz	2.4	Body	9.58	12.0	15.85	No
WLAN 5GHz	5.2	Body	6.58	10.0	10.00	No
	5.3	Body	6.52	10.0	10.00	No
	5.8	Body	6.23	8.5	7.08	No

## 12. Evaluation of Simultaneous

**Table 12.1: The sum of reported SAR values for main antenna and WLAN**

/	Position	Main Antenna (W/kg)	WLAN (W/kg)	Sum (W/kg)
Highest reported SAR value for Body	Top	1.18	0.41	1.59

Note: the test positions of above tables are for the worse case that has been evaluated.

According to the KDB 447498 D01, when the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR to peak location separation ratio. The ratio is determined by  $(SAR1 + SAR2)^{1.5}/R_i$ , rounded to two decimal digits, and must be  $\leq 0.04$  for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.


**The sum of SAR values for Main Antenna and WLAN 2.4G**

Position	Main Antenna (W/kg)	WLAN 2.4G (W/kg)	Sum (W/kg)	SPLSR	
Rear	GSM850	1.08	0.62	1.70	Yes
	GSM1900	1.13	0.62	1.75	Yes
	WCDMA B4	1.09	0.62	1.71	Yes
	LTE B5	1.01	0.62	1.63	Yes
	LTE B66	1.03	0.62	1.65	Yes


**The sum of SAR values for Main Antenna and WLAN 5G**

Position	Main Antenna (W/kg)	WLAN 5G (W/kg)	Sum (W/kg)	SPLSR	
Rear	GSM850	1.08	0.64	1.72	Yes
	GSM1900	1.13	0.64	1.77	Yes
	WCDMA B4	1.09	0.64	1.73	Yes
	LTE B5	1.01	0.64	1.65	Yes
	LTE B17	0.96	0.64	1.60	Yes
	LTE B66	1.03	0.62	1.67	Yes


Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Pair SAR sum (W/kg)	SPLSR	Simultaneous SAR
				X	Y	Z				
GSM850	Rear	1.08	0	-0.087	-0.022	-0.170	72.6	1.70	0.03	Not required
WLAN 2.4G		0.62	0	-0.090	0.051	-0.171				




Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Pair SAR sum (W/kg)	SPLSR	Simultaneous SAR
				X	Y	Z				
GSM1900	Rear	1.13	0	-0.084	-0.036	-0.172	86.7	1.75	0.03	Not required
WLAN 2.4G		0.62	0	-0.090	0.051	-0.171				



Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Pair SAR sum (W/kg)	SPLSR	Simultaneous SAR
				X	Y	Z				
WCDMA B4	Rear	1.09	0	-0.086	-0.035	-0.172	85.1	1.71	0.03	Not required
WLAN 2.4G		0.62	0	-0.090	0.051	-0.171				




Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Pair SAR sum (W/kg)	SPLSR	Simultaneous SAR
				X	Y	Z				
LTE B5	Rear	1.01	0	-0.093	-0.032	-0.172	82.1	1.63	0.03	Not required
WLAN 2.4G		0.62	0	-0.090	0.051	-0.171				







Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Pair SAR sum (W/kg)	SPLSR	Simultaneous SAR
				X	Y	Z				
LTE B66	Rear	1.03	0	-0.087	-0.041	-0.172	91.6	1.65	0.02	Not required
WLAN 2.4G		0.62	0	-0.090	0.051	-0.171				




Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Pair SAR sum (W/kg)	SPLSR	Simultaneous SAR
				X	Y	Z				
GSM850	Rear	1.08	0	-0.087	-0.022	-0.170	68.5	1.72	0.03	Not required
WLAN 5G		0.64	0	-0.073	0.045	-0.171				




Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Pair SAR sum (W/kg)	SPLSR	Simultaneous SAR
				X	Y	Z				
GSM1900	Rear	1.13	0	-0.084	-0.036	-0.172	81.7	1.77	0.03	Not required
WLAN 5G		0.64	0	-0.073	0.045	-0.171				




Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Pair SAR sum (W/kg)	SPLSR	Simultaneous SAR
				X	Y	Z				
WCDMA B4	Rear	1.09	0	-0.086	-0.035	-0.172	80.5	1.73	0.03	Not required
WLAN 5G		0.64	0	-0.073	0.045	-0.171				




Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Pair SAR sum (W/kg)	SPLSR	Simultaneous SAR
				X	Y	Z				
LTE B5	Rear	1.01	0	-0.093	-0.032	-0.172	79.1	1.65	0.03	Not required
WLAN 5G		0.64	0	-0.073	0.045	-0.171				



Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Pair SAR sum (W/kg)	SPLSR	Simultaneous SAR
				X	Y	Z				
LTE B17	Rear	0.96	0	-0.090	-0.029	-0.172	75.8	1.60	0.03	Not required
WLAN 5G		0.64	0	-0.073	0.045	-0.171				



Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Pair SAR sum (W/kg)	SPLSR	Simultaneous SAR
				X	Y	Z				
LTE B66	Rear	1.03	0	-0.087	-0.041	-0.172	87.1	1.67	0.02	Not required
WLAN 5G		0.64	0	-0.073	0.045	-0.171				



**Table 12.2: The sum of reported SAR values for main antenna and Bluetooth**

/	Position	Main Antenna (W/kg)	Bluetooth (W/kg)	Sum (W/kg)
Highest reported SAR value for Body	Top	1.18	0.37	1.55

Note: the test positions of above tables are for the worse case that has been evaluated.

**Table 12.3: Estimated SAR for Bluetooth**

Position	f (GHz)	Distance (mm)	Upper limit of power *		Estimated <sub>1g</sub> (W/kg)
			dBm	mW	
Body	2.441	5	9.5	8.91	0.37

\* - Maximum possible output power declared by manufacturer

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [ $\sqrt{f(\text{GHz})/x}$ ] W/kg for test separation distances  $\leq 50$  mm;

Where  $x = 7.5$  for 1-g SAR.

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### Conclusion:

According to the above tables, the sum of reported SAR values is 1.59 W/kg. So the simultaneous transmission SAR with volume scans is not required.



### 13. Summary of Test Results

According to the client's decision rule in the test registration form, which is "based on the measurement results as the basis of the conformity statement", the test conclusion of this report meets the limit requirements.

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{\text{Target}} - P_{\text{Measured}})/10}$$

Where  $P_{\text{Target}}$  is the power of manufacturing upper limit;

$P_{\text{Measured}}$  is the measured power in chapter 10.

#### Duty Cycle

Mode	Duty Cycle
GPRS for GSM850/1900	1:4
GPRS for GSM850/1900 (Sensor-on mode)	1:2
WCDMA850/1700/1900	1:1
FDD_LTE Band 2/5/7/17/66	1:1

#### 13.1. Testing Environment

Temperature:	18°C~25°C
Relative humidity:	30%~70%
Ground system resistance:	<4Ω
Ambient noise & Reflection:	< 0.012 W/kg

## 13.2. SAR results

**Table 13.1: SAR Values (GSM 850 - Body)**

Frequency		Test Mode	Test Position	Figure No. / Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift(dB)
MHz	Ch.								
Ambient Temperature: 22.5°C      Liquid Temperature: 22.0°C									
<b>0mm Test Data</b>									
836.6	190	GPRS	Rear	<b>1</b>	22.34	23.0	<b>0.928</b>	<b>1.08</b>	0.08
836.6	190	GPRS	Right	/	22.34	23.0	0.247	0.29	0.19
836.6	190	GPRS	Top	/	22.34	23.0	0.581	0.68	0.01
848.8	251	GPRS	Rear	/	22.00	23.0	0.847	1.07	-0.12
824.2	128	GPRS	Rear	/	22.36	23.0	0.900	1.04	0.06
<b>Sensor off Test Data</b>									
836.6	190	GPRS	Rear	14mm	31.29	32.0	0.371	0.44	0.02
836.6	190	GPRS	Right	6mm	31.29	32.0	0.274	0.32	0.04
836.6	190	GPRS	Top	12mm	31.29	32.0	0.353	0.42	0.12

**Table 13.2: SAR Values (GSM 1900 - Body)**

Frequency		Test Mode	Test Position	Figure No. / Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift(dB)
MHz	Ch.								
Ambient Temperature: 22.8°C      Liquid Temperature: 22.3°C									
<b>0mm Test Data</b>									
1880	661	GPRS	Rear	/	19.41	20.5	0.839	1.08	0.04
1880	661	GPRS	Right	/	19.41	20.5	0.138	0.18	-0.12
1880	661	GPRS	Top	/	19.41	20.5	0.276	0.35	0.03
1909.8	810	GPRS	Rear	<b>2</b>	19.76	20.5	<b>0.950</b>	<b>1.13</b>	0.01
1850.2	512	GPRS	Rear	/	19.09	20.5	0.654	0.90	0.07
1880	661	GPRS	Rear	14mm	29.18	30.0	0.326	0.39	0.05
1880	661	GPRS	Right	6mm	29.18	30.0	0.312	0.38	0.04
1880	661	GPRS	Top	12mm	29.18	30.0	0.250	0.30	0.03

**Table 13.3: SAR Values (WCDMA Band 2 - Body)**

Frequency		Test Mode	Test Position	Figure No. / Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift(dB)
MHz	Ch.								
Ambient Temperature: 22.8°C					Liquid Temperature: 22.3°C				
<b>0mm Test Data</b>									
1880	9400	RMC	Rear	/	16.40	17.0	0.736	0.85	0.09
1880	9400	RMC	Right	/	16.40	17.0	0.144	0.17	0.05
1880	9400	RMC	Top	/	16.40	17.0	0.367	0.42	0.19
1907.6	9538	RMC	Rear	/	16.50	17.0	0.740	0.83	0.01
1852.4	9262	RMC	Rear	<b>3</b>	16.40	17.0	<b>0.749</b>	<b>0.86</b>	0.03
<b>Sensor off Test Data</b>									
1880	9400	RMC	Rear	14mm	23.90	24.5	0.473	0.54	0.15
1880	9400	RMC	Right	6mm	23.90	24.5	0.460	0.53	0.02
1880	9400	RMC	Top	12mm	23.90	24.5	0.431	0.49	0.04

**Table 13.4: SAR Values ( WCDMA Band 4 - Body)**

Frequency		Test Mode	Test Position	Figure No. / Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift(dB)
MHz	Ch.								
Ambient Temperature: 22.2°C					Liquid Temperature: 21.8°C				
<b>0mm Test Data</b>									
1732.6	1413	RMC	Rear	/	16.20	17.0	0.906	<b>1.09</b>	0.01
1732.6	1413	RMC	Right	/	16.20	17.0	0.143	0.17	0.14
1732.6	1413	RMC	Top	/	16.20	17.0	0.330	0.40	0.18
1752.6	1513	RMC	Rear	/	16.30	17.0	0.877	1.03	0.09
1712.4	1312	RMC	Rear	<b>4</b>	16.30	17.0	<b>0.907</b>	1.07	-0.02
<b>Sensor off Test Data</b>									
1732.6	1413	RMC	Rear	14mm	24.00	24.5	0.456	0.51	0.04
1732.6	1413	RMC	Right	6mm	24.00	24.5	0.342	0.38	0.12
1732.6	1413	RMC	Top	12mm	24.00	24.5	0.458	0.51	-0.01





**Table 13.5: SAR Values (WCDMA Band 5 -Body)**

Frequency		Test Mode	Test Position	Figure No. / Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift(dB)
MHz	Ch.								
Ambient Temperature: 22.5°C      Liquid Temperature: 22.0°C									
<b>0mm Test Data</b>									
836.4	4182	RMC	Rear	/	16.30	17.0	0.792	<b>0.93</b>	0.03
836.4	4182	RMC	Right	/	16.30	17.0	0.185	0.22	-0.02
836.4	4182	RMC	Top	/	16.30	17.0	0.495	0.58	0.13
846.6	4233	RMC	Rear	<b>5</b>	16.40	17.0	<b>0.812</b>	<b>0.93</b>	0.13
824.4	4132	RMC	Rear	/	16.40	17.0	0.781	0.90	0.19
<b>Sensor off Test Data</b>									
836.4	4182	RMC	Rear	14mm	23.90	24.5	0.365	0.42	0.08
836.4	4182	RMC	Right	6mm	23.90	24.5	0.303	0.35	0.02
836.4	4182	RMC	Top	12mm	23.90	24.5	0.445	0.51	0.05



**Table 13.6: SAR Values (LTE Band 2 - Body)**

Ambient Temperature: 22.8°C					Liquid Temperature: 22.3°C				
Frequency		Test Mode	Test Position	Figure No. / Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift(dB)
MHz	Ch.								
<b>0mm Test Data</b>									
1860	18700	1RB_50	Rear	/	16.92	17.5	0.754	0.86	0.05
1860	18700	50RB_0	Rear	/	16.98	17.5	0.773	0.87	0.10
1860	18700	1RB_50	Right	/	16.92	17.5	0.217	0.25	0.06
1860	18700	50RB_0	Right	/	16.98	17.5	0.222	0.25	-0.01
1860	18700	1RB_50	Top	/	16.92	17.5	0.374	0.43	0.09
1860	18700	50RB_0	Top	/	16.98	17.5	0.363	0.41	0.12
1900	19100	1RB_50	Rear	/	16.88	17.5	0.772	0.89	0.08
1880	18900	1RB_50	Rear	/	16.81	17.5	0.785	0.92	0.09
1900	19100	50RB_0	Rear	/	16.96	17.5	0.768	0.87	0.08
1880	18900	50RB_0	Rear	<b>6</b>	16.88	17.5	<b>0.818</b>	<b>0.94</b>	0.09
1900	19100	100RB	Rear	/	16.90	17.5	0.786	0.90	0.01
<b>Sensor off Test Data</b>									
1860	18700	1RB_50	Rear	14mm	23.96	24.5	0.455	0.52	0.05
1900	19100	50RB_0	Rear	14mm	23.02	23.5	0.351	0.39	0.14
1860	18700	1RB_50	Right	6mm	23.96	24.5	0.412	0.47	0.02
1900	19100	50RB_0	Right	6mm	23.02	23.5	0.314	0.35	-0.01
1860	18700	1RB_50	Top	12mm	23.96	24.5	0.412	0.47	0.08
1900	19100	50RB_0	Top	12mm	23.02	23.5	0.354	0.40	0.11



**Table 13.7: SAR Values (LTE Band 5 - Body)**

Frequency		Test Mode	Test Position	Figure No. / Note	Ambient Temperature: 22.5°C		Liquid Temperature: 22.0°C		
MHz	Ch.				Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift(dB)
<b>0mm Test Data</b>									
836.5	20525	1RB_24	Rear	<b>7</b>	16.94	17.5	<b>0.858</b>	0.98	0.07
836.5	20525	25RB_12	Rear	/	16.89	17.5	0.856	0.99	0.15
836.5	20525	1RB_24	Right	/	16.94	17.5	0.197	0.22	0.02
836.5	20525	25RB_12	Right	/	16.89	17.5	0.196	0.23	0.06
836.5	20525	1RB_24	Top	/	16.94	17.5	0.453	0.52	0.09
836.5	20525	25RB_12	Top	/	16.89	17.5	0.447	0.51	0.09
844	20600	1RB_24	Rear	/	16.76	17.5	0.852	<b>1.01</b>	0.02
829	20450	1RB_24	Rear	/	16.84	17.5	0.838	0.98	0.02
844	20600	25RB_12	Rear	/	16.87	17.5	0.854	0.99	0.10
829	20450	25RB_12	Rear	/	16.86	17.5	0.841	0.97	0.06
836.5	20525	50RB	Rear	/	16.87	17.5	0.836	0.97	-0.01
<b>Sensor off Test Data</b>									
836.5	20525	1RB_24	Rear	14mm	23.41	24.5	0.373	0.48	0.04
836.5	20525	25RB_12	Rear	14mm	22.44	23.5	0.281	0.36	0.06
836.5	20525	1RB_24	Right	6mm	23.41	24.5	0.262	0.34	-0.01
836.5	20525	25RB_12	Right	6mm	22.44	23.5	0.213	0.27	0.02
836.5	20525	1RB_24	Top	12mm	23.41	24.5	0.460	0.59	0.06
836.5	20525	25RB_12	Top	12mm	22.44	23.5	0.320	0.41	0.05



**Table 13.8: SAR Values (LTE Band 7 - Body)**

Ambient Temperature: 22.3°C					Liquid Temperature: 21.8°C				
Frequency		Test Mode	Test Position	Figure No. / Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift(dB)
MHz	Ch.								
<b>0mm Test Data</b>									
2560	21350	1RB_50	Rear	/	12.52	13.0	0.290	0.32	0.02
2560	21350	50RB_25	Rear	/	12.56	13.0	0.286	0.32	0.08
2560	21350	1RB_50	Right	/	12.52	13.0	0.126	0.14	0.03
2560	21350	50RB_25	Right	/	12.56	13.0	0.129	0.14	0.06
2560	21350	1RB_50	Top	/	12.52	13.0	0.873	0.98	-0.02
2560	21350	50RB_25	Top	/	12.56	13.0	0.866	0.96	0.07
2535	21100	1RB_50	Top	/	12.37	13.0	0.818	0.95	0.12
2510	20850	1RB_50	Top	/	12.50	13.0	0.770	0.86	0.12
2535	21100	50RB_25	Top	/	12.44	13.0	0.834	0.95	0.05
2510	20850	50RB_25	Top	/	12.45	13.0	0.795	0.90	0.05
2560	21350	100RB	Top	/	12.46	13.0	0.851	0.96	0.03
<b>Sensor off Test Data</b>									
2560	21350	1RB_50	Rear	14mm	21.54	22.5	0.449	0.56	0.19
2510	20850	50RB_50	Rear	14mm	20.51	21.5	0.292	0.37	0.03
2560	21350	1RB_50	Right	6mm	21.54	22.5	0.198	0.25	0.09
2510	20850	50RB_50	Right	6mm	20.51	21.5	0.153	0.19	-0.12
2560	21350	1RB_50	Top	8/ 12mm	21.54	22.5	<b>0.949</b>	<b>1.18</b>	0.04
2510	20850	50RB_50	Top	12mm	20.51	21.5	0.604	0.76	0.13
2535	21100	1RB_50	Top	12mm	21.36	22.5	0.848	1.10	-0.06
2510	20850	1RB_50	Top	12mm	21.43	22.5	0.698	0.89	0.05
2510	20850	100RB	Top	12mm	20.45	21.5	0.578	0.74	0.03



**Table 13.9: SAR Values (LTE Band 12 - Body)**

Frequency		Test Mode	Test Position	Figure No. / Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift(dB)
MHz	Ch.								
Ambient Temperature: 22.8°C					Liquid Temperature: 22.4°C				
<b>0mm Test Data</b>									
711	23130	1RB_24	Rear	<b>9</b>	16.18	17.5	<b>0.517</b>	<b>0.70</b>	0.00
711	23130	25RB_0	Rear	/	16.17	17.5	0.500	0.68	0.06
711	23130	1RB_24	Right	/	16.18	17.5	0.092	0.12	0.02
711	23130	25RB_0	Right	/	16.17	17.5	0.092	0.12	0.16
711	23130	1RB_24	Top	/	16.18	17.5	0.247	0.33	0.04
711	23130	25RB_0	Top	/	16.17	17.5	0.288	0.39	0.03
<b>Sensor off Test Data</b>									
711	23130	1RB_24	Rear	14mm	23.10	24.5	0.122	0.17	0.09
711	23130	25RB_0	Rear	14mm	22.16	23.5	0.033	0.05	0.18
711	23130	1RB_24	Right	6mm	23.10	24.5	0.026	0.03	-0.03
711	23130	25RB_0	Right	6mm	22.16	23.5	0.336	0.46	0.03
711	23130	1RB_24	Top	12mm	23.10	24.5	0.264	0.36	0.01
711	23130	25RB_0	Top	12mm	22.16	23.5	0.122	0.17	0.09



**Table 13.10: SAR Values (LTE Band 17 - Body)**

Frequency		Test Mode	Test Position	Figure No. / Note	Ambient Temperature: 22.5°C		Liquid Temperature: 22.0°C		
MHz	Ch.				Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift(dB)
<b>0mm Test Data</b>									
710	23790	1RB_24	Rear	<b>9</b>	16.76	17.5	<b>0.807</b>	<b>0.96</b>	0.16
710	23790	25RB_12	Rear	/	16.79	17.5	0.805	0.95	0.18
710	23790	1RB_24	Right	/	16.76	17.5	0.119	0.14	0.17
710	23790	25RB_12	Right	/	16.79	17.5	0.121	0.14	0.02
710	23790	1RB_24	Top	/	16.76	17.5	0.353	0.42	0.06
710	23790	25RB_12	Top	/	16.79	17.5	0.352	0.41	0.04
711	23800	1RB_24	Rear	/	16.75	17.5	0.786	0.93	0.15
709	23780	1RB_24	Rear	/	16.71	17.5	0.781	0.94	0.10
711	23800	25RB_12	Rear	/	16.74	17.5	0.805	<b>0.96</b>	0.11
709	23780	25RB_12	Rear	/	16.77	17.5	0.799	0.95	0.19
710	23790	50RB	Rear	/	16.71	17.5	0.773	0.93	0.03
<b>Sensor off Test Data</b>									
710	23790	1RB_24	Rear	14mm	23.42	24.5	0.224	0.29	0.14
710	23790	25RB_12	Rear	14mm	22.41	23.5	0.193	0.25	0.05
710	23790	1RB_24	Right	6mm	23.42	24.5	0.166	0.21	-0.02
710	23790	25RB_12	Right	6mm	22.41	23.5	0.142	0.18	0.01
710	23790	1RB_24	Top	12mm	23.42	24.5	0.330	0.42	0.08
710	23790	25RB_12	Top	12mm	22.41	23.5	0.266	0.34	0.13



**Table 13.11: SAR Values (LTE Band 66 - Body)**

Frequency		Test Mode	Test Position	Figure No. / Note	Ambient Temperature: 22.3°C		Liquid Temperature: 21.8°C		
MHz	Ch.				Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift(dB)
<b>0mm Test Data</b>									
1745	132322	1RB_50	Rear	/	16.45	17.0	0.866	0.98	0.05
1745	132322	50RB_0	Rear	<b>10</b>	16.44	17.0	<b>0.905</b>	<b>1.03</b>	0.08
1745	132322	1RB_50	Right	/	16.45	17.0	0.171	0.19	0.04
1745	132322	50RB_0	Right	/	16.44	17.0	0.175	0.20	0.11
1745	132322	1RB_50	Top	/	16.45	17.0	0.418	0.47	-0.09
1745	132322	50RB_0	Top	/	16.44	17.0	0.418	0.48	-0.08
1770	132572	1RB_50	Rear	/	16.43	17.0	0.840	0.96	0.08
1720	132072	1RB_50	Rear	/	16.36	17.0	0.892	<b>1.03</b>	0.19
1770	132572	50RB_0	Rear	/	16.42	17.0	0.836	0.96	0.08
1720	132072	50RB_25	Rear	/	16.36	17.0	0.882	1.02	0.05
1745	132322	100RB	Rear	/	16.37	17.0	0.884	1.02	0.02
<b>Sensor off Test Data</b>									
1745	132322	1RB_50	Rear	14mm	23.47	24.5	0.432	0.55	0.04
1745	132322	50RB_25	Rear	14mm	22.48	23.5	0.354	0.45	0.07
1745	132322	1RB_50	Right	6mm	23.47	24.5	0.318	0.40	0.04
1745	132322	50RB_25	Right	6mm	22.48	23.5	0.295	0.37	0.04
1745	132322	1RB_50	Top	12mm	23.47	24.5	0.394	0.50	0.08
1745	132322	50RB_25	Top	12mm	22.48	23.5	0.290	0.37	0.08

**Note:** SAR for LTE Band 4 is covered by LTE Band 66 due to similar frequency range, same maximum tune-up limit and same channel bandwidth.

### 13.3. WLAN Evaluation for 2.4G

According to the KDB248227 D01, SAR is measured for 2.4GHz 802.11b DSSS using the initial test position procedure.

**Table 13.12: SAR Values (WLAN 2.4G - Body)**

Frequency		Test Mode	Test Position	Figure No. / Note	Ambient Temperature: 22.4°C		Liquid Temperature: 21.9°C		Power Drift(dB)
MHz	Ch.				Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	
<b>0mm Test Data</b>									
2437	6	802.11b	Rear	<b>11</b>	11.56	12.0	<b>0.564</b>	<b>0.62</b>	0.04
2437	6	802.11b	Left	/	11.56	12.0	0.120	0.13	-0.09
2437	6	802.11b	Top	/	11.56	12.0	0.284	0.31	0.02

Note1: For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

**Table 13.13: SAR Values (WLAN - Body) – 802.11b (Scaled Reported SAR)**

Frequency		Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g)(W/kg)	Scaled reported SAR (1g)(W/kg)
MHz	Ch.					
2437	6	Rear	100%	100%	0.62	<b>0.62</b>

SAR is not required for OFDM because the 802.11b adjusted SAR ≤ 1.2 W/kg.



### 13.4. WLAN Evaluation for 5G

**Table 13.14: SAR Values (WLAN 5G - Body)**

Frequency		Test Mode	Test Position	Figure No.	Ambient Temperature: 22.5°C		Liquid Temperature: 22.0°C		Power Drift(dB)
MHz	Ch.				Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	
<b>U-NII-2A - 0mm Test Data</b>									
5320	64	802.11a	Rear	/	9.17	10.0	<b>0.472</b>	0.57	0.03
5320	64	802.11a	Left	/	9.17	10.0	0.235	0.28	-0.09
5320	64	802.11a	Top	/	9.17	10.0	0.340	0.41	-0.19
<b>U-NII-3 - 0mm Test Data</b>									
5825	165	802.11a	Rear	<b>12</b>	7.71	8.5	<b>0.533</b>	<b>0.64</b>	0.01
5825	165	802.11a	Left	/	7.71	8.5	0.301	0.36	0.03
5825	165	802.11a	Top	/	7.71	8.5	0.176	0.21	0.07

**Note1:** U-NII-1 and U-NII-2A bands have the same specified maximum output and tolerance; SAR is measured for U-NII-2A band first. Adjusted SAR of U-NII-2A band is  $\leq 1.2$ W/kg, SAR is not required for U-NII-1 band.

**Note2:** For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is  $> 0.8$  W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel until the reported SAR is  $\leq 1.2$  W/kg or all required channels are tested.

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

**Table 13.15: SAR Values (WLAN - Body) – 802.11a (Scaled Reported SAR)**

Frequency		Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g)(W/kg)	Scaled reported SAR (1g)(W/kg)
MHz	Ch.					
5320	64	Rear	100%	100%	0.64	<b>0.64</b>

## 14. SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.

The following procedures are applied to determine if repeated measurements are required.

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

**Table 14.1: SAR Measurement Variability for Body – GSM850**

Frequency		Test Position	Original	1 <sup>st</sup> Repeated	Ratio	2 <sup>nd</sup> Repeated
MHz	Ch.		SAR (W/kg)	SAR (W/kg)		SAR (W/kg)
836.6	190	Rear	0.928	0.922	1.01	/

**Table 14.2: SAR Measurement Variability for Body – GSM1900**

Frequency		Test Position	Original	1 <sup>st</sup> Repeated	Ratio	2 <sup>nd</sup> Repeated
MHz	Ch.		SAR (W/kg)	SAR (W/kg)		SAR (W/kg)
1909.8	810	Rear	0.950	0.934	1.02	/

**Table 14.3: SAR Measurement Variability for Body – WCDMA Band 4**

Frequency		Test Position	Original	1 <sup>st</sup> Repeated	Ratio	2 <sup>nd</sup> Repeated
MHz	Ch.		SAR (W/kg)	SAR (W/kg)		SAR (W/kg)
1712.4	1312	Rear	0.907	0.886	1.02	/

**Table 14.4: SAR Measurement Variability for Body – WCDMA Band 5**

Frequency		Test Position	Original	1 <sup>st</sup> Repeated	Ratio	2 <sup>nd</sup> Repeated
MHz	Ch.		SAR (W/kg)	SAR (W/kg)		SAR (W/kg)
846.6	4233	Rear	0.812	0.795	1.02	/

**Table 14.5: SAR Measurement Variability for Body – LTE Band 2**

Frequency		Test Position	Original	1 <sup>st</sup> Repeated	Ratio	2 <sup>nd</sup> Repeated
MHz	Ch.		SAR (W/kg)	SAR (W/kg)		SAR (W/kg)
1880	18900	Rear	0.818	0.784	1.04	/

**Table 14.6: SAR Measurement Variability for Body – LTE Band 5**

Frequency		Test Position	Original	1 <sup>st</sup> Repeated	Ratio	2 <sup>nd</sup> Repeated
MHz	Ch.		SAR (W/kg)	SAR (W/kg)		SAR (W/kg)
836.5	20525	Rear	0.858	0.833	1.03	/

**Table 14.7: SAR Measurement Variability for Body – LTE Band 7**

Frequency		Test Position	Original	1 <sup>st</sup> Repeated	Ratio	2 <sup>nd</sup> Repeated
MHz	Ch.		SAR (W/kg)	SAR (W/kg)		SAR (W/kg)
2560	21350	Rear	0.858	0.833	1.03	/

**Table 14.8: SAR Measurement Variability for Body – LTE Band 17**

Frequency		Test Position	Original	1 <sup>st</sup> Repeated	Ratio	2 <sup>nd</sup> Repeated
MHz	Ch.		SAR (W/kg)	SAR (W/kg)		SAR (W/kg)
710	23790	Rear	0.807	0.789	1.02	/

**Table 14.9: SAR Measurement Variability for Body – LTE Band 66**

Frequency		Test Position	Original	1 <sup>st</sup> Repeated	Ratio	2 <sup>nd</sup> Repeated
MHz	Ch.		SAR (W/kg)	SAR (W/kg)		SAR (W/kg)
1745	132322	Rear	0.905	0.888	1.02	/

## 15. Measurement Uncertainty

### 15.1. Measurement Uncertainty for Normal SAR Tests (300MHz~3GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
<b>Measurement system</b>										
1	Probe calibration	B	12	N	2	1	1	6.0	6.0	∞
2	Axial isotropy	B	4.7	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	4.3	4.3	∞
3	Hemispherical isotropy	B	9.6	R	$\sqrt{3}$	1	1	4.8	4.8	∞
4	Boundary effect	B	1.1	R	$\sqrt{3}$	1	1	0.6	0.6	∞
5	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
6	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
7	Modulation response	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
8	Readout electronics	B	1.0	N	1	1	1	1.0	1.0	∞
9	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
10	Integration time	B	1.7	R	$\sqrt{3}$	1	1	1.0	1.0	∞
11	RF ambient conditions-noise	B	3.0	R	$\sqrt{3}$	1	1	1.7	1.7	∞
12	RF ambient conditions-reflection	B	3.0	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Probe positioned mech. restrictions	B	0.35	R	$\sqrt{3}$	1	1	0.2	0.2	∞
14	Probe positioning with respect to phantom shell	B	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
15	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
<b>Test sample related</b>										
16	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	5
17	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
18	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
<b>Phantom and set-up</b>										
19	Phantom uncertainty	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
20	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
21	Liquid conductivity (meas.)	A	1.3	N	1	0.64	0.43	0.83	0.56	9
22	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
23	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	0.96	0.78	9
Combined standard uncertainty		$u_c' = \sqrt{\sum_{i=1}^{23} c_i^2 u_i^2}$						11.3	11.2	95.5
Expanded uncertainty (Confidence interval of 95 %)		$u_e = 2u_c$						22.6	22.4	

**15.2. Measurement Uncertainty for Normal SAR Tests (3GHz~6GHz)**

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
<b>Measurement system</b>										
1	Probe calibration	B	13	N	2	1	1	6.5	6.5	∞
2	Axial isotropy	B	4.7	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	4.3	4.3	∞
3	Hemispherical isotropy	B	9.6	R	$\sqrt{3}$	1	1	4.8	4.8	∞
4	Boundary effect	B	2.3	R	$\sqrt{3}$	1	1	1.3	1.3	∞
5	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
6	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
7	Modulation response	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
8	Readout electronics	B	1.0	N	1	1	1	1.0	1.0	∞
9	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
10	Integration time	B	1.7	R	$\sqrt{3}$	1	1	1.0	1.0	∞
11	RF ambient conditions-noise	B	3.0	R	$\sqrt{3}$	1	1	1.7	1.7	∞
12	RF ambient conditions-reflection	B	3.0	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Probe positioned mech. restrictions	B	0.71	R	$\sqrt{3}$	1	1	0.4	0.4	∞
14	Probe positioning with respect to phantom shell	B	5.7	R	$\sqrt{3}$	1	1	3.3	3.3	∞
15	Post-processing	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
<b>Test sample related</b>										
16	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	5
17	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
18	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
<b>Phantom and set-up</b>										
19	Phantom uncertainty	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
20	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
21	Liquid conductivity (meas.)	A	1.3	N	1	0.64	0.43	0.83	0.56	9
22	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
23	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	0.96	0.78	9
Combined standard uncertainty		$u_c = \sqrt{\sum_{i=1}^{23} c_i^2 u_i^2}$						12.2	12.1	95.5
Expanded uncertainty (Confidence interval of 95 %)		$u_e = 2u_c$						24.4	24.2	

## 16. Main Test Instruments

**Table 16.1: List of Main Instruments**

No.	Name	Type	Serial Number	Calibration Date	Valid Period
01	Network analyzer	Agilent E5071C	MY46103759	2019-11-15	One year
02	Dielectric probe	85070E	MY44300317	/	/
03	Power meter	E4418B	MY50000366	2019-12-14	One year
04	Power sensor	E9304A	MY50000188		
05	Power meter	NRP	101460	2020-01-15	One year
06	Power sensor	NRP-Z91	100553		
07	Signal Generator	E8257D	MY47461211	2020-01-15	One year
08	Amplifier	VTL5400	0404	/	/
09	E-field Probe	EX3DV4	3633	2020-04-01	One year
11	DAE	DAE4	786	2020-03-03	One year
12	Dipole Validation Kit	D750V3	1163	2019-09-03	One year
13	Dipole Validation Kit	D835V2	4d057	2018-10-09	Three year
14	Dipole Validation Kit	D1750V2	1152	2019-08-30	One year
15	Dipole Validation Kit	D1900V2	5d088	2018-10-24	Three year
16	Dipole Validation Kit	D2450V2	873	2018-10-26	Three year
17	Dipole Validation Kit	D2550V2	1058	2018-08-24	Three year
18	Dipole Validation Kit	D5GHzV2	1238	2019-08-29	One year
19	Radio Communication Analyzer	Anristu MT8820C	6201341853	2020-01-15	One year
20	BTS	E5515C	GB46110722	2020-01-05	One year
21	Software	DASY5	52.8.8.1222	/	/

## ANNEX A: Graph Results

### GSM850 Body

Date: 2020-6-9

Electronics: DAE4 Sn786

Medium: Head 835MHz

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.885$  S/m;  $\epsilon_r = 41.807$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, GPRS 4Txslot (0) Frequency: 836.6 MHz Duty Cycle: 1:2

Probe: EX3DV4 – SN3633 ConvF (9.59, 9.59, 9.59);

**Rear Side Middle/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 1.51 W/kg

**Rear Side Middle/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 2.795 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 2.34 W/kg

**SAR(1 g) = 0.928 W/kg; SAR(10 g) = 0.369 W/kg**

Maximum value of SAR (measured) = 1.28 W/kg




Fig.1 GSM 850 Body

**GSM1900 Body**

Date: 2020-6-15

Electronics: DAE4 Sn786

Medium: Head 1900MHz

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.386$  S/m;  $\epsilon_r = 39.143$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, GPRS 4Txslot (0) Frequency: 1909.8 MHz Duty Cycle: 1:2

Probe: EX3DV4 – SN3633 ConvF (7.76, 7.76, 7.76);

**Rear Side High/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.64 W/kg

**Rear Side High/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.540 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.83 W/kg

**SAR(1 g) = 0.950 W/kg; SAR(10 g) = 0.524 W/kg**

Maximum value of SAR (measured) = 1.25 W/kg




Fig.2 GSM 1900 Body



**WCDMA Band 2 Body**

Date: 2020-6-15

Electronics: DAE4 Sn786

Medium: Head 1900MHz

Medium parameters used (interpolated):  $f = 1852.4$  MHz;  $\sigma = 1.336$  S/m;  $\epsilon_r = 39.368$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, WCDMA (0) Frequency: 1850.2 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (7.76, 7.76, 7.76);

**Rear Side Low/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 1.26 W/kg


**Rear Side Low/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 1.282 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.40 W/kg

**SAR(1 g) = 0.749 W/kg; SAR(10 g) = 0.415 W/kg**

Maximum value of SAR (measured) = 0.959 W/kg

**Fig.3 WCDMA Band 2 Body**

**WCDMA Band 4 Body**

Date: 2020-6-13

Electronics: DAE4 Sn786

Medium: Head 1750MHz

Medium parameters used (interpolated):  $f = 1712.4$  MHz;  $\sigma = 1.352$  S/m;  $\epsilon_r = 39.597$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, WCDMA (0) Frequency: 1712.4 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (8.09, 8.09, 8.09);

**Rear Side Low/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 1.45 W/kg

**Rear Side Low/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 2.487 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.59 W/kg

**SAR(1 g) = 0.907 W/kg; SAR(10 g) = 0.492 W/kg**

Maximum value of SAR (measured) = 1.21 W/kg




Fig.4 WCDMA Band 4 Body

**WCDMA Band 5 Body**

Date: 2020-6-9

Electronics: DAE4 Sn786

Medium: Head 835MHz

Medium parameters used (interpolated):  $f = 846.6$  MHz;  $\sigma = 0.895$  S/m;  $\epsilon_r = 41.687$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, WCDMA (0) Frequency: 846.6 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (9.59, 9.59, 9.59);

**Rear Side High/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 1.07 W/kg


**Rear Side High/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 4.098 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 2.09 W/kg

**SAR(1 g) = 0.812 W/kg; SAR(10 g) = 0.405 W/kg**

Maximum value of SAR (measured) = 1.48 W/kg



**Fig.5 WCDMA Band 5 Body**

**LTE Band 2 Body**

Date: 2020-6-15

Electronics: DAE4 Sn786

Medium: Head 1900MHz

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.359$  S/m;  $\epsilon_r = 39.26$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, LTE\_FDD (0) Frequency: 1880 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (7.76, 7.76, 7.76);

**Rear Side Middle 50RB\_0/Area Scan (51x51x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.17 W/kg

**Rear Side Middle 50RB\_0/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.726 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.53 W/kg

**SAR(1 g) = 0.818 W/kg; SAR(10 g) = 0.439 W/kg**

Maximum value of SAR (measured) = 1.06 W/kg




Fig.6 LTE Band 2 Body

**LTE Band 5 Body**

Date: 2020-6-9

Electronics: DAE4 Sn786

Medium: Head 1750MHz

Medium parameters used (interpolated):  $f = 836.5$  MHz;  $\sigma = 0.885$  S/m;  $\epsilon_r = 41.808$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, LTE\_FDD (0) Frequency: 836.5 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (9.59, 9.59, 9.59);

**Rear Side Middle 1RB\_24/Area Scan (51x51x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.983 W/kg


**Rear Side Middle 1RB\_24/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.139 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 2.24 W/kg

**SAR(1 g) = 0.858 W/kg; SAR(10 g) = 0.420 W/kg**

Maximum value of SAR (measured) = 1.32 W/kg

**Fig.7 LTE Band 5 Body**

**LTE Band 7 Body**

Date: 2020-6-30

Electronics: DAE4 Sn786

Medium: Head 2550MHz

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 1.961$  S/m;  $\epsilon_r = 37.804$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, LTE\_FDD (0) Frequency: 2560 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (7.20, 7.20, 7.20);

**Top Side High 1RB\_50/Area Scan (81x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.45 W/kg


**Top Side High 1RB\_50/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.936 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.79 W/kg

**SAR(1 g) = 0.949 W/kg; SAR(10 g) = 0.478 W/kg**

Maximum value of SAR (measured) = 1.37 W/kg

**Fig.8 LTE Band 7 Body**

**LTE Band 12 Body**

Date: 2020-7-18

Electronics: DAE4 Sn786

Medium: Head 750MHz

Medium parameters used:  $f = 711$  MHz;  $\sigma = 0.888$  S/m;  $\epsilon_r = 40.914$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, LTE\_FDD (0) Frequency: 711 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (9.59, 9.59, 9.59);

**Rear Side High 1RB\_24/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.942 W/kg


**Rear Side High 1RB\_24/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.762 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.56 W/kg

**SAR(1 g) = 0.517 W/kg; SAR(10 g) = 0.238 W/kg**

Maximum value of SAR (measured) = 0.935 W/kg

**Fig.9 LTE Band 12 Body**

**LTE Band 17 Body**

Date: 2020-6-8

Electronics: DAE4 Sn786

Medium: Head 750MHz

Medium parameters used:  $f = 710$  MHz;  $\sigma = 0.877$  S/m;  $\epsilon_r = 41.474$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, LTE\_FDD (0) Frequency: 710 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (9.59, 9.59, 9.59);

**Rear Side Middle 1RB\_24/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.50 W/kg


**Rear Side Middle 1RB\_24/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.662 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 2.34 W/kg

**SAR(1 g) = 0.807 W/kg; SAR(10 g) = 0.372 W/kg**

Maximum value of SAR (measured) = 1.46 W/kg

**Fig.1 LTE Band 17 Body**



**LTE Band 66 Body**

Date: 2020-6-13

Electronics: DAE4 Sn786

Medium: Head 1750MHz

Medium parameters used:  $f = 1745$  MHz;  $\sigma = 1.381$  S/m;  $\epsilon_r = 39.47$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, WCDMA (0) Frequency: 1745 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (8.09, 8.09, 8.09);

**Rear Side Middle 50RB\_0/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.25 W/kg


**Rear Side Middle 50RB\_0/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.138 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.58 W/kg

**SAR(1 g) = 0.905 W/kg; SAR(10 g) = 0.492 W/kg**

Maximum value of SAR (measured) = 1.16 W/kg

**Fig.2 LTE Band 66 Body**

**WLAN 2.4G Body**

Date: 2020-6-29

Electronics: DAE4 Sn786

Medium: Head 2450MHz

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.823$  S/m;  $\epsilon_r = 38.621$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, WiFi (0) Frequency: 2437 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN3633 ConvF (7.43, 7.43, 7.43)

**Rear Side Middle/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.934 W/kg


**Rear Side Middle /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.112 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.49 W/kg

**SAR(1 g) = 0.564 W/kg; SAR(10 g) = 0.257 W/kg**

Maximum value of SAR (measured) = 0.969 W/kg

**Fig.3 WLAN 2.4G Body**

**WLAN 5G Body**

Date: 2020-6-29

Electronics: DAE4 Sn786

Medium: Head 5750MHz

Medium parameters used (interpolated):  $f = 5825$  MHz;  $\sigma = 5.249$  S/m;  $\epsilon_r = 35.653$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: UID 0, WiFi (0) Frequency: 5825 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (4.73, 4.73, 4.73);

**Rear Side CH165/Area Scan (71x71x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.827 W/kg

**Rear Side CH165/Zoom Scan (8x8x21)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 1.786 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.91 W/kg

**SAR(1 g) = 0.533 W/kg; SAR(10 g) = 0.140 W/kg**

Maximum value of SAR (measured) = 1.19 W/kg




Fig.4 WLAN 5G Body

## ANNEX B: System Verification Results

### 750MHz

Date: 2020-6-8

Electronics: DAE4 Sn786

Medium: Head 750MHz

Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.903 \text{ S/m}$ ;  $\epsilon_r = 40.994$ ;  $\rho = 1000 \text{ kg/m}^3$

Communication System: CW\_TMC Frequency: 750 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (9.59, 9.59, 9.59);

**System Validation /Area Scan (81x161x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$

Reference Value = 59.815 V/m; Power Drift = 0.10 dB

**SAR(1 g) = 2.19 W/kg; SAR(10 g) = 1.45 W/kg**

Maximum value of SAR (interpolated) = 2.55 W/kg


**System Validation /Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 59.815 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 2.92 W/kg

**SAR(1 g) = 2.23 W/kg; SAR(10 g) = 1.47 W/kg**

Maximum value of SAR (measured) = 2.58 W/kg



0 dB = 2.58 W/kg = 4.12 dB W/kg

Fig.B.1. Validation 750MHz 250mW

**750MHz**

Date: 2020-7-18

Electronics: DAE4 Sn786

Medium: Head 750MHz

Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.913 \text{ S/m}$ ;  $\epsilon_r = 40.446$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Communication System: CW\_TMC Frequency: 750 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (9.59, 9.59, 9.59);

**System Validation /Area Scan (81x161x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$ 

Reference Value = 60.422 V/m; Power Drift = -0.03 dB

**SAR(1 g) = 2.24 W/kg; SAR(10 g) = 1.48 W/kg**

Maximum value of SAR (interpolated) = 2.64 W/kg


**System Validation /Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ 

Reference Value = 60.422 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 3.13 W/kg

**SAR(1 g) = 2.21 W/kg; SAR(10 g) = 1.45 W/kg**

Maximum value of SAR (measured) = 2.60 W/kg



0 dB = 2.60 W/kg = 4.15 dB W/kg

**Fig.B.2. Validation 750MHz 250mW**

**835MHz**

Date: 2020-6-9

Electronics: DAE4 Sn786

Medium: Head 835MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.884 \text{ S/m}$ ;  $\epsilon_r = 41.826$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Communication System: CW Frequency: 835 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (9.59, 9.59, 9.59);

**System Validation /Area Scan (91x161x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$ 

Reference Value = 60.123 V/m; Power Drift = -0.06 dB

**SAR(1 g) = 2.37 W/kg; SAR(10 g) = 1.59 W/kg**

Maximum value of SAR (interpolated) = 3.22 W/kg


**System Validation /Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ 

Reference Value = 60.123 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 3.64 W/kg

**SAR(1 g) = 2.31 W/kg; SAR(10 g) = 1.55 W/kg**

Maximum value of SAR (measured) = 3.18 W/kg



0 dB = 3.18 W/kg = 5.02 dB W/kg

**Fig.B.3. Validation 835MHz 250mW**

**1750MHz**

Date: 2020-6-13

Electronics: DAE4 Sn786

Medium: Head 1750MHz

Medium parameters used:  $f = 1750 \text{ MHz}$ ;  $\sigma = 1.385 \text{ S/m}$ ;  $\epsilon_r = 39.45$ ;  $\rho = 1000 \text{ kg/m}^3$

Communication System: CW\_TMC Frequency: 1750 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (8.09, 8.09, 8.09);

**System Validation/Area Scan (81x121x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$

Reference Value = 78.726 V/m; Power Drift = 0.09 dB

**SAR(1 g) = 9.33 W/kg; SAR(10 g) = 4.85 W/kg**

Maximum value of SAR (interpolated) = 10.4 W/kg


**System Validation/Zoom Scan (7x7x7)/Cube0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 78.726 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 20.1 W/kg

**SAR(1 g) = 9.48 W/kg; SAR(10 g) = 4.94 W/kg**

Maximum value of SAR (measured) = 10.6 W/kg



0 dB = 10.6 W/kg = 10.25 dB W/kg

**Fig.B.4. Validation 1750MHz 250mW**

**1900MHz**

Date: 2020-6-15

Electronics: DAE4 Sn786

Medium: Head 1900MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.377$  S/m;  $\epsilon_r = 39.182$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: CW\_TMC Frequency: 1900 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (7.76, 7.76, 7.76);

**System Validation/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 81.005 V/m; Power Drift = -0.08 dB

**SAR(1 g) = 10.1 W/kg; SAR(10 g) = 5.23 W/kg**

Maximum value of SAR (interpolated) = 11.5 W/kg


**System Validation/Zoom Scan (7x7x7)/Cube0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 81.005 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 21.8 W/kg

**SAR(1 g) = 9.68 W/kg; SAR(10 g) = 5.12 W/kg**

Maximum value of SAR (measured) = 11.2 W/kg



0 dB = 11.2 W/kg = 10.49 dB W/kg

**Fig.B.5. Validation 1900MHz 250mW**



**2450MHz**

Date: 2020-6-29

Electronics: DAE4 Sn786

Medium: Head 2450MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.838$  S/m;  $\epsilon_r = 38.262$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: CW\_TMC Frequency: 2450 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (7.43, 7.43, 7.43);

**System Validation /Area Scan (81x121x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 88.432 V/m; Power Drift = 0.12 dB

**SAR(1 g) = 13.1 W/kg; SAR(10 g) = 6.05 W/kg**

Maximum value of SAR (interpolated) = 14.4 W/kg


**System Validation/Zoom Scan (7x7x7)/Cube0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.432 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 28.6 W/kg

**SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.11 W/kg**

Maximum value of SAR (measured) = 14.7 W/kg



0 dB = 14.7 W/kg = 11.67 dB W/kg

**Fig.B.6. Validation 2450MHz 250mW**

**2550MHz**

Date: 2020-6-30

Electronics: DAE4 Sn786

Medium: Head 2550MHz

Medium parameters used:  $f = 2550 \text{ MHz}$ ;  $\sigma = 1.949 \text{ S/m}$ ;  $\epsilon_r = 37.837$ ;  $\rho = 1000 \text{ kg/m}^3$

Communication System: CW\_TMC Frequency: 2550 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (7.20, 7.20, 7.20);

**System Validation/Area Scan (91x91x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$

Reference Value = 93.048 V/m; Power Drift = 0.02 dB

**SAR(1 g) = 14.8 W/kg; SAR(10 g) = 6.68 W/kg**

Maximum value of SAR (interpolated) = 16.5 W/kg


**System Validation/Zoom Scan (7x7x7)/Cube0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 93.048 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 34.1 W/kg

**SAR(1 g) = 15.0 W/kg; SAR(10 g) = 6.82 W/kg**

Maximum value of SAR (measured) = 16.9 W/kg



0 dB = 16.9 W/kg = 12.28 dB W/kg

**Fig.B.7. Validation 2550MHz 250mW**

**5250MHz**

Date: 2020-6-29

Electronics: DAE4 Sn786

Medium: Head 5250MHz

Medium parameters used:  $f = 5250$  MHz;  $\sigma = 4.626$  S/m;  $\epsilon_r = 36.951$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: CW Frequency: 5250 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (5.47, 5.47, 5.47);

**System Validation/Area Scan (61x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 61.456 V/m; Power Drift = -0.05 dB

**SAR(1 g) = 7.66 W/kg; SAR(10 g) = 2.20 W/kg**

Maximum value of SAR (interpolated) = 9.42 W/kg


**System Validation/Zoom Scan (8x8x21)/Cube0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 61.456 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 23.9 W/kg

**SAR(1 g) = 7.48 W/kg; SAR(10 g) = 2.16 W/kg**

Maximum value of SAR (measured) = 9.36 W/kg



0 dB = 9.36 W/kg = 9.71 dB W/kg

**Fig.B.8. Validation 5250MHz 100mW**

**5750MHz**

Date: 2020-6-29

Electronics: DAE4 Sn786

Medium: Head 5750 MHz

Medium parameters used:  $f = 5750$  MHz;  $\sigma = 5.148$  S/m;  $\epsilon_r = 35.855$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Communication System: CW Frequency: 5750 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3633 ConvF (4.73, 4.73, 4.73);

**System Validation/Area Scan (61x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 61.875 V/m; Power Drift = -0.11 dB

**SAR(1 g) = 7.75 W/kg; SAR(10 g) = 2.23 W/kg**

Maximum value of SAR (interpolated) = 9.59 W/kg


**System Validation/Zoom Scan (8x8x21)/Cube0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 61.875 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 24.5 W/kg

**SAR(1 g) = 7.57 W/kg; SAR(10 g) = 2.19 W/kg**

Maximum value of SAR (measured) = 9.52 W/kg




0 dB = 9.52 W/kg = 9.79 dB W/kg

**Fig.B.9. Validation 5750MHz 100mW**

## ANNEX C: SAR Measurement Setup

### C.1. Measurement Set-up

DASY5 system for performing compliance tests is illustrated above graphically. This system consists of the following items:



**Picture C.1 SAR Lab Test Measurement Set-up**

- A standard high precision 6-axis robot (Stäubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as
- warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

## C.2. DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY5 software reads the reflection during a software approach and looks for the maximum using 2<sup>nd</sup> order curve fitting. The approach is stopped at reaching the maximum.

### Probe Specifications:

<b>Model:</b>	<b>ES3DV3, EX3DV4</b>
<b>Frequency</b>	<b>10MHz — 6.0GHz(EX3DV4)</b>
<b>Range:</b>	<b>10MHz — 4GHz(ES3DV3)</b>
<b>Calibration:</b>	<b>In head and body simulating tissue at Frequencies from 835 up to 5800MHz</b>
<b>Linearity:</b>	<b>± 0.2 dB(30 MHz to 6 GHz) for EX3DV4 ± 0.2 dB(30 MHz to 4 GHz) for ES3DV3</b>
<b>Dynamic Range:</b>	<b>10 mW/kg — 100W/kg</b>
<b>Probe Length:</b>	<b>330 mm</b>
<b>Probe Tip</b>	
<b>Length:</b>	<b>20 mm</b>
<b>Body Diameter:</b>	<b>12 mm</b>
<b>Tip Diameter:</b>	<b>2.5 mm (3.9 mm for ES3DV3)</b>
<b>Tip-Center:</b>	<b>1 mm (2.0mm for ES3DV3)</b>
<b>Application:</b>	<b>SAR Dosimetry Testing Compliance tests of mobile phones Dosimetry in strong gradient fields</b>



Picture C.2 Near-field Probe



Picture C.3 E-field Probe

## C.3. E-field Probe Calibration

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density ( $1 \text{ mW/cm}^2$ ) using an RF Signal generator, TEM cell, and RF Power Meter.

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or

other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/ cm<sup>2</sup>:

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

Where:

$\Delta t$  = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

$\Delta T$  = Temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

$\sigma$  = Simulated tissue conductivity,

$\rho$  = Tissue density (kg/m<sup>3</sup>).

## C.4. Other Test Equipment

### C.4.1. Data Acquisition Electronics (DAE)

The data acquisition electronics consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



PictureC.4: DAE

#### C.4.2. Robot

The SPEAG DASY system uses the high precision robots (DASY5: RX160L) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchron motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)



Picture C.5 DASY 5

#### C.4.3. Measurement Server

The Measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chipdisk (DASY5:128MB), RAM (DASY5:128MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.



Picture C.6 Server for DASY 5



#### C.4.4. Device Holder for Phantom

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5mm distance, a positioning uncertainty of  $\pm 0.5\text{mm}$  would produce a SAR uncertainty of  $\pm 20\%$ . Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric


parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

<Laptop Extension Kit>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin-SAM and ELI phantoms.



Picture C.7-1: Device Holder



Picture C.7-2: Laptop Extension Kit

#### C.4.5. Phantom

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a table. The shape of the shell is based on data from an anatomical study designed to

Represent the 90<sup>th</sup> percentile of the population. The phantom enables the dissymmetric evaluation of SAR for both left and right handed handset usage, as well as body-worn usage using the flat phantom region. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. The shell phantom has a 2mm shell thickness (except the ear region where shell thickness increases to 6 mm).



Shell Thickness:  $2 \pm 0.2$  mm  
Filling Volume: Approx. 25 liters  
Dimensions: 810 x 1000 x 500 mm (H x L x W)  
Available: Special




**Picture C.8: SAM Twin Phantom**

## ANNEX D: Position of the wireless device in relation to the phantom


### D.1. General considerations

This standard specifies two handset test positions against the head phantom – the “cheek” position and the “tilt” position.




- $w_t$  Width of the handset at the level of the acoustic
- $w_b$  Width of the bottom of the handset
- A Midpoint of the width  $w_t$  of the handset at the level of the acoustic output
- B Midpoint of the width  $w_b$  of the bottom of the handset

Picture D.1-a Typical “fixed” case handset      Picture D.1-b Typical “clam-shell” case handset




Picture D.2 Cheek position of the wireless device on the left side of SAM



Picture D.3 Tilt position of the wireless device on the left side of SAM

## D.2. Body-worn device

A typical example of a body-worn device is a mobile phone, wireless enabled PDA or other battery operated wireless device with the ability to transmit while mounted on a person's body using a carry accessory approved by the wireless device manufacturer.




Picture D.4 Test positions for body-worn devices

## D.3. Desktop device

A typical example of a desktop device is a wireless enabled desktop computer placed on a table or desk when used.

The DUT shall be positioned at the distance and in the orientation to the phantom that corresponds to the intended use as specified by the manufacturer in the user instructions. For devices that employ an external antenna with variable positions, tests shall be performed for all antenna positions specified. Picture 8.5 show positions for desktop device SAR tests. If the intended use is not specified, the device shall be tested directly against the flat phantom.



Picture D.5 Test positions for desktop devices

#### D.4. DUT Setup Photos



Picture D.6

## ANNEX E: Equivalent Media Recipes

The liquid used for the frequency range of 700-6000 MHz consisted of water, sugar, salt, preventol, glycol monobutyl and Cellulose. The liquid has been previously proven to be suited for worst-case. The Table E.1 shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528 and IEC 62209.

**Table E.1: Composition of the Tissue Equivalent Matter**

Frequency (MHz)	835 Head	835 Body	1900 Head	1900 Body	2450 Head	2450 Body	5800 Head	5800 Body
Ingredients (% by weight)								
Water	41.45	52.5	55.242	69.91	58.79	72.60	65.53	65.53
Sugar	56.0	45.0	\	\	\	\	\	\
Salt	1.45	1.4	0.306	0.13	0.06	0.18	\	\
Preventol	0.1	0.1	\	\	\	\	\	\
Cellulose	1.0	1.0	\	\	\	\	\	\
Glycol Monobutyl	\	\	44.452	29.96	41.15	27.22	\	\
Diethylenglycol monoheylether	\	\	\	\	\	\	17.24	17.24
Triton X-100	\	\	\	\	\	\	17.24	17.24
Dielectric Parameters Target Value	$\epsilon=41.5$ $\sigma=0.90$	$\epsilon=55.2$ $\sigma=0.97$	$\epsilon=40.0$ $\sigma=1.40$	$\epsilon=53.3$ $\sigma=1.52$	$\epsilon=39.2$ $\sigma=1.80$	$\epsilon=52.7$ $\sigma=1.95$	$\epsilon=35.3$ $\sigma=5.27$	$\epsilon=48.2$ $\sigma=6.00$

**Note: There is a little adjustment respectively for 750, 1800, 2600, 5200, 5300, and 5600, based on the recipe of closest frequency in table E.1**



## ANNEX F: System Validation

The SAR system must be validated against its performance specifications before it is deployed. When SAR probes, system components or software are changed, upgraded or recalibrated, these must be validated with the SAR system(s) that operates with such components.

**Table F.1: System Validation**

Probe SN.	Liquid name	Validation date	Frequency point	Status (OK or Not)
3633	Head 750MHz	2020-04-03	750 MHz	OK
3633	Head 900MHz	2020-04-03	900 MHz	OK
3633	Head 1750MHz	2020-04-03	1750 MHz	OK
3633	Head 1900MHz	2020-04-03	1900 MHz	OK
3633	Head 2300MHz	2020-04-04	2300 MHz	OK
3633	Head 2450MHz	2020-04-04	2450 MHz	OK
3633	Head 2550MHz	2020-04-04	2550 MHz	OK
3633	Head 5200MHz	2020-04-05	5250 MHz	OK
3633	Head 5600MHz	2020-04-05	5600 MHz	OK
3633	Head 5750MHz	2020-04-05	5750 MHz	OK



No. I20N01406-SAR

# ANNEX G: DAE Calibration Certificate

## DAE4 SN: 786 Calibration Certificate

 In Collaboration with  
**s p e a g**  
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: cttl@chinant.com <http://www.chinant.cn>

  中国认可  
国际互认  
校准  
CALIBRATION  
CNAS L0570

Client : **CTTL(South Branch)**

Certificate No: **Z20-60101**

CALIBRATION CERTIFICATE			
Object	DAE4 - SN: 786		
Calibration Procedure(s)	FF-Z11-002-01 Calibration Procedure for the Data Acquisition Electronics (DAEx)		
Calibration date:	March 03, 2020		
This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.			
All calibrations have been conducted in the closed laboratory facility; environment temperature(22±3)°C and humidity<70%.			
Calibration Equipment used (M&TE critical for calibration)			
Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Process Calibrator 753	1971018	24-Jun-19 (CTTL, No.J19X05126)	Jun-20
Calibrated by:	Name Yu Zongying	Function SAR Test Engineer	Signature 
Reviewed by:	Name Lin Hao	Function SAR Test Engineer	Signature 
Approved by:	Name Qi Dianyuan	Function SAR Project Leader	Signature 
Issued: March 05, 2020			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			

Certificate No: Z20-60101

Page 1 of 3





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com Http://www.chinattl.cn

**Glossary:**

DAE data acquisition electronics  
Connector angle information used in DASY system to align probe sensor X to the robot coordinate system.

**Methods Applied and Interpretation of Parameters:**

- *DC Voltage Measurement:* Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle:* The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The report provide only calibration results for DAE, it does not contain other performance test results.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: cctl@chinattl.com Http://www.chinattl.cn

**DC Voltage Measurement**

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1μV, full range = -100...+300 mV

Low Range: 1LSB = 61nV, full range = -1...+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	404.081 ± 0.15% (k=2)	404.251 ± 0.15% (k=2)	404.649 ± 0.15% (k=2)
Low Range	3.97247 ± 0.7% (k=2)	3.97408 ± 0.7% (k=2)	3.95771 ± 0.7% (k=2)

**Connector Angle**


Connector Angle to be used in DASY system	229.5° ± 1 °
---	--------------



No. I20N01406-SAR



# ANNEX H: Probe Calibration Certificate

## Probe EX3DV4-SN: 3633 Calibration Certificate



In Collaboration with  
**s p e a g**  
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com Http://www.chinattl.cn

中国认可  
国际互认  
校准  
CALIBRATION  
CNAS L0570

Client: **CTTL(South Branch)** Certificate No: **Z20-60108**

### CALIBRATION CERTIFICATE

Object: **EX3DV4 - SN : 3633**

Calibration Procedure(s): **FF-Z11-004-01  
Calibration Procedures for Dosimetric E-field Probes**

Calibration date: **April 01, 2020**




This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)℃ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	18-Jun-19(CTTL, No.J19X05125)	Jun-20
Power sensor NRP-Z91	101547	18-Jun-19(CTTL, No.J19X05125)	Jun-20
Power sensor NRP-Z91	101548	18-Jun-19(CTTL, No.J19X05125)	Jun-20
Reference 10dBAttenuator	18N50W-10dB	10-Feb-20(CTTL, No.J20X00525)	Feb-22
Reference 20dBAttenuator	18N50W-20dB	10-Feb-20(CTTL, No.J20X00526)	Feb-22
Reference Probe EX3DV4	SN 7307	24-May-19(SPEAG, No.EX3-7307_May19/2)	May-20
DAE4	SN 1525	26-Aug-19(SPEAG, No.DAE4-1525_Aug19)	Aug-20

Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
SignalGenerator MG3700A	6201052605	18-Jun-19(CTTL, No.J19X05127)	Jun-20
Network Analyzer E5071C	MY46110673	10-Feb-20(CTTL, No.J20X00515)	Feb-21

	Name	Function	Signature
Calibrated by:	Yu Zongying	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: April 03, 2020

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z20-60108 Page 1 of 10



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) <http://www.chinattl.cn>

#### Glossary:

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A,B,C,D	modulation dependent linearization parameters
Polarization $\Phi$	$\Phi$ rotation around probe axis
Polarization $\theta$	$\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), $\theta=0$ is normal to probe axis

Connector Angle information used in DASY system to align probe sensor X to the robot coordinate system

#### Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>: Assessed for E-field polarization  $\theta=0$  ( $f \leq 900\text{MHz}$  in TEM-cell;  $f > 1800\text{MHz}$ ; waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the  $E^2$ -field uncertainty inside TSL (see below ConvF).
- NORM( $f$ )<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; VR<sub>x,y,z</sub>; A,B,C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800\text{MHz}$ ) and inside waveguide using analytical field distributions based on power measurements for  $f > 800\text{MHz}$ . The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty valued are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50\text{MHz}$  to  $\pm 100\text{MHz}$ .
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

Certificate No:Z20-60108

Page 2 of 10



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: ttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)

## DASY/EASY – Parameters of Probe: EX3DV4 – SN:3633

### Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup>	0.37	0.37	0.39	$\pm 10.0\%$
DCP(mV) <sup>B</sup>	98.2	98.8	98.0	

### Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB· $\mu\text{V}$	C	D dB	VR mV	Unc <sup>E</sup> (k=2)
0	CW	X	0.0	0.0	1.0	0.00	141.5	$\pm 2.3\%$
		Y	0.0	0.0	1.0		141.5	
		Z	0.0	0.0	1.0		141.9	

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X, Y, Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Page 4 and Page 5).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: [ctrl@chinattl.com](mailto:ctrl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

## DASY/EASY – Parameters of Probe: EX3DV4 – SN: 3633

### Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz] <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unct. (k=2)
750	41.9	0.89	9.59	9.59	9.59	0.40	0.75	±12.1%
900	41.5	0.97	9.33	9.33	9.33	0.21	1.14	±12.1%
1640	40.3	1.29	8.17	8.17	8.17	0.16	1.22	±12.1%
1750	40.1	1.37	8.09	8.09	8.09	0.15	1.42	±12.1%
1900	40.0	1.40	7.76	7.76	7.76	0.19	1.14	±12.1%
2100	39.8	1.49	7.73	7.73	7.73	0.18	1.26	±12.1%
2300	39.5	1.67	7.69	7.69	7.69	0.48	0.78	±12.1%
2450	39.2	1.80	7.43	7.43	7.43	0.50	0.77	±12.1%
2600	39.0	1.96	7.20	7.20	7.20	0.58	0.72	±12.1%
3500	37.9	2.91	6.88	6.88	6.88	0.35	1.23	±13.3%
3700	37.7	3.12	6.57	6.57	6.57	0.44	0.98	±13.3%
3900	37.5	3.32	6.51	6.51	6.51	0.35	1.40	±13.3%
4100	37.2	3.53	6.44	6.44	6.44	0.40	1.20	±13.3%
4400	36.9	3.84	6.30	6.30	6.30	0.35	1.35	±13.3%
4600	36.7	4.04	6.10	6.10	6.10	0.45	1.40	±13.3%
4800	36.4	4.25	5.98	5.98	5.98	0.45	1.60	±13.3%
4950	36.3	4.40	5.80	5.80	5.80	0.45	1.45	±13.3%
5250	35.9	4.71	5.47	5.47	5.47	0.45	1.25	±13.3%
5600	35.5	5.07	4.72	4.72	4.72	0.45	1.50	±13.3%
5750	35.4	5.22	4.73	4.73	4.73	0.45	1.50	±13.3%

<sup>C</sup> Frequency validity above 300 MHz of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>F</sup> At frequency below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) <http://www.chinattl.cn>

## DASY/EASY – Parameters of Probe: EX3DV4 – SN: 3633

### Calibration Parameter Determined in Body Tissue Simulating Media

f [MHz] <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unct. (k=2)
750	55.5	0.96	9.57	9.57	9.57	0.40	0.80	±12.1%
900	55.0	1.05	9.34	9.34	9.34	0.25	1.11	±12.1%
1640	53.8	1.40	8.05	8.05	8.05	0.22	1.19	±12.1%
1750	53.4	1.49	7.85	7.85	7.85	0.16	1.35	±12.1%
1900	53.3	1.52	7.66	7.66	7.66	0.17	1.32	±12.1%
2100	53.2	1.62	7.69	7.69	7.69	0.21	1.30	±12.1%
2300	52.9	1.81	7.61	7.61	7.61	0.50	0.86	±12.1%
2450	52.7	1.95	7.56	7.56	7.56	0.50	0.83	±12.1%
2600	52.5	2.16	7.33	7.33	7.33	0.59	0.74	±12.1%
3500	52.3	3.31	6.28	6.28	6.28	0.40	1.30	±13.3%
3700	52.1	3.55	6.14	6.14	6.14	0.40	1.35	±13.3%
3900	50.8	3.78	6.13	6.13	6.13	0.40	1.45	±13.3%
4100	50.5	4.01	6.12	6.12	6.12	0.35	1.40	±13.3%
4400	50.1	4.37	5.93	5.93	5.93	0.35	1.70	±13.3%
4600	49.8	4.60	5.60	5.60	5.60	0.45	1.50	±13.3%
4800	49.6	4.83	5.42	5.42	5.42	0.45	1.60	±13.3%
4950	49.4	5.01	5.22	5.22	5.22	0.45	1.70	±13.3%
5250	48.9	5.36	5.04	5.04	5.04	0.50	1.45	±13.3%
5600	48.5	5.77	4.16	4.16	4.16	0.55	1.50	±13.3%
5750	48.3	5.94	4.26	4.26	4.26	0.55	1.60	±13.3%

<sup>C</sup> Frequency validity above 300 MHz of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.


<sup>F</sup> At frequency below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) <http://www.chinattl.cn>

### Frequency Response of E-Field (TEM-Cell: ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field:  $\pm 7.4\%$  ( $k=2$ )








Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: [cttl@chinattl.com](mailto:cttl@chinattl.com) <http://www.chinattl.cn>

### Receiving Pattern ( $\Phi$ ), $\theta=0^\circ$

**f=600 MHz, TEM**

**f=1800 MHz, R22**





Uncertainty of Axial Isotropy Assessment:  $\pm 1.2\%$  ( $k=2$ )



In Collaboration with  
**TTL speaq**  
 CALIBRATION LABORATORY  
 Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: cttl@chinattl.com <http://www.chinattl.cn>

### Dynamic Range f(SAR<sub>head</sub>) (TEM cell, f = 900 MHz)



Uncertainty of Linearity Assessment: ±0.9% (k=2)





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: [ttl@chinattl.com](mailto:ttl@chinattl.com) <http://www.chinattl.cn>


### Conversion Factor Assessment

f=750 MHz,WGLS R9(H\_convF)

f=1750 MHz,WGLS R22(H\_convF)



### Deviation from Isotropy in Liquid



Uncertainty of Spherical Isotropy Assessment:  $\pm 3.2\%$  (K=2)



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: ctd@chinattl.com <http://www.chinattl.cn>

## DASY/EASY – Parameters of Probe: EX3DV4 – SN:3633

### Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	71.2
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disable
Probe Overall Length	337mm
Probe Body Diameter	10mm
Tip Length	10mm
Tip Diameter	2.5mm
Probe Tip to Sensor X Calibration Point	1mm
Probe Tip to Sensor Y Calibration Point	1mm
Probe Tip to Sensor Z Calibration Point	1mm
Recommended Measurement Distance from Surface	1.4mm



No. I20N01406-SAR

# ANNEX I: Dipole Calibration Certificate

## 750MHz Dipole Calibration Certificate



In Collaboration with  
**s p e a g**  
CALIBRATION LABORATORY



中国认可  
国际互认  
校准  
CALIBRATION  
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com http: www.chinattl.cn

Client **CTTL(South Branch)**

Certificate No: **Z19-60291**

### CALIBRATION CERTIFICATE

Object: **D750V3 - SN: 1163**

Calibration Procedure(s): **FF-Z11-003-01  
Calibration Procedures for dipole validation kits**

Calibration date: **September 3, 2019**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106276	11-Apr-19 (CTTL, No.J19X02605)	Apr-20
Power sensor NRP6A	101369	11-Apr-19 (CTTL, No.J19X02605)	Apr-20
Reference Probe EX30V4	SN 3617	31-Jan-19(SPEAG,No.EX3-3617_Jan19)	Jan-20
DAE4	SN 1555	22-Aug-19(CTTL-SPEAG,No.Z19-60295)	Aug-20
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	23-Jan-19 (CTTL, No.J19X00336)	Jan-20
NetworkAnalyzer E5071C	MY46110673	24-Jan-19 (CTTL, No.J19X00547)	Jan-20

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: September 6, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cttf@chinattl.com http://www.chinattl.cn

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
N/A	not applicable or not measured

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution Corresponds to a coverage probability of approximately 95%.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
 E-mail: cttf@chinattl.com http://www.chinattl.cn

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	V52.10.2
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	750 MHz $\pm$ 1 MHz	

### Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.6 $\pm$ 6 %	0.90 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	----	----

### SAR result with Head TSL

SAR averaged over 1 $cm^3$ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.16 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.53 W/kg $\pm$ 18.8 % (k=2)
SAR averaged over 10 $cm^3$ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.44 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.70 W/kg $\pm$ 18.7 % (k=2)

### Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	55.9 $\pm$ 6 %	0.94 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	----	----

### SAR result with Body TSL

SAR averaged over 1 $cm^3$ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.16 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	8.78 W/kg $\pm$ 18.8 % (k=2)
SAR averaged over 10 $cm^3$ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	1.45 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	5.87 W/kg $\pm$ 18.7 % (k=2)



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com http://www.chinattl.cn

#### Appendix (Additional assessments outside the scope of CNAS L0570)

##### Antenna Parameters with Head TSL

Impedance, transformed to feed point	50.5Ω- 4.53jΩ
Return Loss	- 26.9dB

##### Antenna Parameters with Body TSL

Impedance, transformed to feed point	48.5Ω- 3.38jΩ
Return Loss	- 28.5dB

##### General Antenna Parameters and Design

Electrical Delay (one direction)	0.900 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

##### Additional EUT Data

Manufactured by	SPEAG
-----------------	-------





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
 E-mail: cttl@chinattl.com http://www.chinattl.cn

**DASY5 Validation Report for Head TSL**

Date: 09.03.2019

Test Laboratory: CTTL, Beijing, China

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1163**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.904$  S/m;  $\epsilon_r = 41.62$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(10.03, 10.03, 10.03) @ 750 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/22/2019
- Phantom: MFP\_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)


**Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 55.16 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.11 W/kg

**SAR(1 g) = 2.16 W/kg; SAR(10 g) = 1.44 W/kg**


Maximum value of SAR (measured) = 2.81 W/kg





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cml@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Head TSL





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
 E-mail: ctll@chinattl.com http://www.chinattl.cn

**DASY5 Validation Report for Body TSL**

Date: 09.03.2019

Test Laboratory: CTTL, Beijing, China

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1163**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.942$  S/m;  $\epsilon_r = 55.87$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(9.85, 9.85, 9.85) @ 750 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/22/2019
- Phantom: MFP\_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)


**Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 52.88 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.20 W/kg

**SAR(1 g) = 2.16 W/kg; SAR(10 g) = 1.45 W/kg**


Maximum value of SAR (measured) = 2.85 W/kg





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cntl@chinantl.com http://www.chinantl.cn

Impedance Measurement Plot for Body TSL





No. I20N01406-SAR

### 835 MHz Dipole Calibration Certificate



In Collaboration with  
**s p e a g**  
CALIBRATION LABORATORY



中国认可  
国际互认  
校准  
CALIBRATION  
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client **CTTL(South Branch)**

Certificate No: **Z18-60385**

## CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d057**

Calibration Procedure(s) **FF-Z11-003-01  
Calibration Procedures for dipole validation kits**

Calibration date: **October 9, 2018**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRVD	102083	01-Nov-17 (CTTL, No.J17X08756)	Oct-18
Power sensor NRV-Z5	100542	01-Nov-17 (CTTL, No.J17X08756)	Oct-18
Reference Probe EX3DV4	SN 7514	27-Aug-18(SPEAG,No.EX3-7514_Aug18)	Aug-19
DAE4	SN 1555	20-Aug-18(SPEAG,No.DAE4-1555_Aug18)	Aug-19
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	23-Jan-18 (CTTL, No.J18X00560)	Jan-19
NetworkAnalyzer E5071C	MY46110673	24-Jan-18 (CTTL, No.J18X00561)	Jan-19

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: October 11, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z18-60385

Page 1 of 8



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com http://www.chinattl.cn

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
N/A	not applicable or not measured

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
 E-mail: ttl@chinattl.com http://www.chinattl.cn

**Measurement Conditions**

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.10.1.1476
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

**Head TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	42.2 $\pm$ 6 %	0.91 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	---	---

**SAR result with Head TSL**

SAR averaged over 1 $cm^3$ (1 g) of Head TSL	Condition:	
SAR measured	250 mW input power	2.42 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>9.62 mW / g <math>\pm</math> 18.8 % (k=2)</b>
SAR averaged over 10 $cm^3$ (10 g) of Head TSL	Condition:	
SAR measured	250 mW input power	1.58 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>6.29 mW / g <math>\pm</math> 18.7 % (k=2)</b>

**Body TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	55.9 $\pm$ 6 %	0.99 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	---	---

**SAR result with Body TSL**

SAR averaged over 1 $cm^3$ (1 g) of Body TSL	Condition:	
SAR measured	250 mW input power	2.51 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>9.90 mW / g <math>\pm</math> 18.8 % (k=2)</b>
SAR averaged over 10 $cm^3$ (10 g) of Body TSL	Condition:	
SAR measured	250 mW input power	1.66 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>6.56 mW / g <math>\pm</math> 18.7 % (k=2)</b>



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cti@chinamtl.com http://www.chinamtl.cn

Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Table with 2 columns: Parameter (Impedance, transformed to feed point; Return Loss) and Value (49.6Ω- 4.08jΩ; - 27.7dB)

Antenna Parameters with Body TSL

Table with 2 columns: Parameter (Impedance, transformed to feed point; Return Loss) and Value (46.8Ω- 4.96jΩ; - 24.3dB)

General Antenna Parameters and Design

Table with 2 columns: Parameter (Electrical Delay (one direction)) and Value (1.260 ns)

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Table with 2 columns: Parameter (Manufactured by) and Value (SPEAG)





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
 E-mail: cttl@chinattl.com http://www.chinattl.cn

**DASY5 Validation Report for Head TSL**

Date: 10.08.2018

Test Laboratory: CTTL, Beijing, China

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d057**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.912$  S/m;  $\epsilon_r = 42.22$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7514; ConvF(9.09, 9.09, 9.09) @ 835 MHz; Calibrated: 8/27/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/20/2018
- Phantom: MFP\_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)


**Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 55.57 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.61 W/kg

SAR(1 g) = 2.42 W/kg; SAR(10 g) = 1.58 W/kg


Maximum value of SAR (measured) = 3.22 W/kg





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Head TSL



**DASY5 Validation Report for Body TSL**

Date: 10.08.2018

Test Laboratory: CTTL, Beijing, China

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d057**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.992$  S/m;  $\epsilon_r = 55.93$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7514; ConvF(9.47, 9.47, 9.47) @ 835 MHz; Calibrated: 8/27/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/20/2018
- Phantom: MFP\_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)


**Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.64 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.83 W/kg

**SAR(1 g) = 2.51 W/kg; SAR(10 g) = 1.66 W/kg**

Maximum value of SAR (measured) = 3.36 W/kg




0 dB = 3.36 W/kg = 5.26 dBW/kg



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cntl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Body TSL





No. I20N01406-SAR

### 1750 MHz Dipole Calibration Certificate



In Collaboration with  
**s p e a g**  
CALIBRATION LABORATORY



中国认可  
国际互认  
校准  
CALIBRATION  
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client **CTTL(South Branch)**

Certificate No: **Z19-60292**

#### CALIBRATION CERTIFICATE

Object **D1750V2 - SN: 1152**

Calibration Procedure(s) **FF-Z11-003-01**  
**Calibration Procedures for dipole validation kits**

Calibration date: **August 30, 2019**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)℃ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106276	11-Apr-19 (CTTL, No.J19X02605)	Apr-20
Power sensor NRP6A	101369	11-Apr-19 (CTTL, No.J19X02605)	Apr-20
Reference Probe EX3DV4	SN 3617	31-Jan-19(SPEAG,No.EX3-3617_Jan19)	Jan-20
DAE4	SN 1555	22-Aug-19(CTTL-SPEAG,No.Z19-60295)	Aug-20
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	23-Jan-19 (CTTL, No.J19X00336)	Jan-20
NetworkAnalyzer E5071C	MY46110673	24-Jan-19 (CTTL, No.J19X00547)	Jan-20

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: September 2, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: ctf@chinattl.com http://www.chinattl.cn

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
N/A	not applicable or not measured

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

**Measurement Conditions**

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	V52.10.2
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1750 MHz $\pm$ 1 MHz	

**Head TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.1	1.37 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	39.9 $\pm$ 6 %	1.36 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	---	---

**SAR result with Head TSL**

SAR averaged over 1 $cm^3$ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.05 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	<b>36.4 W/kg <math>\pm</math> 18.8 % (k=2)</b>
SAR averaged over 10 $cm^3$ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	4.80 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	<b>19.3 W/kg <math>\pm</math> 18.7 % (k=2)</b>

**Body TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.4	1.49 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	53.1 $\pm$ 6 %	1.52 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	---	---

**SAR result with Body TSL**

SAR averaged over 1 $cm^3$ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.45 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	<b>37.3 W/kg <math>\pm</math> 18.8 % (k=2)</b>
SAR averaged over 10 $cm^3$ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	5.05 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	<b>20.0 W/kg <math>\pm</math> 18.7 % (k=2)</b>



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: ttl@chinattl.com http://www.chinattl.cn

Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Table with 2 columns: Parameter, Value. Rows: Impedance, transformed to feed point (49.1Ω- 0.84 jΩ), Return Loss (- 38.1 dB)

Antenna Parameters with Body TSL

Table with 2 columns: Parameter, Value. Rows: Impedance, transformed to feed point (45.2Ω- 1.37 jΩ), Return Loss (- 25.5 dB)

General Antenna Parameters and Design

Table with 2 columns: Parameter, Value. Row: Electrical Delay (one direction) (1.064 ns)

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Table with 2 columns: Parameter, Value. Row: Manufactured by (SPEAG)



**DASY5 Validation Report for Head TSL**

Date: 08.30.2019

Test Laboratory: CTTL, Beijing, China

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1152**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.358$  S/m;  $\epsilon_r = 39.91$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(8.38, 8.38, 8.38) @ 1750 MHz; Calibrated: 1/31/2019.
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/22/2019
- Phantom: MFP\_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**System Performance Check/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:**


$dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 97.38 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 16.8 W/kg

SAR(1 g) = 9.05 W/kg; SAR(10 g) = 4.8 W/kg


Maximum value of SAR (measured) = 13.9 W/kg





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cni@chinantl.com http://www.chinantl.cn

Impedance Measurement Plot for Head TSL



**DASY5 Validation Report for Body TSL**

Date: 08.30.2019

Test Laboratory: CTTL, Beijing, China

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1152**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.516$  S/m;  $\epsilon_r = 53.05$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(8.03, 8.03, 8.03) @ 1750 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/22/2019
- Phantom: MFP\_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**System Performance Check/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:**


$dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 87.16 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 17.0 W/kg

SAR(1 g) = 9.45 W/kg; SAR(10 g) = 5.05 W/kg


Maximum value of SAR (measured) = 14.4 W/kg





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China.  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: ttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Body TSL





No. I20N01406-SAR

### 1900 MHz Dipole Calibration Certificate



In Collaboration with  
**s p e a g**  
CALIBRATION LABORATORY



中国认可  
国际互认  
校准  
CALIBRATION  
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client **CTTL(South Branch)**

Certificate No: **Z18-60387**

#### CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d088**

Calibration Procedure(s) **FF-Z11-003-01  
Calibration Procedures for dipole validation kits**

Calibration date: **October 24, 2018**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRVD	102083	01-Nov-17 (CTTL, No.J17X08756)	Oct-18
Power sensor NRV-Z5	100542	01-Nov-17 (CTTL, No.J17X08756)	Oct-18
Reference Probe EX3DV4 DAE4	SN 7514	27-Aug-18(SPEAG No.EX3-7514_Aug18)	Aug-19
	SN 1555	20-Aug-18(SPEAG No.DAE4-1555_Aug18)	Aug-19
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	23-Jan-18 (CTTL, No.J18X00560)	Jan-19
NetworkAnalyzer E5071C	MY46110673	24-Jan-18 (CTTL, No.J18X00561)	Jan-19

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: October 23, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.