



TEST REPORT

No. I21N02089-BT

for

TCL Communication Ltd.

MOVEAUDIO S180 TRUE WIRELESS IN-EAR NC HEADPHONES

Model Name: TW18

with

Hardware Version: TW18_V1.1

Software Version: TW18_buds_1.0.0.5

FCC ID: 2ACCJB163

Issued Date: 2021-08-11

Designation Number: CN1210

ISED Assigned Code: 23289

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

Test Laboratory:

SAICT, Shenzhen Academy of Information and Communications Technology

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518000.

Tel:+86(0)755-33322000, Fax:+86(0)755-33322001

Email: yewu@saict.ac.cn. www.saict.ac.cn



CONTENTS

| | |
|---|-----------|
| CONTENTS | 2 |
| 1. SUMMARY OF TEST REPORT..... | 3 |
| 1.1. TEST ITEMS..... | 3 |
| 1.2. TEST STANDARDS | 3 |
| 1.3. TEST RESULT | 3 |
| 1.4. TESTING LOCATION | 3 |
| 1.5. PROJECT DATA | 3 |
| 1.6. SIGNATURE | 3 |
| 2. CLIENT INFORMATION..... | 4 |
| 2.1. APPLICANT INFORMATION | 4 |
| 2.2. MANUFACTURER INFORMATION | 4 |
| 3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) | 5 |
| 3.1. ABOUT EUT | 5 |
| 3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST | 5 |
| 3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST | 5 |
| 3.4. GENERAL DESCRIPTION..... | 5 |
| 4. REFERENCE DOCUMENTS..... | 6 |
| 4.1. DOCUMENTS SUPPLIED BY APPLICANT..... | 6 |
| 4.2. REFERENCE DOCUMENTS FOR TESTING | 6 |
| 5. TEST RESULTS..... | 7 |
| 5.1. TESTING ENVIRONMENT..... | 7 |
| 5.2. TEST RESULTS | 7 |
| 5.3. STATEMENTS..... | 7 |
| 6. TEST EQUIPMENTS UTILIZED..... | 8 |
| 7. LABORATORY ENVIRONMENT..... | 9 |
| 8. MEASUREMENT UNCERTAINTY | 10 |
| ANNEX A: DETAILED TEST RESULTS..... | 11 |
| TEST CONFIGURATION..... | 11 |
| A.0 ANTENNA REQUIREMENT | 13 |
| A.1 MAXIMUM PEAK OUTPUT POWER | 14 |
| A.2 BAND EDGES COMPLIANCE | 15 |
| A.3 CONDUCTED EMISSION | 22 |
| A.4 RADIATED EMISSION..... | 33 |
| A.5 20DB BANDWIDTH..... | 51 |
| A.6 TIME OF OCCUPANCY (DWELL TIME)..... | 56 |
| A.7 NUMBER OF HOPPING CHANNELS..... | 60 |
| A.8 CARRIER FREQUENCY SEPARATION | 64 |



1. Summary of Test Report

1.1. Test Items

| | |
|---------------------|---|
| Description | MOVEAUDIO S180 TRUE WIRELESS IN-EAR NC HEADPHONES |
| Model Name | TW18 |
| Applicant's name | TCL Communication Ltd. |
| Manufacturer's Name | TCL Communication Ltd. |

1.2. Test Standards

FCC Part15-2019; ANSI C63.10-2013;

1.3. Test Result

Pass

1.4. Testing Location

Address: Building G, Shenzhen International Innovation Center, No.1006 Shennan Road,
Futian District, Shenzhen, Guangdong, P. R. China

1.5. Project data

| | |
|---------------------|------------|
| Testing Start Date: | 2021-07-10 |
| Testing End Date: | 2021-07-30 |

1.6. Signature

An Ran
(Prepared this test report)

Tang Weisheng
(Reviewed this test report)

Zhang Bojun
(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
Contact Person: Gong Zhizhou
E-Mail: zhizhou.gong@tcl.com
Telephone: 0086-755-36611722
Fax: 0086-755-36612000-81722

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
Contact Person: Gong Zhizhou
E-Mail: zhizhou.gong@tcl.com
Telephone: 0086-755-36611722
Fax: 0086-755-36612000-81722



3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

| | |
|------------------------------|---|
| Description | MOVEAUDIO S180 TRUE WIRELESS IN-EAR NC HEADPHONES |
| Model Name | TW18 |
| Frequency Band | 2400MHz~2483.5MHz |
| Type of Modulation | GFSK/ π /4 DQPSK/8DPSK |
| Number of Channels | 79 |
| Antenna Type | Integrated |
| Antenna Gain | 0.19dBi |
| Power Supply | 3.7V DC by Battery |
| FCC ID | 2ACCJB163 |
| Condition of EUT as received | No abnormality in appearance |

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Shenzhen Academy of Information and Communications Technology.

3.2. Internal Identification of EUT used during the test

| EUT ID* | IMEI | HW Version | SW Version | Receive Date |
|---------|------|------------|-------------------|--------------|
| UT03aa | / | TW18_V1.1 | TW18_buds_1.0.0.5 | 2021-07-05 |
| UT01aa | / | TW18_V1.1 | TW18_buds_1.0.0.5 | 2021-07-05 |

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

| AE ID* | Description | AE ID* |
|--------|-------------|--------|
| AE1 | Battery | / |

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment under Test (EUT) is a model of MOVEAUDIO S180 TRUE WIRELESS IN-EAR NC HEADPHONES (the left headphone) with integrated antenna and battery.

It consists of normal options: Charger.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.



4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

| Reference | Title | Version |
|------------------|---|----------------|
| FCC Part 15 | FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz | 2019 |
| ANSI C63.10 | American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices | 2013 |

5. Test Results

5.1. Testing Environment

Normal Temperature: 15~35°C

Relative Humidity: 20~75%

5.2. Test Results

| No | Test cases | Sub-clause of Part 15C | Sub-clause of IC | Verdict |
|----|-------------------------------------|------------------------|--|-----------|
| 0 | Antenna Requirement | 15.203 | / | P |
| 1 | Maximum Peak Output Power | 15.247 (b) | RSS-247 section 5.4 | P |
| 2 | Band Edges Compliance | 15.247 (d) | RSS-247 section 5.1 | P |
| 3 | Conducted Spurious Emission | 15.247 (d) | RSS-247 section 5.5/ RSS-Gen section 6.13 | P |
| 4 | Radiated Spurious Emission | 15.247,15.205,15.209 | RSS-247 section 5.5/ RSS-Gen section 6.13 | P |
| 5 | Occupied 20dB bandwidth | 15.247(a) | RSS-247 section 5.1 | / |
| 6 | Time of Occupancy (Dwell Time) | 15.247(a) | RSS-247 section 5.1 | P |
| 7 | Number of Hopping Channel | 15.247(a) | RSS-247 section 5.1 | P |
| 8 | Carrier Frequency Separation | 15.247(a) | RSS-247 section 5.1 | P |
| 9 | AC Power line Conducted Emission | 15.107,15.207 | RSS-Gen section 8.8 | NA |

See **ANNEX A** for details.

NA: Because the device can not use Bluetooth function when charging, the conducted continuous disturbance test is not required.

5.3. Statements

SAICT has evaluated the test cases requested by the applicant/manufacture as listed in section 5.2 of this report, for the EUT specified in section 3, according to the standards or reference documents listed in section 4.2.

6. Test Equipments Utilized

Conducted test system

| No. | Equipment | Model | Serial Number | Manufacturer | Calibration Due date | Calibration Period |
|-----|------------------------|-------|---------------|-----------------|----------------------|--------------------|
| 1 | Vector Signal Analyzer | FSV40 | 100903 | Rohde & Schwarz | 2021-12-30 | 1 year |
| 2 | Bluetooth Tester | CBT32 | 100584 | Rohde & Schwarz | 2021-12-30 | 1 year |

Radiated emission test system

| NO. | Equipment | Model | Serial Number | Manufacturer | Calibration Due date | Calibration Period |
|-----|-------------------|-------------------|---------------|-----------------|----------------------|--------------------|
| 1 | Loop Antenna | HLA6120 | 35779 | TESEQ | 2022-04-25 | 3 years |
| 2 | BiLog Antenna | 3142E | 00224831 | ETS-Lindgren | 2024-05-27 | 3 years |
| 3 | Horn Antenna | 3117 | 00066577 | ETS-Lindgren | 2022-04-02 | 3 years |
| 4 | Test Receiver | ESR7 | 101676 | Rohde & Schwarz | 2021-11-25 | 1 year |
| 5 | Spectrum Analyser | FSV40 | 101192 | Rohde & Schwarz | 2022-01-13 | 1 year |
| 6 | Chamber | FACT3-2.0 | 1285 | ETS-Lindgren | 2023-05-29 | 2 years |
| 7 | Antenna | QSH-SL-18-26-S-20 | 17013 | Q-par | 2023-01-06 | 3 years |

Test software

| No. | Equipment | Manufacturer | Version |
|-----|------------------|-----------------|----------|
| 1 | TechMgr Software | CAICT | 2.1.1 |
| 2 | EMC32 | Rohde & Schwarz | 8.53.0 |
| 3 | EMC32 | Rohde & Schwarz | 10.01.00 |

EUT is engineering software provided by the customer to control the transmitting signal. The EUT was programmed to be in continuously transmitting mode.

Anechoic chamber

Fully anechoic chamber by ETS-Lindgren

7. Laboratory Environment

Semi-anechoic chambe

| | |
|-----------------------------------|---|
| Temperature | Min. = 15 °C, Max. = 35 °C |
| Relative humidity | Min. = 20 %, Max. = 75 % |
| Shielding effectiveness | 0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB |
| Electrical insulation | > 2MΩ |
| Ground system resistance | < 4Ω |
| Normalised site attenuation (NSA) | < ± 4 dB, 3 m distance, from 30 to 1000 MHz |

Shielded room

| | |
|--------------------------|--|
| Temperature | Min. = 15 °C, Max. = 35 °C |
| Relative humidity | Min. = 20 %, Max. = 75 % |
| Shielding effectiveness | 0.014MHz-1MHz> 60 dB; 1MHz-1000MHz>90 dB |
| Electrical insulation | > 2MΩ |
| Ground system resistance | < 4Ω |

Fully-anechoic chamber

| | |
|------------------------------------|---|
| Temperature | Min. = 15 °C, Max. = 35 °C |
| Relative humidity | Min. = 20 %, Max. = 75 % |
| Shielding effectiveness | 0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB |
| Electrical insulation | > 2MΩ |
| Ground system resistance | < 4Ω |
| Voltage Standing Wave Ratio (VSWR) | ≤ 6 dB, from 1 to 18 GHz, 3 m distance |
| Uniformity of field strength | Between 0 and 6 dB, from 80 to 6000 MHz |

8. Measurement Uncertainty

| Test Name | Uncertainty ($k=2$) | |
|---|--|--------|
| 1. RF Output Power - Conducted | 1.32dB | |
| 2. Time of Occupancy - Conducted | 0.58ms | |
| 3. Occupied channel bandwidth - Conducted | 66Hz | |
| 4 Transmitter Spurious Emission - Conducted | $30\text{MHz} \leq f \leq 1\text{GHz}$ | 1.41dB |
| | $1\text{GHz} \leq f \leq 7\text{GHz}$ | 1.92dB |
| | $7\text{GHz} \leq f \leq 13\text{GHz}$ | 2.31dB |
| | $13\text{GHz} \leq f \leq 26\text{GHz}$ | 2.61dB |
| 5. Transmitter Spurious Emission - Radiated | $9\text{kHz} \leq f \leq 30\text{MHz}$ | 1.70dB |
| | $30\text{MHz} \leq f \leq 1\text{GHz}$ | 4.90dB |
| | $1\text{GHz} \leq f \leq 18\text{GHz}$ | 4.60dB |
| | $18\text{GHz} \leq f \leq 40\text{GHz}$ | 4.10dB |
| 6. AC Power line Conducted Emission | $150\text{kHz} \leq f \leq 30\text{MHz}$ | 3.00dB |


ANNEX A: Detailed Test Results

Test Configuration

The measurement is made according to ANSI C63.10.


1) Conducted Measurements

1. Connect the EUT to the test system correctly.
2. Set the EUT to the required work mode.
3. Set the EUT to the required channel.
4. Set the EUT hopping mode (hopping on or hopping off).
5. Set the spectrum analyzer to start measurement.
6. Record the values.




2) Radiated Measurements

Test setup: EUT was placed on a 1.5 meter high non-conductive table at a 3 meter test distance from the receive antenna. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT and adjusting the receiving antenna polarization.



3) AC Power line Conducted Emission Measurement

The EUT is working as Bluetooth terminal. A communication link of Bluetooth is set up with a System Simulator (SS). The EUT is commanded to operate at maximum transmitting power.





A.0 Antenna requirement

Measurement Limit:

| Standard | Requirement |
|---------------------|--|
| FCC CRF Part 15.203 | An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded. |

**Conclusion: The Directional gains of antenna used for transmitting is 0.19dBi.
The RF transmitter uses an integrate antenna without connector.**

**A.1 Maximum Peak Output Power****Method of Measurement: See ANSI C63.10-clause 7.8.5.**

Use the following spectrum analyzer settings:

- a) Set Span = 6 MHz.
- b) Set RBW = 3 MHz.
- c) Set VBW = 3 MHz.
- d) Sweep time = auto.
- e) Detector = peak.
- f) Trace = max hold.
- g) Allow trace to stabilize.
- h) Use the marker-to-peak function to set the marker to the peak of the emission.
- i) The indicated level is the peak output power.

Measurement Limit:

| Standard | Limit (dBm) | E.I.R.P Limit (dBm) |
|--|-------------|---------------------|
| FCC CRF Part 15.247(b)(1) & RSS-247 Section 5.4 | < 30 | < 36 |

Measurement Results:

| Mode | Peak Conducted Output Power (dBm) | | |
|---------------|-----------------------------------|----------------|----------------|
| | 2402MHz (Ch0) | 2441MHz (Ch39) | 2480MHz (Ch78) |
| GFSK | 9.35 | 8.71 | 8.34 |
| $\pi/4$ DQPSK | 9.31 | 8.67 | 8.33 |
| 8DPSK | 9.24 | 8.62 | 8.24 |

The E.I.R.P Results are listed below:

| Mode | E.I.R.P (dBm) | | |
|---------------|---------------|----------------|----------------|
| | 2402MHz (Ch0) | 2441MHz (Ch39) | 2480MHz (Ch78) |
| GFSK | 9.54 | 8.90 | 8.53 |
| $\pi/4$ DQPSK | 9.50 | 8.86 | 8.52 |
| 8DPSK | 9.43 | 8.81 | 8.43 |

Note: E.I.R.P value = Conducted values (with conducted samples) + Antenna Gain.

Conclusion: Pass



A.2 Band Edges Compliance

Measurement Limit:

| Standard | Limit (dB) |
|---|------------|
| FCC 47 CFR Part 15.247 (d) & RSS-247 Section 5.1 | > 20 |

Measurement Result:

| Mode | Channel | Hopping | Test Results | Conclusion |
|---------------|---------|---------|--------------|------------|
| GFSK | 0 | ON | Fig.1 | P |
| | 78 | ON | Fig.2 | P |
| $\pi/4$ DQPSK | 0 | ON | Fig.3 | P |
| | 78 | ON | Fig.4 | P |
| 8DPSK | 0 | ON | Fig.5 | P |
| | 78 | ON | Fig.6 | P |

| Mode | Channel | Hopping | Test Results | Conclusion |
|---------------|---------|---------|--------------|------------|
| GFSK | 0 | OFF | Fig.7 | P |
| | 78 | OFF | Fig.8 | P |
| $\pi/4$ DQPSK | 0 | OFF | Fig.9 | P |
| | 78 | OFF | Fig.10 | P |
| 8DPSK | 0 | OFF | Fig.11 | P |
| | 78 | OFF | Fig.12 | P |

See below for test graphs.

Conclusion: Pass




Fig. 1 Band Edges (GFSK, Ch 0, Hopping ON)




Fig. 2 Band Edges (GFSK, Ch 78, Hopping ON)




Fig. 3 Band Edges (π /4 DQPSK, Ch 0, Hopping ON)




Fig. 4 Band Edges (π /4 DQPSK, Ch 78, Hopping ON)




Fig. 5 Band Edges (8DPSK, Ch 0, Hopping ON)




Fig. 6 Band Edges (8DPSK, Ch 78, Hopping ON)




Fig. 7 Band Edges (GFSK, Ch 0, Hopping OFF)




Fig. 8 Band Edges (GFSK, Ch 78, Hopping OFF)




Fig. 9 Band Edges ($\pi/4$ DQPSK, Ch 0, Hopping OFF)




Fig. 10 Band Edges ($\pi/4$ DQPSK, Ch 78, Hopping OFF)




Fig. 11 Band Edges (8DPSK, Ch 0, Hopping OFF)




Fig. 12 Band Edges (8DPSK, Ch 78, Hopping OFF)



A.3 Conducted Emission

Measurement Limit:

| Standard | Limit |
|---|---|
| FCC 47 CFR Part 15.247 (d) & RSS-247 section 5.5/RSS-Gen section 6.13 | 20dB below peak output power in 100 kHz bandwidth |

Measurement Results:

| MODE | Channel | Frequency Range | Test Results | Conclusion |
|---------------|--------------|-----------------|--------------|------------|
| GFSK | 0 | 1GHz-3GHz | Fig.13 | P |
| | | 3GHz-10GHz | Fig.14 | P |
| | 39 | 1GHz-3GHz | Fig.15 | P |
| | | 3GHz-10GHz | Fig.16 | P |
| | 78 | 1GHz-3GHz | Fig.17 | P |
| | | 3GHz-10GHz | Fig.18 | P |
| $\pi/4$ DQPSK | 0 | 1GHz-3GHz | Fig.19 | P |
| | | 3GHz-10GHz | Fig.20 | P |
| | 39 | 1GHz-3GHz | Fig.21 | P |
| | | 3GHz-10GHz | Fig.22 | P |
| | 78 | 1GHz-3GHz | Fig.23 | P |
| | | 3GHz-10GHz | Fig.24 | P |
| 8DPSK | 0 | 1GHz-3GHz | Fig.25 | P |
| | | 3GHz-10GHz | Fig.26 | P |
| | 39 | 1GHz-3GHz | Fig.27 | P |
| | | 3GHz-10GHz | Fig.28 | P |
| | 78 | 1GHz-3GHz | Fig.29 | P |
| | | 3GHz-10GHz | Fig.30 | P |
| / | All channels | 30 MHz-1GHz | Fig.31 | P |
| | | 10GHz-26GHz | Fig.32 | P |

See below for test graphs.

Conclusion: Pass




Fig. 13 Conducted Spurious Emission (GFSK, Ch0, 1 GHz-3 GHz)




Fig. 14 Conducted Spurious Emission (GFSK, Ch0, 3GHz-10 GHz)




Fig. 15 Conducted Spurious Emission (GFSK, Ch39, 1GHz-3 GHz)




Fig. 16 Conducted Spurious Emission (GFSK, Ch39, 3GHz-10 GHz)




Fig. 17 Conducted Spurious Emission (GFSK, Ch78, 1GHz-3 GHz)




Fig. 18 Conducted Spurious Emission (GFSK, Ch78, 3GHz-10 GHz)




Fig. 19 Conducted Spurious Emission ($\pi/4$ DQPSK, Ch0, 1GHz-3 GHz)




Fig. 20 Conducted Spurious Emission ($\pi/4$ DQPSK, Ch0, 3GHz-10 GHz)




Fig. 21 Conducted Spurious Emission (π /4 DQPSK, Ch39, 1GHz-3 GHz)




Fig. 22 Conducted Spurious Emission (π /4 DQPSK, Ch39, 3GHz-10 GHz)




Fig. 23 Conducted Spurious Emission (π /4 DQPSK, Ch78, 1GHz-3 GHz)




Fig. 24 Conducted Spurious Emission (π /4 DQPSK, Ch78, 3GHz-10 GHz)




Fig. 25 Conducted Spurious Emission (8DPSK, Ch0, 1GHz-3 GHz)




Fig. 26 Conducted Spurious Emission (8DPSK, Ch0, 3GHz-10 GHz)




Fig. 27 Conducted Spurious Emission (8DPSK, Ch39, 1GHz-3 GHz)




Fig. 28 Conducted Spurious Emission (8DPSK, Ch39, 3GHz-10 GHz)




Fig. 29 Conducted Spurious Emission (8DPSK, Ch78, 1GHz-3 GHz)




Fig. 30 Conducted Spurious Emission (8DPSK, Ch78, 3GHz-10 GHz)




Fig. 31 Conducted Spurious Emission (All channel, 30 MHz-1 GHz)




Fig. 32 Conducted Spurious Emission All channel, 10 GHz-26 GHz)

A.4 Radiated Emission

Measurement Limit:

| Standard | Limit |
|---|------------------------------|
| FCC 47 CFR Part 15.247, 15.205, 15.209 & RSS-247 section 5.5/RSS-Gen section 6.13 | 20dB below peak output power |

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

| Frequency of emission (MHz) | Field strength(μV/m) | Measurement distance(meters) |
|-----------------------------|----------------------|------------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

Test Condition:

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

| Frequency of emission (MHz) | RBW/VBW | Sweep Time(s) |
|-----------------------------|---------------|---------------|
| 30-1000 | 120kHz/300kHz | 5 |
| 1000-4000 | 1MHz/3MHz | 15 |
| 4000-18000 | 1MHz/3MHz | 40 |
| 18000-26500 | 1MHz/3MHz | 20 |

Note: According to the performance evaluation, the radiated emission margin of EUT is over 20dB in the band from 9kHz to 30MHz. Therefore, the measurement starts from 30MHz to tenth harmonic.

The measurement results include the horizontal polarization and vertical polarization measurements.

Measurement Results:

| Mode | Channel | Frequency Range | Test Results | Conclusion |
|------------------|------------------------|---------------------|--------------|------------|
| GFSK | 0 | 1 GHz ~3 GHz | Fig.33 | P |
| | | 3 GHz ~18 GHz | Fig.34 | P |
| | 39 | 1 GHz ~3 GHz | Fig.35 | P |
| | | 3 GHz ~18 GHz | Fig.36 | P |
| | 78 | 1 GHz ~3 GHz | Fig.37 | P |
| | | 3 GHz ~18 GHz | Fig.38 | P |
| | Restricted Band(CH0) | 2.38 GHz ~ 2.45 GHz | Fig.39 | P |
| | Restricted Band (CH78) | 2.45 GHz ~ 2.5 GHz | Fig.40 | P |
| $\pi/4$ DQPSK | 0 | 1 GHz ~3 GHz | Fig.41 | P |
| | | 3 GHz ~18 GHz | Fig.42 | P |
| | 39 | 1 GHz ~3 GHz | Fig.43 | P |
| | | 3 GHz ~18 GHz | Fig.44 | P |
| | 78 | 1 GHz ~3 GHz | Fig.45 | P |
| | | 3 GHz ~18 GHz | Fig.46 | P |
| | Restricted Band (CH0) | 2.38 GHz ~ 2.45 GHz | Fig.47 | P |
| | Restricted Band (CH78) | 2.45 GHz ~ 2.5 GHz | Fig.48 | P |
| 8DPSK | 0 | 1 GHz ~3 GHz | Fig.49 | P |
| | | 3 GHz ~18 GHz | Fig.50 | P |
| | 39 | 1 GHz ~3 GHz | Fig.51 | P |
| | | 3 GHz ~18 GHz | Fig.52 | P |
| | 78 | 1 GHz ~3 GHz | Fig.53 | P |
| | | 3 GHz ~18 GHz | Fig.54 | P |
| | Restricted Band (CH0) | 2.38 GHz ~ 2.45 GHz | Fig.55 | P |
| | Restricted Band (CH78) | 2.45 GHz ~ 2.5 GHz | Fig.56 | P |
| / | All channels | 9 kHz ~30 MHz | Fig.57 | P |
| | | 30 MHz ~1 GHz | Fig.58 | P |
| | | 18 GHz ~26.5 GHz | Fig.59 | P |



Worst Case Result

GFSK CH39 (1-18GHz)

| Frequency (MHz) | MaxPeak (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|------------------|----------------|-------------|-----|--------------|
| 4881.500000 | 56.31 | 74.00 | 17.69 | H | -0.1 |
| 11220.000000 | 46.95 | 74.00 | 27.05 | V | 6.2 |
| 12961.000000 | 48.25 | 74.00 | 25.75 | V | 9.2 |
| 14534.500000 | 49.23 | 74.00 | 24.77 | H | 11.6 |
| 17021.000000 | 51.75 | 74.00 | 22.25 | V | 15.2 |
| 17983.500000 | 52.50 | 74.00 | 21.50 | H | 16.9 |

| Frequency (MHz) | Average (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|------------------|----------------|-------------|-----|--------------|
| 4881.000000 | 49.09 | 54.00 | 4.91 | H | 0.0 |
| 7323.000000 | 39.10 | 54.00 | 14.90 | H | 2.2 |
| 12633.000000 | 35.78 | 54.00 | 18.22 | V | 8.8 |
| 14459.000000 | 37.53 | 54.00 | 16.47 | V | 11.8 |
| 16819.000000 | 39.82 | 54.00 | 14.18 | H | 15.9 |
| 17945.500000 | 40.89 | 54.00 | 13.11 | V | 17.3 |

$\pi/4$ DQPSK CH0 (1-18GHz)

| Frequency (MHz) | MaxPeak (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|------------------|----------------|-------------|-----|--------------|
| 4804.000000 | 55.53 | 74.00 | 18.47 | H | -0.3 |
| 11430.000000 | 47.43 | 74.00 | 26.57 | V | 6.8 |
| 13168.000000 | 48.28 | 74.00 | 25.72 | H | 9.6 |
| 14527.000000 | 49.90 | 74.00 | 24.10 | V | 11.7 |
| 16966.000000 | 51.68 | 74.00 | 22.32 | H | 16.1 |
| 17942.000000 | 52.19 | 74.00 | 21.81 | H | 17.2 |

| Frequency (MHz) | Average (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|------------------|----------------|-------------|-----|--------------|
| 4804.000000 | 49.80 | 54.00 | 4.20 | H | -0.3 |
| 7206.000000 | 35.54 | 54.00 | 18.46 | H | 2.6 |
| 12677.000000 | 36.27 | 54.00 | 17.73 | H | 8.9 |
| 15293.500000 | 37.36 | 54.00 | 16.64 | V | 12.2 |
| 16852.500000 | 39.81 | 54.00 | 14.19 | H | 16.0 |
| 17953.000000 | 40.80 | 54.00 | 13.20 | H | 17.1 |

**8DPSK CH78 (1-18GHz)**

| Frequency (MHz) | MaxPeak (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|------------------------|----------------------|-------------|-----|--------------|
| 4959.500000 | 53.08 | 74.00 | 20.92 | H | -0.1 |
| 11467.000000 | 46.76 | 74.00 | 27.24 | V | 6.7 |
| 12616.500000 | 47.82 | 74.00 | 26.18 | V | 8.7 |
| 14457.500000 | 50.16 | 74.00 | 23.84 | H | 11.7 |
| 16846.000000 | 52.48 | 74.00 | 21.52 | H | 15.9 |
| 17910.000000 | 51.98 | 74.00 | 22.02 | V | 17.4 |

| Frequency (MHz) | Average (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|------------------------|----------------------|-------------|-----|--------------|
| 4960.000000 | 49.54 | 54.00 | 4.55 | H | -0.1 |
| 11436.500000 | 34.87 | 54.00 | 19.13 | H | 6.8 |
| 13213.500000 | 36.18 | 54.00 | 17.82 | H | 9.8 |
| 14456.000000 | 37.52 | 54.00 | 16.48 | V | 11.7 |
| 16877.500000 | 39.68 | 54.00 | 14.32 | V | 16.0 |
| 17910.500000 | 40.73 | 54.00 | 13.27 | H | 17.4 |

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and Antenna Factor, the gain of the preamplifier, the cable loss. P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= P_{Mea} +Cable Loss +Antenna Factor-Gain of the preamplifier.

See below for test graphs.

Conclusion: Pass




Fig. 33 Radiated Spurious Emission (GFSK, Ch0, 1 GHz ~3 GHz)




Fig. 34 Radiated Spurious Emission (GFSK, Ch0, 3 GHz ~18 GHz)




Fig. 35 Radiated Spurious Emission (GFSK, Ch39, 1 GHz ~3 GHz)




Fig. 36 Radiated Spurious Emission (GFSK, Ch39, 3 GHz ~18 GHz)




Fig. 37 Radiated Spurious Emission (GFSK, Ch78, 1 GHz ~3 GHz)




Fig. 38 Radiated Spurious Emission (GFSK, Ch78, 3 GHz ~18 GHz)




Fig. 39 Radiated Band Edges (GFSK, Ch0, 2380GHz~2450GHz)




Fig. 40 Radiated Band Edges (GFSK, Ch78, 2450GHz~2500GHz)




Fig. 41 Radiated Spurious Emission ($\pi/4$ DQPSK, Ch0, 1 GHz ~3 GHz)




Fig. 42 Radiated Spurious Emission ($\pi/4$ DQPSK, Ch0, 3 GHz ~18 GHz)




Fig. 43 Radiated Spurious Emission ($\pi/4$ DQPSK, Ch39, 1 GHz ~3 GHz)




Fig. 44 Radiated Spurious Emission ($\pi/4$ DQPSK, Ch39, 3 GHz ~18 GHz)




Fig. 45 Radiated Spurious Emission ($\pi/4$ DQPSK, Ch78, 1 GHz ~3 GHz)




Fig. 46 Radiated Spurious Emission ($\pi/4$ DQPSK, Ch78, 3 GHz ~18 GHz)




Fig. 47 Radiated Band Edges ($\pi/4$ DQPSK, Ch0, 2380GHz~2450GHz)




Fig. 48 Radiated Band Edges ($\pi/4$ DQPSK, Ch78, 2450GHz~2500GHz)




Fig. 49 Radiated Spurious Emission (8DPSK, Ch0, 1 GHz ~3 GHz)




Fig. 50 Radiated Spurious Emission (8DPSK, Ch0, 3 GHz ~18 GHz)




Fig. 51 Radiated Spurious Emission (8DPSK, Ch39, 1 GHz ~3 GHz)




Fig. 52 Radiated Spurious Emission (8DPSK, Ch39, 3 GHz ~18 GHz)




Fig. 53 Radiated Spurious Emission (8DPSK, Ch78, 1 GHz ~3 GHz)




Fig. 54 Radiated Spurious Emission (8DPSK, Ch78, 3 GHz ~18 GHz)




Fig. 55 Radiated Band Edges (8DPSK, Ch0, 2380GHz~2450GHz)




Fig. 56 Radiated Band Edges (8DPSK, Ch78, 2450GHz~2500GHz)




Fig. 57 Radiated Spurious Emission (All Channels, 9 kHz ~30 MHz)




Fig. 58 Radiated Spurious Emission (All Channels, 30 MHz ~1 GHz)