

Fig.58. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz




Fig.59. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz




Fig.60. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz




Fig.61. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz




Fig.62. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz




Fig.63. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz

## B.6. Transmitter Spurious Emission - Radiated

**Method of Measurement:** See ANSI C63.10-2013-clause 6.4 & 6.5 & 6.6

**Measurement Limit:**

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

**Limit in restricted band:**

Frequency (MHz)	Field strength(μV/m)	Measurement distance(m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength (uV/m)	Field strength (dBuV/m)	Measurement distance (m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

**Set up:**

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The EUT and transmitting antenna shall be centered on the turntable.

**Note:**

1. A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

$P_{Mea}$  is the field strength recorded from the instrument.

The measurement results are obtained as described below:

$$\text{Result} = P_{Mea} + A_{Rpl} = P_{Mea} + \text{Cable Loss} + \text{Antenna Factor}$$

2. The range of evaluated frequency is from 9 kHz to 26GHz. Measurement value showed here only up to 6 maximum emissions noted.

**Peak Measurement results**
**GFSK Ch 0**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2383.590	60.06	5.34	32.17	22.55	74.00	13.94	V
2385.390	60.13	5.34	32.20	22.60	74.00	13.87	V
4803.500	43.74	-35.01	34.10	44.65	74.00	30.26	V
7206.000	42.50	-32.65	35.81	39.34	74.00	31.50	V
9608.000	43.72	-32.16	36.90	38.97	74.00	30.28	H
12010.000	45.70	-31.65	38.72	38.63	74.00	28.30	H

**GFSK Ch 39**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2375.400	43.61	-29.09	32.06	40.65	74.00	30.39	H
2501.000	42.84	-28.28	32.60	38.51	74.00	31.16	V
4882.000	40.90	-34.32	34.16	41.06	74.00	33.10	V
7323.000	43.60	-32.61	35.91	40.30	74.00	30.40	H
9764.000	43.60	-32.26	36.93	38.94	74.00	30.40	V
12205.000	45.58	-31.13	39.09	37.62	74.00	28.42	H

**GFSK Ch 78**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.225	60.78	5.46	32.60	22.72	74.00	13.22	H
2484.600	60.32	5.46	32.60	22.26	74.00	13.68	H
4960.000	44.08	-34.82	34.26	44.63	74.00	29.92	V
7440.000	42.76	-32.54	35.80	39.50	74.00	31.24	H
9920.000	43.67	-32.17	37.10	38.74	74.00	30.33	H
12400.000	45.78	-31.31	39.00	38.09	74.00	28.22	H

**$\pi/4$  DQPSK Ch 0**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2386.538	59.86	5.35	32.21	22.30	74.00	14.14	H
2387.070	60.63	5.35	32.22	23.06	74.00	13.37	V
4804.000	41.62	-35.01	34.10	42.54	74.00	32.38	V
7206.000	42.48	-32.65	35.81	39.31	74.00	31.52	V
9608.000	43.19	-32.16	36.90	38.44	74.00	30.81	V
12010.000	45.77	-31.65	38.72	38.70	74.00	28.23	V

 **$\pi/4$  DQPSK Ch 39**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2373.200	41.97	-29.15	32.03	39.09	74.00	32.03	V
2500.800	43.43	-28.27	32.60	39.09	74.00	30.57	V
4882.000	43.12	-34.32	34.16	43.28	74.00	30.88	V
7323.000	42.24	-32.61	35.91	38.94	74.00	31.76	H
9764.000	43.08	-32.26	36.93	38.42	74.00	30.92	H
12205.000	44.89	-31.13	39.09	36.93	74.00	29.11	H

 **$\pi/4$  DQPSK Ch 78**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2485.060	61.27	5.46	32.60	23.21	74.00	12.73	V
2484.925	61.51	5.46	32.60	23.45	74.00	12.49	V
4960.000	43.82	-34.82	34.26	44.38	74.00	30.18	V
7440.000	42.54	-32.54	35.80	39.28	74.00	31.46	H
9920.000	43.61	-32.17	37.10	38.68	74.00	30.39	V
12400.000	44.69	-31.31	39.00	37.00	74.00	29.31	H

**8DPSK Ch 0**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2384.466	59.97	5.34	32.18	22.45	74.00	14.03	H
2386.034	59.63	5.34	32.21	22.08	74.00	14.37	H
4804.000	41.93	-35.01	34.10	42.85	74.00	32.07	V
7206.000	43.90	-32.65	35.81	40.74	74.00	30.10	H
9608.000	43.17	-32.16	36.90	38.43	74.00	30.83	V
12010.000	45.19	-31.65	38.72	38.12	74.00	28.81	H

**8DPSK Ch 39**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2375.000	42.44	-29.10	32.05	39.49	74.00	31.56	V
2498.600	43.77	-28.15	32.60	39.32	74.00	30.23	H
4882.000	41.33	-34.32	34.16	41.49	74.00	32.67	H
7323.000	42.84	-32.61	35.91	39.54	74.00	31.16	V
9764.000	44.16	-32.26	36.93	39.49	74.00	29.84	H
12205.000	45.22	-31.13	39.09	37.26	74.00	28.78	H

**8DPSK Ch 78**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2483.970	60.65	5.46	32.60	22.59	74.00	13.35	H
2484.525	61.04	5.46	32.60	22.98	74.00	12.96	H
4960.000	40.06	-34.82	34.26	40.62	74.00	33.94	V
7440.000	42.70	-32.54	35.80	39.44	74.00	31.30	H
9920.000	42.34	-32.17	37.10	37.41	74.00	31.66	V
12400.000	46.10	-31.31	39.00	38.41	74.00	27.90	H

**Average Measurement results**
**GFSK Ch 0**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2365.612	45.24	5.31	31.92	8.01	54.00	8.76	V
2384.587	45.24	5.34	32.19	7.72	54.00	8.76	V
4803.750	34.38	-35.01	34.10	35.29	54.00	19.62	H
7206.150	31.26	-32.65	35.81	28.10	54.00	22.74	H
9607.900	32.15	-32.16	36.90	27.41	54.00	21.85	V
12009.975	33.59	-31.65	38.72	26.52	54.00	20.41	H

**GFSK Ch 39**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2363.512	45.32	5.31	31.89	8.12	54.00	8.68	V
2391.487	45.66	5.36	32.28	8.02	54.00	8.34	V
4882.075	29.05	-34.32	34.16	29.21	54.00	24.95	V
7323.150	31.12	-32.61	35.91	27.82	54.00	22.88	V
9763.900	31.86	-32.26	36.93	27.19	54.00	22.14	H
12204.975	33.80	-31.13	39.09	25.84	54.00	20.20	H

**GFSK Ch 78**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2492.137	48.07	5.47	32.60	10.00	54.00	5.93	V
2511.562	48.29	5.49	32.62	10.18	54.00	5.71	V
4960.000	35.97	-34.82	34.26	36.53	54.00	18.03	H
7440.150	30.64	-32.54	35.80	27.38	54.00	23.36	V
9919.900	31.52	-32.17	37.10	26.60	54.00	22.48	H
12399.975	33.41	-31.31	39.00	25.71	54.00	20.59	H



**$\pi/4$  DQPSK Ch 0**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2385.412	45.61	5.34	32.20	8.07	54.00	8.39	V
2388.300	45.67	5.35	32.24	8.08	54.00	8.33	V
4803.750	30.59	-35.01	34.10	31.50	54.00	23.41	V
7206.150	31.27	-32.65	35.81	28.11	54.00	22.73	H
9607.900	32.19	-32.16	36.90	27.45	54.00	21.81	V
12009.975	33.55	-31.65	38.72	26.48	54.00	20.45	H

 **$\pi/4$  DQPSK Ch 39**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2458.987	47.93	5.43	32.60	9.90	54.00	6.07	V
2473.462	47.93	5.45	32.60	9.88	54.00	6.07	V
4881.750	30.79	-34.32	34.16	30.95	54.00	23.21	V
7323.150	31.14	-32.61	35.91	27.84	54.00	22.86	H
9763.900	31.88	-32.26	36.93	27.21	54.00	22.12	V
12204.975	33.78	-31.13	39.09	25.82	54.00	20.22	H

 **$\pi/4$  DQPSK Ch 78**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2500.762	48.05	5.48	32.60	9.96	54.00	5.95	V
2508.112	48.21	5.49	32.62	10.11	54.00	5.79	V
4959.750	30.51	-34.82	34.26	31.06	54.00	23.49	V
7440.150	30.66	-32.54	35.80	27.40	54.00	23.34	H
9919.900	31.55	-32.17	37.10	26.62	54.00	22.45	H
12399.975	33.38	-31.31	39.00	25.68	54.00	20.62	V

**8DPSK Ch 0**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2386.875	45.73	5.35	32.22	8.16	54.00	8.27	V
2389.238	45.69	5.35	32.25	8.09	54.00	8.31	V
4804.075	32.02	-35.01	34.10	32.93	54.00	21.98	V
7206.150	31.17	-32.65	35.81	28.01	54.00	22.83	H
9607.900	32.22	-32.16	36.90	27.47	54.00	21.78	H
12009.975	33.66	-31.65	38.72	26.59	54.00	20.34	H

**8DPSK Ch 39**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2437.800	47.58	5.41	32.55	9.62	54.00	6.42	V
2444.475	47.61	5.41	32.58	9.62	54.00	6.39	V
4882.075	31.69	-34.32	34.16	31.85	54.00	22.31	H
7323.150	31.17	-32.61	35.91	27.88	54.00	22.83	V
9736.900	31.97	-32.18	36.87	27.28	54.00	22.03	H
12204.975	33.79	-31.13	39.09	25.83	54.00	20.21	V

**8DPSK Ch 78**

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2483.662	47.97	5.46	32.60	9.91	54.00	6.03	V
2484.900	48.03	5.46	32.60	9.96	54.00	5.97	V
4881.750	31.75	-34.32	34.16	31.91	54.00	22.25	H
7440.150	30.72	-32.54	35.80	27.47	54.00	23.28	V
9919.900	31.56	-32.17	37.10	26.63	54.00	22.44	V
12399.975	33.48	-31.31	39.00	25.78	54.00	20.52	H

**Conclusion: Pass**

## B.7. Time of Occupancy (Dwell Time)

**Method of Measurement: See ANSI C63.10-clause 7.8.4**

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW  $\geq$  RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

### Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

### Measurement Result:

#### For GFSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
		Fig.	Value	Fig.	Value		
39	DH1	Fig.64	0.38	Fig.65	320	121.6	P
	DH3	Fig.66	1.63	Fig.67	112	182.56	P
	DH5	Fig.68	2.87	Fig.69	51	146.37	P

#### For $\pi/4$ DQPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
		Fig.	Value	Fig.	Value		
39	2DH1	Fig.70	0.38	Fig.71	319	121.22	P
	2DH3	Fig.72	1.64	Fig.73	98	160.72	P
	2DH5	Fig.74	2.88	Fig.75	65	187.2	P

**For 8DPSK**

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	3DH1	Fig.76	0.38	Fig.77	320	121.6	P
	3DH3	Fig.78	1.63	Fig.79	108	176.04	P
	3DH5	Fig.80	2.89	Fig.81	75	216.75	P

**Conclusion: PASS**

**Test graphs as below:**




Fig.64. Time of occupancy (Dwell Time): Channel 39, Packet DH1




Fig.65. Number of Transmissions Measurement: Channel 39,Packet DH1




Fig.66. Time of occupancy (Dwell Time): Channel 39, Packet DH3




Fig.67. Number of Transmissions Measurement: Channel 39,Packet DH3




Fig.68. Time of occupancy (Dwell Time): Channel 39, Packet DH5




Fig.69. Number of Transmissions Measurement: Channel 39,Packet DH5




Fig.70. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1




Fig.71. Number of Transmissions Measurement: Channel 39,Packet 2-DH1




Fig.72. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3






Fig.73. Number of Transmissions Measurement: Channel 39,Packet 2-DH3




Fig.74. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5




Fig.75. Number of Transmissions Measurement: Channel 39,Packet 2-DH5




Fig.76. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1




Fig.77. Number of Transmissions Measurement: Channel 39,Packet 3-DH1




Fig.78. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3




Fig.79. Number of Transmissions Measurement: Channel 39,Packet 3-DH3




Fig.80. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5




Fig.81. Number of Transmissions Measurement: Channel 39,Packet 3-DH5

## B.8. 20dB Bandwidth

**Method of Measurement: See ANSI C63.10-clause 6.9.2**

Measurement Procedure - Unwanted Emissions

1. Set RBW = 30kHz.
2. Set VBW = 100 kHz.
3. Set span to 3MHz
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

Use NdB Down function of the SA to measure the 20dB Bandwidth

\* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for “carrier frequency separation” test case, in Annex A.8.

### Measurement Results:

#### For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.82	940.50	NA
39	Fig.83	940.50	NA
78	Fig.84	940.50	NA

#### For $\pi/4$ DQPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.85	1223.25	NA
39	Fig.86	1224.00	NA
78	Fig.87	1222.50	NA

#### For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.88	1261.50	NA
39	Fig.89	1257.75	NA
78	Fig.90	1233.00	NA

**Conclusion: NA**

**Test graphs as below:**




Fig.82. 20dB Bandwidth: GFSK, Channel 0




Fig.83. 20dB Bandwidth: GFSK, Channel 39




Fig.84. 20dB Bandwidth: GFSK, Channel 78




Fig.85. 20dB Bandwidth:  $\pi/4$  DQPSK, Channel 0






Fig.86. 20dB Bandwidth:  $\pi/4$  DQPSK, Channel 39




Fig.87. 20dB Bandwidth:  $\pi/4$  DQPSK, Channel 78




Fig.88. 20dB Bandwidth: 8DPSK, Channel 0




Fig.89. 20dB Bandwidth: 8DPSK, Channel 39




Fig.90. 20dB Bandwidth: 8DPSK, Channel 78

## B.9. Carrier Frequency Separation

**Method of Measurement: See ANSI C63.10-clause 7.8.2**

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

\* Comment: This limit should be over 25 kHz or  $(2/3) * 20\text{dB}$  bandwidth, whichever is greater.

### Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth

### Measurement Result:

#### For GFSK

Channel	Carrier frequency separation (kHz)	Conclusion	
39	Fig.91	1008.75	P

#### For $\pi/4$ DQPSK

Channel	Carrier frequency separation (kHz)	Conclusion	
39	Fig.92	985.50	P

#### For 8DPSK

Channel	Carrier frequency separation (kHz)	Conclusion	
39	Fig.93	1035.75	P

**Conclusion: PASS**

**Test graphs as below:**




Fig.91. Carrier frequency separation measurement: GFSK, Channel 39




Fig.92. Carrier frequency separation measurement:  $\pi/4$  DQPSK, Channel 39




Fig.93. Carrier frequency separation measurement: 8DPSK, Channel 39

## B.10. Number of Hopping Channels

**Method of Measurement: See ANSI C63.10-clause 7.8.3**

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = the frequency band of operation
- RBW = 500kHz
- VBW = 500kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii)	At least 15 non-overlapping channels

### Measurement Result:

#### For GFSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.94	79	P
40~78	Fig.95		

#### For $\pi/4$ DQPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.96	79	P
40~78	Fig.97		

#### For 8DPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.98	79	P
40~78	Fig.99		

**Conclusion: PASS**

**Test graphs as below:**




Fig.94. Number of hopping frequencies: GFSK, Channel 0 - 39




Fig.95. Number of hopping frequencies: GFSK, Channel 40 - 78






Fig.96. Number of hopping frequencies:  $\pi/4$  DQPSK, Channel 0 - 39




Fig.97. Number of hopping frequencies:  $\pi/4$  DQPSK, Channel 40 - 78




Fig.98. Number of hopping frequencies: 8DPSK, Channel 0 - 39




Fig.99. Number of hopping frequencies: 8DPSK, Channel 40 - 78

## B.11. AC Powerline Conducted Emission

### Method of Measurement:

See Clause 6.2 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

The conducted emissions from the AC port of the EUT are measured in a shielding room. The EUT is connected to a Line Impedance Stabilization Network (LISN). An overview sweep with peak detection was performed. The measurements were performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver: Quasi-Peak / Average Detector.


The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/IF bandwidth
0.15-30	9kHz

### Test Condition:

Voltage (V)	Frequency (Hz)
120	60

### Measurement Setup



**Measurement Result and limit:**
**EUT ID: UT19a**

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	66 to 56	Fig.B.11.1	Fig.B.11.2	<b>P</b>
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.


Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	56 to 46	Fig.B.11.1	Fig.B.11.2	<b>P</b>
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

**Conclusion: Pass**
**Test graphs as below:**

Note: The measurement results showed here are worst cases.



**Fig.B.11.1 AC Powerline Conducted Emission- bluetooth**


Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.159000	50.8	1000.0	9.000	On	L1	26.8	14.7	65.5
0.177000	45.3	1000.0	9.000	On	N	23.5	19.4	64.6
0.222000	36.3	1000.0	9.000	On	N	19.7	26.5	62.7
0.411000	28.0	1000.0	9.000	On	N	19.8	29.6	57.6
0.523500	46.3	1000.0	9.000	On	N	19.8	9.7	56.0
1.117500	35.8	1000.0	9.000	On	N	19.6	20.2	56.0

**Final Result 2**

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.154500	38.4	1000.0	9.000	On	N	27.7	17.3	55.8
0.523500	41.7	1000.0	9.000	On	N	19.8	4.3	46.0
0.618000	32.0	1000.0	9.000	On	N	19.7	14.0	46.0
0.946500	34.0	1000.0	9.000	On	N	19.7	12.0	46.0
1.014000	33.2	1000.0	9.000	On	N	19.6	12.8	46.0
1.441500	29.8	1000.0	9.000	On	N	19.6	16.2	46.0



**Fig.B.11.2 AC Powerline Conducted Emission-Idle**

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.159000	55.2	1000.0	9.000	On	L1	26.8	10.3	65.5
0.208500	42.2	1000.0	9.000	On	N	19.7	21.0	63.3
0.249000	39.3	1000.0	9.000	On	N	19.7	22.5	61.8
0.519000	45.2	1000.0	9.000	On	N	19.8	10.8	56.0
0.577500	39.0	1000.0	9.000	On	N	19.7	17.0	56.0
0.955500	38.5	1000.0	9.000	On	N	19.7	17.5	56.0

**Final Result 2**

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.514500	42.4	1000.0	9.000	On	N	19.8	3.6	46.0
0.573000	33.6	1000.0	9.000	On	N	19.7	12.4	46.0
0.613500	31.4	1000.0	9.000	On	N	19.7	14.6	46.0
0.964500	34.8	1000.0	9.000	On	N	19.7	11.2	46.0
1.720500	30.0	1000.0	9.000	On	N	19.6	16.0	46.0
2.548500	31.3	1000.0	9.000	On	N	19.6	14.8	46.0

## ANNEX C: Accreditation Certificate

<p>United States Department of Commerce National Institute of Standards and Technology</p>  	
<hr/> <b>Certificate of Accreditation to ISO/IEC 17025:2017</b> <hr/>	
NVLAP LAB CODE: 600118-0	
<b>Telecommunication Technology Labs, CAICT</b> Beijing China	
<i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i>	
<b>Electromagnetic Compatibility &amp; Telecommunications</b>	
<i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i>	
<hr/> 2022-10-01 through 2023-09-30 <i>Effective Dates</i>	 For the National Voluntary Laboratory Accreditation Program

\*\*\*END OF REPORT\*\*\*