



**FCC PART 15C  
TESTREPORT  
No. I16Z42442-SRD01**

**for**

**TCL Mobile Communication Co. Ltd. Huizhou**

**Door & Window Sensor**

**Model Name:DS01**

**with**

**FCC ID: 2ACCJBC04**

**Hardware Version: V05**

**Software Version: DS01\_00\_01.00\_17**

**Issued Date: 2017-01-17**



**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

**Test Laboratory:**

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email:[cttl\\_terminals@catr.cn](mailto:cttl_terminals@catr.cn), website:[www.chinattl.com](http://www.chinattl.com)

©Copyright. All rights reserved by CTTL.



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I16Z42442-SRD01	Rev.0	1st edition	2017-01-09
I16Z42442-SRD01	Rev.1	2nd edition	2017-01-17



## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>5</b>
<b>1.1. TESTING LOCATION .....</b>	<b>5</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>5</b>
<b>1.3. PROJECT DATA .....</b>	<b>5</b>
<b>1.4. SIGNATURE.....</b>	<b>5</b>
<b>2. CLIENT INFORMATION.....</b>	<b>6</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>6</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>6</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>7</b>
<b>3.1. ABOUT EUT .....</b>	<b>7</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT .....</b>	<b>7</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE .....</b>	<b>7</b>
<b>3.4. GENERAL DESCRIPTION .....</b>	<b>8</b>
<b>3.5. INTERPRETATION OF THE TEST ENVIRONMENT .....</b>	<b>8</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>8</b>
<b>4.1. DOCUMENTS SUPPLIED BY APPLICANT .....</b>	<b>8</b>
<b>4.2. REFERENCE DOCUMENTS FOR TESTING .....</b>	<b>8</b>
<b>5. TEST RESULTS .....</b>	<b>9</b>
<b>5.1. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>5.2. STATEMENTS.....</b>	<b>9</b>
<b>5.3. TEST CONDITIONS.....</b>	<b>9</b>
<b>6. TEST FACILITIES UTILIZED .....</b>	<b>10</b>
<b>7. MEASUREMENT UNCERTAINTY .....</b>	<b>11</b>
<b>7.1. MAXIMUM OUTPUT POWER .....</b>	<b>11</b>
<b>7.2. PEAK POWER SPECTRAL DENSITY.....</b>	<b>11</b>
<b>7.3. DTS 6-DB SIGNAL BANDWIDTH .....</b>	<b>11</b>
<b>7.4. BAND EDGES COMPLIANCE.....</b>	<b>11</b>
<b>7.5. TRANSMITTER SPURIOUS EMISSION.....</b>	<b>11</b>
<b>7.6. AC POWER-LINE CONDUCTED EMISSION .....</b>	<b>11</b>
<b>ANNEX A: DETAILED TEST RESULTS.....</b>	<b>12</b>



<b>A.1. MEASUREMENT METHOD.....</b>	<b>12</b>
<b>A.2. MAXIMUM OUTPUT POWER.....</b>	<b>13</b>
A.2.1. PEAK OUTPUT POWER-CONDUCTED .....	13
A.2.2. AVERAGE OUTPUT POWER-CONDUCTED.....	13
<b>A.3. PEAK POWER SPECTRAL DENSITY.....</b>	<b>15</b>
<b>A.4. DTS 6-DB SIGNAL BANDWIDTH .....</b>	<b>17</b>
<b>A.5. BAND EDGES COMPLIANCE .....</b>	<b>20</b>
<b>A.6. TRANSMITTER SPURIOUS EMISSION.....</b>	<b>22</b>
A.6.1 TRANSMITTER SPURIOUS EMISSION – CONDUCTED .....	22
A.6.2 TRANSMITTER SPURIOUS EMISSION - RADIATED.....	36

## **1. Test Laboratory**

### **1.1. Testing Location**

Conducted testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China100191

Radiated testing Location: CTTL(BDA)

Address: No. 18 Jia Kangding Street, BDA District, Beijing, P. R.  
China 100191

### **1.2. Testing Environment**

Normal Temperature: 15-35°C

Extreme Temperature: -10/+55°C

Relative Humidity: 20-75%

### **1.3. Project data**

Testing Start Date: 2016-12-23


Testing End Date: 2017-01-09

### **1.4. Signature**




---

**Jiang Xue**  
**(Prepared this test report)**



---

**Zheng Wei**  
**(Reviewed this test report)**



---

**Lv Songdong**  
**(Approved this test report)**



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5F, C-Tower, No.232, Liangjing Road, Zhangjiang High-tech Park,  
Pudong, Shanghai, China  
Contact Person: Liu Feng  
Contact Email liu.feng@tcl.com  
Telephone: 0755-33035419  
Fax: 0755-33035419

### **2.2. Manufacturer Information**

Company Name: TCL Mobile Communication Co. Ltd. Huizhou  
Address /Post: 70 Huifeng 4rd., ZhongKai High-Technology Development District,  
Huizhou, Guangdong, PRC. 516006  
Contact Person: Liu Feng  
Contact Email liu.feng@tcl.com  
Telephone: 0755-33035419  
Fax: 0755-33035460

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	Door & Window Sensor
Model name	DS01
FCC ID	2ACCJBC04
IC ID	/
With WLAN Function	Yes
Frequency Range	ISM 2400MHz~2483.5MHz
Type of Modulation	DQPSK
Number of Channels	11
Antenna	Integral Antenna
MAX Conducted Power	11.21dBm(OFDM)
Power Supply	3.0V DC by Battery

#### **3.2. Internal Identification of EUT**

<b>EUT ID*</b>	<b>SN or IMEI</b>	<b>HW Version</b>	<b>SW Version</b>
EUT1	/	V05	DS01_00_01.00_17
EUT2	/	V05	DS01_00_01.00_17

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE**

<b>AE ID*</b>	<b>Description</b>	<b>SN</b>
---------------	--------------------	-----------

\*AE ID: is used to identify the test sample in the lab internally.

### **3.4. General Description**

The Equipment under Test (EUT) is a model of Door & Window Sensor with integrated antenna and inbuilt battery.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

### **3.5. Interpretation of the Test Environment**

For the test methods, the test environment uncertainty figures correspond to an expansion factor  $k=2$ .

Measurement Uncertainty

Parameter	Uncertainty
temperature	0.48°C
humidity	2 %
DC voltages	0.003V

## **4. Reference Documents**

### **4.1. Documents supplied by applicant**

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

### **4.2. Reference Documents for testing**

The following documents listed in this section are referred for testing.

Reference	Title	Version
	FCC CFR 47, Part 15, Subpart C:	
	15.205 Restricted bands of operation;	
FCC Part15	15.209 Radiated emission limits, general requirements;	2015
	15.247 Operation within the bands 902-928MHz, 2400-2483.5 MHz, and 5725-5850 MHz.	
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	2013



## 5. Test Results

### 5.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.247 (b)	/	<b>P</b>
Peak Power Spectral Density	15.247 (e)	/	<b>P</b>
Occupied 6dB Bandwidth	15.247 (a)	/	<b>P</b>
Band Edges Compliance	15.247 (d)	/	<b>P</b>
Transmitter Spurious Emission - Conducted	15.247 (d)	/	<b>P</b>
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	/	<b>P</b>
AC Powerline Conducted Emission	15.107, 15.207	/	<b>NA</b>

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NP	Not Perform, The test was not performed by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard
F	Fail, The EUT does not comply with the essential requirements in the standard

### 5.2. Statements

The test cases as listed in section 5.1 of this report for the EUT specified in section 3 was performed by CTTL and according to the standards or reference documents listed in section 4.2 The EUT met all requirements of the standards or reference documents, and only the WLAN function was tested in this report.

The EUT is tested in engineering model, and the duty is about 100%.

### 5.3. Test Conditions

T nom	Normal Temperature
T min	Low Temperature
T max	High Temperature
V nom	Normal Voltage

For this report, if the test cases listed above are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	T nom	26°C
Voltage	V nom	3.0V (By battery)
Humidity	H nom	44%

## 6. Test Facilities Utilized

### Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	2016-06-07	2017-06-06
2	Test Receiver	ESCI	100344	Rohde & Schwarz	2016-03-02	2017-03-01
3	LISN	ESH3Z2	357881052	Rohde & Schwarz	2016-10-06	2017-10-05
4	Shielding Room	S81	/	ETS-Lindgren	/	/

### Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Calibration Due date
1	Test Receiver	ESU26	100235	Rohde & Schwarz	2016-03-03	2017-03-02
2	Loop antenna	HFH2-Z2	829324/007	Rohde & Schwarz	2014-12-17	2017-12-16
3	BiLog Antenna	VULB9163	301	Schwarzbeck	2014-12-17	2017-12-16
4	Dual-Ridge Waveguide Horn Antenna	3115	6914	EMCO	2014-12-16	2017-12-15
5	Dual-Ridge Waveguide Horn Antenna	3116	2661	ETS-Lindgren	2014-06-18	2017-06-17
6	Vector Signal Analyzer	FSV40	101047	Rohde & Schwarz	2016-06-29	2017-06-28
7	Semi-anechoic chamber	/	CT000332-1074	Frankonia German	/	/

## 7. Measurement Uncertainty

### 7.1. Maximum Output Power

Measurement Uncertainty: 0.339dB,k=1.96

### 7.2. Peak Power Spectral Density

Measurement Uncertainty: 0.705dBm/MHz,k=1.96

### 7.3. DTS 6-dB Signal Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

### 7.4. Band Edges Compliance

Measurement Uncertainty : 0.62dBm,k=1.96

### 7.5. Transmitter Spurious Emission

#### Conducted (k=1.96)

Frequency Range	Uncertainty(dBm)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

#### Radiated (k=2)

Frequency Range	Uncertainty(dBm)
$30\text{MHz} \leq f \leq 1\text{GHz}$	4.86
$1\text{GHz} \leq f \leq 18\text{GHz}$	5.26
$18\text{GHz} \leq f \leq 40\text{GHz}$	5.28

### 7.6. AC Power-line Conducted Emission

Measurement Uncertainty : 3.38dBm,k=2

## **ANNEX A: Detailed Test Results**

### **A.1. Measurement Method**

#### **A.1.1. Conducted Measurements**

Connect the EUT to the test system as Fig.A.1.1.1 shows.

Set the EUT to the required work mode.

Set the EUT to the required channel.

Set the Vector Signal Analyzer and start measurement.

Record the values. Vector Signal Analyzer




Fig.A.1.1.1: Test Setup Diagram for Conducted Measurements

#### **A.1.2. Radiated Emission Measurements**

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;




Fig.A.1.2.1: Test Setup Diagram for Radiated Measurements



**A.2. Maximum Output Power**

**Method of Measurement: See ANSI C63.10-2013-clause 11.9.1.2**

- a) Set the RBW = 1MHz.
- b) Set the VBW = 3MHz.
- c) Set the span  $\geq [1.5 \times \text{DTS bandwidth}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument’s band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector).

**Measurement Limit:**

Standard	Limit (dBm)
FCC CRF Part 15.247(b)	< 30

**EUT ID: EUT2**

**A.2.1. Peak Output Power-conducted**

**Measurement Results:**

Mode	Test Result (dBm)		
	2405MHz (Ch11)	2440MHz (Ch18)	2480 MHz (Ch26)
ZigBee	10.68	11.21	10.82

**Conclusion: Pass**

**A.2.2. Average Output Power-conducted**

**Method of Measurement: See ANSI C63.10-2013-clause 11.9.2.2.2**

The procedure for this method is as follows:

- a) Set span = 3MHz.
- b) Set RBW = 100 kHz.
- c) Set VBW = 300 kHz.
- d) Number of points in sweep = 625
- e) Sweep time = auto.
- f) Detector = RMS.
- g) The trigger shall be set to “free run.”
- h) Trace average 100 traces in power averaging (rms) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges.



Mode	Test Result (dBm)		
	2405MHz (Ch11)	2440MHz (Ch18)	2480 MHz (Ch26)
ZigBee	7.45	7.43	6.64

**Conclusion: Pass**

### A.3. Peak Power Spectral Density

**Method of Measurement: See ANSI C63.10-2013-clause 11.10.2**

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to RBW = 3 kHz.
- Set the VBW = 10 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

**Measurement Limit:**


Standard	Limit
FCC CRF Part 15.247(e)	< 8 dBm/3 kHz

**Measurement Results:**

Mode	Frequency (MHz)	Power Spectral Density ( dBm / MHz)		Conclusion
Zigbee	2405(CH11)	Fig.B.3.1	-4.30	P
	2440(CH18)	Fig.B.3.2	-3.49	P
	2480(CH26)	Fig.B.3.3	-4.21	P

**Conclusion: Pass**

**Test graphs as below:**



**Fig.A.3.1 Power Spectral Density(802.11b,Ch 11)**




Fig.A.3.2 Power Spectral Density (802.11b, Ch 18)




Fig.A.3.3 Power Spectral Density (802.11b, Ch 26)



**A.4. DTS 6-dB Signal Bandwidth**

**Method of Measurement: See ANSI C63.10-2013 section 11.8.1.**

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) = 300 kHz.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**Measurement Limit:**

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500


**EUT ID: EUT2**

**Measurement Result:**


Mode	Frequency (MHz)	Occupied Channel Bandwidth (MHz)	Conclusion
Zigbee	2405	Fig.B.4.1. 1.54	<b>P</b>
	2440	Fig.B.4.2. 1.56	<b>P</b>
	2480	Fig.B.4.3. 1.56	<b>P</b>

**Conclusion: Pass**

**Test graphs as below:**



**Fig.A.4.1 Occupied 6dB Bandwidth( Zigbee Channel 11)**



**Fig.A.4.2 Occupied 6dB Bandwidth (Zigbee Channel 18)**




Fig.A.4.3 Occupied 6dB Bandwidth (Zigbee Channel 26)

### A.5. Band Edges Compliance

**Method of Measurement: See ANSI C63.10-2013-clause 6.10.4**

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below.

- a) Set Span = 100MHz
- b) Sweep Time: coupled
- c) Set the RBW= 100 kHz
- c) Set the VBW= 300 kHz
- d) Detector: Peak
- e) Trace: Max hold

**Measurement Limit:**

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20


**EUT ID: EUT2**

**Measurement Result:**

Mode	Channel	Test Results	Conclusion
Zigbee	11	Fig.A.5.1	<b>P</b>
	26	Fig.A.5.2	<b>P</b>

**Conclusion: Pass**

**Test graphs as below:**



**Fig.A.5.1 Band Edges (Zigbee Channel 11)**




Fig.A.5.2 Band Edges (Zigbee Channel 26)



**A.6. Transmitter Spurious Emission**

**A.6.1 Transmitter Spurious Emission – Conducted**

**Method of Measurement: See ANSI C63.10-2013-clause 11.11.2**

Establish a reference level by using the following procedure:

- a) Set instrument center frequency to DTS channel center frequency
- b) Set the span to  $\geq 1.5$  times the DTS bandwidth
- c) Set the RBW= 100 kHz
- d) Set the VBW= 300 kHz
- e) Detector = Peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW = 300 kHz.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

**Measurement Limit:**

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

**EUT ID: EUT2**

**Measurement Results:**

802.11b mode

MODE	Channel	Frequency Range	Test Results	Conclusion
Zigbee	11	2.412 GHz	Fig.A.6.1.1	P
		30 MHz ~ 1 GHz	Fig.A.6.1.2	P
		1 GHz ~ 2.5 GHz	Fig.A.6.1.3	P
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.4	P
		7.5 GHz ~ 10 GHz	Fig.A.6.1.5	P
		10 GHz ~ 15 GHz	Fig.A.6.1.6	P
		15 GHz ~ 20 GHz	Fig.A.6.1.7	P
		20 GHz ~ 26 GHz	Fig.A.6.1.8	P
	18	2.437 GHz	Fig.A.6.1.9	P
		30 MHz ~ 1 GHz	Fig.A.6.1.10	P
		1 GHz ~ 2.5 GHz	Fig.A.6.1.11	P
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.12	P
		7.5 GHz ~ 10 GHz	Fig.A.6.1.13	P
		10 GHz ~ 15 GHz	Fig.A.6.1.14	P
		15 GHz ~ 20 GHz	Fig.A.6.1.15	P
		20 GHz ~ 26 GHz	Fig.A.6.1.16	P
	26	2.462 GHz	Fig.A.6.1.17	P
		30 MHz ~ 1 GHz	Fig.A.6.1.18	P
		1 GHz ~ 2.5 GHz	Fig.A.6.1.19	P
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.20	P
		7.5 GHz ~ 10 GHz	Fig.A.6.1.21	P
		10 GHz ~ 15 GHz	Fig.A.6.1.22	P
		15 GHz ~ 20 GHz	Fig.A.6.1.23	P
		20 GHz ~ 26 GHz	Fig.A.6.1.24	P

Conclusion: Pass

Test graphs as below:



Fig.A.6.1.1 Transmitter Spurious Emission - Conducted (Zigbee Channel 11, Center Frequency)






Fig.A.6.1.2 Transmitter Spurious Emission - Conducted (Zigbee Channel 11, 30 MHz-1 GHz)







**Fig.A.6.1.3 Transmitter Spurious Emission - Conducted (Zigbee Channel 11, 1 GHz-2.5 GHz)**




**Fig.A.6.1.4 Transmitter Spurious Emission - Conducted (Zigbee Channel 11, 2.5 GHz-7.5 GHz)**




**Fig.A.6.1.5 Transmitter Spurious Emission - Conducted (Zigbee Channel 11, 7.5 GHz-10 GHz)**



**Fig.A.6.1.6 Transmitter Spurious Emission - Conducted (Zigbee Channel 11, 10 GHz-15 GHz)**




**Fig.A.6.1.7 Transmitter Spurious Emission - Conducted (Zigbee Channel 11, 15 GHz-20 GHz)**




**Fig.A.6.1.8 Transmitter Spurious Emission - Conducted (Zigbee Channel 11, 20 GHz-26 GHz)**




**Fig.A.6.1.9 Transmitter Spurious Emission - Conducted (Zigbee Channel 18, Center Frequency)**




**Fig.A.6.1.10 Transmitter Spurious Emission - Conducted (Zigbee Channel 18, 30 MHz-1 GHz)**




**Fig.A.6.1.11 Transmitter Spurious Emission - Conducted (Zigbee Channel 18, 1 GHz-2.5 GHz)**




**Fig.A.6.1.12 Transmitter Spurious Emission - Conducted (Zigbee Channel 18, 2.5 GHz-7.5 GHz)**




**Fig.A.6.1.13 Transmitter Spurious Emission - Conducted (Zigbee Channel 18, 7.5 GHz-10 GHz)**




**Fig.A.6.1.14 Transmitter Spurious Emission - Conducted (Zigbee Channel 18, 10 GHz-15 GHz)**




**Fig.A.6.1.15 Transmitter Spurious Emission - Conducted (Zigbee Channel 18, 15 GHz-20 GHz)**



**Fig.A.6.1.16 Transmitter Spurious Emission - Conducted (Zigbee Channel 18, 20 GHz-26 GHz)**




**Fig.A.6.1.17 Transmitter Spurious Emission - Conducted (Zigbee Channel 26, Center Frequency)**




**Fig.A.6.1.18 Transmitter Spurious Emission - Conducted (Zigbee Channel 26, 30 MHz-1 GHz)**







**Fig.A.6.1.19 Transmitter Spurious Emission - Conducted (Zigbee Channel 26, 1 GHz-2.5 GHz)**




**Fig.A.6.1.20 Transmitter Spurious Emission - Conducted (Zigbee Channel 26, 2.5 GHz-7.5 GHz)**




**Fig.A.6.1.21 Transmitter Spurious Emission - Conducted (Zigbee Channel 26, 7.5 GHz-10 GHz)**



**Fig.A.6.1.22 Transmitter Spurious Emission - Conducted (Zigbee Channel 26, 10 GHz-15 GHz)**



**Fig.A.6.1.23 Transmitter Spurious Emission - Conducted (Zigbee Channel 26, 15 GHz-20 GHz)**



**Fig.A.6.1.24 Transmitter Spurious Emission - Conducted (Zigbee Channel 26, 20 GHz-26 GHz)**

**A.6.2 Transmitter Spurious Emission - Radiated**

**Method of Measurement: See ANSI C63.10-2013-clause 6.4 &6.5 & 6.6**

**Measurement Limit:**

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

**Limit in restricted band:**

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Frequency (MHz)	Field strength(µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

**Test Condition**

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

**EUT ID: EUT1**

**Measurement Results:**

**Zigbee**

Mode	Channel	Frequency Range	Test Results	Conclusion
Zigbee	Power	2.38GHz ~2.45GHz	Fig.A.6.2.1	<b>P</b>
	11	1 GHz ~ 3 GHz	Fig.A.6.2.2	<b>P</b>
		3 GHz ~ 18 GHz	Fig.A.6.2.3	<b>P</b>
	18	9 kHz ~30 MHz	Fig.A.6.2.4	<b>P</b>
		30 MHz ~1 GHz	Fig.A.6.2.5	<b>P</b>
		1 GHz ~ 3 GHz	Fig.A.6.2.6	<b>P</b>
		3 GHz ~ 18 GHz	Fig.A.6.2.7	<b>P</b>
		18 GHz~ 26.5 GHz	Fig.A.6.2.8	<b>P</b>
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.9	<b>P</b>
	26	1 GHz ~ 3 GHz	Fig.A.6.2.10	<b>P</b>
		3 GHz ~ 18 GHz	Fig.A.6.2.11	<b>P</b>

**Conclusion: Pass**

**Note:**

A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

$P_{Mea}$  is the field strength recorded from the instrument.

The measurement results are obtained as described below:

$$\text{Result} = P_{Mea} + A_{Rpl} = P_{Mea} + \text{Cable Loss} + \text{Antenna Factor}$$

**Average Result:**

**Zigbee**

**Ch11**

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P <sub>Mea</sub> (dBuV/m)	Polarization
2386.250	42.0	-38.8	27.7	53.100	V
17973.500	43.7	-17.7	45.6	15.800	H
17875.000	43.5	-18.5	45.6	16.400	V
17869.000	43.4	-18.5	45.6	16.300	V
17885.500	43.4	-18.5	45.6	16.300	H
17879.000	43.4	-18.5	45.6	16.300	H

**Ch18**

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P <sub>Mea</sub> (dBuV/m)	Polarization
17874.000	43.6	-18.5	45.6	16.500	H
17887.000	43.5	-18.5	45.6	16.400	V
17880.500	43.5	-18.5	45.6	16.400	V
17901.500	43.4	-18.5	45.6	16.300	H
17874.500	43.4	-18.5	45.6	16.300	V
17891.000	43.4	-18.5	45.6	16.300	H

**Ch26**

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P <sub>Mea</sub> (dBuV/m)	Polarization
2484.535	42.2	-38.9	27.7	53.400	H
17880.000	43.8	-18.5	45.6	16.700	H
17864.000	43.8	-18.5	45.6	16.700	V
17875.000	43.8	-18.5	45.6	16.700	V
17879.500	43.7	-18.5	45.6	16.600	H
17876.000	43.6	-18.5	45.6	16.500	H



**Peak Result:**

**Zigbee**

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P <sub>Mea</sub> (dBuV/m)	Polarization
2386.195	54.9	-38.8	27.7	66.000	V
17909.000	56.0	-18.5	45.6	28.900	H
17875.000	55.3	-18.5	45.6	28.200	V
17929.500	55.2	-17.7	45.6	27.300	H
17863.500	55.1	-18.5	45.6	28.000	H
17669.500	54.9	-18.9	45.6	28.200	V


Ch18

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P <sub>Mea</sub> (dBuV/m)	Polarization
17877.000	55.3	-18.5	45.6	28.200	H
17889.500	55.1	-18.5	45.6	28.000	H
17961.500	55.0	-17.7	45.6	27.100	V
17860.000	54.9	-18.5	45.6	27.800	H
17862.500	54.8	-18.5	45.6	27.700	V
17974.500	54.7	-17.7	45.6	26.800	V


Ch26

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P <sub>Mea</sub> (dBuV/m)	Polarization
2483.645	55.2	-38.9	27.7	66.400	V
17983.000	56.1	-17.7	45.6	28.200	H
17860.500	55.8	-18.5	45.6	28.700	V
17885.000	55.8	-18.5	45.6	28.700	V
17869.000	55.3	-18.5	45.6	28.200	H
17888.000	55.3	-18.5	45.6	28.200	H

Test graphs as below:



**Fig.A.6.2.1 Transmitter Spurious Emission - Radiated (Power): Zigbee, ch11, 2.38 GHz – 2.43GHz**



**Fig.A.6.2.2 Transmitter Spurious Emission - Radiated (Zigbee, ch11, 1 GHz-3 GHz)**






Fig.A.6.2.3 Transmitter Spurious Emission - Radiated (Zigbee, ch11, 3 GHz-18 GHz)




Fig.A.6.2.4 Transmitter Spurious Emission - Radiated (Zigbee, ch18, 9kHz-30 MHz)

Normal RE\_30M-1GHz\_10m\_Class B




Fig.A.6.2.5 Transmitter Spurious Emission - Radiated (Zigbee, ch18, 30 MHz-1 GHz)

Full Spectrum




Fig.A.6.2.6 Transmitter Spurious Emission - Radiated (Zigbee, ch18, 1 GHz-3 GHz)

Full Spectrum




Fig.A.6.2.7 Transmitter Spurious Emission - Radiated (Zigbee, ch18, 3 GHz-18 GHz)






Fig.A.6.2.8 Transmitter Spurious Emission - Radiated (Zigbee, ch18, 18GHz – 26.5GHz)



**Fig.A.6.2.9 Transmitter Spurious Emission - Radiated (Power): Zigbee, ch26, 2.45 GHz - 2.50GHz**



**Fig.A.6.2.10 Transmitter Spurious Emission - Radiated (Zigbee, ch26, 1 GHz-3 GHz)**

Full Spectrum




Fig.A.6.2.11 Transmitter Spurious Emission - Radiated (Zigbee, ch26, 3 GHz-18 GHz)

\*\*\*END OF REPORT\*\*\*