

# TEST REPORT

For

**Mobile Phone**

**Model Number: 7071A**

**FCC ID: 2ACCJBT06**

**Report Number : WT178004536**

Test Laboratory : Shenzhen Academy of Metrology and Quality  
Inspection  
National Digital Electronic Product Testing Center  
Site Location : NETC Building, No.4 Tongfa Rd., Xili, Nanshan,  
Shenzhen, China  
Tel : 0086-755-86928965  
Fax : 0086-755-86009898-31396  
Web : [www.smq.com.cn](http://www.smq.com.cn)  
E-mail : [emcrf@smq.com.cn](mailto:emcrf@smq.com.cn)

## Test report declaration

Applicant : TCL Communication Ltd  
Address : 5F, C-Tower, No.232, Liangjing Road, Zhangjiang High-tech Park, Pudong, Shanghai, China  
Manufacturer : TCL Communication Ltd  
Address : 5F, C-Tower, No.232, Liangjing Road, Zhangjiang High-tech Park, Pudong, Shanghai, China  
EUT Description : Mobile Phone  
Model No : 7071A  
Trade mark : alcatel  
Serial Number : /  
FCC ID : 2ACCJBT06

Test Standards:

**FCC Part 15 15.207, 15.209, 15.247(2016)**

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Project Engineer:	 _____ (Chen Silin 陈司林)	Date:	<u>Aug.31, 2017</u>
Checked by:	 _____ (Lin Yixiang 林奕翔)	Date:	<u>Aug.31, 2017</u>
Approved by:	 _____ (Lin Bin 林斌)	Date:	<u>Aug.31, 2017</u>

## TABLE OF CONTENTS

<b>TEST REPORT DECLARATION</b> .....	<b>2</b>
<b>1. TEST RESULTS SUMMARY</b> .....	<b>5</b>
<b>2. GENERAL INFORMATION</b> .....	<b>6</b>
2.1. Report information.....	6
2.2. Laboratory Accreditation and Relationship to Customer .....	6
2.3. Measurement Uncertainty .....	6
<b>3. PRODUCT DESCRIPTION</b> .....	<b>7</b>
3.1. EUT Description .....	7
3.2. Related Submittal(s) / Grant (s).....	7
3.3. Block Diagram of EUT Configuration .....	7
3.4. Operating Condition of EUT .....	7
3.5. Support Equipment List.....	8
3.6. Test Conditions .....	8
3.7. Special Accessories .....	8
3.8. Equipment Modifications .....	8
<b>4. TEST EQUIPMENT USED</b> .....	<b>9</b>
<b>5. CONDUCTED DISTURBANCE TEST</b> .....	<b>10</b>
5.1. Test Standard and Limit .....	10
5.2. Test Procedure.....	10
5.3. Test Arrangement .....	10
5.4. Test Data.....	10
<b>6. RADIATED DISTURBANCE TEST</b> .....	<b>19</b>
6.1. Test Standard and Limit .....	19
6.2. Test Procedure.....	19
6.3. Test Arrangement .....	19
6.4. Test Data.....	20
<b>7. 20DB BANDWIDTH MEASUREMENT</b> .....	<b>41</b>
7.1. LIMITS OF 20dB BANDWIDTH MEASUREMENT.....	41
7.2. TEST PROCEDURE .....	41
7.3. TEST SETUP .....	41
7.4. Test Data.....	41
<b>8. CARRIER FREQUENCY SEPARATION MEASUREMENT</b> .....	<b>44</b>
8.1. LIMITS OF Carrier frequency separation measurement .....	44
8.2. TEST PROCEDURES.....	44
8.3. TEST SETUP .....	44
8.4. Test Data.....	44
<b>9. NUMBER OF HOPPING CHANNEL</b> .....	<b>47</b>
9.1. LIMITS OF 9. NUMBER OF HOPPING CHANNEL.....	47
9.2. TEST PROCEDURE .....	47
9.3. TEST SETUP .....	47
9.4. Test Data.....	48
<b>10. TIME OF OCCUPANCY</b> .....	<b>49</b>
10.1. LIMITS OF TIME OF OCCUPANCY.....	49
10.2. TEST PROCEDURE.....	49

10.3.	TEST RESULTS .....	50
<b>11.</b>	<b>PEAK POWER.....</b>	<b>54</b>
11.1.	LIMITS OF Peak Power.....	54
11.2.	TEST PROCEDURE.....	54
11.3.	TEST RESULTS .....	54
<b>12.</b>	<b>BAND EDGES MEASUREMENT.....</b>	<b>57</b>
12.1.	Limits of Band Edges Measurement.....	57
12.2.	TEST PROCEDURE.....	57
12.3.	Test Results.....	57
<b>13.</b>	<b>CONDUCTED SPURIOUS EMISSIONS.....</b>	<b>66</b>
13.1.	Limits of Band Edges Measurement.....	66
13.2.	Test Procedure .....	66
13.3.	TEST RESULTS .....	66
<b>14.</b>	<b>ANTENNA REQUIREMENTS .....</b>	<b>71</b>
14.1.	Applicable requirements .....	71
14.2.	Antenna Connector.....	71
14.3.	Antenna Gain.....	71

# 1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	FCC Rules	Test Results
20dB bandwidth measurement	15.247 (a) (1)	Pass
Carrier frequency separation measurement	15.247 (a) (1)	Pass
Number of hopping channel	15.247 (a) (1) III	Pass
Time of occupancy	15.247 (a) (1) III	Pass
Peak output power	15.247 (b) (1)	Pass
Band edge compliance measurement	15.247 (d)	Pass
Radiated spurious emission & Radiated restricted band measurement	15.247 (d) / 15.205 & 15.209	Pass
Conducted emission test for power port	15.207	Pass
Antenna Requirment	15.203	Pass

Remark: "N/A" means "Not applicable."

## 2. GENERAL INFORMATION

### 2.1. Report information

This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.

The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

### 2.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is accredited by the United States of American Federal Communications Commission (FCC), and the registration number is 582918.

The Laboratory is registered to perform emission tests with Industry Canada (IC), and the registration number is 11177A-1 11177A-2.

TUV Rhineland accredits the Laboratory for conformance to IEC and EN standards, the registration number is E2024086Z02.

### 2.3. Measurement Uncertainty

Conducted Emission  
9kHz~30MHz 3.5dB

Radiated Emission  
30MHz~1000MHz 4.5dB  
1GHz~26.5GHz 4.6dB

### 3. PRODUCT DESCRIPTION

#### 3.1.EUT Description

Description	:	Mobile Phone
Manufacturer	:	TCL Communication Ltd
Model Number	:	7071A
Operate Frequency	:	2.402GHz~2.480GHz
Antenna Designation	:	BT: DIPOLE ANTENNA 1.5dBi
Operating voltage	:	3.5V (Low)/3.8V (Nominal)/ 4.35V (Max)
Software Version	:	vG2J
Hardware Version	:	V03

- Remark: 1. The modes of adaptor QC11US (1#)、QC11RU (4#)、QC11EU (5#)、QC11ART (6#)、QC11UK(7#) are identical in circuit design and PCB layout, the only difference is the plug type. The modes of adaptor QC11US (2#)、QC11EU(8#)、QC11UK (9#)are identical in circuit design and PCB layout, the only difference is the plug type. EMC tests were performed on the type QC11US (1#) and QC11US (2#).
- Two models of batteries provided, TLp038B1 and TLp038B7 respectively, Full tests were performed on model TLp038B1, and the worst case results are recorded in this report.
  - Two models of Earphones provided, 1# (Superb) and 2# (JUWEI) respectively, Full tests were performed on model 1# (Superb), and the worst case results are recorded in this report.
  - Two models of USB provided, 1# (PUAN) and 2# (JUWEI) respectively, Full tests were performed on model 1# (PUAN), and the worst case results are recorded in this report.

#### 3.2.Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **2ACCJBT06** filing to comply with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C .

#### 3.3.Block Diagram of EUT Configuration




Figure 1 EUT setup

### 3.4. Operating Condition of EUT

The transmitter has a maximum peak conducted output power of Basic rate GFSK modulation and EDR mode 8DPSK modulation. Tests were performed with Basic rate GFSK modulation and EDR mode 8DPSK modulation.

### 3.5. Support Equipment List

Table 2 Support Equipment List

Name	Model No	S/N	Manufacturer
Adaptor 1# for EUT	QC11US	--	Ten Pao Industrial Co.,Ltd.
Adaptor 2# for EUT	QC11US	--	Huizhou BYD Electronic Co.,Ltd.
Adaptor 3# for EUT	UC13EU	--	Huizhou BYD Electronic Co.,Ltd.
Adaptor 4# for EUT	QC11RU	--	Ten Pao Industrial Co.
Adaptor 5# for EUT	QC11EU	--	Ten Pao Industrial Co.
Adaptor 6# for EUT	QC11ART	--	Ten Pao Industrial Co.
Adaptor 7# for EUT	QC11UK	--	Ten Pao Industrial Co.
Adaptor 8# for EUT	QC11EU	--	Huizhou BYD Electronic Co.,Ltd.
Adaptor 9# for EUT	QC11UK	--	Huizhou BYD Electronic Co.,Ltd.
USB 1# for EUT	--	--	PUAN
USB 2# for EUT	--	--	JUWEI
Battery 1# for EUT	TLp038B1	--	Shenzhen BYD Lithium Battery Company Limited
Battery 2# for EUT	TLp038B7	--	Ningbo Veken Battery Co.,Ltd.
Earphone 1# for EUT	--	--	Dong Guan Superb electronic Co.,Ltd.
Earphone 2# for EUT	--	--	HUIZHOU JUWEI ELECTRONICS CO.,LTD

### 3.6. Test Conditions

Date of test : Aug.03, 2017- Aug.31, 2017

Date of EUT Receive : Aug.01, 2017

Temperature: 18-24 °C

Relative Humidity: 39-61%

### 3.7. Special Accessories

Not available for this EUT intended for grant.

### 3.8. Equipment Modifications

Not available for this EUT intended for grant.



#### 4. TEST EQUIPMENT USED

Table 3 Test Equipment

No.	Equipment	Manufacturer	Model No.	Last Cal.	Cal. Interval
SB3319	EMI Test Receiver	Rohde & Schwarz	ESCS30	Nov.29, 2016	1 Year
SB4357	AMN	Rohde & Schwarz	ESH2-Z5	Sep.29, 2016	1 Year
SB3436	EMI Test Receiver	Rohde & Schwarz	ESI26	Nov.29, 2016	1 Year
SB8501/09	EMI Test Receiver	Rohde & Schwarz	ESU40	Mar.21, 2017	1 Year
SB8501/04	Bilog Antenna	Schwarzbeck	VULB9163	Mar.21, 2017	1 Year
SB3955	Bilog Antenna	Schwarzbeck	VULB9163	Mar.22 ,2017	1 Year
SB3435	Horn Antenna	Rohde & Schwarz	HF906	Jan.03, 2017	1 Year
SB8501/01	Horn Antenna	Rohde & Schwarz	HF907	Mar.22, 2017	1 Year
SB8501/11	Horn Antenna	ETS-Lindgren	3160-09	Mar.1,2017	1 Year
SB3345	Loop Antenna	Schwarzbeck	FMZB1516	Mar.22, 2017	2 Years
SB8501/14	Preamplifier	Rohde & Schwarz	SCU-03	Mar.19, 2017	1 Year
SB8501/16	Preamplifier	Rohde & Schwarz	SCU-26	Mar.06, 2017	1 Year
SB8501/17	Preamplifier	Rohde & Schwarz	SCU-18	Mar.06, 2017	1 Year
SB12827/01	Power Sensor	Rohde & Schwarz	NRP-Z22	Jun.19, 2017	1 Year
SB11873/01	Power Sensor	Rohde & Schwarz	OSP120+OSP-B157	Mar.13, 2017	1 Year
--	Test Software	Rohde & Schwarz	Power Viewer Plus	--	--
SB7941/02	Signal Analyzer	Rohde & Schwarz	FSU26	Jun.19,2017	1 Year

## 5. CONDUCTED DISTURBANCE TEST

### 5.1. Test Standard and Limit

#### 5.1.1. Test Standard

FCC Part 15 15.207

#### 5.1.2. Test Limit

Table 4 Conducted Disturbance Test Limit

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

\* Decreasing linearly with logarithm of the frequency

\* The lower limit shall apply at the transition frequency.

### 5.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions form both sides of AC line.

Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

The bandwidth of EMI test receiver is set at 9kHz.

### 5.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

### 5.4. Test Data

The emissions don't show in below are too low against the limits. Refer to the test curves.

**Table 5 Conducted Disturbance Test Data**

Model No.: 7071A								
Test mode: Charging and Transmitting								
Adaptor:1#								
	Frequency (MHz)	Correction Factor (dB)	Quasi-Peak			Average		
			Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)
Line	0.186	9.7	40.1	49.8	64.2	24.2	33.9	54.2
	0.242	9.7	33.4	43.1	62.0	19.8	29.5	52.0
	0.418	9.7	33.1	42.8	57.5	22.7	32.4	47.5
	0.542	9.8	33.3	43.1	56	22.7	32.5	46
	0.590	9.8	34.0	43.8	56	23.5	33.3	46
	22.620	10.2	30.1	40.3	60	18.1	28.3	50
Neutral	0.198	9.7	40.4	50.1	63.7	24.2	33.9	53.7
	0.250	9.7	34.0	43.7	61.8	19.1	28.8	51.8
	0.418	9.7	32.0	41.7	57.5	21.5	31.2	47.5
	0.550	9.8	30.4	40.2	56	21.7	31.5	46
	0.662	9.8	29.7	39.5	56	21.4	31.2	46
	23.228	10.2	28.5	38.7	60	16.5	26.7	50

**Table 6 Conducted Disturbance Test Data**


Model No.: 7071A								
Test mode: Charging and Transmitting								
Adaptor:2#								
	Frequency (MHz)	Correction Factor (dB)	Quasi-Peak			Average		
			Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)
Line	0.170	9.7	34.1	43.8	65.0	21.1	30.8	55.0
	0.542	9.8	37.7	47.5	56	25.9	35.7	46
	0.654	9.8	36.1	45.9	56	21.2	31.0	46
	2.558	9.9	27.9	37.8	56	14.2	24.1	46
	17.000	9.9	37.7	47.6	60	23.6	33.5	50
	24.844	10.2	40.5	50.7	60	24.1	34.3	50
Neutral	0.162	9.7	32.8	42.5	65.4	23.4	33.1	55.4
	0.582	9.8	32.8	42.6	56	26.7	36.5	46
	0.646	9.8	39.6	49.4	56	34.8	44.6	46
	1.290	9.8	26.1	35.9	56	19.1	28.9	46
	15.152	9.9	35.9	45.8	60	27.5	37.4	50
	25.236	10.2	43.1	53.3	60	21.9	32.1	50

**Table 7 Conducted Disturbance Test Data**


Model No.: 7071A								
Test mode: Charging and Transmitting								
Adaptor:3#								
	Frequency (MHz)	Correction Factor (dB)	Quasi-Peak			Average		
			Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)
Line	0.150	9.7	32.1	41.8	66	18.7	28.4	56
	0.562	9.8	32.1	41.9	56	25.6	35.4	46
	0.602	9.8	31.0	40.8	56	24.4	34.2	46
	1.542	9.8	30.7	40.5	56	24.6	34.4	46
	1.742	9.8	31.4	41.2	56	25.5	35.3	46
	1.890	9.8	31.5	41.3	56	24.9	34.7	46
Neutral	0.154	9.7	33.0	42.7	65.8	8.7	18.4	55.8
	0.562	9.8	28.9	38.7	56	19.3	29.1	46
	0.622	9.8	23.0	32.8	56	11.3	21.1	46
	0.858	9.8	20.3	30.1	56	8.3	18.1	46
	1.670	9.8	27.0	36.8	56	13.7	23.5	46
	1.898	9.8	26.3	36.1	56	12.8	22.6	46

- REMARKS: 1. Emission level(dBuV)=Read Value(dBuV) + Correction Factor(dB)  
 2. Correction Factor(dB) =LISN Factor (dB) + Cable Factor (dB)+Limiter Factor(dB)  
 3. The other emission levels were very low against the limit.


EUT: 7071A  
Manufacturer:  
Operating Condition: Charging and Transmitting  
Test Site:  
Operator:  
Test Specification: L  
Comment: AC 120V/60Hz  
Comment: Adaptor: 1#




EUT: 7071A  
Manufacturer:  
Operating Condition: Charging and Transmitting  
Test Site:  
Operator:  
Test Specification: N  
Comment: AC 120V/60Hz  
Comment: Adaptor: 1#



EUT: 7071A  
Manufacturer:  
Operating Condition: Charging and Transmitting  
Test Site:  
Operator:  
Test Specification: L  
Comment: AC 120V/60Hz  
Comment: Adaptor: 2#




EUT: 7071A  
Manufacturer:  
Operating Condition: Charging and Transmitting  
Test Site:  
Operator:  
Test Specification: N  
Comment: AC 120V/60Hz  
Comment: Adaptor: 2#






EUT: 7071A  
 Manufacturer:  
 Operating Condition: Charging and Transmitting  
 Test Site:  
 Operator:  
 Test Specification: L  
 Comment: AC 120V/60Hz  
 Comment: Adaptor: 3#



EUT: 7071A  
 Manufacturer:  
 Operating Condition: Charging and Transmitting  
 Test Site:  
 Operator:  
 Test Specification: N  
 Comment: AC 120V/60Hz  
 Comment: Adaptor: 3#



## 6. RADIATED DISTURBANCE TEST

### 6.1. Test Standard and Limit

#### 6.1.1. Test Standard

FCC Part 15 15.209

#### 6.1.2. Test Limit

Table 8 Radiation Disturbance Test Limit for FCC (Class B)(9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Table 9 Radiation Disturbance Test Limit for FCC (Class B)(Above 1G)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

\* The lower limit shall apply at the transition frequency.

\* The test distance is 3m.

### 6.2. Test Procedure

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10-2013. The EUT is set to transmit in a continuous mode. Radiated measurements were performed on the frequency range from 30MHz to 25GHz. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz, VBW ≥ RBW. All readings above 1 GHz are AV and PK values. RBW=1MHz and 1/T (10Hz) for AV value, RBW=1MHz and VBW ≥ RBW for peak value. Measurements were made at 3 meters

### 6.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

#### 6.4. Test Data

The emissions don't show in following result tables are more than 20dB below the limits.

Bluetooth basic rate and Bluetooth EDR mode were tested, below only shows worst case result of Bluetooth basic rate.

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Adaptor 1# for EUT: UC11US TENPAO

9KHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Table 10 Radiated Emission Test Data 9k Hz-30MHz

Frequency MHz	Cable Loss(dB)	Antenna Factor(dB)	Readings(dBμV/m)	Level(dBμV/m)	Polarity(H/V)	Turntable Angle(deg)	Antenna Height(m)	Limits(dBμV/m)	Margin(dB)
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--

30MHz-1GHz

Worst case is shown below for 30MHz-1GHz only.

The emissions don't show in following result tables are more than 20dB below the limits.

Table 11 Radiated Emission Test Data 30MHz-1GHz

Frequency MHz	Cable Loss(dB)	Antenna Factor(dB)	Readings(dBμV/m)	Level(dBμV/m)	Polarity(H/V)	Turntable Angle(deg)	Antenna Height(m)	Limits(dBμV/m)	Margin(dB)
32.271	0.7	12.3	6.7	19.7	H	10	2.0	40	20.3
47.496	0.8	13.6	-2.6	11.8	H	0	1.0	40	28.2
76.651	1.0	7.8	4.7	13.5	H	10	1.0	40	26.5
96.171	1.1	12.8	0.4	14.3	H	40	1.0	43.5	29.2
173.855	1.5	9.0	8.4	18.9	H	30	2.0	43.5	24.6
211.353	1.8	10.6	19.2	31.6	H	60	2.0	43.5	11.9
31.211	0.6	12.3	12.2	25.1	V	10	1.0	40	14.9
37.991	0.7	12.3	18.8	31.8	V	30	1.0	40	8.2
45.589	0.8	13.6	12.2	26.6	V	330	1.0	40	13.4
86.371	1.1	10.3	8.4	19.8	V	10	1.0	40	20.2
105.160	1.2	13.2	7.2	21.6	V	30	1.0	43.5	21.9
211.553	1.8	10.6	20.8	33.2	V	70	1.0	43.5	10.3

Adaptor for 2# EUT: UC11US BYD

9KHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Table 12 Radiated Emission Test Data 9k Hz-30MHz

Frequency MHz	Cable Loss(dB)	Antenna Factor(dB)	Readings(dBμV/m)	Level(dBμV/m)	Polarity(H/V)	Turntable Angle(deg)	Antenna Height(m)	Limits(dBμV/m)	Margin(dB)
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--

30MHz-1GHz

Worst case is shown below for 30MHz-1GHz only.

The emissions don't show in following result tables are more than 20dB below the limits.

Table 13 Radiated Emission Test Data 30MHz-1GHz

Frequency MHz	Cable Loss(dB)	Antenna Factor(dB)	Readings(dBμV/m)	Level(dBμV/m)	Polarity(H/V)	Turntable Angle(deg)	Antenna Height(m)	Limits(dBμV/m)	Margin(dB)
30.020	0.6	12.3	23.8	36.7	V	10	1.0	40	3.3
35.511	0.6	12.3	18.7	31.6	V	30	1.0	40	8.4
43.376	0.7	13.6	3.0	17.3	V	30	1.0	40	22.7
100.443	1.1	13.2	1.7	16.0	V	340	1.0	43.5	27.5
161.314	1.5	8.7	3.4	13.6	V	10	1.0	43.5	29.9
209.923	1.7	10.6	19.2	31.5	V	30	1.0	43.5	12.0
30.020	0.6	12.3	10.5	23.4	H	10	2.0	40	16.6
35.310	0.6	12.3	2.7	15.6	H	40	2.0	40	24.4
53.890	0.8	13.3	-0.7	13.4	H	10	2.0	40	26.6
94.148	1.1	11.9	3.7	16.7	H	0	1.0	43.5	26.8
161.521	1.5	8.7	3.4	13.6	H	310	1.0	43.5	29.9
209.898	1.7	10.6	16.8	29.1	H	40	2.0	43.5	14.4

Adaptor 3# for EUT: UC13EU BYD

9KHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Table 14 Radiated Emission Test Data 9k Hz-30MHz

Frequency MHz	Cable Loss(dB)	Antenna Factor(dB)	Readings(dBμV/m)	Level(dBμV/m)	Polarity(H/V)	Turntable Angle(deg)	Antenna Height(m)	Limits(dBμV/m)	Margin(dB)
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--

30MHz-1GHz

Worst case is shown below for 30MHz-1GHz only.

The emissions don't show in following result tables are more than 20dB below the limits.


Table 15 Radiated Emission Test Data 30MHz-1GHz

Frequency MHz	Cable Loss(dB)	Antenna Factor(dB)	Readings(dBμV/m)	Level(dBμV/m)	Polarity(H/V)	Turntable Angle(deg)	Antenna Height(m)	Limits(dBμV/m)	Margin(dB)
50.952	0.8	13.3	9.0	23.1	H	30	1.0	40	16.9
86.648	1.1	10.3	16.1	27.5	H	20	1.0	40	12.5
91.207	1.2	11.9	16.9	30.0	H	30	2.0	43.5	13.5
150.571	1.4	8.3	16.9	26.6	H	10	2.0	43.5	16.9
199.168	1.6	10.6	14.0	26.2	H	20	2.0	43.5	17.3
269.299	2.0	12.1	20.0	34.1	H	10	2.0	46	11.9
30.185	0.6	12.3	19.8	32.7	V	20	1.0	40	7.3
34.947	0.6	12.3	19.0	31.9	V	10	1.0	40	8.1
90.431	1.2	11.9	15.4	28.5	V	30	1.0	43.5	15.0
205.376	1.6	10.6	16.5	28.7	V	20	1.0	43.5	14.8
208.577	1.7	10.6	16.8	29.1	V	10	1.0	43.5	14.4
267.747	2.0	12.1	15.2	29.3	V	20	1.0	46	16.7

REMARK: Emission level(dBuV)=Read Value(dBuV/m) + Antenna Factor(dB)+ Cable Loss +preamp(dB)

### Radiated Emission


EUT Name: 7071A  
Operating Condition: Charging and Transmitting  
Test site: SMQ NETC EMC Lab.  
Antenna Position: Vertical & Horizontal  
Comment: 120V/60Hz  
Comment: Adaptor: 1#






### Radiated Emission

EUT Name: 7071A  
Operating Condition: Charging and Transmitting  
Test site: SMQ NETC EMC Lab.  
Antenna Position: Vertical & Horizontal  
Comment: 120V/60Hz  
Comment: Adaptor: 2#




## Radiated Emission

EUT Name: 7071A  
Operating Condition: Charging and Transmitting  
Test site: SMQ NETC EMC Lab.  
Antenna Position: Vertical & Horizontal  
Comment: 120V/60Hz  
Comment: Adaptor: 3#



(Horizontal)



(Vertical)

1GHz-18GHz

BDR CH0

## Radiated Emission


### EUT Information

EUT Model Name: 7071A  
Operation mode: BT DH1 CH0 TX  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



# Radiated Emission


## EUT Information

EUT Model Name: 7071A  
Operation mode: BT DH1 CH0 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



1GHz-18GHz

BDR CH39

# Radiated Emission


## EUT Information

EUT Model Name: 7071A  
Operation mode: BT DH1 CH39 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



# Radiated Emission


## EUT Information

EUT Model Name: 7071A  
Operation mode: BT DH1 CH39 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



1GHz-18GHz

BDR CH78

# Radiated Emission


## EUT Information

EUT Model Name: 7071A  
Operation mode: BT DH1 CH78 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



# Radiated Emission


## EUT Information

EUT Model Name: 7071A  
Operation mode: BT DH1 CH78 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz





1GHz-18GHz

EDR CH0

# Radiated Emission


## EUT Information

EUT Model Name: 7071A  
Operation mode: BT 3-DH1 CH0 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



# Radiated Emission


## EUT Information

EUT Model Name: 7071A  
Operation mode: BT 3-DH1 CH0 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



1GHz-18GHz

EDR CH39

## Radiated Emission


### EUT Information

EUT Model Name: 7071A  
Operation mode: BT 3-DH1 CH39 TX  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



# Radiated Emission


## EUT Information

EUT Model Name: 7071A  
Operation mode: BT 3-DH1 CH39 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



1GHz-18GHz

EDR CH78

# Radiated Emission


## EUT Information

EUT Model Name: 7071A  
Operation mode: BT 3-DH1 CH78 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



# Radiated Emission


## EUT Information

EUT Model Name: 7071A  
Operation mode: BT 3-DH1 CH78 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



18-25GHz

No Peak found in pre-scan, only worst case result is listed in this report.

FCC Electric Field Strength 18-26.5GHz




Table 16 Restricted Band Radiated Emission Data

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	
6.31175 - 6.31225	123 - 138	2200 - 2300	
8.291 - 8.294	149.9 - 150.05	2310 - 2390	
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	
12.29 - 12.293	167.72 - 173.2	3332 - 3339	
12.51975 -	240 - 285	3345.8 - 3358	
12.52025	322 - 335.4	3600 - 4400	
12.57675 -			
12.57725			
13.36 - 13.41			

Except as shown in table 9 to table 15, all other emission of the above band were less than the limit 20dB.



## 7. 20DB BANDWIDTH MEASUREMENT

### 7.1.LIMITS OF 20dB BANDWIDTH MEASUREMENT

CFR 47 (FCC) part 15.247 (a) (1) and DA 00-705

### 7.2.TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and  $VBW \geq RBW$ . The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.



### 7.3.TEST SETUP



### 7.4.Test Data


Table 17 20dB Bandwidth Test Data Modulation: GFSK

CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)	results
2402	0.9375	Pass
2441	0.9375	Pass
2480	0.9375	Pass



Date: 28.AUG.2017 14:48:55



Date: 28.AUG.2017 14:51:00



Date: 28.AUG.2017 14:52:16


Table 18 20dB Bandwidth Test Data Modulation: 8DPSK

CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)	results
2402	1.2740	Pass
2441	1.2700	Pass
2480	1.2700	Pass



Date: 28.AUG.2017 14:57:08

Date: 28.AUG.2017 14:58:38



Date: 28.AUG.2017 15:00:30

## 8. CARRIER FREQUENCY SEPARATION MEASUREMENT

### 8.1.LIMITS OF CARRIER FREQUENCY SEPARATION MEASUREMENT

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

### 8.2.TEST PROCEDURES

- (a) Connect test port of EUT to spectrum analyzer and universal communication tester.
- (b) Set the EUT to transmit maximum output power at 2.4GHz and switch off frequency hopping function, then set the measured frequency number to two adjacent channels separately and test the carrier frequency separation with spectrum analyzer.

### 8.3.TEST SETUP





### 8.4.Test Data

BDR


Table 19 Carrier Frequencies Separation

Frequency [GHz]	Frequency [GHz]	frequency separation [MHz]	Limit [MHz]	Result
2.402	2.403	1.000	0.625	Pass
2.440	2.441	1.006	0.625	Pass
2.479	2.480	1.000	0.625	Pass



Date: 28.AUG.2017 15:09:15

Date: 28.AUG.2017 15:07:56





Date: 28.AUG.2017 15:06:28

EDR


Table 20 Carrier Frequencies Separation

Frequency [GHz]	Frequency [GHz]	frequency separation [MHz]	Limit [MHz]	Result
2.402	2.403	1.000	0.845	Pass
2.440	2.441	1.000	0.845	Pass
2.479	2.480	1.003	0.845	Pass



Date: 28.AUG.2017 15:02:30

Date: 28.AUG.2017 15:03:45



Date: 28.AUG.2017 15:05:02

## 9. NUMBER OF HOPPING CHANNEL

### 9.1.LIMITS OF NUMBER OF HOPPING CHANNEL

Number of hopping channel should be compliance with the requirements in part15.247 (a) (1) III.

### 9.2.TEST PROCEDURE

- (a) Connect test port of EUT to spectrum analyzer
- (b) Set the EUT to transmit maximum output power at 2.4GHz and switch on Frequency hopping function, then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer.
- (c) Count the quantity of peaks to get the number of hopping channels.

### 9.3.TEST SETUP




## 9.4. Test Data


Table 21 Hopping Channel Number Test Data

Hopping numbers	LIMIT	results
79	>15	Pass

BDR



EDR





## 10. TIME OF OCCUPANCY

### 10.1. LIMITS OF TIME OF OCCUPANCY

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 10.2. TEST PROCEDURE

- (a) Connect test port of EUT to spectrum analyzer and universal communication tester.
- (b) Set the EUT to transmit maximum output power at 2.4GHz and switch on frequency hopping function.
- (c) Set the span of spectrum analyzer to 0 Hz, and set the resolution bandwidth to 1 MHz and the video bandwidth to 1 MHz, then get the time domain measured diagram. and set sweep time to 2 times of one burst occupancy time, and measure the time of occupancy of one burst.
- (d) Set the resolution bandwidth to 1 MHz and the video bandwidth to 3 MHz ,and set the sweep time to a period (0.4 seconds multiplied by the number of hopping channels employed), and count the number of the bursts.
- (e) Calculate the time of occupancy in a period with time occupancy of a burst and quantity of bursts.


# 10.3.TEST RESULTS

## GFSK


Table 22 Time of Occupancy

	Time of Single Slot [ms]	Numbers of slots in a period	Time of occupied in a period [s]	Limit [s]	Result
DH1	0.409	32	0.1309	≤ 0.4	Pass
DH3	1.683	17	0.2861	≤ 0.4	Pass
DH5	2.933	13	0.3813	≤ 0.4	Pass

### DH1




Date: 28.AUG.2017 16:25:25




Date: 28.AUG.2017 16:25:45

### DH3




Date: 28.AUG.2017 16:27:01




Date: 28.AUG.2017 16:27:25

# DH5



Date: 28.AUG.2017 16:28:11




Date: 28.AUG.2017 16:28:50

# 8DPSK


## Table 23 Time of Occupancy

	Time of Single Slot [ms]	Numbers of slots in a period	Time of occupied in a period [s]	Limit [s]	Result
3-DH1	0.449	34	0.1527	≤ 0.4	Pass
3-DH3	1.715	16	0.2744	≤ 0.4	Pass
3-DH5	2.917	10	0.2917	≤ 0.4	Pass

### 3-DH1




Date: 28.AUG.2017 16:19:19




Date: 28.AUG.2017 16:19:51

### 3-DH3




Date: 28.AUG.2017 16:21:02




Date: 28.AUG.2017 16:21:43

# 3-DH5



Date: 31.AUG.2017 14:59:38



Date: 31.AUG.2017 15:00:37

## **11. PEAK POWER**

### **11.1. LIMITS OF Peak Power**

Compliance with part 15.247 (b) (1) & RSS-247 Clause 5.4(2), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.

For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watt.

### **11.2. TEST PROCEDURE**




- (a) Connect test port of EUT to universal communication tester.
- (b) Set the EUT to transmit maximum output power at 2.4GHz and switch off frequency hopping function.
- (c) Then set the EUT to transmit at high, middle and low frequency and measure the conducted output power separately.

### **11.3. TEST RESULTS**

BDR

Table 24 Peak Power Test Data

Channel	Channel No.	Center Freq. [MHz]	Meas. Level (Cond.) [dBm]	Limit [dBm]	Result
Bottom	0	2402	6.36	< 30	Pass
Middle	39	2441	6.70	< 30	Pass
Top	78	2480	6.60	< 30	Pass






Date: 28.AUG.2017 15:10:51

Date: 28.AUG.2017 15:11:27

EDR

Table 25 Peak Power Test Data

Channel	Channel No.	Center Freq. [MHz]	Meas. Level (Cond.) [dBm]	Limit [dBm]	Result
Bottom	0	2402	5.49	< 21	Pass
Middle	39	2441	5.83	< 21	Pass
Top	78	2480	5.66	< 21	Pass



Date: 28.AUG.2017 15:14:00

Date: 28.AUG.2017 15:14:00



## 12. BAND EDGES MEASUREMENT

### 12.1. Limits of Band Edges Measurement

Below  $-20\text{dB}$  of the highest emission level of operating band (in  $100\text{kHz}$  resolution bandwidth).

### 12.2. TEST PROCEDURE

1. The EUT is placed on a turntable, which is  $1.5\text{m}$  above the ground plane.
2. The turntable shall be rotated for  $360$  degrees to determine the position of maximum emission level.
3. EUT is set  $3\text{m}$  away from the receiving antenna, which is varied from  $1\text{m}$  to  $4\text{m}$  to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK:  $\text{RBW}=\text{VBW}=1\text{MHz}$  / Sweep=AUTO
  - (b) AVERAGE:  $\text{RBW}=1\text{MHz}$  /  $\text{VBW}=10\text{Hz}$  / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

### 12.3. Test Results


The measured plots are attached on the following. Test data shows compliance with the band edge requirement in part 15.247(d).

Bluetooth Basic Rate


Low edge

Horizontal

FCC Electric Field Strength 2.4GHz Bandedge-PK




FCC Electric Field Strength 2.4GHz Bandedge-AV




Vertical

FCC Electric Field Strength 2.4GHz Bandedge-PK




FCC Electric Field Strength 2.4GHz Bandedge-AV




Upper Edge  
Horizontal

FCC Electric Field Strength 2.4GHz Bandedge-PK




FCC Electric Field Strength 2.4GHz Bandedge-AV




Vertical

FCC Electric Field Strength 2.4GHz Bandedge-PK



FCC Electric Field Strength 2.4GHz Bandedge-AV




Bluetooth EDR


Low edge

Horizontal

FCC Electric Field Strength 2.4GHz Bandedge-PK




FCC Electric Field Strength 2.4GHz Bandedge-AV




Vertical

FCC Electric Field Strength 2.4GHz Bandedge-PK



FCC Electric Field Strength 2.4GHz Bandedge-AV




Bluetooth EDR


Upper edge

Horizontal

FCC Electric Field Strength 2.4GHz Bandedge-PK




FCC Electric Field Strength 2.4GHz Bandedge-AV






Vertical

FCC Electric Field Strength 2.4GHz Bandedge-PK



FCC Electric Field Strength 2.4GHz Bandedge-AV



## **13. CONDUCTED SPURIOUS EMISSIONS**

### **13.1.Limits of Band Edges Measurement**

Below –20dB of the highest emission level of operating band (in 100kHz resolution bandwidth).

### **13.2.Test Procedure**

The transmitter output was connected to the spectrum analyzer.

The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal

### **13.3.TEST RESULTS**


# Bluetooth Basic

## Low channel




# Bluetooth Basic



## Mid channel




# Bluetooth Basic High Channel




# Bluetooth Basic Bandedge hopping On




# Bluetooth EDR Low Channel




# Bluetooth EDR Mid Channel



# Bluetooth EDR High Channel



# Bluetooth EDR Bandedge



## **14. ANTENNA REQUIREMENTS**

### **14.1. Applicable requirements**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **14.2. Antenna Connector**

Antenna Connector is on the PCB within enclosure and not accessible to user.

### **14.3. Antenna Gain**

The antenna gain of EUT is less than 6 dBi.