



TEST REPORT

No. I17Z61902-EMC01

for

TCL Communication Ltd.

Mobile phone

Model Name: 5026J

FCC ID: 2ACCJBT10

with

Hardware Version: V03

Software Version: FD1

Issued Date: 2017-11-24



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



REPORT HISTORY

Report Number	Revision	Description	Issue Date
I17Z61902-EMC01	Rev.0	1 st edition	2017-11-24



CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. TESTING ENVIRONMENT	4
1.3. PROJECT DATA	4
1.4. SIGNATURE.....	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION.....	5
2.2. MANUFACTURER INFORMATION.....	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT.....	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	6
3.4. EUT SET-UPS	7
4. REFERENCE DOCUMENTS.....	8
4.1. REFERENCE DOCUMENTS FOR TESTING.....	8
5. LABORATORY ENVIRONMENT.....	9
6. SUMMARY OF TEST RESULTS.....	10
7. TEST EQUIPMENTS UTILIZED.....	11
ANNEX A: MEASUREMENT RESULTS	12
ANNEX B: ACCREDITATION CERTIFICATE	34

1. Test Laboratory

1.1. Testing Location

CTTL (BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology Development Area, Beijing, P. R. China 100176

1.2. Testing Environment

Normal Temperature: 15-35°C


Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2017-11-10

Testing End Date: 2017-11-24


1.4. Signature



Wang Junqing
(Prepared this test report)



Zhang Ying
(Reviewed this test report)



Liu Baodian
Deputy Director of the laboratory
(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address /Post: 5F, C-Tower, No. 232, Liang Jing Road, ZhangJiang High-Tech Park,
Pudong Area,Shanghai,201203,P.R.China
Contact Person: Gong Zhizhou
Contact Email zhizhou.gong@tcl.com
Telephone: 0086-21-31363544
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address /Post: 5F, C-Tower, No. 232, Liang Jing Road, ZhangJiang High-Tech Park,
Pudong Area,Shanghai,201203,P.R.China
Contact Person: Gong Zhizhou
Contact Email zhizhou.gong@tcl.com
Telephone: 0086-21-31363544
Fax: 0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Mobile phone
Model Name	5026J
FCC ID	2ACCJBT10
Extreme vol. Limits	3.65VDC to 4.35VDC (nominal: 3.8VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	015088000200145	V03	FD1
EUT11	353441090200048	V03	FD1

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN	Remarks
AE1	Battery	/	inbuilt
AE2	Battery	/	inbuilt
AE3	Charger	/	17TCT-CH-0482
AE4	Charger	/	17TCT-CH-0736
AE5	USB Cable	/	16TCT-DC-0002
AE6	USB Cable	/	17TCT-DC-0238
AE31	Charger	/	17TCT-CH-1145 NEW Charger
AE41	Charger	/	17TCT-CH-1155 NEW Charger

AE1

Model	TLp029C7
Manufacturer	VEKEN
Capacitance	2900 mAh
Nominal voltage	3.85V

AE2

Model	TLp029C1
Manufacturer	BYD
Capacitance	2900 mAh
Nominal voltage	3.85V

AE3

Model	CBA0058AGAC5
Manufacturer	PUAN
Length of cable	/



AE4

Model CBA0058AGAC2
 Manufacturer TENPAO
 Length of cable /

AE5

Model CDA3122005C1
 Manufacturer JUWEI
 Length of cable 100cm

AE6

Model CDA3122005C8
 Manufacturer PUAN
 Length of cable 100cm

AE31

Model CBA0058AMAC5
 Manufacturer PUAN
 Length of cable /

AE41

Model CBA0058AMAC2
 Manufacturer TENPAO
 Length of cable /

*AE ID: is used to identify the test sample in the lab internally.

Note: The USB cables are shielded.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1/AE2+ AE3+ AE5/AE6	Charger
Set.2	EUT1+ AE1/AE2+ AE4+ AE5/AE6	Charger
Set.3	EUT1+ AE1/AE2+ AE5/AE6	USB mode
Set.11	EUT11+ AE1/AE2+ AE31+ AE5/AE6	Charger
Set.21	EUT11+ AE1/AE2+ AE41+ AE5/AE6	Charger

Note: I17Z61902 is based on I17Z61900 with adding two chargers. According to the declaration of changes, the following items are tested on Set.11 and Set.21.

Mode or Feature	EUT set-up No	Test Item
GSM 900MHz	Set.11	all test cases
GSM 900MHz	Set.21	all test cases

Other results are inherited from the initial model. The report number of initial model is I17Z61900-EMC01.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	2016
ANSI C63.4	American National Standard for Methods of Measurement of Radio- Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

Note: The test methods have no deviation with standards.

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber SAC-2 (10 meters×6.7meters×6.1meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ± 4 dB, 3m distance, from 30 to 1000 MHz
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Shielded room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz—1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω



6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	B.1	P	CTTL(BDA)
2	Conducted Emission	15.107(a)	B.2	P	CTTL(BDA)

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE	CALIBRATION INTERVAL
1	Test Receiver	ESU26	100235	R&S	2018-04-01	1 year
2	Test Receiver	ESCI 7	100344	R&S	2018-03-15	1 year
3	Universal Radio Communication Tester	CMW500	143008	R&S	2017-12-01	1 year
4	Universal Radio Communication Tester	CMW500	155415	R&S	2018-02-15	1 year
5	LISN	ENV216	101200	R&S	2018-08-03	1 year
6	EMI Antenna	VULB 9163	9163-301	Schwarzbeck	2017-12-16	3 years
7	EMI Antenna	3115	6914	ETS-Lindgren	2017-12-15	3 years
8	PC	OPTIPLEX 380	2X1YV2X	DELL	N/A	N/A
9	Printer	P1606dn	VNC3L52122	HP	N/A	N/A
10	Keyboard	L100	CN0RH6596589 07ATOI40	DELL	N/A	N/A
11	Mouse	M-UAE119	LZ935220ZRC	Lenovo	N/A	N/A

Test Item	Test Software and Version	Software Vendor
Radiated Continuous Emission	EMC32 V9.01	R&S
Conducted Emission	EMC32 V8.52.0	R&S

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission

Reference

FCC: CFR Part 15.109(a).

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at distances of 10 meters(for 30MHz-1GHz) and 3 meters (for above 1GHz) is tested. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.1.3 Measurement Limit

Frequency range (MHz)	Field strength limit ($\mu\text{V/m}$)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

A.1.4 Test Condition

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/1MHz	15	Peak, Average

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Measurement uncertainty (worst case): $U = 4.3 \text{ dB}$, $k=2$.

Measurement results for Set.1:

Charging Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
16812.750	38.2	-26.1	41.5	22.84	54.0	15.8	H
16948.500	38.2	-25.7	41.4	22.44	54.0	15.8	V
16946.250	38.1	-25.7	41.4	22.34	54.0	15.9	V
16959.750	38.1	-25.6	41.4	22.33	54.0	15.9	H
16816.500	38.0	-26.1	41.5	22.63	54.0	16.0	V
16785.000	38.0	-26.2	41.5	22.73	54.0	16.0	H

Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17969.250	50.4	-25.1	40.8	34.71	74.0	23.6	V
17610.000	50.4	-25.8	41.1	35.09	74.0	23.6	V
16917.000	50.3	-25.8	41.4	34.63	74.0	23.7	H
17096.250	50.3	-25.5	41.3	34.46	74.0	23.7	H
16932.000	50.1	-25.7	41.4	34.38	74.0	23.9	V
16785.000	50.1	-26.2	41.5	34.83	74.0	23.9	V

Measurement results for Set.2:

Charging Mode/Average detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
16773.750	38.0	-26.2	41.5	22.74	54.0	16.0	H
16785.750	38.0	-26.2	41.5	22.72	54.0	16.0	V
16792.500	38.0	-26.2	41.5	22.70	54.0	16.0	H
16815.000	38.0	-26.1	41.5	22.64	54.0	16.0	V
16800.000	37.9	-26.2	41.5	22.58	54.0	16.1	V
16779.750	37.9	-26.2	41.5	22.64	54.0	16.1	H

Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17975.250	50.7	-25.2	40.8	35.09	74.0	23.3	H
17529.750	50.3	-25.5	41.2	34.60	74.0	23.7	H
16887.750	50.2	-25.9	41.4	34.61	74.0	23.8	V
17103.750	50.2	-25.5	41.3	34.35	74.0	23.8	V
16703.250	50.2	-26.1	41.4	34.87	74.0	23.8	H
16780.500	49.9	-26.2	41.5	34.64	74.0	24.1	V

Measurement results for Set.3:

USB Mode/Average detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
16947.000	38.2	-25.7	41.4	22.44	54.0	15.8	V
16799.250	38.2	-26.2	41.5	22.88	54.0	15.8	V
16778.250	38.2	-26.2	41.5	22.95	54.0	15.8	H
16935.750	38.1	-25.7	41.4	22.37	54.0	15.9	H
16789.500	38.1	-26.2	41.5	22.81	54.0	15.9	V
16788.000	38.0	-26.2	41.5	22.72	54.0	16.0	H

USB Mode/ Peak detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17003.250	50.3	-25.6	41.4	34.50	74.0	23.7	H
17803.500	50.3	-23.1	41.0	32.43	74.0	23.7	V
17655.000	50.0	-25.5	41.1	34.46	74.0	24.0	H
17532.750	49.9	-25.5	41.2	34.21	74.0	24.1	V
16887.000	49.8	-25.9	41.4	34.22	74.0	24.2	V
17052.750	49.8	-25.5	41.4	33.97	74.0	24.2	H

Measurement results for Set.11:

Charging Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
16953.750	38.2	-25.7	41.4	22.43	54.0	15.8	H
16792.500	38.2	-26.2	41.5	22.90	54.0	15.8	H
16941.000	38.0	-25.7	41.4	22.25	54.0	16.0	V
16797.750	38.0	-26.2	41.5	22.69	54.0	16.0	V
16934.250	37.9	-25.7	41.4	22.17	54.0	16.1	V
16789.500	37.9	-26.2	41.5	22.61	54.0	16.1	H

Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
16790.250	51.1	-26.2	41.5	35.81	74.0	22.9	V
16625.250	50.5	-25.9	41.3	35.13	74.0	23.5	H
16503.000	50.2	-26.0	41.1	35.07	74.0	23.8	H
16809.000	49.9	-26.1	41.5	34.55	74.0	24.1	V
17790.000	49.8	-23.3	41.0	32.14	74.0	24.2	V
16698.750	49.8	-26.1	41.4	34.46	74.0	24.2	H

Measurement results for Set.21:

Charging Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
16809.000	38.2	-26.1	41.5	22.85	54.0	15.8	V
16793.250	38.1	-26.2	41.5	22.80	54.0	15.9	H
16803.750	38.1	-26.1	41.5	22.77	54.0	15.9	V
16946.250	38.1	-25.7	41.4	22.34	54.0	15.9	H
16787.250	38.1	-26.2	41.5	22.82	54.0	15.9	H
16801.500	38.1	-26.2	41.5	22.78	54.0	15.9	V

Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17440.500	51.0	-25.3	41.2	35.06	74.0	23.0	V
16933.500	50.6	-25.7	41.4	34.88	74.0	23.4	V
16939.500	50.5	-25.7	41.4	34.76	74.0	23.5	H
16791.750	50.3	-26.2	41.5	35.01	74.0	23.7	V
17656.500	50.3	-25.5	41.1	34.73	74.0	23.7	H
17504.250	49.9	-25.4	41.2	34.07	74.0	24.1	H

Note: The measurement results of Set.1, Set.2, Set.3, Set.11 and Set.21 showed here are worst cases of the combinations of different batteries and USB cables.

Charging Mode, Set.1

15B RE 30MHz-1GHz




Fig A.1 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
31.746000	25.3	109.0	V	245.0	-4.5	14.7	40.0	

15B RE - 1GHz-3GHz




Fig A.2 Radiated Emission from 1GHz to 3GHz

15b RE - 3GHz-18GHz




Fig A.3 Radiated Emission from 3GHz to 18GHz

Charging Mode, Set.2

15B RE 30MHz-1GHz




Fig A.4 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
31.746000	31.8	100.0	V	187.0	-4.5	8.2	40.0	
35.432000	35.2	100.0	V	114.0	-3.1	4.8	40.0	

15B RE - 1GHz-3GHz




Fig A.5 Radiated Emission from 1GHz to 3GHz

15b RE - 3GHz-18GHz




Fig A.6 Radiated Emission from 3GHz to 18GHz

USB Mode, Set.3

15B RE 30MHz-1GHz




Fig A.7 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
48.042000	31.5	109.0	V	107.0	-1.1	8.5	40.0	
69.964000	24.2	109.0	V	315.0	-5.1	15.8	40.0	
136.603000	37.2	125.0	H	271.0	-4.5	6.3	43.5	
140.968000	40.9	125.0	H	270.0	-4.8	2.6	43.5	
204.697000	38.9	121.0	H	10.0	-1.9	4.6	43.5	
212.263000	36.8	109.0	H	-42.0	-1.6	6.7	43.5	

15B RE - 1GHz-3GHz




Fig A.8 Radiated Emission from 1GHz to 3GHz

15b RE - 3GHz-18GHz




Fig A.9 Radiated Emission from 3GHz to 18GHz

Charging Mode, Set.11

15B RE 30MHz-1GHz




Fig A.10 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.358000	33.4	100.0	V	197.0	-4.7	6.6	40.0	
32.813000	31.8	100.0	V	108.0	-4.0	8.2	40.0	
34.656000	32.1	100.0	V	135.0	-3.4	7.9	40.0	

15B RE - 1GHz-3GHz




Fig A.11 Radiated Emission from 1GHz to 3GHz

15b RE - 3GHz-18GHz




Fig A.12 Radiated Emission from 3GHz to 18GHz

Charging Mode, Set.21

15B RE 30MHz-1GHz




Fig A.13 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
84.611000	24.6	121.0	V	259.0	-5.6	15.4	40.0	
350.488000	38.9	109.0	H	79.0	3.5	7.1	46.0	

15B RE - 1GHz-3GHz




Fig A.14 Radiated Emission from 1GHz to 3GHz

15b RE - 3GHz-18GHz




Fig A.15 Radiated Emission from 3GHz to 18GHz

A.2 Conducted Emission

Reference

FCC: CFR Part 15.107(a).

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 7.3.

A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results

Measurement uncertainty: $U= 2.9$ dB, $k=2$.

Charging Mode, Set.1




Fig A.16 Conducted Emission

Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
1.374000	46.8	2000.0	9.000	L1	10.2	9.2	56.0
1.540500	44.2	2000.0	9.000	L1	10.2	11.8	56.0
1.671000	45.3	2000.0	9.000	L1	10.2	10.7	56.0
1.698000	46.3	2000.0	9.000	L1	10.2	9.7	56.0
1.738500	45.7	2000.0	9.000	L1	10.2	10.3	56.0
1.774500	45.6	2000.0	9.000	L1	10.2	10.4	56.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.388500	42.6	2000.0	9.000	N	10.2	5.5	48.1
0.519000	39.5	2000.0	9.000	N	10.2	6.5	46.0
0.843000	40.9	2000.0	9.000	N	10.2	5.1	46.0
0.915000	40.6	2000.0	9.000	N	10.2	5.4	46.0
0.978000	39.0	2000.0	9.000	N	10.2	7.0	46.0
1.369500	40.1	2000.0	9.000	N	10.2	5.9	46.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

Charging Mode, Set.2




Fig A.17 Conducted Emission

Final Result 1


Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154500	52.9	2000.0	9.000	L1	10.1	12.9	65.8
0.208500	49.0	2000.0	9.000	L1	10.1	14.2	63.3
0.262500	44.4	2000.0	9.000	L1	10.1	17.0	61.4
0.307500	41.6	2000.0	9.000	N	10.2	18.5	60.0
0.465000	41.1	2000.0	9.000	L1	10.2	15.5	56.6
0.501000	35.0	2000.0	9.000	L1	10.2	21.0	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154500	38.2	2000.0	9.000	L1	10.1	17.5	55.8
0.208500	38.0	2000.0	9.000	L1	10.1	15.2	53.3
0.312000	35.5	2000.0	9.000	L1	10.2	14.4	49.9
0.361500	33.5	2000.0	9.000	L1	10.2	15.2	48.7
0.465000	35.7	2000.0	9.000	L1	10.2	10.9	46.6
0.726000	33.2	2000.0	9.000	L1	10.2	12.8	46.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

USB Mode, Set.3



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.860000	46.1	2000.0	9.000	N	10.3	9.9	56.0
2.611500	46.0	2000.0	9.000	L1	10.2	10.0	56.0
3.570000	44.0	2000.0	9.000	L1	10.3	12.0	56.0
3.696000	45.5	2000.0	9.000	L1	10.3	10.5	56.0
4.272000	41.8	2000.0	9.000	L1	10.3	14.2	56.0
8.632500	42.4	2000.0	9.000	L1	10.5	17.6	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.199500	36.6	2000.0	9.000	L1	10.1	17.0	53.6
0.262500	31.7	2000.0	9.000	L1	10.1	19.6	51.4
1.878000	37.1	2000.0	9.000	N	10.3	8.9	46.0
2.616000	36.9	2000.0	9.000	L1	10.2	9.1	46.0
3.750000	37.1	2000.0	9.000	N	10.3	8.9	46.0
8.677500	34.3	2000.0	9.000	N	10.5	15.7	50.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

Charging Mode, Set.11




Fig A.18 Conducted Emission

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.798000	42.4	2000.0	9.000	N	10.2	13.6	56.0
1.032000	39.6	2000.0	9.000	L1	10.2	16.4	56.0
1.225500	43.8	2000.0	9.000	N	10.2	12.2	56.0
1.284000	43.6	2000.0	9.000	N	10.2	12.4	56.0
1.896000	43.1	2000.0	9.000	N	10.3	12.9	56.0
2.998500	43.0	2000.0	9.000	N	10.3	13.0	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.555000	33.0	2000.0	9.000	L1	10.2	13.0	46.0
0.861000	33.0	2000.0	9.000	L1	10.2	13.0	46.0
1.032000	29.2	2000.0	9.000	L1	10.2	16.8	46.0
1.099500	31.9	2000.0	9.000	L1	10.2	14.1	46.0
1.221000	33.2	2000.0	9.000	L1	10.2	12.8	46.0
1.779000	31.5	2000.0	9.000	N	10.2	14.5	46.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

Charging Mode, Set.21




Fig A.19 Conducted Emission

Final Result 1








Frequency (MHz)	QuasiPeak (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.550500	44.1	2000.0	9.000	N	10.2	11.9	56.0
0.802500	41.8	2000.0	9.000	N	10.2	14.2	56.0
0.919500	42.4	2000.0	9.000	N	10.2	13.6	56.0
1.221000	43.7	2000.0	9.000	N	10.2	12.3	56.0
1.270500	42.2	2000.0	9.000	N	10.2	13.8	56.0
1.896000	43.0	2000.0	9.000	N	10.3	13.0	56.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.550500	33.9	2000.0	9.000	N	10.2	12.1	46.0
0.789000	32.8	2000.0	9.000	L1	10.2	13.2	46.0
1.158000	32.6	2000.0	9.000	L1	10.2	13.4	46.0
1.221000	33.9	2000.0	9.000	L1	10.2	12.1	46.0
1.279500	32.8	2000.0	9.000	L1	10.2	13.2	46.0
1.779000	32.1	2000.0	9.000	L1	10.2	13.9	46.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

ANNEX B: Accreditation Certificate

<p>United States Department of Commerce National Institute of Standards and Technology</p>  <hr/> <p>Certificate of Accreditation to ISO/IEC 17025:2005</p> <hr/> <p>NVLAP LAB CODE: 600118-0</p> <p>Telecommunication Technology Labs, CAICT Beijing China</p> <p><i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i></p> <p>Electromagnetic Compatibility & Telecommunications</p> <p><i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i></p> <hr/> <table border="0" style="width: 100%;"><tr><td style="width: 40%; text-align: center;"><p>2016-09-29 through 2017-09-30 <i>Effective Dates</i></p></td><td style="width: 20%; text-align: center;"></td><td style="width: 40%; text-align: center;"> <i>For the National Voluntary Laboratory Accreditation Program</i></td></tr></table>		<p>2016-09-29 through 2017-09-30 <i>Effective Dates</i></p>		 <i>For the National Voluntary Laboratory Accreditation Program</i>
<p>2016-09-29 through 2017-09-30 <i>Effective Dates</i></p>		 <i>For the National Voluntary Laboratory Accreditation Program</i>		

END OF REPORT