



The Photos of SAR test

No. I18Z60479-SEM03

For

TCL Communication Ltd.

LTE/UMTS/GSM mobile phone

Model Name: A502DL

With

Hardware Version: PIO

Software Version: vGP1

FCC ID: 2ACCJH086



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT


No. 51, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504


Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn




Picture - 1 Constituents of the sample




Picture - 2 Left Hand Touch Cheek Position



Picture - 3 Left Hand Tilt 15° Position




Picture - 4 Right Hand Touch Cheek Position




Picture - 5 Right Hand Tilt 15° Position

Test positions for body:


The Body SAR is tested at the following 6 test positions all with the distance =10mm between the EUT and the phantom bottom:




Picture - 6 Front




Picture - 7 Rear




Picture - 8 Left edge



Picture - 9 Right edge



Picture - 10 Bottom edge



Picture - 11 Top edge