



# TEST REPORT

## No. I18Z61343-EMC04

for

**Vodafone Procurement Company S.à.r.l**

**LTE / UMTS / GSM mobile phone**

**Model Name: VFD 528**

**FCC ID: 2ACCJH095**

with

**Hardware Version: 05**

**Software Version: v7LT8**

**Issued Date: 2018-08-15**



**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

**Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: [ctl\\_terminals@caict.ac.cn](mailto:ctl_terminals@caict.ac.cn), website: [www.caict.ac.cn](http://www.caict.ac.cn)



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I18Z61343-EMC04	Rev.0	1 <sup>st</sup> edition	2018-08-15



## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. TESTING LOCATION .....</b>	<b>4</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>4</b>
<b>1.3. PROJECT DATA .....</b>	<b>4</b>
<b>1.4. SIGNATURE.....</b>	<b>4</b>
<b>2. CLIENT INFORMATION .....</b>	<b>5</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>5</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>5</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>6</b>
<b>3.1. ABOUT EUT.....</b>	<b>6</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>6</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....</b>	<b>6</b>
<b>3.4. EUT SET-UPS .....</b>	<b>10</b>
<b>4. REFERENCE DOCUMENTS.....</b>	<b>11</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING.....</b>	<b>11</b>
<b>5. LABORATORY ENVIRONMENT.....</b>	<b>12</b>
<b>6. SUMMARY OF TEST RESULTS.....</b>	<b>13</b>
<b>7. TEST EQUIPMENTS UTILIZED.....</b>	<b>14</b>
<b>ANNEX A: MEASUREMENT RESULTS .....</b>	<b>15</b>
<b>ANNEX B: PERSONS INVOLVED IN THIS TESTING .....</b>	<b>33</b>

## **1. Test Laboratory**

### **1.1. Testing Location**

CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China 100191

### **1.2. Testing Environment**

Normal Temperature: 15-35°C


Relative Humidity: 20-75%

### **1.3. Project data**

Testing Start Date: 2018-04-12

Testing End Date: 2018-08-07

### **1.4. Signature**




---

**Wang Junqing**  
**(Prepared this test report)**



---

**Zhang Ying**  
**(Reviewed this test report)**



---

**Liu Baodian**  
**Deputy Director of the laboratory**  
**(Approved this test report)**



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCL Communication Ltd.  
7/F, Block F4, TCL Communication Technology Building, TCL  
Address /Post: International E City, Zhong Shan Yuan Road, Nanshan District,  
Shenzhen, Guangdong, P.R. China 518052  
City: Shenzhen  
Postal Code: 518052  
Country: China  
Contact Person: Gong Zhizhou  
Contact Email: zhizhou.gong@tcl.com  
Telephone: 0086-755-36611722  
Fax: /

### **2.2. Manufacturer Information**

Company Name: Vodafone Procurement Company S.à.r.l  
Address /Post: Vodafone S.à.r.l, 15 rue Edward Steichen, L-2540 Luxembourg,  
Grand-Duché de Luxembourg  
City: /  
Postal Code: /  
Country: /  
Telephone: /  
Fax: /

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	LTE / UMTS / GSM mobile phone
Model Name	VFD 528
FCC ID	2ACCJH095
Extreme vol. Limits	3.5VDC to 4.4VDC (nominal: 3.8VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, CAICT.

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>SN or IMEI</b>	<b>HW Version</b>	<b>SW Version</b>
EUT1	/	05	v7LT8

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>	<b>SN</b>	<b>Remarks</b>
AE1	Battery	/	1860562BA001
AE2	Charger	/	16TCT-CH-1675
AE3	Charger	/	1860562CH004
AE4	Charger	/	1860562CH002
AE5	USB Cable	/	16TCT-DC-0029
AE6	USB Cable	/	17TCT-DC-0492
AE7	Charger	/	/
AE8	Charger	/	/
AE9	Charger	/	/
AE10	Charger	/	/
AE11	Charger	/	/
AE12	Charger	/	/
AE13	Charger	/	/
AE14	Charger	/	/
AE15	Charger	/	/
AE16	Charger	/	/
AE17	Charger	/	/
AE18	Charger	/	/
AE19	Charger	/	/
AE20	Charger	/	/
AE21	Charger	/	/
AE22	Battery	/	/



AE1

Model CAB1930000C7  
Manufacturer Ningbo Veken Battery Co.,LTD  
Capacitance 2000mAh  
Nominal voltage 3.85V

AE2

Model CBA0066AGAC5  
Manufacturer PUAN  
Length of cable /

AE3

Model CBA0066AGAC7  
Manufacturer CHENYANG  
Length of cable /

AE4

Model CBA3068AGAC5  
Manufacturer PUAN  
Length of cable /

AE5

Model CDA3122005C1  
Manufacturer HUIZHOU JUWEI ELECTRONICS CO.,LTD  
Length of cable 100cm

AE6

Model CDA3122005C2  
Manufacturer ShengHua Industrial Co., Ltd  
Length of cable 100cm

AE7

Model CBA0066AAAC5  
Manufacturer HUIZHOU PUAN ELECTRONICS CO.,LTD  
Length of cable /

AE8

Model CBA0066AAAC7  
Manufacturer JIANGSU CHENYANG ELECTRON CO.,LTD  
Length of cable /

AE9

Model CBA0066ABAC5  
Manufacturer PUAN  
Length of cable /

AE10

Model CBA0066ABAC7  
Manufacturer CHENYANG  
Length of cable /



AE11	
Model	CBA3068AAAC5
Manufacturer	HUIZHOU PUAN ELECTRONICS CO.,LTD
Length of cable	/
AE12	
Model	CBA3068ABAC5
Manufacturer	PUAN
Length of cable	/
AE13	
Model	CBA3068AANC7
Manufacturer	CHENYANG
Length of cable	/
AE14	
Model	CBA3068ABNC7
Manufacturer	CHENYANG
Length of cable	/
AE15	
Model	CBA0066AA2C5
Manufacturer	PUAN
Length of cable	/
AE16	
Model	CBA0066ABNC5
Manufacturer	PUAN
Length of cable	/
AE17	
Model	CBA0066AANC7
Manufacturer	CHENYANG
Length of cable	/
AE18	
Model	CBA0066ABNC7
Manufacturer	CHENYANG
Length of cable	/
AE19	
Model	CBA3068AANC5
Manufacturer	PUAN
Length of cable	/
AE20	
Model	CBA3068ABNC5
Manufacturer	PUAN
Length of cable	/
AE21	
Model	CBA3068ACNC5
Manufacturer	PUAN
Length of cable	/





AE22

Model	CAB1930006C7
Manufacturer	Ningbo Veken Battery Co.,LTD
Capacitance	2000mAh
Nominal voltage	3.85V

\*AE ID: is used to identify the test sample in the lab internally.

Note: The USB cables are shielded.

### 3.4. EUT set-ups

<b>EUT set-up No.</b>	<b>Combination of EUT and AE</b>	<b>Remarks</b>
Set.1	EUT1+ AE1+ AE2+ AE5/AE6	Charger
Set.2	EUT1+ AE1+ AE3+ AE5/AE6	Charger
Set.3	EUT1+ AE1+ AE4+ AE5/AE6	Charger
Set.4	EUT1+ AE1+ AE5/AE6	USB mode
Set.5	EUT1+ AE1+ AE13+ AE5/AE6	Charger

Note: LTE / UMTS / GSM mobile phone, VFD 528 manufactured by Vodafone Procurement Company S.à.r.l is a variant model based on 5033X for conformance test. According to the KDB 484596, the following test is performed:

GSM 1900MHz	Set.5	All tests
-------------	-------	-----------

other results are cited from the initial model. The report number for initial model is I18Z60981-EMC01.

## **4. Reference Documents**

### **4.1. Reference Documents for testing**

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	2016
ANSI C63.4	American National Standard for Methods of Measurement of Radio- Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

Note: The test methods have no deviation with standards.

## 5. LABORATORY ENVIRONMENT

**Semi-anechoic chamber SAC-1** (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 M
Ground system resistance	< 4
Normalised site attenuation (NSA)	< ± 4 dB, 3m/10m distance, from 30 to 1000 MHz
Site voltage standing-wave ratio (SVSWR)	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

**Shielded room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz— 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω



## 6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	B.1	P	CTTL(huayuan North Road)
2	Conducted Emission	15.107(a)	B.2	P	CTTL(huayuan North Road)

**7. Test Equipments Utilized**

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE	CALIBRATION INTERVAL
1	Test Receiver	ESU26	100235	R&S	2019-02-28	1 year
2	Test Receiver	ESCI 7	100344	R&S	2019-02-28	1 year
3	Universal Radio Communication Tester	CMU200	109914	R&S	2019-04-01	1 year
4	Universal Radio Communication Tester	CMW500	116588	R&S	2018-12-26	1 year
5	LISN	ENV216	101200	R&S	2019-04-15	1 year
6	EMI Antenna	VULB 9163	9163-301	Schwarzbeck	2019-01-03	3 years
7	EMI Antenna	3115	00167250	ETS-Lindgren	2019-06-17	1 years
8	PC	OPTIPLEX 380	2X1YV2X	DELL	N/A	N/A
9	Printer	P1606dn	VNC3L52122	HP	N/A	N/A

Test Item	Test Software and Version	Software Vendor
Radiated Continuous Emission	EMC32 V9.01	R&S
Conducted Emission	EMC32 V8.52.0	R&S

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 Radiated Emission**

#### **Reference**

FCC: CFR Part 15.109(a).

#### **A.1.1 Method of measurement**

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at distances of 10 meters(for 30MHz-1GHz) and 3 meters (for above 1GHz) is tested. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

#### **A.1.2 EUT Operating Mode**

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

#### **A.1.3 Measurement Limit**

Frequency range (MHz)	Field strength limit ( $\mu\text{V/m}$ )		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

#### **A.1.4 Test Condition**

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/1MHz	15	Peak, Average

### A.1.5 Measurement Results

A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

$G_A$ : Antenna factor of receive antenna

$G_{\text{PL}}$ : Path Loss

$P_{\text{Mea}}$ : Measurement result on receiver.

Measurement uncertainty (worst case):  $U = 4.3 \text{ dB}$ ,  $k=2$ .

#### Measurement results for Set.1:

##### Charging Mode/Average detector

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Antenna Pol. (H/V)
17858.050	38.7	-18.5	45.6	11.600	H
17387.150	38.6	-19.5	41.5	16.600	H
17787.500	38.4	-18.5	45.6	11.300	V
17371.850	38.4	-19.5	41.5	16.400	H
17908.200	38.4	-18.5	45.6	11.300	H
17588.600	38.2	-18.9	45.6	11.500	H

##### Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Antenna Pol. (H/V)
17978.750	50.2	-17.7	45.6	22.300	H
17902.250	49.3	-18.5	45.6	22.200	H
17818.100	48.8	-18.5	45.6	21.700	V
17869.950	48.6	-18.5	45.6	21.500	H
17618.350	48.6	-18.9	45.6	21.900	H
17716.950	48.6	-18.9	45.6	21.900	H



**Measurement results for Set.2:**

**Charging Mode/Average detector**

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Antenna Pol. (H/V)
17416.050	38.7	-19.2	41.5	16.400	H
17903.100	38.6	-18.5	45.6	11.500	H
17371.000	38.4	-19.5	41.5	16.400	V
17459.400	38.4	-19.2	41.5	16.100	H
17975.350	38.4	-17.7	45.6	10.500	H
17869.100	38.4	-18.5	45.6	11.300	H

**Charging Mode/Peak detector**

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Antenna Pol. (H/V)
17757.750	49.1	-18.5	45.6	22.000	H
17422.000	49.0	-19.2	41.5	26.700	H
17881.000	49.0	-18.5	45.6	21.900	V
17462.800	49.0	-19.2	41.5	26.700	H
17914.150	48.9	-18.5	45.6	21.800	H
17427.950	48.8	-19.2	41.5	26.500	H

**Measurement results for Set.3:**

**Charging Mode/Average detector**

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Antenna Pol. (H/V)
17763.700	38.5	-18.5	45.6	11.400	H
17897.150	38.5	-18.5	45.6	11.400	H
17908.200	38.4	-18.5	45.6	11.300	V
17906.500	38.3	-18.5	45.6	11.200	H
17282.600	38.3	-19.5	41.5	16.300	H
17893.750	38.2	-18.5	45.6	11.100	H

**Charging Mode/ Peak detector**

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Antenna Pol. (H/V)
17858.050	48.9	-18.5	45.6	21.800	H
17227.350	48.8	-19.5	41.5	26.800	H
17869.950	48.7	-18.5	45.6	21.600	V
17381.200	48.7	-19.5	41.5	26.700	H
17832.550	48.7	-18.5	45.6	21.600	H
17897.150	48.6	-18.5	45.6	21.500	H

**Measurement results for Set.4:**

**USB Mode/Average detector**

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Antenna Pol. (H/V)
17888.367	37.4	-18.5	45.6	10.300	H
17365.900	37.4	-19.5	41.5	15.400	H
17789.200	37.4	-18.5	45.6	10.300	V
17891.767	37.2	-18.5	45.6	10.100	H
17773.333	37.2	-18.5	45.6	10.100	H
17875.333	37.2	-18.5	45.6	10.100	H

**USB Mode/ Peak detector**

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Antenna Pol. (H/V)
17411.800	49.8	-19.2	41.5	27.500	H
17535.333	49.1	-19.2	45.6	22.700	H
17769.933	48.6	-18.5	45.6	21.500	V
17912.167	48.6	-18.5	45.6	21.500	H
17941.067	48.5	-17.7	45.6	20.600	H
17389.700	48.5	-19.2	41.5	26.200	H

**Measurement results for Set.5:**

**Charging Mode/Average detector**

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Antenna Pol. (H/V)
17997.167	40.2	-25.5	43.4	22.302	H
17969.967	40.2	-25.5	43.4	22.302	H
17986.400	40.1	-25.5	43.4	22.202	V
17951.833	40.1	-25.5	43.4	22.202	H
17968.267	40.1	-25.5	43.4	22.202	H
17983.567	40.0	-25.5	43.4	22.102	H

**Charging Mode/ Peak detector**

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Antenna Pol. (H/V)
17947.300	52.0	-25.5	43.4	34.102	H
17981.867	51.4	-25.5	43.4	33.502	H
17976.200	51.3	-25.5	43.4	33.402	V
17964.300	51.3	-25.5	43.4	33.402	H
17991.500	51.1	-25.5	43.4	33.202	H
17924.633	51.1	-25.5	43.4	33.202	H

Note: The measurement results of Set.1, Set.2, Set.3, Set.4 and Set.5 showed here are worst cases of the combinations of different USB cables.

Charging Mode, Set.1




Fig A.1 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
49.418000	17.85	30.00	12.15	1000.0	120.000	176.0	V	30.0




Fig A.2 Radiated Emission from 1GHz to 18GHz

Charging Mode, Set.2




Fig A.3 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
50.061000	18.01	30.00	11.99	1000.0	120.000	111.0	V	30.0




Fig A.4 Radiated Emission from 1GHz to 18GHz

Charging Mode, Set.3




Fig A.5 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
49.576000	18.50	30.00	11.50	1000.0	120.000	125.0	V	30.0
52.532000	16.96	30.00	13.04	1000.0	120.000	100.0	V	195.0




Fig A.6 Radiated Emission from 1GHz to 18GHz

USB Mode, Set.4





Fig A.7 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
34.074000	24.91	30.00	5.09	1000.0	120.000	184.0	V	202.0
39.090000	25.79	30.00	4.21	1000.0	120.000	325.0	V	93.0
39.857000	27.45	30.00	2.55	1000.0	120.000	125.0	V	97.0
42.495000	23.22	30.00	6.78	1000.0	120.000	278.0	V	174.0





**Fig A.8 Radiated Emission from 1GHz to 18GHz**

Charging Mode, Set.5




Fig A.9 Radiated Emission from 30MHz to 1GHz




Fig A.10 Radiated Emission from 1GHz to 18GHz

## A.2 Conducted Emission

### Reference

FCC: CFR Part 15.107(a).

### A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 7.3.

### A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

### A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency

### A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

### A.2.5 Measurement Results

Measurement uncertainty:  $U= 2.9$  dB,  $k=2$ .

#### Charging Mode, Set.1




Fig A.11 Conducted Emission

#### Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.195000	40.7	2000.0	9.000	L1	19.8	23.1	63.8
0.735000	36.6	2000.0	9.000	L1	19.8	19.4	56.0
1.131000	38.4	2000.0	9.000	L1	19.6	17.6	56.0
1.968000	42.1	2000.0	9.000	L1	19.7	13.9	56.0
3.097500	43.5	2000.0	9.000	L1	19.7	12.5	56.0
3.844500	41.5	2000.0	9.000	L1	19.6	14.5	56.0

#### Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.636000	25.3	2000.0	9.000	L1	19.8	20.7	46.0
1.108500	27.8	2000.0	9.000	L1	19.6	18.2	46.0
1.869000	31.1	2000.0	9.000	L1	19.7	14.9	46.0
2.688000	33.0	2000.0	9.000	L1	19.7	13.0	46.0
3.628500	31.9	2000.0	9.000	L1	19.6	14.1	46.0
6.171000	28.5	2000.0	9.000	L1	19.7	21.5	50.0

Note: The measurement results showed here are worst cases of the combinations of different USB cables.

Charging Mode, Set.2




Fig A.12 Conducted Emission

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.393000	42.5	2000.0	9.000	L1	19.9	15.5	58.0
0.672000	44.7	2000.0	9.000	L1	19.8	11.3	56.0
1.180500	39.5	2000.0	9.000	L1	19.6	16.5	56.0
2.004000	46.3	2000.0	9.000	L1	19.7	9.7	56.0
3.331500	45.0	2000.0	9.000	L1	19.7	11.0	56.0
4.110000	46.0	2000.0	9.000	L1	19.6	10.0	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.339000	38.5	2000.0	9.000	L1	19.8	10.7	49.2
0.730500	35.0	2000.0	9.000	L1	19.8	11.0	46.0
1.176000	37.3	2000.0	9.000	L1	19.6	8.7	46.0
2.067000	37.5	2000.0	9.000	L1	19.7	8.5	46.0
3.484500	32.7	2000.0	9.000	L1	19.7	13.3	46.0
4.272000	37.0	2000.0	9.000	L1	19.6	9.0	46.0

Note: The measurement results showed here are worst cases of the combinations of different USB cables.

Charging Mode, Set.3




Fig A.13 Conducted Emission

Final Result 1


Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.424500	40.1	2000.0	9.000	L1	19.9	17.2	57.4
0.703500	40.1	2000.0	9.000	L1	19.8	15.9	56.0
1.216500	44.1	2000.0	9.000	L1	19.6	11.9	56.0
1.729500	44.9	2000.0	9.000	L1	19.7	11.1	56.0
2.796000	43.3	2000.0	9.000	L1	19.7	12.7	56.0
3.655500	41.5	2000.0	9.000	L1	19.6	14.5	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.415500	28.7	2000.0	9.000	L1	19.9	18.9	47.5
0.703500	29.3	2000.0	9.000	L1	19.8	16.7	46.0
1.212000	34.1	2000.0	9.000	L1	19.6	11.9	46.0
1.797000	31.9	2000.0	9.000	L1	19.7	14.1	46.0
2.674500	32.9	2000.0	9.000	L1	19.7	13.1	46.0
3.655500	28.3	2000.0	9.000	L1	19.6	17.7	46.0

Note: The measurement results showed here are worst cases of the combinations of different USB cables.

USB Mode, Set.4



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.204000	45.1	2000.0	9.000	L1	19.8	18.3	63.4
0.978000	32.1	2000.0	9.000	N	19.7	23.9	56.0
3.520500	30.8	2000.0	9.000	N	19.7	25.2	56.0
4.398000	33.7	2000.0	9.000	N	19.7	22.3	56.0
6.598500	41.8	2000.0	9.000	N	19.8	18.2	60.0
24.009000	38.3	2000.0	9.000	N	20.2	21.7	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.168000	44.7	2000.0	9.000	L1	19.8	10.4	55.1
0.267000	34.4	2000.0	9.000	L1	19.8	16.8	51.2
3.381000	21.7	2000.0	9.000	N	19.7	24.3	46.0
4.600500	25.4	2000.0	9.000	N	19.7	20.6	46.0
6.598500	38.9	2000.0	9.000	N	19.8	11.1	50.0
24.009000	38.4	2000.0	9.000	N	20.2	11.6	50.0

Note: The measurement results showed here are worst cases of the combinations of different USB cables.

Charging Mode, Set.5




Fig A.14 Conducted Emission

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.402000	42.7	2000.0	9.000	L1	19.9	15.1	57.8
0.690000	43.6	2000.0	9.000	L1	19.8	12.4	56.0
1.207500	45.5	2000.0	9.000	L1	19.6	10.5	56.0
2.071500	46.0	2000.0	9.000	L1	19.7	10.0	56.0
3.340500	45.4	2000.0	9.000	L1	19.7	10.6	56.0
3.772500	45.4	2000.0	9.000	L1	19.6	10.6	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.402000	33.1	2000.0	9.000	On	L1	19.9	14.7
0.456000	38.2	2000.0	9.000	On	L1	19.9	8.6
1.207500	38.5	2000.0	9.000	On	L1	19.6	7.5
2.071500	36.0	2000.0	9.000	On	L1	19.7	10.0
2.980500	34.9	2000.0	9.000	On	L1	19.7	11.1
3.975000	37.2	2000.0	9.000	On	L1	19.6	8.8

Note: The measurement results showed here are worst cases of the combinations of different USB cables.





**ANNEX B: PERSONS INVOLVED IN THIS TESTING**

<b>Test Item</b>	<b>Test Software and Version</b>	<b>Software Vendor</b>	<b>Test operator</b>
Conducted Emission	EMC32 V8.5.2	R&S	Wang Huan
Radiated Emission	EMC32 V9.01.00	R&S	Li Jinpeng

**\*\*\*END OF REPORT\*\*\***