



# TEST REPORT

No. I18Z61787-WMD02

for

**TCL Communication Ltd.**

**GSM/UMTS/LTE mobile phone**

**Model Name: A503DL**

**FCC ID: 2ACCJH096**

with

**Hardware Version: PIO**

**Software Version: vTV5**

**Issued Date: 2018-11-09**



**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

**Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: [ctl\\_terminals@caict.ac.cn](mailto:ctl_terminals@caict.ac.cn), website: [www.caict.ac.cn](http://www.caict.ac.cn)

## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I18Z61787-WMD02	Rev.0	1 <sup>st</sup> edition	2018-11-09



## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. TESTING LOCATION .....</b>	<b>4</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>4</b>
<b>1.3. PROJECT DATA .....</b>	<b>4</b>
<b>1.4. SIGNATURE.....</b>	<b>4</b>
<b>2. CLIENT INFORMATION.....</b>	<b>5</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>5</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>5</b>
<b>3. EQUIPMENT UNDERTEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>6</b>
<b>3.1. ABOUT EUT .....</b>	<b>6</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>6</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>6</b>
<b>3.4. NORMAL ACCESSORY SETTING.....</b>	<b>7</b>
<b>3.5. GENERAL DESCRIPTION .....</b>	<b>7</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>8</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING.....</b>	<b>8</b>
<b>5. LABORATORY ENVIRONMENT.....</b>	<b>9</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>10</b>
<b>7. TESTEQUIPMENTS UTILIZED.....</b>	<b>11</b>
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>12</b>
<b>A.1 OUTPUT POWER.....</b>	<b>12</b>
<b>A.2 EMISSION LIMIT.....</b>	<b>18</b>
<b>A.3 FREQUENCY STABILITY .....</b>	<b>24</b>
<b>A.4 OCCUPIED BANDWIDTH.....</b>	<b>28</b>
<b>A.5 EMISSION BANDWIDTH .....</b>	<b>41</b>
<b>A.6 BAND EDGE COMPLIANCE.....</b>	<b>53</b>
<b>A.7 CONDUCTED SPURIOUS EMISSION .....</b>	<b>60</b>
<b>A.8 PEAK-TO-AVERAGE POWER RATIO .....</b>	<b>68</b>
<b>ANNEX B: ACCREDITATION CERTIFICATE.....</b>	<b>69</b>

## 1. Test Laboratory

### 1.1. Testing Location

Location 1: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China 100191

Location 2: CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,  
Haidian District, Beijing, P. R. China 100191

### 1.2. Testing Environment

Normal Temperature: 15-35°C

Relative Humidity: 20-75%

### 1.3. Project data

Testing Start Date: 2018-10-15

Testing End Date: 2018-11-07

### 1.4. Signature



---

Dong Yuan  
(Prepared this test report)



---

Zhou Yu  
(Reviewed this test report)



---

Zhao Hui Lin  
Deputy Director of the laboratory  
(Approved this test report)



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCL Communication Ltd.  
7/F, Block F4, TCL Communication Technology Building, TCL  
Address /Post: International E City, Zhong Shan Yuan Road, Nanshan District,  
Shenzhen, Guangdong, P.R. China 518052  
Contact: Gong Zhizhou  
Email: zhizhou.gong@tcl.com  
Telephone: 0086-755-36611722  
Fax: 0086-755-36612000-81722

### **2.2. Manufacturer Information**

Company Name: TCL Communication Ltd.  
7/F, Block F4, TCL Communication Technology Building, TCL  
Address /Post: International E City, Zhong Shan Yuan Road, Nanshan District,  
Shenzhen, Guangdong, P.R. China 518052  
Contact: Gong Zhizhou  
Email: zhizhou.gong@tcl.com  
Telephone: 0086-755-36611722  
Fax: 0086-755-36612000-81722

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	GSM/UMTS/LTE mobile phone
Model Name	A503DL
FCC ID	2ACCJH096
Antenna	Embedded
Output power	24.26dBm maximum EIRP measured for WCDMA Band IV
Extreme vol. Limits	3.5VDC to 4.4VDC (nominal: 3.8VDC)
Extreme temp. Tolerance	-10°C to +40°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>IMEI</b>	<b>HW Version</b>	<b>SW Version</b>	<b>Date of receipt</b>
UT04a	014989000001253	PIO	vTV5	2018-10-08

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>
AE1	Battery
AE1	
Model	CAC2900019C1
Manufacturer	BYD
Capacitance	2900mAh

\*AE ID: is used to identify the test sample in the lab internally.



### **3.4. Normal Accessory setting**

Fully charged battery was used during the test.

### **3.5. General Description**

The Equipment Under Test (EUT) is a model of GSM/UMTS/LTE mobile phone with embedded antenna. Manual and specifications of the EUT were provided to fulfil the test.

## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-17 Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-17 Edition
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES	10-1-17 Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2016
TIA-102.CAAA-E	DIGITAL C4FMCQPSK TRANSCEIVER MEASUREMENT METHODS	2016
ANSI C63.26	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services	2015
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS	v03r01



## 5. LABORATORY ENVIRONMENT

**Control room / conducted chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber 2** (8.6 meters X 6.1 meters X 3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 1 Ω
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

**Semi-anechoic chamber 2 / Fully-anechoic chamber 3** (10 meters X 6.7 meters X 6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

## 6. SUMMARY OF TEST RESULTS

### WCDMA Band II

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	24.232(c)	P
2	Emission Limit	24.238, 2.1051	P
3	Frequency Stability	24.235, 2.1055	P
4	Occupied Bandwidth	2.1049(h)(i)	P
5	Emission Bandwidth	24.238(b)	P
6	Band Edge Compliance	24.238(b)	P
7	Conducted Spurious Emission	24.238, 2.1057	P
8	Peak-to-Average Power Ratio	24.232(d)	P

### WCDMA Band V

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	§2.1046(a), 22.913(a)	P
2	Emission Limit	22.917, 2.1051	P
3	Frequency Stability	22.235, 2.1055	P
4	Occupied Bandwidth	2.1049(h)(i)	P
5	Emission Bandwidth	22.917(b)	P
6	Band Edge Compliance	22.917(b)	P
7	Conducted Spurious Emission	22.917, 2.1057	P

### WCDMA Band IV

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50(d)(4)	P
2	Emission Limit	27.53(h), 2.1051	P
3	Frequency Stability	27.54, 2.1055	P
4	Occupied Bandwidth	2.1049(h)(i)	P
5	Emission Bandwidth	27.53(h)	P
6	Band Edge Compliance	27.53(h)	P
7	Conducted Spurious Emission	27.53(h), 2.1057	P
8	Peak-to-Average Power Ratio	27.50(a)	P

## 7. Test Equipments Utilized

NO.	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	Test Receiver	ESU26	100235	R&S	2019-03-31	1 year
2	Test Receiver	ESU26	100376	R&S	2018-12-27	1 year
3	EMI Antenna	3117	00058889	ETS-Lindgren	2020-05-27	3 year
4	Universal Radio Communication Tester	CMU200	108646	R&S	2019-01-05	1 year
5	Universal Radio Communication Tester	CMW500	159082	R&S	2019-01-05	1 year
6	Spectrum Analyzer	FSU26	200030	R&S	2019-06-04	1 year
7	EMI Antenna	VULB9163	9163-235	Schwarzbeck	2019-05-10	3 year
8	Signal Generator	SMF100A	101295	R&S	2018-12-23	1 year
9	Climate chamber	SH-242	93008556	ESPEC	2019-12-21	2 year
10	Loop Antenna	HFH2-Z2	829324/007	R&S	2018-12-14	3 year
1	Test Receiver	ESU26	100235	R&S	2019-03-31	1 year

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 OUTPUT POWER**

#### **A.1.1 Summary**

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### **A.1.2 Conducted**

##### **A.1.2.1 Method of Measurements**

The EUT was set up for the max output power with pseudo random data modulation. These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II; 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V (bottom, middle and top of operational frequency range).

#### **WCDMA Band II**

##### **Measurement result-QPSK**

	CH	Frequency(MHz)	output power(dBm)
WCDMA (Band II)	9262	1852.4	23.94
	9400	1880.0	23.97
	9538	1907.6	23.99

##### **Measurement result-16QAM**

	CH	Frequency(MHz)	output power(dBm)
WCDMA (Band II)	9262	1852.4	22.36
	9400	1880.0	22.55
	9538	1907.6	22.77

#### **WCDMA Band V**

##### **Measurement result-QPSK**

	CH	Frequency(MHz)	output power(dBm)
WCDMA (Band V)	4132	826.4	22.77
	4183	836.6	22.38
	4233	846.6	22.83

##### **Measurement result-16QAM**

	CH	Frequency(MHz)	output power(dBm)
WCDMA (Band V)	4132	826.4	22.57
	4183	836.6	22.58
	4233	846.6	22.63



**WCDMA Band IV**

**Measurement result-QPSK**

WCDMA (Band IV)	CH	Frequency(MHz)	output power(dBm)
	1312	1712.4	22.93
	1450	1740.0	22.98
	1513	1752.6	22.83

**Measurement result-16QAM**

WCDMA (Band IV)	CH	Frequency(MHz)	output power(dBm)
	1312	1712.4	22.98
	1450	1740.0	22.99
	1513	1752.6	22.79

### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."


Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Rule Part 27.50(d)(2) specifies, "Fixed, mobile, and portable (handheld) stations operating in the 1710–1755MHz band are limited to a peak EIRP of 1 watt."


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as ( $P_r$ ).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the

reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.  
The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .



**WCDMA Band II-EIRP**

**Limits**

	Burst Peak EIRP (dBm)
WCDMA Band II	≤33dBm (2W)

**Measurement result-QPSK**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.40	-25.24	2.84	43.75	4.87	20.54	33.00	12.46	H
1880.00	-25.00	2.85	43.75	4.82	20.72	33.00	12.28	H
1907.60	-22.61	2.88	43.77	4.77	23.05	33.00	9.95	H

**Measurement result-16QAM**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.40	-26.39	2.84	43.75	4.87	19.39	33.00	13.61	V
1880.00	-25.92	2.85	43.75	4.82	19.80	33.00	13.20	H
1907.60	-23.73	2.88	43.77	4.77	21.93	33.00	11.07	H

**ANALYZER SETTINGS: RBW = VBW = 5MHz**

Frequency: 1907.60MHz

Peak EIRP(dBm)=P<sub>Mea</sub>(-22.61dBm)-P<sub>cl</sub>(2.88dB)-P<sub>Ag</sub>(-43.77dB)-G<sub>a</sub>(-4.77dB)= 23.05dBm

**WCDMA Band V-ERP**

**Limits**

	Burst Peak ERP (dBm)
WCDMA Band V	≤38.45dBm

**Measurement result-QPSK**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.40	-20.69	2.25	45.76	0.93	2.15	21.60	38.45	16.85	H
836.60	-21.31	2.26	45.66	0.82	2.15	20.76	38.45	17.69	H
846.60	-22.58	2.26	45.56	0.81	2.15	19.38	38.45	19.07	H

**Measurement result-16QAM**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.40	-21.70	2.25	45.76	0.93	2.15	20.59	38.45	17.86	H
836.60	-22.26	2.26	45.66	0.82	2.15	19.81	38.45	18.64	H
846.60	-23.06	2.26	45.56	0.81	2.15	18.90	38.45	19.55	H

**ANALYZER SETTINGS: RBW = VBW = 5MHz**

Frequency: 826.40MHz

Peak ERP(dBm)=P<sub>Mea</sub>(-20.69dBm)-P<sub>cl</sub>(2.25dB)-P<sub>Ag</sub>(-45.76dB)-G<sub>a</sub>(-0.93dB)-2.15dB= 21.60dBm





**WCDMA Band IV-EIRP**

**Limits**

	Burst Peak EIRP (dBm)
WCDMA Band IV	30dBm (1W)

**Measurement result-QPSK**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>ci</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.40	-21.40	3.66	44.10	5.12	24.16	30.00	5.84	H
1740.00	-21.60	4.36	44.15	5.07	23.26	30.00	6.74	H
1752.60	-21.08	3.85	44.14	5.05	24.26	30.00	5.74	H

**Measurement result-16QAM**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>ci</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.40	-22.82	3.66	44.10	5.12	22.74	30.00	7.26	H
1740.00	-22.55	4.36	44.15	5.07	22.31	30.00	7.69	H
1752.60	-22.13	3.85	44.14	5.05	23.21	30.00	6.79	H

**ANALYZER SETTINGS: RBW = VBW = 5MHz**

Frequency: 1752.60MHz

Peak EIRP(dBm)=P<sub>Mea</sub>(-21.08dBm)-P<sub>ci</sub>(3.85dB)-P<sub>Ag</sub>(-44.14dB)-G<sub>a</sub> (-5.05dB)= 24.26dBm

**Note: The EUT is tested in vertical polarization mode**

## **A.2 EMISSION LIMIT**


### **A.2.1 Measurement Method**

The measurements procedures in TIA-603E-2016 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238, Part 22.917. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II, WCDMA Band V and WCDMA Band IV.

#### **The procedure of radiated spurious emissions is as follows:**

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as ( $P_r$ ).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_{pl}$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss ( $P_{pl}$ ) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{pl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15 \text{dBi}$ .

### A.2.2 Measurement Limit

Part 24.238, Part 22.917 and Part 27.53 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power ( $P$ ) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power ( $P$ ) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of WCDMA Band II (1852.4 MHz, 1880.0 MHz and 1907.6 MHz), WCDMA Band V (826.4 MHz, 836.6 MHz and 846.6 MHz) and WCDMA Band IV (1712.4 MHz, 1740 MHz and 1752.6 MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II, WCDMA Band V and WCDMA Band IV into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

**A.2.4 Measurement Results Table**

Frequency	Channel	Frequency Range	Result
WCDMA Band V	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
WCDMA Band II	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass
WCDMA Band IV	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

**A.2.5 Sweep Table**

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
WCDMA Band V	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
WCDMA Band II	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
WCDMA Band IV	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2



**WCDMA BAND II Mode Channel 9262/1852.4MHz**

Frequency(MHz )	P <sub>Mea</sub> (dBm )	Path Loss	Antenna Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB )	Polarization
7432.01	-55.15	8.21	12.12	-51.24	-13.00	38.24	H
9282.01	-54.47	9.11	13.27	-50.31	-13.00	37.31	H
11124.01	-52.21	9.73	13.18	-48.76	-13.00	35.76	H
12949.01	-49.29	10.49	13.47	-46.31	-13.00	33.31	H
14826.00	-45.35	11.14	14.14	-42.35	-13.00	29.35	H
16675.00	-42.33	11.80	13.67	-40.46	-13.00	27.46	V

**WCDMA BAND II Mode Channel 9400/1880MHz**

Frequency(MHz )	P <sub>Mea</sub> (dBm )	Path Loss	Antenna Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB )	Polarization
7532.01	-54.21	8.26	12.23	-50.24	-13.00	37.24	H
9383.01	-53.82	9.05	13.33	-49.54	-13.00	36.54	H
11297.01	-50.58	9.98	13.14	-47.42	-13.00	34.42	H
13140.01	-47.64	10.76	13.70	-44.70	-13.00	31.70	V
15017.00	-45.27	11.24	13.99	-42.52	-13.00	29.52	H
16897.00	-42.56	12.00	13.76	-40.80	-13.00	27.80	V

**WCDMA BAND II Mode Channel 9538/1907.6MHz**

Frequency(MHz )	P <sub>Mea</sub> (dBm )	Path Loss	Antenna Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB )	Polarization
7626.01	-54.71	8.09	12.30	-50.50	-13.00	37.50	H
9527.01	-52.85	9.45	13.37	-48.93	-13.00	35.93	H
11466.01	-50.77	9.90	13.11	-47.56	-13.00	34.56	H
13364.01	-47.80	10.57	14.01	-44.36	-13.00	31.36	H
15265.00	-45.42	11.32	13.84	-42.90	-13.00	29.90	V
17204.00	-42.74	12.35	14.25	-40.84	-13.00	27.84	V



**WCDMA BAND V Mode Channel 4132/826.4MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
1656.01	-57.99	3.57	5.22	2.15	-58.49	-13.00	45.49	H
2482.00	-51.40	4.61	6.05	2.15	-52.11	-13.00	39.11	V
3303.02	-55.02	5.29	7.73	2.15	-54.73	-13.00	41.73	H
4106.02	-55.34	6.04	9.01	2.15	-54.52	-13.00	41.52	H
4958.01	-54.20	6.68	9.86	2.15	-53.17	-13.00	40.17	H
5788.01	-54.20	7.21	10.54	2.15	-53.02	-13.00	40.02	H

**WCDMA BAND V Mode Channel 4183/836.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
1671.01	-55.06	3.58	5.19	2.15	-55.60	-13.00	42.60	H
2526.00	-52.30	4.65	6.15	2.15	-52.95	-13.00	39.95	H
3351.02	-53.85	5.32	7.84	2.15	-53.48	-13.00	40.48	H
4198.02	-54.66	6.20	9.10	2.15	-53.91	-13.00	40.91	V
5032.01	-54.63	6.58	9.94	2.15	-53.42	-13.00	40.42	V
5853.01	-52.90	7.24	10.53	2.15	-51.76	-13.00	38.76	V

**WCDMA BAND V Mode Channel 4233/846.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
1696.01	-55.14	3.60	5.15	2.15	-55.74	-13.00	42.74	H
2546.00	-52.87	4.66	6.18	2.15	-53.50	-13.00	40.50	H
3403.02	-55.22	5.36	7.97	2.15	-54.76	-13.00	41.76	V
4248.02	-55.16	6.24	9.15	2.15	-54.40	-13.00	41.40	H
5106.01	-55.63	6.79	10.05	2.15	-54.52	-13.00	41.52	V
5942.01	-52.62	7.47	10.51	2.15	-51.73	-13.00	38.73	H

**WCDMA BAND IV Mode Channel 1312/1712.4MHz**

Frequency(MHz )	P <sub>Mea</sub> (dBm )	Path Loss	Antenna Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB )	Polarization
8712.01	-54.95	8.40	13.04	-50.31	-13.00	37.31	V
10450.01	-51.77	9.73	13.08	-48.42	-13.00	35.42	V
12176.01	-49.59	10.13	13.07	-46.65	-13.00	33.65	H
13900.01	-47.01	10.80	14.44	-43.37	-13.00	30.37	H
15653.00	-45.36	11.55	13.70	-43.21	-13.00	30.21	H
17417.00	-42.94	12.54	14.72	-40.76	-13.00	27.76	V

**WCDMA BAND IV Mode Channel 1450/1740MHz**

Frequency(MHz )	P <sub>Mea</sub> (dBm )	Path Loss	Antenna Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB )	Polarization
3481.02	-49.47	5.49	8.15	-46.81	-13.00	33.81	H
10448.01	-51.18	9.73	13.08	-47.83	-13.00	34.83	H
12161.01	-48.80	10.17	13.06	-45.91	-13.00	32.91	H
13927.01	-47.83	10.82	14.46	-44.19	-13.00	31.19	H
15658.00	-44.75	11.55	13.70	-42.60	-13.00	29.60	H
17385.00	-42.39	12.48	14.65	-40.22	-13.00	27.22	V

**WCDMA BAND IV Mode Channel 1513/1752.6MHz**

Frequency(MHz )	P <sub>Mea</sub> (dBm )	Path Loss	Antenna Gain	Peak EIRP(dBm )	Limit (dBm)	Margin(dB )	Polarization
8698.01	-54.42	8.36	13.04	-49.74	-13.00	36.74	H
10458.01	-51.30	9.71	13.08	-47.93	-13.00	34.93	H
12163.01	-49.52	10.17	13.07	-46.62	-13.00	33.62	V
13937.01	-47.06	10.82	14.46	-43.42	-13.00	30.42	H
15640.00	-45.39	11.53	13.70	-43.22	-13.00	30.22	V
17380.00	-42.58	12.47	14.64	-40.41	-13.00	27.41	H

### **A.3 FREQUENCY STABILITY**

#### **A.3.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -10°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of WCDMA Band II and WCDMA Band V, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -10°C to +40°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +40°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from -10°C to +40°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

#### **A.3.2 Measurement Limit**

##### **A.3.2.1 For Hand carried battery powered equipment**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.4VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.

##### **A.3.2.2 For equipment powered by primary supply voltage**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies.



### A.3.3 Measurement results

#### WCDMA Band II

##### Frequency Error vs Voltage-QPSK

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-20.84	0.0111
3.8	-18.60	0.0099
4.4	-14.63	0.0078

##### Frequency Error vs Temperature-QPSK

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-15.47	0.0082
0	-12.13	0.0065
10	-16.53	0.0088
20	-15.44	0.0082
30	-18.88	0.0100
40	-15.55	0.0083

##### Frequency Error vs Voltage-16QAM

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-22.91	0.0122
3.8	-15.67	0.0083
4.4	-15.69	0.0083

##### Frequency Error vs Temperature-16QAM

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-10.35	0.0055
0	-13.30	0.0071
10	-16.53	0.0088
20	-15.70	0.0084
30	-11.57	0.0062
40	-13.53	0.0072



**WCDMA Band V**

**Frequency Error vs Voltage-QPSK**

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-16.37	0.0196
3.8	-11.81	0.0141
4.4	-16.16	0.0193

**Frequency Error vs Temperature-QPSK**

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-9.83	0.0117
0	-11.83	0.0141
10	-16.51	0.0197
20	-14.88	0.0178
30	-12.73	0.0152
40	-7.89	0.0094

**Frequency Error vs Voltage-16QAM**

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-7.73	0.0092
3.8	-11.79	0.0141
4.4	-12.82	0.0153

**Frequency Error vs Temperature-16QAM**

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-6.84	0.0082
0	-10.86	0.0130
10	-14.08	0.0168
20	-15.50	0.0185
30	-12.83	0.0153
40	-10.56	0.0126



**WCDMA Band IV**

**Frequency Error vs Voltage-QPSK**

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-15.81	0.0091
3.8	-19.53	0.0112
4.4	-14.33	0.0082

**Frequency Error vs Temperature-QPSK**

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-12.60	0.0072
0	-16.22	0.0093
10	-17.11	0.0098
20	-20.40	0.0117
30	-15.11	0.0087
40	-10.77	0.0062

**Frequency Error vs Voltage-16QAM**

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-16.90	0.0097
3.8	-8.09	0.0046
4.4	-15.71	0.0090

**Frequency Error vs Temperature-16QAM**

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-11.91	0.0068
0	-12.55	0.0072
10	-15.52	0.0089
20	-14.52	0.0083
30	-15.49	0.0089
40	-12.33	0.0071



## **A.4 OCCUPIED BANDWIDTH**

### **Reference**

FCC: CFR Part 2.1049(h)(i)

### **A.4.1 Occupied Bandwidth Results**

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from KDB 971168 4.2:


- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least  $10\log(\text{OBW} / \text{RBW})$  below the reference level.
- d) Set the detection mode to peak, and the trace mode to max hold.
- e) Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

**WCDMA Band II (99% BW)-QPSK**

Frequency(MHz)	Occupied Bandwidth (99% BW)( KHz)
1852.4	4182.69
1880.0	4166.67
1907.6	4198.72


**WCDMA Band II**

**Channel 9262-Occupied Bandwidth (99% BW)**




Date: 17.OCT.2018 19:40:44

### Channel 9400-Occupied Bandwidth (99% BW)



Date: 17.OCT.2018 19:41:55

### Channel 9538-Occupied Bandwidth (99% BW)




Date: 17.OCT.2018 19:43:06

**WCDMA Band II (99% BW)-16QAM**


Frequency(MHz)	Occupied Bandwidth (99% BW)( KHz)
1852.4	4166.67
1880.0	4182.69
1907.6	4166.67

**WCDMA Band II  
Channel 9262-Occupied Bandwidth (99% BW)**




Date: 18.OCT.2018 07:52:29

### Channel 9400-Occupied Bandwidth (99% BW)



Date: 18.OCT.2018 07:53:40

### Channel 9538-Occupied Bandwidth (99% BW)



Date: 18.OCT.2018 07:54:52




**WCDMA Band V(99% BW)-QPSK**

Frequency(MHz)	Occupied Bandwidth (99% BW)( KHz)
826.4	4182.69
836.6	4214.74
846.6	4182.69


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth (99% BW)**




Date: 17.OCT.2018 19:49:05

### Channel 4183-Occupied Bandwidth (99% BW)



Date: 17.OCT.2018 19:50:16

### Channel 4233-Occupied Bandwidth (99% BW)




Date: 17.OCT.2018 19:51:27

**WCDMA Band V(99% BW)-16QAM**

Frequency(MHz)	Occupied Bandwidth (99% BW)( KHz)
826.4	4182.69
836.6	4198.72
846.6	4182.69


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth (99% BW)**




Date: 18.OCT.2018 08:01:26

### Channel 4183-Occupied Bandwidth (99% BW)



Date: 18.OCT.2018 08:02:38

### Channel 4233-Occupied Bandwidth (99% BW)




Date: 18.OCT.2018 08:03:49

**WCDMA Band IV(99% BW)-QPSK**

Frequency(MHz)	Occupied Bandwidth (99% BW)( KHz)
1712.4	4198.72
1740.0	4182.69
1752.6	4182.69


**WCDMA Band IV**

**Channel 1312-Occupied Bandwidth (99% BW)**




Date: 17.OCT.2018 19:44:54

### Channel 1450-Occupied Bandwidth (99% BW)



Date: 17.OCT.2018 19:46:05

### Channel 1513-Occupied Bandwidth (99% BW)




Date: 17.OCT.2018 19:47:16

**WCDMA Band IV(99% BW)-16QAM**


Frequency(MHz)	Occupied Bandwidth (99% BW)( KHz)
1712.4	4166.67
1740.0	4166.67
1752.6	4182.69

**WCDMA Band IV  
Channel 1312-Occupied Bandwidth (99% BW)**




Date: 18.OCT.2018 07:56:58

### Channel 1450-Occupied Bandwidth (99% BW)



Date: 18.OCT.2018 07:58:09

### Channel 1513-Occupied Bandwidth (99% BW)



Date: 18.OCT.2018 07:59:20



## A.5 EMISSION BANDWIDTH

### Reference

FCC: CFR Part 22.917(b), 24.238(a), 27.53(h)

### A.5.1 Emission Bandwidth Results


The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

### WCDMA Band II-QPSK

Frequency(MHz)	Emission Bandwidth ( KHz)
1852.4	4727.56
1880.0	4727.56
1907.6	4711.54


### WCDMA Band II

### Channel 9262-Emission Bandwidth




Date: 17.OCT.2018 19:53:28

### Channel 9400-Emission Bandwidth



Date: 17.OCT.2018 19:54:40

### Channel 9538-Emission Bandwidth




Date: 17.OCT.2018 19:55:51

**WCDMA Band II -16QAM**

Frequency(MHz)	Emission Bandwidth ( KHz)
1852.4	4679.49
1880.0	4679.49
1907.6	4679.49


**WCDMA Band II**

**Channel 9262-Emission Bandwidth**




Date: 18.OCT.2018 08:06:02

### Channel 9400-Emission Bandwidth



Date: 18.OCT.2018 08:07:14

### Channel 9538-Emission Bandwidth




Date: 18.OCT.2018 08:08:26

**WCDMA Band V-QPSK**

Frequency(MHz)	Emission Bandwidth ( KHz)
826.40	4727.56
836.60	4759.62
846.60	4711.54


**WCDMA Band V**

**Channel 4132-Emission Bandwidth**




Date: 17.OCT.2018 20:01:52

### Channel 4183-Emission Bandwidth



Date: 17.OCT.2018 20:03:04

### Channel 4233-Emission Bandwidth




Date: 17.OCT.2018 20:04:16

**WCDMA Band V-16QAM**

Frequency(MHz)	Emission Bandwidth ( KHz)
826.40	4695.51
836.60	4663.46
846.60	4679.49


**WCDMA Band V**

**Channel 4132-Emission Bandwidth**




Date: 18.OCT.2018 08:15:03

### Channel 4183-Emission Bandwidth



Date: 18.OCT.2018 08:16:14

### Channel 4233-Emission Bandwidth




Date: 18.OCT.2018 08:17:26



**WCDMA Band IV-QPSK**


Frequency(MHz)	Emission Bandwidth ( KHz)
1712.4	4743.59
1740.0	4711.54
1752.6	4711.54

**WCDMA Band IV  
Channel 1312-Emission Bandwidth**




Date: 17.OCT.2018 19:57:40

### Channel 1450-Emission Bandwidth



Date: 17.OCT.2018 19:58:52

### Channel 1513-Emission Bandwidth




Date: 17.OCT.2018 20:00:03

**WCDMA Band IV-16QAM**


Frequency(MHz)	Emission Bandwidth ( KHz)
1712.4	4679.49
1740.0	4695.51
1752.6	4679.49

**WCDMA Band IV  
Channel 1312-Emission Bandwidth**




Date: 18.OCT.2018 08:10:32

### Channel 1450-Emission Bandwidth



Date: 18.OCT.2018 08:11:44

### Channel 1513-Emission Bandwidth



Date: 18.OCT.2018 08:12:56



## **A.6 BAND EDGE COMPLIANCE**

### **Reference**


FCC: CFR Part 22.917(b), 24.238(a), 27.53(h).

### **A.6.1 Measurement limit**

On any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power ( $P$ , in Watts) by at least  $43+10\text{Log}(P)$  dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm. According to KDB 971168 6.0, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.


### **A.6.2 Measurement result**

**WCDMA Band II-QPSK**  
**LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262**




Date: 17.OCT.2018 20:05:24

**HIGH BAND EDGE BLOCK-C (WCDMA Band II) -Channel 9538**




Date: 17.OCT.2018 20:05:44

**WCDMA Band II -16QAM**  
**LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262**




Date: 18.OCT.2018 08:18:47

**HIGH BAND EDGE BLOCK-C (WCDMA Band II) -Channel 9538**




Date: 18.OCT.2018 08:19:07

**WCDMA Band V-QPSK**  
**LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132**



Date: 17.OCT.2018 20:07:57

**HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233**




Date: 17.OCT.2018 20:08:16




### WCDMA Band V -16QAM

#### LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132




Date: 18.OCT.2018 08:21:55

#### HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233




Date: 18.OCT.2018 08:22:15

**WCDMA Band IV-QPSK  
LOW BAND EDGE BLOCK-A (WCDMA Band IV)-Channel 1312**




Date: 17.OCT.2018 20:06:41

**HIGH BAND EDGE BLOCK-C (WCDMA Band IV) -Channel 1513**




Date: 17.OCT.2018 20:07:00

**WCDMA Band IV-16QAM**  
**LOW BAND EDGE BLOCK-A (WCDMA Band IV)-Channel 1312**



Date: 18.OCT.2018 08:20:21

**HIGH BAND EDGE BLOCK-C (WCDMA Band IV) -Channel 1513**



Date: 18.OCT.2018 08:20:41

## **A.7 CONDUCTED SPURIOUS EMISSION**

### **Reference**

FCC: CFR Part 2.1057, 22.917, 24.238, 27.53(h).

### **A.7.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
3. According to KDB 971168 6.0, the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz)

#### **WCDMA Band II Transmitter**

Channel	Frequency (MHz)
9262	1852.40
9400	1880.00
9538	1907.60

#### **WCDMA Band IV Transmitter**

Channel	Frequency (MHz)
1312	1712.40
1450	1740.00
1513	1752.60

#### **WCDMA Band V Transmitter**

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60

### **A. 7.2 Measurement Limit**

Part 24.238, Part 22.917 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried




out.

### A.7.3 Measurement result

#### WCDMA Band II

#### Channel 9262: 30MHz – 19.1GHz


Spurious emission limit –13dBm.



Date: 17.OCT.2018 20:09:21


#### Channel 9400: 30MHz – 19.1GHz

Spurious emission limit –13dBm.




Date: 17.OCT.2018 20:09:37

**Channel 9538: 30MHz –19.1GHz**  
Spurious emission limit –13dBm.




Date: 17.OCT.2018 20:09:52

**WCDMA Band IV**  
**Channel 1312: 30MHz –17.55GHz**  
Spurious emission limit –13dBm.



Date: 17.OCT.2018 20:10:45


**WCDMA Band IV**  
**Channel 1450: 30MHz –17.55GHz**  
Spurious emission limit –13dBm.



Date: 17.OCT.2018 20:11:01



**WCDMA Band IV**  
**Channel 1513: 30MHz –17.55GHz**  
Spurious emission limit –13dBm.




Date: 17.OCT.2018 20:11:16

**WCDMA Band V**

**Channel 4132: 30MHz –8.49GHz**

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



**Channel 4** Date: 17.OCT.2018 20:12:09

Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 17.OCT.2018 20:12:25

**Channel 4233: 30MHz –8.49GHz**

Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**



Date: 17.OCT.2018 20:12:41

## **A.8 PEAK-TO-AVERAGE POWER RATIO**

### **Reference**

FCC: CFR Part 24.232 (d)

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

According to KDB 971168:

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e) Record the maximum PAPR level associated with a probability of 0.1%

### **A.8.1 Measurement limit**

not exceed 13 dB

### **A.8.2 Measurement results**

#### **WCDMA Band II-QPSK**

##### **Measurement result**

WCDMA (Band II)	CH	Frequency(MHz)	PAPR(dB)
	9400	1880.0	3.65

#### **WCDMA Band II-16QAM**

##### **Measurement result**

WCDMA (Band II)	CH	Frequency(MHz)	PAPR(dB)
	9400	1880.0	5.00

#### **WCDMA Band IV-QPSK**

##### **Measurement result**

WCDMA (Band IV)	CH	Frequency(MHz)	PAPR(dB)
	1450	1740.0	3.33

#### **WCDMA Band IV-16QAM**

##### **Measurement result**

WCDMA (Band IV)	CH	Frequency(MHz)	PAPR(dB)
	1450	1740.0	4.62

**ANNEX B: Accreditation Certificate**

**United States Department of Commerce  
National Institute of Standards and Technology**

**NVLAP<sup>®</sup>**

---

**Certificate of Accreditation to ISO/IEC 17025:2005**

---

NVLAP LAB CODE: 600118-0

**Telecommunication Technology Labs, CAICT**  
Beijing  
China

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,  
listed on the Scope of Accreditation, for:*

**Electromagnetic Compatibility & Telecommunications**

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.  
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality  
management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).*

---

2018-09-28 through 2019-09-30  
*Effective Dates*



  
For the National Voluntary Laboratory Accreditation Program

\*\*\*END OF REPORT\*\*\*