

Fig.A.6.1.95 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 15 GHz-20 GHz)




Fig.A.6.1.96 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 20 GHz-26 GHz)

A.6.2 Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 & 6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Frequency (MHz)	Field strength(μ V/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

EUT ID: EUT1

Measurement Results:
802.11b mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11b	Power	2.31GHz ~2.43GHz	Fig.A.6.2.1	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.2	P

802.11g mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11g	Power	2.31GHz ~2.43GHz	Fig.A.6.2.3	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.4	P

802.11n-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT20)	Power	2.31GHz ~2.43GHz	Fig.A.6.2.5	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.6	P

802.11n-HT40 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT40)	Power	2.31GHz ~2.43GHz	Fig.A.6.2.7	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.8	P

Conclusion: Pass

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

$$\text{Result} = P_{Mea} + A_{Rpl} = P_{Mea} + \text{Cable Loss} + \text{Antenna Factor}$$

Average Measurement results
802.11b

Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17995.5	41.8	-25.5	43.4	23.9	H	54	12.2
17971.5	41.6	-25.5	43.4	23.7	H	54	12.4
17974.5	41.6	-25.5	43.4	23.7	H	54	12.4
17985	41.6	-25.5	43.4	23.7	H	54	12.4
17976	41.5	-25.5	43.4	23.6	H	54	12.5
2333.1	42.5	-14.6	27.2	29.9	V	54	11.5

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17992.5	41.7	-25.5	43.4	23.8	H	54	12.3
17994	41.7	-25.5	43.4	23.8	H	54	12.3
17995.5	41.7	-25.5	43.4	23.8	H	54	12.3
17997	41.6	-25.5	43.4	23.7	H	54	12.4
17983.5	41.5	-25.5	43.4	23.6	H	54	12.5
17991	41.5	-25.5	43.4	23.6	H	54	12.5

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17985	41.9	-25.5	43.4	24	H	54	12.1
17991	41.7	-25.5	43.4	23.8	H	54	12.3
17980.5	41.6	-25.5	43.4	23.7	H	54	12.4
17983.5	41.6	-25.5	43.4	23.7	H	54	12.4
17986.5	41.5	-25.5	43.4	23.6	H	54	12.5
2485.1	42.3	-14.2	27.2	29.3	H	54	11.7

802.11g

Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Margin (dBuV/m)
17982	41.8	-25.5	43.4	23.9	H	54	12.2
17986.5	41.7	-25.5	43.4	23.8	H	54	12.3
17979	41.6	-25.5	43.4	23.7	H	54	12.4
17973	41.5	-25.5	43.4	23.6	H	54	12.5
17983.5	41.5	-25.5	43.4	23.6	H	54	12.5
2389.980	44.3	-38.8	27.7	55.400	H	54	9.7

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Margin (dBuV/m)
17979	41.7	-25.5	43.4	23.8	H	54	12.3
17992.5	41.7	-25.5	43.4	23.8	H	54	12.3
17991	41.6	-25.5	43.4	23.7	H	54	12.4
17976	41.5	-25.5	43.4	23.6	H	54	12.5
17997	41.5	-25.5	43.4	23.6	H	54	12.5
17982	41.4	-25.5	43.4	23.5	H	54	12.6

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Margin (dBuV/m)
17991	41.9	-25.5	43.4	24	H	54	12.1
17983.5	41.7	-25.5	43.4	23.8	H	54	12.3
17979	41.6	-25.5	43.4	23.7	H	54	12.4
17994	41.6	-25.5	43.4	23.7	H	54	12.4
17997	41.6	-25.5	43.4	23.7	H	54	12.4
2483.585	47.9	-38.9	27.7	59.100	H	54	6.1

802.11n-HT20

Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17994	41.7	-25.5	43.4	23.8	H	54	12.3
17976	41.6	-25.5	43.4	23.7	H	54	12.4
17988	41.6	-25.5	43.4	23.7	H	54	12.4
17986.5	41.5	-25.5	43.4	23.6	H	54	12.5
17995.5	41.5	-25.5	43.4	23.6	H	54	12.5
2389.920	43.3	-38.8	27.7	54.400	H	54	10.7

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17973	41.7	-25.5	43.4	23.8	H	54	12.3
17994	41.7	-25.5	43.4	23.8	H	54	12.3
17974.5	41.6	-25.5	43.4	23.7	H	54	12.4
17989.5	41.6	-25.5	43.4	23.7	H	54	12.4
17997	41.6	-25.5	43.4	23.7	H	54	12.4
17979	41.5	-25.5	43.4	23.6	H	54	12.5

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17991	41.8	-25.5	43.4	23.9	H	54	12.2
17980.5	41.7	-25.5	43.4	23.8	H	54	12.3
17976	41.6	-25.5	43.4	23.7	H	54	12.4
17982	41.6	-25.5	43.4	23.7	H	54	12.4
17985	41.6	-25.5	43.4	23.7	H	54	12.4
2485.105	46.2	-38.9	27.7	57.400	H	54	7.8

802.11n-HT40

Ch3

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Margin (dBuV/m)
17985	41.7	-25.5	43.4	23.8	H	54	12.3
17992.5	41.7	-25.5	43.4	23.8	H	54	12.3
17995.5	41.7	-25.5	43.4	23.8	H	54	12.3
17977.5	41.5	-25.5	43.4	23.6	H	54	12.5
17979	41.5	-25.5	43.4	23.6	H	54	12.5
2312.1	42.4	-14.5	27.2	29.7	V	54	11.6

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Margin (dBuV/m)
17995.5	41.8	-25.5	43.4	23.9	H	54	12.2
17983.5	41.6	-25.5	43.4	23.7	H	54	12.4
17986.5	41.6	-25.5	43.4	23.7	H	54	12.4
17980.5	41.5	-25.5	43.4	23.6	H	54	12.5
17997	41.5	-25.5	43.4	23.6	H	54	12.5
17977.5	41.4	-25.5	43.4	23.5	H	54	12.6

Ch9

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Margin (dBuV/m)
17977.5	41.5	-25.5	43.4	23.6	H	54	12.5
17980.5	41.5	-25.5	43.4	23.6	H	54	12.5
17986.5	41.5	-25.5	43.4	23.6	H	54	12.5
17989.5	41.5	-25.5	43.4	23.6	H	54	12.5
17992.5	41.5	-25.5	43.4	23.6	H	54	12.5
2485.1	42.4	-14.2	27.2	29.4	H	54	11.6

Peak Measurement results
802.11b

Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17986.5	53.9	-25.5	43.4	36	V	74	20.1
17871	53.6	-25.5	43.4	35.7	H	74	20.4
17908.5	53	-25.5	43.4	35.1	H	74	21
17976	53	-25.5	43.4	35.1	H	74	21
17958	52.9	-25.5	43.4	35	H	74	21.1
2337	55.8	-14.6	27.2	43.2	V	74	18.2

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17994	53.6	-25.5	43.4	35.7	H	74	20.4
17982	53.3	-25.5	43.4	35.4	H	74	20.7
17997	53.2	-25.5	43.4	35.3	H	74	20.8
17977.5	53.1	-25.5	43.4	35.2	H	74	20.9
17991	52.8	-25.5	43.4	34.9	H	74	21.2
17892	52.7	-25.5	43.4	34.8	H	74	21.3

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17883	54.2	-25.5	43.4	36.3	H	74	19.8
17955	53.9	-25.5	43.4	36	H	74	20.1
17982	53.2	-25.5	43.4	35.3	H	74	20.8
17995.5	53.2	-25.5	43.4	35.3	V	74	20.8
17994	53	-25.5	43.4	35.1	V	74	21
2485.6	55.1	-14.2	27.2	42.1	H	74	18.9

802.11g

Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Margin (dBuV/m)
17980.5	53.2	-25.5	43.4	35.3	H	74	20.8
17968.5	53.1	-25.5	43.4	35.2	H	74	20.9
17910	53	-25.5	43.4	35.1	V	74	21
17989.5	53	-25.5	43.4	35.1	H	74	21
17802	52.8	-25.5	43.4	34.9	H	74	21.2
2389.968	57.6	-38.8	27.7	68.700	H	74	16.4

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Margin (dBuV/m)
17952	53.5	-25.5	43.4	35.6	H	74	20.5
17968.5	53.2	-25.5	43.4	35.3	V	74	20.8
17988	53.1	-25.5	43.4	35.2	H	74	20.9
17992.5	53.1	-25.5	43.4	35.2	H	74	20.9
17991	53	-25.5	43.4	35.1	H	74	21
17997	52.9	-25.5	43.4	35	H	74	21.1

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Margin (dBuV/m)
17908.5	53.3	-25.5	43.4	35.4	H	74	20.7
17904	53.2	-25.5	43.4	35.3	H	74	20.8
17974.5	53.2	-25.5	43.4	35.3	H	74	20.8
17985	53.2	-25.5	43.4	35.3	H	74	20.8
17928	53	-25.5	43.4	35.1	H	74	21
2484.865	61.1	-38.9	27.7	72.300	H	74	12.9

802.11n-HT20

Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17946	54.3	-25.5	43.4	36.4	H	74	19.7
17970	53.8	-25.5	43.4	35.9	H	74	20.2
17962.5	53.4	-25.5	43.4	35.5	H	74	20.6
17994	53	-25.5	43.4	35.1	H	74	21
17601	52.9	-25.7	43.4	35.2	H	74	21.1
2389.848	55.4	-38.8	27.7	66.500	H	74	18.6

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17974.5	54	-25.5	43.4	36.1	H	74	20
17979	53.5	-25.5	43.4	35.6	H	74	20.5
17904	53.2	-25.5	43.4	35.3	H	74	20.8
17686.5	53.1	-25.7	43.4	35.4	H	74	20.9
17958	53	-25.5	43.4	35.1	H	74	21
17896.5	52.9	-25.5	43.4	35	H	74	21.1

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17982	53.3	-25.5	43.4	35.4	H	74	20.7
17997	52.9	-25.5	43.4	35	V	74	21.1
17947.5	52.8	-25.5	43.4	34.9	H	74	21.2
17989.5	52.8	-25.5	43.4	34.9	H	74	21.2
17886	52.7	-25.5	43.4	34.8	H	74	21.3
2484.950	67.1	-38.9	27.7	78.300	H	74	6.9

802.11n-HT40

Ch3

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17842.5	53.4	-25.5	43.4	35.5	H	74	20.6
17878.5	53.3	-25.5	43.4	35.4	H	74	20.7
17983.5	53.1	-25.5	43.4	35.2	H	74	20.9
17985	53.1	-25.5	43.4	35.2	H	74	20.9
17989.5	52.9	-25.5	43.4	35	H	74	21.1
2360.2	55.8	-14.3	27.2	42.9	H	74	18.2

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17949	53.9	-25.5	43.4	36	H	74	20.1
17805	53.6	-25.5	43.4	35.7	H	74	20.4
17961	53.2	-25.5	43.4	35.3	V	74	20.8
17973	53.2	-25.5	43.4	35.3	H	74	20.8
17997	53.2	-25.5	43.4	35.3	H	74	20.8
17982	53	-25.5	43.4	35.1	H	74	21

Ch9

Frequency (MHz)	Result (dBuV/m)	Cable Loss (dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization	Limit (dBuV/m)	Magin (dBuV/m)
17980.5	53.6	-25.5	43.4	35.7	H	74	20.4
17970	53.4	-25.5	43.4	35.5	H	74	20.6
17986.5	53.3	-25.5	43.4	35.4	H	74	20.7
17991	52.9	-25.5	43.4	35	H	74	21.1
17968.5	52.7	-25.5	43.4	34.8	H	74	21.3
2487.5	55.7	-14.2	27.2	42.7	V	74	18.3

Test graphs as below:

Full Spectrum




Fig.A.6.2.1 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch1, 2.31 GHz - 2.43GHz

Full Spectrum




Fig.A.6.2.2 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch11, 2.45 GHz - 2.50GHz




Fig.A.6.2.3 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch1, 2.31 GHz - 2.43GHz






Fig.A.6.2.4 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch11, 2.45 GHz - 2.50GHz



**Fig.A.6.2.5 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch1,
2.38 GHz - 2.45GHz
Fig.A.6.2.6 GHz)**



**Fig.A.6.2.6 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch11,
2.45 GHz - 2.50GHz**




Fig.A.6.2.7 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch3, 2.31 GHz - 2.43GHz




Fig.A.6.2.8 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch9, 2.45 GHz - 2.50GHz

A.7. AC Power-line Conducted Emission

Method of Measurement: See ANSI C63.10-2013-clause 6.2

- 1 The one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
- 2 If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
- 3 The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
- 4 If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.
- 5 If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.³⁶ Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

Set.1

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		With charger	
		802.11b	
0.15 to 0.5	66 to 56	Fig.A.7.1	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dB μ V)	Result (dB μ V)	Conclusion
		With charger	
		802.11b	
0.15 to 0.5	56 to 46	Fig.A.7.1	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Conclusion: Pass

Test graphs as below:




Fig.A.7.1 AC Powerline Conducted Emission-802.11b

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.429000	34.7	1000.0	L1	19.8	22.5	57.3
0.546000	40.9	1000.0	L1	19.9	15.1	56.0
1.113000	30.9	1000.0	N	19.9	25.1	56.0
1.689000	28.4	1000.0	N	19.8	27.6	56.0
2.998500	31.0	1000.0	N	19.8	25.0	56.0
4.087500	29.4	1000.0	N	19.8	26.6	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.424500	24.3	1000.0	L1	19.8	23.0	47.4
0.555000	27.2	1000.0	L1	19.9	18.8	46.0
1.077000	26.6	1000.0	L1	19.8	19.4	46.0
1.711500	21.5	1000.0	L1	19.8	24.5	46.0
2.494500	20.7	1000.0	L1	19.8	25.3	46.0
3.961500	21.3	1000.0	L1	19.8	24.7	46.0

ANNEX B: Accreditation Certificate

<p>United States Department of Commerce National Institute of Standards and Technology</p> 	
<hr/> <p>Certificate of Accreditation to ISO/IEC 17025:2005</p> <hr/>	
<p>NVLAP LAB CODE: 600118-0</p>	
<p>Telecommunication Technology Labs, CAICT Beijing China</p>	
<p><i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i></p>	
<p>Electromagnetic Compatibility & Telecommunications</p>	
<p><i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i></p>	
<hr/> <p>2019-09-26 through 2020-09-30 <i>Effective Dates</i></p>	 <hr/> <p><i>[Signature]</i> For the National Voluntary Laboratory Accreditation Program</p>

END OF REPORT