



# TEST REPORT

## No. I20Z60463-WMD03

for

**TCL Communication Ltd.**

**LTE/UMTS/GSM mobile phone**

**Model Name: 5061A**

**FCC ID: 2ACCJH125**

with

**Hardware Version: PIO**

**Software Version: v6H1H**

**Issued Date: 2020-05-19**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

**Test Laboratory:**

**CTTL, Telecommunication Technology Labs, CAICT**

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: [ctl\\_terminals@caict.ac.cn](mailto:ctl_terminals@caict.ac.cn), website: [www.caict.ac.cn](http://www.caict.ac.cn)



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I20Z60463-WMD03	Rev.0	1 <sup>st</sup> edition	2020-05-12
I20Z60463-WMD03	Rev.1	2 <sup>nd</sup> edition Updated the results of Emission Limit for LTE Band 7	2020-05-19

Note: the latest revision of the test report supersedes all previous version.

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. INTRODUCTION &amp; ACCREDITATION .....</b>	<b>4</b>
<b>1.2. TESTING LOCATION .....</b>	<b>4</b>
<b>1.3. TESTING ENVIRONMENT .....</b>	<b>5</b>
<b>1.4. PROJECT DATA .....</b>	<b>5</b>
<b>1.5. SIGNATURE .....</b>	<b>5</b>
<b>2. CLIENT INFORMATION .....</b>	<b>6</b>
<b>2.1. APPLICANT INFORMATION .....</b>	<b>6</b>
<b>2.2. MANUFACTURER INFORMATION .....</b>	<b>6</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>7</b>
<b>3.1. ABOUT EUT .....</b>	<b>7</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>7</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>7</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>8</b>
<b>5. LABORATORY ENVIRONMENT .....</b>	<b>9</b>
<b>6. SUMMARY OF TEST RESULT .....</b>	<b>10</b>
<b>7. TEST EQUIPMENT UTILIZED .....</b>	<b>13</b>
<b>ANNEX A: MEASUREMENT RESULTS .....</b>	<b>14</b>
<b>A.1 OUTPUT POWER .....</b>	<b>14</b>
<b>A.2 EMISSION LIMIT .....</b>	<b>39</b>
<b>A.3 FREQUENCY STABILITY .....</b>	<b>48</b>
<b>A.4 OCCUPIED BANDWIDTH .....</b>	<b>52</b>
<b>A.5 EMISSION BANDWIDTH .....</b>	<b>79</b>
<b>A.6 BAND EDGE COMPLIANCE .....</b>	<b>106</b>
<b>A.7 CONDUCTED SPURIOUS EMISSION .....</b>	<b>131</b>
<b>A.8 PEAK-TO-AVERAGE POWER RATIO .....</b>	<b>137</b>
<b>ANNEX B: ACCREDITATION CERTIFICATE .....</b>	<b>139</b>



## **1. Test Laboratory**

### **1.1. Introduction & Accreditation**

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0 and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

### **1.2. Testing Location**

Location 1: CTTL (huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China 100191

Location 2: CTTL (Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,  
Haidian District, Beijing, P. R. China 100191

### 1.3. Testing Environment

Normal Temperature: 15-35°C  
Relative Humidity: 20-75%

### 1.4. Project data

Testing Start Date: 2020-04-16  
Testing End Date: 2020-05-07

### 1.5. Signature



---

Dong Yuan  
(Prepared this test report)



---

Zhou Yu  
(Reviewed this test report)



---

Zhao Hui Lin  
Deputy Director of the laboratory  
(Approved this test report)



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong  
Contact: Gong Zhizhou  
Email: zhizhou.gong@tcl.com  
Telephone: 0086-755-36611722

### **2.2. Manufacturer Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong  
Contact: Gong Zhizhou  
Email: zhizhou.gong@tcl.com  
Telephone: 0086-755-3661172

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	LTE/UMTS/GSM mobile phone
Model Name	5061A
FCC ID	2ACCJH125
Antenna	Embedded
Output power	24.30dBm maximum EIRP measured for LTE Band 7
Extreme vol. Limits	3.5VDC to 4.4VDC (nominal: 3.8VDC)
Extreme temp. Tolerance	-10C to +55°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>IMEI</b>	<b>HW Version</b>	<b>SW Version</b>	<b>Date of receipt</b>
UT03a	355823110201189	PIO	v6H1H	2020-03-30
UT10a	355823110201197	PIO	v6H1H	2020-03-30

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>
AE1	Battery
AE2	Battery
<b>AE1</b>	
Model	CAC4850000C1
Manufacturer	BYD
Capacitance	5000mAh
<b>AE2</b>	
Model	CAC4850002C7
Manufacturer	VEKEN
Capacitance	5000mAh

\*AE ID: is used to identify the test sample in the lab internally.

#### **4. Reference Documents**

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-19 Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-19 Edition
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES	10-1-19 Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2016
ANSI C63.26	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services	2015
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS	v03r01



## 5. LABORATORY ENVIRONMENT

**Semi-anechoic chamber 2 / Fully-anechoic chamber 3** (10 meters×6.7 meters×6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	<±3.5 dB, 3 m distance
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

## 6. SUMMARY OF TEST RESULT

### LTE Band 2

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	24.232	P
2	Emission Limit	2.1051/24.238	P
3	Frequency Stability	2.1055	P
4	Occupied Bandwidth	2.1049	P
5	Emission Bandwidth	24.238	P
6	Band Edge Compliance	24.238	P
7	Conducted Spurious Emission	24.238	P
8	Peak-to-Average Power Ratio	24.232	P

### LTE Band 5

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	22.913	P
2	Emission Limit	2.1051/22.917	P
3	Frequency Stability	2.1055	P
4	Occupied Bandwidth	2.1049	P
5	Emission Bandwidth	22.917	P
6	Band Edge Compliance	22.917	P
7	Conducted Spurious Emission	22.917	P

### LTE Band 7

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	P
2	Emission Limit	2.1051/27.53	P
3	Frequency Stability	2.1055	P
4	Occupied Bandwidth	2.1049	P
5	Emission Bandwidth	27.53	P
6	Band Edge Compliance	27.53	P
7	Conducted Spurious Emission	27.53	P
8	Peak-to-Average Power Ratio	27.50	P

**LTE Band 12**

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	P
2	Emission Limit	2.1051/27.53	P
3	Frequency Stability	2.1055	P
4	Occupied Bandwidth	2.1049	P
5	Emission Bandwidth	27.53	P
6	Band Edge Compliance	27.53	P
7	Conducted Spurious Emission	27.53	P
8	Peak-to-Average Power Ratio	27.50	P

**LTE Band 13**

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	P
2	Emission Limit	2.1051/27.53	P
3	Frequency Stability	2.1055	P
4	Occupied Bandwidth	2.1049	P
5	Emission Bandwidth	27.53	P
6	Band Edge Compliance	27.53	P
7	Conducted Spurious Emission	27.53	P
8	Peak-to-Average Power Ratio	27.50	P

**LTE Band 66**

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	P
2	Emission Limit	2.1051/27.53	P
3	Frequency Stability	2.1055	P
4	Occupied Bandwidth	2.1049	P
5	Emission Bandwidth	27.53	P
6	Band Edge Compliance	27.53	P
7	Conducted Spurious Emission	27.53	P
8	Peak-to-Average Power Ratio	27.50	P

## Terms used in Verdict column

P	Pass. The EUT complies with the essential requirements in the standard.
NP	Not Performed. The test was not performed by CTTL.
NA	Not Applicable. The test was not applicable.
BR	Re-use test data from basic model report.
F	Fail. The EUT does not comply with the essential requirements in the standard.

## Explanation of worst-case configuration

The worst-case scenario for all measurements is based on the conducted output power measurement investigation results. Output power was measured on QPSK and 16QAM modulations. It was found that QPSK was the worst case. All testing was performed using QPSK modulations to represent the worst case unless otherwise stated. The test results shown in the following sections represent the worst case emission.

## 7. Test Equipment Utilized

NO	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	Universal Radio Communication Tester	CMW500	159082	R&S	2020-12-24	1 year
2	Spectrum Analyzer	FSU26	200030	R&S	2020-06-03	1 year
3	Climate chamber	SH-242	93008556	ESPEC	2020-12-21	3 year
4	Universal Radio Communication Tester	CMW500	143008	R&S	2020-11-26	1 year
5	Test Receiver	E4440A	MY48250642	Agilent	2021-03-12	1 year
6	EMI Antenna	VULB9163	9163-235	Schwarzbeck	2020-11-24	1 year
7	EMI Antenna	3117	00058889	ETS-Lindgren	2020-11-18	1 year
8	EMI Antenna	3117	00119021	ETS-Lindgren	2021-01-14	1 year
9	Signal Generator	N5183A	MY48250642	Agilent	2020-06-24	1 year
10	Power Amplifier	5S1G4	0341863	AR	/	/
11	EMI Antenna	9117	167	Schwarzbeck	2020-05-27	1 year

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 OUTPUT POWER**

#### **A.1.1 Summary**

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMW500) to ensure max power transmission and proper modulation.

In all cases, output power is within the specified limits.

#### **A.1.2 Conducted**

##### **A.1.2.1 Method of Measurements**

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies (bottom, middle and top of operational frequency range) for each bandwidth.

##### **A.1.2.2 Measurement result**

#### **LTE band 2**

Bandwidth	RB size/offset	Frequency (MHz)	Power (dBm)	
			QPSK	16QAM
1.4MHz	1 RB high	1909.3	22.84	21.91
		1880.0	22.88	21.96
		1850.7	22.88	22.27
	1 RB low	1909.3	22.81	21.89
		1880.0	22.91	21.95
		1850.7	22.85	22.25
	50% RB mid	1909.3	22.95	22.10
		1880.0	22.97	22.03
		1850.7	23.05	22.23
	100% RB	1909.3	22.00	21.15
		1880.0	22.01	21.11
		1850.7	21.95	20.83
3MHz	1 RB high	1908.5	22.83	21.83
		1880.0	22.84	21.76
		1851.5	22.87	22.22
	1 RB low	1908.5	22.89	21.89
		1880.0	22.80	21.81
		1851.5	22.84	22.21
	50% RB mid	1908.5	21.98	21.00
		1880.0	21.95	21.04
		1851.5	21.95	21.03

	100% RB	1908.5	21.92	20.86
		1880.0	21.93	20.96
		1851.5	21.91	20.90
5MHz	1 RB high	1907.5	22.76	21.91
		1880.0	22.73	21.95
		1852.5	22.73	22.27
	1 RB low	1907.5	22.77	21.89
		1880.0	22.74	21.97
		1852.5	22.74	22.27
	50% RB mid	1907.5	21.96	21.00
		1880.0	21.94	20.98
		1852.5	21.93	21.07
	100% RB	1907.5	21.90	20.85
		1880.0	21.89	20.94
		1852.5	21.90	20.94
10MHz	1 RB high	1905.0	22.92	21.89
		1880.0	22.85	21.80
		1855.0	22.83	22.26
	1 RB low	1905.0	22.95	21.89
		1880.0	22.88	21.81
		1855.0	22.82	22.24
	50% RB mid	1905.0	21.98	21.05
		1880.0	21.96	21.01
		1855.0	21.97	21.01
	100% RB	1905.0	21.98	21.01
		1880.0	21.99	20.98
		1855.0	22.00	20.98
15MHz	1 RB high	1902.5	22.83	22.17
		1880.0	22.78	21.77
		1857.5	22.80	22.14
	1 RB low	1902.5	22.84	22.19
		1880.0	22.80	21.80
		1857.5	22.81	22.17
	50% RB mid	1902.5	22.03	20.97
		1880.0	22.01	20.94
		1857.5	21.97	20.98
	100% RB	1902.5	22.02	21.00
		1880.0	22.03	20.99
		1857.5	21.98	20.93

20MHz	1 RB high	1900.0	22.68	22.09
		1880.0	22.65	22.06
		1860.0	22.64	22.17
	1 RB low	1900.0	22.66	22.09
		1880.0	22.64	22.04
		1860.0	22.63	22.18
	50% RB mid	1900.0	22.00	20.99
		1880.0	21.97	20.93
		1860.0	21.93	20.98
	100% RB	1900.0	22.02	20.98
		1880.0	22.01	20.97
		1860.0	21.94	20.97



**LTE band 5**

Bandwidth	RB size/offset	Frequency (MHz)	Power (dBm)	
			QPSK	16QAM
1.4MHz	1 RB high	848.3	22.71	21.81
		836.5	22.80	21.89
		824.7	22.84	22.21
	1 RB low	848.3	22.69	21.80
		836.5	22.85	21.89
		824.7	22.86	22.21
	50% RB mid	848.3	22.87	22.04
		836.5	22.87	21.93
		824.7	22.96	22.10
	100% RB	848.3	21.85	21.03
		836.5	21.92	21.01
		824.7	21.92	20.84
3MHz	1 RB high	847.5	22.79	21.85
		836.5	22.88	21.75
		825.5	22.88	22.26
	1 RB low	847.5	22.85	21.85
		836.5	22.84	21.82
		825.5	22.96	22.27
	50% RB mid	847.5	21.99	20.96
		836.5	21.96	21.03
		825.5	21.99	21.04
	100% RB	847.5	21.89	20.83
		836.5	21.91	20.88
		825.5	21.92	20.93
5MHz	1 RB high	846.5	22.79	21.91
		836.5	22.84	21.93
		826.5	22.80	22.34
	1 RB low	846.5	22.75	21.81
		836.5	22.90	22.01
		826.5	22.81	22.31
	50% RB mid	846.5	21.92	20.94
		836.5	21.93	20.95
		826.5	21.94	21.03
	100% RB	846.5	21.86	20.80
		836.5	21.91	20.90
		826.5	21.88	20.96
10MHz	1 RB high	844.0	22.88	22.21

		836.5	22.83	21.83
		829.0	22.88	21.87
	1 RB low	844.0	22.83	22.13
		836.5	22.87	21.92
		829.0	22.87	21.83
	50% RB mid	844.0	21.88	20.91
		836.5	21.93	21.01
		829.0	21.94	20.94
	100% RB	844.0	21.85	20.84
		836.5	21.94	20.98
		829.0	21.97	20.97

**LTE band 7**

Bandwidth	RB size/offset	Frequency (MHz)	Power (dBm)	
			QPSK	16QAM
5MHz	1 RB high	2567.5	22.74	21.77
		2535	22.75	21.81
		2502.5	22.68	22.08
	1 RB low	2567.5	22.76	21.83
		2535	22.77	21.81
		2502.5	22.64	22.08
	50% RB mid	2567.5	21.86	20.90
		2535	21.83	20.84
		2502.5	21.77	20.85
	100% RB	2567.5	21.81	20.75
		2535	21.79	20.75
		2502.5	21.73	20.76
10MHz	1 RB high	2565	22.82	21.75
		2535	22.77	21.66
		2505	22.79	22.04
	1 RB low	2565	22.79	21.78
		2535	22.77	21.66
		2505	22.75	22.00
	50% RB mid	2565	21.86	20.92
		2535	21.80	20.79
		2505	21.74	20.77
	100% RB	2565	21.83	20.85
		2535	21.78	20.78
		2505	21.71	20.68
15MHz	1 RB high	2562.5	22.79	21.99
		2535	22.69	21.56
		2507.5	22.66	21.90
	1 RB low	2562.5	22.71	22.09
		2535	22.69	21.60
		2507.5	22.67	21.94
	50% RB mid	2562.5	21.93	20.83
		2535	21.86	20.76
		2507.5	21.83	20.80
	100% RB	2562.5	21.92	20.88
		2535	21.87	20.77
		2507.5	21.77	20.72

20MHz	1 RB high	2560	22.54	22.04
		2535	22.56	21.99
		2510	22.43	21.81
	1 RB low	2560	22.56	22.05
		2535	22.49	21.94
		2510	22.43	21.75
	50% RB mid	2560	21.84	20.91
		2535	21.78	20.77
		2510	21.69	20.66
	100% RB	2560	21.84	20.86
		2535	21.80	20.78
		2510	21.66	20.64

**LTE band 12**

Bandwidth	RB size/offset	Frequency (MHz)	Power (dBm)	
			QPSK	16QAM
1.4MHz	1 RB high	715.3	22.73	21.77
		707.5	22.76	21.86
		699.7	22.80	22.09
	1 RB low	715.3	22.72	21.76
		707.5	22.79	21.87
		699.7	22.80	22.10
	50% RB mid	715.3	22.91	22.00
		707.5	22.84	21.90
		699.7	22.90	21.98
	100% RB	715.3	21.86	21.03
		707.5	21.81	20.97
		699.7	21.85	20.79
3MHz	1 RB high	714.5	22.82	21.80
		707.5	22.86	21.74
		700.5	22.89	22.21
	1 RB low	714.5	22.81	21.89
		707.5	22.82	21.79
		700.5	22.87	22.19
	50% RB mid	714.5	21.90	21.02
		707.5	21.89	21.05
		700.5	21.91	21.03
	100% RB	714.5	21.84	20.82
		707.5	21.83	20.88
		700.5	21.84	20.89
5MHz	1 RB high	713.5	22.82	21.84
		707.5	22.87	21.93
		701.5	22.79	22.29
	1 RB low	713.5	22.73	21.79
		707.5	22.86	21.92
		701.5	22.76	22.25
	50% RB mid	713.5	21.87	20.96
		707.5	21.87	20.97
		701.5	21.92	21.05
	100% RB	713.5	21.89	20.87
		707.5	21.87	20.88
		701.5	21.88	20.96
10MHz	1 RB high	711.0	22.83	21.84
		707.5	22.83	21.73



		704.0	22.88	22.19
	1 RB low	711.0	22.83	21.85
		707.5	22.78	21.70
		704.0	22.83	22.13
	50% RB mid	711.0	21.83	20.98
		707.5	21.90	20.94
		704.0	21.90	20.94
	100% RB	711.0	21.79	20.85
		707.5	21.85	20.89
		704.0	22.01	21.05

**LTE band 13**

Bandwidth	RB size/offset	Frequency (MHz)	Power (dBm)	
			QPSK	16QAM
5MHz	1 RB high	784.5	22.76	21.76
		782	22.82	21.81
		779.5	22.76	22.21
	1 RB low	784.5	22.78	21.81
		782	22.82	21.90
		779.5	22.72	22.18
	50% RB mid	784.5	21.84	20.85
		782	21.82	20.89
		779.5	21.89	20.97
	100% RB	784.5	21.75	20.73
		782	21.81	20.83
		779.5	21.82	20.90
10MHz	1 RB high	782.0	22.87	22.10
	1 RB low	782.0	22.80	22.11
	50% RB mid	782.0	21.87	20.93
	100% RB	782.0	21.88	20.90

**LTE band 66**

Bandwidth	RB size/offset	Frequency (MHz)	Power (dBm)	
			QPSK	16QAM
1.4MHz	1 RB high	1779.3	22.72	21.88
		1745.0	22.67	22.02
		1710.7	22.60	21.75
	1 RB low	1779.3	22.73	21.87
		1745.0	22.68	22.03
		1710.7	22.60	21.74
	50% RB mid	1779.3	22.83	21.92
		1745.0	22.82	21.92
		1710.7	22.89	22.04
	100% RB	1779.3	21.80	20.98
		1745.0	21.66	20.63
		1710.7	21.80	20.95
3MHz	1 RB high	1778.5	22.76	21.69
		1745.0	22.74	22.08
		1711.5	22.70	21.79
	1 RB low	1778.5	22.67	21.74
		1745.0	22.75	22.07
		1711.5	22.76	21.84
	50% RB mid	1778.5	21.83	20.92
		1745.0	21.72	20.81
		1711.5	21.81	20.84
	100% RB	1778.5	21.78	20.83
		1745.0	21.69	20.72
		1711.5	21.77	20.74
5MHz	1 RB high	1777.5	22.72	21.88
		1745.0	22.62	22.12
		1712.5	22.73	21.81
	1 RB low	1777.5	22.70	21.88
		1745.0	22.63	22.08
		1712.5	22.72	21.77
	50% RB mid	1777.5	21.83	20.87
		1745.0	21.71	20.88
		1712.5	21.82	20.87
	100% RB	1777.5	21.81	20.81
		1745.0	21.69	20.78
		1712.5	21.74	20.73
10MHz	1 RB high	1775.0	22.68	21.70
		1745.0	22.69	22.03



	1 RB low	1715.0	22.75	21.83
		1775.0	22.64	21.70
		1745.0	22.67	22.06
	50% RB mid	1715.0	22.72	21.75
		1775.0	21.81	20.90
		1745.0	21.76	20.77
	100% RB	1715.0	21.85	20.97
		1775.0	21.82	20.81
		1745.0	21.76	20.82
15MHz	1 RB high	1715.0	21.89	20.92
		1775.0	21.82	20.81
		1745.0	21.76	20.82
	1 RB low	1772.5	22.57	21.63
		1745.0	22.59	21.95
		1717.5	22.72	22.17
	50% RB mid	1772.5	22.55	21.60
		1745.0	22.65	22.01
		1717.5	22.68	22.04
	100% RB	1772.5	21.83	20.80
		1745.0	21.77	20.78
		1717.5	21.83	20.78
20MHz	1 RB high	1772.5	21.88	20.85
		1745.0	21.77	20.75
		1717.5	21.89	20.85
	1 RB low	1770.0	22.43	21.92
		1745.0	22.37	21.97
		1720.0	22.49	22.04
	50% RB mid	1770.0	22.31	21.83
		1745.0	22.46	21.95
		1720.0	22.46	21.95
	100% RB	1770.0	21.82	20.82
		1745.0	21.73	20.76
		1720.0	21.81	20.85
		1770.0	21.79	20.80
		1745.0	21.70	20.78
		1720.0	21.85	20.87

### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Rule Part 22.913(a) specifies "Mobile stations are limited to 2.0 watts EIRP".

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power". and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 27.50(d) specifies "Fixed, mobile, and portable (handheld) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP".


Rule Part 27.50(h)(2) specifies "Mobile stations are limited to 2.0 watts EIRP".

Rule Part 27.50(c) specifies "Portable stations (hand-held de-vices) are limited to 3 watts ERP".


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360 and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the amplifier and the substitution antenna.  
The cable loss ( $P_{cl}$ ), the substitution antenna Gain ( $G_a$ ) and the amplifier Gain ( $P_{Ag}$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{Mea} - P_{cl} + P_{Ag} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15$ .

### A.1.3.3 Measurement result

#### LTE Band 2- EIRP

Limits:  $\leq 33\text{dBm}$  (2W)

#### LTE Band 2\_1.4MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.70	-25.69	2.92	43.75	4.87	20.01	33.00	12.99	H
1880.00	-23.27	2.85	43.75	4.82	22.45	33.00	10.55	H
1909.30	-22.31	2.87	43.77	4.76	23.35	33.00	9.65	H

#### LTE Band 2\_3MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.50	-25.80	2.87	43.75	4.87	19.95	33.00	13.05	H
1880.00	-23.71	2.85	43.75	4.82	22.01	33.00	10.99	H
1908.50	-22.44	2.89	43.78	4.76	23.21	33.00	9.79	H

#### LTE Band 2\_5MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.50	-25.79	2.87	43.75	4.87	19.96	33.00	13.04	H
1880.00	-23.73	2.85	43.75	4.82	21.99	33.00	11.01	H
1907.50	-22.51	2.84	43.77	4.77	23.19	33.00	9.81	H

#### LTE Band 2\_10MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.00	-25.71	2.88	43.74	4.86	20.01	33.00	12.99	H
1880.00	-23.64	2.85	43.75	4.82	22.08	33.00	10.92	H
1905.00	-22.48	2.87	43.77	4.77	23.19	33.00	9.81	H

#### LTE Band 2\_15MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.50	-25.80	2.87	43.75	4.86	19.94	33.00	13.06	H
1880.00	-23.73	2.85	43.75	4.82	21.99	33.00	11.01	H
1902.50	-22.72	2.86	43.77	4.78	22.97	33.00	10.03	H

#### LTE Band 2\_20 MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.00	-25.37	2.86	43.75	4.85	20.37	33.00	12.63	H
1880.00	-23.54	2.85	43.75	4.82	22.18	33.00	10.82	H
1900.00	-22.82	2.87	43.77	4.78	22.86	33.00	10.14	H

**LTE Band 2\_1.4MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.70	-26.64	2.92	43.75	4.87	19.06	33.00	13.94	H
1880.00	-24.33	2.85	43.75	4.82	21.39	33.00	11.61	H
1909.30	-23.39	2.87	43.77	4.76	22.27	33.00	10.73	H

**LTE Band 2\_3MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.50	-26.74	2.87	43.75	4.87	19.01	33.00	13.99	H
1880.00	-24.61	2.85	43.75	4.82	21.11	33.00	11.89	H
1908.50	-23.49	2.89	43.78	4.76	22.16	33.00	10.84	H

**LTE Band 2\_5MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.50	-26.60	2.87	43.75	4.87	19.15	33.00	13.85	H
1880.00	-24.74	2.85	43.75	4.82	20.98	33.00	12.02	H
1907.50	-23.48	2.84	43.77	4.77	22.22	33.00	10.78	H

**LTE Band 2\_10MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.00	-26.72	2.88	43.74	4.86	19.00	33.00	14.00	H
1880.00	-24.65	2.85	43.75	4.82	21.07	33.00	11.93	H
1905.00	-23.38	2.87	43.77	4.77	22.29	33.00	10.71	H

**LTE Band 2\_15MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.50	-26.64	2.87	43.75	4.86	19.10	33.00	13.90	H
1880.00	-24.64	2.85	43.75	4.82	21.08	33.00	11.92	H
1902.50	-23.74	2.86	43.77	4.78	21.95	33.00	11.05	H

**LTE Band 2\_20 MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.00	-26.35	2.86	43.75	4.85	19.39	33.00	13.61	H
1880.00	-24.59	2.85	43.75	4.82	21.13	33.00	11.87	H
1900.00	-23.74	2.87	43.77	4.78	21.94	33.00	11.06	H

### LTE Band 5- ERP

Limits:  $\leq 38.45\text{dBm}$  (7W)

#### LTE Band 5\_1.4MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.70	-23.83	2.26	45.79	0.95	2.15	18.50	38.45	19.95	V
836.50	-22.79	2.26	45.66	0.82	2.15	19.28	38.45	19.17	V
848.30	-22.65	2.27	45.55	0.80	2.15	19.28	38.45	19.17	V

#### LTE Band 5\_3MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
825.50	-23.95	2.26	45.79	0.94	2.15	18.37	38.45	20.08	V
836.50	-22.90	2.26	45.66	0.82	2.15	19.17	38.45	19.28	V
847.50	-22.76	2.27	45.56	0.81	2.15	19.19	38.45	19.26	V

#### LTE Band 5\_5MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.50	-23.90	2.25	45.77	0.93	2.15	18.40	38.45	20.05	V
836.50	-22.93	2.26	45.66	0.82	2.15	19.14	38.45	19.31	V
846.50	-22.76	2.26	45.56	0.82	2.15	19.21	38.45	19.24	V

#### LTE Band 5\_10MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
829.00	-23.75	2.13	45.74	0.90	2.15	18.61	38.45	19.84	V
836.50	-22.81	2.26	45.66	0.82	2.15	19.26	38.45	19.19	V
844.00	-22.81	2.26	45.59	0.82	2.15	19.19	38.45	19.26	V

**LTE Band 5\_1.4MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.70	-24.84	2.26	45.79	0.95	2.15	17.49	38.45	20.96	V
836.50	-23.69	2.26	45.66	0.82	2.15	18.38	38.45	20.07	V
848.30	-23.67	2.27	45.55	0.80	2.15	18.26	38.45	20.19	V

**LTE Band 5\_3MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
825.50	-24.82	2.26	45.79	0.94	2.15	17.50	38.45	20.95	V
836.50	-23.87	2.26	45.66	0.82	2.15	18.20	38.45	20.25	V
847.50	-23.71	2.27	45.56	0.81	2.15	18.24	38.45	20.21	V

**LTE Band 5\_5MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.50	-24.71	2.25	45.77	0.93	2.15	17.59	38.45	20.86	V
836.50	-23.84	2.26	45.66	0.82	2.15	18.23	38.45	20.22	V
846.50	-23.63	2.26	45.56	0.82	2.15	18.34	38.45	20.11	V

**LTE Band 5\_10MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
829.00	-24.71	2.13	45.74	0.90	2.15	17.65	38.45	20.80	V
836.50	-23.63	2.26	45.66	0.82	2.15	18.44	38.45	20.01	V
844.00	-23.81	2.26	45.59	0.82	2.15	18.19	38.45	20.26	V

### LTE Band 7- EIRP

Limits: ≤33 dBm (2W)

#### LTE Band 7\_5MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2502.50	-25.66	3.58	45.68	6.10	22.54	33.00	10.46	H
2535.00	-23.58	3.63	44.82	6.16	23.77	33.00	9.23	H
2567.50	-23.33	3.65	44.92	6.22	24.16	33.00	8.84	H

#### LTE Band 7\_10MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2505.00	-25.46	3.59	45.64	6.11	22.70	33.00	10.30	H
2535.00	-23.55	3.63	44.82	6.16	23.80	33.00	9.20	H
2565.00	-23.39	3.65	44.97	6.22	24.15	33.00	8.85	H

#### LTE Band 7\_15MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2507.50	-24.49	3.59	44.92	6.11	22.95	33.00	10.05	H
2535.00	-23.56	3.63	44.82	6.16	23.79	33.00	9.21	H
2562.50	-24.13	3.65	45.67	6.21	24.10	33.00	8.90	H

#### LTE Band 7\_20MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2510.00	-24.66	3.58	45.36	6.12	23.24	33.00	9.76	H
2535.00	-23.48	3.63	44.82	6.16	23.87	33.00	9.13	H
2560.00	-24.25	3.64	45.98	6.21	24.30	33.00	8.70	H



**LTE Band 7\_5MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2502.50	-26.54	3.58	45.68	6.10	21.66	33.00	11.34	H
2535.00	-24.52	3.63	44.82	6.16	22.83	33.00	10.17	H
2567.50	-24.14	3.65	44.92	6.22	23.35	33.00	9.65	H

**LTE Band 7\_10MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2505.00	-26.43	3.59	45.64	6.11	21.73	33.00	11.27	H
2535.00	-24.38	3.63	44.82	6.16	22.97	33.00	10.03	H
2565.00	-24.34	3.65	44.97	6.22	23.20	33.00	9.80	H

**LTE Band 7\_15MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2507.50	-25.40	3.59	44.92	6.11	22.04	33.00	10.96	H
2535.00	-24.40	3.63	44.82	6.16	22.95	33.00	10.05	H
2562.50	-25.05	3.65	45.67	6.21	23.18	33.00	9.82	H

**LTE Band 7\_20MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2510.00	-25.70	3.58	45.36	6.12	22.20	33.00	10.80	H
2535.00	-24.36	3.63	44.82	6.16	22.99	33.00	10.01	H
2560.00	-25.17	3.64	45.98	6.21	23.38	33.00	9.62	H

**LTE Band 12 - ERP**
**Limits:** ≤34.77dBm (3W)

**LTE Band 12\_1.4MHz\_QPSK**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
699.70	-26.34	1.90	44.66	0.77	2.15	15.04	34.77	19.73	V
707.50	-26.41	1.91	44.94	0.62	2.15	15.09	34.77	19.68	V
715.30	-26.55	1.92	45.26	0.50	2.15	15.14	34.77	19.63	H

**LTE Band 12\_3MHz\_QPSK**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
700.50	-26.33	1.90	44.68	0.76	2.15	15.06	34.77	19.71	V
707.50	-26.69	1.91	44.94	0.62	2.15	14.81	34.77	19.96	V
714.50	-27.00	1.92	45.26	0.50	2.15	14.69	34.77	20.08	V

**LTE Band 12\_5MHz\_QPSK**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
701.50	-26.49	1.90	44.81	0.74	2.15	15.01	34.77	19.76	V
707.50	-26.73	1.91	44.94	0.62	2.15	14.77	34.77	20.00	V
713.50	-26.95	1.92	45.22	0.50	2.15	14.70	34.77	20.07	V

**LTE Band 12\_10MHz\_QPSK**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
704.00	-26.45	1.91	44.93	0.70	2.15	15.12	34.77	19.65	V
707.50	-26.64	1.91	44.94	0.62	2.15	14.86	34.77	19.91	V
711.00	-26.87	1.92	45.19	0.53	2.15	14.78	34.77	19.99	V

**LTE Band 12\_1.4MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
699.70	-27.25	1.90	44.66	0.77	2.15	14.13	34.77	20.64	V
707.50	-27.32	1.91	44.94	0.62	2.15	14.18	34.77	20.59	V
715.30	-28.04	1.92	45.26	0.50	2.15	13.65	34.77	21.12	V

**LTE Band 12\_3MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
700.50	-27.27	1.90	44.68	0.76	2.15	14.12	34.77	20.65	V
707.50	-27.46	1.91	44.94	0.62	2.15	14.04	34.77	20.73	V
714.50	-27.96	1.92	45.26	0.50	2.15	13.73	34.77	21.04	V

**LTE Band 12\_5MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
701.50	-27.31	1.90	44.81	0.74	2.15	14.19	34.77	20.58	V
707.50	-27.58	1.91	44.94	0.62	2.15	13.92	34.77	20.85	V
713.50	-27.87	1.92	45.22	0.50	2.15	13.78	34.77	20.99	V

**LTE Band 12\_10MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
704.00	-27.42	1.91	44.93	0.70	2.15	14.15	34.77	20.62	V
707.50	-27.43	1.91	44.94	0.62	2.15	14.07	34.77	20.70	V
711.00	-27.77	1.92	45.19	0.53	2.15	13.88	34.77	20.89	V

**LTE Band 13- ERP**
**Limits:** ≤34.77 dBm (3W)

**LTE Band 13\_5MHz\_QPSK**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
779.50	-27.51	2.01	45.64	0.04	2.15	14.01	34.77	20.76	H
782.00	-27.67	2.01	45.65	0.09	2.15	13.91	34.77	20.86	H
784.50	-27.60	2.01	45.67	0.16	2.15	14.07	34.77	20.70	H

**LTE Band 13\_10MHz\_QPSK**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
782.00	-27.50	2.01	45.65	0.09	2.15	14.08	34.77	20.69	H

**LTE Band 13\_5MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
779.50	-28.33	2.01	45.64	0.04	2.15	13.19	34.77	21.58	H
782.00	-28.64	2.01	45.65	0.09	2.15	12.94	34.77	21.83	H
784.50	-28.48	2.01	45.67	0.16	2.15	13.19	34.77	21.58	H

**LTE Band 13\_10MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
782.00	-28.47	2.01	45.65	0.09	2.15	13.11	34.77	21.66	H

### LTE Band 66- EIRP

Limits: ≤30dBm (1W)

#### LTE Band 66\_1.4MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.70	-31.43	3.17	44.10	5.12	20.96	30.00	9.04	H
1745.00	-32.14	3.68	44.16	5.06	20.76	30.00	9.24	H
1779.30	-30.17	3.04	44.03	5.00	21.90	30.00	8.10	H

#### LTE Band 66\_3MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.50	-31.74	3.40	44.10	5.12	20.88	30.00	9.12	H
1745.00	-32.28	3.68	44.16	5.06	20.62	30.00	9.38	H
1778.50	-30.33	3.04	44.03	5.00	21.74	30.00	8.26	H

#### LTE Band 66\_5MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.50	-24.66	3.66	44.10	5.12	20.90	30.00	9.10	H
1745.00	-24.87	3.68	44.16	5.06	20.67	30.00	9.33	H
1777.50	-24.22	3.04	44.04	5.00	21.78	30.00	8.22	H

#### LTE Band 66\_10MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.00	-24.61	3.56	44.10	5.11	21.04	30.00	8.96	H
1745.00	-24.74	3.68	44.16	5.06	20.80	30.00	9.20	H
1775.00	-24.26	3.05	44.05	5.01	21.74	30.00	8.26	H

#### LTE Band 66\_15MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.50	-24.80	3.47	44.11	5.11	20.95	30.00	9.05	H
1745.00	-24.85	3.68	44.16	5.06	20.69	30.00	9.31	H
1772.50	-24.49	3.05	44.06	5.01	21.53	30.00	8.47	H

#### LTE Band 66\_20MHz\_QPSK

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.00	-24.88	3.37	44.11	5.10	20.96	30.00	9.04	H
1745.00	-24.73	3.68	44.16	5.06	20.81	30.00	9.19	H
1770.00	-24.54	3.05	44.07	5.01	21.50	30.00	8.50	H

**LTE Band 66\_1.4MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.70	-32.29	3.17	44.10	5.12	20.10	30.00	9.90	H
1745.00	-33.08	3.68	44.16	5.06	19.82	30.00	10.18	H
1779.30	-31.14	3.04	44.03	5.00	20.93	30.00	9.07	H

**LTE Band 66\_3MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.50	-32.61	3.40	44.10	5.12	20.01	30.00	9.99	H
1745.00	-32.73	3.68	44.16	5.06	20.17	30.00	9.83	H
1778.50	-31.18	3.04	44.03	5.00	20.89	30.00	9.11	H

**LTE Band 66\_5MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.50	-25.51	3.66	44.10	5.12	20.05	30.00	9.95	H
1745.00	-25.74	3.68	44.16	5.06	19.80	30.00	10.20	H
1777.50	-25.12	3.04	44.04	5.00	20.88	30.00	9.12	H

**LTE Band 66\_10MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.00	-25.42	3.56	44.10	5.11	20.23	30.00	9.77	H
1745.00	-25.70	3.68	44.16	5.06	19.84	30.00	10.16	H
1775.00	-24.88	3.05	44.05	5.01	21.12	30.00	8.88	H

**LTE Band 66\_15MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.50	-25.68	3.47	44.11	5.11	20.07	30.00	9.93	H
1745.00	-25.65	3.68	44.16	5.06	19.89	30.00	10.11	H
1772.50	-25.14	3.05	44.06	5.01	20.88	30.00	9.12	H

**LTE Band 66\_20MHz\_16QAM**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.00	-25.80	3.37	44.11	5.10	20.04	30.00	9.96	H
1745.00	-25.49	3.68	44.16	5.06	20.05	30.00	9.95	H
1770.00	-25.51	3.05	44.07	5.01	20.53	30.00	9.47	H

$$\text{Peak EIRP(dBm)} = P_{\text{Mea}}(-24.25 \text{ dBm}) + G_a (6.21\text{dBi}) + P_{\text{Ag}} (45.98\text{dB}) - P_{\text{cl}} (3.64\text{dB}) = 24.30\text{dBm}$$

Note: Expanded measurement uncertainty is  $U = 2.84 \text{ dB}$ ,  $k = 2$ .

## A.2 EMISSION LIMIT


### A.2.1 Measurement Method

The measurements procedures in TIA-603E-2016 are used. This measurement is carried out in fully-anechoic chamber FAC-3.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier. The resolution bandwidth is set 1MHz. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE Bands 2,5,7,12,13,66.

#### The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5-meter-high non-conductive stand at a 3-meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360 and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_{pl}$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

An amplifier should be connected in for the test.

The Path loss ( $P_{pl}$ ) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{Mea} + P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit: dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dB}$ .

### A.2.2 Measurement Limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power ( $P$ ) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power ( $P$ ) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than  $40 + 10 \log(P)$  dB on all frequencies between the channel edge and 5 megahertz from the channel edge,  $43 + 10 \log(P)$  dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and  $55 + 10 \log(P)$  dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than  $43 + 10 \log(P)$  dB on all frequencies between 2490.5 MHz and 2496 MHz and  $55 + 10 \log(P)$  dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(c) states for operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power ( $P$ ) within the licensed band(s) of operation, measured in watts, in accordance with the following: (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power ( $P$ ) by at least  $43 + 10 \log(P)$  dB; (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power ( $P$ ) by at least  $43 + 10 \log(P)$  dB; (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than  $65 +$



10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

### **A.2.3 Measurement Results**

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the LTE Bands 2,5,7,12,13,66. It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the LTE Bands 2,5,7,12,13,66 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this. The evaluated frequency range is from 30MHz to 26GHz.

**LTE Band 2, 1.4MHz, QPSK, Channel 18607**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3702.02	-43.56	6.42	8.48	-41.50	-13.00	28.50	V
5556.02	-34.88	7.19	10.59	-31.48	-13.00	18.48	H
7409.01	-37.82	8.14	12.09	-33.87	-13.00	20.87	H
9260.01	-42.54	9.06	13.26	-38.34	-13.00	25.34	H
11114.01	-44.32	9.78	13.18	-40.92	-13.00	27.92	H
12925.01	-48.66	10.50	13.46	-45.70	-13.00	32.70	H

**LTE Band 2, 1.4MHz, QPSK, Channel 18900**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.02	-47.78	6.26	8.56	-45.48	-13.00	32.48	V
5643.02	-33.52	7.27	10.57	-30.22	-13.00	17.22	H
7523.01	-35.55	8.30	12.22	-31.63	-13.00	18.63	V
9405.01	-47.08	9.06	13.34	-42.80	-13.00	29.80	V
11297.01	-46.60	9.98	13.14	-43.44	-13.00	30.44	H
13120.01	-47.62	10.85	13.67	-44.80	-13.00	31.80	V

**LTE Band 2, 1.4MHz, QPSK, Channel 19193**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.02	-47.63	6.08	8.65	-45.06	-13.00	32.06	H
5729.02	-39.00	7.29	10.55	-35.74	-13.00	22.74	V
7641.01	-32.41	8.16	12.31	-28.26	-13.00	15.26	V
9551.01	-46.05	9.36	13.35	-42.06	-13.00	29.06	V
11468.01	-48.29	9.89	13.11	-45.07	-13.00	32.07	V
13400.01	-47.31	10.57	14.06	-43.82	-13.00	30.82	H

**LTE Band 5, 1.4MHz, QPSK, Channel 20407**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1650.01	-51.22	3.57	5.23	2.15	-51.71	-13.00	38.71	H
2472.00	-52.80	4.59	6.02	2.15	-53.52	-13.00	40.52	V
3292.02	-54.44	5.29	7.70	2.15	-54.18	-13.00	41.18	V
4127.02	-52.57	6.04	9.03	2.15	-51.73	-13.00	38.73	V
4952.01	-52.50	6.69	9.85	2.15	-51.49	-13.00	38.49	V
5759.01	-53.06	7.25	10.55	2.15	-51.91	-13.00	38.91	H

**LTE Band 5, 1.4MHz, QPSK, Channel 20525**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.01	-52.75	3.58	5.19	2.15	-53.29	-13.00	40.29	H
2510.00	-52.50	4.63	6.12	2.15	-53.16	-13.00	40.16	V
3352.02	-53.84	5.32	7.84	2.15	-53.47	-13.00	40.47	H
4185.02	-53.82	6.17	9.09	2.15	-53.05	-13.00	40.05	V
5027.01	-54.10	6.57	9.94	2.15	-52.88	-13.00	39.88	V
5848.01	-52.79	7.23	10.53	2.15	-51.64	-13.00	38.64	V

**LTE Band 5, 1.4MHz, QPSK, Channel 20643**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.01	-54.61	3.60	5.15	2.15	-55.21	-13.00	42.21	H
2541.00	-53.20	4.66	6.17	2.15	-53.84	-13.00	40.84	H
3406.02	-54.77	5.37	7.97	2.15	-54.32	-13.00	41.32	H
4246.02	-50.88	6.24	9.15	2.15	-50.12	-13.00	37.12	H
5081.01	-53.52	6.72	10.01	2.15	-52.38	-13.00	39.38	V
5945.01	-53.14	7.47	10.51	2.15	-52.25	-13.00	39.25	V

**LTE Band 7, 5 MHz, QPSK, Channel 20775**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5009.02	-53.35	6.59	9.91	-50.03	-25.00	25.03	V
7511.01	-30.17	8.35	12.21	-26.31	-25.00	1.31	H
10020.01	-42.51	9.24	12.91	-38.84	-25.00	13.84	H
12518.01	-49.16	10.23	13.21	-46.18	-25.00	21.18	H
15008.00	-45.91	11.23	14.00	-43.14	-25.00	18.14	V
17501.00	-43.99	12.73	14.90	-41.82	-25.00	16.82	H

**LTE Band 7, 5 MHz, QPSK, Channel 21100**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5073.02	-52.94	6.70	10.00	-49.64	-25.00	24.64	V
7611.01	-32.13	8.02	12.29	-27.86	-25.00	2.86	H
10156.01	-46.07	9.37	12.96	-42.48	-25.00	17.48	H
12677.01	-48.68	10.34	13.31	-45.71	-25.00	20.71	H
15190.00	-45.40	11.39	13.89	-42.90	-25.00	17.90	V
17762.00	-44.52	12.52	15.27	-41.77	-25.00	16.77	V

**LTE Band 7, 5 MHz, QPSK, Channel 21425**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5139.02	-53.61	6.86	10.09	-50.38	-25.00	25.38	V
7709.01	-31.66	8.41	12.37	-27.70	-25.00	2.70	H
10286.01	-39.98	9.60	13.01	-36.57	-25.00	11.57	H
12854.01	-46.88	10.63	13.41	-44.10	-25.00	19.10	V
15405.00	-44.96	11.40	13.76	-42.60	-25.00	17.60	H
17974.00	-43.23	12.89	15.56	-40.56	-25.00	15.56	H

**LTE Band 12, 1.4MHz, QPSK, Channel 23017**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1400.01	-48.87	3.24	4.98	2.15	-49.28	-13.00	36.28	H
2100.00	-36.72	4.19	4.90	2.15	-38.16	-13.00	25.16	H
2799.00	-52.45	4.91	6.64	2.15	-52.87	-13.00	39.87	V
3499.02	-54.30	5.52	8.20	2.15	-53.77	-13.00	40.77	H
4194.02	-54.23	6.19	9.09	2.15	-53.48	-13.00	40.48	V
4902.01	-52.40	6.73	9.80	2.15	-51.48	-13.00	38.48	V

**LTE Band 12, 1.4MHz, QPSK, Channel 23095**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.01	-47.23	3.25	5.06	2.15	-47.57	-13.00	34.57	H
2123.00	-36.78	4.21	4.97	2.15	-38.17	-13.00	25.17	H
2842.00	-51.77	4.95	6.72	2.15	-52.15	-13.00	39.15	V
3538.02	-49.19	5.70	8.25	2.15	-48.79	-13.00	35.79	H
4251.02	-53.75	6.24	9.15	2.15	-52.99	-13.00	39.99	H
4953.01	-52.44	6.68	9.85	2.15	-51.42	-13.00	38.42	V

**LTE Band 12, 1.4MHz, QPSK, Channel 23173**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1431.01	-46.95	3.28	5.14	2.15	-47.24	-13.00	34.24	H
2146.00	-38.40	4.24	5.04	2.15	-39.75	-13.00	26.75	H
2860.00	-50.43	4.96	6.75	2.15	-50.79	-13.00	37.79	H
3577.02	-50.51	6.10	8.31	2.15	-50.45	-13.00	37.45	H
4298.02	-52.81	6.20	9.20	2.15	-51.96	-13.00	38.96	H
5008.01	-53.12	6.59	9.91	2.15	-51.95	-13.00	38.95	H

**LTE Band 13, 5MHz, QPSK, Channel 23205**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1560.01	-51.96	3.47	5.39	2.15	-52.19	-13.00	39.19	V
2339.00	-42.41	4.44	5.62	2.15	-43.38	-13.00	30.38	H
3130.02	-53.05	5.40	7.31	2.15	-53.29	-13.00	40.29	V
3899.02	-53.16	6.11	8.76	2.15	-52.66	-13.00	39.66	V
4681.02	-50.37	6.49	9.58	2.15	-49.43	-13.00	36.43	V
5466.01	-54.18	6.93	10.55	2.15	-52.71	-13.00	39.71	H

**LTE Band 13, 5MHz, QPSK, Channel 23230**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1565.01	-53.91	3.48	5.38	2.15	-54.16	-13.00	41.16	V
2347.00	-44.56	4.45	5.64	2.15	-45.52	-13.00	32.52	H
3140.02	-52.88	5.38	7.34	2.15	-53.07	-13.00	40.07	H
3911.02	-51.00	6.12	8.78	2.15	-50.49	-13.00	37.49	V
4696.02	-49.58	6.50	9.60	2.15	-48.63	-13.00	35.63	V
5478.01	-53.42	6.98	10.57	2.15	-51.98	-13.00	38.98	H

**LTE Band 13, 5MHz, QPSK, Channel 23255**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1570.01	-52.21	3.48	5.37	2.15	-52.47	-13.00	39.47	V
2354.00	-44.92	4.46	5.66	2.15	-45.87	-13.00	32.87	H
3145.02	-52.41	5.38	7.35	2.15	-52.59	-13.00	39.59	H
3924.02	-54.65	6.12	8.79	2.15	-54.13	-13.00	41.13	V
4711.02	-50.76	6.51	9.61	2.15	-49.81	-13.00	36.81	V
5497.01	-54.10	7.05	10.60	2.15	-52.70	-13.00	39.70	V

**LTE Band 66, 1.4MHz QPSK, Channel 131979**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3422.02	-50.36	5.38	8.01	-47.73	-13.00	34.73	V
5138.02	-65.16	6.86	10.09	-61.93	-13.00	48.93	H
6847.01	-59.86	7.83	11.42	-56.27	-13.00	43.27	V
8559.01	-47.29	8.57	13.01	-42.85	-13.00	29.85	H
10280.01	-57.34	9.57	13.01	-53.90	-13.00	40.90	H
12028.01	-60.24	10.13	13.01	-57.36	-13.00	44.36	V

**LTE Band 66, 1.4MHz, QPSK, Channel 132322**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.02	-52.27	5.50	8.18	-49.59	-13.00	36.59	H
5238.02	-63.78	7.00	10.23	-60.55	-13.00	47.55	H
6984.01	-59.28	8.17	11.58	-55.87	-13.00	42.87	H
8729.01	-47.19	8.45	13.05	-42.59	-13.00	29.59	H
10484.01	-57.54	9.68	13.09	-54.13	-13.00	41.13	H
12229.01	-59.22	10.04	13.09	-56.17	-13.00	43.17	H

**LTE Band 66, 1.4MHz, QPSK, Channel 132665**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3559.02	-45.79	5.92	8.28	-43.43	-13.00	30.43	V
5344.02	-60.73	6.95	10.38	-57.30	-13.00	44.30	H
7121.01	-55.51	8.16	11.75	-51.92	-13.00	38.92	H
8902.01	-53.81	8.85	13.08	-49.58	-13.00	36.58	H
10686.01	-56.55	9.30	13.14	-52.71	-13.00	39.71	H
12493.01	-59.67	10.19	13.20	-56.66	-13.00	43.66	V

Note: The maximum value of expanded measurement uncertainty for this test item is  $U = 5.16$  dB,  $k = 2$ .

## **A.3 FREQUENCY STABILITY**

### **A.3.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a “call mode”. This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE Bands 2,5,7,12,13,66, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the center channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.4VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.



### A.3.2 Measurement results

#### LTE Band 2, 20MHz bandwidth QPSK (worst case of all bandwidths)

##### Frequency Error vs Temperature

Temperature(°C)	Voltage(V)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
20	3.8	1850.881	1909.119		
50				-1.91	0.0010
40				-8.32	0.0044
30				-4.10	0.0022
10				-1.73	0.0009
0				-3.09	0.0016
-10				-4.09	0.0022
-20				-5.56	0.0030
-10				-0.93	0.0005

##### Frequency Error vs Voltage

Voltage(V)	Temperature(°C)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
3.5	20	1850.881	1909.119	2.66	0.0014
4.4				0.20	0.0001

#### LTE Band 5, 10MHz bandwidth QPSK (worst case of all bandwidths)

##### Frequency Error vs Temperature

Temperature(°C)	Voltage(V)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
20	3.8	824.433	848.567		
50				-0.80	0.0010
40				0.50	0.0006
30				-1.02	0.0012
10				-2.72	0.0033
0				-1.85	0.0022
-10				0.60	0.0007
-20				-1.29	0.0015
-10				0.44	0.0005

##### Frequency Error vs Voltage

Voltage(V)	Temperature(°C)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
3.5	20	824.433	848.567	3.60	0.0043
4.4				2.80	0.0033

**LTE Band 7, 20MHz bandwidth QPSK (worst case of all bandwidths)**

**Frequency Error vs Temperature**

Temperature(°C)	Voltage(V)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
20	3.8	2500.625	2569.375		
50				-4.85	0.0021
40				2.62	0.0011
30				5.28	0.0023
10				-0.36	0.0002
0				0.67	0.0003
-10				-4.29	0.0018
-20				2.10	0.0009
-10				3.43	0.0015

**Frequency Error vs Voltage**

Voltage(V)	Temperature(°C)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
3.5	20	2500.625	2569.375	6.02	0.0026
4.4				3.83	0.0016

**LTE Band 12, 10MHz bandwidth QPSK (worst case of all bandwidths)**

**Frequency Error vs Temperature**

Temperature(°C)	Voltage(V)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
20	3.8	699.481	715.503		
50				3.89	0.0055
40				4.44	0.0063
30				3.55	0.0050
10				3.18	0.0045
0				-0.61	0.0009
-10				-1.36	0.0019
-20				2.50	0.0035
-10				4.41	0.0062

**Frequency Error vs Voltage**

Voltage(V)	Temperature(°C)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
3.5	20	699.481	715.503	3.35	0.0047
4.4				3.51	0.0050

**LTE Band 13, 10MHz bandwidth QPSK (worst case of all bandwidths)**

**Frequency Error vs Temperature**

Temperature(°C)	Voltage(V)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
20	3.8	777.481	786.503		
50				1.04	0.0013
40				-0.12	0.0002
30				2.64	0.0034
10				-3.55	0.0045
0				1.01	0.0013
-10				1.40	0.0018
-20				-1.05	0.0013
-10				-3.18	0.0041

**Frequency Error vs Voltage**

Voltage(V)	Temperature(°C)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
3.5	20	777.481	786.503	4.87	0.0062
4.4				-0.35	0.0004

**LTE Band 66, 20MHz bandwidth QPSK (worst case of all bandwidths)**

**Frequency Error vs Temperature**

Temperature(°C)	Voltage(V)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
20	3.8	1710.865	1779.135		
50				-4.05	0.0023
40				-0.73	0.0004
30				-0.19	0.0001
10				-3.02	0.0017
0				-4.15	0.0024
-10				-3.82	0.0022
-20				-2.35	0.0013
-10				-3.98	0.0023

**Frequency Error vs Voltage**

Voltage(V)	Temperature(°C)	F <sub>L</sub> (MHz)	F <sub>H</sub> (MHz)	Offset(Hz)	Frequency error(ppm)
3.5	20	1710.865	1779.135	-4.05	0.0023
4.4				-0.19	0.0001

#### **A.4 OCCUPIED BANDWIDTH**

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the mid frequencies frequency. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.


The measurement method is from ANSI C63.26:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts.
- b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set  $\geq 3 \times$  RBW.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.
- d) Set the detection mode to peak, and the trace mode to max-hold.

### LTE band 2, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	1097.76	1089.74

### LTE band 2, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:01:55

### LTE band 2, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:02:33

**LTE band 2, 3MHz (99%)**


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	2692.31	2692.31

**LTE band 2, 3MHz Bandwidth, QPSK (99% BW)**



Date: 15.APR.2020 20:04:04

**LTE band 2, 3MHz Bandwidth, 16QAM (99% BW)**




Date: 15.APR.2020 20:04:42

**LTE band 2, 5MHz (99%)**


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	4471.15	4471.15

**LTE band 2, 5MHz Bandwidth, QPSK (99% BW)**



Date: 15.APR.2020 20:06:13

**LTE band 2, 5MHz Bandwidth, 16QAM (99% BW)**




Date: 15.APR.2020 20:06:51

**LTE band 2, 10MHz (99%)**


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	8990.38	8990.38

**LTE band 2, 10MHz Bandwidth, QPSK (99% BW)**



Date: 15.APR.2020 20:08:24

**LTE band 2, 10MHz Bandwidth, 16QAM (99% BW)**




Date: 15.APR.2020 20:09:03



**LTE band 2, 15MHz (99%)**


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	13485.58	13413.46

**LTE band 2, 15MHz Bandwidth, QPSK (99% BW)**



Date: 15.APR.2020 20:10:35

**LTE band 2, 15MHz Bandwidth, 16QAM (99% BW)**




Date: 15.APR.2020 20:11:14

### LTE band 2, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	17884.62	17884.62

### LTE band 2, 20MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:12:53

### LTE band 2, 20MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:13:32

### LTE band 5, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
	836.5	QPSK
1081.73		1089.74

### LTE band 5, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:15:03

### LTE band 5, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:15:42

### LTE band 5, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
836.5	QPSK	16QAM
	2692.31	2692.31

### LTE band 5, 3MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:17:13

### LTE band 5, 3MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:17:51

### LTE band 5, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
836.5	QPSK	16QAM
	4519.23	4471.15

### LTE band 5, 5MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:19:22

### LTE band 5, 5MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:20:00

### LTE band 5, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
836.5	QPSK	16QAM
	8990.38	8990.38

### LTE band 5, 10MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:21:31

### LTE band 5, 10MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:22:10

**LTE band 7, 5MHz (99%)**


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
2535.0	QPSK	16QAM
	4495.19	4471.15

**LTE band 7, 5MHz Bandwidth, QPSK (99% BW)**



Date: 15.APR.2020 20:23:41

**LTE band 7, 5MHz Bandwidth, 16QAM (99% BW)**




Date: 15.APR.2020 20:24:20

### LTE band 7, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
2535.0	QPSK	16QAM
	8942.31	8942.31

### LTE band 7, 10MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:25:59

### LTE band 7, 10MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:26:38



### LTE band 7, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
2535.0	QPSK	16QAM
	13413.46	13413.46

### LTE band 7, 15MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:28:26

### LTE band 7, 15MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:29:05

### LTE band 7, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
2535.0	QPSK	16QAM
	17884.62	17884.62

### LTE band 7, 20MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:30:55

### LTE band 7, 20MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:31:34

### LTE band 12, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707.5	QPSK	16QAM
	1081.73	1089.74

### LTE band 12, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:33:02

### LTE band 12, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:33:41

### LTE band 12, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707.5	QPSK	16QAM
	2692.31	2692.31

### LTE band 12, 3MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:35:14

### LTE band 12, 3MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:35:53

### LTE band 12, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707.5	QPSK	16QAM
	4495.19	4471.15

### LTE band 12, 5MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:37:23

### LTE band 12, 5MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:38:02

### LTE band 12, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707.5	QPSK	16QAM
	8990.38	8990.38

### LTE band 12, 10MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:39:35

### LTE band 12, 10MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:40:14

**LTE band 13, 5MHz (99%)**


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
782.0	QPSK	16QAM
	4495.19	4495.19

**LTE band 13, 5MHz Bandwidth, QPSK (99% BW)**



Date: 15.APR.2020 20:41:45

**LTE band 13, 5MHz Bandwidth, 16QAM (99% BW)**




Date: 15.APR.2020 20:42:24

### LTE band 13, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
782.0	QPSK	16QAM
	8990.38	9038.46

### LTE band 13, 10MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:43:53

### LTE band 13, 10MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:44:31



### LTE band 66, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1745.0	QPSK	16QAM
	1081.73	1089.74

### LTE band 66, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:46:03


### LTE band 66, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:46:42

**LTE band 66, 3MHz (99%)**

Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1745.0	QPSK	16QAM
	2692.31	2692.31

**LTE band 66, 3MHz Bandwidth, QPSK (99% BW)**


Date: 15.APR.2020 20:48:12


**LTE band 66, 3MHz Bandwidth, 16QAM (99% BW)**


Date: 15.APR.2020 20:48:51

### LTE band 66, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1745.0	QPSK	16QAM
	4495.19	4471.15

### LTE band 66, 5MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:50:21

### LTE band 66, 5MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:51:00

### LTE band 66, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1745.0	QPSK	16QAM
	8990.38	8990.38

### LTE band 66, 10MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:52:31

### LTE band 66, 10MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:53:10

### LTE band 66, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1745.0	QPSK	16QAM
	13485.58	13485.58

### LTE band 66, 15MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:54:40

### LTE band 66, 15MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2020 20:55:19

### LTE band 66, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
	1745.0	QPSK
17980.77		17980.77

### LTE band 66, 20MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2020 20:56:50

### LTE band 66, 20MHz Bandwidth, 16QAM (99% BW)



Date: 15.APR.2020 20:57:29

## **A.5 EMISSION BANDWIDTH**

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.


The measurement method is from ANSI C63.26:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be wide enough to see sufficient roll off of the signal to make the measurement.
- b) The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set  $\geq 3 \times$  RBW.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.
- d) The dynamic range of the spectrum analyzer at the selected RBW shall be more than 10 dB below the target “-X dB” requirement, i.e., if the requirement calls for measuring the -26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be at least 36 dB below the reference level.
- e) Set spectrum analyzer detection mode to peak, and the trace mode to max hold.

### LTE band 2, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	1274.04	1290.06

### LTE band 2, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 20:58:43

### LTE band 2, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 20:59:22



### LTE band 2, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	2900.64	2884.62

### LTE band 2, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:00:53

### LTE band 2, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:01:33

### LTE band 2, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	4855.77	4831.73

### LTE band 2, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:03:04

### LTE band 2, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:03:43

**LTE band 2, 10MHz (-26dBc)**


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	9615.38	9615.38

**LTE band 2, 10MHz Bandwidth, QPSK (-26dBc BW)**



Date: 15.APR.2020 21:05:14

**LTE band 2, 10MHz Bandwidth, 16QAM (-26dBc BW)**




Date: 15.APR.2020 21:05:54

### LTE band 2, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	14639.42	14567.31

### LTE band 2, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:07:27

### LTE band 2, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:08:06

**LTE band 2, 20MHz (-26dBc)**


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	19326.92	19230.77

**LTE band 2, 20MHz Bandwidth, QPSK (-26dBc BW)**



Date: 15.APR.2020 21:09:46

**LTE band 2, 20MHz Bandwidth, 16QAM (-26dBc BW)**




Date: 15.APR.2020 21:10:26

### LTE band 5, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
	836.5	QPSK
1282.05		1290.06

### LTE band 5, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:12:00

### LTE band 5, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:12:40

**LTE band 5, 3MHz (-26dBc)**


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
	836.5	QPSK
2884.62		2884.62

**LTE band 5, 3MHz Bandwidth, QPSK (-26dBc BW)**



Date: 15.APR.2020 21:14:11

**LTE band 5, 3MHz Bandwidth, 16QAM (-26dBc BW)**




Date: 15.APR.2020 21:14:50

### LTE band 5, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
836.5	QPSK	16QAM
	4831.73	4807.69

### LTE band 5, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:16:21

### LTE band 5, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:17:01



**LTE band 5, 10MHz (-26dBc)**


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
836.5	QPSK	16QAM
	9663.46	9663.46

**LTE band 5, 10MHz Bandwidth, QPSK (-26dBc BW)**



Date: 15.APR.2020 21:18:30

**LTE band 5, 10MHz Bandwidth, 16QAM (-26dBc BW)**




Date: 15.APR.2020 21:19:09

### LTE band 7, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
2535.0	QPSK	16QAM
	4831.73	4855.77

### LTE band 7, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:20:42

### LTE band 7, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:21:21

**LTE band 7, 10MHz (-26dBc)**


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
2535.0	QPSK	16QAM
	9663.46	9663.46

**LTE band 7, 10MHz Bandwidth, QPSK (-26dBc BW)**



Date: 15.APR.2020 21:23:01

**LTE band 7, 10MHz Bandwidth, 16QAM (-26dBc BW)**




Date: 15.APR.2020 21:23:40

### LTE band 7, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
	2535.0	QPSK
14567.31		14567.31

### LTE band 7, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:25:29

### LTE band 7, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:26:09

### LTE band 7, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
	2535.0	QPSK
	19134.62	19230.77

### LTE band 7, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:28:00

### LTE band 7, 20MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:28:39

### LTE band 12, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
	707.5	QPSK
1282.05		1314.10

### LTE band 12, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:30:09

### LTE band 12, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:30:48

### LTE band 12, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
707.5	QPSK	16QAM
	2884.62	2884.62

### LTE band 12, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:32:19

### LTE band 12, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:32:59

**LTE band 12, 5MHz (-26dBc)**


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
707.5	QPSK	16QAM
	4951.92	4927.88

**LTE band 12, 5MHz Bandwidth, QPSK (-26dBc BW)**



Date: 15.APR.2020 21:34:30

**LTE band 12, 5MHz Bandwidth, 16QAM (-26dBc BW)**




Date: 15.APR.2020 21:35:10



### LTE band 12, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
707.5	QPSK	16QAM
	9855.77	9855.77

### LTE band 12, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:36:41

### LTE band 12, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:37:20

### LTE band 13, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
782.0	QPSK	16QAM
	5024.04	4975.96

### LTE band 13, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:38:50

### LTE band 13, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:39:30

**LTE band 13, 10MHz (-26dBc)**


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
782.0	QPSK	16QAM
	9807.69	10000.00

**LTE band 13, 10MHz Bandwidth, QPSK (-26dBc BW)**



Date: 15.APR.2020 21:41:01

**LTE band 13, 10MHz Bandwidth, 16QAM (-26dBc BW)**




Date: 15.APR.2020 21:41:41

### LTE band 66, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
	1745.0	QPSK
1282.05		1306.09

### LTE band 66, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:43:13

### LTE band 66, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:43:53

### LTE band 66, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
	1745.0	QPSK
2884.62		2900.64

### LTE band 66, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:45:24

### LTE band 66, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:46:03

### LTE band 66, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1745.0	QPSK	16QAM
	5000.00	5000.00

### LTE band 66, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:47:34

### LTE band 66, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:48:14

### LTE band 66, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
	1745.0	QPSK
9903.8		9951.92

### LTE band 66, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:49:45

### LTE band 66, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:50:25

### LTE band 66, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
	1745.0	QPSK
15000.00		14855.77

### LTE band 66, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:51:56

### LTE band 66, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2020 21:52:36



### LTE band 66, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
	1745.0	QPSK
19519.23		19711.54

### LTE band 66, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2020 21:54:07

### LTE band 66, 20MHz Bandwidth, 16QAM (-26dBc BW)



Date: 15.APR.2020 21:54:47

## **A.6 BAND EDGE COMPLIANCE**

### **A.6.1 Measurement limit**

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


According to KDB 971168, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than  $40 + 10 \log(P)$  dB on all frequencies between the channel edge and 5 megahertz from the channel edge,  $43 + 10 \log(P)$  dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and  $55 + 10 \log(P)$  dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than  $43 + 10 \log(P)$  dB on all frequencies between 2490.5 MHz and 2496 MHz and  $55 + 10 \log(P)$  dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.


Part 27.53(c) states for operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following: (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB; (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB; (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than  $65 + 10 \log(P)$  dB in a 6.25 kHz band segment, for mobile and portable stations.

**A.6.2 Measurement result**  
**Only the worst case result is given below**  
**LTE band 2**  
**OBW: 1RB-low\_offset**




Date: 16.APR.2020 17:45:56

**LOW BAND EDGE BLOCK-1RB-low\_offset**




Date: 16.APR.2020 17:47:34

### OBW: 1RB-high\_offset




Date: 16.APR.2020 17:50:46

### HIGH BAND EDGE BLOCK-1RB-high\_offset




Date: 16.APR.2020 17:52:24

### LOW BAND EDGE BLOCK-20MHz-100%RB




Date: 16.APR.2020 17:49:33

### HIGH BAND EDGE BLOCK-20MHz-100%RB




Date: 16.APR.2020 17:54:22

**LTE band 5**  
**OBW: 1RB-low\_offset**




Date: 16.APR.2020 17:55:36

**LOW BAND EDGE BLOCK-1RB-low\_offset**




Date: 16.APR.2020 17:57:14

### OBW: 1RB-high\_offset




Date: 16.APR.2020 17:59:47

### HIGH BAND EDGE BLOCK-1RB-high\_offset




Date: 16.APR.2020 18:01:25

### LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 16.APR.2020 17:59:13


### HIGH BAND EDGE BLOCK-10MHz-100%RB



Date: 16.APR.2020 18:03:17




**LTE band 7**  
**OBW: 1RB-low\_offset**




Date: 16.APR.2020 18:03:52


**LOW BAND EDGE BLOCK-1RB-low\_offset**



Date: 16.APR.2020 18:05:36




Date: 16.APR.2020 18:07:18




Date: 16.APR.2020 18:07:28

OBW: 1RB-high\_offset




Date: 16.APR.2020 18:15:39


HIGH BAND EDGE BLOCK-1RB-high\_offset



Date: 16.APR.2020 18:17:23




Date: 16.APR.2020 18:19:07




Date: 16.APR.2020 18:19:18

### LOW BAND EDGE BLOCK-20MHz-100%RB




Date: 16.APR.2020 18:11:08




Date: 16.APR.2020 18:12:47

### HIGH BAND EDGE BLOCK-20MHz-100%RB




Date: 16.APR.2020 18:22:58




Date: 16.APR.2020 18:24:36

**LTE band 12**  
**OBW: 1RB-low\_offset**




Date: 16.APR.2020 18:27:39

**LOW BAND EDGE BLOCK-1RB-low\_offset**




Date: 16.APR.2020 18:29:17

### OBW: 1RB-high\_offset



Date: 16.APR.2020 18:31:49


### HIGH BAND EDGE BLOCK-1RB-high\_offset



Date: 16.APR.2020 18:33:27




**LOW BAND EDGE BLOCK-10MHz-100%RB**




Date: 16.APR.2020 18:31:15

**HIGH BAND EDGE BLOCK-10MHz-100%RB**




Date: 16.APR.2020 18:35:19

LTE band 13  
OBW: 1RB-low\_offset




Date: 16.APR.2020 18:35:53

LOW BAND EDGE BLOCK-1RB-low\_offset




Date: 16.APR.2020 18:37:31




Date: 16.APR.2020 18:39:09

**OBW: 1RB-high\_offset**




Date: 16.APR.2020 18:43:11

### HIGH BAND EDGE BLOCK-1RB-high\_offset




Date: 16.APR.2020 18:44:49




Date: 16.APR.2020 18:46:26

### LOW BAND EDGE BLOCK-10MHz-100%RB




Date: 16.APR.2020 18:41:00




Date: 16.APR.2020 18:42:37

### HIGH BAND EDGE BLOCK-10MHz-100%RB




Date: 16.APR.2020 18:48:18




Date: 16.APR.2020 18:49:55

**LTE band 66**  
**OBW: 1RB-low\_offset**



Date: 16.APR.2020 18:51:09


**LOW BAND EDGE BLOCK-1RB-low\_offset**



Date: 16.APR.2020 18:52:47




### OBW: 1RB-high\_offset




Date: 16.APR.2020 18:55:21

### HIGH BAND EDGE BLOCK-1RB-high\_offset




Date: 16.APR.2020 18:56:59

### LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 16.APR.2020 18:54:46

### HIGH BAND EDGE BLOCK-20MHz-100%RB



Date: 16.APR.2020 18:58:57

## **A.7 CONDUCTED SPURIOUS EMISSION**

### **A.7.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. In measuring unwanted emissions, the spectrum shall be investigated from 30 MHz or the lowest radio frequency signal generated in the equipment, whichever is lower, without going below 9 kHz, up to at least the frequency given below:
  - (a) If the equipment operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
  - (b) If the equipment operates at or above 10 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
3. The number of sweep points of spectrum analyzer is set to 30001 which is greater than span/RBW.

### **A. 7.2 Measurement Limit**

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than  $40 + 10 \log(P)$  dB on all frequencies between the channel edge and 5 megahertz from the channel edge,  $43 + 10 \log(P)$  dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and  $55 + 10 \log(P)$  dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than  $43 + 10 \log(P)$  dB on all frequencies between 2490.5 MHz and 2496 MHz and  $55 + 10 \log(P)$  dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(c) states for operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least  $43 +$




10 log (P) dB;(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB;(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than  $65 + 10 \log (P)$  dB in a 6.25 kHz band segment, for mobile and portable stations.

### A. 7.2 Measurement result


Only the worst case result is given below

#### LTE band 2: 30MHz – 19.1GHz




Date: 16.APR.2020 18:59:56

#### LTE band 5: 30MHz – 8.49GHz




Date: 16.APR.2020 19:01:16

### LTE band 7: 30MHz – 25.7GHz




Date: 16.APR.2020 19:01:47

### LTE band 12: 30MHz – 7.16GHz




Date: 16.APR.2020 19:02:53

### LTE band 13: 30MHz – 7.87GHz



Date: 16.APR.2020 19:04:11

### LTE band 13: 1559MHz – 1610MHz



Date: 16.APR.2020 19:04:39





## **A.8 PEAK-TO-AVERAGE POWER RATIO**

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e) Record the maximum PAPR level associated with a probability of 0.1%

### **A.8.1 Measurement limit**

not exceed 13 dB

### **A.8.2 Measurement results**

#### **LTE band 2, 20MHz**

Frequency(MHz)	PAPR(dB)	
1880.0	QPSK	16QAM
	6.70	7.31

#### **LTE band 7, 20MHz**

Frequency(MHz)	PAPR(dB)	
2535.0	QPSK	16QAM
	6.86	7.50

#### **LTE band 12, 10MHz**

Frequency(MHz)	PAPR(dB)	
707.5	QPSK	16QAM
	5.32	6.28

**LTE band 13, 10MHz**

Frequency(MHz)	PAPR(dB)	
782.0	QPSK	16QAM
	5.32	6.15

**LTE band 66, 20MHz**

Frequency(MHz)	PAPR(dB)	
1745.0	QPSK	16QAM
	6.57	7.24

## ANNEX B: Accreditation Certificate

<p>United States Department of Commerce National Institute of Standards and Technology</p> 	
<hr/> <b>Certificate of Accreditation to ISO/IEC 17025:2005</b> <hr/>	
NVLAP LAB CODE: 600118-0	
<b>Telecommunication Technology Labs, CAICT</b> Beijing China	
<i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i>	
<b>Electromagnetic Compatibility &amp; Telecommunications</b>	
<i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i>	
<hr/> 2019-09-26 through 2020-09-30 <i>Effective Dates</i>	 For the National Voluntary Laboratory Accreditation Program

\*\*\*END OF REPORT\*\*\*