



Mar 12, 2021

Declaration – MIF for HAC RF Interference Evaluation

To Whom It May Concern,

This device, with FCC ID: **2ACCJH126**, Hearing Aid Compatibility Requirement is going to be certified under **ANSI C63.19-2011 version per Part 20.19**.

The M rating was determined by measuring the maximum steady state average E-field values in dB (V/m) as documented in the HAC report and adding the MIF value in dB (V/m) using pre-determined values provided by Speag under the below table:

Typical MIF levels in ANSI C63.19-2011	
Transmission protocol	Modulation interference factor
GSM-FDD (TDMA, GMSK)	+3.63 dB
EDGE-FDD (TDMA, 8PSK, TN 0-1)	+1.23dB
EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	-0.52dB
EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	-1.82dB
UMTS-FDD(WCDMA, AMR)	-25.43dB
UMTS-FDD (HSPA)	-20.75dB
LTE-FDD (SC-FDMA, 1RB, 20MHz, QPSK)	-15.63 dB
LTE-FDD (SC-FDMA, 1RB, 20MHz, 16QAM)	-9.76 dB
LTE-FDD (SC-FDMA, 1RB, 20MHz, 64QAM)	-9.93 dB
IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	-5.90 dB
IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	-5.17 dB
IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	-3.37 dB
IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	-2.02 dB
IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	-0.36dB
IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	-15.80 dB

The Speag-reference documentation for supporting the pre-determined MIF value is Schmid &Partner Engineering AG, **UID SUMMARY (Communication Systems for Calibration, Issued Date 07/03/2018)**.

We confirm that the Speag simulation provided represents all the air interface modes applicable for a HAC rating for this handset.

Sincerely Yours.

Signature:

GONG Zhizhou

Product Certification Manager/ TCL Communication Ltd.