



**FCC PART 15C
TEST REPORT
No.I17Z61036-IOT07**

for

TCL Communication Ltd.

GSM Quad-band/HSPA-UMTS Six-band/LTE 19-band mobile phone

BBD100-1

With

FCC ID: 2ACCJN019

Hardware Version: 04

Software Version: AAN966

Issued Date: 2017-09-04



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I17Z61036-IOT07	Rev.0	1st edition	2017-09-04



CONTENTS

CONTENTS	3
1. TEST LATORATORY	7
1.1. TESTING LOCATION	7
1.2. TESTINGENVIRONMENT	7
1.3. PROJECT DATA	7
1.4. SIGNATURE	7
2. CLIENT INFORMATION	8
2.1. APPLICANT INFORMATION	8
2.2. MANUFACTURER INFORMATION	8
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT(AE)	9
3.1. ABOUT EUT	9
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	9
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	9
3.4. GENERAL DESCRIPTION	10
4. REFERENCE DOCUMENTS	10
4.1. DOCUMENTS SUPPLIED BY APPLICANT	10
4.2. REFERENCE DOCUMENTS FOR TESTING	10
5. LABORATORY ENVIRONMENT	10
6. SUMMARY OF TEST RESULTS	11
6.1. SUMMARY OF TEST RESULTS	11
6.2. STATEMENTS	11
6.3. TEST CONDITIONS	11
7. TEST EQUIPMENTS UTILIZED	12
8. MEASUREMENT UNCERTAINTY	13
8.1. TRANSMITTER OUTPUT POWER	13
8.2. PEAK POWER SPECTRAL DENSITY	13
8.3. OCCUPIED 6DB BANDWIDTH	13
8.4. BAND EDGES COMPLIANCE	13
8.5. SPURIOUS EMISSIONS	13
8.6. AC POWER-LINE CONDUCTED EMISSION	13
ANNEX A: MEASUREMENT RESULTS	14
A.1. MEASUREMENT METHOD	14
A.2. MAXIMUM PEAK OUTPUT POWER	15

A.2.1 ANTENNA GAIN	15
A.2.2. MAXIMUM PEAK OUTPUT POWER-CONDUCTED	15
A.2.3. MAXIMUM AVERAGE OUTPUT POWER-CONDUCTED	17
A.3. PEAK POWER SPECTRAL DENSITY	19
A.4. OCCUPIED 6dB BANDWIDTH	20
FIG. 1 OCCUPIED 6dB BANDWIDTH (802.11A, CH 149).....	21
FIG. 2 OCCUPIED 6dB BANDWIDTH (802.11A, CH 157).....	21
FIG. 3 OCCUPIED 6dB BANDWIDTH (802.11A, CH 165).....	22
FIG. 4 OCCUPIED 6dB BANDWIDTH (802.11N-HT20, CH 149)	22
FIG. 5 OCCUPIED 6dB BANDWIDTH (802.11N-HT20, CH 157)	23
FIG. 6 OCCUPIED 6dB BANDWIDTH (802.11N-HT20, CH 165)	23
FIG. 7 OCCUPIED 6dB BANDWIDTH (802.11AC-HT20, CH 149).....	24
FIG. 8 OCCUPIED 6dB BANDWIDTH (802.11AC-HT20, CH 157).....	24
FIG. 9 OCCUPIED 6dB BANDWIDTH (802.11AC-HT20, CH 165).....	25
FIG. 10 OCCUPIED 6dB BANDWIDTH (802.11N-HT40, CH 151)	26
FIG. 11 OCCUPIED 6dB BANDWIDTH (802.11N-HT40, CH 159).....	26
FIG. 12 OCCUPIED 6dB BANDWIDTH (802.11AC-HT40, CH 151).....	26
FIG. 13 OCCUPIED 6dB BANDWIDTH (802.11AC-HT40, CH 159).....	27
FIG. 14 OCCUPIED 6dB BANDWIDTH (802.11AC-HT80, CH 155).....	27
A.5. TRANSMITTER SPURIOUS EMISSION	28
A.5.1 TRANSMITTER SPURIOUS EMISSION - CONDUCTED	28
FIG. 15 CONDUCTED SPURIOUS EMISSION (802.11A, CH149, 30 MHZ-1 GHZ).....	30
FIG. 16 CONDUCTED SPURIOUS EMISSION (802.11A, CH149, 1 GHZ -12 GHZ).....	31
FIG. 17 CONDUCTED SPURIOUS EMISSION (802.11A, CH149, 12 GHZ-25 GHZ)	31
FIG. 18 CONDUCTED SPURIOUS EMISSION (802.11A, CH149, 25 GHZ-40 GHZ)	32
FIG. 19 CONDUCTED SPURIOUS EMISSION (802.11A, CH157, 30 MHZ-1 GHZ).....	32
FIG. 20 CONDUCTED SPURIOUS EMISSION (802.11A, CH157, 1 GHZ -12 GHZ).....	33
FIG. 21 CONDUCTED SPURIOUS EMISSION (802.11A, CH157, 12 GHZ-25 GHZ)	33
FIG. 22 CONDUCTED SPURIOUS EMISSION (802.11A, CH157, 25 GHZ-40 GHZ)	34
FIG. 23 CONDUCTED SPURIOUS EMISSION (802.11A, CH165, 30 MHZ-1 GHZ).....	34
FIG. 24 CONDUCTED SPURIOUS EMISSION (802.11A, CH165, 1 GHZ -12 GHZ).....	35
FIG. 25 CONDUCTED SPURIOUS EMISSION (802.11A, CH165, 12 GHZ-25 GHZ)	35
FIG. 26 CONDUCTED SPURIOUS EMISSION (802.11A, CH165, 25 GHZ-40 GHZ)	36
FIG. 27 CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH149, 30 MHZ-1 GHZ)	36
FIG. 28 CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH149, 1 GHZ -12 GHZ).....	37
FIG. 29 CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH149, 12 GHZ-25 GHZ).....	37
FIG. 30 CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH149, 25 GHZ-40 GHZ).....	38
FIG. 31 CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH157, 30 MHZ-1 GHZ)	38
FIG. 32 CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH157, 1 GHZ -12 GHZ).....	39
FIG. 33 CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH157, 12 GHZ-25 GHZ).....	39
FIG. 34 CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH157, 25 GHZ-40 GHZ).....	40
FIG. 35 CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH165, 30 MHZ-1 GHZ)	40
FIG. 36 CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH165, 1 GHZ -12 GHZ).....	41
FIG. 37 CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH165, 12 GHZ-25 GHZ).....	41

FIG. 38	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH165, 25 GHz-40 GHz).....	42
FIG. 39	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH149, 30 MHz-1 GHz).....	42
FIG. 40	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH149, 1 GHz -12 GHz).....	43
FIG. 41	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH149, 12 GHz-25 GHz).....	43
FIG. 42	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH149, 25 GHz-40 GHz).....	44
FIG. 43	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH157, 30 MHz-1 GHz).....	44
FIG. 44	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH157, 1 GHz -12 GHz).....	45
FIG. 45	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH157, 12 GHz-25 GHz).....	45
FIG. 46	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH157, 25 GHz-40 GHz).....	46
FIG. 47	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH165, 30 MHz-1 GHz).....	46
FIG. 48	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH165, 1 GHz -12 GHz).....	47
FIG. 49	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH165, 12 GHz-25 GHz).....	47
FIG. 50	CONDUCTED SPURIOUS EMISSION (802.11AC-HT20, CH165, 25 GHz-40 GHz).....	48
FIG. 51	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH151, 30 MHz-1 GHz).....	48
FIG. 52	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH151, 1 GHz -12 GHz).....	49
FIG. 53	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH151, 12 GHz-25 GHz).....	49
FIG. 54	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH151, 25 GHz-40 GHz).....	50
FIG. 55	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH159, 30 MHz-1 GHz).....	50
FIG. 56	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH159, 1 GHz -12 GHz).....	51
FIG. 57	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH159, 12 GHz-25 GHz).....	51
FIG. 58	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH159, 25 GHz-40 GHz).....	52
FIG. 59	CONDUCTED SPURIOUS EMISSION (802.11AC-HT40, CH151, 30 MHz-1 GHz).....	52
FIG. 60	CONDUCTED SPURIOUS EMISSION (802.11AC-HT40, CH151, 1 GHz -12 GHz).....	53
FIG. 61	CONDUCTED SPURIOUS EMISSION (802.11AC-HT40, CH151, 12 GHz-25 GHz).....	53
FIG. 62	CONDUCTED SPURIOUS EMISSION (802.11AC-HT40, CH151, 25 GHz-40 GHz).....	54
FIG. 63	CONDUCTED SPURIOUS EMISSION (802.11AC-HT40, CH159, 30 MHz-1 GHz).....	54
FIG. 64	CONDUCTED SPURIOUS EMISSION (802.11AC-HT40, CH159, 1 GHz -12 GHz).....	55
FIG. 65	CONDUCTED SPURIOUS EMISSION (802.11AC-HT40, CH159, 12 GHz-25 GHz).....	55
FIG. 66	CONDUCTED SPURIOUS EMISSION (802.11AC-HT40, CH159, 25 GHz-40 GHz).....	56
FIG. 67	CONDUCTED SPURIOUS EMISSION (802.11AC-HT80, CH155, 30 MHz-1 GHz).....	56
FIG. 68	CONDUCTED SPURIOUS EMISSION (802.11AC-HT80, CH155, 1 GHz -12 GHz).....	57
FIG. 69	CONDUCTED SPURIOUS EMISSION (802.11AC-HT80, CH155, 12 GHz-25 GHz).....	57
FIG. 70	CONDUCTED SPURIOUS EMISSION (802.11AC-HT80, CH155, 25 GHz-40 GHz).....	58
A.5.2 TRANSMITTER SPURIOUS EMISSION - RADIATED.....		59
A.6. BAND EDGES COMPLIANCE.....		69
A6.1 BAND EDGES - CONDUCTED.....		69
FIG. 71	BAND EDGES (802.11A, 5745MHz).....	70
FIG. 72	BAND EDGES (802.11A, 5825MHz).....	70
FIG. 73	BAND EDGES (802.11N-HT20, 5745MHz).....	71
FIG. 74	BAND EDGES (802.11N-HT20, 5825MHz).....	72
FIG. 75	BAND EDGES (802.11AC-HT20, 5745MHz).....	72
FIG. 76	BAND EDGES (802.11AC-HT20, 5825MHz).....	72
FIG. 77	BAND EDGES (802.11N-HT40, 5755MHz).....	73
FIG. 78	BAND EDGES (802.11N-HT40, 5795MHz).....	73



FIG. 79	BAND EDGES (802.11AC-HT40, 5755MHZ).....	74
FIG. 80	BAND EDGES (802.11AC-HT40, 5795MHZ).....	74
FIG. 81	BAND EDGES (802.11AC-HT80, 5775MHZ).....	75
FIG. 82	BAND EDGES (802.11AC-HT80, 5775MHZ).....	75
A.6.2	BAND EDGES - RADIATED.....	76
FIG. 83	BAND EDGES (802.11A, 5745MHZ)	77
FIG. 84	BAND EDGES (802.11A, 5825MHZ)	77
FIG. 85	BAND EDGES (802.11N-HT20, 5745MHZ).....	78
FIG. 86	BAND EDGES (802.11N-HT20, 5825MHZ).....	78
FIG. 87	BAND EDGES (802.11N-HT40, 5755MHZ).....	79
FIG. 88	BAND EDGES (802.11N-HT40, 5795MHZ).....	79
FIG. 89	BAND EDGES (802.11AC-HT20, 5745MHZ).....	80
FIG. 90	BAND EDGES (802.11AC-HT20, 5825MHZ).....	80
FIG. 91	BAND EDGES (802.11AC-HT40, 5755MHZ).....	81
FIG. 92	BAND EDGES (802.11AC-HT40, 5795MHZ).....	81
FIG. 93	BAND EDGES (802.11AC-HT80, 5775MHZ).....	82
A.7.	AC POWERLINE CONDUCTED EMISSION.....	82
FIG. 94	AC POWERLINE CONDUCTED EMISSION-802.11A	84
FIG. 95	AC POWERLINE CONDUCTED EMISSION-IDLE.....	85
ANNEX B: ACCREDITATION CERTIFICATE.....		86

1. TEST LATORATORY

1.1. Testing Location

Conducted testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China100191

Radiated testing Location: CTTL(BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology
Development Area, Beijing, P. R. China 100176

1.2. TestingEnvironment

Normal Temperature: 15-35°C

Extreme Temperature: -10/+55°C

Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2017-06-29


Testing End Date: 2017-08-24

1.4. Signature




Jiang Xue

(Prepared this test report)



Zheng Wei

(Reviewed this test report)



Lv Songdong

(Approved this test report)



2. CLIENT INFORMATION

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-31363544
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-31363544
Fax: 0086-21-61460602

3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY

EQUIPMENT(AE)

3.1. About EUT

Description	GSM Quad-band/HSPA-UMTS Six-band/LTE 19-band mobile phone
Model name	BBD100-1
FCC ID	2ACCJN019
WLAN Frequency Range	ISM Band: 5725MHz~5825MHz
Type of modulation	OFDM
Voltage	3.8VDC by Battery

Note: Photographs of EUT are shown in ANNEX C of this test report. Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	/	04	AAN966
EUT2	/	04	AAN966

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	/
AE2	Charger	17TCT-CH-0976
AE4	USB Cable	17TCT-DC-0133
AE1		
Model	TLp038B1	
Manufacturer	BYD	
Capacitance	3860 mAh	
Nominal voltage	3.85V	
AE2		
Model	QC10US	
Manufacturer	BYD	
Length of cable	/	
AE4		
Model	CDA0000113CF	
Manufacturer	LUXSHARE	
Length of cable	60cm	

3.4. General Description

The Equipment under Test (EUT) is a model of GSM Quad-band/HSPA-UMTS Six-band/LTE 19-band mobile phone with integrated antenna and inbuilt battery.

It has Bluetooth (EDR) function.

It consists of normal options: travel charger, USB cable and Phone.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

4. REFERENCE DOCUMENTS

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

	FCC CFR 47, Part 15, Subpart C:	
	15.205 Restricted bands of operation;	
FCC Part15	15.209 Radiated emission limits, general requirements;	2016
	15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz.	
ANSI C63.10	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2013

5. LABORATORY ENVIRONMENT

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.407 (a)	/	P
Peak Power Spectral Density	15.407 (a)	/	P
Occupied 6dB Bandwidth	15.247 (a)	/	P
Band Edges Compliance	15.209 (b)	/	P
Transmitter Spurious Emission - Conducted	15.407	/	P
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	/	P
AC Powerline Conducted Emission	15.107, 15.207	/	P
Transmitter Spurious Emission - Radiated < 30MHz	15.247, 15.209	/	P

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

CTTL has evaluated the test cases requested by the client/manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.1.

This report only deals with the WLAN function among the features described in section 3.

This model is a variant product which market name is BBD100-2; and all the test results have been tested from BBD100-2.

6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26°C
Voltage	3.8V
Humidity	44%

7. TEST EQUIPMENTS UTILIZED

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	2017-06-02	2018-06-01
2	LISN	ENV216	101200	Rohde & Schwarz	2017-08-04	2018-08-03
3	Test Receiver	ESCI	100344	Rohde & Schwarz	2017-03-16	2018-03-15
4	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESCI 7	100948	Rohde & Schwarz	2017-07-26	2018-07-25
3	BiLog Antenna	VULB9163	235	Schwarzbeck	2016-05-09	2019-05-10
4	Dual-Ridge Waveguide Horn Antenna	3115	6914	EMCO	2014-12-16	2017-12-15
5	Vector Signal Analyzer	FSV	101047	Rohde & Schwarz	2017-07-23	2018-07-22

8. Measurement Uncertainty

8.1. Transmitter Output Power

Measurement Uncertainty: 0.339dB,k=1.96

8.2. Peak Power Spectral Density

Measurement Uncertainty: 0.705dBm/MHz,k=1.96

8.3. Occupied 6dB Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

8.4. Band Edges Compliance

Measurement Uncertainty : 0.62dBm,k=1.96

8.5. Spurious Emissions

Conducted (k=1.96)

Frequency Range	Uncertainty(dBm)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

Radiated (k=2)

Frequency Range	Uncertainty(dBm)
$30\text{MHz} \leq f \leq 1\text{GHz}$	4.86
$1\text{GHz} \leq f \leq 18\text{GHz}$	5.26
$18\text{GHz} \leq f \leq 40\text{GHz}$	5.28

8.6. AC Power-line Conducted Emission


Measurement Uncertainty : 3.2dBm,k=2

ANNEX A: MEASUREMENT RESULTS

A.1. Measurement Method

A.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer




A.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



The measurement is made according to ANSI C63.10.

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

A.2. Maximum Peak Output Power

Measurement Limit and Method:

Standard	Limit (dBm)
FCC CRF Part 15.407(a)	< 30

A.2.1 Antenna Gain

Antenna gain is -0.5 dBi and the value is supplied by the applicant or manufacturer.

A.2.2. Maximum Peak Output Power-conducted

Measurement Results:

802.11a mode

Mode	Data Rate (Mbps)	Test Result (dBm)		
		5745MHz (Ch149)	5785MHz (Ch157)	5825MHz (Ch165)
802.11a	6	20.19	/	/
	9	20.23	/	/
	12	19.98	/	/
	18	20.02	/	/
	24	20.54	/	/
	36	20.44	/	/
	48	20.58	/	/
	54	20.63	21.17	20.27

The data rate 54Mbps is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT20 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		5745MHz (Ch149)	5785MHz (Ch157)	5825MHz (Ch165)
802.11n (20MHz)	MCS0	19.25	/	/
	MCS1	19.09	/	/
	MCS2	19.06	/	/
	MCS3	19.56	/	/
	MCS4	19.58	/	/
	MCS5	19.64	/	/
	MCS6	19.62	/	/
	MCS7	19.65	20.18	19.28

The data rate MCS7 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT20 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		5745MHz (Ch149)	5785MHz (Ch157)	5825MHz (Ch165)
802.11ac (20MHz)	MCS0	18.14	18.76	17.84
	MCS1	17.85	/	/
	MCS2	17.73	/	/
	MCS3	17.92	/	/
	MCS4	16.81	/	/
	MCS5	16.92	/	/
	MCS6	16.73	/	/
	MCS7	15.41	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT40 mode

Mode	Data Rate (Index)	Test Result (dBm)	
		5755MHz (Ch151)	5795MHz (Ch159)
802.11n (40MHz)	MCS0	18.54	/
	MCS1	19.41	/
	MCS2	19.38	/
	MCS3	19.83	/
	MCS4	19.81	/
	MCS5	19.88	22.36
	MCS6	19.85	/
	MCS7	19.82	/

The data rate MCS5 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT40 mode

Mode	Data Rate (Index)	Test Result (dBm)	
		5755MHz (Ch151)	5795MHz (Ch159)
802.11ac (40MHz)	MCS0	17.27	/
	MCS1	17.17	/
	MCS2	17.84	/
	MCS3	18.23	19.77
	MCS4	18.19	/
	MCS5	17.77	/
	MCS6	16.95	/
	MCS7	15.61	/

The data rate MCS3 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT80 mode

Mode	Data Rate (Index)	Test Result (dBm)
		5775MHz (Ch155)
802.11ac (80MHz)	MCS0	17.21
	MCS1	16.71
	MCS2	17.83
	MCS3	18.04
	MCS4	17.94
	MCS5	17.88
	MCS6	16.62
	MCS7	15.58

The data rate MCS3 is selected as worse condition, and the following cases are performed with this condition.

Conclusion: PASS

A.2.3. Maximum Average Output Power-Conducted

Method of Measurement: See ANSI C63.10-clause 12.3.2.2 Method SA-1

802.11a mode

Mode	Test Result (dBm)		
	5745MHz (Ch149)	5785MHz (Ch157)	5825MHz (Ch165)
802.11a	11.70	12.12	11.22

802.11n-HT20 mode

Mode	Test Result (dBm)		
	5745MHz (Ch149)	5785MHz (Ch157)	5825MHz(Ch165)
802.11n(20MHz)	10.78	11.15	10.27

802.11ac-HT20 mode

Mode	Test Result (dBm)		
	5745MHz (Ch149)	5785MHz (Ch157)	5825MHz(Ch165)
802.11ac(20MHz)	9.19	9.58	8.69

802.11n-HT40 mode

Mode	Test Result (dBm)	
	5755MHz (Ch151)	5795MHz(Ch159)
802.11n(40MHz)	10.39	12.91



802.11ac-HT40 mode

Mode	Test Result (dBm)	
	5755MHz (Ch151)	5795MHz(Ch159)
802.11ac(40MHz)	7.56	10.12

802.11ac-HT80 mode

Mode	Test Result (dBm)
	5775MHz (Ch155)
802.11ac(80MHz)	6.61

Conclusion: PASS

A.3. Peak Power Spectral Density

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407(a)	< 30 dBm/500 kHz

The measurement is made according to ANSI C63.10 and KDB789033 D02

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

Measurement Results:

Mode	Channel	Power Spectral Density (dBm/500kHz)	Conclusion
802.11a	149	10.16	P
	157	9.85	P
	165	9.18	P
802.11n HT20	149	7.17	P
	157	7.56	P
	165	7.00	P
802.11ac HT20	149	5.91	P
	157	5.69	P
	165	5.30	P
802.11n HT40	151	3.85	P
	159	6.20	P
802.11ac HT40	151	1.35	P
	159	3.91	P
802.11ac HT80	155	-1.19	P

Conclusion: PASS

A.4. Occupied 6dB Bandwidth

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500

The measurement is made according to KDB789033 D02 .

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------

Measurement Result:

Mode	Channel	Occupied 6dB Bandwidth (MHz)		conclusion
		Fig.	Value	
802.11a	149	Fig.1	16.60	P
	157	Fig.2	16.60	P
	165	Fig.3	16.55	P
802.11n HT20	149	Fig.4	17.85	P
	157	Fig.5	17.80	P
	165	Fig.6	15.65	P
802.11ac HT20	149	Fig.7	6.10	P
	157	Fig.8	6.80	P
	165	Fig.9	1.12	P

802.11n HT40	151	Fig.10	33.44	P
	159	Fig.11	34.08	P
802.11ac HT40	151	Fig.12	3.76	P
	159	Fig.13	4.72	P

802.11ac HT80	155	Fig.14	2.08	P
---------------	-----	--------	------	---

Conclusion: PASS

Test graphs as below:




Fig. 1 Occupied 6dB Bandwidth (802.11a, Ch 149)




Fig. 2 Occupied 6dB Bandwidth (802.11a, Ch 157)




Fig. 3 Occupied 6dB Bandwidth (802.11a, Ch 165)




Fig. 4 Occupied 6dB Bandwidth (802.11n-HT20, Ch 149)




Fig. 5 Occupied 6dB Bandwidth (802.11n-HT20, Ch 157)




Fig. 6 Occupied 6dB Bandwidth (802.11n-HT20, Ch 165)




Fig. 7 Occupied 6dB Bandwidth (802.11ac-HT20, Ch 149)





Fig. 8 Occupied 6dB Bandwidth (802.11ac-HT20, Ch 157)



Date: 22.AUG.2017 10:32:14

Fig. 9 Occupied 6dB Bandwidth (802.11ac-HT20, Ch 165)




Fig. 10 Occupied 6dB Bandwidth (802.11n-HT40, Ch 151)




Fig. 11 Occupied 6dB Bandwidth (802.11n-HT40, Ch 159)




Fig. 12 Occupied 6dB Bandwidth (802.11ac-HT40, Ch 151)




Fig. 13 Occupied 6dB Bandwidth (802.11ac-HT40, Ch 159)




Fig. 14 Occupied 6dB Bandwidth (802.11ac-HT80, Ch 155)

A.5. Transmitter Spurious Emission

Measurement Limit:

Standard	Frequency (MHz)	Limit (dBm/MHz)
FCC 47 CFR Part 15.407	5725MHz~5850MHz	< -27

The measurement is made according to ANSI C63.10 .

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Measurement Uncertainty:

Frequency Range	Uncertainty(dB)
30MHz ≤ f ≤ 2GHz	0.63
2GHz ≤ f ≤3.6GHz	0.82
3.6GHz ≤ f ≤8GHz	1.55
8GHz ≤ f ≤20GHz	1.86
20GHz ≤ f ≤22GHz	1.90
22GHz ≤ f ≤26GHz	2.20

A.5.1 Transmitter Spurious Emission - Conducted

Measurement Results:

802.11a mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11a	149	30 MHz ~ 1 GHz	Fig.15	P
		1 GHz ~ 12 GHz	Fig.16	P
		12 GHz ~ 25 GHz	Fig.17	P
		25 GHz ~ 40 GHz	Fig.18	P
	157	30 MHz ~ 1 GHz	Fig.19	P
		1 GHz ~ 12 GHz	Fig.20	P
		12 GHz ~ 25 GHz	Fig.21	P
		25 GHz ~ 40 GHz	Fig.22	P
	165	30 MHz ~ 1 GHz	Fig.23	P
		1 GHz ~ 12 GHz	Fig.24	P
		12 GHz ~ 25 GHz	Fig.25	P
		25 GHz ~ 40 GHz	Fig.26	P

802.11n-HT20 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n HT20	149	30 MHz ~ 1 GHz	Fig.27	P
		1 GHz ~ 12 GHz	Fig.28	P
		12 GHz ~ 25 GHz	Fig.29	P
		25 GHz ~ 40 GHz	Fig.30	P
	157	30 MHz ~ 1 GHz	Fig.31	P
		1 GHz ~ 12 GHz	Fig.32	P
		12 GHz ~ 25 GHz	Fig.33	P
		25 GHz ~ 40 GHz	Fig.34	P
	165	30 MHz ~ 1 GHz	Fig.35	P
		1 GHz ~ 12 GHz	Fig.36	P
		12 GHz ~ 25 GHz	Fig.37	P
		25 GHz ~ 40 GHz	Fig.38	P

802.11ac-HT20 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11ac HT20	149	30 MHz ~ 1 GHz	Fig.39	P
		1 GHz ~ 12 GHz	Fig.40	P
		12 GHz ~ 25 GHz	Fig.41	P
		25 GHz ~ 40 GHz	Fig.42	P
	157	30 MHz ~ 1 GHz	Fig.43	P
		1 GHz ~ 12 GHz	Fig.44	P
		12 GHz ~ 25 GHz	Fig.45	P
		25 GHz ~ 40 GHz	Fig.46	P
	165	30 MHz ~ 1 GHz	Fig.47	P
		1 GHz ~ 12 GHz	Fig.48	P
		12 GHz ~ 25 GHz	Fig.49	P
		25 GHz ~ 40 GHz	Fig.50	P

802.11n-HT40 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n HT40	151	30 MHz ~ 1 GHz	Fig.51	P
		1 GHz ~ 12 GHz	Fig.52	P
		12 GHz ~ 25 GHz	Fig.53	P
		25 GHz ~ 40 GHz	Fig.54	P
	159	30 MHz ~ 1 GHz	Fig.55	P
		1 GHz ~ 12 GHz	Fig.56	P
		12 GHz ~ 25 GHz	Fig.57	P
		25 GHz ~ 40 GHz	Fig.58	P

802.11ac-HT40 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11ac HT40	151	30 MHz ~ 1 GHz	Fig.59	P
		1 GHz ~ 12 GHz	Fig.60	P
		12 GHz ~ 25 GHz	Fig.61	P
		25 GHz ~ 40 GHz	Fig.62	P
	159	30 MHz ~ 1 GHz	Fig.63	P
		1 GHz ~ 12 GHz	Fig.64	P
		12 GHz ~ 25 GHz	Fig.65	P
		25 GHz ~ 40 GHz	Fig.66	P

802.11ac-HT80 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11ac HT80	155	30 MHz ~ 1 GHz	Fig.67	P
		1 GHz ~ 12 GHz	Fig.68	P
		12 GHz ~ 25 GHz	Fig.69	P
		25 GHz ~ 40 GHz	Fig.70	P

Conclusion: PASS

Test graphs as below:




Fig. 15 Conducted Spurious Emission (802.11a, Ch149, 30 MHz-1 GHz)




Fig. 16 Conducted Spurious Emission (802.11a, Ch149, 1 GHz -12 GHz)




Fig. 17 Conducted Spurious Emission (802.11a, Ch149, 12 GHz-25 GHz)




Fig. 18 Conducted Spurious Emission (802.11a, Ch149, 25 GHz-40 GHz)




Fig. 19 Conducted Spurious Emission (802.11a, Ch157, 30 MHz-1 GHz)




Fig. 20 Conducted Spurious Emission (802.11a, Ch157, 1 GHz -12 GHz)




Fig. 21 Conducted Spurious Emission (802.11a, Ch157, 12 GHz-25 GHz)




Fig. 22 Conducted Spurious Emission (802.11a, Ch157, 25 GHz-40 GHz)




Fig. 23 Conducted Spurious Emission (802.11a, Ch165, 30 MHz-1 GHz)




Fig. 24 Conducted Spurious Emission (802.11a, Ch165, 1 GHz -12 GHz)




Fig. 25 Conducted Spurious Emission (802.11a, Ch165, 12 GHz-25 GHz)




Fig. 26 Conducted Spurious Emission (802.11a, Ch165, 25 GHz-40 GHz)




Fig. 27 Conducted Spurious Emission (802.11n-HT20, Ch149, 30 MHz-1 GHz)




Fig. 28 Conducted Spurious Emission (802.11n-HT20, Ch149, 1 GHz -12 GHz)




Fig. 29 Conducted Spurious Emission (802.11n-HT20, Ch149, 12 GHz-25 GHz)




Fig. 30 Conducted Spurious Emission (802.11n-HT20, Ch149, 25 GHz-40 GHz)




Fig. 31 Conducted Spurious Emission (802.11n-HT20, Ch157, 30 MHz-1 GHz)




Fig. 32 Conducted Spurious Emission (802.11n-HT20, Ch157, 1 GHz -12 GHz)




Fig. 33 Conducted Spurious Emission (802.11n-HT20, Ch157, 12 GHz-25 GHz)




Fig. 34 Conducted Spurious Emission (802.11n-HT20, Ch157, 25 GHz-40 GHz)




Fig. 35 Conducted Spurious Emission (802.11n-HT20, Ch165, 30 MHz-1 GHz)




Fig. 36 Conducted Spurious Emission (802.11n-HT20, Ch165, 1 GHz -12 GHz)




Fig. 37 Conducted Spurious Emission (802.11n-HT20, Ch165, 12 GHz-25 GHz)




Fig. 38 Conducted Spurious Emission (802.11n-HT20, Ch165, 25 GHz-40 GHz)




Fig. 39 Conducted Spurious Emission (802.11ac-HT20, Ch149, 30 MHz-1 GHz)




Fig. 40 Conducted Spurious Emission (802.11ac-HT20, Ch149, 1 GHz -12 GHz)




Fig. 41 Conducted Spurious Emission (802.11ac-HT20, Ch149, 12 GHz-25 GHz)