



TEST REPORT

No. I19Z60613-EMC03

for

HSUPA/HSDPA/UMTS Tri Band/GSM Quad Band/CDMA Tri Band/LTE

9 Band Mobile Phone

4052W, 4052Z

FCC ID: 2ACCJN032

Hardware Version: 04

Software Version: YWX9

Issued Date: 2019-06-28



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



REPORT HISTORY

| Report Number | Revision | Description | Issue Date |
|----------------------|-----------------|--------------------|-------------------|
| I19Z60613-EMC03 | Rev.0 | 1st edition | 2019-06-18 |
| I19Z60613-EMC03 | Rev.1 | 2nd edition | 2019-06-28 |



CONTENTS

| | |
|---|-----------|
| 1. TEST LABORATORY..... | 4 |
| 1.1. TESTING LOCATION | 4 |
| 1.2. TESTING ENVIRONMENT | 4 |
| 1.3. PROJECT DATA..... | 4 |
| 1.4. SIGNATURE | 4 |
| 2. CLIENT INFORMATION..... | 5 |
| 2.1. APPLICANT INFORMATION..... | 5 |
| 2.2. MANUFACTURER INFORMATION..... | 5 |
| 3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) | 6 |
| 3.1. ABOUT EUT | 6 |
| 3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST | 6 |
| 3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST..... | 6 |
| 3.4. GENERAL DESCRIPTION | 7 |
| 3.5. EUT SET-UPS | 7 |
| 4. REFERENCE DOCUMENTS | 8 |
| 4.1. REFERENCE DOCUMENTS FOR TESTING..... | 8 |
| 5. LABORATORY ENVIRONMENT | 9 |
| 6. SUMMARY OF TEST RESULTS..... | 10 |
| 6.1. SUMMARY OF TEST RESULTS | 10 |
| 6.2. STATEMENTS | 10 |
| 7. TEST EQUIPMENTS UTILIZED..... | 11 |
| TEST SOFTWARE UTILIZED | 11 |
| ANNEX A: MEASUREMENT RESULTS | 12 |
| A.1 OUTPUT POWER..... | 12 |
| A.2 TRANSMITTER UNWANTED EMISSIONS..... | 15 |
| ANNEX B: PERSONS INVOLVED IN THIS TESTING..... | 18 |

1. Test Laboratory

1.1. Testing Location

Location 1: CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China 100191


1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2019-05-27
Testing End Date: 2019-06-03


1.4. Signature



Wang Junqing
(Prepared this test report)



Zhang Ying
(Reviewed this test report)



Liu Baodian
Deputy Director of the laboratory
(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address: 7/F, Block F4, TCL International E City, Zhong Shan Yuan Road,
Nanshan District, Shenzhen, Guangdong, P.R. China 518052
City: Shenzhen
Postal Code: 518052
Country: China
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@tcl.com
Telephone: 0086-755-36611722
Fax: 0086-755-36612000-81722

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address: 7/F, Block F4, TCL Communication Technology Building, TCL
International E City, Zhong Shan Yuan Road, Nanshan District,
Shenzhen, Guangdong, P.R. China 518052
City: Shenzhen
Postal Code: 518052
Country: China
Telephone: 0086-755-36611722
Fax: 0086-75536612000-81722



3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

| | |
|---------------------|---|
| Description | HSUPA/HSDPA/UMTS Tri Band/GSM Quad Band/CDMA Tri Band/LTE 9 Band Mobile Phone |
| Antenna | Internal |
| Power supply | Battery |
| Extreme vol. Limits | 3.5VDC to 4.2VDC (nominal: 3.7VDC) |

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, CAICT.

3.2. Internal Identification of EUT used during the test

| EUT ID* | IMEI | HW Version | SW Version |
|----------------|-----------------|-------------------|-------------------|
| EUT4 | 015490000004669 | 04 | YWX9 |

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

| AE ID* | Description | SN | Note |
|---------------|--------------------|-----------|-------------|
| AE1 | battery | / | / |

AE1

| | |
|-----------------|--------------|
| Type | TLi013C1 |
| Model | CAB1350001C1 |
| Manufacturer | BYD |
| Capacitance | 1350mAh |
| Nominal voltage | 3.7V |

*AE ID: is used to identify the test sample in the lab internally.



3.4. General Description

Equipment Under Test (EUT) is a model of smart phone with integrated antenna.

It supports GSM 900/1800/850/1900MHz, WCDMA Bands 2/4/5, CDMA Class 0, CDMA Class 1 and CDMA Class 10 with 1X RTT and EvDo, LTE Bands 2/4/5/12/25/26/41/66/71.

It has MP3, Camera, FM, USB memory, Bluetooth (EDR and BLE), Wi-Fi (802.11b/g/n) and GNSS functions.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

3.5. EUT set-ups

| EUT Set-up No. | Combination of EUT and AE | Remarks |
|-----------------------|----------------------------------|--------------------|
| Set.10 | EUT4 + AE1 | ERP/EIRP/RSE tests |



4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

| Reference | Title | Version |
|------------------|--|--------------------|
| FCC Part 90 | PRIVATE LAND MOBILE RADIO SERVICES | 10-1-15 Edition |
| ANSI/TIA-603-E | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards | 2016 |
| ANSI C63.4 | Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz | 2014 |
| KDB 971168 D01 | Measurement Guidance for Certification of Licensed Digital Transmitters | v02r02 |

5. LABORATORY ENVIRONMENT

Fully-anechoic chamber FAC-3 (9 meters×6.5 meters×4 meters) did not exceed following limits along the EMC testing:

| | |
|---|---|
| Temperature | Min. = 15 °C, Max. = 35 °C |
| Relative humidity | Min. = 15 %, Max. = 75 % |
| Shielding effectiveness | 0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB. |
| Electrical insulation | > 2 MΩ |
| Ground system resistance | < 4 Ω |
| Site voltage standing-wave ratio (S_{VSWR}) | Between 0 and 6 dB, from 1GHz to 18GHz |
| Uniformity of field strength | Between 0 and 6 dB, from 80 to 4000 MHz |



6. SUMMARY OF TEST RESULTS

6.1. Summary of test results

| Abbreviations used in this clause: | | |
|------------------------------------|----|--|
| Verdict Column | P | Pass |
| | F | Fail |
| | NA | Not applicable |
| | NM | Not measured |
| Location Column | 1 | The test is performed in test location which are described in section 1.1 of this report |

CDMA800 BC10

| Items | Test Name | Clause in FCC rules | Section in this report | Verdict | Test Location |
|-------|----------------|---------------------|------------------------|---------|---------------|
| 1 | Output Power | 90.635(b) | 5.4 | A.1 | 2 |
| 2 | Emission Limit | 90.210, 90.691 | 5.5 | A.2 | 2 |

6.2. Statements

The test cases listed in section 6.1 of this report for the EUT specified in section 3 were performed according to the standards or reference documents in section 4.1

The EUT met all applicable requirements of the standards or reference documents in section 4.1.

This report only deals with the CDMA functions among the features described in section 3.



7. Test Equipments Utilized

| NO. | NAME | TYPE | PRODUCER | SERIES NUMBER | CAL. DUE DATE | CAL. INTERVAL |
|-----|--------------------------------------|-----------|--------------|---------------|---------------|---------------|
| 1. | EMI Antenna | VULB 9163 | Schwarzbeck | 9163-235 | 2019-11-20 | 1 Year |
| 2. | EMI Antenna | 3117 | ETS-Lindgren | 00119024 | 2020-01-21 | 3 Years |
| 3. | EMI Antenna | 3117 | ETS-Lindgren | 00058889 | 2021-01-12 | 3 Years |
| 4. | Signal Generator | N5183A | Agilent | MY49060052 | 2020-03-31 | 1 Year |
| 5. | Spectrum Analyzer | E4440A | Agilent | MY48250642 | 2020-03-31 | 1 Year |
| 6. | Universal Radio Communication Tester | E5515C | Agilent | MY48363198 | 2019-06-22 | 1 Year |
| 7. | Universal Radio Communication Tester | CMW500 | R&S | 143008 | 2019-11-26 | 1 Year |

Test Software Utilized

| Test Item | Test Software and Version | Software Vendor |
|--------------|---------------------------|-----------------|
| ERP/EIRP/RSE | Tile V7.2.3.5 | ETS-Lindgren |

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

Reference

FCC: CFR Part 90.635, and 2.1053

A.1.1 Summary

During the process of testing, the EUT was controlled via Agilent Universal Radio Communication Tester (E5515C) to ensure max power transmission and proper modulation.

This result contains peak output power and ERP/EIRP measurements for the EUT.

In all cases, output power is within the specified limits.

A.1.2 Radiated

A.1.2.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 22.913(a)(2) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Rule Part 24.232 specifies, "Mobile/portable stations are limited to 2 watts EIRP. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."


A.1.2.2 Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with AV detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the amplifier and the substitution antenna. The cable loss (P_{cl}), the substitution antenna Gain (G_a) and the amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (Unit dBi) and known input power.
 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15$.
- For test layout photo, please refer to Pic.1 in Annex B.

CDMA800(BC10)- ERP

Limits

| Band | Average ERP (dBm) |
|---------------|-------------------|
| CDMA800(BC10) | ≤50dBm (100W) |

Measurement result

1x RTT

| Frequency (MHz) | P_{Mea} (dBm) | P_{cl} (dB) | P_{Ag} (dB) | G_a (dBi) | Correction (dB) | Peak ERP(dBm) | Polarization |
|-----------------|-----------------|---------------|---------------|-------------|-----------------|---------------|--------------|
| 817.90 | -20.91 | 2.18 | 45.87 | 1.03 | 2.15 | 21.66 | Horizontal |
| 823.10 | -19.02 | 2.24 | 45.80 | 0.10 | 2.15 | 22.49 | Horizontal |

Sample calculation: 823.10MHz

$$\begin{aligned} \text{Peak ERP (dBm)} &= P_{Mea} (-19.02\text{dBm}) - G_a (-0.10\text{dBi}) - P_{Ag} (-45.80 \text{ dB}) - P_{cl} (2.24 \text{ dB}) - 2.15\text{dBm} \\ &= 22.49 \text{ dBm} \end{aligned}$$



Ev-Do

| Frequency (MHz) | P _{Mea} (dBm) | P _{cl} (dB) | P _{Ag} (dB) | G _a (dBi) | Correction (dB) | Peak ERP(dBm) | Polarization |
|-----------------|------------------------|----------------------|----------------------|----------------------|-----------------|---------------|--------------|
| 817.90 | -20.92 | 2.18 | 45.87 | 1.03 | 2.15 | 21.65 | Horizontal |
| 823.10 | -18.98 | 2.24 | 45.80 | 0.10 | 2.15 | 22.53 | Horizontal |

Sample calculation: 823.10Hz

$$\begin{aligned} \text{Peak ERP (dBm)} &= P_{\text{Mea}}(-18.98\text{dBm}) - G_a(-0.10\text{ dBi}) - P_{\text{Ag}}(-45.80\text{ dB}) - P_{\text{cl}}(2.24\text{ dB}) - 2.15\text{dBm} \\ &= 22.53\text{ dBm} \end{aligned}$$

ANALYZER SETTINGS: RBW = VBW = 5MHz

Note: Expanded measurement uncertainty for CDMA800 (BC10) is U = 3.63dB, k = 2.

A.2 Transmitter Unwanted Emissions

Reference

FCC: 47 CFR 90.210 and 90.691


A.2.1 Measurement Method

The measurements procedures in TIA-603E-2016 are used. This measurement is carried out in fully-anechoic chamber 3.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set 1MHz as outlined in Part 22.917(a) and 24.238(a). The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of CDMA800 and CDMA 1900.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with AV detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.





In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

An amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{Mea} - P_{pl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit: dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dB}$.

A.2.2 Measurement Limit

CFR Part 90.210 For transmitters that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

(1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 10 kHz, but no more than 250 percent of the authorized bandwidth: At least $116 \log (f_d/6.1)$ dB, or $50 + 10 \log (P)$ dB, or 70 dB, whichever is the lesser attenuation;

(2) On any frequency removed from the center of the authorized bandwidth by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log (P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $50 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -20 dBm.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper and lower carrier frequencies of the CDMA BC10 (817.9MHz and 823.1MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the CDMA BC0, CDMA BC1 or CDMA BC10 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.



The worst cases:

CDMA BC10, Channel 475/817.9MHz

| Frequency (MHz) | P _{Mea} (dBm) | Path Loss(dB) | Antenna Gain(dBi) | Correction (dB) | Peak ERP(dBm) | Limit (dBm) | Polarization |
|-----------------|------------------------|---------------|-------------------|-----------------|---------------|-------------|--------------|
| 1632.01 | -42.33 | 3.55 | 5.26 | 2.15 | -42.77 | -20 | H |
| 2454.00 | -53.04 | 4.58 | 5.96 | 2.15 | -53.81 | -20 | V |
| 3270.02 | -55.20 | 5.28 | 7.65 | 2.15 | -54.98 | -20 | V |
| 4093.02 | -55.43 | 6.04 | 8.99 | 2.15 | -54.63 | -20 | V |
| 4907.01 | -55.97 | 6.73 | 9.81 | 2.15 | -55.04 | -20 | H |
| 5722.01 | -54.50 | 7.30 | 10.56 | 2.15 | -53.39 | -20 | V |

CDMA BC10, Channel 684/823.1MHz

| Frequency (MHz) | P _{Mea} (dBm) | Path Loss(dB) | Antenna Gain(dBi) | Correction (dB) | Peak ERP(dBm) | Limit (dBm) | Polarization |
|-----------------|------------------------|---------------|-------------------|-----------------|---------------|-------------|--------------|
| 1646.01 | -54.11 | 3.56 | 5.24 | 2.15 | -54.58 | -20 | H |
| 2468.00 | -52.61 | 4.59 | 6.00 | 2.15 | -53.35 | -20 | V |
| 3297.02 | -56.01 | 5.29 | 7.71 | 2.15 | -55.74 | -20 | H |
| 4117.02 | -56.76 | 6.04 | 9.02 | 2.15 | -55.93 | -20 | H |
| 4935.01 | -56.29 | 6.72 | 9.84 | 2.15 | -55.32 | -20 | H |
| 5757.01 | -53.59 | 7.25 | 10.55 | 2.15 | -52.44 | -20 | V |

Sample calculation: 1646.01MHz

$$\begin{aligned} \text{Peak ERP (dBm)} &= P_{\text{Mea}}(-54.11 \text{ dBm}) - P_{\text{cl}}(3.56\text{dB}) - G_{\text{a}}(-5.24 \text{ dBi}) - 2.15\text{dBm} \\ &= -54.58 \text{ dBm} \end{aligned}$$

Note: Expanded measurement uncertainty for this test item is U = 4.92 dB, k = 2.



ANNEX B: Persons involved in this testing

| Test Item | Tester |
|-------------------------------|--------------|
| Output Power | Chen Tianwei |
| Transmitter Spurious Emission | Chen Tianwei |

END OF REPORT