



**FCC PART 15C
TEST REPORT
No.I19Z61261-IOT03**

for

TCL Communication Ltd.

HSUPA/HSDPA/UMTS Bi-Bands/GSM Quad-Bands/LTE 7

Bands/CDMA Tri-bands mobile phone

4053S

With

FCC ID: 2ACCJN033

Hardware Version: 05

Software Version: 1A38

Issued Date: 2019-10-12



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



REPORT HISTORY

Report Number	Revision	Description	Issue Date
I19Z61261-IOT03	Rev.0	1st edition	2019-10-12

CONTENTS

CONTENTS	3
1. TEST LATORATORY	5
1.1. INTRODUCTION & ACCREDITATION	5
1.2. TESTING LOCATION	5
1.3. TESTING ENVIRONMENT.....	5
1.4. PROJECT DATA	5
1.5. SIGNATURE	5
2. CLIENT INFORMATION.....	6
2.1 APPLICANT INFORMATION	6
2.2 MANUFACTURER INFORMATION	6
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARYEQUIPMENT(AE)	7
3.1. ABOUT EUT	7
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	7
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	7
3.4. GENERAL DESCRIPTION.....	8
3.5. INTERPRETATION OF THE TEST ENVIRONMENT.....	8
4. REFERENCE DOCUMENTS	8
4.1. DOCUMENTS SUPPLIED BY APPLICANT	8
4.2. REFERENCE DOCUMENTS FOR TESTING.....	8
5. LABORATORY ENVIRONMENT	8
6. SUMMARY OF TEST RESULTS	9
6.1. SUMMARY OF TEST RESULTS.....	9
6.2. STATEMENTS.....	9
6.3. TEST CONDITIONS	9
7. TEST EQUIPMENTS UTILIZED	10
8. MEASUREMENT UNCERTAINTY	11
8.1 TRANSMITTER OUTPUT POWER	11
8.2 PEAK POWER SPECTRAL DENSITY	11
8.3 OCCUPIED CHANNEL BANDWIDTH.....	11
8.4 BAND EDGES COMPLIANCE	11
8.5 SPURIOUS EMISSIONS	11
ANNEX A: MEASUREMENT RESULTS.....	12
A.1. MEASUREMENT METHOD	12
A.2. MAXIMUM OUTPUT POWER	13
A.3. PEAK POWER SPECTRAL DENSITY (CONDUCTED).....	14
A.4. OCCUPIED 26DB BANDWIDTH(CONDUCTED).....	15



A.5. BAND EDGES COMPLIANCE 20
A.5.1 BAND EDGES - RADIATED..... 20
FIG.9 BAND EDGES (802.11A, 5180MHZ) 20
FIG.10 BAND EDGES (802.11A, 5240MHZ) 21
FIG.11 BAND EDGES (802.11N-HT20, 5180MHZ)..... 21
FIG.12 BAND EDGES (802.11N-HT20, 5240MHZ)..... 22
FIG.13 BAND EDGES (802.11N-HT40, 5190MHZ)..... 22
FIG.14 BAND EDGES (802.11N-HT40, 5230MHZ)..... 23
A.6. TRANSMITTER SPURIOUS EMISSION 24
A.7. AC POWERLINE CONDUCTED EMISSION (150KHZ- 30MHZ)..... 29
FIG. 15 CONDUCTED EMISSION(802.11A, CH40, TX)..... 30
FIG. 16 CONDUCTED EMISSION(802.11A, IDLE)..... 31
FIG. 17 CONDUCTED EMISSION(802.11A, IDLE)..... 32
A.8. 99% OCCUPIED BANDWIDTH 33
A.9. FREQUENCY STABILITY 38
A.10. POWER CONTROL 38
ANNEX B: ACCREDITATION CERTIFICATE..... 39

1. TEST LATORATORY

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Conducted testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China100191

Radiated testing Location: CTTL(BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology
Development Area, Beijing, P. R. China 100176

Radiated testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China100191

1.3. Testing Environment

Normal Temperature: 15-35℃

Relative Humidity: 20-75%

1.4. Project data


Testing Start Date: 2019-07-24

Testing End Date: 2019-09-16


1.5. Signature



Xie Fangfang
(Prepared this test report)



Zheng Wei
(Reviewed this test report)



Hu Xiaoyu
(Approved this test report)



2. CLIENT INFORMATION

2.1 Applicant Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Telephone: 0086-755-36611722
Fax: 0086-755-36612000-81722

2.2 Manufacturer Information

Company Name: TCL Communication Ltd.
Address: 75/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Telephone: 0086-755-36611722
Fax: 0086-755-36612000-81722

3. EQUIPMENT UNDER TEST (EUT) AND

ANCILLARY EQUIPMENT(AE)

3.1. About EUT

Description	HSUPA/HSDPA/UMTS Bi-Bands/GSM Quad-Bands/LTE 7 Bands/CDMA Tri-bands mobile phone
Model name	4053S
FCC ID	2ACCJN033
WLAN Frequency Range	ISM Bands: -5150MHz~5250MHz
Type of modulation	OFDM
Antenna	Integral Antenna
Voltage	3.8V

Note: Photographs of EUT are shown in ANNEX C of this test report. Components list, please refer to documents of the manufacturer.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT34	015501000008516	05	1A38
EUT02	015501000009423	05	1A38

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Type	SN
AE1	Battery	/	/
AE2	Travel charger	/	/
AE3	Travel charger	/	/
AE4	USB Cable	/	/
AE5	USB Cable	/	/

AE1

Model	TLi017C1
Manufacturer	/
Capacitance	1780 mAh
Nominal voltage	3.8V

AE2

Model	UC11US
Manufacturer	PUAN
Length of cable	/

AE3

Model	UC11US
Manufacturer	Chenyang
Length of cable	/

AE4

Model	CDA0000123C1
Manufacturer	Juwei
Length of cable	/
AE5	
Model	CDA0000123C2
Manufacturer	Shenghua
Length of cable	/

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment under Test (EUT) is a model of HSUPA/HSDPA/UMTS Bi-Bands/GSM Quad-Bands/LTE 7 Bands/CDMA Tri-bands mobile phone with integrated antenna and inbuilt battery. It has Bluetooth (EDR)function.

It consists of normal options: travel charger, USB cable.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

3.5. Interpretation of the Test Environment

For the test methods, the test environment uncertainty figures correspond to an expansion factor k=2.

Measurement Uncertainty

Parameter	Uncertainty
temperature	0.48°C
humidity	2 %
DC voltages	0.003V

4. REFERENCE DOCUMENTS

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

FCC Part15	Title 47 of the Code of Federal Regulations; Chapter I Part 15 - Radio frequency devices	2018
ANSI C63.10	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2013
UNII: KDB 789033 D02	General U-NII Test Procedures New Rules v02r01	2017-12

5. LABORATORY ENVIRONMENT

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15E	Sub-clause of IC	Verdict
Maximum Output Power	15.407	/	P
Power Spectral Density	15.407	/	P
Occupied 26dB Bandwidth	15.403	/	P
Band edge compliance	15.209	/	P
Transmitter spurious emissions radiated	15.407	/	P
Spurious emissions radiated < 30 MHz	15.407	/	P
Spurious emissions conducted < 30 MHz	15.407	/	P
Frequency Stability	15.407	/	P
Transmit Power Control	15.407	/	NA

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

CTTL has evaluated the test cases requested by the client/manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.1.

This report only deals with the WLAN function among the features described in section 3.

6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26°C
Voltage	3.8V
Humidity	44%

7. TEST EQUIPMENTS UTILIZED

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	1 year	2020-05-15
2	Test Receiver	ESCI	100766	Rohde & Schwarz	1 year	2020-03-14
3	LISN	ESH2-Z5	829991/012	Rohde & Schwarz	1 year	2020-02-14
4	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100235	Rohde & Schwarz	1 year	2020-02-27
2	BiLog Antenna	VULB9163	1222	Schwarzbeck	1 year	2020-03-14
3	Dual-Ridge Waveguide Horn Antenna	3115	00167250	ETS-Lindgren	1 year	2020-05-14
4	EMI Antenna	3116	2661	ETS-Lindgren	1 year	2020-10-15
5	Spectrum Analyzer	FSV40	101047	Rohde & Schwarz	1 year	2020-05-16

8. Measurement Uncertainty

8.1 Transmitter Output Power

Measurement Uncertainty: 0.387dB,k=1.96

8.2 Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

8.3 Occupied Channel Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

8.4 Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

8.5 Spurious Emissions

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

Radiated (k=2)


Frequency Range	Uncertainty(dB)
9kHz-30MHz	/
$30\text{MHz} \leq f \leq 1\text{GHz}$	5.40
$1\text{GHz} \leq f \leq 18\text{GHz}$	4.32
$18\text{GHz} \leq f \leq 40\text{GHz}$	5.26

ANNEX A: MEASUREMENT RESULTS

A.1. Measurement Method

A.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer




A.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



The measurement is made according to KDB 789033

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

A.2. Maximum output Power

Measurement Limit and Method:

Standard	Frequency (MHz)	Limit (dBm)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	24dBm

Limit use the less value, and B is the 26dB bandwidth.

The measurement method SA-1 is made according to KDB 789033

Measurement Results:

802.11a mode

Mode	Channel	Test Result (dBm)							
		Data Rate (Mbps)							
		6	9	12	18	24	36	48	54
802.11a	5180MHz	15.70	/	/	/	/	/	/	/
	5200MHz	15.89	14.78	13.75	13.72	13.68	13.67	13.62	13.13
	5240MHz	15.67	/	/	/	/	/	/	/

The data rate 6Mbps is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT20 mode

Mode	Channel	Test Result (dBm)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n (HT20)	5180MHz	15.00	13.96	13.91	13.88	13.87	13.84	11.94	10.95
	5200MHz	14.98	/	/	/	/	/	/	/
	5240MHz	14.75	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT40 mode

Mode	Channel	Test Result (dBm)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n (HT40)	5190MHz	13.85	12.91	12.91	12.83	12.79	12.77	11.78	10.77
	5230MHz	13.77	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

A.3. Peak Power Spectral Density (conducted)**Measurement Limit:**

Standard	Frequency (MHz)	Limit (dBm/MHz)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	11

The output power measurement method SA-1 is made according to KDB 789033

Measurement Results:

Mode	Channel	Power Spectral Density (dBm/MHz)	Conclusion
802.11a	5180 MHz	7.25	P
	5200 MHz	6.76	P
	5240 MHz	7.04	P
802.11n HT20	5180 MHz	6.16	P
	5200 MHz	5.81	P
	5240 MHz	5.89	P
802.11n HT40	5190 MHz	2.21	P
	5230 MHz	1.84	P

Conclusion: PASS

A.4. Occupied 26dB Bandwidth(conducted)

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.403 (i)	/

The measurement is made according to KDB 789033

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------

Measurement Result:

Mode	Channel	Occupied 26dB Bandwidth (MHz)		conclusion
		Fig.	Value	
802.11a	5180 MHz	Fig.1	41.65	P
	5200 MHz	Fig.2	39.90	P
	5240 MHz	Fig.3	38.10	P
802.11n HT20	5180 MHz	Fig.4	39.30	P
	5200 MHz	Fig.5	37.80	P
	5240 MHz	Fig.6	39.95	P
802.11n HT40	5190 MHz	Fig.7	60.00	P
	5230 MHz	Fig.8	56.80	P

Conclusion: PASS

Test graphs as below:




Fig.1 Occupied 26dB Bandwidth (802.11a, 5180MHz)




Fig.2 Occupied 26dB Bandwidth (802.11a, 5200MHz)




Fig.3 Occupied 26dB Bandwidth (802.11a, 5240MHz)




Fig.4 Occupied 26dB Bandwidth (802.11n-HT20, 5180MHz)




Fig.5 Occupied 26dB Bandwidth (802.11n-HT20, 5200MHz)




Fig.6 Occupied 26dB Bandwidth (802.11n-HT20, 5240MHz)




Fig.7 Occupied 26dB Bandwidth (802.11n-HT40, 5190MHz)




Fig.8 Occupied 26dB Bandwidth (802.11n-HT40, 5230MHz)

A.5. Band Edges Compliance

A5.1 Band Edges - Radiated

Measurement Limit:

Standard	Limit (dB μ V/m)	
	FCC 47 CFR Part 15.209	Peak
Average		54

The measurement is made according to KDB 789033

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

Measurement Result:

Mode	Channel	Test Results	Conclusion
802.11a	5180 MHz	Fig.9	P
	5240 MHz	Fig.10	P
802.11n HT20	5180 MHz	Fig.11	P
	5240 MHz	Fig.12	P
802.11n HT40	5190 MHz	Fig.13	P
	5230 MHz	Fig.14	P

Conclusion: PASS

Test graphs as below:




Fig.9 Band Edges (802.11a, 5180MHz)




Fig.10 Band Edges (802.11a, 5240MHz)




Fig.11 Band Edges (802.11n-HT20, 5180MHz)




Fig.12 Band Edges (802.11n-HT20, 5240MHz)




Fig.13 Band Edges (802.11n-HT40, 5190MHz)




Fig.14 Band Edges (802.11n-HT40, 5230MHz)

A.6. Transmitter Spurious Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407	-27 dBm/MHz

The measurement is made according to KDB 789033

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(dBμV/m)	Measurement distance(m)
30-88	40.0	3
88-216	43.5	3
216-960	46.0	3
Above 960	54.0	3

Note: for frequency range below 960MHz, the limit in 15.209 is defined in 10m test distance. The limit used above is calculated from 10m to 3m

Measurement uncertainty:

Expanded measurement uncertainty for this test item is $U = 3.9\text{dB}$, $k=2$.

Measurement Results:

Conclusion: PASS

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

$$\text{Result} = P_{Mea} + A_{Rpl} = P_{Mea} + \text{Cable Loss} + \text{Antenna Factor}$$

Average

82.11a

Channel 36

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17980.200	35.40	-5.42	33.80	7.02	H
17989.000	35.40	-5.42	43.40	-2.58	V
17985.700	35.30	-5.42	43.40	-2.68	H
17964.800	35.20	-5.42	43.40	-2.78	H
17996.700	35.20	-5.42	43.40	-2.78	H
51499.050	44.70	-6.54	46.40	4.84	H

Channel 40

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
17993.400	35.80	-5.42	43.40	-2.18	H
17969.200	35.60	-5.42	33.80	7.22	H
17989.000	35.50	-5.42	43.40	-2.48	V
17959.300	35.50	-5.42	43.40	-2.48	H
17885.600	35.40	-5.74	43.40	-2.26	H
17934.000	35.40	-5.42	43.40	-2.58	H

Channel 48

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
5352.420	53.60	-16.58	33.40	36.78	H
17970.300	35.60	-5.42	33.80	7.22	H
17962.600	35.60	-5.42	43.40	-2.38	V
17991.200	35.60	-5.42	43.40	-2.38	H
17961.500	35.60	-5.42	43.40	-2.38	H
17949.400	35.40	-5.42	43.40	-2.58	H

802.11n-HT20

Channel 36

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
5149.980	43.20	-16.61	33.40	26.41	H
17980.200	35.70	-5.42	33.80	7.32	H
17978.000	35.70	-5.42	43.40	-2.28	V
17958.200	35.60	-5.42	43.40	-2.38	H
17967.000	35.60	-5.42	43.40	-2.38	H
17987.900	35.50	-5.42	43.40	-2.48	H

Channel 40

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
17980.200	35.80	-5.42	43.40	-2.18	H
17954.900	35.70	-5.42	33.80	7.32	H
17971.400	35.60	-5.42	43.40	-2.38	V
17993.400	35.60	-5.42	43.40	-2.38	H
17990.100	35.60	-5.42	43.40	-2.38	H
17997.800	35.60	-5.42	43.40	-2.38	H

Channel 48

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
5350.550	41.20	-16.58	33.40	24.38	H
17995.600	35.80	-5.42	33.80	7.42	H
17997.800	35.70	-5.42	43.40	-2.28	V
17985.700	35.60	-5.42	43.40	-2.38	H
17959.300	35.60	-5.42	43.40	-2.38	H
17989.000	35.60	-5.42	43.40	-2.38	H

802.11n-HT40

Channel 38

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
5149.930	45.50	-16.61	33.40	28.71	H
17991.200	35.80	-5.42	33.80	7.42	H
17972.500	35.70	-5.42	43.40	-2.28	V
17979.100	35.70	-5.42	43.40	-2.28	H
17983.500	35.60	-5.42	43.40	-2.38	H
17989.000	35.60	-5.42	43.40	-2.38	H

Channel 46

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
5350.150	41.50	-16.58	33.40	24.68	H
17972.500	35.90	-5.42	33.80	7.52	H
17943.900	35.70	-5.42	43.40	-2.28	V
17994.500	35.70	-5.42	43.40	-2.28	H
17982.400	35.60	-5.42	43.40	-2.38	H
17980.200	35.60	-5.42	43.40	-2.38	H

Peak

802.11a

Channel 36

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
5148.175	61.00	-16.61	33.40	44.21	H
17960.400	48.20	-5.42	33.80	19.82	H
17969.200	47.40	-5.42	43.40	9.42	V
17896.600	47.10	-5.74	43.40	9.44	H
17995.600	46.90	-5.42	43.40	8.92	H
17869.100	46.80	-5.74	43.40	9.14	H

Channel 40

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
17942.800	47.70	-5.42	43.40	9.72	H
17901.000	47.30	-5.74	33.80	19.24	H
17916.400	47.20	-5.42	43.40	9.22	V
17978.000	47.10	-5.42	43.40	9.12	H
17970.300	47.10	-5.42	43.40	9.12	H
17912.000	47.10	-5.74	43.40	9.44	H

Channel 48

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
5350.520	41.20	-16.58	33.40	24.38	H
17987.900	47.90	-5.42	33.80	19.52	H
17982.400	47.70	-5.42	43.40	9.72	V
17519.300	47.60	-5.92	43.40	10.12	H
17457.700	47.10	-5.92	40.10	12.92	H
17473.100	47.10	-5.92	40.10	12.92	H

802.11n-HT20

Channel 36

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
5149.440	57.90	-16.61	33.40	41.11	H
17939.500	48.00	-5.42	33.80	19.62	H
17876.800	47.30	-5.74	43.40	9.64	V
17737.100	47.20	-5.74	43.40	9.54	H
17972.500	47.20	-5.42	43.40	9.22	H
17453.300	47.10	-5.92	40.10	12.92	H

Channel 40

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
17390.600	47.70	-5.92	40.10	13.52	H
17963.700	47.50	-5.42	33.80	19.12	H
17984.600	47.40	-5.42	43.40	9.42	V
17952.700	47.30	-5.42	43.40	9.32	H
17906.500	47.10	-5.74	43.40	9.44	H
17264.100	47.10	-6.50	40.10	13.50	H

Channel 48

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
5350.535	53.60	-16.58	33.40	36.78	H
17969.200	47.70	-5.42	33.80	19.32	H
17993.400	47.30	-5.42	43.40	9.32	V
17981.300	47.30	-5.42	43.40	9.32	H
17980.200	47.10	-5.42	43.40	9.12	H
17861.400	47.10	-5.74	43.40	9.44	H

802.11n-HT40

Channel 38

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
5141.185	61.20	-16.61	33.40	44.41	H
17760.200	48.10	-5.74	33.80	20.04	H
17775.600	47.70	-5.74	43.40	10.04	V
17885.600	47.50	-5.74	43.40	9.84	H
17876.800	47.40	-5.74	43.40	9.74	H
17960.400	47.30	-5.42	43.40	9.32	H

Channel 46

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
5353.500	54.70	-16.58	33.40	37.88	H
17500.600	47.60	-5.92	33.80	19.72	H
17949.400	47.40	-5.42	43.40	9.42	V
18000.000	47.30	-6.54	46.40	7.44	H
17958.200	47.30	-5.42	43.40	9.32	H
17610.600	47.30	-6.90	43.40	10.80	H

Sample calculation: 802.11n 40MHz CH46–Peak, 5353.500MHz

$$\text{Peak ERP(dBm)} = P_{\text{Mea}}(37.88 \text{ dBuV/m}) + \text{Cable Loss}(-16.58) + \text{Antenna Factor}(33.40) = 54.70 \text{ dBuV/m}$$

A.7. AC Powerline Conducted Emission (150kHz- 30MHz)

Test Condition:

Voltage (V)	Frequency (Hz)
110	60

Measurement uncertainty:

Expanded measurement uncertainty for this test item is U =3.08dB, k=2.

Measurement Result and limit:

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger		
		11a mode	Idle	
0.15 to 0.5	66 to 56	Fig.15 Fig.17	Fig.16	P
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger		
		11a mode	Idle	
0.15 to 0.5	56 to 46	Fig.15 Fig.17	Fig.16	P
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Conclusion: PASS

Test graphs as below:

Traffic UC11US PUAN




Fig. 15 Conducted Emission(802.11a, Ch40, TX)

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	45.7	N	30.6	20.3	66.0
0.577500	38.8	L1	19.8	17.2	56.0
1.144500	37.6	L1	19.7	18.4	56.0
1.594500	35.5	L1	19.6	20.5	56.0
3.255000	37.3	L1	19.6	18.7	56.0
4.254000	37.1	L1	19.6	18.9	56.0

Final Result 2

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.321000	31.7	N	19.8	18.0	49.7
0.510000	33.1	N	19.8	12.9	46.0
0.753000	28.5	N	19.8	17.5	46.0
1.279500	28.6	N	19.6	17.4	46.0
3.336000	27.7	L1	19.6	18.3	46.0
3.853500	28.3	L1	19.6	17.7	46.0

Idle UC11US PUAN




Fig. 16 Conducted Emission(802.11a, IDLE)

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	43.5	L1	30.7	22.5	66.0
0.586500	36.6	L1	19.8	19.4	56.0
1.203000	38.0	L1	19.7	18.0	56.0
1.279500	35.7	L1	19.6	20.3	56.0
3.309000	36.9	L1	19.6	19.1	56.0
4.852500	37.2	L1	19.6	18.8	56.0

Final Result 2

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.321000	31.6	N	19.8	18.1	49.7
0.505500	32.8	N	19.8	13.2	46.0
0.748500	28.5	N	19.8	17.5	46.0
1.279500	28.6	N	19.6	17.4	46.0
3.313500	27.6	L1	19.6	18.4	46.0
3.804000	28.1	L1	19.6	17.9	46.0

Traffic UC11US Chenyang




Fig. 17 Conducted Emission(802.11a, IDLE)

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	43.5	L1	30.7	22.5	66.0
0.586500	36.6	L1	19.8	19.4	56.0
1.203000	38.0	L1	19.7	18.0	56.0
1.279500	35.7	L1	19.6	20.3	56.0
3.309000	36.9	L1	19.6	19.1	56.0
4.852500	37.2	L1	19.6	18.8	56.0

Final Result 2

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.321000	31.6	N	19.8	18.1	49.7
0.505500	32.8	N	19.8	13.2	46.0
0.748500	28.5	N	19.8	17.5	46.0
1.279500	28.6	N	19.6	17.4	46.0
3.313500	27.6	L1	19.6	18.4	46.0
3.804000	28.1	L1	19.6	17.9	46.0

A.8. 99% Occupied bandwidth

Method of Measurement: See ANSI C63.10-2013-clause 12.4.2.

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------

Measurement Result:

Mode	Channel	99% Occupied bandwidth (MHz)		conclusion
		Fig.	Value	
802.11a	5180 MHz	Fig.18	19.20	P
	5200 MHz	Fig.19	18.72	P
	5240 MHz	Fig.20	19.12	P
802.11n HT20	5180 MHz	Fig.21	18.96	P
	5200 MHz	Fig.22	18.84	P
	5240 MHz	Fig.23	18.88	P
802.11n HT40	5190 MHz	Fig.24	36.88	P
	5230 MHz	Fig.25	36.80	P

Conclusion: PASS

Test graphs as below:




Fig.18 99% Occupied bandwidth (802.11a, 5180MHz)




Fig.19 99% Occupied bandwidth (802.11a, 5200MHz)




Fig.20 99% Occupied bandwidth (802.11a, 5240MHz)




Fig.21 99% Occupied bandwidth (802.11n-HT20, 5180MHz)




Fig.22 99% Occupied bandwidth (802.11n-HT20, 5200MHz)




Fig.23 99% Occupied bandwidth (802.11n-HT20, 5240MHz)




Fig.24 99% Occupied bandwidth (802.11n-HT40, 5190MHz)




Fig.25 99% Occupied bandwidth (802.11n-HT40, 5230MHz)

A.9. Frequency Stability

Manufacturers ensured the EUT meet the requirement of frequency stability, such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

Measurement Result:

Mode	Channel	Test Condition		Result(MHz)
802.11n-20	5240MHz	Tnom	Vnom	0.02
		Tmax	Vnom	
		Tmin	Vnom	
		Vmax	Tnom	
		Vmin	Tnom	

A.10. Power control

A Transmission Power Control mechanism is not required for systems with an e.i.r.p. of less than 27dBm (500 mW).

ANNEX B: Accreditation Certificate

<p>United States Department of Commerce National Institute of Standards and Technology</p>  <hr/> <p>Certificate of Accreditation to ISO/IEC 17025:2005</p> <hr/> <p>NVLAP LAB CODE: 600118-0</p> <p>Telecommunication Technology Labs, CAICT Beijing China</p> <p><i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i></p> <p>Electromagnetic Compatibility & Telecommunications</p> <p><i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i></p> <hr/> <table border="0" style="width: 100%;"><tr><td style="width: 30%;"><p>2019-09-26 through 2020-09-30 <i>Effective Dates</i></p></td><td style="width: 20%; text-align: center;"></td><td style="width: 50%; text-align: right;"> <i>For the National Voluntary Laboratory Accreditation Program</i></td></tr></table>		<p>2019-09-26 through 2020-09-30 <i>Effective Dates</i></p>		 <i>For the National Voluntary Laboratory Accreditation Program</i>
<p>2019-09-26 through 2020-09-30 <i>Effective Dates</i></p>		 <i>For the National Voluntary Laboratory Accreditation Program</i>		

*** END OF REPORT BODY ***