



No. I20Z60293-SEM05

For

TCL Communication Ltd.

**HSUPA/HSDPA/UMTS Tri Bands / GSM Quad Bands / LTE 10 bands
mobile phone**

Model name: A406DL

With

Hardware Version: 04

Software Version: YXAG

FCC ID: 2ACCJN041

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT


No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn




Picture 1: Constituents of the sample




Picture 2: Left Hand Touch Cheek Position



Picture 3: Left Hand Tilt 15° Position




Picture 4: Right Hand Touch Cheek Position




Picture 5: Right Hand Tilt 15° Position

Test positions for body:


The Body SAR is tested at the following 3 test positions all with the distance =15mm between the EUT and the phantom bottom:



Picture 6: Front 15mm



Picture 7: Rear 15mm



Picture 8: Rear unfold 15mm