



**FCC PART 15
TEST REPORT
No. I20Z62070-IOT04**

for

TCL Communication Ltd.

GSM/UMTS/LTE mobile phone

T7730

FCC ID : 2ACCJN045

with

Hardware Version: 03

Software Version: v3.0.9D1Y

Issued Date: 2021-01-12

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



REPORT HISTORY

Report Number	Revision	Description	Issue Date
I20Z62070-IOT04	Rev.0	1st edition	2021-01-12

CONTENTS

CONTENTS	3
1. TEST LATORATORY	5
1.1. INTRODUCTION & ACCREDITATION	5
1.2. TESTING LOCATION	5
1.3. TESTING ENVIRONMENT.....	6
1.4. PROJECT DATE	6
1.5. SIGNATURE	6
2. CLIENT INFORMATION.....	7
2.1. APPLICANT INFORMATION	7
2.2. MANUFACTURER INFORMATION	7
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARYEQUIPMENT(AE)	8
3.1. ABOUT EUT	8
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	8
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	8
3.4. GENERAL DESCRIPTION.....	9
3.5. INTERPRETATION OF THE TEST ENVIRONMENT.....	10
4. REFERENCE DOCUMENTS	10
4.1. DOCUMENTS SUPPLIED BY APPLICANT	10
4.2. REFERENCE DOCUMENTS FOR TESTING.....	10
5. LABORATORY ENVIRONMENT.....	10
6. SUMMARY OF TEST RESULTS	11
6.1. SUMMARY OF TEST RESULTS.....	11
6.2. STATEMENTS.....	11
6.3. TEST CONDITIONS	11
7. TEST EQUIPMENTS UTILIZED	12
8. MEASUREMENT UNCERTAINTY	13
8.1 TRANSMITTER OUTPUT POWER	13
8.2 PEAK POWER SPECTRAL DENSITY	13
8.3 OCCUPIED CHANNEL BANDWIDTH	13
8.4 BAND EDGES COMPLIANCE	13
8.5 SPURIOUS EMISSIONS	13
ANNEX A: MEASUREMENT RESULTS.....	14
A.1. MEASUREMENT METHOD	14
A.2. MAXIMUM OUTPUT POWER	15
A.3. PEAK POWER SPECTRAL DENSITY (CONDUCTED).....	18



A.4. OCCUPIED 26DB BANDWIDTH(CONDUCTED)..... 20
A.5. BAND EDGES COMPLIANCE 48
A.6. TRANSMITTER SPURIOUS EMISSION 63
A.7. AC POWERLINE CONDUCTED EMISSION..... 96
A.8. 99% OCCUPIED BANDWIDTH 105
A.9. POWER CONTROL113
ANNEX B: ACCREDITATION CERTIFICATE.....114



1. TEST LABORATORY

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Location 1:CTTL(Gaolizhang Road)

Address: Cuihu Cloud Center, No.1, Gaolizhang Road, Wenquan,
Haidian District, Beijing, China

Radiated testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China100191

1.3. Testing Environment

Normal Temperature: 15-35℃
Relative Humidity: 20-75%


1.4. Project date

Testing Start Date: 2020-12-01
Testing End Date: 2021-01-12


1.5. Signature

谢宇

Xie Xiuzhen
(Prepared this test report)



Zheng Wei
(Reviewed this test report)



Hu Xiaoyu
(Approved this test report)



2. CLIENT INFORMATION

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: CHINA
Contact: Gong Zhizhou
Telephone: 0086-755-36611722
E-mail: zhizhou.gong@tcl.com

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: CHINA
Contact: Gong Zhizhou
Telephone: 0086-755-36611722
E-mail: zhizhou.gong@tcl.com

3. EQUIPMENT UNDER TEST (EUT) AND

ANCILLARY EQUIPMENT (AE)

3.1. About EUT

Description	GSM/UMTS/LTE mobile phone
Model name	T7730
FCC ID	2ACCJN045
WLAN Frequency Range	ISM Bands: -5150MHz~5250MHz -5250MHz~5350MHz -5470MHz~5725MHz
Type of modulation	OFDM
Antenna	Integral Antenna
Voltage	3.85 V

Note: Photographs of EUT are shown in ANNEX C of this test report. Components list, please refer to documents of the manufacturer.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	015888000200569/01	03	v3.0.9D1Y
EUT2	015888000200619/01	03	v3.0.9D1Y

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description		
AE1	battery	/	Inbuilt
AE2	battery	/	Inbuilt
AE3	Travel charger	/	/
AE4	Travel charger	/	/
AE5	Travel charger	/	/
AE6	Travel charger	/	/
AE7	USB Cable	/	/
AE8	USB Cable	/	/

AE1

Model	TLp048A1
Manufacturer	BYD
Capacitance	4360mAh
Nominal voltage	3.85V

AE2

Model	TLp048A7
Manufacturer	VEKEN

Capacitance	4360mAh
Nominal voltage	3.85V
AE3	
Model	QC13US
Manufacturer	BYD
Length of cable	/
AE4	
Model	QC13US
Manufacturer	PUAN
Length of cable	/
AE5	
Model	UC13US
Manufacturer	PUAN
Length of cable	/
AE6	
Model	UC13US
Manufacturer	Chen Yang
Length of cable	/
AE7	
Model	CDA0000128C1
Manufacturer	Juwei
Length of cable	/
AE8	
Model	CDA0000128C2
Manufacturer	shenghua
Length of cable	/

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment under Test (EUT) is a GSM/UMTS/LTE mobile phone with Bluetooth, WLAN with integrated antenna and inbuilt battery.

It has Bluetooth (EDR)function.

It consists of normal options: travel charger, USB cable.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

3.5. Interpretation of the Test Environment

For the test methods, the test environment uncertainty figures correspond to an expansion factor $k=2$.

Measurement Uncertainty

Parameter	Uncertainty
temperature	0.48°C
humidity	2 %
DC voltages	0.003V

4. REFERENCE DOCUMENTS

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

FCC Part15	Title 47 of the Code of Federal Regulations; Chapter I Part 15 - Radio frequency devices	2018
ANSI C63.10	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2013
UNII: KDB 789033 D02	General U-NII Test Procedures New Rules v02r01	2017-12
KDB 558074 D01	Federal Communications Commission Office of Engineering and Technology Laboratory Division GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES	2019

5. LABORATORY ENVIRONMENT

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15E	Sub-clause of IC	Verdict
Maximum Output Power	15.407	/	P
Peak Power Spectral Density	15.407	/	P
Occupied 26dB Bandwidth	15.403	/	P
Band edge compliance (Radiated)	15.209	/	P
Transmitter spurious emissions (Radiated)	15.407	/	P
AC Powerline Conducted Emission (150kHz- 30MHz)	15.407	/	P
Frequency Stability	15.407	/	P
99% Occupied bandwidth	/	/	P
Transmit Power Control	15.407	/	NA

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

CTTL has evaluated the test cases requested by the client/manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.1.

This report only deals with the WLAN function among the features described in section 3.

6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26°C
Voltage	3.85 V
Humidity	44%

7. TEST EQUIPMENTS UTILIZED

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	1 year	2021-05-15
2	Test Receiver	ESCI	100766	Rohde & Schwarz	1 year	2021-05-06
3	LISN	ESH2-Z5	829991/012	Rohde & Schwarz	1 year	2021-05-10
4	Shielding Room	S81	/	ETS-Lindgren	/	/
5	Attenuator	K40	/	Rosenberger	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100235	Rohde & Schwarz	1 year	2021-03-03
2	BiLog Antenna	VULB9163	1223	Schwarzbeck	1 year	2021-03-18
3	Dual-Ridge Waveguide Horn Antenna	3115	6914	ETS-Lindgren	1 year	2021-01-14
4	EMI Antenna	3116	2663	ETS-Lindgren	1 year	2021-09-15
5	Spectrum Analyzer	FSV40	101047	Rohde & Schwarz	1 year	2021-06-18

8. Measurement Uncertainty

8.1 Transmitter Output Power

Measurement Uncertainty: 0.387dB,k=1.96

8.2 Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

8.3 Occupied Channel Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

8.4 Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

8.5 Spurious Emissions

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
30MHz ≤ f ≤ 2GHz	1.22
2GHz ≤ f ≤ 3.6GHz	1.22
3.6GHz ≤ f ≤ 8GHz	1.22
8GHz ≤ f ≤ 12.75GHz	1.51
12.75GHz ≤ f ≤ 26GHz	1.51
26GHz ≤ f ≤ 40GHz	1.59

Radiated (k=2)

Frequency Range	Uncertainty(dB)
9kHz-30MHz	/
30MHz ≤ f ≤ 1GHz	5.16
1GHz ≤ f ≤ 18GHz	5.44
18GHz ≤ f ≤ 40GHz	5.28

8.6 AC Power-line Conducted Emission


Measurement Uncertainty : 3.08dB,k=2

ANNEX A: MEASUREMENT RESULTS

A.1. Measurement Method

A.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer




A.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



The measurement is made according to KDB 789033

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

A.2. Maximum output Power

Measurement Limit and Method:

Standard	Frequency (MHz)	Limit (dBm)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	24dBm
	5250MHz~5350MHz	24dBm or 11+10logB
	5470MHz~5725MHz	24dBm or 11+10logB

Limit use the less value, and B is the 26dB bandwidth.

The measurement method SA-2 is made according to KDB 789033

Measurement Results:

802.11a mode

Mode	Frequency	Test Result (dBm)							
		Data Rate (Mbps)							
		6	9	12	18	24	36	48	54
802.11a	5180MHz	15.73	/	/	/	/	/	/	/
	5200MHz	15.87	/	/	/	/	/	/	/
	5240MHz	16.47	/	/	/	/	/	/	/
	5260MHz	16.67	/	/	/	/	/	/	/
	5280MHz	16.61	/	/	/	/	/	/	/
	5320MHz	16.60	/	/	/	/	/	/	/
	5500MHz	15.97	/	/	/	/	/	/	/
	5580MHz	15.47	/	/	/	/	/	/	/
	5700MHz	16.12	/	/	/	/	/	/	/
	5720MHz	15.10	/	/	/	/	/	/	/

The data rate 6Mbps is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT20 mode

Mode	Frequency	Test Result (dBm)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n (HT20)	5180MHz	14.98	/	/	/	/	/	/	/
	5200MHz	14.76	/	/	/	/	/	/	/
	5240MHz	14.85	/	/	/	/	/	/	/
	5260MHz	14.73	/	/	/	/	/	/	/
	5280MHz	14.41	/	/	/	/	/	/	/
	5320MHz	14.28	/	/	/	/	/	/	/
	5500MHz	12.80	/	/	/	/	/	/	/
	5580MHz	13.62	/	/	/	/	/	/	/
	5700MHz	14.85	/	/	/	/	/	/	/
	5720MHz	14.38	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT20 mode

Mode	Frequency	Test Result (dBm)								
		Data Rate								
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
802.11ac (HT20)	5180MHz	14.20	/	/	/	/	/	/	/	/
	5200MHz	14.60	/	/	/	/	/	/	/	/
	5240MHz	14.20	/	/	/	/	/	/	/	/
	5260MHz	14.14	/	/	/	/	/	/	/	/
	5280MHz	13.91	/	/	/	/	/	/	/	/
	5320MHz	14.24	/	/	/	/	/	/	/	/
	5500MHz	12.35	/	/	/	/	/	/	/	/
	5580MHz	12.84	/	/	/	/	/	/	/	/
	5700MHz	14.03	/	/	/	/	/	/	/	/
5720 MHz	14.79	/	/	/	/	/	/	/	/	

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT40 mode

Mode	Frequency	Test Result (dBm)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n (HT40)	5190MHz	15.50	/	/	/	/	/	/	/
	5230MHz	15.56	/	/	/	/	/	/	/
	5270MHz	15.09	/	/	/	/	/	/	/
	5310MHz	14.89	/	/	/	/	/	/	/
	5510MHz	13.52	/	/	/	/	/	/	/
	5550MHz	14.00	/	/	/	/	/	/	/
	5670MHz	14.60	/	/	/	/	/	/	/
	5710MHz	14.78	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT40 mode

Mode	Frequency	Test Result (dBm)									
		Data Rate									
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
802.11ac (HT40)	5190MHz	14.24	/	/	/	/	/	/	/	/	/
	5230MHz	14.17	/	/	/	/	/	/	/	/	/

	5270MHz	14.81	/	/	/	/	/	/	/	/	/
	5310MHz	14.59	/	/	/	/	/	/	/	/	/
	5510MHz	13.17	/	/	/	/	/	/	/	/	/
	5550MHz	13.63	/	/	/	/	/	/	/	/	/
	5670MHz	13.32	/	/	/	/	/	/	/	/	/
	5710MHz	14.92	/	/	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT80 mode

Mode	Frequency	Test Result (dBm)									
		Data Rate									
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
802.11ac (HT80)	5210MHz	14.04	/	/	/	/	/	/	/	/	/
	5290MHz	14.41	/	/	/	/	/	/	/	/	/
	5530MHz	13.16	/	/	/	/	/	/	/	/	/
	5610MHz	13.80	/	/	/	/	/	/	/	/	/
	5690MHz	14.59	/	/	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

A.3. Peak Power Spectral Density (conducted)

Measurement Limit:

Standard	Frequency (MHz)	Limit (dBm/MHz)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	11
	5250MHz~5350MHz	11
	5470MHz~5725MHz	11

The output power measurement method Section F is made according to KDB 789033

Measurement Results:

Mode	Frequency	Power Spectral Density (dBm/MHz)	Conclusion
802.11a	5180 MHz	4.38	P
	5200 MHz	5.09	P
	5240 MHz	5.06	P
	5260 MHz	5.00	P
	5280 MHz	5.06	P
	5320 MHz	4.67	P
	5500 MHz	4.00	P
	5580 MHz	4.47	P
	5700 MHz	5.50	P
	5720MHz	4.99	P
802.11n HT20	5180 MHz	3.66	P
	5200 MHz	3.67	P
	5240 MHz	3.69	P
	5260 MHz	3.59	P
	5280 MHz	3.63	P
	5320 MHz	3.17	P
	5500 MHz	2.63	P
	5580 MHz	3.13	P
	5700 MHz	4.22	P
	5720MHz	5.72	P
802.11ac HT20	5180 MHz	2.96	P
	5200 MHz	3.71	P
	5240 MHz	3.73	P
	5260 MHz	3.51	P
	5280 MHz	3.67	P
	5320 MHz	3.19	P
	5500 MHz	2.61	P
	5580 MHz	3.08	P
	5700 MHz	4.18	P
	5720MHz	5.71	P
802.11n	5190 MHz	0.38	P

HT40	5230 MHz	0.76	P
	5270 MHz	0.51	P
	5310 MHz	0.41	P
	5510 MHz	-0.52	P
	5550 MHz	-0.05	P
	5670 MHz	-0.58	P
	5710MHz	1.53	P
802.11ac HT40	5190 MHz	-1.35	P
	5230 MHz	-0.20	P
	5270 MHz	-0.60	P
	5310 MHz	-0.62	P
	5510 MHz	-1.94	P
	5550 MHz	-1.59	P
	5670 MHz	-0.60	P
802.11ac HT80	5210MHz	-4.39	P
	5290MHz	-3.81	P
	5530MHz	-5.33	P
	5610MHz	-4.53	P
	5690MHz	-2.04	P

Conclusion: PASS

A.4. Occupied 26dB Bandwidth(conducted)

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.403 (i)	/

The measurement is made according to KDB 789033

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------

Measurement Result:

Mode	Frequency	Occupied 26dB Bandwidth (MHz)		conclusion
		Fig.	Value	
802.11a	5180 MHz	Fig.1	23.35	P
	5200 MHz	Fig.2	23.25	P
	5240 MHz	Fig.3	23.10	P
	5260 MHz	Fig.4	22.75	P
	5280 MHz	Fig.5	23.40	P
	5320 MHz	Fig.6	23.20	P
	5500 MHz	Fig.7	22.79	P
	5580 MHz	Fig.8	23.04	P
	5700 MHz	Fig.9	23.20	P
	5720MHz	Fig.10	24.40	P
802.11n HT20	5180 MHz	Fig.11	23.35	P
	5200 MHz	Fig.12	23.54	P
	5240 MHz	Fig.13	23.00	P
	5260 MHz	Fig.14	23.70	P
	5280 MHz	Fig.15	23.85	P
	5320 MHz	Fig.16	23.04	P
	5500 MHz	Fig.17	23.54	P
	5580 MHz	Fig.18	23.35	P
	5700 MHz	Fig.19	23.54	P
	5720MHz	Fig.20	26.04	P
802.11ac HT20	5180 MHz	Fig.21	23.95	P
	5200 MHz	Fig.22	24.00	P
	5240 MHz	Fig.23	23.85	P
	5260 MHz	Fig.24	23.40	P
	5280 MHz	Fig.25	23.40	P
	5320 MHz	Fig.26	23.85	P
	5500 MHz	Fig.27	22.60	P
	5580 MHz	Fig.28	23.90	P
	5700 MHz	Fig.29	23.20	P
	5720MHz	Fig.30	24.15	P

802.11n HT40	5190 MHz	Fig.31	40.88	P
	5230 MHz	Fig.32	40.56	P
	5270 MHz	Fig.33	41.20	P
	5310 MHz	Fig.34	40.72	P
	5510 MHz	Fig.35	40.63	P
	5550 MHz	Fig.36	40.79	P
	5670 MHz	Fig.37	41.11	P
802.11ac HT40	5710MHz	Fig.38	41.43	P
	5190 MHz	Fig.39	40.95	P
	5230 MHz	Fig.40	40.95	P
	5270 MHz	Fig.41	40.95	P
	5310 MHz	Fig.42	40.88	P
	5510 MHz	Fig.43	41.11	P
	5550 MHz	Fig.44	40.72	P
802.11ac HT80	5670 MHz	Fig.45	41.36	P
	5710MHz	Fig.46	41.91	P
	5210MHz	Fig.47	84.16	P
	5290MHz	Fig.48	84.32	P
	5530MHz	Fig.49	84.80	P
	5610MHz	Fig.50	94.72	P
	5690MHz	Fig.51	84.00	P

Conclusion: PASS

Test graphs as below:




Fig.1 Occupied 26dB Bandwidth (802.11a, 5180MHz)




Fig.2 Occupied 26dB Bandwidth (802.11a, 5200MHz)




Fig.3 Occupied 26dB Bandwidth (802.11a, 5240MHz)




Fig.4 Occupied 26dB Bandwidth (802.11a, 5260MHz)




Fig.5 Occupied 26dB Bandwidth (802.11a, 5280MHz)




Fig.6 Occupied 26dB Bandwidth (802.11a, 5320MHz)




Fig.7 Occupied 26dB Bandwidth (802.11a, 5500MHz)




Fig.8 Occupied 26dB Bandwidth (802.11a, 5580MHz)




Fig.9 Occupied 26dB Bandwidth (802.11a, 5700MHz)




Fig.10 Occupied 26dB Bandwidth (802.11a, 5720MHz)




Fig.11 Occupied 26dB Bandwidth (802.11n-HT20, 5180MHz)




Fig.12 Occupied 26dB Bandwidth (802.11n-HT20, 5200MHz)




Fig.13 Occupied 26dB Bandwidth (802.11n-HT20, 5240MHz)




Fig.14 Occupied 26dB Bandwidth (802.11n-HT20, 5260MHz)




Fig.15 Occupied 26dB Bandwidth (802.11n-HT20, 5280MHz)




Fig.16 Occupied 26dB Bandwidth (802.11n-HT20, 5320MHz)




Fig.17 Occupied 26dB Bandwidth (802. 11n-HT20, 5500MHz)




Fig.18 Occupied 26dB Bandwidth (802. 11n-HT20, 5580MHz)




Fig.19 Occupied 26dB Bandwidth (802. 11n-HT20, 5700MHz)




Fig.20 Occupied 26dB Bandwidth (802. 11n-HT20, 5720MHz)




Fig.21 Occupied 26dB Bandwidth (802.11ac-HT20, 5180MHz)




Fig.22 Occupied 26dB Bandwidth (802.11ac-HT20, 5200MHz)




Fig.23 Occupied 26dB Bandwidth (802.11ac-HT20, 5240MHz)




Fig.24 Occupied 26dB Bandwidth (802.11ac-HT20, 5260MHz)




Fig.25 Occupied 26dB Bandwidth (802.11ac-HT20, 5280MHz)




Fig.26 Occupied 26dB Bandwidth (802.11ac-HT20, 5320MHz)




Fig.27 Occupied 26dB Bandwidth (802. 11ac-HT20, 5500MHz)




Fig.28 Occupied 26dB Bandwidth (802. 11ac-HT20, 5580MHz)




Fig.29 Occupied 26dB Bandwidth (802. 11ac-HT20, 5700MHz)




Fig.30 Occupied 26dB Bandwidth (802. 11ac-HT20, 5720MHz)




Fig.31 Occupied 26dB Bandwidth (802.11n-HT40, 5190MHz)




Fig.32 Occupied 26dB Bandwidth (802.11n-HT40, 5230MHz)




Fig.33 Occupied 26dB Bandwidth (802.11n-HT40, 5270MHz)




Fig.34 Occupied 26dB Bandwidth (802.11n-HT40, 5310MHz)




Fig.35 Occupied 26dB Bandwidth (802. 11n-HT40, 5510MHz)




Fig.36 Occupied 26dB Bandwidth (802. 11n-HT40, 5550MHz)




Fig.37 Occupied 26dB Bandwidth (802. 11n-HT40, 5670MHz)




Fig.38 Occupied 26dB Bandwidth (802. 11n-HT40, 5710MHz)




Fig.39 Occupied 26dB Bandwidth (802.11ac-HT40, 5190MHz)




Fig.40 Occupied 26dB Bandwidth (802.11ac-HT40, 5230MHz)




Fig.41 Occupied 26dB Bandwidth (802.11ac-HT40, 5270MHz)




Fig.42 Occupied 26dB Bandwidth (802.11ac-HT40, 5310MHz)




Fig.43 Occupied 26dB Bandwidth (802.11ac-HT40, 5510MHz)




Fig.44 Occupied 26dB Bandwidth (802.11ac-HT40, 5550MHz)