



FCC PART 15C TEST REPORT No.I21Z60291-IOT06

for

TCL Communication Ltd.

GSM/UMTS/LTE mobile phone

T774B, T775B

With

FCC ID: 2ACCJN054

Hardware Version: 03

Software Version: v3.0.9DF2

Issued Date: 2021-03-11

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



REPORT HISTORY

Report Number	Revision	Description	Issue Date
I21Z60291-IOT06	Rev.0	1st edition	2021-03-11

CONTENTS

CONTENTS	3
1. TEST LATORATORY.....	5
1.1. INTRODUCTION & ACCREDITATION	5
1.2. TESTING LOCATION	5
1.3. TESTING ENVIRONMENT	5
1.4. PROJECT DATE	5
1.5. SIGNATURE	5
2. CLIENT INFORMATION.....	6
2.1. APPLICANT INFORMATION	6
2.2. MANUFACTURER INFORMATION	6
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT(AE)	7
3.1. ABOUT EUT	7
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	7
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	7
3.4. GENERAL DESCRIPTION.....	8
4. REFERENCE DOCUMENTS	8
4.1. DOCUMENTS SUPPLIED BY APPLICANT	8
4.2. REFERENCE DOCUMENTS FOR TESTING.....	8
5. LABORATORY ENVIRONMENT.....	8
6. SUMMARY OF TEST RESULTS	9
6.1. SUMMARY OF TEST RESULTS	9
6.2. STATEMENTS.....	9
6.3. TEST CONDITIONS	9
7. TEST EQUIPMENTS UTILIZED	10
8. MEASUREMENT UNCERTAINTY	11
8.1. TRANSMITTER OUTPUT POWER	11
8.2. PEAK POWER SPECTRAL DENSITY	11
8.3. OCCUPIED 6DB BANDWIDTH.....	11
8.4. BAND EDGES COMPLIANCE	11
8.5. SPURIOUS EMISSIONS	11
8.6. AC POWER-LINE CONDUCTED EMISSION	11
ANNEX A: EUT PARAMETERS.....	11
ANNEX B: MEASUREMENT RESULTS.....	12
B.1. MEASUREMENT METHOD	12
B.2. MAXIMUM AVERAGE OUTPUT POWER-CONDUCTED	13



B.2.1 ANTENNA GAIN..... 13

B.2.2. MAXIMUM AVERAGE OUTPUT POWER-CONDUCTED 13

B.3. PEAK POWER SPECTRAL DENSITY 14

B.4. OCCUPIED 6DB BANDWIDTH 15

B.5. TRANSMITTER SPURIOUS EMISSION..... 20

B.5.1 TRANSMITTER SPURIOUS EMISSION - RADIATED 20

B.6. BAND EDGES COMPLIANCE 33

B.6.1 BAND EDGES - RADIATED 33

B.7. AC POWERLINE CONDUCTED EMISSION 40

ANNEX C: ACCREDITATION CERTIFICATE 43

1. TEST LABORATORY

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (ISED#: 24849). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China100191

1.3. Testing Environment

Normal Temperature: 15-35°C


Relative Humidity: 20-75%

1.4. Project date

Testing Start Date: 2021-02-22


Testing End Date: 2021-03-08

1.5. Signature




Xie Xiuzhen

(Prepared this test report)



Zheng Wei

(Reviewed this test report)



Hu Xiaoyu

(Approved this test report)



2. CLIENT INFORMATION

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Telephone: 0086-755-36611722
Fax: 0086-755-36612000-81722

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Telephone: 0086-755-36611722
Fax: 0086-755-36612000-81722

3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY

EQUIPMENT(AE)

3.1. About EUT

Description	GSM/UMTS/LTE mobile phone
Model name	T774B, T775B
FCC ID	2ACCJN054
WLAN Frequency Band	ISM Band: 5725MHz~5850MHz
Type of modulation	OFDM
Voltage	3.85V

3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version
EUT1	351897970000224	03	v3.0.9DF2
EUT2	351897970000240	03	v3.0.9DF2

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	/	/
AE2	/	/
AE3	/	/
AE4	/	/
AE5	/	/

AE1

Model	TLp048A1
Manufacturer	BYD
Capacity	4360 mAh
Nominal Voltage	3.85V

AE2

Model	TLp048A7
Manufacturer	VEKEN
Capacity	4360 mAh
Nominal Voltage	3.85V

AE3

Model	CDA0000128C1
Manufacturer	Juwei
Length of cable	/

AE4

Model	CDA0000128C2
Manufacturer	Shenghua
Length of cable	/

AE5

Model	UC13US
Manufacturer	PUAN
Length of cable	/

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

Equipment Under Test (EUT) is a model of GSM/UMTS/LTE mobile phone with integrated antenna.

It consists of normal options: Battery and Charger.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the Client.

4. REFERENCE DOCUMENTS

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

FCC Part15	FCC CFR 47, Part 15, Subpart C and E: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.407 General technical requirements	2018
ANSI C63.10	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2013
UNII: KDB 789033 D02	General U-NII Test Procedures New Rules v02r01	2017-12
KDB 558074 D01	Federal Communications Commission Office of Engineering and Technology Laboratory Division GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES	2019

5. LABORATORY ENVIRONMENT

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.407 (a)	/	P
Peak Power Spectral Density	15.407 (a)	/	P
Occupied 6dB Bandwidth	15.407 (e)	/	P
Band Edges Compliance - Conducted& Radiated	15.407 (b)	/	P
Transmitter Spurious Emission - Conducted	15.407	/	P
Transmitter Spurious Emission - Radiated	15.407, 15.205, 15.209	/	P
AC Powerline Conducted Emission	15.107, 15.207	/	P

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

CTTL has evaluated the test cases requested by the client/matrix manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.1.

This report only deals with the WLAN function among the features described in section 3.

6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26°C
Voltage	3.85V
Humidity	44%

7. TEST EQUIPMENTS UTILIZED

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	1 year	2021-05-06
2	LISN	ENV216	101200	R&S	1 year	2021-05-19
3	Test Receiver	ESC13	100344	R&S	1 year	2022-02-23
4	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100235	Rohde & Schwarz	1 year	2022-02-23
2	BiLog Antenna	VULB9163	9163-1223	Schwarzbeck	1 year	2021-03-18
3	Antenna	3115	00167250	ETS-Lindgren	1 year	2021-05-14

8. Measurement Uncertainty

8.1. Transmitter Output Power

Measurement Uncertainty: 0.387dB,k=1.96

8.2. Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

8.3. Occupied 6dB Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

8.4. Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

8.5. Spurious Emissions

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

Radiated (k=2)

Frequency Range	Uncertainty(dB)
9kHz-30MHz	/
$30\text{MHz} \leq f \leq 1\text{GHz}$	5.16
$1\text{GHz} \leq f \leq 18\text{GHz}$	5.44
$18\text{GHz} \leq f \leq 40\text{GHz}$	5.28

8.6. AC Power-line Conducted Emission

Measurement Uncertainty : 3.08dB,k=2

ANNEX A: EUT parameters


Disclaimer: the worse case and antenna gain provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

ANNEX B: MEASUREMENT RESULTS

B.1. Measurement Method

B.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer




B.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



The measurement is made according to ANSI C63.10.

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

B.2. Maximum Average Output Power-Conducted

Measurement Limit and Method:

Standard	Limit (dBm)
FCC CRF Part 15.407(a)	< 30

B.2.1 Antenna Gain

Antenna gain is -1.6dBi and the value is supplied by the applicant or manufacturer.

B.2.2. Maximum Average Output Power-Conducted

Method of Measurement: See ANSI C63.10-clause 12.3.2.2 Method SA-1

Mode	802.11a	802.11n-HT20	802.11ac-HT20	802.11n-HT40	802.11ac-HT40	802.11ac-HT80
Duty Cycle	98%	98%	98%	98%	98%	98%

802.11a mode

Mode	Test Result (dBm)		
	5745MHz (Ch149)	5785MHz (Ch157)	5825MHz (Ch165)
802.11a	16.51	17.54	17.45

802.11n-HT20 mode

Mode	Test Result (dBm)		
	5745MHz (Ch149)	5785MHz (Ch157)	5825MHz(Ch165)
802.11n(20MHz)	15.14	15.29	15.28

802.11ac-HT20 mode

Mode	Test Result (dBm)		
	5745MHz (Ch149)	5785MHz (Ch157)	5825MHz(Ch165)
802.11ac(20MHz)	14.79	14.81	14.80

802.11n-HT40 mode

Mode	Test Result (dBm)	
	5755MHz (Ch151)	5795MHz(Ch159)
802.11n(40MHz)	13.98	14.08

802.11ac-HT40 mode

Mode	Test Result (dBm)	
	5755MHz (Ch151)	5795MHz(Ch159)
802.11ac(40MHz)	13.96	14.11

802.11ac-HT80 mode

Mode	Test Result (dBm)
	5775MHz (Ch155)
802.11ac(80MHz)	13.78

Conclusion: PASS

B.3. Peak Power Spectral Density

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407(a)	< 30 dBm/500 kHz

The measurement is made according to ANSI C63.10 and KDB789033 D02

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

Measurement Results:

Mode	Channel	Power Spectral Density (dBm/500kHz)	Conclusion
802.11a	149	0.56	P
	157	0.57	P
	165	0.90	P
802.11n HT20	149	-0.45	P
	157	-0.72	P
	165	-0.40	P
802.11n HT40	151	-4.73	P
	159	-4.77	P
802.11ac HT80	155	-8.05	P

Conclusion: PASS

B.4. Occupied 6dB Bandwidth

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.407 (e)	≥ 500

The measurement is made according to KDB789033 D02 .

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------

Measurement Result:

Mode	Channel	Occupied 6dB Bandwidth (MHz)		conclusion
		Fig.	Value	
802.11a	149	Fig.1	15.35	P
	157	Fig.2	15.55	P
	165	Fig.3	15.35	P
802.11n HT20	149	Fig.4	16.35	P
	157	Fig.5	15.95	P
	165	Fig.6	16.00	P
802.11n HT40	151	Fig.7	35.36	P
	159	Fig.8	35.12	P
802.11ac HT80	155	Fig.9	75.20	P

Conclusion: PASS

Test graphs as below:




Fig. 1 Occupied 6dB Bandwidth (802.11a, Ch 149)




Fig. 2 Occupied 6dB Bandwidth (802.11a, Ch 157)




Fig. 3 Occupied 6dB Bandwidth (802.11a, Ch 165)




Fig. 4 Occupied 6dB Bandwidth (802.11n-HT20, Ch 149)




Fig. 5 Occupied 6dB Bandwidth (802.11n-HT20, Ch 157)




Fig. 6 Occupied 6dB Bandwidth (802.11n-HT20, Ch 165)




Fig. 7 Occupied 6dB Bandwidth (802.11n-HT40, Ch 151)




Fig. 8 Occupied 6dB Bandwidth (802.11n-HT40, Ch 159)




Fig. 9 Occupied 6dB Bandwidth (802.11ac-HT80, Ch 155)

B.5. Transmitter Spurious Emission

Measurement Limit:

Standard	Frequency (MHz)	Limit (dBm/MHz)
FCC 47 CFR Part 15.407	5725MHz~5850MHz	< -27

The measurement is made according to ANSI C63.10 .

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Measurement Uncertainty:

Frequency Range	Uncertainty(dB)
30MHz ≤ f ≤ 2GHz	0.63
2GHz ≤ f ≤ 3.6GHz	0.82
3.6GHz ≤ f ≤ 8GHz	1.55
8GHz ≤ f ≤ 20GHz	1.86
20GHz ≤ f ≤ 22GHz	1.90
22GHz ≤ f ≤ 26GHz	2.20

B.5.1 Transmitter Spurious Emission - Radiated

Measurement Limit:

Standard	Limit (dBm/MHz)	
FCC 47 CFR Part 15.407	at the band edge	27
	at 5 MHz above or below the band edge	15.6
	at 25 MHz above or below the band edge	10
	at 75 MHz or more above or below the band edge	-27
	Note: Increasing linearly from point to point.	

The measurement is made according to KDB 789033

Measurement Results:

802.11a mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11a	149	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	157	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
	165	26.5 GHz~ 40 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11n-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT20)	149	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	157	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
	165	26.5 GHz~ 40 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11n-HT40 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT40)	151	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz~ 40 GHz	---	P
	159	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11ac-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
------	---------	-----------------	--------------	------------

802.11ac (HT20)	149	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	157	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz~ 40 GHz	---	P
	165	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11ac-HT40 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11ac (HT40)	151	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz~ 40 GHz	---	P
	159	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11ac-HT80 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11ac (HT80)	155	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz~ 40 GHz	---	P

Conclusion: PASS

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

Average Results:
802.11a
Ch149

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17987.9	42.8	-25.5	46.7	21.6	54.0	32.4	V
17985.7	42.5	-25.5	46.7	21.3	54.0	32.7	V
17948.8	42.4	-25.5	46.7	21.2	54.0	32.8	V
17962.6	42.4	-25.5	46.7	21.2	54.0	32.8	V
17973	42.4	-25.5	46.7	21.2	54.0	32.8	V
17981.8	42.4	-25.5	46.7	21.2	54.0	32.8	H

Ch157

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17965.3	42.8	-25.5	46.7	21.6	54.0	32.4	V
17968.1	42.7	-25.5	46.7	21.5	54.0	32.5	V
17975.2	42.7	-25.5	46.7	21.5	54.0	32.5	V
17991.2	42.7	-25.5	46.7	21.5	54.0	32.5	V
17997.2	42.7	-25.5	46.7	21.5	54.0	32.5	V
17997.8	42.7	-25.5	46.7	21.5	54.0	32.5	V

Ch165

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17975.8	42.6	-25.5	46.7	21.4	54.0	32.6	V
17991.8	42.6	-25.5	46.7	21.4	54.0	32.6	V
17975.2	42.5	-25.5	46.7	21.3	54.0	32.7	V
17980.8	42.5	-25.5	46.7	21.3	54.0	32.7	V
17986.8	42.5	-25.5	46.7	21.3	54.0	32.7	V
17982.4	42.4	-25.5	46.7	21.2	54.0	32.8	H

802.11n-HT20

Ch149

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17985.2	42.5	-25.5	46.7	21.3	54.0	32.7	H
17961.5	42.4	-25.5	46.7	21.2	54.0	32.8	V
17986.8	42.4	-25.5	46.7	21.2	54.0	32.8	V
17987.3	42.4	-25.5	46.7	21.2	54.0	32.8	V
17991.8	42.4	-25.5	46.7	21.2	54.0	32.8	V
17995	42.4	-25.5	46.7	21.2	54.0	32.8	V

Ch157

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17990.1	42.7	-25.5	46.7	21.5	54.0	32.5	H
17972.5	42.6	-25.5	46.7	21.4	54.0	32.6	V
17979.7	42.6	-25.5	46.7	21.4	54.0	32.6	V
17979.1	42.5	-25.5	46.7	21.3	54.0	32.7	V
17956.5	42.4	-25.5	46.7	21.2	54.0	32.8	V
17961.5	42.4	-25.5	46.7	21.2	54.0	32.8	H

Ch165

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17991.2	42.7	-25.5	46.7	21.5	54.0	32.5	V
17972.5	42.6	-25.5	46.7	21.4	54.0	32.6	V
17994.5	42.6	-25.5	46.7	21.4	54.0	32.6	V
17966.5	42.5	-25.5	46.7	21.3	54.0	32.7	H
17989	42.4	-25.5	46.7	21.2	54.0	32.8	V
17994	42.4	-25.5	46.7	21.2	54.0	32.8	H

802.11n-HT40

Ch151

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17998.3	42.8	-25.5	46.7	21.6	54.0	32.4	V
17977.5	42.7	-25.5	46.7	21.5	54.0	32.5	V
17996.2	42.7	-25.5	46.7	21.5	54.0	32.5	V
17975.8	42.5	-25.5	46.7	21.3	54.0	32.7	V
17985.7	42.5	-25.5	46.7	21.3	54.0	32.7	V
17986.8	42.5	-25.5	46.7	21.3	54.0	32.7	V

Ch159

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17982.4	42.6	-25.5	46.7	21.4	54.0	32.6	H
17989.5	42.6	-25.5	46.7	21.4	54.0	32.6	V
17977.5	42.5	-25.5	46.7	21.3	54.0	32.7	H
17979.1	42.5	-25.5	46.7	21.3	54.0	32.7	V
17991.8	42.5	-25.5	46.7	21.3	54.0	32.7	V
17995	42.5	-25.5	46.7	21.3	54.0	32.7	H

802.11ac-HT20

Ch149

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17979.1	42.8	-25.5	46.7	21.6	54.0	32.4	V
17980.8	42.7	-25.5	46.7	21.5	54.0	32.5	H
17985.7	42.5	-25.5	46.7	21.3	54.0	32.7	V
17964.8	42.4	-25.5	46.7	21.2	54.0	32.8	V
17974.2	42.4	-25.5	46.7	21.2	54.0	32.8	V
17987.9	42.4	-25.5	46.7	21.2	54.0	32.8	H

Ch157

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17981.8	42.7	-25.5	46.7	21.5	54.0	32.5	V
17979.7	42.6	-25.5	46.7	21.4	54.0	32.6	V
17880.7	42.5	-25.5	46.7	21.3	54.0	32.7	V
17992.3	42.5	-25.5	46.7	21.3	54.0	32.7	V
17972.5	42.4	-25.5	46.7	21.2	54.0	32.8	V
17973.6	42.4	-25.5	46.7	21.2	54.0	32.8	V

Ch165

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17977.5	42.8	-25.5	46.7	21.6	54.0	32.4	V
17985.2	42.5	-25.5	46.7	21.3	54.0	32.7	V
17989	42.5	-25.5	46.7	21.3	54.0	32.7	V
17969.2	42.4	-25.5	46.7	21.2	54.0	32.8	V
17973	42.4	-25.5	46.7	21.2	54.0	32.8	V
17976.9	42.4	-25.5	46.7	21.2	54.0	32.8	V

802.11ac-HT40
Ch151

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17978.5	42.5	-25.5	46.7	21.3	54.0	32.7	V
17973	42.4	-25.5	46.7	21.2	54.0	32.8	V
17979.1	42.4	-25.5	46.7	21.2	54.0	32.8	H
17980.8	42.4	-25.5	46.7	21.2	54.0	32.8	H
17953.2	42.3	-25.5	46.7	21.1	54.0	32.9	V
17958.2	42.3	-25.5	46.7	21.1	54.0	32.9	V

Ch159

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17994	42.5	-25.5	46.7	21.3	54.0	32.7	H
17981.8	42.4	-25.5	46.7	21.2	54.0	32.8	V
17985.2	42.4	-25.5	46.7	21.2	54.0	32.8	V
17989	42.4	-25.5	46.7	21.2	54.0	32.8	V
17991.2	42.4	-25.5	46.7	21.2	54.0	32.8	H
17991.8	42.4	-25.5	46.7	21.2	54.0	32.8	H

802.11ac-HT80
Ch155

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17988.5	42.7	-25.5	46.7	21.5	54.0	32.5	V
17982.4	42.6	-25.5	46.7	21.4	54.0	32.6	V
17987.9	42.5	-25.5	46.7	21.3	54.0	32.7	V
17965.9	42.4	-25.5	46.7	21.2	54.0	32.8	H
17967.5	42.4	-25.5	46.7	21.2	54.0	32.8	V
17973	42.4	-25.5	46.7	21.2	54.0	32.8	V

Peak Results:
802.11a
Ch149

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17977.5	55.6	-25.5	46.7	34.4	74.0	39.6	V
17993.4	54.2	-25.5	46.7	33.0	74.0	41.0	V
17908.2	54.1	-25.5	46.7	32.9	74.0	41.1	H
17891.1	53.4	-25.5	46.7	32.2	74.0	41.8	V
17971.4	53.4	-25.5	46.7	32.2	74.0	41.8	H
17973.6	53.3	-25.5	46.7	32.1	74.0	41.9	V

Ch157

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17997.2	55.1	-25.5	46.7	33.9	74.0	40.1	V
17985.7	54.2	-25.5	46.7	33.0	74.0	41.0	H
17876.2	53.9	-25.5	46.7	32.7	74.0	41.3	H
17956	53.9	-25.5	46.7	32.7	74.0	41.3	H
17951.6	53.8	-25.5	46.7	32.6	74.0	41.4	H
17980.8	53.7	-25.5	46.7	32.5	74.0	41.5	V

Ch165

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17884.5	53.6	-25.5	46.7	32.4	74.0	41.6	H
17986.2	53.6	-25.5	46.7	32.4	74.0	41.6	V
17997.8	53.5	-25.5	46.7	32.3	74.0	41.7	H
17978	53.4	-25.5	46.7	32.2	74.0	41.8	H
17855.9	53.3	-25.5	46.7	32.1	74.0	41.9	V
17885.6	53.3	-25.5	46.7	32.1	74.0	41.9	V

802.11n-HT20
Ch149

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17990.7	54	-25.5	46.7	32.8	74.0	41.2	H
17863.6	53.9	-25.5	46.7	32.7	74.0	41.3	V
17968.1	53.8	-25.5	46.7	32.6	74.0	41.4	V
17990.1	53.6	-25.5	46.7	32.4	74.0	41.6	H
17955.5	53.5	-25.5	46.7	32.3	74.0	41.7	V
17975.8	53.5	-25.5	46.7	32.3	74.0	41.7	V

Ch157

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17489.6	53.8	-26.9	45.2	35.4	74.0	38.6	V
17951	53.5	-25.5	46.7	32.3	74.0	41.7	V
17980.8	53.5	-25.5	46.7	32.3	74.0	41.7	V
17976.9	53.4	-25.5	46.7	32.2	74.0	41.8	H
17980.2	53.4	-25.5	46.7	32.2	74.0	41.8	V
17929.6	53.2	-25.5	46.7	32.0	74.0	42.0	V

Ch165

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17992.8	54.1	-25.5	46.7	32.9	74.0	41.1	V
17959.8	54	-25.5	46.7	32.8	74.0	41.2	V
17994	53.7	-25.5	46.7	32.5	74.0	41.5	H
17896	53.5	-25.5	46.7	32.3	74.0	41.7	H
17965.3	53.5	-25.5	46.7	32.3	74.0	41.7	V
17970.3	53.5	-25.5	46.7	32.3	74.0	41.7	V

802.11n-HT40

Ch151

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17889.5	53.7	-25.5	46.7	32.5	74.0	41.5	V
17885.6	53.5	-25.5	46.7	32.3	74.0	41.7	H
17964.8	53.5	-25.5	46.7	32.3	74.0	41.7	H
17987.9	53.5	-25.5	46.7	32.3	74.0	41.7	V
17526.5	53.3	-26.9	45.2	34.9	74.0	39.1	V
17977.5	53.3	-25.5	46.7	32.1	74.0	41.9	V

Ch159

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17965.3	54.4	-25.5	46.7	33.2	74.0	40.8	V
17934	53.9	-25.5	46.7	32.7	74.0	41.3	V
17864.7	53.5	-25.5	46.7	32.3	74.0	41.7	V
17871.8	53.5	-25.5	46.7	32.3	74.0	41.7	H
17975.2	53.5	-25.5	46.7	32.3	74.0	41.7	H
17990.7	53.5	-25.5	46.7	32.3	74.0	41.7	V

802.11ac-HT20

Ch149

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17902.7	54.5	-25.5	46.7	33.3	74.0	40.7	H
17965.3	53.8	-25.5	46.7	32.6	74.0	41.4	V
17896.6	53.7	-25.5	46.7	32.5	74.0	41.5	V
17959.3	53.7	-25.5	46.7	32.5	74.0	41.5	H
17924.7	53.4	-25.5	46.7	32.2	74.0	41.8	V
17969.8	53.3	-25.5	46.7	32.1	74.0	41.9	H

Ch157

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17913.7	53.5	-25.5	46.7	32.3	74.0	41.7	V
17864.2	53.4	-25.5	46.7	32.2	74.0	41.8	H
17884.5	53.4	-25.5	46.7	32.2	74.0	41.8	H
17961	53.4	-25.5	46.7	32.2	74.0	41.8	V
17996.7	53.3	-25.5	46.7	32.1	74.0	41.9	H
17400.5	53.2	-26.9	45.2	34.8	74.0	39.2	H

Ch165

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17975.2	53.7	-25.5	46.7	32.5	74.0	41.5	H
17991.2	53.7	-25.5	46.7	32.5	74.0	41.5	V
17960.4	53.5	-25.5	46.7	32.3	74.0	41.7	H
17871.8	53.4	-25.5	46.7	32.2	74.0	41.8	V
17947.2	53.4	-25.5	46.7	32.2	74.0	41.8	H
17914.8	53.3	-25.5	46.7	32.1	74.0	41.9	V

802.11ac-HT40

Ch151

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17965.3	53.6	-25.5	46.7	32.4	74.0	41.6	V
17980.2	53.5	-25.5	46.7	32.3	74.0	41.7	V
17962.6	53.4	-25.5	46.7	32.2	74.0	41.8	H
17979.7	53.4	-25.5	46.7	32.2	74.0	41.8	V
17881.2	53.3	-25.5	46.7	32.1	74.0	41.9	V
17799.2	53.1	-25.5	46.7	31.9	74.0	42.1	V

Ch159

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17998.9	54.7	-25.5	46.7	33.5	74.0	40.5	H
17936.2	54	-25.5	46.7	32.8	74.0	41.2	H
17973.6	53.5	-25.5	46.7	32.3	74.0	41.7	H
17969.8	53.4	-25.5	46.7	32.2	74.0	41.8	H
17994	53.4	-25.5	46.7	32.2	74.0	41.8	H
17510.5	53.3	-26.9	45.2	34.9	74.0	39.1	V

802.11ac-HT80

Ch155

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17877.9	53.5	-25.5	46.7	32.3	74.0	41.7	H
17879.5	53.5	-25.5	46.7	32.3	74.0	41.7	V
17884.5	53.5	-25.5	46.7	32.3	74.0	41.7	V
17889.5	53.5	-25.5	46.7	32.3	74.0	41.7	H
17594.1	53.4	-25.7	46.0	33.2	74.0	40.8	V
17974.2	53.4	-25.5	46.7	32.2	74.0	41.8	H

B.6. Band Edges Compliance

B.6.1 Band Edges - Radiated

Measurement Limit:

Standard	Limit (dBm/MHz)	
	FCC 47 CFR Part 15.407	at the band edge
at 5 MHz above or below the band edge		15.6
at 25 MHz above or below the band edge		10
at 75 MHz or more above or below the band edge		-27
Note: increasing linearly from point to point.		

Measurement Result:

Mode	Channel	Test Results	Conclusion
802.11a	5745 MHz	Fig.10	P
	5825 MHz	Fig.11	P
802.11n HT20	5745 MHz	Fig.12	P
	5825 MHz	Fig.13	P
802.11n HT40	5755 MHz	Fig.14	P
	5795 MHz	Fig.15	P
802.11ac HT20	5745 MHz	Fig.16	P
	5825 MHz	Fig.17	P
802.11ac HT40	5755 MHz	Fig.18	P
	5795 MHz	Fig.19	P
802.11ac HT80	5775 MHz	Fig.20 Fig.21	P

Conclusion: PASS

Test graphs as below:




Fig. 10 Band Edges (802.11a Ch149, 5745MHz)




Fig. 11 Band Edges (802.11a Ch165, 5825MHz)




Fig. 12 Band Edges (802.11n-HT20 Ch149, 5745MHz)




Fig. 13 Band Edges (802.11n-HT20 Ch165, 5825MHz)

Full Spectrum




Fig. 14 Band Edges (802.11n-HT40 Ch151, 5755MHz)

Full Spectrum




Fig. 15 Band Edges (802.11n-HT40 Ch159, 5795MHz)




Fig. 16 Band Edges (802.11ac-HT20 Ch149, 5745MHz)




Fig. 17 Band Edges (802.11ac-HT20 Ch165, 5825MHz)




Fig. 18 Band Edges (802.11ac-HT40 Ch151, 5755MHz)




Fig. 19 Band Edges (802.11ac-HT40 Ch159, 5795MHz)




Fig. 20 Band Edges (802.11ac-HT80 Ch155, 5775MHz)




Fig. 21 Band Edges (802.11ac-HT80 Ch155, 5775MHz)

B.7. AC Powerline Conducted Emission

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement uncertainty:

Expanded measurement uncertainty for this test item is $U = 3.08\text{dB}$, $k=2$.

Measurement Result and limit:

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger AE5		
		802.11a	Idle	
0.15 to 0.5	66 to 56	Fig.22	Fig.23	P
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger AE5		
		802.11a	Idle	
0.15 to 0.5	56 to 46	Fig.22	Fig.23	P
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

The measurement is made according to ANSI C63.10 .

Conclusion: PASS

Test graphs as below:

Traffic:




Fig. 22 AC Power line Conducted Emission-802.11a

Note1: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.199500	35.1	1000.0	9.000	On	L1	19.6	28.5	63.6	
0.568500	42.8	1000.0	9.000	On	N	19.5	13.2	56.0	
1.018500	34.0	1000.0	9.000	On	N	19.6	22.0	56.0	
1.770000	29.6	1000.0	9.000	On	L1	19.5	26.4	56.0	
2.148000	29.2	1000.0	9.000	On	L1	19.6	26.8	56.0	
4.191000	27.5	1000.0	9.000	On	N	19.7	28.5	56.0	

Final Result 2

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.307500	25.9	1000.0	9.000	On	N	19.6	24.1	50.0	
0.577500	37.1	1000.0	9.000	On	N	19.5	8.9	46.0	
1.027500	28.4	1000.0	9.000	On	N	19.6	17.6	46.0	
1.945500	26.7	1000.0	9.000	On	N	19.5	19.3	46.0	
2.292000	26.5	1000.0	9.000	On	N	19.6	19.5	46.0	
4.191000	21.7	1000.0	9.000	On	N	19.7	24.3	46.0	

Note2: The measurement results showed here are worst cases of the combinations of different cables and chargers

Idle:




Fig. 23 AC Power line Conducted Emission-Idle

Note1: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1





Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.370500	30.7	1000.0	9.000	On	N	19.6	27.8	58.5	
0.595500	39.4	1000.0	9.000	On	N	19.5	16.6	56.0	
0.793500	31.8	1000.0	9.000	On	N	19.5	24.2	56.0	
1.702500	24.4	1000.0	9.000	On	L1	19.6	31.6	56.0	
2.422500	29.3	1000.0	9.000	On	N	19.6	26.7	56.0	
4.519500	26.0	1000.0	9.000	On	N	19.7	30.0	56.0	

Final Result 2

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.375000	24.0	1000.0	9.000	On	N	19.6	24.4	48.4	
0.586500	35.0	1000.0	9.000	On	N	19.5	11.0	46.0	
0.793500	26.4	1000.0	9.000	On	N	19.5	19.6	46.0	
1.828500	23.9	1000.0	9.000	On	N	19.5	22.1	46.0	
2.418000	23.5	1000.0	9.000	On	N	19.6	22.5	46.0	
4.519500	20.1	1000.0	9.000	On	N	19.7	25.9	46.0	

Note2: The measurement results showed here are worst cases of the combinations of different cables and chargers

ANNEX C: Accreditation Certificate

<p>United States Department of Commerce National Institute of Standards and Technology</p>  	
<hr/> Certificate of Accreditation to ISO/IEC 17025:2017 <hr/>	
NVLAP LAB CODE: 600118-0	
Telecommunication Technology Labs, CAICT Beijing China	
<i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i>	
Electromagnetic Compatibility & Telecommunications	
<i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i>	
2020-09-29 through 2021-09-30 <i>Effective Dates</i>	  <i>For the National Voluntary Laboratory Accreditation Program</i>

*** END OF REPORT BODY ***