



n77H,90MHz(-26dBc)


Frequency (MHz)	Emission Bandwidth (-26dBc) (MHz)	
	DFT-s-pi/2 BPSK	DFT-s-QPSK
3840	91.710	92.250

n77H,90MHz Bandwidth,DFT-s-pi/2 BPSK (-26dBc BW)

n77H,90MHz Bandwidth,DFT-s-QPSK (-26dBc BW)



n77H,100MHz(-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc) (MHz)	
	DFT-s-pi/2 BPSK	DFT-s-QPSK
3840	101.600	101.900

n77H,100MHz Bandwidth,DFT-s-pi/2 BPSK (-26dBc BW)



n77H,100MHz Bandwidth,DFT-s-QPSK (-26dBc BW)




LTE Band 66+NR n7 n7,5MHz(-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc) (MHz)	
	DFT-s-pi/2 BPSK	DFT-s-QPSK
2535	5.125	4.945

n7,5MHz Bandwidth,DFT-s-pi/2 BPSK (-26dBc BW)




n7,5MHz Bandwidth,DFT-s-QPSK (-26dBc BW)




**LTE Band 66+NR n7
n7,10MHz(-26dBc)**

Frequency (MHz)	Emission Bandwidth (-26dBc) (MHz)	
	DFT-s-pi/2 BPSK	DFT-s-QPSK
2535	9.710	9.680

n7,10MHz Bandwidth,DFT-s-pi/2 BPSK (-26dBc BW)




n7,10MHz Bandwidth,DFT-s-QPSK (-26dBc BW)




**LTE Band 66+NR n7
n7,15MHz(-26dBc)**

Frequency (MHz)	Emission Bandwidth (-26dBc) (MHz)	
	DFT-s-pi/2 BPSK	DFT-s-QPSK
2535	14.565	14.386

n7,15MHz Bandwidth,DFT-s-pi/2 BPSK (-26dBc BW)




n7,15MHz Bandwidth,DFT-s-QPSK (-26dBc BW)




**LTE Band 66+NR n7
n7,20MHz(-26dBc)**

Frequency (MHz)	Emission Bandwidth (-26dBc) (MHz)	
	DFT-s-pi/2 BPSK	DFT-s-QPSK
2535	19.301	19.540

n7,20MHz Bandwidth,DFT-s-pi/2 BPSK (-26dBc BW)




n7,20MHz Bandwidth,DFT-s-QPSK (-26dBc BW)




**LTE Band 66+NR n25
n25,5MHz(-26dBc)**

Frequency (MHz)	Emission Bandwidth (-26dBc) (MHz)	
	DFT-s-pi/2 BPSK	DFT-s-QPSK
1882.5	5.365	5.035

n25,5MHz Bandwidth,DFT-s-pi/2 BPSK (-26dBc BW)




n25,5MHz Bandwidth,DFT-s-QPSK (-26dBc BW)




LTE Band 66+NR n25
n25,10MHz(-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc) (MHz)	
	DFT-s-pi/2 BPSK	DFT-s-QPSK
1882.5	9.800	9.830

n25,10MHz Bandwidth,DFT-s-pi/2 BPSK (-26dBc BW)




n25,10MHz Bandwidth,DFT-s-QPSK (-26dBc BW)




LTE Band 66+NR n25
n25,15MHz(-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc) (MHz)	
	DFT-s-pi/2 BPSK	DFT-s-QPSK
1882.5	14.925	14.565

n25,15MHz Bandwidth,DFT-s-pi/2 BPSK (-26dBc BW)




n25,15MHz Bandwidth,DFT-s-QPSK (-26dBc BW)




**LTE Band 66+NR n25
n25,20MHz(-26dBc)**

Frequency (MHz)	Emission Bandwidth (-26dBc) (MHz)	
	DFT-s-pi/2 BPSK	DFT-s-QPSK
1882.5	19.301	20.020

n25,20MHz Bandwidth,DFT-s-pi/2 BPSK (-26dBc BW)



n25,20MHz Bandwidth,DFT-s-QPSK (-26dBc BW)



A.6 Band Edge Compliance

A.6.1 Measurement limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Part 27.53(m) specifies for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(g) states for operations in the 600 MHz band and the 698–746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

Part 27.53(n) states for mobile operations in the 3450-3550 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz. Compliance with this paragraph (n)(2) is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed, but limited to a maximum of 200 kHz. In the bands between 1 and 5 MHz removed from the licensee's frequency block, the minimum resolution bandwidth for the measurement shall be 500 kHz. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

Part 27.53(l) states for mobile operations in the 3700-3980 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz. Compliance with this paragraph (l)(2) is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, the minimum resolution bandwidth for the measurement shall be either one percent of the emission bandwidth of the fundamental emission of the transmitter or 350 kHz. In the bands between 1 and 5 MHz removed from the licensee's frequency block, the minimum resolution bandwidth for the measurement shall




be 500 kHz. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


A.6.2 Measurement result

NR n41


OBW: 1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




Channal Power




OBW: 1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset



LOW BAND EDGE BLOCK-100M-100%RB




Channal Power



10:16:38 26.02.2022

LOW BAND EDGE BLOCK-100M-100%RB




10:17:18 26.02.2022

HIGH BAND EDGE BLOCK-100M-100%RB




HIGH BAND EDGE BLOCK-100M-100%RB




NR n5

OBW: 1RB-LOW_offset




10:31:29 26.02.2022

LOW BAND EDGE BLOCK-1RB-LOW_offset




10:32:16 26.02.2022

OBW: 1RB-HIGH_offset




10:32:57 26.02.2022

HIGH BAND EDGE BLOCK-1RB-HIGH_offset



10:33:44 26.02.2022

LOW BAND EDGE BLOCK-20M-100%RB



HIGH BAND EDGE BLOCK-20M-100%RB

